



PROFESSIONAL MEDICAL PRODUCTS



iHEALTH WIRELESS HEALTH-CARE PRODUCTS DIAGNOSTIC TESTS LABORATORY

**OPERATOR'S PROTECTION** 

HOLLOWARE - SURGICAL INSTRUMENTS - SYRINGES

MEDICAL BAGS

SCALES & MEASURES

HEALTH CARE PATIENT AIDS

**FURNITURE** 

PHYSIOTHERAPY NEBULIZERS - SUCTION PUMPS

GYNAECOLOGY & PROCTOLOGY

CAUTERY & ELECTROSURGERY

LOUPES, VISION & ENDOSCOPY

MEDICAL LIGHTS

DIAGNOSTICS

AUDIOMETRY & RESPIRATORY

ECG, MONITORS & ULTRASOUND

FIRST AID PARAMEDICAL - EMERGENCY

**STERILIZATION** 

**VETERINARY** 

HUMAN ANATOMY MODELS



**ELECTROSURGERY** page 181-193

page 229-238

**STETHOSCOPES** 

#### Dear Dealer,

Welcome to the new GIMA INTERNATIONAL CATALOGUE 2018-19. your one-stop shopping source for over 8,000 sales opportunities to offer your customers.

Gima catalogue is designed to make it easier for you to find. choose and buy your medical consumable and equipment. Our customers throughout 140 countries know that they can count on GIMA for nine reasons:

Quick delivery

all products always in stock ready for immediate delivery

Quality products at competitive prices every product carefully selected and checked by our experts to offer the best value for money

On going research

for the most innovative and advanced devices

Careful attention

order progress monitored at every stage

Flexible response

from small quantities to large volume orders

Complete service

full commitment to support before, during and after sales Four language service

we speak English, on parle Français, parliamo Italiano, hablamos Español

Most products provided with English or multilingual user manual Easy ordering

a simple e-mail, fax or call with your requirements is all we need Personalizations

Made-to-order products and packaging with your marks

The best way to benefit from GIMA advantages is to try us. Contact us today to establish a long term relationship.

Your sincerely

Dr.-Giulio Manzoni (General Manager)





GIMA S.p.A. - Via Marconi, 1 20060 Gessate (MI) - Italy

Fax: +39 02 95380056 E-mail: export@gimaitaly.com www.gimaitaly.com

## 1926 - 2018: 92 YEARS OF EXPERIENCE

CONTACTS AREA	TEL.
Letizia European Communitý - South, America +39 Sabrina European Community - North and East +39 Cristiano Eastern Europe, Middle-East +39 Mariagrazia Africa +39 Arianna Arabian Gulf, Oceania +39	

## **OUR BRANDS**





SOEHNLE

DURICO







Abbott







RIMSA



rann-Mortonº



meso-relle

**B** BRAUN



SPENCER

Welch Allyn'



CLINICON®

















Ambu\*


# Catalogue update with over 700 new products, 36 new pages

## GLUCOSE MONITORS, SMART DIABETES MANAGEMENT

#### ADVANCED FEATURES FOR DIABETES MANAGEMENT:




























#### GIMA GLUCOSE MONITORS

Accurate and reliable glucose monitors for self testing and professional use. Extensive clinical studies demonstrate the accuracy of Gima glucose monitoring system, powered by Acon, with fresh capillary, venous, neonatal blood samples. Comply with ISO15197:2013/EN ISO15197:2015.

#### Available as meter only or complete kit.

Kit includes 10 strips, code chip, control solution,

10 sterile lancets, lancet device, clear cap (for testing on forearm or palm), carrying case, user manual.

#### Bluetooth version (24114 only):

Result calibration:

Fully integrated Bluetooth allows for data transmission to data management platforms.

TECHNICAL SPECIFICATION
-------------------------

Biosensor/Electrochemical

Technology: Glucose dehydrogenase (GDH-FAD) Calibration method: No coding Plasma-equivalent

Test time: 5 seconds Sample size:

Sample type: Fresh whole blood (capillary, venous, neonatal)

Test sites: Fingertip, forearm, palm Hematocrit range:

1.000 results with date and time Memory storage: 7, 14, 30, 60, 90-day averages Test averaging: Data transfer

Control solution 3 levels Automatic shutoff:

2 minutes after last action 2x CR 2032 3.0V coin cell batteries Battery: Battery life: 3.000 measurements Automatic detection of insufficient sample Other functions:

2nd sample application allowed Sample perturbation detection



Multilanguage box and manual GB, FR, IT, ES, PT\*, DE\*, GR\*, SE "Manual not included in the box, only for download from www.gimaitaly.com



			24114				
GIMA code	GIMA	GLUCO	SE MONIT	OR METI	ER OR KIT		uages I manual
24108	GIMA	Glucos	e monito	r - mete	er only	GB, IT, S	E, FI
24110	GIMA	Glucos	e monito	r kit	-	GB, FR, I	
			e monito				R, Arabic
24114	GIMA	Glucos	e monito	r kit - B	luetooth	GB, FR, I	T, ES
GIMA code			CCESSORII FOR GIMA				
24118	Gluco	se Strip	s - box of	25 stri	os		
24119	Gluco	se Strip	s - box of	50 stri	os		
24120	Gluco	se Strip	s - box of	100 str	ips		
		ol Solu			•		
23919	Auto	lancet o	device				

23917 Lancets 28G for 23919 - sterile - box of 25 pcs

23916 Lancets 28G for 23919 - sterile - box of 100 pcs

NEWS 1

#### **NEW PRODUCTS 2020**

## MULTICAREIN MULTIPARAMETER DIAGNOSTIC DEVICE

Amperometr

GLC >>

SPARE STRIPS FOR MULTICARE "IN", MULTICAREIN

9 LANGUAGE BOX

• 24150 MULTICAREIN KIT - Italian manual

• 24151 MULTICAREIN KIT - English manual

• 24152 MULTICAREIN KIT - USB key multilanguage manual

• 24153 MULTICAREIN KIT BLUETOOTH - USB key

#### multilanguage manual\*

'Include 9 languages: GB, IT, FR, ES, GR, PT, PL, HU, RU . Selectable internal software: GB, FR, IT, ES.

AMPEROMETRIC SUCTION STRIP - glucose

Electro-chemical technology for a practical us

Tube of 50 of 25

23978 Glucose control solution

23979 Cholesterol control solution

23980 Triglycerides control solution

23917 Lancets 28G - sterile - bag of 25 pcs

23916 Lancets 28G - sterile - box of 100

- Requires very little blood samples (0.5 μl).

Short time for the results (5 sec.)

24158 24159

24160 24161

Multicarein is a multiparameter diagnostic device for the periodical self-monitor of risk factors: cholesterol, triglycerides

Portable device for easy test procedure and quick results. Accurate with Amperometric Technology for glucose and Reflectometric Technology for cholesterol and tryglicerides. Supplied in cardboard box with a nylon bag, 10 glucose strips, lancet device, 10 lancets, rapid guide and user manual. Multilanguage box: GB, FR, IT, ES, GR, PT, PL, HU, Arab.

• 23892 SOFTWARE FOR MULTICAREIN - GB, FR, IT, ES - optional Operating system: Windows XP, Windows 7, 8, 10, Vista, 16 Mb Ram, 10 Mb remaining space on hard disk.

The first and only multi-parameter device with double technology

**REFLECTOMETRIC SUCTION STRIP - cholesterol and tryglicerides** 

24156 24157 Glucose strips biosensor + 1 chip

LANCETS FOR MULTICARE, MULTICARE "IN", MULTICAREIN

Cholesterol strips + 1 chip

Triglycerides strips + 1 chip

CONTROL SOLUTION FOR MULTICARE "IN", MULTICAREIN







MULTICAREIN













TECHNICAL SPECIFICATIONS

Glucose electro-chemical: 10-600 mg/dl Cholesterol Triglycerides Memory: Display: Batteries:

Measuring range Measuring time Blood sample 130-400 mg/dl 30"-60" 50-500 mg dl 30"-60" 10 µl 500 test results with date and time

2 lithium batteries Cr 2032 3 Volts (32212) suitable for 1 year or 1,000 measurements

97x49x20.5 mm - 65 q

## SOUARE AND ROUND SAFETY LANCETS

Easy to use, comfortable, safety lancets to meet various capillary blood requirements.

Strips are sold in a 9 languages box: GB, IT, FR, ES, PT, PL, GR, HU, Arab.

- single-use: the build-in-self-destructing design can prevent reuse of the device

- no accidental injury risk: needle is hidden before and after use to prevent accidental injuries

- sterilization quaranteed: the lancet is Gamma sterilized and the needle tip is protected with a sterility tab until its use

allowing a long shelf life - no blood contamination 24463 24465 24451 24453 24454 24455





ched the lancet tin conversely insert the cap into the ancet for disposa to avoid blood





1 Remove the 2 Push gently against the testing site. 3 Dispose of safety lancets in sharps

Easy to use pre-loaded and pressure activated device High quality tri-bevel needle high-speed penetration with single spring

	GIMA ROUND SAFETY LANCETS - NEEDLES										
GIMA code		Depth of penetration	Gauge	Blood Flow	Finger Stick	Glucose	Hematocrit	Bleeding	Minimum order		
24451	Yellow	2.2 mm	G21	40-60 µl	•	•	٠	High	box of 100		
24453	Green	2.2 mm	G23	40-60 µl	•	•	•	High	box of 100		
24454	Light blue	1.8 mm	G26	5-10 µl	٠	٠	٠	Medium	box of 100		
24455	Purple	1.8 mm	G28	5-10 µl	•	•		Low	box of 100		
	GIM	A SQUARE	SAFE	TY LAN	CE.	TS	٠ ١	IEEDLES			
24463	Orange	1.8 mm	G23	20-40 ul	•	٠	•	Medium	box of 100		

24465 Purple 1.8 mm G28 5-10 µl • • Low box of 100

## GIMA URINE SCREEN VISUAL STRIPS - MADE IN GERMANY **GIMA**

• 24073 10 PARAMETER STRIP - tube of 100 strips

• 24074 11 PARAMETER STRIP - tube of 100 strips

These strips can be used by professionals for visual tests and can also be used with Gima urine analyzer (24046).

- global check/screening for general health condition

- check for healthy nutrition, urinary tract infection, tumors, kidney damage, gout, fever, cirrhosis, viral hepatitis, liver disease, congestive heart failure, jaundice, diabetes and acute renal failure.

For professional use only.

Multilanguage instructions: GB, FR, IT, ES, PT, DE, NL, GR, NO. SE, FI, DK, RU, CZ, PL, TR and box: GB, FR, IT, ES, PT, DE, PL, GR.

GIMA URINE S	CREEN	
Parameters	24073	24074
Glucose	•	•
Ascorbic Acid		•
Ketones	•	•
Protein	•	•
pH-Value	•	•
Blood	•	•
Nitrite	•	•
Leucocytes	•	•
Spec. Gravity	•	•
Bilirubin	•	•
Urobilinogen	•	•



 $\epsilon$ 

## ANALYTICON COMBISCREEN® PLUS AND CLASSIC URINE TEST STRIPS

Urine strips for visual test or for use with Urilyzer® 100, 100 Pro. 500 Pro and Combiscan 100 (24057\*, 24062, 24063, 24064 only) Features: \*Not suitable for 500 Pro

- excellent ascorbic acid protection for glucose and blood pad offers relevant reduction of false negatives due to interference with ascorbic acid (only CombiScreen® Plus)
- high quality water resistant label made with real colour printing guarantees an exact visual evaluation.
- distinct colour changes in the clinically relevant range even at low concentration level
- easy to use: results can be read directly on the strip after about 60 seconds (up to 120 for Leucocytes) and compared with the label on the bottle

Supplied in alluminium tube in single cardboard box. For professional use.

Made in Germany.

Glucose

Protein

Blood

Nitrite

Leucocytes

Bilirubin

Spec. Gravity

Urobilinoger

pH-Value

Ascorbic Acid Ketones

·												
	ANALYTICON URINE STRIPS											
GIMA	COMBISCREEN® PLUS URINE STRIPS Minimum with ascorbic acid protection order											
24059 24061 24063	4057 CombiScreen® 55YS Plus - 5 parameters tube o 4059 CombiScreen® 9-Leuko Plus - 9-1 parameters tube o 4061 CombiScreen® 10SL Plus - 10 parameters tube o 4063 CombiScreen® 11SYS Plus - 11 parameters tube o								pe of 100 pe of 100 pe of 100 pe of 100 pe of 150			
		w	ithout as	scorbio	acid p	rotect	ion					
			creen® 1 creen® 1						oe of 150 oe of 150			
	COMBISCREEN® PLUS COMBISCREEN® CLASSIC											
GIMA code		24057	24059	24061	24063	24064	24068		24062			
Paramete	rs	5SYS	9±Leuko	1051	115YS	115YS	1051	10SI 11SYS				



## SUTURES - BRAND COMPATIBILITY 📕 SUTURE TRAINING PAD

GIMA SUTURES	ETHICON SUTURES
-	GUT SUTURE PLAIN & CHROMIC
TRUGLYDE	-
TRUGLYDE FAST	-
TRUSYNTH	VICRYL
TRUSYNTH FAST	VICRYL RAPID
-	VICRYL PLUS
PD SYNTH	PDS OR PDS II
MONOGLYDE	MONOCRYL
TRULON	ETHILON / NUROLON
TRUSILK	MERSILK / PERMA-HAND SILK
TRULENE	PROLENE
-	ETHIBOND
-	SURGICAL STEEL
	SUTURES - TRUGLYDE TRUGLYDE FAST TRUSYNTH TRUSYNTH FAST - PD SYNTH MONOGLYDE TRULON TRUSILK

• 23020 SUTURE TRAINING PAD with wounds with mesh Silicone suture training pad with 14 wounds. 3 layers: skin, subcutis, muscle (extra layer mesh under the skin). Soft true to life skin textur Size. 17.2x12x1.2 cm. Adhesive skin closure strips, sterile, breathable and comfortable to wear.

3M STERI-STRIP™

See page 345 for: - 3M reinforced Steri-strip

- 3M elastic Steri-strip

- Suture strips



## SURGICAL NON ABSORBABLE SUTURES - STERILE

TRULON - polyamide nylon non absorbable monofilament suture TRUSILK - braided black silk non absorbable multifilament suture Equivalent Ethicon brand: ETHILON / NUR

- **Technical details** - monofilament polyamide
- non-adhering and biologi
- sterilized by ethylene oxid - shelf life of 5 years
- Applications - for cuticular and
- subcuticular closure
- orthopedic surgery
- ophthalmic
- general closure
- micro surgery

Multilanguage manual and GB, FR, IT, ES, PT, DE, GR

cally ir	nert		E 2265
	TRULON	-	
l box:		Sutures	

GD, IN,	11, 23	, , , , ,	JE, GI					
			TF	RULON	- box of 12			
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle length		
22800	2/0	3.0	Blue	3/8	Reverse Cutting	26 mm	45 cm	
22801	2/0	3.0	Black	3/8	Reverse Cutting	45 mm	70 cm	
22803	3/0	2.0	Blue	3/8	Conventional Cutting	20 mm	45 cm	
22804	3/0	2.0	Blue	3/8	Reverse Cutting	24 mm	45 cm	
22805	3/0	2.0	Blue	3/8	Conventional Cutting	25 mm	45 cm	
22807	3/0	2.0	Black	3/8	Reverse Cutting	19 mm	45 cm	
22808	3/0	2.0	Black	3/8	Reverse Cutting	24 mm	45 cm	
22810	4/0	1.5	Blue	3/8	Reverse Cutting	19 mm	45 cm	
22811	4/0	1.5	Black	3/8	Conventional Cutting	10 mm	38 cm	
22812	4/0	1.5	Black	3/8	Reverse Cutting	19 mm	45 cm	
22814	5/0	1.0	Blue	3/8	Reverse Cutting	16 mm	70 cm	
22815	5/0	1.0	Blue	3/8	Reverse Cutting	19 mm	70 cm	
22816	5/0	1.0	Black	3/8	Reverse Cutting	19 mm	45 cm	
22817	5/0	1.0	Black	3/8	Reverse Cutting	19 mm	75 cm	į
22820	6/0	0.7	Blue	3/8	Reverse Cutting	12 mm	45 cm	į
22821	6/0	0.7	Blue	3/8	Reverse Cutting	16 mm	45 cm	į

#### 22822 6/0 0.7 Black 3/8 Reverse Cutting 16 mm 45 cm TRULENE - monofilament non absorbable suture - polypropylene **Equivalent Ethicon brand: PROLENE** € 2265 **Technical details**

- monofilament polypropylene

- non-adhering and biologically inert - sterilized by ethylene oxide
- shelf life of 5 years
- **Applications**
- hernia repair
- permanent fixtures
- general surgery - micro surgery
- orthopedic surgery
- cardiovascular surgery
- can also be used in ophthalmic and neurological procedures Multilanguage manual and box: GB, FR, IT, ES, PT, DE, GR.

plastic surgery

Equivalent Ethicon brand: MERSILK / PERMA-HAND SILK **Technical details** 

- made from 100% protein fiber spun
- coating of wax/silicone
- sterilized by ethylene oxide
- shelf life of 5 years
- **Applications**
- general surgery
- ophthalmic surgery
- cardiovascular surgery - gastrointestinal surgery
- orthopedic surgery

Multilanguage manual and box: GB, FR, IT, ES, PT, DE, GR.

			Т	RUSILK	- box of 12		
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle length	Suture
22830	0	3.5	Black	1/2	Round Body	30 mm	76 cm
22831	2/0	2.0	Black	1/2	Taper Cutting	19 mm	75 cm
22832	2/0	3.0	Black	3/8	Reverse Cutting	26 mm	45 cm
22833	2/0	3.0	Black	1/2	Reverse Cutting	22 mm	45 cm
22834	2/0	3.0	Black	1/2	Taper Cutting	25 mm	75 cm
22835	2/0	3.0	Black	1/2	Round Body	30 mm	76 cm
22836	3/0	2.0	Black	1/2	Conventional Cutting	22 mm	45 cm
22837	3/0	2.0	Black	1/2	Round Body	22 mm	45 cm
22838	3/0	2.0	Black	3/8	Reverse Cutting	19 mm	70 cm
22839	3/0	2.0	Black	3/8	Reverse Cutting	24 mm	45 cm
22840	3/0	2.0	Black	1/2	Taper Cutting	19 mm	75 cm
22842	3/0	2.0	Black	1/2	Taper Cutting	25 mm	75 cm
22844	4/0	1.5	Black	1/2	Reverse Cutting	17 mm	45 cm
22845	4/0	1.5	Black	1/2	Taper Cutting	19 mm	75 cm
22846	4/0	1.5	Black	1/2	Taper Cutting	25 mm	75 cm
22847	4/0	1.5	Black	Straight	Round Body	19 mm	45 cm
22848	4/0	1.5	Black	3/8	Reverse Cutting	13 mm	45 cm
22849	4/0	1.5	Black	3/8	Reverse Cutting	19 mm	45 cm
22851	5/0	1.0	Black	3/8	Reverse Cutting	19 mm	70 cm
22852	6/0	0.7	Black	3/8	Reverse Cutting	16 mm	45 cm

			TF	RULENE	- box of 12		
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle length	Suture length
22870	1	4.0	Blue	1/2	Round Body	30 mm	70 cm
22871	0	3.5	Blue	1/2	Round Body	30 mm	70 cm
22872	2/0	3.0	Blue	3/8	Reverse Cutting	24 mm	70 cm
22874	3/0	2.0	Blue	3/8	Reverse Cutting	24 mm	70 cm
22875	3/0	2.0	Blue	Straight	Conventional Cutting	60 mm	70 cm
22877	4/0	1.5	Blue	3/8	Reverse Cutting	19 mm	45 cm
22879	4/0	1.5	Blue	3/8	Reverse Cutting	19 mm	75 cm
22881	5/0	1.0	Blue	3/8	Reverse Cutting	16 mm	70 cm
22882	5/0	1.0	Blue	3/8	Reverse Cutting	19 mm	70 cm
22884	6/0	0.7	Blue	3/8	Reverse Cutting	13 mm	45 cm
22885	6/0	0.7	Blue	3/8	Conventional Cutting	16 mm	45 cm

NEWS 3

CE

## SURGICAL ABSORBABLE SUTURES - STERILE

MONOGLYDE - monofilament absorbable suture poliglecaprone 25 Equivalent Ethicon brand: MONOCRYL ( **E** 2265 Technical details

MONOGLYDE

monofilament

- poliglecaprone 25
   synthetic absorbable suture
- sterilized by ethylene oxide
- shelf life of 3 years
- wound support: 21-28 days - mass absorption: 90-120 days
- Applications used for subcuticular repair and general soft-tissue approximation
- bowel anastomoses
- closure of the peritoneum
- closure of uterus and vaginal cuff
- not recommended for use in cardiovascular or neurological tissues. microsurgery or ophthalmic surgery
- since this is an absorbable suture, it should not be used for extended approximation of tissue (fascia) e manual and box: GB. FR. IT FS PT DF GR

Walthanguage manual and box. Gb, FK, FI, E5, FT, DE, GK.												
	MONOGLYDE - box of 12											
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle length	Suture length					
22901	0	3.5	Undyed		Round Body	30 mm	70 cm					
22902	2/0	3.0	Undyed	1/2	Round Body	30 mm	70 cm					
22903	3/0	2.0	Undyed	3/8	Slim Blade Cutting	25 mm	70 cm					
22904	5/0	1.0	Undyed	3/8	Round Body	19 mm	45 cm					
TRUSYNTH FAST - braided & coated polyglactin 910 fast Equivalent Ethicon brand: VICRYL RAPID  C 2265												
recrifical details												
- synth	etic al	bsorba	able su	rgical	suture	F						
- Dialu	eu aiii	u coai	.eu		100							

- polyglactin 910 sterilized by ethylene oxide TRUSYNTH FAST
- shelf life of 5 years - absorption period: 42 days
- Applications
- general soft tissue approximation

Multilanguage manual and box: GB. FR. IT. ES. PT. DE. GR.

	TRUSYNTH FAST - box of 12								
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle Suture length length			
22910	2/0	3.0	Undyed	3/8	Reverse Cutting	24 mm 70 cm			
22911	3/0	2.0	Undyed	1/2	Round Body	17 mm 45 cm			
22912	3/0	2.0	Undyed	3/8	Reverse Cutting	19 mm 45 cm			
22913	3/0	2.0	Undyed	1/2	Round Body	17 mm 70 cm			
22914	3/0	2.0	Undyed	1/2	Round Body	22 mm 70 cm			
22915	3/0	2.0	Undyed	3/8	Reverse Cutting	14 mm 75 cm			
22916	3/0	2.0	Undyed	3/8	Reverse Cutting	24 mm 70 cm			
22917	4/0	1.5	Undyed	3/8	Reverse Cutting	19 mm 45 cm			
22918	4/0	1.5	Undyed	3/8	Reverse Cutting	19 mm 70 cm			
22919	5/0	1.0	Undyed	3/8	Reverse Cutting	16 mm 70 cm			
22920	6/0	0.7	Undyed	3/8	Reverse Cutting	11 mm 45 cm			

#### TRUGLYDE FAST - Braided and coated Polyglycolic Acid fast Undyed **Technical details** - braided and coated

TRUGLYDE FAST

- coated with calcium stearate and polycaprolactone
- sterilized by ethylene oxide
- shelf life of 5 years
- wound support: 7-10 days - mass absorption: 40-42 days

## Applications

- for episiotomy
- for circumcision - closure of skin

viuitiia	iuitilanguage manual and box: GB, FR, 11, ES, P1, DE, GR.							
			TRUGE	YDE F	AST - box of 12			
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle length	Suture length	
22980	1	4.0	Undyed	1/2	Round Body	40 mm	90 cm	
22981	2/0	3.0	Undyed	1/2	Round Body	35 mm	75 cm	
22983	3/0	2.0	Undyed	3/8	Reverse Cutting	24 mm	70 cm	
22984	3/0	2.0	Undyed	3/8	Reverse Cutting	20 mm	75 cm	
22986	4/0	1.5	Undyed	3/8	Reverse Cutting	16 mm	70 cm	
22988	4/0	1.5	Undyed	3/8	Reverse Cutting	20 mm	75 cm	
22989	5/0	1.0	Undyed	1/2	Round Body	17 mm	75 cm	

PDSYNTH - monofilament absorbable suture polydioxanone Equivalent Ethicon brand: PDS or PDS II
Technical details monofilament polydioxanone synthetic absorbable suture PDSYNTH - sterilized by ethylene oxide - shelf life of 5 years

- wound Support: 35-42 days - mass absorption: 180-210 days Applications for rectus sheath closure

- fascia closure and gastrointestinal trac pediatric cardiovascular surgery

geriatric surgeries orthopedic surgery

 general surgery Multilanguage manual and box: GB, FR, IT, ES, PT, DE, GR.

			PD:	SYNTH	I - box of 12		
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle length	
2940	1	4.0	Violet	1/2	Round Body	40 mm	90 cn
2941	0	3.5	Violet	1/2	Round Body	30 mm	70 cn
2942	0	3.5	Violet	1/2	Round Body	40 mm	70 cn
					1 1 1 000		

TRUSYNTH

#### TRUSYNTH - braided & coated polyglactin 910 Equivalent Ethicon brand: VICRYL

**Technical details** - braided and coated polyglactin 910

- coating of calcium stearate and polyglactin 910

- sterilized by ethylene oxide

- shelf life of 5 years
- wound support: 28-30 days - mass absorption: 56-70 days
- Applications ophthalmic procedures
- mucosal closures
- skin closure
- dental surgery
- orthopedic surgery
- general soft tissue approximation

Multilanguage manual and box: GB, FR, IT, ES, PT, DE, GR

withit	ingua	ge ille	iiiuai a	nu bu	v. GD, 111, 11, LJ, 1 1,	DL, GI		
	TRUSYNTH - box of 12							
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle length		
22950	1	4.0	Violet	1/2	Round Body	40 mm	90 cm	
22951	0	3.5	Violet	1/2	Round Body	40 mm	90 cm	
22952	2/0	3.0	Violet	1/2	Taper Cutting	19 mm	75 cm	
22953	2/0	3.0	Violet	1/2	Round Body	30 mm	90 cm	
22954	3/0	2.0	Violet	1/2	Taper Cutting	19 mm	75 cm	
22955	4/0	1.5	Violet	1/2	Taper Cutting	19 mm	75 cm	
RUGLYDE - braided & coated polyglycolic acid								

TRUGLYDE

**Technical details** - braided and coated polyglycolic acid - coating of calcium stearate

and polyglactin 310

- sterilized by ethylene oxide - shelf life of 5 years

- wound Support: 28-30 days - mass Absorption: 70-90 days

Applications for soft tissue approximation

during general, gynecological and orthopedic surgeries

Multilanguage manual and box: GB, FR, IT, ES, PT, DE, GR TRUGIVDE - hox of 12

	TRUGET DE - DOX OT 12							
GIMA code	Gauge	Metric	Colour	Circle	Needle profile	Needle Suture length length		
22960	1	4.0	Violet	1/2	Round Body	40 mm 90 cm		
22961	0	3.5	Violet	1/2	Round Body	40 mm 90 cm		
22962	2/0	3.0	Violet	3/8	Reverse Cutting	24 mm 70 cm		
22963	2/0	3.0	Violet	1/2	Round Body	30 mm 90 cm		
22964	3/0	2.0	Violet	3/8	Reverse Cutting	19 mm 45 cm		
22965	3/0	2.0	Violet	3/8	Reverse Cutting	19 mm 70 cm		
22966	3/0	2.0	Undyed	3/8	Reverse Cutting	19 mm 75 cm		
22967	3/0	2.0	Undyed	1/2	Round Body	22 mm 75 cm		
22968	4/0	1.5	Violet	3/8	Reverse Cutting	19 mm 45 cm		
22969	4/0	1.5	Violet	3/8	Reverse Cutting	19 mm 70 cm		
22970	4/0	1.5	Undyed	3/8	Reverse Cutting	16 mm 45 cm		
22971	4/0	1.5	Undyed	1/2	Round Body	17 mm 75 cm		
22972	5/0	1.0	Undyed	1/2	Round Body	17 mm 75 cm		
22973	5/0	1.0	Undyed	3/8	Reverse Cutting	13 mm 45 cm		

## ETHICON SUTURES - ABSORBABLE AND NON ABSORBABLE



## NON ABSORBABLE STERILE SURGICAL SUTURES

ETHICON Gauge Metric Colour Circle Needle length Needle Non absorbable surgical sutures are indicated for use in general soft tissue approximation and/or ligation included use in cardiovascular, ophthalmic and neurosurgical procedures

#### **ETHILON - monofilament suture**



22297	EH7145H	4/0	1.5	Black	3/8	19 mm	FS-2	45 cm	box of 36
22298	1162H	4/0	1.5	Black	3/8	16 mm	FS-3	45 cm	box of 36
22299	2808G	8/0	0.4	Black	3/8	6.5 mm	BV130-5	13 cm	box of 12
22300	660H	6/0	0.7	Black	3/8	16 mm	FS-3	45 cm	box of 36
22301	661H	5/0	1.0	Black	3/8	19 mm	FS-2	45 cm	box of 36
22302	662SLH	4/0	1.5	Black	3/8	19 mm	FS-2S	45 cm	box of 36
22303	663H	3/0	2.0	Black	3/8	24 mm	FS-1	45 cm	box of 36
22304	EH7506H	3/0	2.0	Black	3/8	19 mm	FS-2	45 cm	box of 36
22305	EW661	5/0	1.0	Blue	3/8	19 mm	FS-2	75 cm	box of 36
22306	668H	5/0	1.0	Black	3/8	13 mm	C-2	45 cm	box of 36
22307	698H	5/0	1.0	Black	3/8	13 mm	P-3	45 cm	box of 36
22308	669H	3/0	2.0	Black	3/8	24 mm	FS-1	75 cm	box of 36

#### PERMA-HAND - silk sutures - braided



22310	18501G	4/0	1.5	Black	1/2	17 mm	J-1	45 cm	box of 12
22311	632G	3/0	2.0	Black	1/2	22 mm	X-1	45 cm	box of 12
22312	737G	2/0	3.0	Black	1/2	22 mm	X-1	45 cm	box of 12
22313	18507G			Black					box of 12
22314	18508G	4/0	1.5	Black	3/8	13 mm	P-3 prime	45 cm	box of 12
22315	18509G	3/0	2.0	Black	1/2	22 mm	SH-1 Plus	45 cm	box of 12
22316	EH7149G	4/0	1.5	Black	3/8	19 mm	FS-2	45 cm	box of 12
22317	K872	3/0	2.0	Black	1/2	17 mm	RB-1	75 cm	box of 36
22318	683H	4/0	1.5	Black	3/8	19 mm	FS-2S	45 cm	box of 36
22319	684H	3/0	2.0	Black	3/8	24 mm	FS-1	45cm	box of 36

#### PROLENE - blue pigmented monifilament sutures



22320	EH7150H	4/0	1.5	Blue	3/8	19 mm	FS-2	75 cm	box of 36
22321	EH7151H	4/0	1.5	Blue	3/8	19 mm	FS-2	45 cm	box of 36
22322	W8873T	6/0	0.7	Blue	3/8	16 mm	PC-3 Prime	45 cm	box of 24

## ABSORBABLE STERILE SURGICAL SUTURES

Needle Suture Minimum Gauge Metric Colour Circle

#### MONOCRYL - complete absorption in 91-119 days

Monocryl is indicated for use in general soft tissue approximation and/or ligation, but not for cardio, neuro, micro and ophthalmic surgery



22350 Y493H 5/0 1.0 Undyed 3/8 13 mm P-3 prime 45 cm box of 36

### VICRYL PLUS BRAIDED - complete absorption in 56-70 days

Vicryl Plus is indicated for use in general tissue approximation and/or ligation except for ophthalmic, neuro, cardiovascular



22360 VCP392ZH 4/0 1.5 Violet 3/8 19 mm FS-2 45 cm box of 36 22361 VCP305H 3/0 2.0 Violet 1/2 17 mm RB-1 PLus 70 cm box of 36 2.0 Violet 3/8 24 mm FS-1 70 cm box of 36 22363 VCP453H 3.0 Violet 3/8 24 mm FS-1 70 cm box of 36 22364 VCP311H 3/0 2.0 Violet 3/8 22 mm SH-1 70 cm box of 36 22365 VCP317H 2/0 3.0 Violet 1/2 26 mm SH 70 cm box of 36 22366 VCP494H 4/0 1.5 Undyed 3/8 13 mm P-3 45 cm box of 36

#### VICRYL RAPID BRAIDED - complete absorption in 42 days Vicryl Rapid Braided indicated only for: use in superficial

soft tissue approximation of the skin and mucosa, where only short term (7-10 days) wound support is required.



**22370 V76H** 3/0 2.0 Undyed 1/2 17 mm J-1 **22371 V2920G** 4/0 1.5 Undyed 3/8 19 mm FS-2 45 cm box of 36 FS-2 45 cm box of 12 2.0 Undved 3/8 19 mm FS-2 45 cm box of 12 22372 V2930G 3/0 22373 V2150G 3/0 2.0 Undved 1/2 17 mm RB-1 PLus 70 cm box of 12 22374 V2190G 3/0 2.0 Undved 1/2 22 mm SH-1 PLus 70 cm box of 12 22375 VR2298 3/0 2.0 Undyed 3/8 19 mm FS-2 75 cm box of 36

# VICRYL



3/0 2.0 Violet 3/8 24 mm FS-1 70 cm box of 36



22390 Z340H 0 3.5 Violet 1/2 36 mm CT-1 70 cm box of 36 **22391 Z317H** 2/0 3.0 Violet 1/2 26 mm SH

NEWS 6

# GIMA

• 25891 DISPOSABLE STERILE SKIN STAPLER - box of 5 Easy to use device with 35 staples made of High Quality 317 L Stainless Steel for medical use. High sewing up and stapling speed help shorten the time of sewing and avoid cross infection of contagious diseases. Reduced tissue reaction, thinner scar after operation and faster wound healing. Painless and convenient staples removal after the incision has healed up. For skin closure in operating room, delivery, emergency, outpatient surgery, clinics and physician's office.

## DISPOSABLE SKIN STAPLER ■ 3M™ PRECISE™ SKIN STAPLERS

• 25896 3M PRECISE™ SKIN STAPLER 5 staples - sterile - box of 12 25897 3M PRECISE™ SKIN STAPLER 15 staples - sterile - box of 12 The disposable Precise skin staplers offer numerous

benefits over sutures - significantly quicker, simpler ( **E** 0086 to use and safer than sutures

- better cosmetic effect - six times faster than suturing
- no risk of accidental stick injury
- less painful than sutures easy to remove.

It comes pre-loaded with 5 or 15 staples (6.5x4.5 mm). Suitable for simple, recent, open, unbruised wounds.

Staples are particularly suitable for scalp wounds as they do not catch on surrounding hair and are more easily identifiable at the time of removal.



## SKIN STAPLE REMOVERS



- 25893 DISPOSABLE SKIN STAPLE REMOVER 11 cm sterile box of 50 Suitable for use with most brands of skin staples. It combines functionality with cost effectiveness.
- 26737 S/S SPENCER SCISSORS 13 cm
- 26722 S/S MICHEL STITCH REMOVER FORCEPS 12 cm



- 25892 DISPOSABLE REMOVER FORCEPS box of 20 pcs. Practical disposable forceps for removing regular and wider size staples. Sterile.
- 25895 SR-3 DISPOSABLE SKIN STAPLE REMOVER box of 10 pcs. 3M original forceps for removing staples. Sterile.

## SURGICAL NON ABSORBABLE MESH - BLUE COLOUR

**£** 2265

TRULENE (Polypropylene) MESH - Non-Absorbable Equivalent Ethicon brand: PROLENE MESH Features

- non-adhering to tissue and biologically inert - gives strong support for indefinite periods
- excellent tensile strength and pliability - easy to draw through tissues - inert material
- does not harbor micro-organisms
- Applications
- hernia repair, plastic, general and gastrointestinal surgery Technical details
- the product does not require any coating is sold untreated sterilized by ethylene oxide

TRULENE	TRULENE MESH - non absorbable								
GIMA code	Size	Minimum order							
23012	6 x 11 cm	box of 6							
23013	7.6 x 15 cm	box of 6							
23014	10 x 15 cm	box of 3							
23015	15 x 15 cm	box of 3							
23016	30 x 30 cm	box of 1							



- monofilament polypropylene non-absorbable surgical sutures

## 🛮 BONEWAX - STERILE 📕 CLINICEL OXIDIZED REGENERATED CELLULOSE

#### • 23000 TRUWAX STERILE SURGICAL BONEVAX 2.5 g - box of 12

**Equivalent Ethicon brand: BONE WAX** Truwax is a sterile mixture of beeswax. paraffin wax and iso propyl palmitate (bone wax). It can be safely used to control bleeding from surfaces of injured bones during bone repair surgery. Multilanguage manual and box: GB, FR, IT, ES, PT,

DF GR 23000

#### **TECHNICAL SPECIFICATIONS**

Bees wax I.P., White Hard Paraffin Composition: Wax, I.P., Iso Propvl Palmitate, U.S.P. Colour - Odour: opaque - waxy odour Sterilization: Shelf life: 5 years Packing: 2.5 g per unit pack

## CLINICEL OXIDIZED REGENERATED CELLULOSE

#### Equivalent Ethicon brand: SURGICEL Features

absorbable hemostat

- least thrombogenic

- made from oxidized regenerated cellulose (plant based product)
- malleable and flexible Applications

- Neurosurgery: operative intervention into the cerebrum, ventricular system, spinal surgery Cardiac Surgery: valve replacement surgery, sterna medullary bleeding, approaches to

the skull base, cerebrovascular surgery - Gynecological surgeries: uterine wall - ENT: posterior epistaxis perforation

General surgeries: latrogenic perforations TECHNICAL SPECIFICATIONS

Effective Hemostasis: in 3-5 minutes gamma radiation Sterilization: Shelf life: 3 years

# 23004 Multilanguage manual and box: GB, FR, IT, ES, PT,

	GIMA	CLINICEL STANDARD - box of 6				
	code		cm	inches		
	23003	Clinicel standard	5.1x7.6	2x3		
	23004	Clinicel standard	5.1x35.5	2x14		
•	23005	Clinicel standard	10x20	4x8		
	GIMA	CLINICEL FIBRIL	TYPE - bo	ox of 6		
	code		cm	inches		
	23007	Clinicel fibril type	2.5x5.1	1x2		
	23008	Clinical fibril type	5 1v10	2v4		

NEWS 7

## GIMA SURGICAL CLIPPER



• 27083 GIMA SURGICAL CLIPPER

Water-Proof surgical clipper widely used in operation room for surgery preparation or other procedures requiring for hair removal. Safe for patients to avoid any risk of cross infec-

Supplied with charger and multilanguage manual: GB, FR, IT, ES. Blade not included.

• 27084 CLIPPER BLADE ASSEMBLY - sterile -

#### box of 20 pcs

Sterile disposable blades for all types of body hair. Disposable use for each patient with ETO sterilization. Smooth to the skin.

TECHNICAL SPECIFICATIONS

Battery indicator with overcharge protection autonomy 60 min Li-Ion Battery type

Charging time 4-5 hours

# 3M™ SURGICAL CLIPPER WITH PIVOTING HEAD\*

• 27054 3M™ SURGICAL CLIPPER STARTER KIT (CLIPPER + CHARGER) - 9667L-E The 3M surgical clipper with its unique pivoting head is a safe, reliable and easy to use device nead" and charger providing a comfortable clipping experience for patients. \*When used with 3M clipper blades 9660 (27055) SURGICAL CLIPPER FEATURES WITH DIFFERENT SURGICAL CLIPPER BLADES Pivoting head Ergonomically designed handle that's easy to hold

Easy-to-attach blade Cuts through all types of head and body hair, wet or dry, in a single pass Ouickly and effectively removes hair in trauma and neuro cases

Away-from-the-skin cutting blade minimizes potential for nicks or cuts, which helps reduce the risk of SSIs (surgical site infections) Li-ion battery designed to hold a charger longer and battery indicator light

Approximately 160 minutes of run time on a four-hour recharge Submersible for easy cleaning (meets IPX7 rating of submersible in water no deeper than 1 m for up to 30 min)

• 27055 3M™ SURGICAL CLIPPER BLADES - 9660 - pivoting - box of 50 27056 3M™ SURGICAL CLIPPER BLADES - 9690 - non pivoting - box of 20

Single use clipper blade individually sealed and heavy body hair





# ■ VEINSPY™ HAND-HELD VEIN FINDER

#### • 23450 VEINSPY™ HAND-HELD VEIN FINDER

27054

**3M** 

**3M** 

VeinSpy™ is a portable vein finder for easy visualisation of veins in adult, pediatric, geriatric, obese and dark skin patients with difficult venous access.

It works on Transverse Illumination Technology: light beams from a circular LED array penetrate the skin and act as a light source to achieve deep illumination of subcutaneous tissues. The veins in the illuminated area absorb the light and become prominent as dark lines.

The VeinSpy™ device consist of two sets of coloured LEDs: one set emits orange light optimal for superficial veins, another set emits red light to find deeper veins.

#### Advantages of the VeinSpy™:

- reduces multiple needle prick and improves site selection for needle insertion
- no treatment delay due to difficult venous access
- reduces patient pain due to needle insertion - increases patient comfort, avoids hematoma
- 23451 PLASTIC SLEEVES FOR 23450 disposable box of 50

## TECHNICAL SPECIFICATIONS

Functional opening: Viewing diameter: Rechargeable battery Battery charger: Rattery backup: Dimensions - weight

Number of LED's:

22 Orange, 8 Red 17 mm 33 mm Lithium Ion, 3.7V, 1150mAh 110-240 V AC input, 5V DC output 750mA 11/2 hours continuous use 125x65x22.7 mm - 90 q

How to use VeinSpy 1- Wipe the area of the patient's skin with alcohol swab 2- Insert VeinSny™ into the disposable sleeve and switch ON. . 3- Move the VeinSpv™ across and forth to get a clear view of the specific vein



4- After visualization of vein move the device so that needle can be inserted easily



27083

27084

through the open end of VeinSpy™ insert needle into the vein

#### STANDARD ACCESSORIES

Rechargeable battery 50 disposable plastic sleeves Multilanguage user manual: GB FR, IT, PT, ES, RU, Arab

## I TRAVELJOHN™ RESEALABLE DISPOSABLE URINAL AND VOMITBAG



- 25879 TRAVELIOHN™ PAPER DISPOSABLE URINAL 800 cc - box of 4 • 25880 TRAVELJOHN™ DISPOSABLE URINAL 800 cc - box of 3
- practical super absorbent polymer pouch that instantly turns urine to gel - no closure needed (only 25880)
- reusable until it is full (only 25880) waste disposal safe, simply throw away unisex collar for easy handling



Travel John strip

Closure

25879

with alu

- 25887 TRAVELJOHN™ DISPOSABLE VOMIT BAG 800 cc box of 5
- gels instantly and water proof
- convenient sanitary and compact
- odourless and waste disposal safe

## MALE EXTERNAL LATEX CATHETERS AND CATHETER FIXATIONS



External male catheters made from natural medical latex. The graded cap design eliminates the possibility of twisting of the drainage system and blockage of the urine flow. No leaking or ballooning is possible.

GIMA code	MALE EXTERNAL LATEX CATHETERS	Size	Minimum order						
28713	Male external catheter Ø 20 mm	XS	box of 30						
28709	Male external catheter Ø 25 mm	S	box of 30						
28710	Male external catheter Ø 30 mm	L	box of 30						
28711	Male external catheter Ø 35 mm	XL	box of 30						
28712	Male external catheter Ø 40 mm	XXL	box of 30						
KIT: M	KIT: MALE EXTERNAL CATHETER + ADHESIVE STRIP IN A POUCH								
28724	Kit: catheter Ø 30 mm + hydrocolloid strip	L	box of 30						
28725	Kit: catheter Ø 35 mm + hydrocolloid strip	XL	box of 30						

28716	28715	
Hydrocolloid	Foam strip	28718
strip		Safe & Secure elastic foam strap with pile and hook fastener which offers a non adhesive alternative for fastening the male external catheter


	MALE EXTERNAL CATHETER FIXATIONS	
28715	Biadhesive foam strip 15x2x0.3 cm	box of 30
28716	Biadhesive hydrocolloid strip 12x1.8x0.1 cm	box of 30
28718	Safe & Secure reusable foam strap	bag of 3

## Z-STRAP 3 IN ONE - FOR FIXING URINE BAGS, TUBES OR CATHETERS

#### • 28727 Z-STRAP FIXING SYSTEM FOR URINE BAG, TUBE, CATHETER - box of 2

Comfortable and discreet all in one universal strap for fixing a urine bag, a urine bag tube or a catheter. Special designed Z-strap is made of top-quality medical garment preventing irritations; silicone beading on internal side keeps the strap in place preventing any inconvenience.

- one size fits all (70 cm long), can be cut to desired size wide band (5 cm width), distributes pressure and weight better, especially for diabetics
- easy application, for nurse and user, fast wear and removal
- skin friendly, no use of adhesive / no need to shave hair
- fixing straps for silicone tubes to prevent slipping - prevents injures caused by sudden movement
- fits all size of urine bags / leg bags - reusable can be machine washed, does not shrink - prevents pressure wounds, wide strap







Fixing strap

28727

## DOUBLE CURETTE - EXTRACTOR

HANGER HOLDER FOR URINE BAG • 28698 HANGER HOLDER WITH REUSABLE COVER FOR URINE



**(** €1370 22660 Ø curette 2.5 mm Ø extractor 4 mm 22660 CURMEDON DOUBLE CURETTE BESNIER TYPE AND

EXTRACTOR - sterile - box of 20 Medical device for skin care procedure in Dermatology. Sterilization: Ethylene Oxyde. Latex and PVC free. Each curette is individually packed in a pouch.

NEWS 9

## STIEFEL DERMAL CURETTES AND BIOPSY PUNCHES

rate skin biopsy. Stainless steel seamless

sharp edge. Ribbed handle for

more precise grip.

Size engra-

ved on

for easy

identifi

each punch

Extremely sharp stainless steel half edge for soft tissue. Ergonomic handle for a better grip. Size engraved on each curette for easy identification.





GIMA code	STIEFEL code	BIOPSY PUNCHES - STERILE	Minimum order
22650	STIEF-BP2	Biopsy punches Ø 2 mm	box of 10
22651	STIEF-BP3	Biopsy punches Ø 3 mm	box of 10
22652	STIEF-BP35	Biopsy punches Ø 3.5 mm	box of 10
22653	STIEF-BP4	Biopsy punches Ø 4 mm	box of 10
		Biopsy punches Ø 5 mm	box of 10
22655	STIEF-BP6	Biopsy punches Ø 6 mm	box of 10
22656	STIEF-BP8	Biopsy punches Ø 8 mm	box of 10

#### **DERMAL CURETTES - STERILE** order 22642 STIEF-CUR4 Dermal curettes Ø 4 mm box of 10 22644 STIEF-CUR7 Dermal curettes Ø 7 mm box of 10

## GIMA SINGLE-USE STERILE DERMAL CURETTES - LATEX FREE



Sterile, ready-to-use, disposable curettes eliminate need for re-sharpening and sterilization. Seamless, stainless steel sharp cutting edge. Easy dynamic gripping handle for sure grip. Size embossed on each curette for easy identification. Wide range of sizes.

Clinical Areas: dermatology, surgical, podiatry, oncology, veterinary.

Multilanguage box and instructions: GB, FR, IT, ES, PT, DE, PL, GR, RU, FI, SE, NL, RO, BG, HR, HU, NO, Arab.



GIMA code	DERMAL CURETTES - STERILE	Minimum order
22572	Dermal curettes Ø 2 mm	box of 10
22573	Dermal curettes Ø 3 mm	box of 10
22574	Dermal curettes Ø 4 mm	box of 10
22575	Dermal curettes Ø 5 mm	box of 10
22577	Dermal curettes Ø 7 mm	box of 10

Cutting Edge

Ensures a consistently

smooth cutting surface,

## GIMA SINGLE-USE, STERILE BIOPSY PUNCHES - LATEX FREE Seamless Stainless Stee

Sterile, ready-to-use, disposable punches eliminate need for sterilization. Seamless, stainless steel sharp cutting edge, ribbed handle for sure grip and control. Size embossed on each punch for easy identification. Wide range of sizes. Each punch is individually sealed in a peel-apart see-through package.

Clinical areas: dermatology, gynaecology, podiatry. Multilanguage box and instructions: GB, FR, IT, ES, PT, DE, PL, GR, RU, FI, SE, NL, RO, BG, HR, HU, NO, Arab.

GIMA code	BIOPSY PUNCHES - STERILE	Blade length mm	Minimum order
22580	Biopsy Punches Ø 1 mm	8	box of 10
22581	Biopsy Punches Ø 1.5 mm	8	box of 10
22582	Biopsy Punches Ø 2 mm	8	box of 10
22583	Biopsy Punches Ø 2.5 mm	8	box of 10
22584	Biopsy Punches Ø 3 mm	8	box of 10
	Biopsy Punches Ø 3.5 mm	8	box of 10
22586	Biopsy Punches Ø 4 mm	8	box of 10
22587	Biopsy Punches Ø 5 mm	8	box of 10
22588	Biopsy Punches Ø 6 mm	8	box of 10
22589	Biopsy Punches Ø 7 mm	8	box of 10
22590	Biopsy Punches Ø 8 mm	8	box of 10



## SWANN-MORTON RETRACTABLE BLADE SCALPELS AND STITCH CUTTERS

SWANN-MORTON DISPOSABLE BLADES AND SCALPELS Swann-Morton blades and scalpels are renowned their exceptional quality, precision, consistency and reliability. Swann-Morton manufactures in the UK using high quality

SAFETY SCALPELS WITH RETRACTABLE BLADE



steel that gives exceptional cutting performance. They operate stringent quality control procedures which ensure unrivalled blade consistency and reliability. This is why Swann-Morton is the preferred choice of many medical professionals worldwide

#### STITCH CUTTER WITH RETRACTABLE BLADE





## SWANN-MORTON BLADE REMOVER

• 22455 SURGICAL BLADE REMOVER - sterile - box of 50 The Swann-Morton Blade Remover allows for

safe and easy removal of all sizes scalpel blade from both No. 3 and No. 4 handles assisting in the reduction of accidental

## STITCH CUTTER

• 27058 STITCH CUTTER - sterile - box of 10



## DIAMANTINE™ EDGE HIGH PERFORMANCE BLADES AND SCALPELS

DIAMANTINE™ EDGE HIGH PERFORMANCE BLADES High quality, super sharp blades with zirconium nitride coating fused on the cutting edge to satisfy the most demanding surgeons requirements.

Durable cutting edge, that stays sharp incision after incision. The diamond like material creates a very hard edge that will not dull even under the most demanding cutting needs. Bio-compatible and highly corrosion resistant.

Compatible with autoclavable scalpel handles N. 3 and N. 4. Stainless steel sterile





DIAMANTINE HIGH PERFORMANCE SCALPELS - sterile High-Performance Edge blade for extreme and durable sharpness

- sensory grip handle enhances cutting action and control of the line of incision
- each handle has a graduated 6 cm ruler to help determine incision length (indicative only)
- protective sheath covers blade to help prevent accidental cuts







Edge high performance coated Size is clearly marked on blade and handle for easy identification blade Hardness over 2 500 Vickers

DIA	MANTINE STAINLESS STEE	EL BLADE	S - sterile (box of 100)
GIMA code		GIMA code	
27010	Blades N. 10	27015	Blades N. 21
27011	Blades N. 11	27016	Blades N. 22
27013	Blades N. 15	27017	Blades N. 23
27014	Blades N 20	27018	Blades N 24

#### DIAMANTINE STAINLESS STEEL SCALPELS - sterile (box of 10) GIMA GIMA 22460 Scalpels - blade 10 22465 Scalpels - blade 21 22466 Scalpels - blade 22 22461 Scalpels - blade 11 22463 Scalpels - blade 15 22467 Scalpels - blade 23 **22464** Scalpels - blade 20 **22468** Scalpels - blade 24

## GOUGE BLADES AND HANDLES

#### **CARBON STEEL GOUGE BLADES - sterile**

Sterile, sharp, surgical gouge blades are used by podologists for hand, feet and skin care. Each blade is sterilized by gamma



GIMA code	CA	RBON STEEL	GOUGE code	BLADES	- STERILE	
22501	Blades 1 - k	ox of 50	22506	Blades 6	6 - box of 50	
22502	Blades 2 - k	ox of 50	22508	Blades 8	8 - box of 50	
22503	Blades 3 - k	ox of 50	22510	Blades 1	10 - box of 50	
22504	Blades 4 - k	ox of 50	22512	Blades 1	12 - box of 50	
22505	Blades 5 - k	ox of 50	22515	Blades '	15 - box of 50	

radiation and protected by VCI paper in a peel - open foil sachet. Gouge blades fit into handle no. 3 and special gouge



22520 Special gouge handle - stainless steel

26913 Gouge/scalpel handle N°3 - stainless steel

NEWS 11

## ATTRACTIVE, LIGHTWEIGHT ALUMINIUM ROLLATORS WITH SEAT









#### • 43160 LIGHTWEIGHT ROLLATOR

Lightweight blue aluminium frame with PP comfortable seat. Seat adjustable height fit for different height users. Handy up seat, padded backrest foldable up and down, wheeled detachable legs make the packing size very small. Loop brakes for more safety. Size 56x77 cm. Packing dimension 60x18x58 cm. Multilanguage manual: GB, FR, IT, ES.

#### 43162 COMPACT ROLLATOR

Lightweight red aluminium frame, mesh cloth seat with pull up strap. Ergonomic handle and loop brakes for more safety. Cane holder.

Two front revolving and fold-up wheels, two rear legs fold up for a very compact folded size. Size 64x66.5 cm.

Packing dimension 66x29x37 cm. Multilanguage manual: GB, FR, IT, ES.

#### 43164 STYLISH ROLLATOR

Lightweight silver aluminium frame, foam padded nylon seat with pull up strap. Ergonomic handle and loop brakes for more safety. Hidden brake cable. Cane holder. Quick release front wheel, rear tubes fold up without any screw for a very compact folded size. Size 66x73 cm. Packing dimension 66x29x37 cm. Multilanguage manual: GB, FR, IT, ES.

## CONTACT PLUS SOFT RAISED TOILET SEATS

## • 27743 CONTACT PLUS SOFT RAISED TOILET SEAT

• 27745 CONTACT PLUS SOFT RAISED TOILET SEAT - with lid High quality soft toilet raiser, made of high-density foam injected in a waterproof PVC skin. It fits any toilet bowl in a very secure way. This comfortable seat with ergonomic shape and high density foam, raises the toilet by 11 cm (4.3 inches). Tested for 185 kg (407 lb). Made in France.











37 cm

21 cm

41 cm

26 cm

Outside



ADVANCE ELBOW CRUTCHES

- 43090 ADVANCE CRUTCHES blue/black pair
- 43091 ADVANCE CRUTCHES turquoise/black pair
- 43092 ADVANCE CRUTCHES orange/black pair Advance is the first polypropylene and elastomer bi-injected

crutch, bringing enhanced comfort to the user. Certified and tested up to 140 kg. Adjustable in height 10 times per clip. Integrated anti-noise

140

cap and Pivoflex tip. Made in France. • 43121 PIVOFLEX TIP - box of 10 - spare

Inner Ø 19 mm, outer Ø 40 mm.

Weight ka: Height handle to floor cm Material of handle: Number of adjustment of height Tube finishing/material: Certified and tested for kg:

**TECHNICAL SPECIFICATIONS** 77-98 cm polypropylene and elastomer anodized aluminiun

Hiah auality ti





NEWS 12

Handgrip length cm:

## LIFT ARMCHAIRS WITH 1 OR 2 MOTORS

Lift armchairs that feature a powered lifting mechanism that pushes the chair up from its base to assist the user to a standing position. Multilanguage manual: GB, FR, IT, ES. 1 motor lift armchair:

the chair's backrest and footrest can lift or recline together and very easily.







#### 2 motors lift armchair:

it can reach the bed position providing a relaxing experience. Its backrest and footrest can operate separately to any position. ARIANNA LIFT ARMCHAIRS with 1 or 2 motors

Blue	<b>Brown</b>	Green	Burgundy				
45170	-	-	45173	Ariann	na 1 moto	or	
45175	175 45176 45177 45178 Arianna 2 motors						
45179	45179 Arianna 2 motors - fireproof						
	COVERS FOR LIFT ARMCHAIRS						
45195	45196	45197	45198	Covers	for armo	hairs	
	Seat		Backrest	Cl	hair	Lo	oad
Width cm	Depth cm	Height cm	Height cm	Width cm	Length cm (reclined)	kg	lbs
49	49.5	49	70	75	170.5	160	352
						-	



GINEVRA LIFT ARMCHAIRS with 2 motors							
Blue	Brown	Green	Burgundy				
45180	-	<b>45182 45183</b> Ginevra 2 motors					
- 45184 Ginevra 2 motors - fireproof			eproof				
COVERS FOR LIFT ARMCHAIRS							
45195	45196	45197	45198	8 Covers for armchairs			
	Seat		Backrest	Cl	nair	Lo	ad
Width cm	Depth cm	Height cm	Height cm	Width cm	Length cm (reclined)	kg	lbs
46	51	40	66	74	169	160	352
	-	Aller					



FLAVIA LIFT ARMCHAIRS with 2 motors							
Blue	Brown	Burgund	y				
45185	45186	45188	Flavia	2 moto	rs		
-	-	45190 Flavia 2 motors - fireproof					
COVERS FOR LIFT ARMCHAIRS							
45195	45196	45198	Covers	for arn	nchairs		
	Seat		Backrest	Cl	nair	Lo	ad
Width cm	Depth cm	Height cm	Height cm	Width cm	Length cm (reclined)	kg	lbs
47	50	47	74	78	171.5	160	352





## IHEALTH WIRELESS PERSONAL HEALTHCARE SCALES



#### For iOS 9.0 and Android version 4.4 + • 23504 iHEALTH LINA HS2 WIRELESS SCALE

See the list of compatible devices Weight and BMI monitoring on iPhone, iPad and Android smartphone.

- light and compact home scale
- measures weight and BMI
- luminous LED display
- tracks data, graphs and history on the iHealth MyVitals App - store up to 200 measurements before synchronisation.
- Selection filter in the patient profile

- share your medical data with your healthcare professional or family

Bluetooth Sync, easy to install, Secure and free data storage.

TECHNICAL SPECIFICATIONS Connectivity Bluetooth 4.0 Class 2 5-180 kg - ±1% (50 - 180 kg) Range: Size - weight 310x310x26.5 mm - 1,750 g Batteries 4x1.5 V AAA included

#### • 23503 iHEALTH FIT HS2S WIRELESS BODY ANALYSIS SCALE Weight and body composition monitoring on iPhone, iPad and Android smartphone.

- light and compact body analysis scale

- measures weight, BMI (Body Mass Index), lean, bone, muscle, water mass, body fat, daily caloric intake and visceral fat rating - luminous LED display
- 8 users
- track data, graphs and history on the iHealth MyVitals App - store up to 500 measurements per user before synchronization
- share your medical data with your healthcare professional Bluetooth Sync, easy to install. Secure and free data storage.

#### TECHNICAL SPECIFICATIONS

Dimensions - weight Battery: Range- sensitivity:

Bluetooth 4.0 306x306x26.6 mm - 1,850 g 4 AAA batteries 1.5 V (included) 5-180 kg (11-400 lb) - ±1%

body fat 5%-65% ±1%

## 📕 HOSPITAL DIGITAL BABY SCALE 📕 SIRIO SCALE



 27260 SOEHNLE 7752 EXKLUSIV HOSPITAL SCALE - digital - Class III High precision and reliability scale suitable for hospital use (approved class III, MPG class I).

- attractive baby scale with very fine division of 2g / 5g - 5-button operation with programmable function key
- hold function: the weight value will freeze after stand still
- simple differential weighing after breastfeeding / feeding possible (BMIF)
- analogue and digital measurements with optional baby height rod
- tara function: covers / paddings can be tared - manual input of tare values by function key
- backlit LCD display, 16 mm digit height
- detachable baby tray
- protection Class IP X2
- provisional tare
- 27264 BABY HEIGHT ROD Digital and mechanical rod, 35 to 80 cm, division 1 mm. 27260+

Manual in 23 languages. 27264 **TECHNICAL SPECIFICATIONS** 

Sensitivity: 2 g up to 6 kg, 5 g up to 15 kg Dimensions - weight: 60x38.5x12.9 cm - 6.8 kg Operating voltage: 100-240 V, 50/60 Hz

NEWS 14



Sturdy and reliable dial scale to warrant exact and precise measurements. Large dial for easy reading. User manual in GB, FR, IT, ES, PT, DE, GR,


### **TECHNICAL SPECIFICATIONS**

Capacity: 150 kg 500 g Sensitivity Weight: 13 kg 68x27 5x108 cm Dimensions: Platform: 37x27 cm

Package size: 106x34x29 cm



## HYRIDIA 7 LEDS LIGHTS - 65.000 LUX



- 49040 HYRIDIA 7 LEDS LIGHT flexible arm trolley
- 49041 HYRIDIA 7 LEDS LIGHT metal spring arm trolley

7 Leds 10W medical procedure lights on trolley with flexible soft arm or metal spring arm. Digital brightness control. Manual: GB, FR, IT, ES, PT, DE, PL, GR.

TECHNICAL SPECIFICATIONS					
Consumption:	10 W	Light intensity and Light field	IØ:		
Colour temperature:	4,800-5,500 °K	Illumination	Ø	Distance	
External Ø of reflector:	89 mm	78,000 lux	9 cm	30 cm	
Colour rendering index (CRI):	75 Ra	65,000 lux	12 cm	50 cm	
Operating voltage: 110-265 V, 50/60 Hz 22,000 lux 18 cm 100 cm					

## LUMINA LED LIGHT



49035 LUMINA LED LIGHT - trolley Classic examination LED light with flexible arm. Manual: GB, FR, IT, ES, PT, DE, PL, GR. TECHNICAL SPECIFICATIONS

Consumption	3 W
Light intensity at 50/30 cm	37,000/89,000
Colour temperature:	6,000 °K
External Ø of reflector:	75 mm
Colour rendering index (CRI):	75 Ra
Light field Ø:	4 cm at 50 cn
Oneretine veltages	110 26E V FOICE

of headhand

Adjustable width

# SURGICAL LED HEADLIGHT

## • 30936 GIMA 40 KL SURGICAL LED HEADLIGHT

Latest generation of portable headlight system offering high quality performance. Features:

- spot size adjustable by inner mini light grating
- precise light imaging by multi optical lens
- integrated cordless design

Lamp working life: 40,000 hours

- low weight only 200 g
- Supplied with battery and battery charger

#### **TECHNICAL SPECIFICATIONS**

I LED SPOT-ADJUSTED\_LIGHT

Illumination source: 5W LED Illumination intensity: 30,000 lux Colour temperature: 6.000K Spot size: Max 70 mm, Min 50 mm at 32 cm

Battery: 3.7V Lithium Battery Battery run time: 6 hours Battery charging time: 3.6 hours Input voltage: 100-240VAC

Stainless stee

by circle or

mp head

brightness

handle



• 49047 LED SPOT-ADJUSTED LIGHT - trolley LED Spot examination lamp with multi-optical lens and light spot adjustable by inner mini light grating. Additional features: Super long flexible soft arm, length 100 cm

- uniform and pure light spot - front optical lens

- inner light grating
- rear dual optical lens
- 100 cm super long 360°

free position and PVC coated flexible metal arm

Manual: GB, FR, IT, ES, PT, DE, PL, GR.

#### TECHNICAL SPECIFICATIONS

Bulbs/power: Illumination:

Light field Ø:

1 LED / 5 W 25,000 lux at 30 cm max 70 mm,

10 000 lux at 50 cm min 15 mm at 30 cm 4,800°-6,000° K Ø 25 mm, length 125 mm Lamphead: Power supply 100-260 V 50/60 Hz Power cord: length 272 cm



rechargeable batteries

Advanced LED technology headlight with white and homoge-neous light, ideal for all surgical and dental applications - brilliant LED micro 3W provides free range of movement and

wide field of view - coaxial illumination, shadow-free illumination of cavities, ideal for ENT and dental applications.

- compact, lightweight, ensures perfect comfort

- compact and long lasting aluminium housing,

reduces heat build-up. Easy to clean. individual adjustment of the angle of view.

Hygienic

and comfortable



Illumination: 38,000 lux 40-150 mm LED operating life: up to 50,000 hours Brightness intensity: 0-100% adjustable Battery charger: 100-240 V, 50/60 Hz

Battery duration: 5-12 hours

On/off switch

rightness control and battery state

LED on the battery

NEWS 15

30879

## GIMA MOBILE SPACE: WORKTOPS AND MOBILE UNITS



furniture for medical, physiotherapy and professional beauty use. These units feature wheels and offer the same levels of functionality as trolleys. The visible edges are radiating and covered in shockproof material. The steel handles provide good grip without dangerous edges. Stability is optimised by the inner and outer sides, the extra-thick backs and invisible wheel positioning. The steel runners of the drawers with rocker arm closing ensure smooth opening while preventing undesired opening during transport.

The independent worktop makes it possible to fully pull out the units for easier floor cleaning and position the trolleys according to need. It is available with or without washbasin (left or right). The broad choice of unit configurations and colour range make it possible to personalise interiors according to individual requirements. Made in Italy.

code	STANDARD WORKTOPS - WHITE
45420	Worktop 106 cm - right washbasin
45421	Worktop 106 cm - left washbasin
	Worktop 106 cm - without washbasin
	Worktop 156 cm - right washbasin
45424	Worktop 156 cm - left washbasin
45425	Worktop 156 cm - without washbasin
	Worktop 206 cm - right washbasin
45427	Worktop 206 cm - left washbasin
45428	Worktop 206 cm - without washbasin
	ACCESSORIES
45459	Chromed mixer tap 45459
	•

#### Fixed panel with front pull handle 45453 45452 **MOBILE UNITS** Model white green 45440 45450\* 4 drawers 45441 45451 4 drawers 45442 45452 6 drawers 45443 45453\* under washbasin 'Available in 45 days, please specify colour with orde

45440

Front null handle

55 mm

130 mm

#### INFUSION STANDS • 27826 INFUSION STAND • 27829 INFUSION STAND with hydraulic pump Made of chrome plated steel. Four chrome plated steel hooks. Five spoke stainless steel base Ø 60 cm with castors Ø 50 mm, two with brake. Made in Italy. TECHNICAL SPECIFICATIONS 27826 27829 Adjustable height (cm): 160-250 189-260 Load (kg)\*: 30 Weight (kg): 10 18 Infusion pump frame (cm): - 39x75 27826 Packaging size (cm): ----185x18x43 -----27829 'Load 5 kg each hook, 10 kg for infusion pump frame

## OVERBED TABLE

• 27475 OVERBED DIFFUSION TABLE - white Overbed table with high quality, laminated, fire resistant tabletop with an edging strip. Epoxy coated "C" shaped steel frame allows for closer access while in a chair. Delivered ready to use and easy to fold flat (15 cm) for ease of storage. Weight: 8 kg. Max load: 10kg. Made in France.



45451

Top for all

mobile units

## SINTHESI MI.TO. ELECTRIC HEIGHT-ADJUSTABLE TABLES







#### SINTHESI MI.TO TABLES - electric

Two-motor examination and treatment tables, electric height adjustment by foot rail or a low voltage (24 V) foot switch. The couches have six or eight sections: the trunk section can be electrically adjusted by the operator with no effort, using the keyboard behind the head of the table, while the patient undergoes a treatment; other sections can be adjusted by one or more gas springs system. The head section is equipped with an elongated breathing hole for a higher comfort. It's a dedicated therapy table for the myofascial release techniques and postural analysis. Wide range of possible positions in flexion/extension, symmetrical or asymmetrical. Power 230 V - 50/60 Hz. Supplied with mouth-nose hole plug and postural education exercises manual. Made in Italy.

	GIMA code	SINTHESI MI.TO. TABLES	Sections	SWL.	Height adjustment
2	7578	Electric - blue	6	180 kg	foot switch
2	7579	Electric - any colour**	6	180 kg	foot switch
2	7581	Electric - any colour**	6	180 kg	foot rail
2	7583	Electric with armrest - any colour**	8	180 kg	foot switch
*SI	WL: Safe	Working Load "Available in 30 day	s		

*SWL: Safe	Working Load **Available in 30 days
GIMA code	ACCESSORIES FOR ALL TABLES
	Wheels set Ø 6.5 cm*** - retractable Mouth-nose hole plug - any colour** for Bruxelles tables
27590	Couch roll holder for rolls 50 to 63 cm for Bruxelles and Ther tables

27592 Couch roll holder for rolls 50 to 68 cm for Sinthesi tables

## VALUE EXAMINATION COUCHES • 44452 VALUE EXAMINATION COUCH - white painted - black

- 44453 VALUE EXAMINATION COUCH white painted white
- 44457 VALUE EXAMINATION COUCH chrome blue
- 44458 VALUE EXAMINATION COUCH chrome beige

Suitable for medical practices or small surgeries. Top is made with wooden panel, foam rubber and covered with washable, fireproof simulated leather Class 1.

Two sections: one fixed 131x62xh 6 cm and one adjustable (backrest) 51x62xh 6 cm. Couch size: 182x62xh 79 cm. Weight 27 kg.

Maximum load: 120 kg.
Delivered in kit form: 173x74xh 16 cm. Easy to assemble. Multilanguage manual (GB, FR, IT, ES, PT, DE). Made in Italy.

• 27418 COUCH ROLL HOLDER - optional





6 cm

73 cm



## VALUE FOR MONEY LIGHT BOXES

GIMA X-ray illuminators have been designed according to clinical recommendations for an extra white light to give an accurate and precise reading of any detail. Made of enamelled sheet steel.

Unbreakable white monochromatic diffuser, stainless steel gripping system. On/off switch for separate use of each panel for 44692. Made in Italy.

GIMA code			Exte dimension Height		Types				
		Length	neight	Depth	Weight				
44690	40x43 cm	43	46	14	6		1 panel		
44692	80x43 cm	83	46	14	10	-	2 panels		
44695	Round fluorescent light 32 W - spare								



PREGNANCY TESTS: MIDSTREAM, STRIP AND CASSETTE



urine sample reducing the risk of false results

GIMA offers a complete line of pregnancy tests, both for OTC market (self test) and for professional use. All products are packed in cardboard boxes with multilingual user manual (GB, IT, ES, FR, GR, PT). Main features:

- each test is individually packed in sealed aluminium pouch - very quick, in 3 minutes
- early detection: it can be used since the first day you miss your period (three days before for 29103) - reliability: 99.9%
- sensitivity: 20 mlU/ml (29090, 29091, 29092, 29097, 29098) 10 mlU/ml (29103)
- clinically tested - shelf life 36 months

## GYN&CUBE PESSARY

• 29887 GYN&CUBE PESSARY Ø 28/38 mm, h 38 mm - standard 29888 GYN&CUBE PESSARY Ø 32/44 mm, h 44 mm - large Silicone, autoclavable, latex free pessary with pyramidal shape and draining holes. Keylar reinforced lanvard. Multilanguage instructions: GB, FR, IT, ES, DE, NL



- stress urinary incontinence during sustained exertion (aerobics, tennis, jogging) - moderate or exteriorized prolapse moderate cystocele and rectocel

## GLOVES DISPENSERS 25431 Weight: 322 g

• 25431 GLOVES DISPENSER - single • 25432 GLOVES DISPENSER - triple Hold 1 or 3 standard boxes of 100 gloves. Made of AISI 304 stainless steel.

Can be easily hung to the wall (screw included) and into ambulances. 25432 S - M - L box of glov





## BREAST PUMPS

## • 41700 MANUAL BREAST PUMP

• 41701 SINGLE ELECTRIC BREAST PUMP Compact and lightweight breast pumps for efficient and

discreet pumping. Easy to assemble, use and clean. Supplied with breast shield, nipple with cover, milk bottle with lid, multilanguage manual (GB, FR, IT, ES).




- 41705 BREAST SHIELD + NIPPLE spare
- 41706 BREAST MILK BOTTLE 150 ml with lid set of 3 spare
- 41708 AC ADAPTER for 41701 optional

#### TECHNICAL SPECIFICATIONS 41700 41701 stimulate: - 60-130 Vacuum mmHq: - 250 expression: - 60-250 Weight: 265 q 205x186x90 129x129x55 Operation: manual 4AA batteries not included or AC adapter (optional)



## IUD - INTRAUTERINE CONTRACEPTIVE DEVICE



## PLUS - sterile

Sterile disposable medical device Class III for intrauterine contraception in women of child bearing age. Can be left inserted for a maximum of 5 years. Packed in a pouch with an insertion tube equipped with a movable flange to aid in gauging the right depht of insertion and a rod. Complies with ISO-7349.



• 29712 GYNEAS IUD KIT - sterile A complete disposable kit for IUD insertion including: 1 intrauterine device (IUD), 1 speculum medium size,

hysterometer. 1 pair of Pozzi tenaculum forceps, 1 Evolution forceps,

1 pair of thread-cutting scissors, 1 practitioner and 1 patient brochure.

Ergonomic, strong and thin single-

use forceps suitable for grasping of

conisations, IUD insertion

vagina axis).

- box of 25

the insertion.

Stainless steel blades with a


notch allowing to trap the

IUD threads to ease the cut

(align cervix and womb with

the cervix, cervical cerclage, biopsies,

Increased stiffness



Instructions: GB, FR, IT.

#### • 29714 IUD INSERTION AND REMOVAL KIT - sterile

Disposable kit for IUD insertion and removal including: 1 Evolution Pozzi forceps, 1 long Littauer scissors, 1 Evolution long forceps.

## GYNAECOLOGY FORCEPS AND SCISSORS

#### • 29717 CHERON FORCEPS 25 cm - box of 25 • 29718 POZZI FORCEPS 25 cm - box of 25 Suitable for:

- cervix cleaning/disinfection before any intervention (ex. IUD insertion) used with a gauze or a piece of cotton and disinfectant solution

- IUD removal



#### 25 cm - box of 25

Same applications as Cheron forceps, but with longer and thiner jaws. Longer and thiner jaws allowing:

 to insert the forceps in the endocervi. (when IUD threads are no longer visible outside the cervix)

- to improve the grip on the IUD threads to remove it

## BIOPSY FORCEPS

## 29724 GYN&PUSH CERVICAL BIOPSY

FORCEPS 21.5 cm - box of 25 Effective cervical biopsy forceps for a successfully biopsy, quickly achieved with a high quality sample.

Complete comfort and safety for both doctor and patient. Disposable sterile medical device, Class II a.

Latex free and phtalates free. Shelf life: 5 years.



Sterile disposable medical device, Class I. Latex free. Sterilized by ETO. Shelf lifes 5 years.

## I FLEXIBLE HYSTEROMETERS

29720

Plastic handle

#### SINGLE USE, STERILE, FLEXIBLE HYSTEROMETERS

29927

Hysterometers with soft distal part on a rigid handle for IUD (29925, 29926). Hysterometer with progressive dilation distal part from CH 10 to CH 14 on 25 mm, suitable for IUS\*\* (29927).

	A RESIDENCE OF THE PROPERTY OF		
	29926		
-	29925	(	<b>(</b> 1370
GIMA code	HYSTEROMETERS SINGLE USE - STERILE - LATEX FREE	Ø	Minimum order
	Hysterometer CH 10 - 30 cm	3.3 mm	box of 25
29926	Hysterometer CH 12 - 30 cm	4.3 mm	box of 25
29927	Hysterometer CH 14 - 30 cm		box of 25
	*IUD: Intra Uterine Device	"IUS: Intre	a Uterine System

## EVOLUTION HYSTEROMETER

• 29929 EVOLUTION DOUBLE HYSTEROMETER 30 cm - box of 25 The most versatile, economical and eco-friendly single-use hysterometer. Estimating the uterine depth, checking cervical canal permeability and womb orientation.

Sterile, disposable medical device, class I. Latex free, PVC free. Shelf life: 5 years.

> Innovative double track system 2 flexible and shape memory tips with gradual dilation For all types of IUD insertion and womb shapes

Diameter CH 10→CH 14 3 3 mm→4 7 mm

29929 Pale pink color allowing better observation of cervical mucus

Diameter CH 8→CH 12

**( (** 1370

NEWS 19

## OMRON EVOLV ALL IN ONE ARM BLOOD PRESSURE MONITOR

#### 49900 OMRON EVOLV ALL IN ONE ARM BLOOD PRESSURE MONITOR

The new, easy to use, all in one upper arm blood pressure monitor. Take accurate readings in any position around the upper arm and track progress via smartphone.

- All in one upper arm blood pressure monitor: no tubes, no wires, simply accurate
- Intellisense Technology: inflates the cuff to the ideal level
- Intelli Wrap cuff: for an easy and accurate reading - Clinically Validated: proven reliability and accuracy under
- vigorous testing procedures by major health organisations.
- Cuff Wrap guide: indicates if the cuff is wrapped correctly, not too loose or too tight
- OMRON connect App: get connected, access anytime, see progress. Mobile application for iPhone / Android™. Supplied with battery set, storage case, manuals. Made in Japan.

#### TECHNICAL SPECIFICATIONS

Cuff Type: Intelli Wrap Cuff 22-42 cm

Memory: Cuff Wrap Guide: 100 Readings

Irregular Heartbeat Detection: Body Movement Detection: Yes

Validation: Clinical Validation, Pregnancy Validation

Intellisense Technology Stroke Prevention:

12x17.3x12.5 cn





With standard cuffs, 1-in-3 people neasure their blood pressure incorrectly EVOLV's Intelli Wrap Cuff Technology ensures 360° accuracy in any position



EVOLV can sync your readings to your smartphone to track results, monitor pro-gress, and get a deeper understanding of vour health. See smartphone compatibilit list on omronconnect.com/emea/en\_abi

## OMRON DIGITAL BLOOD PRESSURE MONITOR

#### • 32946 OMRON RS4 HEM-6181-E - wrist

Multilanguage manual and box: GB, FR, IT, ES, DE, NL, RU, TR, Arabic.

#### TECHNICAL SPECIFICATIONS

Measuring method Measuring range:

Pressure Memory (with date and time): Inflation - deflation:

Rating: Power source Rattery life (N° of measurements)

Protection against electric shock Weight (console+cuff) without batteries

Cuff materials: Measurable circumference (cm):

DC3 V 3.0W 2 "AAA"batteries 1.5 V 300 internally powered ME equipment 86 g 93x62 xh 20 mm

0 mmHa to 299 mmHa ± 3 mmHa

40 to 180 min ± 5% of display reading

32690

nylon and polyester

automatic



## KOBE PALM SPHYGMO

#### • 32690 KOBE PALM SPHYGMOMANOMETER

Economic, lightweight, palm type sphygmomanometer with reliable large dial manometer for easy reading. Scale 0-300 mmHg, graduated every 2 mmHg. Adult nylon cuff, PVC bladder, PVC inflation bulb with handle,

release valve nickeled in black. Supplied in PVC carrying case with 8 languages user manual and box (GB, FR, IT, ES, PT, DE, GR, Arabic).

• 32845 ADULT CUFF - spare


only 135 g

• 32846 PEDIATRIC CUFF - optional

## MESH NEBULIZER 28066 MESH NEBULIZER

Small, handy, lightweight nebulizer for the treatment of respiratory diseases such as acute inflammation, tracheitis, bronchitis, swelling and pain in throat. Can operate with 2xAA standard batteries or USB cable.

- maximizes the benefits of medicine
- portable, handheld design (110 mm height)
- ultra-low noise, ultra-light only 104g
- one-button operation for easy use - for adult and child: noiseless use and
- compact design allow to make inhalation even while children are sleeping Supplied with adult and child mask, mouthpiece, 2xAA batteries, USB cable, carrying bag, manual (GB, IT, FR, ES, PT, DE).
- 28067 RESPIRATORY ACCESSORY KIT (adult and child mask, mouthpiece) - spare • 28068 NEBULIZER HEAD - spare



## TECHNICAL SPECIFICATIONS 2xAA batteries or USB cable DC 5V approximately 110kHz

Ultrasonic frequency: Nehulizer rate Max. / min. liquid volume: MMAD Nebulizing head life: Battery life: Shutdown Safety leve

Power supply

>0.25ml / min 10ml / 0.5ml approximately 4µm 180 hours 60 minutes

automatic without liquid Type B. Class II, IP 22



NEBUL OF B

## ■ VISIO 5 PLUS WALL DIAGNOSTIC STATION 3.5 V - XENON OR LED

VISIO 5 PLUS WALL DIAGNOSTIC STATION 3.5 V Modern design diagnostic station to satisfy all practitioners

and clinics needs. Two configurations availables - oto-ophthalmoscope with disposable ear tip dispenser


- ophthalmoscope only.

Two illumination technologies: LED or Xenon-Halogen. Regulated output prolongs the bulb life and guarantees optimal light intensity.

- ergonomic designed non-slip handles
- constant output transformer with integrated surge protection
- soft start technology to introduce voltage gently, eliminates cold-shock when turning ON increasing bulb life
- automatic ON-OFF switch once the handle

is removed or replaced in the cradle

- adjustable light intensity, low power consumption
- precise brightness control, between 3 and 100%
- spiral cord of 3 meters when stretched



Visio 5XE Plus additional features (31623) Coaxial ontics for easier examination of undilated nunils

Detection of corneal abrasion with cobalt blue filter



#### GIMA VISIO 5 PLUS DIAGNOSTIC STATION

31620 Visio 5GE Plus oto-ophthalmo diagnostic station\* - Xenon 31621 Visio 5GE Plus oto-ophthalmo diagnostic station\* - LED

Include power transformer, 2 handles, oto/ophthalmo heads, dispenser with 100 disposable grey peculum (50 Ø 2.5 mm, 50 Ø 4 mm), wall board for easy mounting or removal of diagnostic station 31622 Visio 5GE Plus ophthalmoscope diagnostic station - LED

31623 Visio 5XE Plus ophthalmoscope diagnostic station - LED 31428 Xenon bulb for ophthalmoscope - spare

31544 Xenon bulb for otoscope - spare

31485 Disposable mini ear speculum Ø 2.5 mm - grey - box of 100

Disposable mini ear speculum Ø 4 mm - grey - box of 100

## SIGMA-C LED OTOSCOPES

- 31591 SIGMA-C LED OTOSCOPE black pouch • 31592 SIGMA-C LED OTOSCOPE - blue - pouch
- 31593 SIGMA-C LED OTOSCOPE violet pouch

- made from light weight impact resistant re-enforced plastic and highly corrosion resistant stainless steel material for exterior finish - swivel type window with 3X magnification lens for sharp

image and minimal reflection
- optional insufflation port for pneumatic testing of tympanic
mobility (needs codes 31532 and 31500)
- compatible with Gima ear specula 31485-8, 31491-2, 31495-9

- 50.000 hours lifetime
- super bright 7,500 LUX

31527

31530

31513,

31524,

31525,

31526

- extended battery life of 50 hours
- colour temperature 4,300 K, CRI>95 ensures real colour.

# 31591

31593

## SIGMA F.O. XENON OR LED OTO AND OPHTHALMO SETS SIGMA F.O. OTOSCOPES AND OPHTHALMOSCOPES 2.5V - standard hand

31591

High quality pocket diagnostic instruments	NEW LAUN
designed for professiona	l use in ENT
and ophthalmoscopy. Lig	ht weight and
manufactured from impa	act resistant
re-enforced plastic. See cata	loque page 212

•	HI 31	GIVIA 1.O.	JIOSCOI E.	stanuaru manule		
_		TOSCOPES	·	OPHTHALMOSCOPES		
	Black	Blue	Purple	Black	Туре	Packing
	31524	31523	31511	31530	Xenon-Halogen	Pouch
	31525	-	-	31527	Xenon-Halogen	Case
	31513	-	-	-	LED	Pouch
	31526	31518	-	31529	LED	Case
	SIGMA F	O. LED OT	OSCOPE AN	ID OPHTHALMO 2.5V - rechargeabl	e" handle with b	attery
	31580	Otoscope v	eable handle and battery - black	LED	Pouch	
	31582	Ophthalmo	scope with re	echargeable handle and battery - black	LED	Pouch
	Otoscopes an	e supplied with	14 disposable	e specula (7 with Ø 2.5 mm, 7 with Ø 4 mm)		

31592

Rechargeable handle can be used with "AA" standard batteries or rechargeable battery code 31587 (needs charging station code 31586) Full battery charge in 2.5 hours. Can be connected to PC or laptop via standard USB cable (not included)

GIMA code	SIGMA F.O. OTO-OPHTHALMOSCOPE SETS*** 2.5V - black	Туре	Packing
31533	Oto-ophthalmoscope set with 1 handle	Xenon-Halogen	Case
31528	Oto-ophthalmoscope set with 2 handles	Xenon-Halogen	Case
31534	Oto-ophthalmoscope set with 2 handles	LED	Case
31584	Oto-ophthalmoscope set with 2 recharg. handles and batteries	LED	Case

"Oto-ophthalmo sets are supplied with oto and ophthalmo head, 1 handle (31533) or 2 handles (31528, 31534, 31584), 14 disposable specula (7 with Ø 2.5 mm, 7 with Ø 4 mm), 2 rechargeable batteries (31584)





١.		
١	GIMA code	CHARGING SYSTEM
,	31586	Charging station
,	31587	Rechargeable battery
1	31588	Metal endcap

NEWS 21

## 3M™ LITTMANN® CLASSIC III STETHOSCOPES

The 3M™ Littmann® Classic III™ Stethoscope offers high acoustic sensitivity for exceptional performance when doing general physical assessments.

- It features dual tunable diaphragms and updated design.
- versatile adult and pediatric two-sides chestpiece
- dual single-piece tunable diaphragms (pressure sensitive)
- small-side diaphragm prevents debris in open bell
- high acoustic sensitivity
- snap tight soft-sealing eartips
- next generation longer-life tubing
- small side converts to open bell



## **NEW LAUNCH**

GIMA	3M	3M™ LITTMANN® CLASSIC III
code	code	MIRROR/CHAMPAGNE
32239	5960	Littmann® Classic III - plum - mirror
32240	5962	Littmann® Classic III - pearl pink - mirror
32243	5861	■ Littmann® Classic III - black - champagne
32244	5862	■ Littmann® Classic III - raspberry - mirror
32245	5863	Littmann® Classic III - navy blue - mirror
32246	5864	■ Littmann® Classic III - burgundy - champagne
32247	5865	Littmann® Classic III - lavender - mirror
32248	5874	Littmann® Classic III - caribbean blue - mirror
32249	5959	Littmann® Classic III - ceil blue - mirror

# ttmann Stethoscopes



## **Authorized Distributor**



## 5872 Littmann<sup>®</sup> Classic III - turquoise - smoke chestpiece

32308 5870 ■ Littmann® Classic III - black - rainbow finish 32309 5871 Littmann® Classic III - raspberry - smoke finish 32310 5803 ■ Littmann® Classic III - black edition 32311 5809 ■ Littmann® Classic III - chocolate - copper fin. 32312 5806 Littmann® Classic III - raspberry - rainbow fin. 32313 5807 Littmann® Classic III - caribbean blue - rainbow fin. 32314 5811 ■ Littmann® Classic III - black - smoke finish 32315 5812 Littmann® Classic III - dark olive green - smoke fin.

32316 5867 Littmann® Classic III - navy blue - black finish 32317 5868 ■ Littmann® Classic III - burgundy - black finish 32318 5869 Littmann® Classic III - caribbean blue - black fin.

32319 5873 Littmann<sup>®</sup> Classic III - grey - smoke chestpiece

32320 5875 Littmann® Classic III - lime-green - smoke chestpiece



CLASSIC III - PEARL PINK



CLASSIC III - BLACK - SMOKE FINISH



CLASSIC III - NAVY BLUE - MIRROR



CLASSIC III - RASPBERRY RAINROW FINISH

## CLASSIC CASE FOR STETHOSCOPES

- 32667 CLASSIC CASE FOR STETHOSCOPES black
- 32668 CLASSIC CASE FOR STETHOSCOPES burgundy • 32669 CLASSIC CASE FOR STETHOSCOPES - turquoise

High quality protective hard case for classic style, single tube stethoscopes, available in 3 colours. Its design holds the stethoscope secured in place by a preformed interior, keeping the sensitive diaphragm and tubing protected. Lightweight EVA construction and strong protective outer shell covered in 1680D

Pre-formed moulded interior can also be removed for flexible usage. Sealed dustproof and waterproof zipper with rubber easy-grip zipper pulls for easy opening and closing.

Interior mesh pocket for additional accessory storage. 32668 Carry handle for easy transportation. Outside size 28x16x5 cm; inside size 26.5x14.5x4 cm.

Removable FVA tray with multispandex fabric 32669 32667



Mesh pocket with elastic 14x19 cm

Weight: 220 g NEWS 22

## ■ 3M<sup>™</sup> LITTMANN® CARDIOLOGY IV STETHOSCOPES

smoke

rainbow

black edition

black - red stem

black - blue stem



The 3M™ Littmann® Cardiology IV helps you to catch more of the subtle critical sounds, thanks to the improved acoustics and the new design, more versatile than ever.

- better audibility of high-frequency sounds

- tunable diaphragms for hearing both high and low frequency sounds without turning over the chestpiece (pressure sensitive) - adult and paediatric sides for more versatility

3M™ LITTMANN® STETHOSCOPES - length 69 cm

- single-piece diaphragm, easier to attach and clean,

because the surface is smooth without crevices

- next generation longer-life tubing snap tight soft-sealing eartips.



Ŋ.				C	ARDIOLOGY IV - head	Ø 43/33 mm	
烮					Littmann® Cardiology		
P					Littmann® Cardiology		
					Littmann® Cardiology		en
					Littmann® Cardiology		
	ı	32612	6158		Littmann® Cardiology	IV - raspberry	
	ı	CARDI	OLOGY	<b>/</b> I\	/ SPECIAL HIGH POLISH	FINISH - head Ø	43/33 mi
_	J					Tubing	Finish
		32614	6232		Littmann® Cardiology IV	black	smoke
		32615	6234		Littmann® Cardiology IV	carribbean blue	smoke
		32616	6238		Littmann® Cardiology IV	grey	smoke
		32617	6240		Littmann® Cardiology IV	black	rainbow
		32618	6241		Littmann® Cardiology IV	raspberry	rainbow
		32619	6242		Littmann® Cardiology IV	navy blue	rainbow
d		32642	6204		Littmann® Cardiology IV	black	smoke
		32651	6202		Littmann® Cardiology IV	navy blue	smoke
		c	ARDIC	L	OGY IV SPECIAL FINISH	- head Ø 43/3	3 mm

32643 6190 Littmann® Cardiology IV carribbean blue champagne 32644 6176 Littmann® Cardiology IV burgundy 32645 6206 ■ Littmann® Cardiology IV hunter green 32646 6169 ■ Littmann® Cardiology IV carribbean blue mirror 32647 6170 Littmann® Cardiology IV burgundy 32648 6177 ■ Littmann® Cardiology IV black mirror 32649 6179 ■ Littmann® Cardiology IV black/champagne smoke



3M™ LITTMANN® STETHOSCOPES - length 69 cm

CARDIOLOGY IV SPECIAL FINISH - head Ø 43/33 mm

32630 6205 Littmann® Cardiology IV plum

32631 6162 ■ Littmann® Cardiology IV black

32632 6163 ■ Littmann® Cardiology IV black

32633 6164 ■ Littmann® Cardiology IV black

32634 6165 ■ Littmann® Cardiology IV black

32635 6166 ■ Littmann® Cardiology IV plum

32639 6200 ■ Littmann® Cardiology IV black

32640 6201 ■ Littmann® Cardiology IV black

32636 6168 Littmann® Cardiology IV navy blue black

32637 6171 Littmann® Cardiology IV turquoise smoke

32638 6178 ■ Littmann® Cardiology IV raspberry smoke





chestpiece

## 3M™ LITTMANN® MASTER CARDIOLOGY STETHOSCOPES



MASTER CARDIOLOGY





	code	code	3M™ LITTMANN® STETHOSCOPES - length 69 cm							
-	MASTER CARDIOLOGY - head Ø 51 mm									
	32435	2160	■ Littmann® Master Cardiology - black							
	32436	2163	■ Littmann® Master Cardiology - burgundy							
	32437	2164	■ Littmann® Master Cardiology - navy blue							
	32439	2167	■ Littmann® Master Cardiology - plum							
	32361	2178	Littmann® Master Cardiology - caribbean blue							
	32362		Littmann® Master Cardiology - colour on request							
	MAS	STER CA	RDIOLOGY SPECIAL EDITION - head Ø 51 mm							
	32356	2175	■ Littmann® Master Card black - brass finish							
	32357	2182	■ Littmann® Master Card dark olive green smoke finish							
	32360	2176	■ Littmann® Master Card black - smoke edition							
	32473	2161	■ Littmann® Master Card black edition							

NEWS 23

## NUVOAIR NEXT SPIROMETER WITH BLUETOOTH

• 33478 NUVOAIR NEXT SPIROMETER WITH BLUETOOTH Professional, clinically validated, affordable, connected spirometer. It measures FEV1, FVC, PEF, FEV1/FVC, predicted values, expiratory curve, inspiratory curve, to detect and monitor lung function diseases. An intuitive App with clear visual instructions allows to perform lung function test, to see how your lung health develops over time and to stay connected with your doctor, sharing results with a touch of a button. Compatible with most Apple and Android smartphones and tablets. Requires iOS 8.0 (or later) or Android 5.0 Lollipop (or later). Easy to use and ultraportable. Maintenance free with the hygienic and calibration free turbines. Designed in Sweden, assembled in China Medical device Class IIa. Supplied with 1 disposable turbine with mouthpiece, 2xAAA batteries.

Multilanguage manual: GB, FR, IT, ES, PT, DE, GR, SE, can be downloaded from NUVOAIR APP.

• 33480 DISPOSABLE TURBINE WITH 33480 INTEGRATED MOUTHPIECE - box of 60

TECHNICAL SPECIFICATIONS

Camera will capture a photo when driver

Flow sensor Bi-directional digital optical Flow range 0-141/s Dynamic resistance: <0.5 cm H<sub>2</sub>O/L/s Measurement method: infrared interrumption Measured parameters: FEV1, FVC, PEF, FEV1/FVC 2x1,5V AAA alkaline batte Size - weight: 98x62x26 mm - 75 a 10 years



## PROFESSIONAL ALCOHOL TESTER

24486 AP338 EASY RECALIBRATION ALCOHOL TESTER with printer

• 24487 PRE-CALIBRATED SENSOR MODULE for 24486 - spare

• 24494 BLOWING TUBES for 24486, 24491 - box of 100 pcs.

• 24495 PAPER ROLLS for 24486, 24491 - box of 10

Professional fuel cell sensor breath alcohol tester with printer and touch screen. The fuel cell is a porous disk with a thin layer of platinum. Any alcohol that comes in contact with the cell's surface is broken down chemically.

For each broken down molecule of alcohol a given number of electrons are freed.

The numbers of electrons generated are in proportion to the amount of alcohol.

Self recalibration: easy replacement of pre-calibrated module.

**TECHNICAL SPECIFICATIONS** Display: Colour 4.5" iPS LCD display Kevboard: Navigation key input with touch panel Rechargeable 3.7 V Li-ion battery Power Supply Warm up: Chamber & Sensor warm up automatically Auto flow monitoring: Automatic flow detection Operating environment: -20 to +45°C (optimal 5 to 40°C) USB port Data download: Windows XP, 7\*, 8\*, 10\* Compatibility: 150,000 memories full test

driver name, vehicle number, inspector name, test result with print date and time, location, calibration data. Measurement precision: Standard deviation ±0,025 mg/L or ±5% of the measurement

Drift: typically <0,8% of the measurement value/month by replacement of pre-calibrated sensor module Calibration mg/L, mg/100 L, %BAC, %BAC Unit setting:

\*Can export files as Microsoft Excel documents directly







Easy handling in 3 step

LACTATE SCOUT 4: PROFESSIONAL LACTATE MEASUREMENT

viewing on the move

23992 LACTATE SCOUT 4

Fast and accurate:

Ergonomic device for fast, accurate and reliable lactate measurement. Easy to use: Stores over 500 results

- only 0.2 µl of capillary blood required

- pre-calibrated sensors

- device calibrated by simple coding

- lactate measurement, date/time, mode, temperature, heart rate and memory ID on a single display

- enzymatic amperometric detection method

- results within 10 seconds - measuring range: 0.5 - 25 mmol/L (±3%)

Performance measurement:

- single and step-test measurements (resting/exercise/recreation)

- stopwatch and countdown timer functions

- connection to heart rate monitors for linking to lactate value Integrated bluetooth technology and PC software:

An USB key allows easy transfer to PC and a 4 language (GB, DE, IT. ES) software allows easy data management. Supplied with nylon bag, empty spray bottle, Bluetooth module, USB key with software and manual (GB, FR, IT, DE, ES, NO, SE, CZ, GR, NL, PL, TR).

• 23991 STRIPS - tube of 24 pcs

• 24513 SURGILANCE SAFETY LANCETS 26G - sterile - box of 100



Prick finger and collect blood by touching sensor



NEWS 24

## ■ MAG 3000 low frequency, high intensity pemf magnetotherapy

180x110x50 mi I-TECH

• 28314 MAG 3000 PEMF MAGNETOTHERAPY - 2 channels

MAG 3000 is a certified medical device

for pulsed electromagnetic field magnetotherapy (PEMF). Suggested for the treatment of delayed union, osteoporosis, bone oedema, osteonecrosis,

as well as ulcers and neuropathies.

Thanks to the high intensity of the magnetic field, it is also suitable for the treatment of bone fractures even in the presence of rigid bandages or plaster casts.

- two indipendent channels

- colour display

magnetic field intensity up to 150 gauss per channel

frequency from 1 to 100 hz

- 41 programmes available

possibility to manage two treatments at the same time by setting different times and programmes (double user)

list of the last 10 programmes used For professional users (doctors, therapist, ...) and for in-home therapy.

Operating power 110-240 V.

28314

• 28315 ELASTIC THERAPEUTIC BELT - light blue - spare Belt with cable with 3 solenoids for low frequency treatments.

• 28316 COUPLE OF PROFESSIONAL SOLENOIDS

Professional solenoids Ø 11 cm for high intensity therapy.

#### STANDARD ACCESSORIES

3 solenoids belt applicator User manual (GB, FR, IT, FS) Carrying bag

Medical power supply Magnet to verify therapy operation Three non-woven fabric strips 15x150 cm

#### Osteonorosis Arthrosis

Arthritis Cervical arthrosis Articular pain Cervicalgias Chronic pain Fractures Epicondylitis **Epitrocleitis** Pseudoarthrosis Lumbalgy

Lumbar pain

Shoulder arthrosis

41 PROGRAMMES Knee arthrosis Scapulo humeral periarthritis Muscular atrophy Muscular treatment Osteonecrosis

Algodystrophy Cartilage lesion Ligament lesion Bone cedema Tendinitis Chondropathy Antinflammatory

Neuropathy Muscle strain Muscular cramp Rizarthrosis Impingement syndrome Carpal Tunnel Titanium prosthesis Rotator cuff Tarsal Tunnel

Healing

Cutaneous ulcers

Myalgia

# OSTEOMAT NEW: MATTRESS FOR LOW FREQUENCY MAGNETOTHERAPY TREATMENTS

Whiplash syndrom


#### • 28318 OSTEOMAT NEW MATTRESS FOR MAGNETOTHERAPY Osteomat New is composed of 4 active sectors, containing 2

solenoids each, for a total of 8 professional solenoids. The Osteomat New is the ideal solution for total body treatment in a single session, thanks to easy-to-use mode and extreme flexibility.

The configuration of Osteomat New stimulates the body areas (shoulders, column, pelvis) that are more affected by bone mass reduction.

This is typical of osteoporosis pathology. Suitable for MAG 2000, MAG 2000 PLUS, MAG 3000 and LaMagneto models. Supplied with non-woven fabric cover (pack of 2 pieces).

Suggested for night therapy during sleep, day therapy in paralyzed patients, active pa-



## PILL PLANNERS



• 41500 7 DAY PILL PLANNER X 2 - GB

• 41501 7 DAY PILL PLANNER X 2 - IT

2 translucent colours. Size 18.3x9.3x3.3 cm

41501


41505



• 41506 7 DAY PILL PLANNER X 4 - IT

4 translucent colours. Size 19x13x2,8 cm

28318



# PILL CRUSHING DEVICE

• 25872 SILENT KNIGHT HOSPITAL PILL CRUSHING DEVICE

• 25873 PILL CRUSHER POUCHES - 1,000 pouches (20 packs of 50) Professional, silent crusher for hospital to effortlessly and easily reduce pills in fine powder in few-seconds. Pouches avoid any cross contamination and eliminatly loss of medication.



Step 1: place pills into pill crusher pouch. Lift handle and place pouch down between

the crusher plates to initiate crushing. Step 2: press handle down to crush pills.

Step 3: press the handle down to activate grinding movement. Press handle down several times to grind pills into fine powder

Step 4: remove the pouch

## TRACKING SYSTEM DOCUMENTATION: 2 LINE LABELER

#### TRACEABILITY/DOCUMENTATION

The traceability system of the instruments provides you a proper and easy handling of sterilized materials. This system tracks each instrument, from the preparation to the sterilization and to its final use. The combined use of Labeler and Labels will give you a complete and essential data system for the safeguarding of each operator and the Healthcare.

- easy print of identical labels with minimum time and effort

- eliminates mistakes in batch numbers
- easy interpretation of the results due to precise colour change. - no need for additional process indicators using our labels with indicator

#### • 35980 2 LINE MEDICAL LABELER 14+14 DIGITS

The two line labeler is reliable, easy to use and durable, it will serve for years of intensive usage. Thanks to Medical Labeler, you are able to print on the labels all requested information as: lot No, sterilizer/cycle No, sterilization date and expiry date. Supplied with multilanguage manual (GB, FR, IT, ES, Arabic)

• 35984 2 LINE STEAM LABEL - box of 12,000 (24 rolls of 500 labels) First print line can display: 3 alphabetic digits + 11 numbers Second print line can display: 14 numbers

Steam indicator label, suitable for steam sterilization cycle. Double adhesive support. After the sterilization cycle the indicator faces a changing from its original colour PINK to BROWN, Process indicator: Steam Standard ISO 11140-1 Class 1, non toxic ink, latex free.

226 Hz at 85 dB SPL

automatic

53563)

1 sec

400 daPa/sec

from +200 to -400 daPa

automatic tympanometry

autothreshold, fixed intensity

0.5. 1. 2 and 4 kHz (with reflex lic. Plus)

ipsilateral at 226 Hz

100 dB HL (ipsi)

10 to 100 dR HI

125-8000 Hz

• 35982 INK ROLL FOR LABELER - box of 5



Expiry 21.10.20 21.10.20 date 21.10.19 21.10.19 We have shown a preferred use of first print line, but user can print alternative information

## I TIMPANI HANDHELD TYMPANOMETER/SCREENING AUDIOMETER





ideal to house the device, to recharge the hattery faster and to transfer data to the PC at the same

53566



Timpani is supplied with Inventis Maestro software, USB connection cable, medical grade power supply, assorted eartips, GB, IT manuals in a carrying case.

• 53560 TIMPANI HANDHELD TYMPANOMETER The handheld tympanometer Timpani is a lightweight, com-

pact and powerful device, designed to conduct middle ear screening tests simply, swiftly and accurately The basic version of Timpani allows to perform automatic tympanometry exam using 226 Hz probe tone. Optional licenses allow acoustic reflexes test and screening pure tone audiometry. The device features a wide colour display with touch-screen interface.

• 53563 REFLEX LICENSE - PLUS

To conduct ipsilateral acoustic reflex test at 0.5, 1, 2 and 4 kHz. • 53564 SCREENING PURE TONE AUDIOMETRY (PTA) WITH PRE-

CALIBRATED HEADSET

To conduct pure tone air conduction audiometry.

- 53565 PATIENT RESPONSE BUTTON FOR PTA
- 53566 DOCKING STATION FOR TIMPANI
- 53567 BLUETOOTH THERMAL PRINTER THERMAL PAPER ROLL 57 mm - box of 5 EARTIPS: see page 258 for spare

LANGUAGES	GB	FR	IT	RU	ES	PL	PT	JP	CH	KR	DE	TR
Firmware	Х	Х	Х		Х	Х						
Maestro software	Х	х	х	х	х	х	х	х	х	х	х	х
Manual*	Х		Х		Х							

color graphical with touch screen

Lithium-Ion rechargeable battery

>4 hours of continuous use

'GB and IT included with product, ES for download from www.gimaitaly.com TECHNICAL SPECIFICATIONS

## Input

Output 0.2 to 8.0 ml at 226 Hz, 0.9 to 16.0 mmho at 1000 Hz Device specifications Display type: Display size:

Resolution Power supply Battery life Pc interface: Software:

Dimensions Weight: Standards:

Inventis Maestro (compatible with Noah) 65 x 44 x 240 mm (2.6 x 1.8 x 9.5 inches)

340 g / 12 oz Imped.: EN 60645-5/ANSI S3.39. Type 2/3 PTA: EN 60645-1/ANSI S3.6, Type 4/4 Safety: EN 60601-1 - EMC: EN 60601-1-2 Class IIA (93/42/EEC) Classification

50 patients

2.8" / 43.2x57.6 mn

240x320 pixels

USB (driverless)

Freq. range NEWS 26

Measurement system

Acoustic reflex (only

Audiometry (only with 53564)

Probe tone:

Comp. range:

Pressure range

Tympanometry

Type of test:

Scan rate:

Stimuli:

Intensity

NEWS 25

Stimulation

Available tests

Maximum int.:

Stim Duration



simultaneously ECG, heart rate, ORS duration, SpO., pulse rate and pulse index. With colour touch screen, well organized user interface and audio instructions, is very intuitive and easy to use. Clinical approved accuracy. ECG + HR + SpO<sub>2</sub> + - supports both cable and cable-free measurement

of ECG and SpO<sub>2</sub> (optional cable) - checks, captures and identifies abnormal ECG in 20 sec.

- professional ECG algorithm provides heart rate, QRS duration, ST segment and rhythm analysis

- check blood oxygenation with built-in SpO, sensor in 20 sec

- high quality ECG waveform can be saved and replayed - professional PC data management software for review and generating reports (compatible with windows OS)

• 35190 EXTERNAL SpO, SENSOR - optional

20 SECONDS ORS + Pulse Rate + P

> Audio instruction GB, PL, DE, IT, FR, ES, HU



STANDARD ACCESSORIES Software

Charging cable, micro D ECG cable

## CHECKME™ PRO VITAL SIGNS MONITORS - WIRELESS WITH BLUETOOTH

 35186 CHECKME™ PRO VITAL SIGNS MONITOR - with Bluetooth 35187 CHECKME™ PRO VITAL SIGNS MONITOR WITH ECG

**HOLTER** - with Bluetooth

All-in-one, compact, versatile and portable wireless vital signs monitors for checking your health anytime anywhere. They can be used in a wide range of application scenarios. including: outpatient, emergency, surgeries, telemedicine.

STANDARD ACCESSORIES

• 35188 AIR BP BLOOD PRESSURE UNIT\* - optional Ultra-portable smart upper arm blood pressure device.

• 35190 EXTERNAL SpO, SENSOR - spare

ECG + SpO<sub>2</sub> + BP (needs 35188) Sleep Apnea + Temp + Pedometer + 24 hours ECG holter (only 35187

supports both cable and cable-free operation measurement of oxygen saturation, pulse rate and pulse strength

manage all vital signs data together Temperature - Integrated infrared temperature sensor

it greatly reduces the frequency and the cost of hospital visit since results can be shared with doctor

user data, user profile, readings and wave form can be exported om Checkme to the browser by USB

Audio instructions: GB, ES, IT, DE, FR, PL, RU, HU
Pc software: GB
App: GB, DE, FR, ES

\*Includes main unit, cuff and charge cable

sport chest band (only 35187)

ECG cable, SpO<sub>2</sub> sensor, ECG electrodes, charge cable, neck

strip, user manual, protective cover, wrist band, Y adaptor and

CHECKME™ PRO FEATURES

ECG - supports both cable and cable-free operation - 500 Hz sampling rate and wide bandwidth - 3006s waveform can be replayed - professional ECG algorithm to provide Heart Rate, QRS duration, ST segment, QT/QTC interval, and rhythm analysis ECG holter (only 35187) - easy to wear and use - cable to the company of the com

the report includes heart rate, rhythm and HRV (heart rate variability) holter report can be stored in Cloud, printed or saved as PDF

Sleep apnea screening
- 5p0, monitor for 05A (Obstructive Sleep Apnea)
- records and tracks 5p0, and Pulse Rate up to 10 hours
- mobile APP to check 5p0, change in details
Blood Pressure via Bluetooth (needs code 35188)

quick measurement with high accuracy - safe and comfortable, no need to wake up child while sleeping

oometer
- accurately calculate steps, calories and amount of fat burned
- built-in high accuracy 3D smart sensor
APP - support IOS and Android
- built-in Bluetooth, all data can be exported from
device to phone/tablet

PC browser medical data management software

Manual: GB, ES, IT, DE, FR

NEWS 27

35188

# GIMA 900 PRO AND PLUS VITAL SIGNS MONITORS • 35124 GIMA 900 PRO VITAL SIGNS MONITOR

• 35132 GIMA 900 PLUS VITAL SIGNS MONITOR

"Vital Signs" is a line of small multi-parameter patient monitors, which can monitor the vital physiological parameters: non-invasive blood pressure (NIBP), pulse oxygen saturation (SpO<sub>2</sub>), electrocardiogram (ECG) and temperature (TEMP).

Features:

- 3.5"LCD display for remote review (GIMA-900 Pro). and 7" high resolution touch screen (GIMA-900 Plus)

- history data records reviewed in waveform, list and trend graph

- USB connection for data output and software upgrade

Optional printer

GIMA **ACCESSORIES AND SPARES** code 35133 Printer\*- optional Installation done by Gima 35141 Paper 5.1 cm x 12 m - box of 5 ordered with monitor.

35126 Lead acid re-chargeable battery - spare for 35120-2 35129 Lithium re-chargeable battery - spare for 35124, 35132

35135 Reusable adult SpO, probe - spare 35136 Reusable pediatric SpO. probe

35137 5 leads ECG cable - spare 35140 NIBP cuff - 10-19 cm - pediatric 35142 NIBP cuff - 18-26 cm - pediatric XL

35139 NIBP cuff - 21-35 cm - adult 35143 NIBP cuff - 27-42 cm - adult XL

35127 Trolley - adjustable 73 to 113 cm 35128 Rail clamp

Adult SpO, probe

NIRP adult cuff Temperature probe - skin type

STANDARD ACCESSORIES · Lithium rechargeable battery - Power supply cable - Dust protective mantle

35128

00 35124

35132

TECHNICAL SPECIFICATIONS Measuring method: Oscillometric

Measurement mode: Manual, Auto, STAT ECG Measurement range: Press(unit) Adult Pediatric Neonate HR display accuracy: ± 1% or ± 2 bpm, SYS mmHa 40-275 40-200 40-135 MAP mmHg 20-230 20-165 20-110 DIA mmHg 10-210 10-150

Measuring range: 35%~100% Measuring accuracy: 3% for range from 70 to 100%

Low perfusion performance: as low as 0.4%

Measuring accuracy: ±2 bpm or ±2% whichever is greater HR display range: 15~350 bpm

whichever is greate HR alarm delay time: <10s Sensitivity selection: x1/4, x1/2, x1, x2 Sweeping speed: 25 mm/s Temperature Measuring range: 21-50°C

Measuring accuracy: ±0.2°C for range 25-45°C

LoFlo™ Sidestrean

33796

LoTto

CO, sensor

Other Technical Specifications Power supply: 100~240 VAC, 50/60 Hz Battery: 11.1 V / 4,400 mAh (Li-ion Battery

# RESPIRONICS CO, SENSORS: CAPNOSTAT MAINSTREAM AND LOFLO SIDESTREAM.

NIBP

35127

• 33797 CAPNOSTAT MAINSTREAM CO. SENSOR for intubated patients

Small, durable and lightweight mainstream CO, sensor provides accurate and reliable monitoring for all intubated patients from neonates to adults. No calibration required. Fast airway measurement.

COMPATIBILITY OF LOFLO AND CAPNOSTAT CO. SENSORS

Bionet (BM1, BM5), Contec (CMS 8000), Creative (PC-3000, UP7000, K10, K12, K15), Mindray (various), Philips (various)

Capnostat® Mainstream CO sensor 33797

• 33796 LOFLO SIDESTREAM CO. SENSOR for intubated and non intubated patients Flexible and compact CO. sensor that

provides consistent and reliable CO. monitoring of adult, pediatric and neonatal patients. No calibration required. 50 ml/minute sampling rate. ACCESSORIES FOR LOFLO SIDESTREAM CO.

• 33790 INTUBATED FILTER LINE H - adult - box of 10 • 33791 INTUBATED FILTER LINE H - infant - box of 10

• 33792 NON INTUBATED CO, NASAL CANNULA - adult - box of 10

• 33793 NON INTUBATED CO NASAL CANNULA - ped. - box of 10 • 33794 NON INTUBATED CO. +O. NASAL CANNULA - adult - box of 10

33795 NON INTUBATED CO<sup>2</sup>+O<sup>2</sup> NASAL CANNULA - ped. - box of 10

CAPNO CUBE CAPNOGRAPH



Update time: Every breath Warm up time: < 15 seconds Memory: 24 hours with trend and numeric

Sensor: Adapter for intubated patient

• 33831 POCKET CAPNO CUBE CAPNOGRAPH (MAINSTREAM) Innovative capnograph designed for monitoring the vital physiological signs of patients from newborn to adult.

real-time Capnogram within 15 seconds - suitable for pre-hospital first aid, incubator, anesthesiology,

respiration, sleeping monitoring and intubated monitoring

· 24 hours memory with data management softwar large numeric display visible from 5 meters

Supplied with adult/pediatric adaptor, neonatal adaptor, silicone protection, USB cable, AC adapter, CD software and manual (GB, IT).

33832 ADULT/PEDIATRIC AIRWAY ADAPTOR

• 33833 NEONATAL AIRWAY ADAPTOR

**TECHNICAL SPECIFICATIONS** 

InsCO<sub>2</sub> Range: 3 - 50 mmHg Respiration Rate
Range: 3-150 rpm ± 1% or ± 1 rpm
Memory: 24 hours with trend and numeric

Airway Adapter dead space: 5 ml (adult/pediatric), 1 ml (neonate) AC input: 100-240 V, 50/60 Hz - 5 W

Charging time: 4 hours Operating time: 6 hours Firmware software: GB, FR, IT, ES, DE, NL Norms: IEC 60601-1/CSA 601-1/UL2601-1 Protection: Type BF - Class II, IP 33

ш

**NEWS 28** 

EtCO<sub>2</sub> Method: Non-dispersive Infrared

Spectroscopy
Range: 0-150 mmHg or 0-20 kPa
Accuracy: ± 2 mmHg, range from 0-40 mmHg
± 5%, range from 41-70 mmHg

± 8%, range from 71-100 mmHg

ECG + SpO<sub>2</sub> + NIBP +

RESP + 2-TEMP

39.4

36.7 37.1 04

onal 2 IBP + EtCO, modu

360° degree

visible indicator

Lithium battery

continuous

Ontional

35133

35148

up to 2.5 hours

with 3 level alarm

## K12 AND K15 PATIENT MONITORS FOR INTENSIVE CARE

15" display with LED backlight 9 waveform

- 35306 K12 MULTIPARAMETER MONITOR 12"
- 35307 K12 TOUCHSCREEN MULTIPARAMETER MONITOR 12"
- 35309 K15 TOUCHSCREEN MULTIPARAMETER MONITOR 15" • 35310 K15 TOUCHSCREEN 2 IBP' MULTIPARAMETER MONITOR 15"

Multi-functional patient monitors, designed for monitoring the vital physiological signs of adult, pediatric and neonate patients. With the functions of real-time recording and 35309 displaying parameters, such as ECG, heart rate (HR), non-invasive blood pressure (NIBP), oxygen saturation (SpO<sub>2</sub>), respiration (RESP), temperature (TEMP), it allows

- comprehensive analysis of patient's physiological conditions. ergonomic design with intuitive user interface
- USB socket for data transfer and software upgrade
- 9 traces on-screen waveforms
- Windows style display view, easy to operate
- visual and audible alarm for physiological and technical alarms
- large capacity storage
- suitable for use with original Nellcor sensors
- protection against defibrillator discharge, resistance against the interference from electro-surgical unit; Cardiac pacemaker pulse detection and inhibition.

#### Internal software: GB, DE, FR, PT, ES, IT, PL, TR, RU. 61 . .. PC software only GB. 母 () 西川 ACCESSORIES FOR K12, K15 35133 Printer\*\* - optional \*Installation done by Gima if 35141 Paper 5.1 cm x 12 m - box of 5 ordered with monitor Need 35311 NIBP cuff - 6x11 cm neonate - optional service if ordered later 35312 NIBP cuff - 10x19 cm pediatric - optional 35313 NIBP cuff - 21x35 cm adult - spare 35315 SpO, probe\*\*\* D type - neonate - optional - need ext. cable 2 IBP module 35316 SpO<sub>2</sub> probe\*\*\* D type - pediatric - optional - need ext. cable 35317 SpO<sub>2</sub> probe\*\*\* D type - adult - spare - need ext. cable (35310 only) = 17 35318 Extension cable for SpO, probes - spare STANDARD ACCESSORIES Nellcor compatible disposable SpO, sensors - pages 293-5 Adult SpO probe NIBP adult cuff Respironic Mainstream and Sidestream CO, sensors - news 28 SpO, extension cable ECG cable 35319 Rechargeable lithium battery - spare Skin temperature probe Power supply cable 35320 ECG cable - spare Re-chargeable lithium battery Dust-protective cover 35148 Trolley - optional Disposable electrode Manual: GB, FR, IT, ES, PL, RU 35321 IBP sensor - disposable - spare for 35310 only - 2 IBP module, cable, sensor (only 35310)

Invasive Blood Pressure (IBP) is a direct measurement of the patient's arterial or venous blood pressure. A catheter is used and inserted directly into a vein, artery or other pressure access areas, and is connected to a pressure transducer for measuring systolic, diastolic and mean blood pressures. The device can display the systolic, diastolic and mean blood pressures and a waveform for each pressure channel.

CO<sub>2</sub> Technique:

Flow rate:

Calibration

Display:

IBP - 35310 only Technique: Input sensitivity:

Measuring range: Measuring positions:

Other Specifications

Alarming method

Networking:

Safety standard:

Power supply: Built-in lithium battery:

Sampling mode

Measuring accuracy:

#### Input dynamic range: Differential input impedance: ≥10 MΩ 0.05~150 Hz (Diagnostic) 0.5~40 Hz (Monitoring) 1~20 Hz (Operation) CMRR ≥90 dB (Diagnostic) ≥105 dB (Monitoring & Operation) ×1/4, ×1/2, ×1, ×2, ×4 and Auto Sensitivity selection: 6.25 mm/s, 12.5 mm/s, 25 mm/s, 50 mm/s Sweeping speed: 15~350 bpm ±1% or ±2 bpm, whichever is greater Pacemaker pulse detection and rejection function RESP Measuring range 0~120 rpm +5% or +2 rpm, whichever is greater TEMP 21.0~50.0 °C ±0.2 °C from 25~45 °C Measuring range Technique Oscillometric method Typical measurement time: <30 seconds (adult cuff) NIBP measuring range: 40~275 mmHg (Adult) 40~200 mmHg (Pediatric) 40~135 mmHg (Neonate) NIBP measuring range

10~210 mmHg (Adult)

10~150 mmHg (Pediatric) 10~95 mmHg (Neonate) 20~230 mmHg (Adult) 20~165 mmHg (Pediatric) 20~110 mmHg (Neonate)

NIBP measuring accuracy: Mean difference: +5 mmHg Standard deviation: 8 mmHo

#### TECHNICAL SPECIFICATIONS Manual, Auto, STAT, Multi-cycle mode NIBP measurement mode: Auto measuring intervals: SpO

Dual-wavelength optical method 0%~100% ±2% for SpO<sub>2</sub> range 70~100% 30~250bpm ±2bpm or ±2%, whichever is greater Technique: Measuring range: PR measuring range: Low perfusion performance: As low as 0.3%

Infrared optical method Sidestream or Mainstream

0~150 mmHg 0~40 mmHa ±2 mmHa 41~70 mmHg ±5% of reading 71~100 mmHg ±8% of reading 101~150 mmHg ±10% of reading

50 ml/min +10 ml/min (Sidestream

Strain gauge transducer 5 µV/V/mmHq

-50~300 mmHg ±2% or ±4 mmHg, whichever is greater ART, RAP, PA, LAP, CVP, ICP, AUXP1, AUXP2 zero calibrating

AC 100-240 V, 50/60 Hz, 60 VA 11.1V/4400 mAh 12 or 15 inch TFT display 3 levels audible-visible alarm

IEC 60601-1

## PATIENT CENTRAL STATION UP TO 64 MONITORS FOR UP7000\*, K12, K15

#### 35323 CENTRAL STATION SOFTWARE

NIBP measuring range

Software that collects all the data of each bedside monitor and display them in a collective way. It stores and monitors the trend data of ECG and other parameters and analyses the stored data. It can support up to 64 bed monitors. It includes Soft-key, CD Software, 2 meters networking cable.

• 33745 CENTRAL STATION SYSTEM PC+MONITOR

#### • 33746 LAN CABLE - 3 m

• 33767 LAN CABLE - 30 m One cable for any monitor to be connected. Customized cable length on request.

Since S.N. J3300PG00766



## AMBU® KING VISION® aBLADE™ VIDEO LARYNGOSCOPE • 58106 KING VISION® aBLADE™ VIDEO LARYNGOSCOPE SET

The King Vision® video laryngoscope is especially designed to visualize, in the most reliable way, the airways for routine and difficult intubations.

The reusable display is lightweight, non-glare, smudge-proof, packaged in a protective foam case and is battery operated. The blades are disposable and are individually packaged, eliminating cross contamination risks. Can be used continuously about 90 min., making it highly portable. Video output compatible with external monitor and recording devices.

Two blade types: a standard blade that requires the use of a stylet to direct the ET tube and a channeled blade where you can guide the ET tube with the blade. Made in the U.S.A.

- 58108 PEDIATRIC STANDARD aBLADES size 2\* box of 20
- 58109 PEDIATRIC CHANNELED aBLADES size 2\* box of 20
- 58110 VIDEO ADAPTER for aBLADES size 2 optional
- 58112 STANDARD VISION aBLADES size 3" box of 20 spare
- 58113 CHANNELED VISION aBLADES size 3\*\* box of 20 spare
- 58116 VIDEO ADAPTER for aBLADES size 3 spare
- " For large children, adults

#### STANDARD ACCESSORIES Vision display 1 reusable video adapter for aBlades size 3 4 channeled vision aRlades - size 3

3 AAA batteries



2 standard vision aBlades - size 3

integrated camera

Protective gasket Ergonomic desian Integrated blader 13 handle design for complete contro Channeled and standard disposable blades for guided or standard insertions Guiding channel for easy ETT placement and remova-58106 Excellent optics

58080

Full colour TFT LCD

display anti-reflective

/New anti-fog lens

## MAXLITE FLEXTIP F.O. XENON/HALOGEN OR LED SETS AND BLADES

58072

#### XENON-HALOGEN OR LED F.O. FLEXTIP LARYNGOSCOPE SETS WITH INTEGRATED FIBRES FOR DIFFICULT INTUBATIONS

Deluxe set including one F.O. rechargeable handle, one or two F.O. Mc Intosh blades N° 3 or N° 3 and 4 and bulb. The movable blade tip facilitates lifting of the epiglottis and enables a perfect visibility of the intubation process even in case of difficult anatomical conditions. A better visibility and a lower lever force reduce the risk of injury of the larynx and the teeth.

- stainless steel construction, matt finish
- can be used with all Green Spec Handles - compatible with ISO 7376 Green Standards
- channel provides improved viewing area
- 4.5 mm fibre bundle with more than 6,500 individual fibre
- high quality fibres ensuring excellent light transmission, 8,000 lux with 2.5V Xenon lamp, 20,000 lux with 2.5V LED lamp - 2x"C" batteries or rechargeable batteries (not included)
- autoclavable at 134° C, approximately 2,000 times
- can sustain Plasma sterilization (Sterrad 100 NX)

MAXLITE FLEXTIP F.O. SETS - 2.5 V with integrated fibres 58070 MAXLITE F.O. XENON FLEXI SET 1 blade Mc Intosh 3

58073 MAXLITE F.O. LED FLEXI SET 1 blade Mc Intosh 3

58072 MAXLITE F.O. XENON FLEXI SET 2 blades Mc Intosh 3-4 34498 MAXLITE FO LED FLEXLSET 2 blades Mc Intosh 3-4

58079 GIMA ACCESSORIES AND SPARES FOR MAXLITE FLEXI 58078 MAXLITE F.O. FLEXI BLADE N° 2 Mc Intosh (115x90 mm) MAXLITE F.O. FLEXI BLADE N° 3 Mc Intosh (135x110 mm) 58080 MAXLITE F.O. FLEXI BLADE N° 4 Mc Intosh (155x130 mm) 34485 Bulb 2.5 V - spare

## PLASTIC OR ALUMINIUM SCOOPING STRETCHERS



- 34103 SCOOPING STRETCHER aluminium
- 34104 SCOOPING STRETCHER plastic

Wonderfully practical scooping stretchers allow to put the stretcher under the patient without moving him/her much.

The shape of the stretchers has been designed to immobilize the patient properly during transport.

- effective hooking and unhooking device for stretcher uncoupling
- adjustable stretcher length with automatic locking device

34467 Adult rechargeable Li-ion battery 2.5 V

31542 Charging station 100-240 V - see page 327

- bag with 3 quick unhooking safety belts for patient
- immobilization
- once folded can be easily stored inside the ambulance - built in light and sturdy aluminium (34103) or plastic (34104)
- X-ray translucent (34104 only)

TECHNICAL SPECIFICATIONS 34104 34103 Onen size cm: min 171x43 max 205x43 min 164x44.5 max 200x44.5 Folded size cm: 121x43x10 118y44 5y8 5 Weight: 7.5 kg 8.5 kg

#### • 34219 DEFIBRILLATOR ACCESSORIES KIT

Pocket mask kit with accessories for reanimation and defibrillation. Kit includes: 1 pocket mask, 1 antiseptic wipe, 4 vinyil gloves, 1 disposable razor





## DAE-AED SIGNS

• 35325 DAE-AED ALUMINIUM FRONT SIGN 25x31 cm • 35326 DAE-AED ALUMINIUM FRONT SIGN 34x36 cm



with thickness 5/10.
Pre-drilled for wall



# 35326

## PRACTI-MAN CPR MANIKIN



- 56500 PRACTI-MAN ADVANCE CPR MANIKIN
- 56501 4 PRACTI-MAN ADVANCE CPR MANIKINS

CPR manikins for massive training events:

- adult and child CPR training with a single manikin - 3-position selector dial: adult, child and test

- real-like system for breathing function - iaw thrust maneuver
- 56504 PRACTI-MAN LUNGS -
- 56505 PRACTI-MAN VALVES -



## DEFIBRILLATOR ACCESSORIES KIT MILITARY TOURNIQUET

• 25526 MILITARY TOURNIQUET - orange • 25527 MILITARY TOURNIQUET - black Mainly used for stopping massive haemorrhage of limbs on field conditions or in normal

25526



25527

pre-hospital emergency.

Easy to use, one-handed application tourniquet improving the efficiency of hemostasis. It can be self-applied or applied by a first responder, allowing a quick and easy regulation of the pressure needed Suitable for both upper and lower limbs. Made in woven synthetic

25526

PVC

fabric with thermoplastic clasp and secure windlass. Size: 95x4 cm.

## EMERGENCY TROLLEY BAGS

Trolley bag and rucksack made of strong, water resistant 600D polyester (27154) and PVC (27173) with durable cold resistant wheels.







#### • 27154 EMERGENCY SMART TROLLEY BAG - 56x32.5x49 cm Extremely capacious with internal adjustable compartments which permit personalized

organization of the space. Provided with external pockets, internal divisions, and one removable pouch with transparent window. Double yellow reflective strips. Waterproof rubber bottom to prevent water infiltration.

• 27173 EMERGENCY LOGIC 2 PVC TROLLEY RUCKSACK - 49x31x57 cm Supplied with 6 coloured pouches with transparent window and velcro strips, 2 frontal po-ckets and 2 lateral pockets. Internal velcro strips and elastics, to retain instruments. Central division with zip and elastics. Provided with vellow reflective strips and shoulder straps

## ■ VENTURI VARIABLE CONCENTRATION MASK FOR OXYGEN THERAPY



• 34170 VENTURI TYPE VARIABLE CONCENTRATION MASK - adult box of 50

• 34171 VENTURI TYPE VARIABLE CONCENTRATION MASK - pediatric -

box of 50

Disposable adult or pediatric mask with Venturi system, with corrugated tubing 15 cm, extension tubing 200 cm, cup and seven adapters for variable oxygen concentration. Latex free.

	•	
% Regulators	Litres/minute to reach desired oxygen concentration	Colour coded according to EN 13544-3:200
24%	2	Blue
28%	4	White
31%	6	Orange
35%	8	Yellow
40%	8	Red
50%	12	Fuchsia Pink
60%	15	Green

NEWS 31

## ■ COMPATIBLE PADS FOR OVER 90% OF DEFIBRILLATORS ON THE MARKET



ADULT COMPATIBLE PADS - disposable

A range of compatible pads BSI certified for patients >8 years (25 kg) for most defibrillators on the market. Excellent adherence and adequate gel thickness. Includes a couple of pads, cable and connector. Maximum shelf life 30 months (24 months for 33584) from production date. Latex free.

Compliance to regulations: Directive 93/42/EEC and amendments. Class IIb medical device. ANSI/AAMI: DF-80; IEC/ EN: 60601-1, 60601-2-4; ISO: 10993-1.

Made in Italy

#### **NEW LAUNCH**

GIMA code	BRAND	MODEL	GIMA code	BRAND	MODEL
33576	Agilent-Philips	- Heartstream/HeartStart XL M4735A	33579	Nihon Kohden	Cardiolife TEC 2202 - 2203 - 5500 - 7531
		- Heartstream/HeartStart XLT M3500B			7600 - 7700 - 8251 all with cable JC-755V,
		- HeartStart XL 861290			TEC 5600 - 8300 with cable JC855V
		- HeartStart 4000 M5500B	33576	Philips Laerdal N	
22570		(all with Philips cable M3508A)			re Runner I AED models E, S, EM
		- Cardio Aid 100 - 200 - 200B - 360B - XL - XL+ - Cardio Aid LS - MC - MC+			AED 940010XX - 940020XX - 940030XX AED M3841A - M3861A
		- Reanibex 200 - 300 - 500 - 700 - 800			AED M3841A - M3861A AED, with ECG module M3840A, M3860A
		- Powerheart AED 9200			1722A/B, M1723A/B, M1724A, M2475B
33300	Cardiac Science	- Powerheart AED G3 9300 series			le M3507A and pad adapter 05-200)
		(G3, G3 Plus, G3 Pro)			M3535A (with Philips cable M3508A)
33581	Cardiaid	- Cardiaid CT0207	33587		- Lifepak 9 connector Quick-Combo
		- Elife 700	55507	,5.000	- Lifepak 10 - 12 - 15 - 20 - 20E - 500 AED
		- Futura			pink or grey socket - 1000 AED
	<b>CU Medical System</b>		33588	Schiller	- Fred Easy - Fred Easy 2G
		- DDU 100 Lifeline AED - DDU 120 Lifeline Auto AED			- Defigard DG4000 - DG5000 - DG6002
33579	Drager	- Cardiolog 2000	33586	Schiller	<ul> <li>Defigard DG1002 - DG3002 - DG2000 EDOS</li> </ul>
		- MDF SAED - MDF II			- Fred - Fred Tele
33580		- Responder AED - AED Pro	33592	Schiller	- Fred easy port - Argus PRO Lifecare
33583		- Responder 1100 - 2000 - 3000 (direct			- Argus PRO Lifecare 2 - Fred PA-1
		connection)			- Cardiovit AT 101 Easy
		- Cardioserv (direct connection)			- Defigard Touch 7
22570		- Dash Responder (direct connection)	33579		- Cardio Aid LS - MC - MC+
33589		- CardioAid 200B - 200 - 100 - 360B - XL+ - XL - AED 7000		Weinmann	- Tecnoheart Plus (for patient >10 kg) - Meducare easy - Meducare standard
		- HeartOn AED A10		Welch-Allyn	- AED 10 - AED20
		- HeartOn AED A10	33379	Weich-Allyn	- PIC30 - PIC40 - PIC50
		- Heartsave AED - AED-M - 6 - 6S	33589	Zoll Medical Corp	- Zoll PD 1200 - 1400 - 1600 - 1700 -
33003		since S.N. 739xxxxxxx	55555	2011 111 Cultur Co. p	2000 - E - M - R - X series
		- Defimonitor XD			- Pro pag MD
33587		- Beneheart D1 - D3 - D6	33585	Zoll Medical Corp	- Aed Plus - AED Pro - AED 3
33579		Lite - Lifequest			without CPR function
Connector	s to defibrillator of comp	patible pads Multilanguage env	elope: Eng	lish, Italian, French, Germ	nan, Spanish, Portuguese, Greek, Dutch, Russian, Swedish
				22570 22	FOC











33581









## PEDIATRIC COMPATIBLE PADS with energy reduction system

#### PEDIATRIC COMPATIBLE PADS - disposable These pads have an energy reduction system: defibrillator output

33592

of 150J (33606) or 200J (33603) is reduced to 50J. International CPR guidelines state 8 years as limit age for pediatric treatment. corresponding to about 25 kg according to standard growth curves. Compliance to regulation as above adult compatible pads. 33603

Latex free. Made in Italy.





_			_
	GIMA code	BRAND	
	33604	<b>Cardiac Science</b>	-
			-
			(
	33604		-
		Mediana	-
	33606	Philips Laerdal	-
3		Medical	-
7			ľ
	33603	Physiocontrol	-
			-

33584 Tecno-Gaz

BRAND	MODEL
Cardiac Science	- Powerheart AED 9200 series
	- Powerheart G3 AED 9300 series (G3, G3 Plus, G3 Pro)
GE	- Responder AED, AED Pro
Mediana	- HeartOn AED A15 (for patient >10 kg)
Medical	- Heartstart FR2 AED M3841A & M3861A - Heartstart FR2 AED, with ECG module 3840A, M3861A, 3860A
•	<ul> <li>Lifepak 500 AED pink socket</li> <li>Lifepak 1000 AED</li> <li>Lifepak CR plus AED - Lifepak Express AED</li> </ul>
	Cardiac Science  GE Mediana Philips Laerdal Medical Physiocontrol

- Tecnoheart Plus (for patient >10 kg)

## RESCUE LIFE MANUAL AND SEMIAUTOMATIC DEFIBRILLATORS

**RESCUE LIFE 7"** 

BESCUE

display 7" to view simultaneously up to 12 ECG channels MADE IN ITALY **AVAILABLE WITH** - SpO - NIBP PACEMAKER OU MAY ORDER UNI

WITH 1 TO 3 OF ABOV

PARAMETERS

#### Fast connection.

User can choose between ergonomic reusable paddles for manual defibrillator or disposable pads for AED defibrillation.

Both types are equipped with a single fast lock connection for reliable rescue operations

## RESCUE LIFE BIPHASIC DEFIBRILLATORS 7"

ECG cable SpO, sensor input Rescue Life is an external defibrillator with monitor. It is designed to be used by out-of-hospital and hospital users. Lightweight, transport facility, attractive line, ergonomic shape, studied in every details. It is a complete acute cardiac care response system designed for Basic Life Support (BLS) and Advanced Life Support (ALS) patient management protocols. The IPX4 standard permits the operation under adverse climatic situations. Rescue Life is totally MADE IN ITALY. SpO, and pacemaker

**C** € 0068

Range includes models with pacemaker and SpO<sub>3</sub>. ECG module for monitoring (not for diagnosis) includes up to 12 derivations standard 5 leads patient cable (for I, II, III, aVL, aVR, aVF) or optional 10 leads patient cable (for 12 derivations).

The NIBP option is focused on advantage A+ module of SunTech Medical that provides the highest NIBP performance during movements. Suitable for adult, pediatric and neonatal. High contrast TFT LCD colour display 7"

Bright, high contrast, wide-angle colour display for simultaneous view of up to 12 ECG channels

#### Data management

The memory is based on a flash disk of 4 GB for 300 recorded hours for all AED models

#### Asynchronous and synchronous

- in asynchronous defibrillation. Rescue is advised on patients

with the following symptoms: unconsciousness, absence of normal breathing and lack of detectable pulse.

- in synchronous defibrillation. Rescue Life is advised on patients with ECG's reporting Atrial

## 3 operation modes: manual, AED, Advisory

- in manual mode RESCUE LIFE is intended for use by doctors and trained individuals. Only 3 steps: energy selection from 1 to 230J, energy charge and shock

- in AED mode, RESCUE LIFE is intended for use by personnel authorized by a physician or medical director. The voice prompts and display messages are assisting the operator during CPR operations, charging automatically to 150J when a shock-able ECG rhythm is detected.

- in advisory Mode, the system alerts when the shock is necessary leaving the energy level and charging choice to the operator.

Initialising and system test at switching on of the device

Auto test and fault recognition.

Clinical test

Available on our web site.

#### Ergonomic design. Impact proof, compact and lightweight Comfortable and washable carrying bag keeps all accessories at hand and protects Rescue

#### Memory and data management.

imple commands, extremely intuitive and easy to use. Immediate access to main setup parameters using only trim knoh and function keys

> **TFT COLOUR DISPLAY** AUTOMATIC SELF TEST



Adult and pediatric

eusable paddles

### STANDARD ACCESSORIES

Internal Li-Ion battery 1 paper roll Patient cables 5 leads 2 disposable pads (AED only) 2 adult and pediatric reusable paddles Manual: GB, IT Other English Italian **RESCUE LIFE 7" DEFIBRILLATORS** 33185 33186 33187 Rescue life AED defibrillator 33192 33193 Rescue life AED defibrillator with pacemaker 33191 33196 Rescue life AED defib. SpO<sub>2</sub>+NIBP+Pacemaker 33194 33195

33188 33189 33190 Rescue life AED defib. other configuration On request we can offer Rescue Life and Rescue Life AED in Spanish and Fren \*On request we can offer Rescue Life and Rescue Life AED with SpO<sub>3</sub>+NIBP, SpO.+Pacemaker (available in GB, FR, IT, ES)

\*On request we can offer Rescue Life 7 with SpO, NIBP or Pacemaker.

You can choose 1 to 3 of above parameters. "Available on request manual in FR and ES.

GIMA code	RESCUE LIFE ACCESSORIES
	Disposable paddles - box of 2 - adult - original Disposable paddles with cable box of 2 - adult - optional
	Disposable paddles with cable box of 2 - adult - optional Disposable paddles with cable - box of 2 - pediatric - original
22502	Cable for disposable paddles
	ECG cable 10 leads
	Rescue Life bag
	Thermal paper
	12V car light adapter - inverter

#### **TECHNICAL SPECIFICATIONS**

high contrast TFT colour or LCD 7" (800x480 dots)

ECG through the discharge paddles (1 trace) or

through 5, 10 leads patient cable for 3, 6, or 12

ECG monitoring
- bandwidth: 0.5 to 120 Hz (-3db) with filters off

gain; 2.5, 5, 10, 20, 40 mm/mV with patient cable;

HR digital readout on the display 20 to 300 hpm (+ 2%)

alarm: settable HR, min 20 bpm, max 250 bpm

Pulse oxymetry (SpO<sub>2</sub>) 33188-33190, 33194-33196

pulse rate: 30 to 150 ppm adjustable in steps of 5 ppm

pulse Current: 0 to 150 mA adjustable in steps of 5 mA

- oxygen saturation range: 0 to 100% - pulse rate range: 30 - 220 pulses per minute

- accuracy SpO<sub>2</sub>: 70-100% ± 2 digits for adults using the finger clip sensor

SpO, Alarms adjustable (min. 50%)

Non-invasive pacemaker (33188-33196)

operating mode: fixed on demand

Automatic change over when plugging th

filters: 50/60 Hz, base line, EMG

speed: 5, 10, 25, 50 mm/sec

traces and SpO, value

heart rate indicato

auto with paddles

rectangular wave

impulse duration: 22 ms

patient cable

#### amplitude: MAX 150 V

NIBP (33188-33190, 33194-33196 only) technique: oscillometric

accuracy: meets ANSI/AAMI SP10-2002, EN 1060-4 patient application; adult/pediatric/neonatal

range mmHg pediatric neonatal systolic MAP 40-160 26-133 40-130 26-110 40-260 26-220 diastolic 20-200 20-120 20-100 Printer:

- manual, automatic (10"pre and post recording) integrated thermal printer for ECG traces and events documentation including HR/SpO. NiBP values

paper speed: 5, 10, 25, 50 mm/sec paper width: 58 mm Safety:

two hand safety shock release FCG input insulation CF class

internal discharge after 30 sec. of standby after charge Power supply: internal Li-lon battery

(charging time 95%: 2 hours) AC 100-240 VAC, 50/60 Hz Memory: internal flash 4 GB up to 300 hours of ECG data, events and usage review

General: Dimensions: 36x24x34 cm Weight: 5.5 kg with battery

## NEWS 33

## ■ 3M™ SCOTCHCAST™ PLUS ■ 3M™ SOFT-CAST™



3M™ SCOTCHCAST™ CASTING TAPE

A lightweight, strong and durable casting tape that combines the benefits of a fiberglass casting tape with the handling ease of plaster.

- water-activated resin lets you control working time according to application needs - high and early strength allows for weight bearing in 20 minutes and provides a durable cast with less chance of breakdown and the need for costly repairs or replacements
- lightweight for easy mobility - stretches to conform well to contours for a more comfortable, better fitting cast

- porous weave allows the skin to breathe

	GII			3M code	3M™	Minimum order
White	Green	Red	Blue	code	SCOTCHCAST™	order
59610	59611	59612	59613	82002	5 cm x 3.65 m	box of 10
59620	59621	59622	59623	82003	7.5 cm x 3.65 m	box of 10
59630	59631	59632	59633	82004	10 cm x 3.65 m	box of 10
59640	-	-	59643	82005	12.7 cm x 3.60 m	box of 10



A fiberglass casting tape that does not set to a completely rigid state, but remains flexible and soft even when it is completely cured. - the soft, pliable cast edges improve patient comfort can be used in combination with rigid fiberglass splints, as soft edges provide additional comfort

Suggested Applications: - sports Medicine: thumb wrist and ankle sprains

pediatric Orthopedics: serial casting for club foot tre general Orthopedics: secondary casting, hybrid casting, corsets

occupational Therapy: removable splints

GIMA code White Red Blue			3M code	3M™ SOFT-CAST™	Minimum order
59650	-	-	82101	2.5 cm x 1.8 m	box of 10
59660	59662	59663	82102	5 cm x 3.65 m	box of 10
59670	59672	59673	82103	7.5 cm x 3.65 m	box of 10
59680	59682	59683	82104	10 cm x 3.65 m	box of 10

## 3M™ STOCKINET™



#### 3M™ STOCKINET™

Water repellent and therefore suitable for use with Soft Cast as a water proof cast. Suitable for use with all casting materials, plaster and synthetic

GIMA code	3M code	3M™ STOCKINET™	Minimum order
59701	MS02	5 cm x 22.8 m	1
59702	MS03	7.5 cm x 22.8 m	1
59703	MS04	10 cm x 22.8 m	1

## ■3M™ MICROFOAM™





59673

59663

3M™ MICROFOAM™ SURGICAL TAPE

Highly conformable elastic foam tape that stretches for compression applications or securing dressings on challenging areas. Multi-directional stretch to accommodate swelling and promote comfort. Gentle, secure adhesion to irregularly contoured sites. Water-resistant. Hypoallergenic and not made with natural rubber latex.

GIMA code	3M code	3M™ MICROFOAM™	Minimum order
59710	1528-1	25 mm x 5 m	box of 12
59711	1528-2	50 mm x 5 m	box of 6

## **■** 3M<sup>™</sup> Transpore<sup>™</sup> white tape **■** 3M<sup>™</sup> synthetic under-cast padding



#### 3M™ TRANSPORE™ WHITE SURGICAL TAPE

Gentle tape with strong adhesion and easy, bi-directional tear for dressing applications. Hypoallergenic, breathable, easy bi-directional tear. Good initial and long-term adhesion (72 hours), easy to handle with gloves, water-resistant.

Suggested Applications: securing dressings to damp or dry skir

- taping fragile, at-risk skin

- anchoring tubes and devices when tane width must be customized

 when repeated taping is needed GIMA 3M 3M™ TRANSPORE™ WHITE TAPE code 34950 1534-0 13 mm x 9.14 m box of 24 34951 1534-1 25 mm x 9.14 m box of 12 34952 1534-2 51 mm x 9.14 m box of 6



#### 3M™ SYNTHETIC LINDER-CAST PADDING

Porous and highly conformable non-woven polyester padding. Strong, yet easy to tear - synthetic cast padding

- non-woven polyester padding which is porous, and highly conformable - easy to tear
- suitable for use with all casting materials

GIMA code	3M code	3M™ UNDER-CAST PADDING	Minimum order
59715	MW02	5 cm x 2.7 m	box of 12
59716	MW03	7.5 cm x 2.7 m	box of 12
59717	MW04	10 cm x 2.7 m	box of 12
59718	MW06	15 cm x 2.7 m	box of 12

## 100% COTTON WOOL

#### 100% COTTON WOOL

Hydrophilic 100% cotton for sanitary and cosmetic use, hygiene, exudate absorption, non-injured skin disinfection. Non-invasive Class I Medical device. Non sterile

Multilingual pack: GB, FR, IT, DE, ES, FI, GR, HR, PL, PT, RO, SE.

GIMA code	COTTON WOOL	Туре	Closing laces	Minimum order
34831	Cotton wool 100 g	Z folded	yes	box of 100 packs
34834	Cotton wool 250 g	Z folded	yes	box of 40 packs
34835	Cotton wool 500 g	Z folded	-	box of 20 packs
34838	Cotton wool 1000 g	roll	-	box of 10 packs
34839	Cotton wool 1000 g	Z folded	-	box of 10 packs



## HYDROGEN PEROXIDE



## (Hydrogen peroxide) - 250 ml

- box of 12
- 36605 OXYGENATED WATER (Hydrogen peroxide) - 1 l
- box of 12

Hydrogen peroxide (3% diluted solution) 10 volumes. Clear solution, colourless. Multilanguage label: GB, FR, IT, ES. Made in Italy.

#### CHEMICAL COMPOSITION Hydrogen peroxide: ≥3% (10 vol.) Stabilizer 0.001%

## GERMOCID TEC

• 36604 OXYGENATED WATER • 36681 GERMOCID TEC - 750 ml Foaming disinfectant cleaner for non-invasive medical devices used in tattoo studios, clinics, hospitals, beauty shops. Suitable for **sensitive** surfaces where you can't use alcohol based disinfectants. It is a safe product, it dries quickly, does not stain and leaves no streaks. Ready-to-use spray that cleans and, thanks to the synergic action of the Quaternary Ammonium Salt with Orthophenylphenol, disinfects from bacteria, yeast, fungi, moulds, TBC, viruses (including HIV, HBV and HCV), Adenovirus and Poliovirus.

• 36682 VAPORIZER - optional

ENSITIVE

SURFACE:

**( 6** 0546

#### CHEMICAL COMPOSITION

100 g of product contain: Benzalkonium Chloride; O-phenylphenol; coformulants; depurated water as needed to 100 g; Product form: Colourless liquid with citron perfume

## SEPTI SAVON

#### • 36674 SEPTI SAVON -

#### 250 ml - box of 12

36605

Septi Savon is a 5.5 pH soap with antibacterial agents that prevents and eliminates unpleasant odours. The presence of orthophenylphenol and Benzalkonium chloride guarantees a sanitizing and antibacterial action. Delicate on the skin, it can be used for total body shower and for children. Its neutral formula. enriched by glycerine, helps to maintain normal equilibrium of skin and prevents dehydration even after repeated washing.

36604



## ALCOHOL SWABSTICKS

#### • 36603 ALCOHOL SWABSTICKS - box of 16

Practical swabstick soak with isopropyl alcohol ready for use. Comes in a protected convenient breakable stick shell with dimension 75x8 mm. Safe for the nurses who does not touch directly the stick neither the alcohol. Suitable for cleaning and disinfection of minor wound care, skin cleaning and disinfection before injection, infusion and transfusion.



## DOSASOAP NO-TOUCH HAND-WASH SYSTEM • 36677 DOSASOAP NO-TOUCH HAND WASH SYSTEM - white

Dosasoap is a no-touch dispenser for antiseptics, convenient for detergents, liquid soaps and gels. Equipped with sensor that detects hand movements, it dispenses the product in a comfortable way. Dosasoap ensures a rapid and safe hand hygiene, without any contact with

the dispenser and unnecessary waste.

Suitable for using with 1 litre bottles (36671, 36672).

• 36678 PUMP FOR DOSASOAP - spare



## FUNNY CAPS - MADE IN ITALY

Wide range of patterns to meet all healthcare professionals needs. Light and comfortable, provided with adjustable laces. Available in two sizes: medium size (M), suggested for men and women with short or medium-long hair; large size (L), suggested for women with long, curly hair. 100% high quality pure cotton, highly breathable surgical caps. MD Class I

#### OTHER PATTERNS ON REQUEST

Select pattern from











• 20803 CORAL - M • 20903 CORAL - L

• 20805 BRIGHT - M • 20804 CHILDREN - M • 20904 CHILDREN - L • 20905 BRIGHT - L









20820 WAVF - M

• 20811 DAISY - M • 20812 TROPICAL - M







• 20816 MILITARY - blue - M • 20817 MILITARY - green - M • 20818 SKULL - M







20824 VETERINARY - M • 20825 DINO - M







20831 DENTAL - M

• 20832 MEDICAL - M

20833 SKFI FTON - M

26165

• 20834 CHEMICAL - M

20835 BIOLOGY - M

## SURGICAL CAPS - MADE IN ITALY

Cotton surgical patterned or green cape

- 26166 GREEN CAP
- 26165 FANTASY CAP light blue
- 26167 FANTASY CAP beige • 26168 FANTASY CAP - red
- Other colour on request. Minimum order 1,000 pieces.









## INDEX

ihealth wireless health-care product	TS <b>1-4</b>		CAUTERY & ELECTROSURGERY	181-193
DIAGNOSTIC TESTS-LABORATORY	5-14		LOUPES, VISION & ENDOSCOPY	194-198
OPERATOR'S PROTECTION	15-25		MEDICAL LIGHTS	199-206
HOLLOWARE - SURGICAL INSTRUMENTS - S	YRINGES 26-56		DIAGNOSTICS	207-256
MEDICAL BAGS	57-63		AUDIOMETRY & RESPIRATORY	257-268
SCALES & MEASURES	64-74		ECG, MONITORS & ULTRASOUND	269-294
HEALTH CARE - PATIENT AIDS	75-99		FIRST AID - PARAMEDICAL - EMERGENCY	295-347
FURNITURE	100-144		STERILIZATION	348-364
PHYSIOTHERAPY - NEBULIZERS - SUCTION P	UMPS <b>145-166</b>		VETERINARY	365-370
GYNAECOLOGY & PROCTOLOGY	167-180		HUMAN ANATOMY - MODELS	371-376
A ABBOT glucose strips	5		Clippers Clogs	42,80 24-25
ABPM monitors	4, 256		Clothes (coats, trousers)	21, 23-24
Activity trackers Aerosols - nebulizers and accessories	1 155-158, 263		Cohesive bandages Collars	238 311-312
Aids for daily living	83		Collectors, biological	45
Air compression therapy	145		Colposcope, Videocolposcope	167-168
Airways, Guedel	323, 335		Commode	87, 93
Alcohol testers	14		Condoms	80
AMBU collars, manikins, resuscitators, 307, 3 blue sensors	12, 321, 323, 325 278		Cott	314
Amniocentesis needles	172		Cotton wool, rolls, gauzes Couches	341-342 II, 131-136
Amnioscope	174		Couches rolls	134
Anatomy models	371-376		Covers for mattress	102
Ano - Procto - Rectoscopes	174		Cpap devices	268
Anti-Decubitus mattresses, cushions Armchairs	97-99 100		CPR mask Cradle	335 105
Aspirators - suction pumps	III, 159-166		Crutches	90
Audiometers and booths	257-260		Cryotherapy	193
Autoclaves	357-360		Cuffs-sphygmomanometers	243-244
Ayre Spatulae	177		Curettes Berkeley-Karman	178
D			Curettes - dermal Curettes - ear	42 222
D Backrest	102		Curtains	106, 137
Bag holder trolleys	115 57-63		Cushions	99
Bags - leather, leatherette, cordura Bandages	80, 336-340		Cutters	29, 35
Bariatric bed	109		Cylinders Cytology spray and accessories	320 178
Bathroom aids	87-88, 93		Cytology spray and accessories	170
Batteries	219 ers 52-55	D	Defibrillators and nade	204 200
BD: needles, syringes, IV catheters, waste contain Bed pads	86		Defibrillators and pads Dental Higiene	301-308 79-80
Bed pans - plastic, stainless steel	45, 50		Dental instruments	36
Beds	103-104, 109 103-104		Dermatoscope Desk - doctor	206-207
Bedside tables	103-104		Desk - doctor	139-140
Bibs Bins	22, 84 139		Diagnostic sets Diagnostic tests	212-218 5-14
Biopsy Punches	42		Diathermy and accessories	181-192
Ripolar forcens, cables	189-190		Dining table	100
Blades - laryngoscope	326-330		Disinfection - germicide	348-352
Blades - scalpel Blankets	I, 41 347		Distiller - water Donor chairs	360 127
Blood pressure monitors	2, 249-255		Dopplers: - foetal	171-172
Body bags	314		- vascular	282
Body fat analyzers	II, 67-68		Drapes	27
Bone densitometer Bracelet I.D.	168 173		Dressing - bandages	80, 343-346
Breast Pump	159		Dressing kits Drugs cabinets and trolleys	33, 38 117-118
Brushes - cleaning	350		Drug tests	13-14
Brushes - gynaecology	177		Drums	48
BSN: tapes, bandages Bulbs - nebulizers	336-340, 344 155		Dynamometer	64
Bulbs - oto/ophthalmo/laryngoscopes	210			
Burn care products	347		Ear curettes, ear speculum	219-220, 222
6			Ear irrigation system Ear plugs	221-222 80
Cabinets 112, 1	18, 129, 138-140		ECG - and accessories	269-279
Cameras	194		Ecographs, Ecocolourdoppler	283-287
Canes	89-90		EEG paste	281
Capillaroscope Capnography	206 296		Electrodepilator and accessories Electrodes for ECG	184, 187-188 277-278
Caps	22, 24		Electrodes for electrosurgery	185, 187
Cardiac marker test	12		Electrosurgery units and accessories	181-192
Cardiolab cardiovascular monitor	4		Electrotherapy units	147-148
Cardiotocograph	169-170		Emergency bags, rucksacks, cases, kits	61-63, 331-334
Carts Catheters	111, 113-124 192 43, 53		Endometrial cannulas Endoscopy	178 194
Cautery	192		Endotracheal tubes	324
Centrifuges	9-10		ENT chairs and cabinets	128
Chairs 87, 125-1	30, 139, 142, 318		ENT head mirrors	196
Cholesterol monitor and strips Cleaning solutions	6-7 84, 348-352		ENT illumination ENT stainless steel instruments	222-223 34
Cicaring solutions	04, 340-332		Livi Stanness steel histi unients	34

	ERKA stethoscopes, sphygmomanometers ETHICON sutures	234, 244, 246, 249
	Exercise bands, tubings, mats	153-154
	Extrication kits	314
	Eye wash system	333
_	,	
F	Face masks	17-18
	Faeces containers	45
	Feeding tubes	43
	Fibre optics - cables/adaptors	195
	Files	35
	Filters: aspiraotrs, spirometers	161-166, 261
	Finger cots	20 54
	Fingerguard Fire blankets	347
	First Aid Cases/Bags/Rucksacs	58-63
	Flowmeters	320
	Foetal monitors	169-170
	Foley catheters	43
	Foot stools	140
	Forceps - instruments 26,29, Forceps - electrosurgery	31-34,36-38,173-174 190-191
	Forceps - electrosurgery	150-151
G		
G	dag	84
	Gallipots	46,49
	Gauze, gauze pads Gel: antibacterial	80, 341-342 348
	Gel: lubricant	43, 176 281
	Gel: ultrasound, ECG, cosmetic,	281
	Germicidal ultraviolet light	357
	Gloves: copolymer, cotton, latex, nitrile, vinyl,	, holder 19-20
	Glucose Monitor and strips	3, 5-7
	Goggles Goniometers	15-16 65
	Gowns: non-woven, polythene, cotton	21, 23
	Grab bars	88
	Grasping tools	83
	Grounding pads	189
	Guedel airways	323
	Gynaecological beds/chairs Gynaecology - disposables/tests/sets	125-127 173-180
	dynaecology - disposables/tests/sets	1/3-100
ш		
п	Hammers	225
	Hand towels	22 188
	Handles for electrosurgery Hanger - coats	139-140
	Head immobilizers	316
	Head lights, head loupes, head mirrors	195-198
	Heat: Heating pads, hot-cold gel	84
	Heel protector	99
	Height measures	66
		7,209, 211, 214, 220 247
	sphygmomanometer laryngoscopes	329
	Hemoglobin measures	7-8
	Histofreezer	193
	Holloware plastic/stainless steel/disposable	46, 48-50 256, 276-278
	Holter: blood pressure monitoring, ECG	256, 276-278
	Hot air sterilizers	355-356
	Hot water bottles Humidifier	84 155
	Hypotermic blanket	347
	Hysterography cups	173
	Hysterometer	178
1	Ice pack/spray, bags	84, 347
-	iHealth wireless healthcare products	04, 347 1-4
	Incontinence pads	86
	Infrared therapy lamps	150
	Infusion cuffs	309
	Infusion pumps	310
	Infusion sets	54 155
	Inhaler Insect repellent devices	79
	Instruments - stainless steel/tungsten	29-36
	Instruments - sterile	37
	Instruments kits: delivery, dressing, suture	33
	Invalid rings	100
	Ionophoretic generator	150
	Irrigation devices Irrigation solutions	221-222 349
	Ishihara test	228
	Isothermic cover	347
	IUKO telescopes, projector	198
	IV catheters	53
	IV stands	105
1		
J	Jackets: non-woven, cotton-polyester	20, 23

K	KAI: biopsy punches and dermal curettes Kidney dishes/trays	42 46, 49-50
ī		
ь.	Lactate scout	8
	LAERDAL training manikins	II 150, 199-206
	Lamps Lancets	150, 199-200
	Lang stereotest	228
	Laryngeal masks	325
	Laryngeal mirrors	34
	Laryngoscopes Laser therapy	194, 326-330 146
	Laundry trolleys	115
	Lice comb and shampoo	79
	Lifters	101
	Light boxes Lights: examination, magnifying, theatre	143-144 199-206
	Light sources	195-200
	Limb clamps	227
	LITTMANN stethoscopes	235-238
	Loupes - magnifying	196-198
	Lung exercise devices	262
R/	l	
IV	Magnetotherapy unit	149-150
	Magnifying lights Manikins-training	205
	Masks - face protection	II, 307 17-18
	Massage beds and chairs	135-136
	Mat: absorbent, anti slip	18
	Mat: decontamination	352
	Mattress: antidecubitus	97-99
	Mattress, covers, pillows Mattress: physiotherapy	102, 149 149, 153
	Mattress - vacuum	314
	Mayo tables	114
	Measuring mat	66
	Medication products	80, 341-346
	Mesotherapy Micro-hematocrit centrifuge	53 10
	MICROLIFE B.P. monitors	254
	MICROPORE	344
	Microscopes	193, 206-207 273, 283-284, 298
	MINDRAY ECG, ultrasound, pulsoximetry Mirrors ENT	273, 283-284, 298 196
	Mirrors larynge	34
	Mitten	84
	Models - teaching	371-376
	Monitor multiparameter and accessories	288-294 225
	Monofilament Monopolar forceps, scissors, cables, handles	188, 191
	Mouthpieces - spirometry	261
	Mouthpieces - spirometry Multicare "in" device and strips	6
N	Nail: scissors, cutters, files	35, 80
	Napkins	22
	Nasal speculum	223
	Nebulizers and accessories	155-158 54
	Needle destroyer Needle holders	29,31,35,37-38
	Needles	51-54
	NONIN: pulse-oximeters	294,300 194
	Nosepharyngoscope	
	Nystagmus spectacles, videonystagmoscope	226
U	Occluders	227
	Office furniture OMRON: B.P. monitors, scale	137-142
	Ophthalmoscopes	II, 67, 69, 245, 253 209-218
	Optical tests	227-228 143-144, 227
	Optometric charts	143-144, 227
	Orthopedic products	311-313
	Otoscillo irrigation device Otoscopes and accessories	221 208-220
	Oximeters	296-300
	Oxygen concentrators	296-300 319
	Oxygen cylinders and accessories	320
В		
P	Pads for defibrillators	304
	Pap devices	268
	Paper ECG, videoprinter Paper products	279-280 22, 134
	Paper products Papettes	22, 134 177
	Pap Test	177 176
	PARAGON blades and scalpels	41
	Patient trolleys Peak flow meters	107-108 262
	Pedal exercisers	92
	Pediatric tables, beds, cradles	105

	Pen-lights Pen-lights	217, 224
	Percussors	217, 224
	Perforator, membrane	173
	Possarios: rubbor silicono	180
	Pessaries: rubber, silicone	153-154
	Physiotherapy Pill cutters/crushers/boxes	153-154 81-82
	Pill cutters/crushers/boxes	
	Pillows	99, 102
	Pipettes	46
	Plasters	80, 343-346
	Plates for electrosurgery	189
	Pneumatic tourniquets	309
	Pocket masks	335
	Podiatry instruments and kits	35
	Podology	35, 64, 129
	Podoscope	64
	Posture englisers	
	Posture analyzers	64
	Pouches for sterilisation	363
	Pregnancy tests	179
	Pressure reducers	320
	Printers	280
	Probe covers - latex	172
	Proctoscopes	174, 176
	PT/INR coagulation monitoring system	7
	Pulse Oximeters and sensors	III, 1, 294-300
5		
3	Razors	42
	Record holders	102
	Rectoscope	174
	Refrigerator bags	58-59
	Removal kits	38
	Respiratory	261-268
	Resuscitators and accessories	321-324
		321-324
	Retinoscope	212
	Retractors	35
	RIESTER oto-ophthalmo, stethoscopes	213, 216, 233
	sphygmomanometers, infusion cuffs 244, 2	45, 248-249, 309
	Rollators	91, 92
	Rolls for sterilization	363
7		
>	Salpingograph - Schultze	172
	Saw for plaster	340
	Scales - baby/adult/vet	3, 67-74, 366
	Scalpels - disposable or stainless steel	I, 31, 41
	Scalps vein	1, 31, 41
	Science 26 20 21 22 25 27	51
	Scissors 26, 30-31, 33-35, 37-	38, 80, 191, 335
	Scissors 26, 30-31, 33-35, 37- Scoliometer	38, 80, 191, 335 64
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs	38, 80, 191, 335 64 350
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders	38, 80, 191, 335 64 350 361-362
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers	38, 80, 191, 335 64 350 361-362
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders Seals cacles, measurers Sensors for oximeters	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 16 22
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 16 22 87, 101
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O.	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 87, 101
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Sigmoidoscopes F.O. Silcone tubes	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 87, 101 174
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 16 22 87, 101 174 159 268
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 16 22 87, 101 174 159 268 178
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 174 159 268 174-376
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 16 22 87, 101 174 159 268 178 374-376
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silcen appea Slides Skietons, spinal columms ad skulls Skin staple removers Skinfold calipiers	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 174 159 268 374-376 39
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silcen appea Slides Skietons, spinal columms ad skulls Skin staple removers Skinfold calipiers	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 22 87, 101 174 159 268 178 374-376 40
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skieletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin Markers Smoke evacuator	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 174 159 268 374-376 39 67 40 191
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skieletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin Markers Smoke evacuator	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 22 87, 101 174 159 268 178 374-376 40 191 84, 348
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone scilicone scilicone scilicone Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Socks	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 171 159 268 374-376 40 191 84, 348 85-86
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Sigmoidoscopes F.O. Silcone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Socks	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 22 87, 101 174 159 268 178 374-376 40 191 84, 348 85-86
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Sigmoidoscopes F.O. Silcone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Socks	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 1011 174 159 268 374-376 40 191 84, 348 85-86 168 85-86
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Sigmoidoscopes F.O. Silcone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Socks	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 1011 174 159 268 374-376 40 191 84, 348 85-86 168 85-86
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Sigmoidoscopes F.O. Silcone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Socks	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 1011 174 159 268 374-376 40 191 84, 348 85-86 168 85-86
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Sooks Sonost - ultrasound bone densitometer Specula - ear - nasal Specula - vaginal	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 55-56, 60 22 87, 101 174 159 268 374-376 40 99 67 40 191 84, 348 85-86 1688 85-86 1688 85-86 1688 219-220, 223
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Spetyman and accessories	38, 80, 191, 335 64 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 174 159 268 374-376 40 191 84, 348 85-86 167, 280 219-220, 223 175 239-255
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Spetyman and accessories	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 174 159 268 374-376 47 49 49 191 84, 348 85-86 168 178 219-220, 223 239-255 261-268
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - vaginal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - epuipment Spirometry - paper, mouthpieces, filters, turbines	38, 80, 191, 335 64 63 636 361-360 361-362 293, 295 55-56, 60 112 166 167 174 159 2688 178 374-376 40 191 84, 348 85-86 168, 219-220, 2219-222 219-220, 2219-225 261-268 261
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columns ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Sooks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Solinters	38, 80, 191, 335 64 63 636 361-360 361-362 293, 295 55-56, 60 112 166 167 174 159 2688 178 374-376 40 191 84, 348 85-86 168, 219-220, 2219-222 219-220, 2219-225 261-268 261
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone tubes Sleep apnea Sikeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - epuipment Spirometry - paper, mouthpieces, filters, turbines Splints - alluminium/air/nylon	38, 80, 191, 335 64 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 171 179 268 374-376 40 191 84, 348 85-86 168 167, 280 219-220, 223 175 239-255 261-268 261 79, 333 313-314
	Scissors 26, 30-31, 33-35, 37- Scollometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone tubes Sleep apnea Sikeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - epuipment Spirometry - paper, mouthpieces, filters, turbines Splints - alluminium/air/nylon	38, 80, 191, 335 64 361-362 66, 70-71, 73 293, 295 55-56, 60 162 22 87, 101 174 159 268 178 374-376 40 91 191 84, 348 85-86 1688 219-220, 223 239-255 261-268 261 79, 333 313-314 292-205
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone tubes Sleep apnea Silicone tubes Skeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SOMY: papers, printers Specula - ear - nasal Specula - vaginal Specula - vaginal Spirometry - equipment Spirometry - epuipment Spirometry - paper, mouthpieces, filters, turbines Spiinters Splints - aluminium/air/nylon SpO, sensors Spoñoges	38, 80, 191, 335 64 64 65 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 174 159 268 178 374-376 40 191 84, 348 85-86 168 85-86 168 85-86 179 20 219-220, 223 219-220, 223 219-230, 233 313-314 293-295 88-84
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone tubes Sleep apnea Silicone tubes Skeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SOMY: papers, printers Specula - ear - nasal Specula - vaginal Specula - vaginal Spirometry - equipment Spirometry - epuipment Spirometry - paper, mouthpieces, filters, turbines Spiinters Splints - aluminium/air/nylon SpO, sensors Spoñoges	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 1122 87, 101 174 159 268 374-376 374-376 47 491 184, 348 85-86 168, 82 19-220, 223 239-255 261-268 261-268 79, 333 313-314 293-295 83-84 178
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone stubes Sleep apnea Silicone stubes Skin staple removers Skin staple removers Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spiriometry - equipment Spiriometry - paper, mouthpieces, filters, turbines Splints - aluminium/air/nylon SpO, sensors Sponges Spray for citology fixation Stainless steel instruments/holloware	38, 80, 191, 335 64 64 64 65 66, 70-71, 73 293, 295 55-56, 60 55-56, 60 62 287, 101 174 159 268 178 374-376 40 191 84, 348 85-86 168 88, 86 167, 280 219-220, 223 225 261-268 219, 239-255 261-268 219, 239-255 261-288 219-240, 248 219-240, 2
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone tubes Sleep apnea Silicone stubes Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - ear in assal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spiliters Spiliters Spiliters Spiliters Spiliters Spiliters Spiliters steel instruments/holloware STERI STRIP	38, 80, 191, 335 64 64 65 66 67 67 67 67 67 67 67 67 67 67 67 67
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone stubes Sleep apnea Silicone stubes Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spiriometry - equipment Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Splints - aluminium/air/nylon SpO, sensors Sponges Spray for citology fixation Stainless steel instruments/holloware STERI STRIP	38, 80, 191, 335 64 64 65 66 67 67 67 67 67 67 67 67 67 67 67 67
	Scissors Scisions Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columns ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sons t ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Splinters Splinters Splinters Splinters Splinters Splinters Splinters splints - aluminium/air/nylon SpO, sensors Sponges Spray for citology fixation Stainless steel instruments/holloware STERI STRIP Sterilization boxes - containers	38, 80, 191, 335 64 64 65 66 67 67 67 67 67 67 67 67 67 67 67 67
	Scissors Scisions Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columns ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sons t ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Splinters Splinters Splinters Splinters Splinters Splinters Splinters splints - aluminium/air/nylon SpO, sensors Sponges Spray for citology fixation Stainless steel instruments/holloware STERI STRIP Sterilization boxes - containers	38, 80, 191, 335 64 64 65 66 67 67 67 67 67 67 67 67 67 67 67 67
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Sealings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Splinters Splinters Spinters Sponges Spray for citology fixation Stainless steel instruments/holloware STERI STRIP Sterilization boxes - containers Sterilization test and tapes	38, 80, 191, 335 64 64 65 66 67 67 67 67 67 67 67 67 67 67 67 67
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Silicone tubes Sleep apnea Silicone stubes Skeletons, spinal columms ad skulls Skeletons, spinal columms ad skulls Skeletons, spinal columms ac skulls Skeletons, spinal columms ac skulls Skeletons, spinal columms and skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY; papers, printers Specula - ear - nasal Specula - vaginal Specula - vagi	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 2 2 2 87, 101 174 159 268 374-376 40 191 84, 348 85-86 168 167, 280 219-220, 223 219-220, 223 313-314 293-295 83-84 47, 351 361-362, 364 375-374, 48-50 47, 351 361-362, 364
	Scissors Scisions Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sealings/thermowelders SECA scales, measurers Senors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Splinters Splin	38, 80, 191, 335 64 3150 361-362 66, 70-71, 73 293, 295 55-56, 60 16 22 87, 101 174 159 268 178 374-376 47 40 191 84, 348 85-86 168 85-86 167, 280 219-220, 223 233 313-314 293-295 87, 297 238 2737 48-50 345 345 345 341-362, 344 345 345 345-355-356 1, 172, 229-238
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slices apnea Slices apnea Slices skeletons, spinal columms ad skulls Skeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Specula - vaginal Specula - vaginal Specula - vaginal Specula - yaginal Specula	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 87, 101 174 159 268 374-376 47 374-376 49 191 184, 348 88-86 168 219-220, 223 2175 221-228 239-255 261-268 219-239, 255 261-268 47, 351 373-314 293-294 47, 351 361-362, 364 355-356 1, 172, 229-238 88-90
	Scissors Scisions Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columns ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin farshe removers Soap Sooks Sonost - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - vaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Splinters Splinters Splinters Splinters Sponges Sponges Spray for citology fixation Stainless steel instruments/holloware STERI STRIP Sterilization boxes - containers Sterilization test and tapes Sterilization test and tapes Sterilization test and tapes Sterilization sterilizatio	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 162 22 87, 101 174 159 268 374-376 374-376 47 493 291 292 292 219-220, 223 217 239-255 261-268 261 79, 333 313-314 293-295 83-84 47, 351 361-362, 364 47, 351 361-362, 364 88-88 87, 125, 129-239
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY; papers, printers Specula - ear - nasal Specula - vaginal Specula - vagin	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 87, 101 174 159 268 374-376 40 191 184, 348 85-86 167, 280 219-220, 223 175 221-220, 223 175 239-255 261-268 219-270, 223 175 239-255 261-268 179, 333 313-314 293-294 178 27-37, 48-50 178 27-37 28-38 28-3
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columns ad skulls Skin staple removers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Soots - ultrasound bone densitometer SONY: papers, printers Specula - ear - nasal Specula - ear - nasal Specula - eaginal Sphygmomanometers and accessories Spirometry - equipment Spirometry - paper, mouthpieces, filters, turbines Splinters Splinters Splinters Splinters Spol, sensors Sponges Spray for citology fixation Stainless steel instruments/holloware STERI STRIP Sterilization test and tapes Sterilization test and tapes Sterilization boxes - containers Sterilization test and tapes Sterilization test and tapes Sterilization test and tapes Sterilizers - dry heat Stethoscopes and accessories Sticks Stockings Stools Strep-A rapid test	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 87, 101 174 159 268 374-376 47 47 491 84, 348 85-86 167, 188 219-220, 223 333 313-314 293-295 38-84 47, 351 361-362, 364 1712, 229-238 86 87, 125, 1172, 129-238
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slices apnea Slices spinal columms ad skulls Skeletons, spinal columms ad skulls Skeletons, spinal columms ad skulls Skeletons, spinal columms and skulls Skeletons, spinal columms and skulls Skeletons, spinal columms and skulls Skeletons, spinal columms ad skulls Skeletons, spinal columns ad skulls Skeletons, s	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 87, 101 174 159 268 374-376 47 47 491 84, 348 85-86 167, 188 219-220, 223 333 313-314 293-295 38-84 47, 351 361-362, 364 1712, 229-238 86 87, 125, 1172, 129-238
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slides Skeletons, spinal columms ad skulls Skin staple removers Skinfold calipers Skin fold calipers Skin fold calipers Skin Markers Smoke evacuator Soap Socks Sonost - ultrasound bone densitometer SONY; papers, printers Specula - ear - nasal Specula - vaginal Specula - vagin	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 1122 87, 101 174 159 268 178 374-376 47 40 191 184, 348 8-5-86 167, 280 219-220, 223 33 313-314 293-295 38-84 178 27-37, 48-50 361-362, 354 47, 351 361-362, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-255 1, 172, 239-258 1, 172, 239-285 1, 172, 172, 173, 173, 173, 173, 174, 174, 174, 174, 174, 174, 174, 174
	Scissors 26, 30-31, 33-35, 37- Scoliometer Scrubs Scalings/thermowelders SECA scales, measurers Sensors for oximeters Sharps bins Shelving system Shields protective Shoe covers Shower chairs, mattress, trolleys Sigmoidoscopes F.O. Silicone tubes Sleep apnea Slices apnea Slices spinal columms ad skulls Skeletons, spinal columms ad skulls Skeletons, spinal columms ad skulls Skeletons, spinal columms and skulls Skeletons, spinal columms and skulls Skeletons, spinal columms and skulls Skeletons, spinal columms ad skulls Skeletons, spinal columns ad skulls Skeletons, s	38, 80, 191, 335 64 350 361-362 66, 70-71, 73 293, 295 55-56, 60 112 22 87, 101 174 159 268 374-376 40 191 184, 348 85-86 167, 280 219-220, 223 175 221-220, 223 175 239-255 261-268 219-270, 223 175 239-255 261-268 179, 333 313-314 293-294 178 27-37, 48-50 178 27-37 28-38 28-3

	Surgical instruments	29-34, 37-41
	SURGILANCE safety lancets Sutures	5 38-40, 345
	Swabs - cotton	177-341
	SWANN-MORTON blades and scalpels	_ I
	Syringe pumps Syringes	310 51-53, 221
_	Syringes	31 33, 221
Т	3M stethoscopes	235-238,
_	dressing	337, 342, 344-346
	Red Dot electrodes	278
	electrosurgery pads, staple remover Tables - theatre	39,189 110-111
	- treatment	131-136
	Tape dressing	343-344
	Tape height measures	261 264
	Tape indicators steam Tape kinesiology	361, 364 336
	Tecar therapy	146
	TEGADERM	346
	Tens - nerve stimulator Test tubes	151-152 46
	Tosts alcohol drug	13-14
	Tests - gynaecology	179-180
	Tests - influenza, ŠtrepA, mononucleosis, D-Din allergy, microalbumin, helicobacter pylor	ner, CRP,
	prostate, malaria, FOB, colon disease	ı, 11-12
	Tests - urine	9
	Thermal recording paper	169, 279-280, 302
	Thermic pads, bottles, bags, devices Thermo feel	58-60 225
	Thermometers	75-78
	Throat scope - illuminator	223
	Toilet aids	88, 93
	Tongue depressors Tonometer Schiotz	223 228
	Torches	224
	Tourniquets	56, 309
	Towels	22 196
	Transformer AC/DC Travel enema	176
	TRAVELJOHN urine and vomit bag	44
	Trays ISO format	111
	Treatment couches Trolleys 101, 107	135-136 111-124, 140-1
	Trousers	21, 23-24
	Tungsten carbide instruments	29-30
	Tuning Forks	226
	Tympanometer and eartips Two points discriminator	257-258 225
U	Ultrasonic cleaners	353-354
	Ultrasonic nebulizers	156
	Ultrasonic therapy units	147-148
	Ultrasound dopplers Ultrasound therapy	283-286 147-148
	Ultraviolet lamps	206
	Umbilical clamps	173
	Urine analyser and strips Urine bags	9-10 44
	Urine containers	44
V	Vaccine carrier	58
_	Ventilators	IV
	Veterinary equipment and instruments	365-370
	Videonystagmoscope Videoprinter paper	226 280
	Videotoscope, videodermatoscope, dentalscope	
	Visors	16
	Vital signs monitors	288-293 44
	Vomit bag	44
X	X-ray viewers	442.444
/\	A-ray viewers	143-144
١٨	Walking frames, sticks, crutches	89-91
W 1	Wall units	123
	Ward screens	106, 137
	Wash basin pump	123
	Waste containers	139
	Watches WC, portable	26 44
	Wheelchairs	93-96
	Wing screens	137
	Wipes Wood James	22, 349
	Wood lamps Worktops	206 124
	Woundcare	344-346

#### NEW PRODUCTS

## SWANN-MORTON DISPOSABLE BLADES, SCALPELS AND STITCH CUTTERS

## SWANN-MORTON DISPOSABLE BLADES AND SCALPELS

Swann-Morton blades and scalpels are renowned their exceptional quality, precision, consistency and reliability. Swann-Morton manufactures in the UK using high quality



Plastic handle scalpels with stainless steel blades, individually packed in sterilized envelope in box of 10 pcs.
Multilanguage box: GB, FR, IT, ES, DE, DK, NL, GR, PT, PL, FI, RU, NO, SE.

code	SWANN-MORTON SCALPELS WITH STAINLESS STEEL BLADE	Minimum order
22430	Disposable scalpels - blade 10 - sterile	box of 10
22431	Disposable scalpels - blade 11 - sterile	box of 10
22432	Disposable scalpels - blade 12 - sterile	box of 10
22433	Disposable scalpels - blade 15 - sterile	box of 10
22435	Disposable scalpels - blade 20 - sterile	box of 10
22436	Disposable scalpels - blade 21 - sterile	box of 10
22437	Disposable scalpels - blade 22 - sterile	box of 10
22438	Disposable scalpels - blade 23 - sterile	box of 10
22439	Disposable scalpels - blade 24 - sterile	box of 10

2	2403		THITTED INGLAND
	GIMA code	SWANN-MORTON S/S HANDLES	Compatibility
		Graduated S/S n° 3 handle Graduated S/S n° 4 handle	


steel that gives exceptional cutting performance. They operate stringent quality control procedures which ensure unrivalled blade consistency and reliability. This is why Swann-Morton is the preferred choice of many medical professionals worldwide



Carbon steel blades individually packed in metal foil and box of 100.



# OCLOURED TRAD STETHOSCOPES



#### COLOURED TRAD STETHOSCOPES

Coloured aluminium stethoscopes, lightweight and reliable. Chestpiece diaphragm Ø 43.5 mm, bell Ø 30 mm external sizes. Brass binaural.

Tubing: length 62 cm, int. Ø 4 mm, ext. Ø 8 mm. Supplied in cardboard box.

Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.



GIMA code	COLOURED TRAD STETHOSCOPES - LATEX FREE
51000	TRAD single head - black
51001	TRAD single head - red
51002	TRAD single head - blue
51003	TRAD single head - yellow
51004	TRAD single head - green
51010	TRAD double head - black
51011	TRAD double head - red
51012	TRAD double head - blue



- 44450 VALUE EXAMINATION COUCH white painted black
- 44451 VALUE EXAMINATION COUCH white painted white
- 44455 VALUE EXAMINATION COUCH chrome blue
- 44456 VALUE EXAMINATION COUCH chrome beige Suitable for medical practices or small surgeries.

Easy to assemble. Multilanguage manual (GB, FR, IT, ES). Comes complete with mattress.

Top is made with wooden panel and foam rubber and covered

with washable simulated leather Class 1.

Two sections: one fixed 130x61xh 5.5 cm and one adjustable (backrest) 50x61xh 5.5 cm

Couch size: 180x61x h 75 cm. Weight 29 kg.

Maximum load: 100 kg.

Delivered in kit form. Made in Italy.

• 27418 COUCH ROLL HOLDER - optional

STOOLS: see at page 141

## LAERDAL LITTLE FAMILY PACK

#### • 56511 LAERDAL LITTLE FAMILY PACK - 125-01050

All-in-one, realistic and inexpertive quality training. A little family with a focus on quality CPR. The Little Family Pack provides quality CPR training at an affordable price. Designed to reflect the realistic anatomical differences among an adult, a child and an infant. It comes complete with:

mat, 2 faces, 2 airways, 6 manikin wipes). Little Junior Manikin (manikin, training mat, Baby Anne 2 faces, 2 airways, manikin wipes), Baby Anne (manikin, training mat, 6 airways, 10 foreign body practice objects) and a large bag on wheels to carry them.

• 56510 LAERDAL LITTLE ANNE - 120-01050



## **56511** (3 manikins)

## LAERDAL RESUSCI ANNE

• 56520 LAERDAL RESUSCI ANNE FIRST AID FULL BODY - 170-01250 • 56522 LAERDAL RESUSCI ANNE QCPR FULL BODY - 171-01250

The Resusci Anne manikins offer optimal realism for basic adult CPR training.

Resusci Anne QCPR allows multiple feed back options that provide opportunity to focus on learner competency:

- measures CPR performance
- assess the results of the performance
- facilitate good feed back to the instructor

Supplied with full body manikin (foam legs), 3 decorated resusci manikin faces, 2 disposable airways,

trolley suitcase, kneel mat,

jacket, pants, 50 resusci manikin wipes, user guide, Skill guide (only 56522), USB cables (only 56522)

## **BODY COMPOSITION MONITOR**

## BODY FAT MONITOR

#### 27092 OMRON BF212 BODY COMPOSITION MONITOR Measures and displays the following body composition parameters: body weight, body fat (in %) and Body Mass Index (BMI). The 4-sensor technology provides clinically validated body measurements.

It measures the body fat percentage by Bioelectrical impedance (Bi)



27092

• 27093 OMRON NBF-306 BODY FAT MONITOR

Measures body fat percentage, Basal Metabolic Rate (BMR). assessment of body fat percentage and Body Mass Index (BMI) with graphical interpretation of body type.

The body fat percentage is measured based on the electric resistance and the personal data.

The measured results are displayed approximately 7 seconds

after setting data. Display € 0197 Easy to read large digital and graphic displays: the measured results based on body fat percentage, BMR and BMI calculations are displayed, as well as their interpretations and body fat percentage assessment Grip electrodes

Memory Memory can store personal data (height, weight, age and gender) of up to 9 people simultaneously

Extremely weak electric current is applied from here during measurement

27093

Ш

56520.

Skill guide

## **OXY 2 PULSE-OXIMETER**

#### • 35072 OXY 2 PULSE OXIMETER

Pulse Oximeter for measuring pulse oxygen saturation and pulse rate through finger.

Suitable for domiciliar and professional use in family, hospital, oxygen bar, community healthcare, physical care in sports. It can be used before or after sports, but not recommended throughout.

#### **TECHNICAL SPECIFICATIONS**

Display mode: LED display SpO, measuring range: 0 - 100%, (resolution 1%)

Accuracy: 70 - 100%: ± 2%, below 70% unspecified PR measuring range: 30 - 250 bpm, (resolution 1 bpm)

Accuracy: ± 2 bpm or ± 2% (select larger)

Measurement performance in weak filling condition: SpQ, and pulse rate can be shown correctly when pulse-filling ratio is 0.4%. SpO<sub>2</sub> error is ± 4%, pulse rate

error is ±2 bpm or ±2% (select larger)

Power consumption: less than 25 mA Voltage: DC 2.6 V - 3.6 V

Battery working hour: two batteries can work continually for 24 hours

Safety Type: Interior Battery, BF Type

Dimension - weight: 60x30.5xh 32.5 mm - 50 g including two batteries

- SpO<sub>2</sub> value display

- pulse rate value display, bar graph display

low-voltage indicator

- automatical power off the unit will automatically switch off within 5 seconds if the finger falls out of probe



# ASPEED 3.0 PROFESSIONAL SINGLE PUMP ASPIRATOR

#### • 28279 ASPEED 3.0 ASPIRATOR 15 I/min

Portable, compact reliable aspirator ideal for small surgery. Piston type continuous cycle electric medical device. High vacuum low flow. It requires no maintenance or lubrification. Made in Italy.
STANDARD ACCESSORIES

Autoclavable policarbonate jar 1,000 cc with safety valve (overflow protection) Disposable suction liner 1 l

99% Antibacterial hydrophobic filte

Sterile disposable cannula

Sterile manual flow regulator

Set of atoxic sterilizable silicone tubes

Power Cable User Manual GB, FR, IT, DE, ES

#### TECHNICAL SPECIFICATIONS

Operating voltage 230 V - 50 Hz max 140 VA Power consumption Bottle capacity:

low flow High vacuum Air flow: 0÷ -0.85 bar (0÷ -85 kPa) Adjustable vacuum level:

300x170xh 160 mm Size: Weight: Noise level: 60 dRA Operating cycle: continuously

28279 GIMA ACCESSORIES AND SPARES FOR ASPEED

28255 Hydrophobic 99% bacterial filter 28258 Autoclavable jar 11 with cover

28259 Disposable suction liner 25480 Silicone tube 6x12 mm - roll of 30 m

28254 Adaptor to connect catheter to silicone tube

## VEGA PLUS PROFESSIONAL SUCTION ASPIRATOR

#### 28170 VEGA PLUS SUCTION ASPIRATOR 40 I/min

Professional aspirator for hospital use: tracheotomy, small surgery and post-operatory treatments. Silent, high-flow and maintenance-free pump allow long product life and durability. Recommended for nasal aspiration, oral aspiration, tracheal aspiration of body liquids (mucus, catarrh or blood) in adults or children. For use with 1 or 2 jars. Made in Italy.

#### STANDARD ACCESSORIES

Autoclavable jar (1 l) with overflow valve system Antibacterial and hydrophobic filter Set of silicone tubes 6x10 mm Suction catheter CH20

Conical connector for probes Power cable (Schuko)

5 languages user manual (GB, FR, IT, DE, ES)





Operating voltage

Bottle capacity:

Air flow:

Class - Type

Size:

Power consumption



#### GIMA **ACCESSORIES AND SPARES FOR VEGA PLUS** code

28229 Hydrophobic, 99% antibacterial filter 28226 | 121°C autoclavable jar 1 | with cover and overflow system

Cover and overflow valve system for 28226 28185 | 134°C autoclavable jar 1 | with cover and overflow system

Cover and overflow valve system for 28185 28271 Disposable liner 1 I (cover + bag)

28270 Container for disposable liner 1 28171 Holder for second autoclavable iar (28226)

28172 Holder for disposable liner (28271)

#### TECHNICAL SPECIFICATIONS

220-230 V - 50/60 Hz

40 l/min - 0.80 bar

Max suction: Weight: 3.6 kg Operating cycle continuous II - BF

# SPENCER 170 AND 190 NXT ELECTRONIC VENTILATORS • 34006 SPENCER 170 NXT ELECTRONIC VENTILATOR • place and shape of adjustment knobs make the setting of

- 34007 SPENCER 170 NXT KOMPAK ELECTRONIC VENTILATOR
- 34009 SPENCER 190 NXT ELECTRONIC VENTILATOR Electronic lung ventilators for non invasive ventilation of adult and pediatric patients
- protection against accidental activation of the AIR mix selection lever
- colour coded manometer for easy identification of pressure ranges
- positioning of input and output ports on the side of the device, make connecting and disconnecting easier and offer greater protection to the elements connected to the device - control knobs on high contrast background for a better identification of the set values

- compact, lightweight aluminium frame						
TECHNICAL SPECIFICATIONS	34006-7	34009				
Drive:		ronic ———				
Frequency:	from 5 to					
Alarms:	High pressure	High pressure Low pressure				
	1	Apnea				
	Pneumatic supply	Pneumatic supply				
	Pneumatic supply Low battery	Low battery				
Flow:	2 to 20	) l/min ———				
I/E Ratio:	1:2	1:2				
Oxygen concentration: Trigger	← 60% or 100% P	atented system→ from -12 to -2 mbar				
Overpressure valve:	20-60 cm H <sub>2</sub> C					
Battery operating time:	Approx.	3 hours				
Manometer scale:	-20 to +8	80 mbar ———				
IP protection:	IP24	IP24				
Non re-breathing valve:	60 cm					
Pneumatic supply: Pneumatic connection:	UNI Trom 280 t					
External source:	12 V	DC——				
	on request AC/DC adap	ter 100-240 V, 50/60 H				
Internal source:	— Rechargeable	Ni-Mh battery —				
Dimensions:	270x177x210 mm					
Weight: Structure:	3.5 kg Aluminium, st	3.6 kg				
		ieei, Diass, PE				
STANDAR	D ACCESSORIES					

Patient circuit (corrugated tubing with non re-breathing valve) Power cable Adult face-mask Oxygen tube Rattery Manual: GB, IT, on request FR, ES, DE, PT UNI adaptor

parameters easier in all operative conditions

- constant I/E ratio
- alarms for ventilation monitoring and device management Ventilator 190 NXT also features:
- led bar for breath monitoring
- three ventilation modes (only one for 34006-7)
- CMV: mandatory inflation is initiated according to the set parameters TVM: inflation initiated according to the set parameters only if triggered by the patient
- A/CV: inflation is assured to be initiated at intervals determined by the set rate, unless initiated by an earlier patient trigger event. Made in Italy.

Kompak ventilator with transport case.

Transport case containing ventilator, oxygen cylinder with pressure regulator ready to use. • 34035 CORRUGATED

PVC TUBE - 117 cm • 34036 PATIENT CIRCUIT (valve+corrugated tube)

• 34037 BATTERY - spare 34006



SPENCER



## SPENCER 118 NXT PNEUMATIC LUNG VENTILATOR

• 34016 SPENCER 118 NXT AUTOMATIC VENTILATOR

 34017 SPENCER 118 NXT KOMPAK AUTOMATIC VENTILATOR Pneumatic lung ventilator for non-invasive ventilation of adult and pediatric patients. The pneumatic mode of operation allows a significant reduction of maintenance costs associated with the requirements of electrical safety regulations. Total absence of electrical shock risks generated by the device. Protections against accidental activation of power and AIR MIX levers. Colour coded manovacuometer for an immediate display of the pressure in the patient circuit. Lateral positioning of the medical gas input and output, makes the connection and disconnection easier and offers greater protection for the elements connected to the device. Adjustment knobs on high-contrast background allows a better identification of settings, Small, lightweight aluminium body, Positioning and shape of the adjustment knobs facilitate the setting of the ventilation parameters in all operating conditions. The nonconstant I/E ratio makes the management of the ventilation more versatile. The presence of one ventilation mode makes it simple and easy to operate. Equipped with alarms required by the EN 794-3 standard.

Class IIb Med. Device according to Dir. 93/42/CEE. Made in Italy. Kompak ventilator with transport case.

Transport case containing ventilator, oxygen cylinder with pressure regulator ready to use.

- 34035 CORRUGATED PVC TUBE 117 cm
- 34036 PATIENT CIRCUIT (valve+corrugated tube)

Patient circuit (corrugated tubing with non re-breathing valve) Oxygen tube 100 cm - UNI adaptor Pressure reducer (34017 only)



100% pneumatic Controlled (VC - CMV) Ventilation mode Respiration frequency 10 to 70 breaths/mir Inspiratory-expiratory phase time I:E 1:2.0 ±0.3 at 10 bpm - 1:1.5 ±0.3 at 70 bpm

Frequency: 10 to 70 bpm 2 to 20 l/min adjustable Oxygen concentration From 60 or 100% From 20 to 60 mbar Safety valve

Monovacuometer precision: -20 to +80 mbar Manovacuometer scale High pressure alarm 60 ±5 mbar Non-rebreathing valve Autoclavable, 60 cm H<sub>2</sub>O UNI Input connection

280 to 600 kPa Input pressure 270x210xh 177 mm - 3.8 kg Dimensions - weight aluminium, steel, brass, PE

#### STANDARD ACCESSORIES

Adult face-mask

2 l oxygen cylinder (34017 only) Transport case (34017 only)

Structure

Guedel cannula, tongue holder (34017 only) Manual: GB, IT, on request FR, ES, DE, PT

## iHEALTH WIRELESS PERSONAL HEALTHCARE PRODUCTS

#### **iHEALTH MYVITALS APP - free**

- track data, graphs and history on the iHealth MyVitals App

- multi-patient App (automatically sort measurements data per users)

- free and secure data storage

- share results with your coach and friends or healthcare professional

To manage wireless:

1 iHEALTH PULSE OXIMETER

*iHEALTH BODY ACTIVITY TRACKER* 

**IHEALTH B.P. MONITOR - ARM** 

**IHEALTH B.P. MONITOR - WRIST** 

**IHEALTH SCALE** 

*iHEALTH BODY ANALYSIS SCALE* (9 parameters)



iHEALTH products to manage your personal health iHealth designs innovative, mobile personal healthcare products for everyone, iHealth wireless products with Bluetooth connectivity for iPad, iPhone, iPod and Android system, allow to easily measure and track personal data and share instantly with family or doctor.

The powerful iHealth MyVitals App will also allow to manage all your health data with custom graphs, statistics, trends. This unique application tracks the relation between various parameters such as blood pressure, weight, calorie intake and activities.

App compatible with all Apple and Android platforms. Includes a free iHealth Cloud service.

iHealth MyVitals App available in: GB, FR, IT, ES, DE, NL, GR, HU, PT, RO, RU, TR, JP, KR, CN, AR.

Product package and manual in 8 languages (GB, FR, IT, ES, DE, PT, NL, GR). All products have 2 years warranty.



See the list of compatible devices on ihealthlabs eu/support

#### iHEALTH AIR PULSE OXIMETER



#### TECHNICAL SPECIFICATIONS

Classification: Display System:

SpO, Measuring Range Pulse Rate Measuring Range Size:

Internally powered, type BF

Battery, 3.7 V Li-ion, 300 mAh 70-99%, ±2% 30-250 bpm, ±2 bpm or ±2% larger one 62x33x28 mm • 23525 iHEALTH AIR - WIRELESS PULSE OXIMETER

The Pulse Oximeter is a reliable way to spotcheck blood oxygen saturation (SpÓ\_) pulse rate (bpm) and volume of blood flow (perfusion index).

This lightweight and portable device takes fast, non invasive measurements at the fingertip.

measures your blood oxygen saturation and pulse rate from your mobile device

- records SpO, and pulse rate easy-to-read LED screen displays SpO pulse rate and perfusion index

- connects wirelessly via Bluetooth 4.0 with low energy technology

- free iHealth app and cloud service include personalized health tools

Supplied with lanyard and USB charging cable.

12:34



For iOS and

See the list of

Android version 4.4 +

compatible devices on

### -2-iHEALTH BODY ACTIVITY TRACKER - WRIST/BELT 23531 iHEALTH EDGE WIRELESS ACTIVITY AND SLEEP

TRACKER

• 23532 IHEALTH WAVE WIRELESS ACTIVITY SWIM AND SLEEP

TRACKER Activity and sleep tracker make it easy to monitor your health.

It allows to know your body in motion and at rest and to track your vital signs any time any place. This innovative device can be worn either as a watch (wrist

band) or as a belt-clip (only 23531).

Sweat and rain proof (23531) or waterproof (23532). iHEALTH activity tracker features:

- track steps, distance, swim, calories burned and monitor sleep - swimming styles recognition (freestyle, breaststroke...) only 23532
- display swimming laps and time, number of strokes and calories burned (only 23532)
- programmable vibrating alarm function
- display time and date
- automatic on screen reports after running, walking, swimming (only 23532), sleeping
- Bluetooth Sync, easy installation

iHEALTH MyVitals App: Connects wirelessly via Bluetooth 4.0 technology.

ihealthlabs.eu/support FDA App Store Scoole play Battery: 1x3.7V Li-Ion 100 mAh - 3 years life. Supplied with 2 wrist bands (23532: blue and black) or 4 wrist bands (23531: black, grey, orange, pink) belt-clips (only 23531) batteries and USB cable for charging.
Manual and box in: GB. FR. IT. ES. DE. PT. NL. GR.

880

23532

IV

## iHEALTH WIRELESS PERSONAL HEALTHCARE PRODUCTS

#### • 23490 iHEALTH CLEAR SMART ARM B.P.M.

- clinically validated blood pressure (ESH) universal cuff (22 42cm)

**(€**0197 **FD** 

For iOS and Android version 4.4 +

- large HD screen which displays results clearly
- stores up to 1.000x2 offline measurements
- automatically save all measurement in your MyVitals app account (Wi-Fi)

**European Society** 

See the list of compatible devices on ihealthlabs.eu/support

Dual use: traditio

8

Smart and thin blood pressure

nonitor with direct visualization on its LED screen of the

last blood pressure

Weight: 232 a

use or use with

-iHEALTH ARM B.P. MONITORS

smartphone

- indoor/outdoor temperature to prevent blood pressure variations

## **TECHNICAL SPECIFICATIONS**

Connectivity: Wifi IEEE802.b/g/n Dimensions: 119×118×51 mm Cuff circumference: 22-42cm Weight: 350g (excluding cuff) Measuring method: Oscillometric, with automatic

-iHEALTH CLEAR SMART ARM B.P. MONITOR - WI-FI

inflation and deflation Battery: 1x3.7V Li-ion 2200mAh Battery life: 180 measurement on a full charge Range: Sys: 60-260mmHg / Dia: 40-199mmHg Pulse: 40-180bts/min



## ─■── iHEALTH TRACK CONNECTED ARM BLOOD PRESSURE MONITOR

- 23499 iHEALTH TRACK CONNECTED ARM B.P.M. clinically validated blood pressure (ESH)
- systolic, diastolic and heart rate (number of beats per minute)
- evaluation of measurements as recommended by the WHO
- detection of arrhythmia
- universal cuff (22-42 cm)
- colour changing display easy to use and comfortable
- 60 memories
- one-Click: save all your measurements in your MyVitals App account Multilanguage box and manual: GB, FR, IT, ES, DE, GR, PT, NL. iHEALTH MyVitals App:
- track data, graphs and history on the iHealth MyVitals App add measurement reminders, free and secure data storage
- share results with friends or healthcare professionals
- 23497 ADULT CUFF 22-42 cm spare

#### 23498 OBESE CUFF - 30-48 cm

Size: 98x98x46 mm Cuff circumference: 22-42 cm Weight: 438 g (cuff + batteries included) Measuring method: Oscillometric, with automatic inflation and deflation

TECHNICAL SPECIFICATIONS

Connectivity: Bluetooth 4.0 Power: 4x1.5V size AAA batteries Battery life: 250 measurements Range: Sys: 60-260 mmHg, Dia: 40-199 mmH Pulse rate range: 40-180 bts/min

## -iHEALTH WRIST B.P. MONITORS



- 23500 iHEALTH BP5S ARM B.P. MONITOR without display 23495 iHEALTH NEO BP5S ARM B.P. MONITOR with display available March 2018
- medically validated blood pressure monitors - easy to read wide Backlit screen (only 23495)
- measurement of blood pressure (systolic, diastolic)
- and of heart rate (number of beats per minute)
- detection of arrhythmia

23495

Easily saves all your

measurements into the

thanks to Bluetooth 4.0

iHealth MvVitals App

- multiple users and unlimited memories
- view historical readings and WHO classification
- Multilanguage box and manual: GB, FR, IT, ES, DE, GR, PT, NL.

TECHNICAL SPECIFICATIONS
Connectivity: Bluetooth 3.0 (23500) 4.0 (23495)
Dimensions: 135x55x12 mm (23495), 145x58x30 mm (23500)
Screen dimensions: 30.4x27.8 mm (23495 only)

Cuff circumference: 22-42 cm Measuring method: Oscillometric, with automatic

inflation and deflation Power: DC: 5 V, 1.0 A, 3.7 V, Li-ion battery Range: Sys: 60-260 mmHg ±3 mmHg Dia: 40-199 mmHg ±3 mmHg Pulse: 40-180 bts/min



ESH

European Society

Hypertension

- 23501 iHEALTH SENSE BP7 WRIST B.P. MONITOR • 23502 iHEALTH VIEW BP7s WRIST B.P. MONITOR - with display
- medically validated blood pressure monitor
- easy to read wide Backlit screen (only 23502)
- measurement of blood pressure (systolic, diastolic)
- and of heart rate (number of beats per minute)
- detection of arrhythmia
- best wrist position sensor for optimum measurement
- evaluation of measurements as recommended by the WHO\* Multilanguage box and manual: GB, FR, IT, ES, DE, GR, PT, NL

## TECHNICAL SPECIFICATIONS

Connectivity: Bluetooth 4.0 Dimensions: 72x74x17.6 mm Screen dimensions: 44x26 mm Cuff circumference: 13.5-22 cm
Measuring method: Oscillometric, with automatic

inflation and deflation Power: DC: 5 V, 1.0 A, 1x3.7 V, Li-ion 400 mAh

Range: Sys: 60-260 mmHq Dia: 40-199 mmHg Pulse: 40-180 bts/min



# iHEALTH WIRELESS PERSONAL HEALTHCARE PRODUCTS



• 23506 iHEALTH LITE HS4 WIRELESS SCALE

A high quality design digital scale, with slim lightweight design and reliable tempered glass platform, iHealth scales work online and offline.

Thanks to the iHealth MyVitals App it is possible to view single readings or long term trends, track calories and daily activities, set target goals for weight management, organize records with personalized graphs and unlimited memories.

#### **TECHNICAL SPECIFICATIONS**

Max weight capacity Size: Accuracy Batteries

180 kg (400 lbs) 350x350x28.5 mm

4x1.5 V AAA included

## -iHEALTH CORE BODY ANALYSIS SCALE

For iOS and Android version 4.0 +

See the list of compatible devices on



• 23508 IHEALTH CORE HS6 WIRELESS BODY ANALYSIS SCALE Weight monitoring and body composition on iPhone, iPad and Android smartphone. It allows to:

- measure weight, BMI (Body Mass Index), lean, bone, muscle, water mass, body fat and visceral fat rating
- estimate daily caloric intake
- display room temperature and humidity
- track data, graphs and history on the iHealth MyVitals App
- define goals to stay motivated
- store unlimited measurements
- share your medical data with your healthcare professional or family

Wi-Fi Sync, easy installation.

Secure and free data storage.

#### **TECHNICAL SPECIFICATIONS**

Connectivity Dimensions Weight: Battery: Range:

350x350x28 5 mm 2,500 g 4 AAA batteries 1.5 V (included)

5-180 kg ±1 % (50-180 kg)



## I IHEALTH GLUCOSE MONITORS - IHEALTH GLUCO APP

#### 23510 iHEALTH GLUCO BG5 SMART GLUCOSE MONITOR KIT

#### 23514 iHEALTH GLUCO BG5 SMART GLUCOSE MONITOR

Pocket sized, ergonomic wireless glucose monitor with advanced technology and high reliability. The Wireless Smart Gluco-Monitoring System is a convenient way to measure and record your blood glucose levels from your mobile device.

- view results instantly on the wireless meter
- save up to 500 test results on the wireless meter
- set up reminders and view glucose and insulin trends in multiple ways
- track test strip quantity and expiration dates automatically, no counting or coding required
- works on-line and off-line, with data automatically uploading at each connection.

Kit 23510 includes 10 test strips, 10 lancets, lancing device, control solution. Both include USB charging cable and travel

## • 23509 iHEALTH ALIGN - BG1 GLUCOMETER

Economic, button size model with advanced technology and good reliability. A convenient way to measure your blood glucose monitor and trasmit by your iPhone.

#### TECHNICAL SPECIFICATIONS

Machine size: Measuring method: Result range: Power source Blood source:

3

90×34.5×19 mm (23510-14) - 53x30x96 mm (23509) Amperometric technology using glucose oxidase 20 mg/dL~600 mg/dL (1.1 mmol/L~33.3 mmol/L) DC 3 6 V (23510-14) - DC 3 0 CR 1620 (23509) Fresh capillary whole blood

**(** €0197 23510





23509



**GLUCOSE MONITOR ACCESSORIES** code

23511 Glucose strips\* - box of 25 Glucose strips\* - box of 50 Lancets 28G - box of 100 Auto lancets device "On Call"

Far phone universal plug compatible with an mobile

\*No coding strips: no need to calibrate glucometer any time These strips are automatically identified by glucometer.

2

**( (** 0123

Easy calibration

On Call Plus II

with chip PLASMA

calibration results

23891

23916

23917

On Call Plus I

2:07 ...

## IHEALTH PRO THE APPLICATION FOR HEALTH PROFESSIONALS

## **iHEALTH PROFESSIONAL APP - free**

To manage wireless:

**IHEALTH B.P. MONITOR - ARM IHEALTH BODY ANALYSIS SCALE** (9 parameters)

*iHEALTH PULSE OXIMETER* 

*IHEALTH GLUCOSE MONITOR IHEALTH CARDIOLAB* 

**IHEALTH AMBULATORY B.P. MONITOR - 24 hours** 

The iPad application for health professionals that enables to monitor patient health data. Use iHealth Pro allows: measure the vital signs of patients with connected iHealth health

products create "patient files", and synchronize their health data in the iHealth Pro App
- integrate self-measurement data of patients from their iHealth My

Vitals application in the iHealth Pro application - follow and retain the measurements of

patients using clear graphs and history

generate reports in PDF format for printing

and sharing with colleagues All products I have 2 years warranty.



Bluetooth FD∕ C €0197

## --ihealth Cardiolab Wireless Cardiovascular Monitoring System (abi)-



Cardiolab includes 2 pressure cuffs, USB cable and manual (GB, IT FR DF FS NI) Tablet not included

**( 6** 0197







#### 23520 iHEALTH WIRELESS CARDIO LAB

Cardiovascular and blood pressure monitoring system with multiple sensors that allow the user to make simultaneous measurements on several limbs in real-time. CardioLab measures ABI (ankle brachial index) and calculates other cardiovascular parameters such as MAP, PP, cardiac output and stroke volume. It provides a full cardiovascular risk assessment according to internationally recognized standards and provides users with an intuitive way of measuring ABI and other cardiovascular parameters and brings detailed vascular assessment within the reach of general practitioners.

#### Early detection of peripheral arterial disease

The ankle brachial index (ABI) is the best predictor of cardiovascular morbidity and mortality of heart attacks and strokes. It is an essential component for the screening, diagnosis and management of peripheral arterial disease (PAD). It offers a simple, rapid and cost-effective method for evaluation of the distal perfusion of lower and upper limbs. Cardio-Lab makes a measurement of ABI in less than 3 minutes and gives a fully comprehensive picture of the arterial state

of the patient. The iHealth CardioLab is a simple, accurate and effective way of calculating the risk of strokes and heart attacks in routine medical examinations, is an excellent predictor of peripheral arterial disease (PAD) and should be used in routine examinations of patients.

#### Track the vital signs of your patients in less than 3 minutes:

- Blood pressure (SYS, DIA) - Heart rate
- Ankle Brachial Index (ABI) - Arrhythmia detection
- Pulse Pressure (PP)
- Mean Arterial Pressure (MAP)
- Stroke Volume (SV)
- Cardiac Output (CO)

#### Intuitive iPad-driven software

The iHealth CardioLab uses electronic palpation technology that combines all the advantages of manual palpation with the speed and accuracy of modern day electronics. It revives the art of palpation using direct oscillometric data obtained from the human body and translating it into a comprehensible format, measuring not only blood pressure, but also mean arterial pressure, pulse pressure, ankle brachial index, stroke volume and cardiac output

#### Track automatically. Know instantly.

- Measure ABI and blood pressure directly from your iPad
- Record systolic/diastolic numbers, heart rate, and pulse waves
- View historical readings and World Health Organisation's (WHO) classifications through
- colourful, easy-to-read displays - Generate custom graphs by date and
- time or systolic/diastolic numbers
- Share results instantly
- Unlimited users and memory

#### TECHNICAL SPECIFICATIONS Classification

Internally powered, Type BF applied part, IPX0, No AP or APG, continuous operation Oscillometric method, automatic inflation and measurement Measuring method:

Memory 9999 Battery 1x3.7 V Li-lon 400 mAh Power: DC: 5V 1.0A USB charge

Battery: IA3.7 v Enrish Section Sec Pulse rate: 40-180 beats/minutes ±5%

Cuff size: 145x58x30 mm Weight: 135 g Cuff circumference: 22-42 cm (universal cuff)

Wireless communication: Bluetooth V3.0 + EDR Class 2 SPP Frequency band: 2.402-2.480 GHz

## ——iHEALTH CARDIOMED - 24 h

## 23536 iHEALTH CARDIOMED - 24h ABPM

- measurement at regular intervals of blood pressure (systolic, diastolic) and heart rate (number of beats per minute) - detection of arrhythmia

- up to 24h monitoring
- universal cuff (22-42cm)
- thin, light and forgettable - activity and posture detection
- during measurements - Bluetooth sync
- secure and free data storage

- import your patient homemonitoring data into the iHealth PRO App Supplied with USB cable and manual (GB, FR, IT, ES, DE).

TECHNICAL SPECIFICATIONS

Connectivity: Bluetooth 4.0 / Micro-usb Dimensions: 135.5x55x12 mm Memory slots: 1x200

Measurement method: Oscillometric

Measurement range: 300 mmHg, 40-180 pulse/min Accuracy: ±3mmHg, ±5% Power Source: 1x3.7 V Li-ion 800 mAh

**( (** 0197 Weight: 110 g 23536

## **GLUCOSE MONITORS** FOR DAILY DIABETES TESTING

BIOSENSOR TECHNOLOGY

5 SECOND TEST TIME ONLY 0.5 µL BLOOD SAMPLE

23896

Advanced technology glucose monitors. Available as unit only or complete kit. Kit includes 10 strips, code chip, control solution, 10 sterile lancets, lancet device, clear cap (for testing on forearm or palm), carrying case, user manual. Main features:

- accurate result in just 5 seconds

- only 0.5 µl sample size

- automatic calibration with code chip

- plasma calibration results

advanced data management with 7, 14, 30 days average

- affordable for frequent monitoring

- flexibility to test on the forearm, palm or fingertip

- certified ISO 15197:2013

Memory

TECHNICAL SPECIFICATIONS Measurement Range

20 to 600 mg/dL or 1.1 to 33.3 mmol/L Sample Sites - Size Finger tips, Forearm or palm - 0.5 µL Approximately 5 seconds One 2032 or equivalent 3.0 V coin cell battery Power Source Battery Life 12 months or approximately 1,000 tests

Up to 300 records with time and date

mmol/L ON CALL® PLUS II GLUCOSE MONITOR Italian English Spanish English Greek French Portuguese French 23890 23891 23892 23881 Glucose monitor Plus-meter only 23895 23896 23897 23886 Glucose monitor Plus-kit Accessories and consumables for GLUCOSE MONITOR ON CALL® PLUS AND ON CALL® PLUS II

23910 Glucose Strips - box of 25 strips 23912 Glucose Strips - box of 50 strips

23913 Glucose Strips - box of 100 strips

23914 Control Solution

23919 Auto lancet device 23917 Lancets 28G for 23919 - sterile - box of 25 pcs

**23916** Lancets 28G for 23919 - sterile - box of 100 pcs

# **ABBOTT GLUCOSE STRIPS**





#### ABBOTT FREESTYLE OPTIUM BLOOD GLUCOSE TEST STRIPS GIMA

23942 FreeStyle Optium Neo, FreeStyle Libre, FreeStyle box of 25 23943 Optium, Optium Xceed, Optium, Optium Easy, Boots box of 50

#### ABBOTT FREESTYLE LITE BLOOD GLUCOSE TEST STRIPS

23944 FreeStyle Lite, FreeStyle Freedom Lite, box of 25

## LANCETS AND LANCET DEVICE



 23917 GIMA LANCETS - 28G - sterile - box of 25 pcs • 23916 GIMA LANCETS - 28G - sterile - box of 100 pcs Lancets are fine needles that can be used with code 23919 and most of lancet devices in the







SURGILANCE SAFETY AUTOMATIC LANCETS - NEEDLES Multi purpose capillary blood sampling devices for all testing requirements

The one-step safety lancet is easier to use, no arming is required, and safer, once lancet is used it is rendered inoperable. High-speed delivery and penetration method minimizes patient pain and operator error.

Latex-free, hypo-allergenic, disposable, sterile.

5

Luccon I	acex mee, mypo amengeme, and postable, seemen								
SURGILANCE™ SAFETY LANCETS - NEEDLES									
GIMA code	Colour	Depth of penetration	needle	Needle tip Gauge	Blood Flow	Finger Stick	Gucose	Hematocrit	
24513	Yellow	1.0 mm	G21	G26	5-10 µl	•	•		box of 100
24514	Grey	1.8 mm	G21	G23	10-20 µl	•	•		box of 100
24515	Orange	2.2 mm	G21	G22	20-40 µl	•	٠	•	box of 100
24517	Pink	2.8 mm	G21	G21	40-60 µl	•	٠	•	box of 100
						-	-	-	





**INSULINE PEN NEEDLES SEE PAGE 52** 

## MULTICARE "IN" - SELF CONTROL OF RISK FACTOR

- 23965 MULTICARE "IN" KIT Italian manua
- 23966 MULTICARE "IN" KIT English manual
- 23967 MULTICARE "IN" KIT CD multilanguage manual

\*Includes 11 languages: GB, IT, FR, ES, GR, PT, PL, SL, HU, TR, DE A new approach for the periodical self-monitor of risk factors - cholesterol, triglycerides and glucose. The only device on sale with reflecto-metrical and electro-chemical bio sensor suction. Multicare "IN" is supplied in cardboard box with a nylon bag, 10 glucose strips, lancet device, 10 lancets, rapid guide and user manual. Multilanguage box: GB, FR, IT, ES, GR, PT, PL.



Short time for the results (5 sec.) **REFLECTOMETRIC SUCTION STRIP - cholesterol and tryglicerides** 

 - multiCare 00 is a unique technology. - It allows a more functional self-monitoring of triglycerides and cholesterol.



Tube	Tube	Tube	SPARE STRIPS FOR MULTICARE "IN			
of 5	of 25	of 50	7 LANGUAGE BOX			
-	23969 23970 1 23972 -		Glucose strips biosensor + 1 chip			
23971			Cholesterol strips + 1 chip			
23973	23974	-	Triglycerides strips + 1 chip			
GIMA	CONTROL COLLITION FOR MULTICARE "INI"					
code	CONTROL SOLUTION FOR WIGHTCARE IN					
22070	Character and and and address					

23978 Glucose control solution 23979 Cholesterol control solution

23980 Triglycerides control solution
LANCETS FOR MULTICARE AND MULTICARE "IN"

23917 Lancets 28G - sterile - bag of 25 pcs 23916 Lancets 28G - sterile - box of 100

23982 SOFTWARE FOR MULTICARE "IN" - GB, FR, IT, ES

Operating system: Windows XP, Windows 7 and 8, Vista, 16 Mb Ram, 10 Mb remaining space on hard disk

EE



-8







TECHNICAL SPECIFICATIONS

Measuring range Measuring Glucose electro-chemical: 10-600 mg/dl 1 ul Cholesterol 130-400 mg/dl 30 10 ul Triglycerides 50-500 mg dl 10 ul 500 test results with date and time 2 lithium batteries Cr 2032 3 Volts (32212) Ratteries

97x49x20.5 mm - 65 a

## CHOLESTEROL, TRIGLYCERIDES, GLUCOSE STRIPS FOR MULTICARE

-

Server on See Serve

multi Care (f)

Tube	Tube	Tube	STRIPS AND CONTROL SOLUTION
of 5	of 25	of 50	FOR OLD MULTICARE (23948, 23950)
-	23955	23956	Glucose strips + 1 chip
23957	23958	-	Cholesterol strips + 1 chip
23959	23960	-	Triglycerides strips + 1 chip
	23961		Glucose control solution (3*x2.5 ml)
	23962		Cholesterol control solution (2x2.5 ml)
	23963		Triglycerides control solution (2x2.5 ml)
'Level low	normal h	iah	

Each strip box has its own coded chip for safe measurement

Size - weight







## MISSION® CHOLESTEROL METER + LIPID PANEL TECHNICAL SPECIFICATIONS

12-03 0900

• 23932 MISSION® CHOLESTEROL METER Provides high quality and reliable results for complete Lipid Panel testing in 45 seconds. 3 in 1 complete Lipid Panel device

tests for Total Cholesterol (CHOL). High Density Lipoprotein (HDL) and Triglycerides (TRIG) Also includes calculated tests: Low Density Lipoprotein (LDL),

CHOL/HDL ratio and Cardiac Risk Assessment

- can test whole blood, serum or plasma - wide hematocrit range of 0-50%

- small printer available for immediate printing of results Easy to use

- large LCD display for easy reading - colour coded test devices with engraved test name for easy identification

battery operated

Supplied with 5 safety lancets, 2 control devices, 4 batteries, carrying case and manual (GB, IT) Available FR,ES, DE, PT manual in www.gimaitaly.com Multilanguage box: GB, FR, IT, ES, DE, PT, PL, SE, FI, GR, NL, RO, BG, RU, ŠA

#### Reflectance Photometr

Detection principle Time to results Memory with date/time 45 seconds-2 minutes 200 results Type of test

Calculated tests Specimen volume

Pc interface for data transfer Calibration

Quantitative CHOL, HDL, TRIG LDL, CHOL/HDL ratio, Cardiac Risk Assessment 3-1 Lipid Panel Device: 35 uL CHOL Individual Test Device: 10 µL Measurement units mg/dL or mmol/L CHOL: 100-500 mg/dL (2.59-12.93 mmol/L) HDL: 15-100 mg/dL (0.39-2.59 mmol/L)

Languages on the screen Power source Battery life Automatic shut off Meter dimensions Display dimensions Weight excluding batteries

Measurement range

TRIG: 45-650 mg/dL (0.51-7.34 mmol/L) Mini USB Port Code Chip English abbreviations 4 AAA or AC Adaptor (Mini USB, 5V dc, 50 mA) ≥ 1.000 tests 5 minutes 137×79×26 mm (5.4" x 3.1" x 1.0") 50×50 mm (2.0" x 2.0")

145 g (5.11 oz) GIMA ACCESSORIES AND SPARES order 23933 3 in 1 Lipid panel tests + capillary tubes 35 ml 23934 Total Cholesterol tests + capillary tubes 10 ml box of 25 box of 25 24024 Capillary transfer tubes 10 ml - plastic box of 50 23917 Gima lancets 28G hox of 25 23916 Gima lancets 28G box of 100 23919 Auto lancet device - AST method 23929 Mission printer 33250 Thermal paper roll 57 mm x 25 m box of 5

## LUX: PROFESSIONAL MONITORING OF LIPIDS, GLUCOSE AND HEMOGLOBIN











#### **TECHNICAL SPECIFICATIONS LUX MONITOR**

Number of measurements

Display Operation buttons

Memory Function Power source More than 500 measurements (lipid) or more than 1'000 measurements (glucose or hemoglobine) Lipids and Hemoglobin: optical method, Glucose: electrochemical method LCD (LED Backlight)

(ON/OFF switch, up button and down button) 1'000 readings

Average of glucose measurements (7, 15, 30 days) 3XAAA 1,5 V alkaline manganese batteries

• 23983 LUX MONITOR for lipid, glucose and hemoglobin The cardiovascular diseases are linked to the concentration of cholesterol in the blood. Many people don't know that their cholesterol is high or do not monitor it. Lux gives benefit to doctor to do a complete lipid screening plus glucose and hemoglobin in less than 3 minutes.

Only 45 µl for the complete lipid panel, 7 µl for the hemoglobin, 0.5 µl for the glucose **Effective** 

Doctor can test during consultation with patient. Complete lipid panel in 3 minutes Measurement of cholesterol, triglycerides, HDL,

LDL at the same time in less than 3 minutes. Additional hemoglobin and glucose test

Software for download PC (GB, IT) Optional data reading software (CD + cable) for easy download Lux monitor is supplied with carrying bag, pipette 15 µl,

pipette 7 µl, 3xAAA batteries 1.5 V and manual (GB, IT). Made in Italy.

GIMA code	ACCESSORIES AND SPARES	Minimum order
23984	Lipid strips with tips and chip - need 23997	box of 10
23985	Hemoglobin strips with chip - need 23998	box of 10
23986	Glucose strips	box of 50
23987	Lipid control solution with chip - 2 ml	3 bottles*
23988	Hemoglobin control solution - 2 ml	1 bottle
23989	Glucose control solution - 2 ml	1 bottle
23997	Pipette 15 µl for lipid	-
23998	Pipette 7 µl for hemoglobin	-
23999	Software (CD + cable)	-
*1 bottle for	each parameter (total cholesterol, triglycerides, HDL)	

**TECHNICAL SPECIFICATIONS - STRIPS** 
 Measuring method
 Photometric, amperometric only for glucose

 Test range
 Total Cholesterol: 100-400 mg/dL,

Measuring unit Measuring time Sample volume

Type of sample

Triglycerides: 50-600 mg/dL, HDL: 20-80 mg/dL Hemoglobin: 5-25 a/dL, Glucose: 20-600 ma/dL mg/dL (standard), mmol/L (settable by user) Linids: within 3 min : Hemoglobin: 5 sec : Glucose: 5 sec 15 µl Cholesterol, Tryglicerides, HDL each test; 7 µl Hemoglobin; 45 µl Lipid 3 tests; 0,5 µl Glucose Lipids and Hemoglobin: fresh capillary blood for self-monitoring and professionals (venous blood samples

must be withdrawn by a healthcare professional); Glucose: fresh capillary blood

box of 12

## MISSION® PT/INR COAGULATION MONITORING SYSTEM

### 23926 PT/INR COAGULATION MONITORING SYSTEM Coagulation testing for professional and self use

- quick results for Prothrombin Time (PT) in seconds and International Normalized Ratio (INR)

- large INR range of 0.7-7.0
- individually packaged strips with 24 months shelf life
- external optional printer available for quick printing of results
- clinical accuracy: ISO 17593 compliant

#### Simple operation

- results in about 2 minutes
- requires only a single drop of capillary blood or 15 µL of venous whole blood
- insert strip, apply specimen and read results

#### User friendly

- handheld portable meter easy to use and ideal for physician offices and home testing
- includes lockout functions and the capability to store patients ID's
- operates with battery or standard AC adaptor






23928 PT test strips with chip 23931 Control solution 24515 Surgilance safety lancets 22G 33250 Thermal paper roll 5.7 cm x 25 m 23929 Mission printer* - need cable 23930 Cable printer to PT/INR 23929					box of 48 1 kit** box of 100 box of 5	
		vel-2 (	oter, package ins 0.4 ml bottles, 1 i	nsert, 1 pi		
		ST	ANDARD ACC	ESSORI	ES V	The same of the sa
1 quick ref	erence guide	1 AC	adaptor	4	AA batteri	es
1 carrying	case	1 use	r's manual (GB,	IT) on re	quest DE, ES	S, PT
Precision Accuracy PC interfa Power sou Battery lif Meter dim Display di	ogy volume type rement range e	κH) /)	HNICAL SPECI Optical fluore About 2 minu 200 results wi 15 μL Fresh capillary 0.7-7.0 25-60 % Repeatability Y=1.076X-0.0 Mini USB 4 AA batteries 100 tests 152x72x37 mr 46x23 mm (1.4 T70 g (6.0 oz)	scence tes th date/t or veno and tota 78, R=0.9 s or AC a n (6.0"x2	ime us whole bl I precision « 24 daptor	

**ACCESSORIES AND SPARES** 

23927 PT test strips with chip



# HEMO CONTROL: HEMOGLOBIN MEASURER AND HEMATOCRIT



# MISSION Hb HEMOGLOBIN TESTING SYSTEM Multilanguage box: GB, FR,IT, ES, PT, DE, PL, RO, SE, FI, GR, TR, Arabic.

0 1-05 10:58

**√** ∪ ►

 24022 MISSION Hb HEMOGLOBIN TESTING SYSTEM Accurately detects Hb and Hct levels. Professional use.

- Hemoglobin (Hb) and Hematocrit (Hct) results in < 15 seconds

- simply insert strip, apply specimen and read results

- features auto-calibration

- no specimen preparation required Accurate

- only 10 μL capillary or venous blood required - precise results equivalent to automatic hematology analyzers

- wide Hb measurement range of 4.5-25.6 g/dL with Hct range of 13-75%

- stores up to 1,000 results Portable

- dry strips eliminate inconvenience in shipping and storage of liquid reagents Convenient

- can test capillary and venous whole blood - quick data transfer via Mini USB port

- minimal training required

- operated by battery  $\epsilon$ - handheld for immediate diagnosis

> 10 test strip 10 lancets (26 G) 24022 1 lancing device

Methodology

Calibration

Accuracy Power source

Battery life

Time to results

Memory Specimen volume / type

Hb measurement range Wavelengths

Hb within run precision CV

≤ 3% Hb Total precision CV ≤ 3% Hb 4.5 - 10 g/dL, ±0.4 g/dL; Hb 10 - 25.6 g/dL ± 4% 3 AAA Batteries or AC Adaptor on request 2,700 tests or 360 hours Automatic shut off Size (LxWxH)

24023 TEST STRIPS - box of 50 + 1 code chip

23916 GIMA LANCETS 28G - sterile - box of 100

23919 AUTO LANCETS DEVICE - AST method

• 24024 CAPILLARY TRANSFER TUBES 10 ml - plastic - box of 50

24513 SURGILANCE SAFETY LANCETS 26G - sterile - box of 100

**TECHNICAL SPECIFICATIONS** 

reflectance Photometry principle Methemoglobin

< 15 seconds

4.5 - 25.6 g/dL

525 nm

automatic

STANDARD ACCESSORIES 3 AAA hatteries 2 control strips 1 carrying case 10 capillary transfer tubes - plastic user manual GB, IT

1,000 tests with date/time and ID number

Hct range 13 - 75%

Hb Total precision CV ≤ 3%

10 µL / capillary and venous whole blood

8 minutes 127x58x25 mm (5.0"x2.28"x0.09")

# GIMA URINE ANALYZER AND URINE STRIPS

#### • 24046 GIMA URINE ANALYZER

Gima urine analyzer is a high-precision instrument with advanced technologies for clinical inspection of urine. It offers easy and quick operation, exact results and good repeatability. Features:

- high-luminance and white LED, features long life and good stability

- large LCD display

- user-friendly interface

- monitoring the whole testing process, and audible-control prompt

- data transmission function.

Application:

Display:

- health examination

- chronic diseases, long-term monitoring for nephrotic patients

- convenient point of care testing for doctor

**TECHNICAL SPECIFICATIONS** 

Test range:

Working mode: One-step Stability Record mode Internal language Italian and English 2.4" LCD, resolution: 320x240 Power supply Data storage 500 sample data

RGB tricolor test theory Principle: Communication interface: Micro USB interface, Bluetooth wireless communication

Repeatability

- portable device, for travelling doctors use as telemedicine terminal. Tested parameters

Glucose (GLU), Bilirubin (BIL), Specific gravity (SG), PH, Ketone body (KET), Occult blood (BLD), Protein (PRO), Urobilinogen (URO), Nitrite (NIT), Leukocytes (LEU), Ascorbic acid (VC).

• 24071 11 PARAMETER STRIP box with 5 pouches of 3 strips • 24072 11 PARAMETER STRIP -

tube of 50 strips

control keyboard CV <1% LCD display, flash ROM data storage Built-in rechargeable lithium battery 3.7 V, 1900 mAh

Test naner tray to place the strip to be tested

USB socket

24046

Host computer: DC 5 V. 1 A Adapter: AC 100-240 V, 50/60 Hz Refer to grads table on www.gimaitaly.com 126x73.5xh 30 mm - 0.18 kg



GIMA VISUAL URINE STRIPS • 24069 10 PARAMETER STRIP - tube of 100 strips

• 24071 11 PARAMETER STRIP - box with 5 pouches of 3 strips

• 24072 11 PARAMETER STRIP - tube of 50 strips

These strips can be used by professionals for visual tests. 11 parameters strips can also be used with Gima urine analyzer (24046) and Bayer CLINITEK-100 reader

- global check/screening for general health condition

- measures level of Leukocytes, Nitrite, Urobilinogen, Protein, pH, Blood, Specific Gravity, Ketone, Bilirubin, Glucose, Ascorbic Acid (24071 and 24072 only) in 1 strip

- check for healthy nutrition, urinary tract infection, tumors, kidney damage, gout, fever, cirrhosis, viral hepatitis, liver disease, congestive heart failure,

jaundice, diabetes and acute renal failure. For professional use only.



# CENTRIFUGES FOR PLASMA, URINE AND BIOLOGICAL LIQUIDS

 24031 UNIVERSAL CENTRIFUGE - 8 tubes fixed rotor 24032 UNIVERSAL CENTRIFUGE - 6 tubes horizontally

pivoting rotor • 24040 TEST TUBES 10 ml - box of 100 pcs

The universal centrifuges are the perfect solution for laboratories and doctors' offices. They feature a ZERO-RPM locking lid for

safety, digital programming of time ranging from 1-99 minutes speed ranging from 500-3300 rpm. They accomodate 6 or 8 tubes (3-15 ml). Achieve up to 1364 g. taking to a perfect separation by centrifugation. They have a DC motor and come with a 110-220 V auto switching power supply. Made in USA. Manual GB, IT. -A Lid B ON/OFF switch (DC power jack) -C Run button -D Stop/Open button E Speed setting **-F** Time setting

24031-2

27x37x37 cm TECHNICAL SPECIFICATIONS 500-3300 rpm (step of 100 rpm) 120 ml Maximum power: 12 W Nominal speed: Maximum volume:

Normal REC: 31-1364 Recommendations Speed 3300 1800 Time Whole blood 10 min

**G** Emergency r

H Lid latch

24031

• 24035 XC-2000 CENTRIFUGE

Very silent centrifuge with 6 tube positions, provided with electronic counter to allow precise speed setting from 1000 rpm to 4000 rpm (500 rpm increments). It is supplied with metal holder for 6 tubes of 10 ml and holder for 6 tubes of 15 ml. Operating time is adjustable from 1 to 60 min.



**TECHNICAL SPECIFICATIONS** 220 V - 50 Hz Power: 80 W Approx 1,000 - 4,000 rpm (increased in increments of 500 rpm's) 1-60 min Speed: Time: 15 ml or 10 ml x 6

9

## ANALYTICON URINE ANALYZER AND URINE STRIPS





• 24049 URILYZER® 100 PRO URINE ANALYZER - with printer Urilyzer® 100 PRO is a small urine test strip reader that offers a broad range of optimized features.

The intuitive user interface improves data entry and allows manual entry of colour and turbidity from a predefined list or by an additional comment.

Moreover, the system provides the user with a high level of customization with flexible testing and reporting options. The intelligent database-driven data management provides multiple filter options.

To be used with urine strips 24062 and 24063 only. CD manual in GB, DE, IT, SE, NO, DK, ES. Internal software: GB, FR, IT, ES, DE, GR, NO, SE, FI, DK, HU, CZ, RO RU

Made in Hungary.

Printout:

Accuracy:

Type: Interfaces:

• 33250 PRINTER PAPER 57 mm x Ø 50 mm - box of 5 rolls

## • 24055 CONTROL SOLUTION - 15 ml - box of 2

TECHNICAL SPECIFICATIONS Measurements: Memory: Display:

50 meas./hour in normal mode, 120 meas./hour in fast mode 3.000 patient test results and 1.000 OC Test results 3.5" QVGA Touch-screen LCD (resolution 240x320) Low noise thermal printer with paper roll for about 280 measures Current number measurement, Date and time, Serial No. of the meter, patient-I-D. Asterisk on pathological results. Parameters can be printed in SI, Conventional or arbitrary units Meter adjustment in 5 levels according to individual requirements Reflectance photometer wavelengths: 505, 530, 620, 660 nm RS232 serial port, USB A, USB B, PS2 (external keyboard, barcode reader), microSD card, Ethernet port, HL7 protocol

Dimensions/Weight: 190x260x77 mm (WxDxH) / 1.5 kg

Power supply: 100-240 V, 50-60 Hz



ANALYTICON COMBI SCREEN® PLUS and SYS - urine strips Urine strips for visual test or for use with Urilyzer® 100 and CombiScan 100 (24062 and 24063 only).
• 24060 COMBI SCREEN® PLUS - 3 parameters -

- tube of 100 strips
- 24061 COMBI SCREEN® PLUS 10 parameters tube of 100 strips
- 24063 COMBI SCREEN® PLUS 11 parameters -

GIMA	24060	24061	24063	24062
Leucocytes Nitrite				:
Urobilinogen		•	•	•
Ha				:
Blood		•	•	•"
Ketones (acetoacetic acid)			:	:
		•	•	•
Glucose	•.	•*	•*	•
Ascorbic acid			•	•
"Ascorbic acid protection pad" "No ascorbic acid protection pad				
	GIMA code Leucocytes Nitrite Urobilinogen Protein (albumin) pH Blood Specific gravity Ketones (acetoacetic acid) Bilirubin Glucose Ascorbic acid	GIMA code Leucocyces Urobilinogen Protein (albumin) pH Blood Specific gravity Ketones Gacetoacetic acid) Glucose Ascorbic acid	code 24060 24061 Leucocytes Nitrite Victoria (albumin) Protein (al	GIMA code 24060 24061 24063 Leucocyces Urobilinogen Protein (albumin) pH Blood Specific gravity Ketones (acetoacetic acid) Glucose Ascorbic acid

protection for glucose and blood tests. Offers relevant reduction of false negatives due to interference with ascorbic acid. Supplied in aluminium tube in single cardboard box. For professional use. Manual in GB, FR, GR, IT, ES, PT, NL, DE. Made in Germany

• 24062 COMBI SCREEN® SYS -11 parameters - tube of 150 strips

Same as code 24063 but without ascorbic acid protection PAD on alucose and blood.

## MICROHEMATOCRIT CENTRIFUGE

 24025 MICROHEMATOCRIT CENTRIFUGE - 180 sec. Economic system, easy to use, fully automatic with LED indicators, no vibration, silent, rapid and provided with rechargeable battery.

Useful for: small labs, office labs, blood drawing areas. pediatric, neonatal settings, dialysis centers, emergency room labs, veterinarians, sample prep for stat chemistries.

• 24026 CAPILLARIES for microhematocrit - tube of 500 Made of glass 9 microliters. Length: 32 mm - Ø 1.5 mm

TECHNICAL SPECIFICATIONS

Power: rechargeable battery (battery charger supplied 100 ÷ 240 V plug in)
Dimensions: 136 mm (L) x 215 mm (W) x 122 mm (H) Weight: approx 1.2 Kg.





24062

## STREP-A RAPID TEST, ACCURATE RESULTS IN 5 MINUTES

• 24522 STREP-A - device - box of 20 tests

• 24523 STREP-A - strip - box of 25 tests

Provides accurate results in few minutes, with a simple procedure easy to perform and to interpret. Immediate diagnosis facilitates patient treatment decisions in the same office visit. Room temperature storage. It includes 20 devices or 25 strips tests (single pack), 2 reagents, 20 (or 25) tubes and swabs. Multilanguage manual and package. For professional use.

#### TECHNICAL SPECIFICATIONS

24523 Relative sensitivity: 97% (91-99%) Accuracy: 95% (93-97%) 97% (96-98%) Relative specificity: 95% (92-97%) 98% (96-99%)

#### PROCEDURE

- add 4 drops Reagent A, then drops reagent B rotate swab 10 times, wait 1 minute, then remove swab while squeezing tube to remove liquid
- place dropper tip to top of tube (24522)
- add 3 drops of specimen (24522)
- immerse strip in specimen (24523) 24523









## STREP-A DUAL COLOUR RAPID TEST, OPTICAL TECHNOLOGY

• 24519 STREP-A DUAL COLOUR TEST - strip - box of 50 tests The new, dual colour rapid test for Strep A uses the antibody labelled colour particles coated at two separate locations in the test device. This new optical immunoassay technology allows greater sensitivity and less false negative results than the conventional single label test, without affecting specificity. The procedure for the user is the same as for the standard test but the result will be easier to view. If Group A Streptococcus is present in the sample, a visible blue Test Line will appear to indicate a positive result and a **red Control Line** will also appear to indicate the test is valid. Kit includes 50 test strips, 50 tubes, 50 swabs, 2 reagents and 2 control solutions. Multilanguage box and manual: GB, FR, IT, ES. Professional use.

TECHNICAL SPECIFICATIONS

Relative sensitivity: 95.1% (95%CI:\*89.6-98.2%) Relative specificity: 97.8% (95%CI:\*95.8-99%) Overall accuracy: 97.1% (95%CI:\*95.3-98.4%)

Blue test line indicates a positive result red control line indicates test validity MONONUCLEOSIS TEST

 $\epsilon$ 

## **INFLUENZA A/B TESTS**

 24537 INFLUENZA A/B TESTS - box of 30 tests (3 packs of 10 pcs.)

Influenza A/B is a rapid in vitro test to detect type A and B influenza antigens (nucleoprotein) FLUA FLUB extracted from the nasal specimens. The test is designed to detect nucleoproteins of Flu-A core subtypes, independent of H and N surface proteins (including H1N1, H3N2, H5N1, H5N3, H7N3, H9N2). A sterile nasal swab allows an easy collection of specimen. Results in 10-15 minutes. Includes rapid influenza A/B test panel, swab, test tube, extraction buffer. For professional use only.

 $\epsilon$ 

antibodies qualitatively in whole blood, serum or plasma. For professional in vitro diagnostic use only. Results in 5 minutes. It includes 20 cassette tests, 20 droppers,

A rapid test for the diagnosis of

Infectious Mononucleosis

Mononucleosis heterophile

(IM) to detect Infectious

buffers and user manual

• 24538 MONONUCLEOSIS TEST - box of 20 tests

24538

WARNING: SHORT EXPIRY DATE FOR TESTS. Tests have 24 months expiry at production time. Our stock may vary from 10 to 22 months.

## FOB-FECAL OCCULT BLOOD TEST FOR EARLY DETECTION

CE

#### • 24530 FOB TEST - box of 25 tests

Provides accurate results in few minutes. It facilitates early patient treatment decision. Simple procedure, easy to perform and interpret. No additional equipment required. It includes 25 pcs of collection stick, device test and one buffer bottle. For professional use



## HELICOBACTER PYLORI TEST FOR ULCER SCREENING

#### • 24528 HELICOBACTER PYLORI TEST - box of 40 tests Helicobacter Pylori is the leading cause of gastric ulcers, this easy to use test allows a guick diagnosis in about 10 minutes.

Easy to perform and interpret, no additional equipment required. For professional use. Diagnosis of H. pilory infection in adults over 18 years of age.

• 24529 HELICOBACTER PYLORI SELF TEST - box of 1 test Same as 24528 but packed in single box including one automatic lancet, single buffer and user manual. This product is provided with self testing certification to be



## PROSTATE SCREENING - PSA ONE-STEP TEST

- 24534 PSA TEST box of 25 tests for doctor/hospital use Provides accurate results in 5-8 minutes.
- over 98% correlation to lab tests

sold to end users in OTC market.

- simple, easy to use serum or plasma test
- detects PSA as low as 4 ng/ml
- contains everything needed to perform test (except lancets see page 5) - for professional use
- 24532 PSA SELF TEST box of 1 test for self test whole blood Same as 24534 with results in 10 min. Packed in single box including one automatic lancet, single buffer and user manual. Provided with self testing certification to be sold to end user.



## CARDIAC MARKER

#### 24525 CARDIAC MARKER

3 parameters: CK-MB, Troponin, Myoglobin - box of 20 tests It allows to check cardiac status and stroke events in just 15 minutes. Ideal to keep under control patients affected by cardiopathies or after heart attack or surgery. Acute Myocardial Infarction-MI (Heart Attack) is responsible for 1 in 5 deaths in the U.S. After 6 hours of AMI onset, the damage to the cardiac muscle is irreversible and permanent. This illustrates that early and accurate diagnosis of AMI is essential. ECG is the most widely used method of MI diagnosis.

Unfortunately, as many as 25% of AMI patients have a normal ECG. GIMA offers an array tests for Biochemical and Protein markers of MI, such as Creatine Kinase Isoenzyme MB (CK-MB), Myoglobin (MB) and Cardiac Troponin I (cTnI) in combination. It includes 20 droppers, 20 cassettes and 1 bottle with dilution



## SEMI-QUANTITATIVE CRP TEST

## • 24527 CRP TEST - box of 20 tests

Measurement of CRP in whole blood, plasma or serum has two

- 1) hs-CRP levels help in assess the risk of cardiovascular and peripheral vascular disease. Higher hs-CRP values have highest risk of cardiovascular disease.
- 2) CRP levels help identify and keep track of infections and diseases that cause inflammation (lymphonoma, lupus, giant cell arteritis, osteonyelitis, rheumatoid arthritis, ....).
- use fingerstick whole blood or serum/plasma - results within 7 minutes - room temperature storage
- built in performance control and reference band It includes 20 cassette tests with droppers. For professional use.



# MALARIA RAPID TEST

• 24547 MALARIA RAPID TEST - box of 40 tests A rapid chromatographic immunoassay test for the qualitative detection of circulating plasmodium falciparum in whole blood. Compared with traditional thick or thin blood smears microscopic analysis, the correlation between the two systems is over 99,0%. Package includes test devices, buffer, disposable specimen dropper and multilanguage manual, lancets are not included For professional use.



WARNING: SHORT EXPIRY DATE FOR TESTS. Tests have 24 months expiry at production time. Our stock may vary from 10 to 22 months.

## DRUG TEST READER SYSTEM - FOR URINE DRUG CUPS/PANELS

- 24570 DRUG READER Italian software
- 24571 DRUG READER English software
- 24576 MULTI DRUG CUP 7 drugs + S.V.T. • 24577 MULTI DRUG CUP - 8 drugs + S.V.T.
- Simply scan one of the two multi drug test on drug reader and get a complete analysis at your
- automated analysis of "visual read" test panels
- automatic test menu recognition (2D barcode)
- in-process system quality control check - image capture, data management/export
- functionality, archived results Main benefits:
- automation eliminates results interpretation variability/subjectivity - accuraté, performance advantages vs. visual interpretation
- speed scanning process requires 15-30 sec.
- flexible semi-portable, simple installation, Windows compatible, Professional use.



SALIVA DRUG TEST

24555

## MULTI DRUG "CUP"

CUT OFF NG/ML

300

300

50

500

500

300

500

#### Test panel is tightly fastened • 24546 MULTI DRUG "CUP" TEST - urine to the cup protecting it from box of 25 tests for 7 drugs Detects following parameters:

- (MTD/MDMA)+<COC>+<AMP500>+<MET500 >+<THC>+<MOP>. For professional use. - easy to use - no urine handling, just insert the key into the active test and
- tightly sealed urine cup no leaking or spilling of urine specimen

read results in 5 min.

- unique design ensures that urine used in the test, will be separated from residual urine, that will remain uncontaminated, to be used for a
- further test when necessary - key packed separately, ensures security that only the technician can begin the test



DETECT

 24555 MULTI DRUG SALIVA TEST oral fluid (saliva) - box of 25 tests for 6 drugs Multi drug tests provide accurate results in 10 min. for the following drugs: amphetamine, cocaine, marijuana cannabis, methamphetamine, opiates, phencyclidine. For medical and professional use. Multilanguage manual: GB, IT, FR, DE, ES, PT,

	5 5 .		•					
	ORAL	ORAL FLUID SCREENING TEST DEVICE - 24555						
TION TIME*	DRUG	CUT OFF NG/ML	DETECTION TIME					
7 days	COC	20	10 min - 24 h					
5 days	THC	30	up to 14 h					
- 1	AMP	50	10 min - 72 h					
5 days	MET	50	10 min - 72 h					
7 days	PCP	10	-					
7 days	OPI	40	1 h - more days					
5 days	MTD	45	up to 2 days					

# DRUGS OF ABUSE, URINE TESTS FOR PROFESSIONAL USE (6

- 24540 COCAINE TEST strip urine
- cut-off: 300 ng/ml

DRUG

MOP

COC

THC

AMP

MTD


MET

ΜΠΜΔ

- 24541 MARIJUANA TEST strip urine - cut-off: 50 ng/ml
- 24542 OPIATES TEST strip urine - cut-off: 300 ng/ml Codes 24540-41-42 are sold in

box of 50 strips individually packed in single pouch.





- 24550 MULTI DRUG PANEL TESTS urine box of 25 tests for 6 drugs\*
  • 24549 MULTI DRUG PANEL TESTS urine
- box of 25 tests for 8 drugs\* 24551 MULTI DRUG PANEL TESTS urine box of 25 tests for 12 drugs

Multi drug tests provide accurate results in 5 min. on the following drugs: amphetamine\*, cocaine\*, marijuana 24551 cannabis\*, methamphetamine\* opiates\*, phencyclidine\*,

barbiturates, benzodiazepines, ecstasy, morphine300, methadone, tricyclic antidepressants. Code 24550 contains tests for drugs with asterisk

\*\*Code 24549 contains tests for drugs with asterisk plus MDMA and 6-AM. Cut-off levels meet SAMHSA

auidelines Manual: GB, FR, IT, ES, DE, PT.



Collect oral fluid

with sponge

 $C \in$ 

# PROFESSIONAL ALCOHOL TESTER • 24491 FIT-333 ALCOHOL TESTER with printer 244

- 24486 AT500 EASY RECALIBRATION ALCOHOL TESTER with printer available jan 2018
- 24487 PRE-CALIBRATED SENSOR MODULE for 24486 spare
- 24494 BLOWING TUBES for 24486, 24491 box of 100 pcs.
- 24495 PAPER ROLLS for 24486, 24491 box of 10

Size: 188x78x33 mm Weight: 300 g

Professional fuel cell sensor breath alcohol tester with printer and touch screen. The fuel cell is a porous disk with a thin layer of platinum. Any alcohol that comes in contact with the cell's surface is broken down chemically. For each broken down molecule of alcohol a given number of electrons are freed.

The numbers of electrons generated are in proportion to the amount of alcohol. Self recalibration (only 24486): easy replacement of pre-calibrated module.

## TECHNICAL SPECIFICATIONS

24491 Colour 3.2 TFT touch screen LCD 5 keys operation: "Up", "Down", "Left", "Right", "OK" Navigation key input with touch page Rechargeable AA battery (about 2500 mAh) Chamber & Sensor warm up automatically

Colour 3.5" touch screen LCD Rechargeable 7.4 V Li-ion battery Automatic flow detection

-20° to +70° (optimal -20° to +40°)

-20 to +45°C (optimal 5 to 40°C)

Windows XP, 7\*\* 10.000-18.000 memories for approx 3.000 full tests

50 000 memories full test driver name, vehicle number, inspector name, test result, with print date and time, location, calibration data, Standard deviation ±0,025 mg/L or ±5% of the measurement

Drift: typically <0,8% of the measurement value/month ——

"Need calibration every 12 months ""Can export files as Microsoft Excel documents directly (24486 only)









## **BREATH ALCOHOL TESTER**

#### • 24500 ALCOHOL TESTER

Display:

Keyboard:

Warm up:

Power Supply:

Data download:

Compatibility:

Memories

Calibration' Unit setting

Auto flow monitoring

Measurement precision

Operating environment:

Compact device to measure your alcohol concentration in your breath Digital/graphic interface and animation, one-hand operation.

% BAC and mg/l values. Supplied in carton box with 3 blowing

tubes Ø 7 mm and one cleaning cap. Multilanguage box and manual: GB, FR, IT, ES, PT

- 24501 BLOWING TUBE box of 12 pcs.
- 32200 "AAA" BATTERIES blister of 4 pieces
- 24503 COUNTER DISPLAY Italian
- 24504 COUNTER DISPLAY English

#### SELF MONITORING

Large display to read exact value of



Battery: 3 x 1.5V AAA batteries (not included) Display: Graphic & Digital display with 3 decimal points (eg. 0.025%BAC) Tolerance compensation: Pre-alert function together

with tri-colour backlighting Breath sampling: less than 5 seconds continuous breath sample

Recycle time: about 20 seconds Size: 107x45x25 mm approx. Weight: 50 g (without batteries) Alert level calibrated: 0.5 % BAC or 0.25mg/l



## POCKET ALCOHOL TESTER

#### • 24499 POCKET ALCOHOL TESTER Pocket, easy to use alcohol tester

TECHNICAL SPECIFICATIONS Range: Low & 0.2 ~ 1.5 %BAC

Accuracy: ± 0.2% BAC at the calibrated point (alert level) Power input: 2 x 1.5V AAA batteries (not included) Display: Digital display

Tolerance compensation: pre-alert function when close to alcohol limit

Auto power off: 2 minutes Breath sampling with auto flow detect: about 6 seconds continuous breath sample Cycle time: about 20 seconds

Alert level calibrated: 0.5% BAC

POCKET, ONLY 8.5x3x1 cm

## SALIVA ALCOHOL STRIPS

• 24502 SALIVA ALCOHOL TEST STRIPS - box of 25 strips GIMA Saliva Alcohol Test Strip is a rapid highly sensitive test for the determination of relative blood alcohol concentration in saliva specimens.

- results in just 3-5 minutes - colour chart provides approximate relative blood alcohol concentrations (BAC)

from 0.02% to 0.30% - no instrumentation is

required - saliva testing avoids urine collection - short expiry date

(average 10-22 months) professional use





# 💄 DRUG OF ABUSE SALIVA MULTITEST - 8 DRUGS

#### • 24566 MULTI DRUG SALIVA MIDSTREAM TEST oral fluid (saliva) - box of 20 tests

A multi parameters, all-in-one test for simultaneous detection

DRUG OF ABUSE SALIVA WULLITEST						
Drug	Cut off	Drug	Cut off			
Opiates	40 ng/ml	Cocaine	30 ng/ml			
Morphine	40 ng/ml	Cannabinoids (THC)	25 ng/ml			
6-MAM	4 ng/ml	Amphetamine, m-Amphetamine	40 ng/ml			
Hydrocodone and Oxycodone	40 ng/ml	MDMA, MDA	50 ng/ml			

of 8 different drugs in 10 minutes. Cost effective system for the screening of workers for illicit substance consumption. Professional use.



## PROTECTIVE GOGGLES



- 25661 POLYSAFE MEDICAL bulk
- 25660 POLYSAFE MEDICAL with box

They are a vital part of any infectious disease control programme for eye protection. They provide a wide field of vision and excellent optical quality. Designed with top and side shields to protect eyes from every angle. They can fit all head sizes comfortably, and have superior optical clarity. Autoclavable, Norms EN 166.



• 25659 GIMASAFE - box of 10 pcs Transparent protective goggle.

€ 89/686 EN 166 / EN 170



#### 25663 HIGH PROTECTION GOGGLES -

#### fog resistant and anti-scratch

Protection against: droplets and splashes of liquids and highspeed particles at extreme temperature. Lateral protection. Protection against large dust particles (>0.5 µ). Protection against optical radiation to standard EN 170. Resistance to surface damage by fine particles. Resistance to fogging of oculars.



 25667 PROTECTIVE GOGGLES 5X7 - fog resistant and anti-scratch Superior quality goggles with excellent optical quality, high protection and maximum comfort. Optical quality: Class I. Protection: protection against high speed particles-low energy and lateral protection. Protection against optical radiations to standard EN 170. Antifog and anti-scratch. Comfort: ultra light, soft pad technology temples, adjustable



• 25644 SAN DIEGO GOGGLES - black - fog resistant 25645 SAN DIEGO GOGGLES - blue - anti-scratch

Temple length and inclination adjustment by snap motion. Protection against high speed particles - low energy and lateral protection. Protection against optical radiation to standard EN 170.



#### • 25260 505 UP GOGGLES - fog resistant, anti-scratch

Protection against high speed particles - low energy and lateral protection. Protection against optical radiation to standard EN 170.

- extremely light 24 g only and encircling
- elastic structure, extremely flexible and resistant
- optimal comfort and fit thanks to the soft adjustable nosepad
- · neck cord included in the packaging



• 25261 506 UP GOGGLES - green - fog resistant, anti-scratch

• 25262 506 UP GOGGLES - pink - fog resistant, anti-scratch Same as 25260 without neck cord, with below additional features:

- panoramic wrapping lens
- temple regulation in length and inclination
- soft terminal tips to eliminate local pressure

## VISOR HEAD MASKS

#### VISOR HEAD MASKS

#### **Great features**

- faceshield with 90° rotation
- inner and outer surface treated against mist
- superior coverage to protect against droplets and splashes Superior materials
- elastic band in anallergic material
- rotation systems in anodized aluminium
- soft support in anallergic interchangeable foam
- faceshield in heat-formed acetate with anti-fog treatment Easy and comfortable use
- fitting headbands adjustable by velcro fasteners
- usable over ophthalmic glasses

GIMA code	VISOR HEAD	Minimum order
25668	VISOR HEAD MASK VISOR SHIELD SPARE SHIELD for 25668	1 1 box of 5

## Antifoa mask ( Class II EN 166-167-168 U1SN 0.7 mm thick 25656 Antifog mask Faceshield with 90° max rotation 25668 25656

## TETI PROTECTIVE SHIELDS

- 30863 TETI PROTECTIVE SHIELD white 1 shield • 30860 TETI PROTECTIVE SHIELD - white - 2
- shields

Comfortable, ultra light stylish protective shields. They provide high protection from squirts and sprays.

Adjustable s
Folding shield behind the nape. to securely Adjustable string Adjustable size, fits majority fasten shield of healthcare professionals. around head Extra wide visor allows to fit over glasses and most of magnification loupes.

Supplied with 2 face transparent shields and 2 padding with velcro (30860) or 1 shield + 1 pack (30863) Certificated EN166. Made in Italy.

• 30875 SET OF 5 TRANSPARENT FACE SHIELDS - spare

30860 Tilting 180 Shield thickness 0.5 mm 30860 or

Super soft padding with velcro

fixing for confortable use



You can create a system adding TETI shield to a IUKO telescope and/or projector

## OP-DOP VISOR SHIELD "PROTECTOR" WITH 3+1 SHIELDS

#### • 25642 VISOR SHIELD "PROTECTOR" - white

The ultra-light face shield that combines function with style: protection: a waterproof plastic barrier will protect you comfort: fast and easy to wear and remove convenience: reusable and replaceable shield optical quality: superior optical quality.

Medium adjustable size: fits over 90% of healthcare professionals. Fits over glasses.

Shielded air vent eliminates fogging.

Supplied with 3 face transparent shields + 1 head shield.

#### 25643 REPLACEMENT SHIELD KIT

**GOGGLES KIT** 

Includes 2 face transparent shields + 1 head shield + 1 foam bumper







25646 GOGGLES KIT - fog resistant

Practical kit composed of 5 supports in different colours and 20 antifog shields. Usable over ophthalmic glasses.

• 25647 SPARE SHIELDS - box of 20

## HIGH PROTECTION MASK 6x1



- 25265 HIGH PROTECTION MASK 6x1 fog resistant, anti-scratch
- wide lens for a field of view without distortion
   temples adjustable in length and inclination with SoftPad technology
- sophisticated indirect ventilation system
- soft internal rubber for comfort without local pressure
- certified according to EN166 point 3 (droplets and splashes) and point 4 (large dust particles)
- supplied with neck cord

## 99% FILTERING 3 PLY MASKS - WITH LACETS OR LOOPS



# 99% FILTERING MASKS MADE IN ITALY - EN 14683:2005



#### • 25648 MASKELLA - face mask with ear loops - light blue

- 3 non-allergenic woven-non woven lavers
- size 90x180 mm
- weight 3 g
- tensile strength extra-long ties: 80 cm
- comfortable, shapeable nose clip - filtering efficiency > 99%
- resistance to breath (MM H<sub>2</sub>O/cm<sup>2</sup>) < 2
- does not contain glass fibres - does not contain latex
- non sterile

  - min. order: 18 packs of 50=900

• 25649 MASKERITA - surgical face mask - 3 non-allergenic woven-non woven layers - size 90x180 mm

- weight 3 g
- tensile strength extra-long lacets: 80 cm
- comfortable, shapeable nose clip
- filtering efficiency > 99%
- resistance to breath (MM H<sub>2</sub>O/cm<sup>2</sup>) < 2
- does not contain glass fibres
- does not contain latex
- non sterile

min. order: 12 packs of 50=600



#### • 25652 MASKOP - ear loop - green • 25654 MASKOP - lacets - light blue Surgical masks with wrap-around visor

- anti-misting, antistatic wrap-around visor - 4 non-allergenic woven-non woven layers
- weight 10.5 g
- atraumatic and conformable nose-clip
- filtering efficiency > 99%
- resistance to respiratory flow (MM H<sub>x</sub>O/cm<sup>2</sup>) <2.5
- latex and glass fibres free. Non sterile
- fluid permeability: impermeable
- external/internal polyethylene anti-misting strip

min. order: box of 50

# 2 PLY MASKS



• 25650 3 PLY MASKS - green

#### • 25651 2 PLY MASKS - light blue box of 2,000 pcs. (40 dispensers of 50 pcs) - 95% filtering mask

- made in soft TNT
- size 17x9 cm with ear loops - comfortable nose band
- antifog, latex free
- EN 14683 conform

# box of 1.000 pcs. (20 dispensers of 50 pcs)

- lightweight and comfortable for soft skin
- size 17x9 cm with ear loops
- comformable nose band for anatomical fitting
- fiber glass free, filtration efficiency of BFE +95% at 1.0 micron
- antifog, latex free
- EN 14683 conform

#### • 25677 MOULDED CONE MASKS - light blue dispenser of 50 pcs.

- splash repellent barrier
- flared edge prevents irritation
- soft, flexible, aluminum nosepiece adjusts for custom fit
- soft, odourless, fiberglass free - high breathability
- non woven fabric

17

## FOLD-FLAT RESPIRATORS FFP1, FFP2, FFP3



Facial filtering respirators to protect against solid (nonoil) and liquid (oil) volatile particles. With exhalation Valve (excluding 25665). Double elastic with buttonhole allows to hang the mask to the neck when it's not worn. Aluminium adjustable nose piece welded with high resistance and internal Polyethylene (PE) Foam nose pad. Single packed guarantees total hygiene and easy maintenance.

GIMA code	PARTICULATE FOLDABLE RESPIRATORS	Minimum order
25666	Particulate respirator - FFP1 - with valve	box of 20
25665	Particulate respirator - FFP2	box of 20
25670	Particulate respirator - FFP2 - with valve	box of 10
25671	Particulate respirator - FFP3 - with valve	box of 10

NORMS: CEI EN 149: 2001 + A1: 2009 AC 538100 05-06-2008



The shape of the respirator has been developed to reduce difficulties of respiration and to improve efficiency in the dialogue. Innovative design allows a perfect view. Wide adaptability to various face contours. Wide filtering area to allow proper ventilation. Light weight.

Conforms to CE standard - EN 149: 2001 + A1: 2009

TECHNICAL SPEC		
25666	25665	256
FFP1	FFP2	FFP

	25666	25665	25670	25671
Protection:	FFP1	FFP2	FFP2	FFP3
Minimum filter efficiency	78%	92%	92%	98%
Exposure limit fine particles up to	4xTLV	12xTLV	12xTLV	50xTLV
Valve	yes	no	yes	yes
Vertically foldable	yes	yes	yes	yes

MATERIALS Elastics: latex-free

Valve: rigid plastic (excluding 25665)
Valve Membrane: Synthetic Rubber (excluding 25665)





## 3M™ EARLOOP MASK 1826 CONE MASKS FFP2, FFP3 with valve • 26006 CONICAL FFP2 MASK WITH

VALVE - box of 10 26007 CONICAL FFP3 MASK WITH VALVE - box of 5

Conical disposable filtering face mask with exhalation valve, for protection against particles and solid or liquid aerosol. Adjustable nose piece and elastic head band. Exhalation valve reduces the accumulation of humidity and heat. Norms: EN 149:2001 + A1:2009. High protection: 94% (FFP2), 99% (FFP3)



26007

## IMPERMEABLE, ABSORBENT, ANTI-SLIP MAT FOR FLOORS

#### IMPERMEABLE ANTI-SLIP ABSORBENT BLUE COLOUR MAT FOR FLOORS

Pre-cut or roll mats to be positioned on the floor of the operating room or near the sink in the pre-operating theatre for holding liquids that could fall on the floor. Mats have high absorbent capacity and optimal speed absorbency. The mats distribute the absorbed liquid by capillary method and maintain it at his internal structure avoiding the lifts on



surface. The special film at rear side blocks the mat on the floor and keeps it stopped without using adhesive matters, which could release glue traces on the floor. They are perfectly adherent at the ground, avoiding risk of accidents. Absorbent rolls

They have 3 different absorbences. Can be cut at desired size. Trolley for rolls

Made in stailess steel with 4 pivoting wheels (2 with brake). Turning base, for rolls with height up to 1 m.

GIMA	ABSORBENT P	RE-CUT MATS	Minimum	
code	Size	Absorbence	order	
25150	90x90 cm	1,700 ml/m <sup>2</sup>	box of 70	
25151	90x120 cm	1,700 ml/m <sup>2</sup>	box of 50	
25152	90x150 cm	1.700 ml/m <sup>2</sup>	box of 40	
25153	90x200 cm	1,700 ml/m <sup>2</sup>	box of 30	
25154	90x250 cm	1,700 ml/m <sup>2</sup>	box of 20	
	ABSOR	BENT ROLLS		
25165	90 cm x 50 m	1,700 ml/m <sup>2</sup>	1	
25166	90 cm x 50 m	2,500 ml/m <sup>2</sup>	1	
25167	90 cm x 50 m	3,500 ml/m <sup>2</sup>	1	
		Y FOR ROLLS		
25169	Trolley for absorbent	rolls	1	



#### VINYL GLOVES:

Sensitivity and protection. Gloves made in polyvinyl chloride, latex-free. Ideal gloves for everyday use, they ensure protection and sensitivity.

Suitable in hospital, ambulatory and for dressing.

Suitable also for laboratory use. Packed in dispenser box of 100 units.

MD class I. PPE cat III. EN455-EN374-AQL<1.5

	Powder free elasticized	Powder free	Pre powdered	VINYL GLOVES - NON STERIL (box of 100)
	25716	25692	25701	Small size - NON sterile
	25717	25693	25702	Medium size - NON sterile
-	25718	25694	25703	Large size - NON sterile

## LATEX GLOVES



#### LATEX GLOVES - ambidextrous - with hem

Pure latex gloves non sterile.

Sensible and resistant, ensure optimal grip and protection. Suitable in hospital, ambulatory and for dressing. Suitable also for laboratory use.

Packed in dispenser of 100 (dispenser of 50 for extra long gloves). Medical device Class I. PPE cat III. EN455-EN374-AOL<1.5

FREE LATEX GLOVES LATEX GLOVES						
Pre	Powder	LATEX GLOVES				
powdered	free	NON STERILE (box of 100)				
25706	25711	Small size - NON sterile				
25707	25712	Medium size - NON sterile				
25708	25713	Large size - NON sterile				
25408	25410	Extra large size - NON sterile				
Pre	Powder	LATEX GLOVES EXTRA LONG				
powdered	free	NON STERILE (box of 50)				
-	25691					

## .ATEX SURGICAL GLOVES - STERILE 🔳 LATEX - EXTRA LIGHT

# 25695

LATEV STEPHE SUBSICAL SLOVES	
LATEX STERILE SURGICAL GLOVES	
The micro textured surface assures a very	
good grip in any different condition of	po
use. High protection and anatomic shape	2
assure a very good comfort.	12
Sterilized by ETO Length 300 mm	1.

Conform to USP: international pharmacopoeia. Packed in dispenser of 50 pairs MD Class II A. PPE cat III. EN455-EN 374-AOL<1.5 25689 25699 Size 8.5 - sterile

		A LUIT SELD			
			LATEX SURGICAL GLOVES STERILE - box of 50 pairs		
	25685	25695	Size 6.5 - sterile		
	25686	25696	Size 7 - sterile		
	25687	25697	Size 7.5 - sterile		
•	25688	25698	Size 8 - sterile		
_	25690	25600	Sizo 9 5 ctorilo		



#### PRO EXTRA LIGHT LATEX GLOVES ambidextrous

Disposable sensitive pure latex gloves non

Suitable for personal protection. AQL <1.5

GIMA code	LATEX GLOVES - box of 100
25420	Small size - non sterile
25421	Medium size - non sterile
25422	Large size - non sterile

## NITRILE GLOVES - POWDER FREE



#### NITRILE GLOVES

Disposable nitrile examination gloves, powder free and latex free, extremely sensitive and resistant.

The micro textured surface ensures an optimal grip. Suitable for use in hospital.

Packed in dispenser of 100. Medical device Class I. PPE (Personal Protective Equipment) cat III. EN455-EN374-AQL<1.5

## ■ NITRILE EXTRA LONG - 400 mm

• 25405 NITRILE GLOVES - extra long - blue

Disposable nitrile examination gloves powder-free and latex free. The micro textured surface assures a very good grip. Suitable in hospital. The 400 mm length and resistance offer high level of protection. Packed in dispenser of 50.

EN455-EN374-AOL<1.5





25416 Medium - non sterile

25417 Large - non sterile

weigth ensure a high level of protection. The micro textured surface ensures a very good grip. Suitable for use in hospital. Medical device. Class I - EN455. PPE (Personal Protection Equipment) Cat III. EN420, EN374, EN388 AOL<1.5

Veloforte

3.5 g\*

25683

25684

25681

25682

ice blue regular blue

25680 25679 25415 Small - non sterile

25396

NITRILE GLOVES

NON STERILE (box of 100)

 $\epsilon$ 

# COPOLYMER GLOVES

COPOLYMER GLOVES ON PAPER Examination gloves, elasticized, medium size, for gynaecological use. MD class 1. • 25714 COPOLYMER GLOVES - non sterile

minimum order: 10 packs of 100 pieces = 1,000 pcs. • 25709 COPOLYMER

**GLOVES** - sterile Sterilized by ETO. AQL <1.5 IV Individually packed. minimum order: pack of 100 pieces



# GLOVES DISPENSER



257x100xh 134 mm

Weight: 322 g

#### • 25430 GLOVES DISPENSER

Holds a standard box of 100 gloves. It is made of unbreakable washable thermoplastic material. It can be easily hung to the wall (screw not included) and into ambulances in a vertical or horizontal position. It is made of two parts: the base, which is fixed and the cover, which can be easily removed once the box of gloves needs to be replaced.

## COTTON GLOVES

and latex-free. The 300 mm length and 5.7 g

White	Size	С	igth m max	9	ight g max	Minimum order	
25864	Size 6.5	20	22	18	20	box of 10 pairs	
25865	Size 7	21	23	19	21	box of 10 pairs	
25866	Size 7.5	23	25	21	23	box of 10 pairs	
25867	Size 8	24	26	23	25	box of 10 pairs	
25868	Size 8.5	25	27	25	27	box of 10 pairs	
25870	Mixed sizes					box of 10* pairs	long cuff
						-	

1x size 6.5 and 8.5, 2x size 7 and 8, 4x size 7.5

## DRACULA



• 25700 DRACULA Universal holder for gloves and tissue boxes, with little sharp teeth which automatically adjust to tightly hold any size of box. It's a universal holder that allows one-hand operation.

or minimum 500 pcs we can put your

## LATEX FINGER COTS

• 25941 LATEX FINGER COTS - medium • 25942 LATEX FINGER COTS - large

Latex finger cots to cover 1 finger. Non sterile, single use, for finger protection, with talc.

minimum order: 1.000 pcs. (10 bags of 100 pcs.)



## NON WOVEN SURGICAL SPECIALISTIC GOWNS - STERILE

#### SURGICAL SPECIALISTIC GOWNS

Specialistic, water repellent, breathable gowns for a barrier effect to fluids and bacteria

- cotton cuffs 8 cm
- ultrasonic welding
- neck velcro closure
- 4 waist straps for internal and external closure


#### Pre folded

For easy programmed dressing

Welded reinforcement (only 21015, 21016) Water-proof, breathable reinforcement on front and on sleeves ultrasonic welded

All gowns include two dry-paper towels. Conforms to UNI EN ISO 13795. Made in Italy.





aowns

DISPOSABLE GOWNS DISPOSABLE SURGICAL GOWNS - green

Disposable non-woven gowns, suitable when comfort and light protection are required

Colour: green Grams: 25 g/m<sup>2</sup> One size: 110x136 cm With cotton cuffs (26100 only).

NON WOVEN GOWNS

Minimum 26099 Disposable Gowns - sterile box of 50 26100 Disposable Gowns - non sterile bag of 10

26100



DISPOSABLE POLYTHENE GOWNS - green Surgical polythene gowns with neck and waist laces and cotton cuff. Made in waterproof non-woven fabric. One size 115x140 cm

Available sterile or non sterile. Made in Italy.


GIMA code	POLYTHENE GOWNS	Minimum order
26092	Poly Gowns - sterile	box of 50
26093	Poly Gowns - non sterile	box of 100

## NON-WOVEN UNIFORM, JACKET AND PANTS COLONSCOPY PANTS



- 26076 UNIFORM COAT+PANT S
- 26077 UNIFORM COAT+PANT M
- 26078 UNIFORM COAT+PANT L
- 26079 UNIFORM COAT+PANT XL minimum order: box of 50 - non sterile

Short sleeve jacket "V" neck, with 3 pockets. Pants with rear pocket, closure by laces.



- 26023 JACKET WITH BUTTON L
- 26024 JACKET WITH BUTTON XL
- 26027 JACKET AND PANTS L
- 26028 JACKET AND PANTS XL minimum order: box of 50 - non sterile

Jacket long sleeve, neck and cuffs made of elastic polyester. Front opening with snap buttons. 2 front pockets. Pants with laces and rear pocket.



#### 21030 COLONSCOPY PANTS

minimum order: box of 50 - non sterile Colonscopy pants, fit all sizes, length 110 cm. Flastic waist rear opening with velcro fixina.

Made in water-repellent non-woven SMS

## DISPOSABLE KITS FOR PATIENT/VISITOR DRESSING - NON STERILE

• 26017

KIMONO - blue

- box of 100

Opaque non-woven SMS kimono 40 a/m<sup>2</sup> with short-sleeves. Front opening and closing at the waist with laces. One size: length 115 cm, width 140 cm.



26018 PATIENT DRESSING KIT - box of 25 Kit includes kimono, round cap with elastic band and shoe-covers.



• 26019 VISITOR DRESSING KIT - box of 25 Kit includes gown for visitor, round cap with elastic band, three layers mask with ear loops, polyethylene shoe-covers.

25202

## C-FOLD AND V-FOLD HAND TOWELS



• 25200 C-FOLD HAND TOWELS - pack of 150 pcs. Pure cellulose, 1 ply. Size 23x33 (folded 23x11 cm).

For C and V fold hand towels

• 25205 DISPENSER

Pure wadding of cellulose, 2 plies (36 g/m<sup>2</sup>: 2x18 g/m<sup>2</sup>). minimum order: box of 24 packs

Size: 25x22.6 cm (folded 25x11.3 cm)

• 25202 V-FOLD HAND TOWELS - 2 plies - pack of 160 pcs. minimum order: 3,200 (20 packs of 160)

25210



25205

25210 HAND TOWEL ROLLS Pure cellulose, 2 plies (36 g/m<sup>2</sup>). Size 23x24 cm. N. of sheets: 252. minimum order: box of 12 rolls 25215 DISPENSER For hand towel rolls

25215

ABSORBENT NON WOVEN WIPES 🔳 HAND TOWELS ROLLS



Non woven absorbent wipes for sanitary, health and hygienic use. Made of wood pulp, PES, spunbonded PP.

ABSORBENT NON WOVEN WIPES Size cm\* Weight g order 1.400 pcs\*\* 25221 Smooth 30x40 45-50 1.400 pcs\*\*\* 25222 Smooth - folded 30x40 45-50 **25223** Microembossed - folded 20x40 45-50 1.400 pcs\*\*\* "14 boxes of 100 Size accuracy: ±5% "28 boxes of 50

## FOLDED NAPKINS

#### FOLDED NAPKINS

Pre-coated folded napkins, made of 2 plies of pure cellulose wadding laminated with 1 ply of polyethylene, or 1 ply of pure cellulose wadding laminated with 1 ply of polyethylene. The special features of materials offer high absorbency and waterproofness to assure high comfort to the patient.

FOLDED NAPKINS - pack of 500 pcs Napkins 2+1 (2 plies cellulose + 1 ply polyethylene) 25230 Napkins 33x45 cm green 25231 Napkins 33x45 cm - Íiaht blue

25232 Napkins 33x45 cm - pink 25233 Napkins 33x45 cm white Napkins 1+1 (1 ply cellulose + 1 ply polyethy

25226 Napkins 33x45 cm - blue 25227 Napkins 33x45 cm - lilac 25228 Napkins 33x45 cm - orange

25240 Plastic dispenser

25239 Chain for napkins

# BOUFFANT, SURGEON CAP SHOE COVERS

25675 BOUFFANT CAP - light blue Minimum order: 1,000 pcs (10 bags of 100 pcs)
 made of light weight PPSB

- breathable, soft, comfortable - elastic headband

medium size 21


25675 • 25678 SURGEON CAP - green • 25655 SURGEON CAP - light blue Minimum order: 1,000 pcs (10 bags of 100 pcs)

ne)

• 25690 SHOE COVERS - light blue box of 100

25676 SHOE COVERS - light blue Carton of 2,000 pcs (20 bags of 100 pcs)
- made of PPSB, breathable

comfortable with elastic band



## BIBS

• 25672 BIBS - roll of 80 50x60 cm Made of 2 plies, one of highly absorbent cellulose tissue and one of waterproof polyethylene. Extremely soft and comfortable, they assure an excellent protection to the

patient. Each roll has 80 bibs with pre-cut and comfortable ribbons or bi-adhesive.

Minimum order: box of 6 rolls

## DOCTOR'S WHITE AND SURGICAL COATS, JACKETS, TROUSERS



#### 100% COTTON COATS, TROUSERS AND JACKETS

Professional and stylish line with all sizes for men and women. pockets. 1 breast pocket and half belt. Woman and man models made in high quality 100% cotton. Doctor's white coats have 2 side have buttons, unisex model has press studs and elasticated cuffs.

THEATRE GOWNS - GREEN					
Size	Man-woman				
52-56	26162				
58-62 26163					

jackets at page 21.

DOCTOR'S WHITE COATS 100% COTTON						JACKETS				
	Size		Woman	Man	Unisex	Size	White	Green	Light Blue	Fantasy
urope	USA	France	with button	with button	with press stud	XS	26124	26126	26128	-
40	XS	36	26110	-	26080	S	26130	26140	26150	26170
42	S	38	26111	-	26081	M	26131	26141	26151	26171
44	S	40	26112	26098	26082	L	26132	26142	26152	26172
46	M	42	26113	26101	26083	XL	26133	26143	26153	26173
48	M	44	26114	26102	26084	XXL	26134	26144	26154	-
50	L	46	26115	26103	26085			TROUSE	RS	
52	L	48	26116	26104	26086	XS	26125	26127	26129	-
54	XL	50	26117	26105	26087	S	26135	26145	26155	-
56	XL	52	-	26106	26088	M	26136	26146	26156	-
58	XXL	54	-	26107	26089	L	26137	26147	26157	-
						XL	26138	26148	26158	-
						XXL	26139	26149	26159	-

#### 60% COTTON - 40% POLYESTER COATS, TROUSERS AND JACKETS Professional and stylish line with all sizes for men and women,

olvester. 1 breast pocket. Man and woman model (weight 190 g) have buttons, unisex model (weight 170 g) has hidden press studs and elasticated cuffs. White jackets

made in 60% high quality cotton and 40% po Doctor's white coats have 2 side pockets and								
DOCTOR'S WHITE COATS 60% COTTON - 40% POLYESTER								
	Size		Woman	Man	Unisex			
Europe	USA	France	with button	with button	with press stud			
38-40 42-44	XS S	36 38-40	21401 21402	- 21412	21421			
46-48	М	42-44						
50-52	L	46-48						
54-56 58-60	XL	50-52 54-56	21405				١.	
62-64	XXXL	58-60	-	21416 21417			X	
02-04			-		21427		_	
Composi			PECIFICA % cotton		lucetor			
Weight:	LIOII.	00	76 COLLOII		00 g/m <sup>2</sup>		Т	
Yarn cou	nt - wa	rp:			20 ± 2			
Yarn cou	nt - we	ft:		Ne	16 ± 2			
	Construction - warp: 42 ± 3							
Construction - weft: $19 \pm 3$								
Breaking strength - warp: 98 kg -5%								
Breaking strength - weft: 39 kg -5% Fastness to washing: 4								
				cross	e resist			
Treatments and finishing: crease resist								

Dimensional stability - washing at 90°C:

JACKETS 60% COTTON - 40% POLYESTER									
Size White Green Light Blue Any									
XS	21431	21441	21451	21471					
S	21432	21442	21452	21472					
M	21433	21443	21453	21473					
L	21434	21444	21454	21474					
XL	21435	21445	21455	21475					
XXL	21436	21446	21456	21476					
XXXL	21437	-	21457	21477					
	1	TROUSER:	S						
XS	21491	21501	21511	21551					
S	21492	21502	21512	21552					
M	21493	21503	21513	21553					
L	21494	21504	21514	21554					
XL	21495	21505	21515	21555					
XXL	21496	21506	21516	21556					
XXXL	21497	-	21517	21557					

1	٥.	ured jacket 20 COLOURS		Г*
	Tan	Coco beige	Pale grey	Virtual grey
	Vert anis	Artic green	Verbena	Empire rea
	Aqua	Prissy pink	Iride	Smokeberry
	Menthe	Doe	Yellow	Sun orange
	New azur		Navy	NYCO khak
		50 days. Specify ler 100 mixed pi		

 21398 EMBROIDERY ON COTTON-POLYESTER COATS/JACKETS ONLY

Possibility of 1 or 2 colour logo, ize 8-10 cm x 2-3 cm on coats and jackets.

## JACKETS WITH PRESS STUD AND TROUSERS



JACKETS WITH PRESSURE STUD								
			Woma	an		Un	isex	
	Size	White	Violet	Colour on request	White	Blue navy	Light blue	Colour on request
	XS	21561	2157	1 21591	21601	21611	2162	1 21651
	S	21562	2157	2 21592	21602	21612	2162	2 21652
	M	21563	2157	3 21593	21603	21613	2162	21653
	L	21564	2157	4 21594	21604	21614	2162	4 21654
	XL	21565	2157	5 21595	21605	21615	2162	21655
	XXL	21566	2157	6 21596	21606	21616	2162	6 21656
			T	ROUSER	S - UNI			
	Size	.   '	White	Violet	Blue		ght lue	Colour on request*
	XS	2	1491	21521	2153	1 21	511	21551
	S	2	1492	21522	2153	2 21	512	21552
	M	2	1493	21523	2153	3 21	513	21553
	L	2	1494	21524	2153	4 21	514	21554
	XL	-	1495	21525	2153		515	21555
	XXI	_ 2	1496	21526	2153	5 21	516	21556
	XXX	L 2	1497	-		21	517	21557

TECHNICAL SPECIFICATIONS	ī
Composition: 60% cotton - 40% polyester	
Weight: 200 g/m <sup>2</sup>	
Yarn count - warp: Ne 20 ± 2	
Yarn count - weft: Ne 16 ± 2	
Construction - warp: 42 ± 3	
Construction - weft: 19 ± 3	
Breaking strenght - warp: 98 kg -5%	
Breaking strenght - weft: 39 kg -5%	
Fastness to washing: 4	
Treatments and finishing: crease resist	
Dimensional stability - washing at 90°C: 3%	

Dimensiona	i stability - wa	sning at 90 C.	3 70					
20 COLOURS ON REQUEST*								
	* U.S.							
Tan	Coco beige	Empire red	Virtual grey					
Iaii	Coto beige	Linpire rea	vii tuai grey					
Vert anis	Artic green	Verbena	Kelly green					
100								
Aqua	Prissy pink	Iride	Smokeberry					
		1 18	MALAN AND AND AND AND AND AND AND AND AND A					
Menthe	Doe	Yellow	Sun orange					
RC blue		New azur						
	60 days. Specify							
Ainimum order 100 mixed pieces same colour								

## SURGICAL CAPS

100% cotton surgical cap with fantasy pictures or green.

on ba

• 26166 GREEN CAP

hidder

Two pockets

and 1 breast pocket

with 2 front pockets and 1 on back

- 26165 FANTASY CAP light blue • 26167 FANTASY CAP - beige
- 26168 FANTASY CAP red

Other colour on request, Minimum order 1,000 pieces.









## **DENTAL JACKETS**

DENTAL JACKETS

Short sleeves round-necked jacket with 2 buttons on right shoulder and 5 hidden buttons.

One pocket and one breast pocket. Green colour 100% pure cotton.

	DENTAL JACKET
Size	Unisex green
XS	21000
S	21001
M	21002
L	21003
XL	21004
XXL	21005

## PROFESSIONAL ULTRALIGHT SHOES



#### GIMA ULTRA LIGHT SHOES

Protective shoes meeting requirements of working shoes norms EN ISO 20347: A E SRC

- extremely light: only 200 g per pair - aerated: lateral holes provide aeration but avoid liquid dropping in
- anatomic: respect natural foot anatomy - antishock: maximum energy absorption in the heel zone
- antislip: the unique design of the sole's tread meet the SRC requirements regarding the slipping resistance
- antistatic: antistatic non marking element in the heel zone working even after many
- washable up to 50°C: with normal neutral detergents, resistant to chemicals or UV sterilizations used in hospitals
- antibacterial, antimould, antifungus

ULTR	A LIGHT	SHOES
Size	White	Blue
34	20000	20020
35	20001	20021
36	20002	20022
37	20003	20023
38	20004	20024
39	20005	20025
40	20006	20026
41	20007	20027
42	20008	20028
43	20009	20029
44	20010	20030
45	20011	20031
46	20012	20032
47	20013	20033

## ANTISTATIC CLOGS - AUTOCLAVABLE AT 134°C



#### GIMA PROFESSIONAL CLOGS

- active arch support to stimulate circulation antistatic material directly injected in the polymeric blend perforated sole for breathability and transpiration
- antislip grooved sole safe on wet floor
- machine washable, sterilizable at 134°C
- available also with strap for extra security (26471-26482)
- individually packed in carton box
- all models (with or without pores, with or without straps)



	UPPER WITHOUT PORES						UPPE	R WITH F	ORES		
Size	White	Green	Electric Blue	Orange	Fuchsia	White with strap	White	Yellow	Blue	Violet with strap	Green with strap
34-35	26311	26331	26351	26371	-	26231	26411	-	26451	-	26471
35-36	26312	26332	26352	26372	-	26232	26412	-	26452	-	26472
36-37	26313	26333	26353	26373	-	26233	26413	-	26453	-	26473
37-38	26314	26334	26354	26374	26394	26234	26414	26434	26454	26254	26474
38-39	26315	26335	26355	26375	-	26235	26415	_	26455	26255	26475
39-40	26316	26336	26356	26376	-	26236	26416	-	26456	26256	26476
40-41	26317	26337	26357	26377	-	26237	26417	-	26457	26257	26477
41-42	26318	26338	26358	26378	26398	26238	26418	26438	26458	26258	26478
42-43	26319	26339	26359	26379	26399	26239	26419	26439	26459	26259	26479
43-44	26320	26340	26360	26380	26400	26240	26420	26440	26460	26260	26480
45-46	26321	26341	26361	26381	-	26241	26421	-	26461	-	26481
47-48	26322	26342	26362	26382	-	26242	26422	-	26462	-	26482

WITH MOVABLE STRAP

WITH OR WITHOUT PORES



Blue

26190 26210 26175

26191 26211 26176

26192 26212 26177

26193 26213 26178

26194 26214 26179

26195 26215 26180

26196 26216 26181

26197 26217 26182

26198 26218 26183

43 26199 26219 26184

35

37

39

40

41

## ULTRA LIGHT CLOGS WITH STRAP



#### GIMA ULTRA LIGHT CLOGS

Protective clogs meeting requirements of working shoes norms EN ISO 20347 A E SRC **ULTRA LIGHT CLOGS** 

- extremely light: only 200 g per pair

- aerated: lateral holes provide

aeration but avoid liquid dropping in

- anatomic: respect natural foot anatomy

- antishock: maximum energy

absorption in the heel zone - antislip: the unique design of the sole's tread meet the SRC

resistance - antistatic: antistatic non marking element in the heel zone working

even after many washing - washable up to 50°C: with normal

neutral detergents, resistant to chemicals or UV sterilizations antibacterial, antimould, antifungus

olour - minimum 50 pair					
	47	26203	26223	26188	
	46		26222		
	45	26201	26221	26186	
	44		26220		

• 26206 ULTRA LIGHT CLOGS - other co (available in light blue, orange, black, fuchsia)

## SILICONE NURSE WATCHES





#### NURSE WATCHES Silicone nurse watches, provided with a Suitable to measure patient pulse, beat and sterilization

procedure timing. Conforming to procedures not allowing nurses to wear wrist watches. Japan movement, watch case 35 mm, watch length 85 mm.

Shelf life of battery: 18 months from the day of first use. Manual: GB, FR, IT, ES, PT, DE, GR, PL, Arab

Silicone straps - spare

20418 Kit of 6 silicone straps\* 20480 Blue



Digital\*\*

20480

GIMA	SILICONE WATCHES	GIMA	SILICONE WATCHES
code	Round - single colour	code	Round - single colour with aluminium box
20400	White	20410	White
20401	Blue	20411	Blue
20402	Red		Squared - single colour
20403	Purple		with aluminium box
20404	Pink	20455	Blue
20405	Black		
20403			
20403	Round - fantasy		Squared - fantasy
20420		20460	Squared - fantasy Violet and sky blue
	Round - fantasy Red & white Colour fantasy	20460 20461	Violet and sky blue Hearts
20420	Round - fantasy Red & white Colour fantasy Zebra		Violet and sky blue
20420 20421	Round - fantasy Red & white Colour fantasy	20461	Violet and sky blue Hearts
20420 20421 20422	Round - fantasy Red & white Colour fantasy Zebra	20461 20462	Violet and sky blue Hearts Flowers

## NURSE STAINLESS STEEL SCISSORS AND FORCEPS





20529

Straight scissors blunt/sharp - 14 cm

## STAINLESS STEEL UTILITY AND BANDAGES SCISSORS

Hearts



All purpose, first aid scissors, easily cut bandages, leather and plaster casts. Autoclavable at 136°C. Instructions: GB, FR, IT, ES, PT, DE.

	UTILIT	Y SCISSORS	- box of 10	
12 cm - 4.7"	16.5 cm - 6.5"	19 cm - 7.5"	Colour	
20560	20570	20580	Black	
-	20571	20581	Blue	- 74
-	20572	20582	Red	- Decement of
-	20573	20583	Purple	1
-	20574	20584	Pink	San Constant
20590	Steel chain	for scissors a	and forceps	20590

## BI-LAYER NON-WOVEN FABRIC STERILE SURGICAL DRAPES



All surgical drapes are made in light-blue bi-layer waterproof non-woven fabric 54 g/m<sup>2</sup>. Individually packed in PE bag, sterile (Ethylene oxide), latex free

GIMA code	DRAPES	Minimum order
	Drape 50x50	box of 100
	Drape 50x75	box of 100
23602	Drape 75x90	box of 75
23604	Drape 100x100	box of 50
23606	Drape 120x150	box of 50
23608	Drape 150x200	box of 25

DRAPES WITH ADHESIVE SIDE



DRAPES WITH

ADHESIVE SIDE


23610 Drape 50x50

23611 Drape 50x75

23612 Drape 75x90 23614 Drape 100x100 23617 Drape 180x200 23618 Drape 150x240

	,	
Minimum order	GIMA code	DRAF
box of 100	23620	Drape
box of 100	23622	Drape
box of 75	23623	Drape
box of 50	23624	Drape
box of 25	23625	Drape
box of 25	23626	Drape

#### DRAPES WITH CENTRAL ADHESIVE HOLE



Drape with hole Ø 10 cm Drape with hole 6x9 cm

GIMA	DRAPES WITH CENTRAL	Minimum
code	ADHESIVE HOLE	order
23620	Drape 50x75 - hole 6x9 cm	box of 75
23622	Drape 75x90 - hole 6x9 cm	box of 75
23623	Drape 75x90 - hole Ø 10 cm	box of 75
23624	Drape 100x100 hole Ø 10 cm	box of 50
23625	Drape 100x150 - hole 9x18 cm	box of 25
23626	Drape 120x150 - hole Ø 10 cm	box of 25

## NON-WOVEN FABRIC STERILE OPHTHALMIC SURGERY DRAPES

Hole 6x9 cm with incision film. Single bag to receive fluids and adaptable



Hole 10x10 cm with incision film. Double bag to receive fluids with adaptable bar



• 23635 OPHTHALMIC SURGERY DRAPE 160x160 cm - sterile - box of 15

Hole Ø11 cm with incision film Double bag 35x73 cm to receive fluids with adaptable bar and adaptable bar for nasal septum. Wrapped in crepe paper.

 23636 OPHTHAI MIC SURGERY DRAPE 160x260 cm - sterile box of 10

## SURGERY COTTON DRAPES 🔲 INCISION FILM - STERILE



• 23634 OPHTHALMIC SURGERY DRAPE

80x100 cm - sterile - box of 40

• 26495 DRAPE 90x150 cm

 26496 DRAPE 150x150 cm

• 26497 DRAPE 250x150 cm Made in 100% high quality cotton, green colour

Made in Europe



It is applied at the point where the wound is, to protect it from possible contamination Incision film made of adhesive polyurethane

GIMΔ Minimum SIZE AxB SIZE AxC code 23628 45x50 cm 45x40 cm box of 10 30x35 cm 30x25 cm box of 50 23630 23631 45x50 cm 45x40 cm box of 50

C

60x55 cm

box of 50

## POLYESTER OR MICROFIBRE SURGERY DRAPES

#### 100% TEXTURIZED POLYESTER DRAPES

Studied for replacing the classic cotton drape in operating rooms.

- it does not have particles release of dust Polyester texturized fabric or cotton fibers that could cause infections during surgery

- various usability on the field:

- as a sheet under the patient
- as a towel
- to tamponage, considering its high absorbency
- as a pre or post surgery cover, thanks to the capability of keeping a good body temperature
- 41000 POLYESTER DRAPE 90x150 cm light blue
- 41001 POLYESTER DRAPE 150x150 cm light blue
- 41002 POLYESTER DRAPE 250x150 cm light blue

### MICROFIBRE DRAPES

(99% polyester + 1% carbon fibre)

The microfibre line is conceived for operating room.

The characteristics and abilities are various:

the fabric does not absorb liquids, maintaining the operating field dry;

60x65 cm

- the fabric does not have particles release of dust or fibre that could cause infections on the patient.


GIMA fabric is composed of polyester and carbon fibres. The addition of carbon fibres serves as protection from potential electric discharges.

- 41009 MICROFIBRE DRAPE 90x150 cm green
- 41010 MICROFIBRE DRAPE 150x150 cm green
- 41011 MICROFIBRE DRAPE 250x150 cm green


Sizes of drapes may vary ±5% due to fabric processing during production phase

27

# STERILE SURGERY SETS



- 23640 UNIVERSAL SET sterile box of 10
- 1 table cover 150x200 cm with central absorbent band
- 1 Mayo stand cover 80x145 cm
- 1 standard surgical drape,
- 150x240 cm with adhesive tape 1 standard surgical drape,



• 23641 GYNAECOLOGY SET - sterile - box of 8

Non woven SMS fabric orthopaedy set for hand surgery - sterile

• 23643 SET FOR HAND SURGERY - sterile - box of 8

- 180x200 cm with adhesive tape 2 standard surgical drapes, 75x90 cm with adhesive tape
- 4 towels 35x40 cm 1 adhesive strip 10x50 cm

1 tube holder 2.5x20 cm

- 1 gynaecology drape for
- 1 table cover 150x200 cm with central absorbent band with filter and drain valve
- lithotomy position 290x240 cm 3 adhesive strips 10x50 cm with adhesive hole, built-in 4 towels 35x40 cm
- leggings, bag for liquid collection 1 Mayo stand cover 80x145 cm 1 drape 75x90 cm 1 incision film 35x50 cm



#### • 23642 SET FOR KNEE ARTHROSCOPY - sterile - box of 8

Non woven bi-layer fabric orthopaedy set for knee arthroscopy - sterile

- 1 table cover 150x200 cm with absorbent central band
- 1 Mayo stand cover 80x145 cm
- 1 standard surgical drape, 150x180 cm
- 1 orthopaedy drape for
- arthroscopy at knee 230x320
- cm with elastic hole and bag for liquid collection
- 1 stockinette 22x75 cm
- 3 adhesive strips cm 10x50 cm 4 towels 35x40 cm
- 1 standard surgical drape, 100x100 cm 2 towels 35x40 cm
- 1 table cover 150x200 cm with 1 T-shape drape for hand central absorbent band surgery 370x190x290 cm with elastic hole 5 cm and cable fixing Velcro strips




#### Non woven SMS fabric obstetrics set for caesarean section - sterile

- 23644 SET FOR CESAREAN SECTION sterile box of 8 1 table cover 150x200 cm with
- central absorbent band
- 1 Mayo stand cover 80x145 cm
- 1 drape for caesarean section
- incision film and bag for liquid collection 1 drape "baby blanket" 75x90 cm

#### 1 table cover 150x200 cm with central absorbent band 1 urology drape for TUR, 200x280x220 cm with perineal and subpubic holes,

Non woven SMS fabric urology set for TUR - sterile

- 23645 UROLOGY SET FOR TUR sterile box of 8 bag for liquid collection with filter, adhesive tape and straps 1 camera drape 13x250 cm
  - 2 towels 35x40 cm



• 23650 Table cover 150x200 cm - sterile - box of 20



• 23654 Adhesive pocket for tools 35x42 cm - box of 100



 23651 Mayo stand cover 80x145 cm - sterile - box of 40



• 23655 Camera drape 13x250 cm - box of 100



• 23652 Drape, 200x240 cm with • 23653 Pair of leggings 75x130



PF Sterile

ments 75x90 cm - box of 100





adhesive U shape cut - box of 15 cm for urology/gynaec. - box of 20



28

# TUNGSTEN CARBIDE INSTRUMENTS - GOLD LINE

#### **GOLD LINE - TUNGSTEN CARBIDE INSTRUMENTS**

A top quality theatre use Tungsten Carbide Instruments made in stainless steel AISI 410 (AISI 420 for scissors) with very hard tips made in Germany to help surgeons perform precision surgeries with best results. Highly reliable for hardness and corrosion resistance



26539 Mayo Hegar needle holder - 14 cm 26530 Mayo Hegar needle holder - 16 cm 26531 Mayo Hegar needle holder - 18 cm 26532 Mayo Hegar needle holder - 20 cm

26535 Mayo Hegar needle holder - 24 cm 26533 Mayo Hegar needle holder - 26 cm 26534 Mayo Hegar needle holder - 30 cm

26549 Derf needle holder - 12 cm

# **TUNGSTEN CARBIDE FORCEPS - AISI 410** LONG LASTING JOINT **GERMAN TIPS**

26560 Adson - 12 cm 38552 Cushing forceps - 18 cm 26561 Adson 1x2 teeth - 12 cm

26563 Micro Adson forceps - 15 cm - 1x2 teeth

26562 Micro Adson forceps - 12 cm - 1x2 teeth 38554 Cushing Taylor forceps - 18 cm - rough tips 26570 Wire Cutter - 14 cm - for soft wires 0-1 mm



26558 Gillies Dissecting forceps - 15 cm - 1x2 teeth 38560 Gerald forceps - 17 cm - rough tips

26565 Potts Smith Dissecting forceps - 15 cm

26566 Potts Smith Dissecting forceps - 18 cm 26567 Potts Smith Dissecting forceps - 20 cm 26568 Potts Smith Dissecting forceps - 23 cm 26569 Potts Smith Dissecting forceps - 25 cm 38565 Mc Indoe forceps - 15 cm - rough tips

# TC MICRO NEEDLE HOLDER - AISI 410



26550 Castroviejo Needle Holder straight - 14 cm - plain tip 26552 Castroviejo Needle Holder curved - 14 cm - plain tip 26553 Castroviejo Needle Holder straight - 14 cm - rough tip 26555 Castroviejo Needle Holder curved - 14 cm - rough tip 26551 Castroviejo Needle Holder straight - 18 cm - rough tip 26556 Castroviejo Needle Holder straight - 21 cm - rough tip 26557 Castroviejo Needle Holder curved - 21 cm - rough tip







38600 Barraquer Micro needle holder - 13 cm smooth tips - with lock



38610 Arruga needle holder - straight - 16 cm plain tips 38611 Arruga needle holder - curved - 16 cm plain tips

# **TC WIRE CUTTERS - AISI 410**



26571 Wire Cutter - 18 cm - for hard wires cutting up to 1.6 mm 26572 Wire Cutter - 23 cm - for hard wires cutting up to 2.0 mm



26575 Wire holding - 18 cm

TC ORGAN HOLDING FORCEPS - AISI



# TUNGSTEN CARBIDE INSTRUMENTS - GOLD LINE




razor-sharp upper blade edge that cuts effortlessly

hlade has micro-fine serrations to hold tissue and

• 26488 METZENBAUM SCISSORS SUPER CUT - curved - 15 cm

• 26489 METZENBAUM SCISSORS SUPER CUT - curved - 18 cm

rough tissue. The lower



for suture

26722 Michel stitch remover forceps - 12 cm

26900 Heaths ligature scissors - 15

26827 Umbilical scissors Usa model

26874 Brown Sadler episiotomy scissors

**DELIVERY SCISSORS** 

# 26824 Iris scissors - curved - 11.5 cm **DERMATOLOGY PROBES**

26822 Iris scissors - straight - 11.5 cm

Straight



Round forceps - 9 cm

26823

PROBES, SCALPELS


26956 Ribbon scissors - straight - 9.5 cm

26957 Ribbon scissors - curved - 9.5 cm

26958 Ribbon scissors - straight - 12 cm

Ribbon scissors - curved - 12 cm

Blunt/blunt straight



26702 Butterfly probe - 14 cm

• 26485 MAYO SCISSORS SUPER CUT WITH T.C. - curved - 14 cm • 26486 MAYO SCISSORS SUPER CUT WITH T.C. - curved - 17 cm

• 26487 MAYO SCISSORS SUPER CUT WITH T.C. - curved - 20 cm

Tungsten carbide insert with micro-

fine serrations

# STAINLESS STEEL SURGICAL FORCEPS








26724 Forceps thin end - 12 cm

26977 English Toe plain dissecting forceps - 14 cm

# 26833 Kocher forceps - curved - 18 cm - 1x2 26834 Kocher forceps - curved - 20 cm - 1x2 26695 Micro Adson forceps - 12 cm - 1x2 26749 Klemmer forceps - straight - 14 cm 26709 Klemmer forceps - straight - 16 cm 26835 Klemmer forceps - straight - 18 cm Klemmer forceps - straight Klemmer forceps - curved 26837 Klemmer forceps - curved - 16 cm Klemmer forceps - curved 26839 Klemmer forceps - curved 26978 Mixter forceps - 23 cm ANESTHESIA FORCEPS







# S/S DRESSING, SUTURE AND DELIVERY SURGERY SETS



26963 DRESSING SET - 8 PIECES 26965 SUTURE SET - 12 PIECES



Kocher artery forceps curved - 16 cm Dressing Forceps (Thumb) - 16 cm English TOE dissecting forceps - plain - 14 cm English TOE dissecting forceps - plain - 18 cm Dissecting forceps toothed 1x2 - 14 cm Suture scissors - Heaths Ligature - 15 cm Mayo scissors - straight - 15 cm Operating scissors sharp/blunt - straight - 15 cm 2 ncs Operating scissors sharp/blunt - curved - 15 cm 2 pcs Rampley sponge holding forceps - str. - 18 cm Rampley sponge holding forceps - str - 24 cm Museux Vulsellum forceps 8 mm - str. - 24 cm 2 pcs Cusco vaginal specula - small Cusco vaginal specula - medium Cusco vaginal specula - large Sims vaginal specula - smal Sims vaginal specula - medium Sims vaginal specula - large Imbilical scissors USA Patent - 10.5 cm instrument tray with lid 25x30x6 2 cm Instrument tray with lid 30x20x5 cm Instrument tray with lid 45x30x6.2 cm

SET CONTENTS

Kidney Dish 20 cm (8") - medium Kidney Dish 25 cm (10") - large


Gallipot 150 ml - 6 oz - medium


Mayo Hegar needle holder - 18 cm

Brown Sadler episiotomy scissors - 14 cm

Kocher artery forceps - straight - 16 cm Kocher artery forceps straight - 18 cm

# GYNAECOLOGY INSTRUMENTS AND KIT





34005 Collin Forceps - 20 cm

34001 Magill Forceps - 15 cm - infants 34002 Magill Forceps - 20 cm - children 34003 Magill Forceps - 25 cm - adults

26979 Museux Vulsellum forceps 8 mm straight - 24 cm BONE CUTTING FORCEPS

26983 Luer forceps - 15 cm - sharp edge

26984 Ruskin Liston forceps - 18 cm

26988 Rampley forceps - 25 cm


26811 Bozeman dressing forceps straight - 26 cm 26812 Bozeman dressing forceps curved - 26 cm

with ★ in a nylon bag.


# ENT STAINLESS STEEL INSTRUMENTS AND KIT



# LARYNGEAL MIRRORS AND SPIRIT LAMP



# PODIATRY-CHIROPODY STAINLESS STEEL INSTRUMENTS



# PODIATRY STAINLESS STEEL KITS



• 39800 HEART SHAPE KIT - blue Cuticle nipper 10 cm, Nail nipper 10 cm, Nail scissors 9.5 cm, Nail file 10 cm. Pusher double ended 12 cm. Tweezers 10 cm.

• 39805 STEEL FRAME KIT Nail nipper 10 cm, Nail Scissor 9.5 cm, Cuticle scissors 9.5 cm Cuticle pusher double


ended 12 cm. Cuticle pusher and cleaner 13 cm, Tweezers 9 cm, Nail file with white plastic handle 9 cm



lail nipper Moon Shape 14 cm, Side cutter 13 cm,

Cuticle Nipper 10 cm, Dressing Scissors 14 cm, B.P. handle No. 4 13.5 cm. Splinter Tweezers 12 cm. Loop 14 cm, Knife & Cleaner double ended 16 cm, Nail file 12 cm, Nail file with white plastic handle 13 cm Spatula double ended 15 cm





 $C \in$ 

#### DENTAL STAINLESS STEEL INSTRUMENTS 60040 set of 10 perforated impression trays (5 lower + 5 upper) fig. 1 fig. 2 fig. 7 fig. 17 fig. 18 fig. 29 60000 60001 60002 60003 60005 60004 upper upper upper upper upper upper 17.5 cm 17.5 cm 17.5 cm 17.5 cm 17.5 cm 17.5 cm 60045 set of 10 solid impression trays (5 lower + 5 upper) Above impression trays sets have below sizes UPPER SIZES mm U1 U2 U3 U4 U5 A 62 60 53 54 52 B 83 75 73 69 68 LOWER SIZES mm fia. 74N fia. 51 fia. 67A fia. 16 fia. 22 fia. 79 fia. 151 L1 L2 L3 L4 L5 60006 60007 60015 60017 60016 60018 60019 A 63 61 57 60 53 B 82 81 78 74 71 lower lower lower lower upper lower 18.5 cm 18.5 cm 15.4 cm 15.1 cm 17.5 cm 18.5 cm **SCALER** CARVER 60101 Explorer - fig. 17/23 60140 Scaler - fig. 1 60170 Cement spatula 60171 Wiland modelling carver 60100 Explorer probe 60141 Mc Call scaler - fig. 18 60172 Interproximal modelling carver 60105 WHO probe 60142 Mitchel scaler GRACEY AND Mc CALL CURETTES 60173 Beale modelling carver - mod. 7A 60144 Langer scaler - fig. 1/2 60145 Langer scaler - fig. 3/4 60120 Mc Call curettes - fig. 13/14 60174 Fahnenstock - modelling carver - 13 cm **FORCEPS** 60148 Hygienist scaler - fig. H6/7 60125 Gracey curette - fig. 1/2 ant. 60190 London college forceps - 15 cm CARTRIDGE SYRINGE 60150 Scaler - fig. 204S 60127 Gracey curette - fig. 7/8 medium 60195 60155 Periodontia instr. - fig. ST 2/3 60130 Gracey curette - fig. 11/12 medium 60195 Cartridge Syringe - 2.2 cc with thread in millimeter with aspiration 60131 Gracey curette - fig. 13/14 post. 60156 Periodontia instr. Rein Seldin root root elevator elevator 60210 60204 60205 Amalgam Winter carrier root elevator Molt 60226 Mouth gag 60220 - 11 cm **Bone Cutter** Bever Forceps 60221 - 14 cm

# DISPOSABLE METAL INSTRUMENTS - STERILE

A complete range of disposable instruments designed to provide users with good quality, sturdy all-metal alternative to plastic disposable instruments. Each instrument has a blue coloured part to avoid mix with reusable instruments and is incorrectly, packed in a single sterile pouch. Sterilized by Gamma radiation.

STERILE SCISSORS

**BLUE HANDLES** for instant identification

- 38800 Surgical scissors sharp/sharp
- straight 13 cm box of 25
- 38801 Surgical scissors sharp/blunt - straight - 13 cm - box of 25
- 38809 Metzenbaum scissors straight - 16 cm - box of 25
- 38810 Metzenbaum scissors -
- curved 16 cm box of 25
- 38812 Metzenbaum scissors curved - 18 cm - box of 25
- 38830 Iris scissors sharp/sharp - straight - 11.5 cm - box of 25
- 38831 Iris scissors sharp/sharp - curved - 11.5 cm - box of 25
- 38820 Mayo scissors straight - 15 cm - box of 25
- 38822 Mayo scissors straight
- 17 cm box of 25

- 38840 Lister bandage scissors 14 cm
- 38841 Lister bandage scissors 16 cm
- 38842 Lister bandage scissors 18 cm
- box of 25
- 38835 Umbilical scissors straight - 10.5 cm - US model - box of 25

• 38870 Adson tissue forceps - straight

• 38871 Adson tissue forceps - straight

• 38880 McIndoe dissecting forceps

- 12 cm 1x2 teeth - box of 25

#### STERILE FORCEPS

- 38850 Dressing tissue forceps straight - 13 cm - box of 25
- 38852 Dressing tissue forceps straight
- 16 cm box of 25
- 38851 Dressing forceps straight - 13 cm 1x2 teeth - box of 25
- 38860 Pean forceps curved 14 cm
- 38861 Pean forceps curved 16 cm • 38862 Pean forceps - curved - 18 cm
- hox of 25
- 38885 Splinter plain forceps 12.5 cm hox of 25 \_\_\_\_80 mm\_

- 38865 Spencer Wells forceps straight - 13 cm - box of 25
- 38875 Haemostatic Halstead-Mosquito artery forceps - straight - 12.5 cm - box of 25
- 38876 Haemostatic Halstead-Mosquito artery forceps - curved - 12.5 cm - box of 25
- straight 15 cm box of 25
- 38890 Magill forceps
- 20 cm for children box of 10
- 38891 Magill forceps
- 25 cm for adult box of 10

- 12 cm - box of 25

#### 38897

- 38895 Micro Hartmann ear forceps - 15 cm - 3 mm - box of 10
- 38897 Micro Bellucci ear scissors -15 cm - 3 mm - box of 10
- 38920 Mayo-Hegar needle holder - 14 cm - box of 25
- 38921 Mayo-Hegar needle holder

• 38887 Foerster polypus forceps

- 16 cm box of 25

- 25 cm - box of 10

- 38930 Crile Wood needle holder

# SINGLE USE STERILE PROCEDURE PACKS

hox of 25 38950 SUTURE REMOVAL PACK

Iris scissors - straight - 11.5 cm Adson tissue forceps toothed - 12 cm



• 38951 SUTURE PROCEDURE PACK Spencer ligature scissors - straight - 9 cm

Adson tissue forceps toothed - 12 cm

• 38952 STANDARD SUTURE PACK Kilner needle holder - 13 cm Spencer Stitch scissors - straight - 9 cm Treeves toothed dissecting forceps - 13 cm T.O.E. (Turnover End) forceps - 13 cm Super crepe sheet

• 38953 STANDARD DELIVERY PACK Umbilical scissors - 10.5 cm - US model Mayo gynaecological scissors - straight - 17 cm 2x Spencer Wells artery forceps - straight - 13 cm









2x Umbilical cord clamps Super crepe sheet

# STERILE MEDICATION, SUTURE, CATHETERIZATION KITS







• 26929 DRESSING KIT 2 - sterile

• 26933 CATHETERIZATION KIT - sterile







• 26937 SUTURE REMOVAL KIT 2 - sterile

• 26932 SUTURE REMOVAL KIT 3 - sterile

	Dre	ssing	Sut	ture	Sut	ure rem	oval	Cathe
KIT CONTENT		26929	26931	26934	26932	26936	26937	269
Field cloth	٠		٠		٠			٠
Cushing surgery forceps			•					
Needle Holder			•	•				
Anatomy forceps	•	•	•	•	•	•	•	
Ring shaped forceps	•	•	•		•			•
Styptic clamp (Kelly forceps)			•					
Haemostatic clamp				•				
Straight scissors			•					
Metal forceps		•		•				
Littauer scissors		•		•	•	•		
Gauze swabs 7.5x7.5 cm 8 ply	•	•	•		•			
Gauze swabs 10x10 cm 8 ply				•	•			
4 or 5 Gauze plugs	•		•	•	•			
3 Gauze plugs		•			•			
Gauze swabs 10x20 cm - 8 plies		•						
Gauze swab 18x40 cm						•		
Latex gloves - medium			•	•	•			
Vinyl gloves								•
Disposable big bag			•		•			•
Medication plaster 15x12 cm					•			
WNW (TNT)+PE drape 32x50 cm		•	•	•				•
WNW (TNT) compresses								•
WNW (TNT)+PE drape 50x60 cm with hole				•				
Water syringe								•
Single dose lubricant								•
Single dose disinfectant								•
Chlorexidina wipe				•				
2 adhesive WNW (Woven Non Woven) strips				•				
Waste bag		•						
Scalpel with handle							•	
2 cotton applicators								





# DISPOSABLE SKIN STAPLER DEVICE



#### • 25890 DISPOSABLE STERILE SKIN STAPLER

Simple and easy to operate. Staples are made of High Quality 317 L Stainless Steel for medical use, each device is provided of 35 staplers. High sewing up and stapling speed help shorten the time of sewing and avoid cross infection of contagious diseases. Reduced tissue reaction, thinner scar after operation and faster wound healing. Painless and convenient staples removal after the incision has healed up.

To be used for skin closure in operating room, labour and delivery, emergency department, outpatient surgery, clinics and physician's office.

# SUTURES - FINE WOUND CLOSURE MATERIAL

#### CLINISILK STERILE BLACK BRAIDED SILK SUTURE B.P.

Non-absorbable sutures made from pure natural silk, braided to form a multifilament thread, double treated with a silicone coating to prevent capillarity and to enhance ease of passage through tissue. Silk sutures are considered to have the best handling and tying characteristics. Suture length: 45 cm. Application: soft tissue approximation and ligation.

#### CLINILON STERILE BLUE MONOFILAMENT NYLON SUTURE B.P. Non-absorbable synthetic monofilament suture made from Polyamide 6.6. No tissue reaction, excellent tensile strength,

easy handling and secure knotting. Suture length: 45 cm. Nylon is a highly favoured material for skin closure. Application: skin closure, general soft tissue approximation and ligation.

		_					
GIMA	code	CLIN	IISILK .			N SUTURES - pack of	
Silk	Nylon	Gauge	Metric	Needle	Needle shape	Type of needle	Suture length
25910	25920	2/0	3	26 mm	3/8	Reverse cutting	45 cm
25911	-	3/0	2	22 mm	1/2	Conventional cutting	45 cm
-	25921	3/0	2	20 mm	3/8	Conventional cutting	45 cm
25912	25922	3/0	2	24 mm	3/8	Reverse cutting	45 cm
-	25923	3/0	2	25 mm	3/8	Fine conventional cutting	45 cm
25914	25924	4/0	1.5	19 mm	3/8	Reverse cutting	45 cm
-	25925	5/0	1	16 mm	3/8	Reverse cutting	45 cm
25916	25926	5/0	1	19 mm	3/8	Reverse cutting	45 cm
-	25927	6/0	0.7	12 mm	3/8	Reverse cutting	45 cm
25918	25928	6/0	0.7	16 mm	3/8	Reverse cutting	45 cm

# CLINITRO SUTURES: BLUE POLYVINYLIDENE FLUORIDE MONOFILAMENT NON ABSORBABLE PVDF SUTURE

It is indicated in procedures where non-absorbable monofilament sutures are required, expecially skin and fascia closure. CliniTro is used in place of nylon for skin closure. The material is much softer and more pliable.

Tensile strength is higher than nylon and knot holding is far

Our SG (Super Glide) are all premium reverse cutting needles. Specifically suggested for dermatology and plastic surgery are our equivalents to Ethicon's Multipass needles.

GIMA	CLINITRO SUTURES - pack of 12 pcs.									
code	Gauge	Metric	Needle	Needle shape	Type of needle	Suture length				
25930	2/0	3	24 mm	3/8	Reverse cutting	70 cm				
25931	3/0	2	24 mm	3/8	Reverse cutting	70 cm				
25932	4/0	1.5	19 mm	3/8	Reverse cutting	70 cm				
25933	5/0	1	19 mm	3/8	Reverse cutting	70 cm				
25934	5/0	1	16 mm	3/8	Reverse cutting	70 cm				
25935	6/0	0.7	13 mm	3/8	Reverse cutting	45 cm				

#### CLINISORB STERILE VIOLET BRAIDED PGA SYNTHETIC ABSORBABLE SUTURE

CliniSorb is a synthetic absorbable braided suture made from a polymer of Glycolic acid. This material is inert, non collagenous, non-antigenic, non-pyrogenic and has a high tensile strength and predictable absorption rate, allowing wound support for approx. 21 days, complete absorption in 56-70 days. It is treated with a surface coating to ensure smooth tissue passage and enhance knot sliding. No risk of infection, inflammatory processes or exposure to protein digesting enzymes in the gastro intestinal tract. Suitable for both skin closure and where non-permanent wound support is indicated Application: dental, general skin closure, gynaecology, plastic and general surgery, orthopedics and urology

GIMA									
code	Gauge	Metric	Needle	Needle shape	Type of needle	Suture length			
25900	2/0	3	24 mm	3/8	Reverse cutting	70 cm			
25901	3/0	2	19 mm	3/8	Reverse cutting	45 cm			
25902	4/0	1.5	19 mm	3/8	Reverse cutting	45 cm			

#### CLINIMONO Q SYNTHETIC MONOFILAMENT

Undyed monofilament rapid absorbable sutures composed of PGCL. Complete absorption in 90 days. Suitable for soft tissue approximation and ligation but not for cardiovascular or neurological procedures. This product is our equivalent to Ethicon's Monocryl. Also used for subcutaneous and subcuticular closure in general surgery as well as skin closure for out of town patients who cannot return to have suture removed

GIMA	CLINIMONO Q SUTURES - pack of 12 pcs.							
code	Gauge	Metric	Needle	Needle shape	Type of needle	Suture length		
25904	2/0	3	24 mm	3/8	Reverse cutting	70 cm		
25905	3/0	2	24 mm	3/8	Reverse cutting	70 cm		
25906	4/0	1.5	19 mm	3/8	Reverse cutting	70 cm		
25907	5/0	1	16 mm	3/8	Reverse cutting	70 cm		
25908	6/0	0.7	11 mm	3/8	Reverse cutting	45 cm		
					A			



# SKIN STAPLE REMOVER



 25892 DISPOSABLE REMOVER FORCEPS - box of 20 pcs. Practical disposable forceps for removing regular and wider size staples. Sterile

• 25895 SR-3 DISPOSABLE SKIN STAPLE REMOVER - box of 10 pcs. 3M original forceps for removing staples. Sterile. 26737

26722

S/S STITCH/SUTURE REMOVERS:

• 26737 SPENCER SCISSORS - 13 cm

26722 MICHEL STITCH REMOVER

FORCEPS - 13 cm

# GENERAL SURGERY PROCEDURE PACK



• 26985 GENERAL SURGERY PACK - sterile Ready to use pack including all necessity for a general surgery procedure.

Peel open PE + tyvek envelope. Sterile EO.

#### KIT CONTENT

1 table cover 150x200 cm 2 surgical gown XL 2 adhesive dranes 75x90 cm 1 foot drape (ADH side) 150x175 cm 1 head drape (ADH side) 150x240 cm 2 syringes 10 ml

2 needles 21Gx1.5"

4 hand towel 1 bowl 90 ml

1 kidney dish 10 scalpel n°15 5 gauze swabs 10x20 cm 4 gauze balls 30 mm

2 foam stick 15 cm

38

# SKIN MARKER



• 33179 SKIN MARKER - dual tips gentian violet - box of 10 Double tips skin marker with polypropylene

cap and body. Polyester fiber tips. Ultra fine tip utility marker to write on adhesive labels and infusion bags.

Regular tip surgical skin marker for use on natient skin Washable with water and soap. Size 138xØ 12.5 mm. Multilanguage box and manual: GB, FR,

# IT, DE, ES, PT, GR, PL, SE, RO, HU, Arab. DERMATOGRAPH MARKERS



- 33175 DERMATOGRAPH MARKER blue • 33176 DERMATOGRAPH MARKER - white
- 33177 DERMATOGRAPH MARKER red
- 33178 DERMATOGRAPH MARKER mix\* \*2 pencils each colour

Special dermatograph pencil to mark the skin for identification of areas to be treated. Made in cedar wood with

GIMA wax lead. Size 175xØ 7 mm. Suitable for general surgery, dermatology,

orthopaedy, radiology, .. Pencils are sold non sharpened in box of 6 with 1 pencil sharpener included. Multilanguage box and manual: GB, FR, IT, DE, ES, PT, GR, PL, SE, RO, HU,

# **SKIN MARKER** - STERILE





 33181 CLINICON® - fine tip - sterile - box of 10 The Clinicon® Surgical Skin Marker features a versatile tip for precise fine line marking preferred in



line (0.2 mm. plastic surgery or when held at an angle, broad line marking for applications in general, neuro and vascular surgery, as well as radiology and radiation therapy. The marker's high visibility Gentian violet ink is nontoxic, non tattoing and surgical prep-resistant. Markings can be removed from the skin with isopropyl (rubbing) alcohol. The package is easy to open, HIBC bar coded and includes a separate six inch, flexible ruler calibrated in both inches and centimeters. Sterile EO.

# ETHICON SUTURES - ABSORBABLE AND NON ABSORBABLE





# ETHICON

ETHICON



NON ABSORBABLE STERILE SURGICAL SUTURES										
GIMA code	ETHICON code	Gauge	Metric	Colour	Circle	Needle length	Needle	Suture length	Minimum order	
ETHILON - monofilament suture										
22300	660H	6/0	0.7	Black	3/8	16 mm	FS-3	45 cm	box of 36	
22301	661H	5/0	1.0	Black	3/8	19 mm	FS-2	45 cm	box of 36	
22302	662H	4/0	1.5	Black	3/8	19 mm	FS-2S	45 cm	box of 36	
22303	663H	3/0	2.0	Black	3/8	24 mm	FS-1	45 cm	box of 36	
22304	EH7506H	3/0	2.0	Black	3/8	19 mm	FS-2	45 cm	box of 36	
22305	EW661	5/0	1.0	Blue	3/8	19 mm	FS-2	75 cm	box of 36	
PERMA-HAND - silk sutures - braided										
22310	18501G	4/0	1.5	Black	1/2	17 mm	J-1	45 cm	box of 12	
22311	18502G	3/0	2.0	Black	1/2	22 mm	X-1	45 cm	box of 12	
22312	18505G	2/0	3.0	Black	1/2	22 mm	X-1	45 cm	box of 12	
22313	18507G	4/0	1.5	Black	Straight	19 mm	ST-4	45 cm	box of 12	
22314	18508G	4/0	1.5	Black	3/8	13 mm	P-3 prime	45 cm	box of 12	
22315	18509G	3/0	2.0	Black	1/2	22 mm	SH-1 Plus	45 cm	box of 12	
22316	EH7149G	4/0	1.5	Black	3/8	19 mm	FS-2	45 cm	box of 12	
	PROLEI	NE - b	lue pi	igmen	ted m	onifila	ment s	utures		
22320	EH7150H	4/0	1.5	Blue	3/8	19 mm	FS-2	75 cm	box of 36	
22321	EH7151H	4/0	1.5	Blue	3/8	19 mm	FS-2	45 cm	box of 36	
22322	W8873T	6/0	0.7	Blue	3/8	16 mm	PC-3 Prime	45 cm	box of 24	
Non ab	sorbabl	e sur	gical	suture	s are	indica	ated fo	r use i	n	

general soft tissue approximation and/or ligation included use

in cardiovascular, ophthalmic and neurosurgical procedures

Monocryl is indicated for use in general soft tissue approximation and/or ligation, but not for cardio, neuro,										
	nd oph								.,	
MONOCRYL - complete absorption in 91-119 days										
22350	Y493H	5/0	1.0	Undyed	3/8	19 mm	P-3 prime	45 cm	box of 36	
Vicryl Plus is indicated for use in general tissue approximation										
and/or ligation except for ophthalmic, neuro, cardiovascular										
VICRYL PLUS BRAIDED - complete absorption in 56-70 days										
22360	VCP392ZH	4/0	1.5	Violet	3/8	19 mm	FS-2	45 cm	box of 36	
22361	VCP305H	3/0	2.0	Violet	1/2	17 mm	RB-1 PLus	70 cm	box of 36	
22362	VCP452H	2/0	2.0	Violet	3/8	24 mm	FS-1	70 cm	box of 36	
									box of 36	
	Rapid Br									
	sue app								re only	
	erm (7-1									
	RYL RAI					te abso				
	V76H	3/0	2.0	Undyed			J-1	45 cm	box of 36	
	V2920G						FS-2		box of 12	
22372	V2930G	3/0	2.0	Undyed	3/8	19 mm	FS-2	45 cm	box of 12	
	V2150G								box of 12	
22374	V2190G	3/0	2.0	Undyed	1/2	22 mm	SH-1 PLus	70 cm	box of 12	
22375	VR2298	3/0	2.0	Undyed	3/8	14 mm	FS-2	75 cm	box of 36	

ABSORBABLE STERILE SURGICAL SUTURES

# GIMA: DISPOSABLE S/S SCALPELS & STAINLESS OR CARBON STEEL BLADES

**( 6** 0434

15 15c

27033

27034

27035

27036

27037

27038

27070

27071

27073

27074

27075

27076

SCALPEL HANDLES - STAINLESS STEEL

Sterilized blades No. 11

Sterilized blades No. 12

Sterilized blades No. 15

Sterilized blades No. 15c

Sterilized blades No. 20

Sterilized blades No. 21

Sterilized blades No. 22

Sterilized blades No. 23

Sterilized blades No. 24

GIMA STERILIZED DISPOSABLE SCALPELS

STAINLESS STEEL (PACK OF 10 PCS.)

Disposable scalpels - blade 10

Disposable scalpels - blade 11

Disposable scalpels - blade 12

Disposable scalpels - blade 15

Disposable scalpels - blade 15c

Disposable scalpels - blade 20

Disposable scalpels - blade 21

Disposable scalpels - blade 22

Disposable scalpels - blade 23

Disposable scalpels - blade 24

Scalpel Handle N° 3 for blades 10-15

Scalpel Handle N° 4 for blades 20-25

27000 27020 27030 Sterilized blades No. 10

10 11

GIMA

26913

26914

27001

27002

27003

27009

27004

27005

27006

27007

27008

Model

27040

27041

27042

27043

27049

27044

27045

27046

27047

27048

27021

27022

27023

27024

27025

27026

27027

27028

Model

27060

27061

27062

27063

27064

27065

27066

27067

"GIMA" DISPOSABLE BLADES - sterile - dispenser box of 100 Surgical blades are available in high quality carbon steel and stainless steel with or without safety round tip. Manufactured in accordance with the requirements of British Standards BS 2982:1992, ISO 7740:1985, ISO 7153-1: 1991, EN 10088-3: 2005. Each blade is hallmarked and individually packed in aluminium foil. Carbon Steel blades are VPI paper protected. Blade size is clearly identified on the reverse side of the foil peel-pack and on product unit boxes.



ABS hadv

27030 Safety blade n. 10

"GIMA" DISPOSABLE SCALPELS - sterile - box of 10 S/S blade fitted into an ABS plastic handle. Individually packed in sterilized envelope. Safety blade guard for premium model.



sandwiched blade

27060-27066

"GIMA" SAFETY PROTECTIVE SHIELD SCALPELS - sterile Protective scalpels with a clear view shield that protects against injuries before use, between steps of procedure and after disposal Latex and phthalates free Complies with US



OSHA standard 29 CFR 1910 1030 and Furopean Directive 2010/32/EU

Stead fast disposable lock, audible, visual and steel blade tactile indication 27070-27078

SAFETY HANDLE

26915 SAFETY S/S HANDLE N 3 for blades 10-15

 26916 SAFETY S/S HANDLE N 4 for blades 20-25 Innovative handle allows hand-free removal

halanced

MODE

quard

Graduated handle (cm)

# PARAGON BLADES AND SCALPELS

"PARAGON" DISPOSABLE S/S BLADES - sterile High quality blades manufactured with best British stainless steel guarantee excellent sharpening and perfect cut control. Individually packed in metal foil. Gamma rays sterilized.

# of blade in compliance with OSHA and CDC. Safety handle N°3 for safety blades N°10-15

# KAI DISPOSABLE BIOPSY BLADE



**SWANN-MORTON SEE PAGE I** 



"PARAGON" DISPOSABLE SCALPELS WITH S/S BLADE - sterile Grip on the plastic handle allows stability for long straight incisions. Individually packed in sterilized envelope, reinforced

cardboard box of 10 units.



STERILE, box of 100 box of 10 S/S BLADE 26901 26920 Blade 10 26902 26921 Blade 11 26903 26922 Blade 12 26904 26923 Blade 15T 26924 Blade 20 26905 26906 26925 Blade 21 26907 26926 Blade 22 26908 26927 Blade 23 26909 26928 Blade 24 Multilanguage box: GB, FR, IT, ES, DE DK, NL, GR, PT, PL, FI, RU, NO, SE

41

# SINGLE-USE STERILE DERMAL CURETTES

**( (** 0197



Stainless steel sharp cutting edge for soft or weak tissue.

Size embossed on each curette for easy identification.

Sterile ready-to-use. Use once and discard eliminates need for re-sharpening and sterilization. Wide range of sizes. Made in

Used in the following minor surgical skin procedures: Curettage of a basal cell carcinoma, curettage of a verruca and curettage of any other benign neoplasms of the skin. Clinical Areas: dermatology, surgical, podiatry, veterinary

GIMA code	DERMAL CURETTES	Minimum order
	Dermal Curettes Ø 2 mm Dermal Curettes Ø 3 mm	box of 20 box of 20
22604	Dermal Curettes Ø 4 mm	box of 20
22605	Dermal Curettes Ø 5 mm	box of 20
22606	Dermal Curettes Ø 7 mm	box of 20

22616

# SINGLE-USE STERILE BIOPSY PUNCHES - LATEX FREE

Stainless steel sharp cutting edge, ribbed handle for sure grip. Size embossed on each punch for easy identification. Suggested for dermatology, gynaecology, podiatry. Each punch is individually sealed in a peel-apart see-through package.

Standard	With plunger	BIOPSY PUNCHES	Blade length mm	Minimum order	
22610	22630	Biopsy Punches Ø 1 mm	7	box of 20	
22611	22631	Biopsy Punches Ø 1.5 mm	7	box of 20	
22612	22632	Biopsy Punches Ø 2 mm	7	box of 20	
22613	-	Biopsy Punches Ø 2.5 mm	7	box of 20	
22614	22634	Biopsy Punches Ø 3 mm	7	box of 20	
22615	-	Biopsy Punches Ø 3.5 mm	7	box of 20	
22616	22636	Biopsy Punches Ø 4 mm	7	box of 20	
22617	-	Biopsy Punches Ø 5 mm	7	box of 20	
22618	-	Biopsy Punches Ø 6 mm	7	box of 20	
22619	-	Biopsy Punches Ø 8 mm	7	box of 20	



utting Edge

nsures a consistenti



Internal Plunger System



35 mm box of 100

4			A. Carrier					,
		27080	2	7081		27	082	
	GIMA code		RILE DISPOS ainless stee		ORS	Blade length	Minimum order	
	27080	Single bla	de - 98.6x41	1 mm		35 mm	box of 100	

27082 Single blade with comb - 103x47 mm 38 mm box of 50

27081 Double blade - 98.6x41 mm

# **SURGICAL CLIPPER**

#### • 27085 SURGICAL CLIPPER

27085

27087

Battery operated surgical clipper for removing body hair from patients in preparation for surgery or other procedures requiring hair removal. Blade not included. Battery 2 x AA 1.5V not included

• 27087 CLIPPER BLADE ASSEMBLY - sterile box of 10 pcs

Disposable use for each patient. Single use blade assembly EO sterilized.




# Two symmetrical eyes with smooth edges LATEX STERILE 100% SILICONE COATED **FOLEY CATHETERS - SINGLE USE** Two-way catheters - balloon 5-10 ml - length 40 cm - soft valve 22054 2-way Foley catheter ch/fr 12 - balloon 5-10 ml box of 10 22055 2-way Foley catheter ch/fr 14 - balloon 5-10 ml box of 10 22056 2-way Foley catheter ch/fr 16 - balloon 5-10 ml box of 10 22057 2-way Foley catheter ch/fr 18 - balloon 5-10 ml box of 10 22058 2-way Foley catheter ch/fr 20 - balloon 5-10 ml box of 10 22059 2-way Foley catheter ch/fr 22 - balloon 5-10 ml box of 10

Two-ways catheters - balloon 30 ml - length 40 cm - soft valve								
22064	2-way Foley catheter ch/fr 12 - balloon 30 ml	box of 50						
22065	2-way Foley catheter ch/fr 14 - balloon 30 ml	box of 50						
22066	2-way Foley catheter ch/fr 16 - balloon 30 ml	box of 50						
22067	2-way Foley catheter ch/fr 18 - balloon 30 ml	box of 50						
22068	2-way Foley catheter ch/fr 20 - balloon 30 ml	box of 50						
22069	2-way Foley catheter ch/fr 22 - balloon 30 ml	box of 50						
22070	2-way Foley catheter ch/fr 24 - balloon 30 ml	box of 50						
Three-	ways catheters - balloon 30 ml - length 40 cm	- soft valve						
22077	3-way Foley catheter ch/fr 18 - balloon 30 ml	box of 50						

22078 3-way Foley catheter ch/fr 20 - balloon 30 ml box of 50 22079 3-way Foley catheter ch/fr 22 - balloon 30 ml box of 50 22080 3-way Foley catheter ch/fr 24 - balloon 30 ml box of 50

# RECTAL CATHETERS



# **FEEDING TUBES**

from the	distal end	
40	4 11 11 11 11	
Feeding t	ube with X-ray line	
GIMA code	PVC DEHP FREE* STERILE FEEDING TUBES length: 50 cm - with Luer fitting and sealing plug adapter	Minimum order
22150	Feeding tube ch/fr 5 - grey	box of 100
22151	Feeding tube ch/fr 6 - light green	box of 100
	Feeding tube ch/fr 8 - light blue	box of 100
	Feeding tube ch/fr 10 - black	box of 100

#### STOMACH TUBES Levin tubes suitable for feeding and irrigation, with X-ray line Four lateral eyes with smooth edges marked between 40-60 cm from the distal end PVC DEHP FREE' STERILE STOMACH TUBES Minimum length: 110 cm - with multi functional adapt 22156 Stomach tube ch/fr 12 box of 100 22157 Stomach tube ch/fr 14 box of 100 22158 Stomach tube ch/fr 16 box of 100

# FOLEY CATHETERS - LATEX FOLEY CATHETERS - SILICONE



# NELATON CATHETERS



# SUCTION CATHETERS



# CATHETER LUBRICANT GEL - STERILE

 22104 CATHETER LUBRICANT GEL 12 ml - sterile - box of 25 Sterile, clear, water soluble gel used before applying catheter, cystoscope or other medical instrument to urethra

It covers urethra generating a slick layer between urethral mucosa and catheter or medical instrument. It has antiseptic effect protecting patient from potential infection risk

It contains Lidocaine 2%, chlorhexidine 0.05%

# URINE BAGS - MADE IN SPAIN



GIMA code	URINE	BAGS	Minimum order
	STANDARD	URINE BAGS	
28690 28688 28692 28689	Urine bag 2000 cc - tul Urine bag 2000 cc - tul Urine bag 2000 cc - tul Urine bag 2000 cc - tul 'Polybag of 30 bags with tipps	be 90 cm - bulk be 130 cm - polybag be 130 cm - bulk	box of 30* box of 250 box of 30* box of 200 and 1 hanger
	URINE BAGS WITH	NON RETURN VALVE	
28691 28694 28693 28695	Urine bag 2000 cc - tul Urine bag 2000 cc - tul Urine bag 2000 cc - tul Urine bag 2000 cc - tul 'Polybag of 30 bags with tipps	be 90 cm - bulk be 130 cm - polybag be 130 cm - bulk	box of 30* box of 250 box of 30* box of 200 and 1 hanger
	URINE LEG BAGS WIT	TH NON RETURN VALV	E
28707	Urine leg bag 750 cc - tube 10 cm - polybag box of 30** complete with push pull outlet device		
28708	Urine leg bag 750 cc - tube 35 cm - polybag box of 30** complete with push pull outlet device "Polybag of 30 bags with 1 set of button straps		
	ions in GB, FR, IT, ES, D internal 5.05 mm, extern		DEHP free.
10	NIII)	Von	2869
	ble for 28690/1/2/3 and 28707/8	28699	
GIMA code	HANGER HOLDER	FOR URINE BAGS	Minimum order
28699	Hanger holder for urine bag - blue - bulk box of 200		box of 200
GIMA code	EXTERNAL LATE	X CATHETERS	Minimum order
28710	Men external catheter		box of 30
28711	Men external catheter		box of 30
28715	Biadhesive tape 2x15x0.5 cm box of 30		

# STERILE PAEDIATRIC URINE BAG FOR BOY AND GIRL



• 28685 PAEDIATRIC URINE BAG 100 ml - sterile - box of 100 Paediatric urine bag, individually wrapped in polybag.

They can be used for boy and girl. Graduated 10 to 100 ml, sterile.



# TRAVELJOHN™ RESEALABLE DISPOSABLE URINAL AND VOMIT BAG



- 25880 TRAVELJOHN™ DISPOSABLE URINAL 800 cc - box of 3 25885 TRAVELJOHN™ DISPOSABLE
- URINAL 600 cc bag of 10 - practical super absorbent polymer pouch that instantly turns urine to gel
- no closure needed - reusable until it is full waste disposal safe, simply throw away
- unisex plastic collar for easy handling 25887 TRAVELJOHN™ DISPOSABLE VOMIT BAG 800 cc - box of 5
- gels instantly and water proof
- convenient sanitary and compact - odourless and waste disposal safe

# URINE CONTAINERS



screw cap and frosted label.

One multilanguage instruction in each carton: GB, FR, IT, ES, PT.

code	URINE CONTAINERS - BULK	order
25958	Urine containers 120 ml	box of 300
URINE CONTAINERS - individually wrapped		
25960	Urine containers 60 ml - cleanroom ISO8	box of 500
25961	Urine containers 60 ml - sterile	box of 500
25962	Urine containers 120 ml - cleanroom ISO8	box of 250
25963	Urine containers 120 ml - sterile	box of 250

# BIOLOGICAL COLLECTORS



Coprotainer® graduated faeces containers made in polypropylene with red screw cap and frosted label, individually wrapped. One multilanguage instruction in each carton: GB, FR, IT, ES, PT.

GIMA code	BIOLOGICAL CONTAINERS	Minimum order
25965	Faeces container 30 ml - cleanroom ISO8	box of 500
25966	Faeces container 30 ml - sterile	box of 500
25967	Faeces container 60 ml - cleanroom ISO8	box of 500
25968	Faeces container 60 ml - sterile	box of 500



24 h graduated urine containers made in polyethylene. One multilanguage instruction in each carton: GB, FR, IT, ES, PT.

GIMA code	24 h URINE CONTAINERS	Minimum order
25980	Bottle 2500 ml	box of 30
25981	Container 2000 ml with ergonomic handle	box of 54
25982	Tank 2500 ml	box of 30

# 📘 24 Hours Urine Containers 🔃 Plastic Bed Pan - Urinal



- 25979 PLASTIC BED PAN box of 20
- Made in polypropylene and individually wrapped. • 25978 MEN PLASTIC URINAL 1,000 ml - box of 60 Made in polyethylene and individually wrapped.

Bed pan and plastic urinal have multilanguage polybag: GB, FR, IT, ES, PT, PL, GR, SE.

# **CONTAINERS IN SINGLE BOX - PHARMACY LINE**



Sterile urine test tube Individually wrapped urine test tube with paper label in single

box. Graduated 0.5, 1, 2.5, 5, 10 ml.

All products have multilanguage box: GB, FR, IT, ES.

25990 Urine test tube 12 ml Polystyrene box of 100 25995 Urine tank 24 h 2500 ml Polyethylene box of 27 25997 Faeces container 60 ml Polypropylene box of 100

# PLASTIC HOLLOWARE - AUTOCLAVABLE 135°C



PLASTIC HOLLOWARE - autoclavable hundreds of times For the protection and delivery of sterile instruments to operating rooms. For the administration of procedures. holding cleansing solutions and the administration of medicines and fluids.

4 good reasons to choose plastic line: • 50% cheaper than stainless steel equivalent

- autoclavable at 135°C with no limits
- attractive modern design

• lighter than equivalent stainless steel All products are manufactured from polypropylene material that is easy to


clean, resistant to most healthcare chemicals.

- 26630 GALLIPOT/LOTION BOWL 60xh 40 mm graduated 50 ml
- 26631 GALLIPOT/LOTION BOWL 80xh 60 mm graduated 200 ml • 26632 GALLIPOT/LOTION BOWL 100xh 45 mm - graduated 300 ml
- 26633 GALLIPOT/LOTION BOWL 150xh 70 mm graduated 500 ml
- 26635 KIDNEY DISH 200xh 45 mm graduated 500 ml
- 26636 KIDNEY DISH 250xh 55 mm graduated 750 ml
- with special nodules on rim to prevent vacuum during autoclaving
- 26638 INSTRUMENT TRAY 200x150x51 mm • 26639 INSTRUMENT TRAY 300x250x52 mm
- 26640 COMPARTMENT TRAY 270x180x41 mm

# VALUE PLASTIC HOLLOWARE - AUTOCLAVABLE 134°C

Economic line of reusable plasticware products. Made in polypropylene, easy to clean and resistant to most healthcare chemicals. Autoclavable at 121°C (15 min). 126°C (10 min) or 134°C (3 min).







- 37705 KIDNEY TRAY 6" 155x75 mm
- 37706 KIDNEY TRAY 8" 205x100 mm • 37707 KIDNEY TRAY 10" 260x125 mm
- 37708 KIDNEY TRAY 12" 306x140 mm





• 37717 COMPARTMENT TRAY 266x175xh 42 mm

POLYSTYRENE TEST TUBES 37902 | 12x75 mm - 5 ml cylindrical, no rim | box of 4,000\* 37903 | 13x75 mm - 5 ml cylindrical, no rim | box of 4,000\*



 37718 INSTRUMENT TRAY 220x150xh 70 mm

# POLYSTYRENE TEST TUBES - GRADUATED PASTEUR PIPETTES



37715 LABORATORY TRAY

375x300xh 75 mm

37715

3/912	16x100 mm - 10 ml cylindrical, with rin	1   box of 2,000
37913	16x100 mm - 10 ml conical, with rin	n box of 2,000
*16 bags o	f 250 pcs	
	WINGED STOPPERS FOR TEST TU	JBES
37930	Stopper for tubes Ø 12 mm	box of 1,000
37931	Stopper for tubes Ø 13 mm	box of 1,000
	Stopper for tubes Ø 16 mm	box of 1,000

	Pipette 1	ml	37950	), 37953	
	Pipette 3	3 ml	37951	1, 37954	
	Plants -				
			37953	3, 37954	
Made of p	olyethylene, ii	ndividually	wrapp	ed in peel pad	ck
GIMA code	PASTEL	JR PIPET	TE	Minimum order	
37950	Pipette 1			box of 5,00	
37951	Pipette 3	ml		box of 5,00	
37953	Pipette 1			box of 1,00	
37954	Pipette 3	ml - ster	ile	box of 1,00	)()
*10 boxes	of 500 pieces				

# ALUMINIUM STERILIZATION CONTAINER SYSTEM



STANDARD	CONTAINER	WITH FILTER*
Not	for sale in Ger	many

LID COLO	DUR		
Height	NON PERFORA	TED BOTTOM	PERFORATED BOTTOM
mm	9	SMALL 285x280 mm	
	1 filt	ter	2 filter
100	37000	37010	37030
135	37001	-	37031
150	37002	37012	37032
200	37003	-	37033
260	37004	-	-
	M	IEDIUM 465x280 r	nm
	1 filt	ter	2 filter
400	27050	27000	27000

	1 1110	ei	Z IIItei
100	37050	37060	37080
135	37051	-	37081
150	37052	37062	37082
200	37053	-	37083
	L	ARGE 580x280 mr	n
	2 filt	er	4 filter
100	37100	37110	37130
135	37101	-	37131

	L	AITOL JOUREOU IIII	
	2 filte	er	4 filter
100	37100	37110	37130
135	37101	-	37131
150	37102	37112	37132
200	37103	-	37133
260	37104	-	-

\*Perforated bottom allows much quicker sterilization process (half time than with not perforated).



WIRE BASKET - stainless steel			
Size		Height	
mm	50 mm*	70 mm**	100 mm***
255x245	37301	37302	37303
405x255	37306	37307	37308
540x255	37311	37312	37313

\*Suggested for container with height 100/135 mm \* Suggested for container with height 135/150 mm

\*\*\* Suggested for container with height >150 mm



BARRIER	SYSTEM CONTAINER WITH VALVE**
	Not for sale in Germany

NON PERFORATED BOTTOM    37180   37181   37182   37182   37182   37182   200   37153   -	LID COLC	DUR		
SMALL 285x280 mm	Height	NON PERI	FORATED BOTTOM	PERFORATED BOTTOM
135 37151 - 37181 150 37152 37162 37182 200 37153 - 37183 260 37154			SMALL 285x280 m	m
150 37152 37162 37182 200 37153 - 37183 260 37154  MEDIUM 465x280 mm  100 37200 37210 37240 135 37201 - 37241 150 37202 37212 37242 200 37203 - 37243  LARGE 580x280 mm  100 37250 37260 37280 135 37251 - 37281 150 37252 37262 37282 200 37253 - 37283 260 37254			37160	
Text	150	37152	37162	37182
100 37200 37210 37240 135 37201 - 37241 150 37202 37212 37242 200 37203 - 37243  LARGE 580x280 mm  100 37250 37260 37280 135 37251 - 37281 150 37252 37262 37282 200 37253 - 37283 260 37254			-	3/183
135 37201 - 37241 150 37202 37212 37242 200 37203 - 37243			MEDIUM 465x280 n	nm
LARGE 580x280 mm       100     37250     37260     37280       135     37251     -     37281       150     37252     37262     37282       200     37253     -     37283       260     37254     -     -	135 150	37201 37202	-	37241 37242
100         37250         37260         37280           135         37251         -         37281           150         37252         37262         37282           200         37253         -         37283           260         37254         -         -	200	37203	-	
135     37251     -     37281       150     37252     37262     37282       200     37253     -     37283       260     37254     -     -			LARGE 580x280 mi	m
<b>200</b> 37253 - 37283 <b>260</b> 37254	135	37251	-	37281
	200	37253	37262 -	
	260	37254	-	-

\*\*This system is preferred when is requested continuous use of containers, it avoids

37320

37321




GIMA code	ACCESSORIES
37320	Silicone mat 220x230 mm - perforated - small
37321	Silicone mat 380x230 mm - perforated - medium
37323	Silicone mat 520x230 mm - perforated - large
37325	S/S Filter holder for paper/textile Ø 18 cm
37328	Disposable Paper filter Ø 18.6 cm with steam
	indicator - box of 100
37329	Reusable Textile* filter Ø 20.5 cm - standard container
37330	Plastic security seal - box of 100
37332	Plastic security seal with steam indicator - box of 100
37333	Container card with steam indicator 68x37.5 mm - box of 250
Long term t	extile filters can be used for 45-50 sterilizations

# **ALUMINIUM BOXES**

- 26662 ALUMINIUM BOX 17.5x7.6xh 2 cm
- 26663 ALUMINIUM BOX 18.5x9.5xh 3 cm
- 26664 ALUMINIUM BOX 21.8x10.6xh 3 cm
- 26665 ALUMINIUM BOX 21.8x10.6xh 5 cm

Useful containers for the sterilization of surgical instruments and to maintain them sterile. Silicone tray not included. Nice aluminium box with blue base and silver cover.

• 26672 SILICONE TRAY 20x10 cm (for 26669, 26664, 26665)



# ROUND STERILIZER DRUMS - STAINLESS STEEL AISI 304



STERILIZER DRUMS STERILIZER DRUMS 26673 Ø 120x h 120 mm 26682 Ø 240x h 240 mm 26675 Ø 150x h 100 mm 26683 Ø 290x h 160 mm 26674 Ø 150x h 150 mm 26684 Ø 290x h 240 mm 26676 Ø 165v h 120 mm 26687 Ø 290x h 290 mm 26678 Ø 180x h 180 mm 26689 Ø 340x h 180 mm **26680** Ø 190x h 160 mm 26688 Ø 340x h 240 mm **26677** Ø 190x h 240 mm 26685 Ø 340x h 340 mm 26681 Ø 240x h 160 mm 26686 Ø 390x h 250 mm 26679 Ø 240x h 190 mm

ROUND STERILIZER DRUMS for autoclave and hot air sterilizer. Cylindrical containers used to sterilize dressing materials (gauze compress or cotton etc.) in a steam sterilizer (autoclave) or hot air sterilizer and to keep them as "sterile". Drums have an effective closing lid with a clip lock system, a carrying handle, air vents system to allow steam to circulate freely during the sterilization cycle/process. Easy to operate lateral air vent system to be manually closed after sterilization.

# STAINLESS STEEL BOXES WITH OR WITHOUT HANDLE



STAINLESS STEEL BOXES - Autoclavable 125°C

- 26653 STAINLESS STEEL BOX 18x8xh 4 cm
- 26654 STAINLESS STEEL BOX 20x10xh 6 cm
- 26655 STAINLESS STEEL BOX 25x12xh 6 cm
- 26656 STAINLESS STEEL BOX 30x15xh 6 cm
- 26657 STAINLESS STEEL BOX 50x20xh 10 cm
- 26672 RUBBER TRAY 20x10 cm for 26654



STAINLESS STEEL BOXES WITH HANDLES - Autoclavable 125°C

- 26668 STAINLESS STEEL BOX 18x8xh 4 cm
- 26669 STAINLESS STEEL BOX 20x10xh 4.5 cm
- 26670 STAINLESS STEEL BOX 25x12.5xh 4.5 cm • 26671 STAINLESS STEEL BOX 30x15xh 6 cm
- 26667 STAINLESS STEEL BOX 50x20xh 10 cm
- 26672 RUBBER TRAY 20x10 cm for 26669

# **BUCKETS WITH LID - STAINLESS STEEL**

- 26576 BUCKET WITH LID 12 I 290x300 mm
- 26577 BUCKET WITH LID 15 I 322x307 mm
- Stainless Steel AISI 304 buckets autoclavable at 121°C.



# DISPOSABLE KIDNEY DISH S/S KIDNEY DISHES - AUTOCLAVABLE 121°C



 26645 DISPOSABLE KIDNEY DISH - box of 300 pcs Safe, clean, easy to use, atoxic and latex free. Suitable for medical use.

Material: Resistance: Maximum capacity: Medical device

#### TECHNICAL SPECIFICATIONS

moulded paper pulp 36 hours to water, 4 hours to organic liquids about 750 ml

biodegradable and compostable 93/42 CE - Class I non sterile



#### **ECONOMIC S/S KIDNEY DISHES**

S/S Kidney dishes, autoclavable 121°C, with 0.5 mm thickness

is maney distres, datociarable 121 e, their ois initi tinetiness				
GIMA code	ECONOMIC S/S KIDNEY DISHES	Capacity		
26642 26643	Tray 6"- 162x77x31 mm Tray 8"- 207x98x39 mm Tray 10"- 247x122x43 mm Tray 12"- 309x149x59 mm	190 ml 400 ml 600 ml 1500 ml		

# S/S AISI 304 - 18/8 KIDNEY DISHES - THICKNESS 0.6 MM - AUTOCLAVABLE 121°C



code	SHALLOW KIDNEY DISHES	Capacity
26610	Tray 8" - 207x128xh 33 mm	
26611	Tray 10"- 254x141xh 33 mm	750 ml
26612	Tray 12"- 280x141xh 40 mm	1600 ml



GIMA code	DEEP KIDNEY DISHES	Capacity
26580 26581 26582 26583	Tray 6"- 162x77x31 mm Tray 8"- 207x98x39 mm Tray 10"- 247x122x43 mm Tray 12"- 309x149x59 mm	



	GIMA DEEP WITH COVER' code KIDNEY DISHES		Capacity	
	26584	Tray 7" - 200x95x35 mm	300 ml	
	<b>26585</b> Tray 10"- 247x122x43 mm <b>26589</b> Tray 12"- 309x149x59 mm		600 ml	
			1500 ml	
	*Thickness			

# S/S AISI 304 - 18/8 WASH BASINS AND GALLIPOTS - AUTOCLAVABLE 121°C



26587 Ø 318x h 84 mm - deep

7		26622			
city	GIMA code	ROUND GALLIPOTS	Capacity		
		Ø 107xh 56 mm Ø 158xh 75 mm	325 ml 940 ml		
I	26622	Ø 208xh 84 mm Ø 258xh 92 mm	1940 ml 3200 ml		
. 11	al Dasins	and Callingtone india			



26616 Ø 56xh 32 mm 50 ml 26617 Ø 88xh 46 mm 170 m 40 ml **26618** Ø 128xh 60 mm 450 ml Ø 158xh 75 mm 940 ml 00 ml 26619

# STAINLESS STEEL HOLLOWARE - AUTOCLAVABLE 121°C - AISI 304



STAINLESS STEEL HOLLOWARE Stainless steel AISI 304 holloware with minimum thickness 0.6 mm.

Autociava	able at 121 C.
GIMA code	INSTRUMENT TRAYS - ANGLED EDGES
	Without cover
26603	306x196x h 50 mm
26604	355x254x h 50 mm
26597	380x304x h 50 mm
26598	440x320x h 64 mm
	With cover
26607	306x196x h 50 mm
26608	355x254x h 50 mm
26609	440x320x h 64 mm



GIMA code	INSTRUMENT TRAYS ROUND EDGES
	Without cover
26599 26602	223x126x h 45 mm 264x172x h 47 mm
	With cover
26605	223x126x h 45 mm
26606	264x172x h 47 mm



code	DENTAL TRAY
26600	208x109x h 15 mm
	INSTRUMENT TRAYS
26601 26629	210x160x h 25 mm 313x218x h 31 mm



code	MAYO TRAYS - SHALLOW
26613	254x165x h 18 mm
26614	350x252x h 16 mm
26615	432x295x h 19 mm



• 26592 BED PAN ROUND WITH COVER -320x85 mm



DRESSING JAR WITH LID

- 26623 DRESSING JAR 0.5 | Ø 102x65 mm 26627 FORCEPS JAR Ø 55xh 180 mm
- 26625 DRESSING JAR 2 | Ø 127x161 mm Ø 33xh 80 mm



- 26624 DRESSING JAR 1 | Ø 103x126 mm 26628 THERMOMETER JAR -



• 26590 BED PAN FRACTURE TYPE with ring - 418x292x85 mm



• 26578 MALE URINAL - 1.2 |



• 26594 BED PAN FRACTURE TYPE with tube handle - 418x292x85 mm





• 26579 FEMALE URINAL - 1.2 |



• 26593 BED PAN PERFECTION TYPE



• 26591 MALE VERTICAL URINAL Ø 114x220 mm - 1.5 l

# HYPODERMIC SYRINGES IN 3 PARTS WITH AND WITHOUT NEEDLE

High-quality range of medical devices ensuring an optimal safety. The range of Hypodermic syringe INJ/LIGHT have been manufactured in compliance with the most important international standards in conformity with European Directive 93/42/EEC and with UNI EN ISO 9001/2000 - UNI EN ISO

13485/2004.			$(\mathbf{X})$		
	SYRINGE WITHOUT NEEDLE				
GIMA	Capacity	Minimum	GIMA		
code	LUER LOCK CONE	order	code		
23808	10 ml	box of 100	23822		
23809	20 ml	box of 50	23824		
23810	30 ml	box of 50	23825		
23811	60 ml	box of 25	23827		
	es diniminini		23828		
	Contract of Section		23830		
	CENTRIC LUER CONE				
23813	3 ml	box of 100			
23814	5 ml	box of 100			
23815	10 ml	box of 100			
	ECCENTRIC LUER CONE				
23816	10 ml	box of 100	23833		
23817	20 ml	box of 50	23834		
23819	60 ml	box of 25			
	diministration and the second				
	127		Needle		

SYRINGE WITH NEEDLE Assembled needle Capacity code **CENTRIC LUER CONE** 3822 1 ml - tubercolin 26G - 0.45x12.7 mm box of 100 23824 21G - 0.8x38 mm | box of 100 2.5 ml 23825 2.5 ml\* 22G - 0.7x32 mm box of 100 21G - 0.8x38 mm box of 100 2827 5 ml 23828 5 ml 22G - 0.7x32 mm box of 100 23830 21G - 0.8x38 mm box of 100 10 ml \*Extended scale: 3 ml **ECCENTRIC LUER CONE** 23833 10 m 21G - 0.8x38 mm | box of 100

The INJ/LIGHT line is completely non-toxic and non-pyrogenic,

made of transparent polypropylene with graduated black colour scale and individually packed in blister pack.

Box in GB, FR, IT, ES, DE, PT, GR, RO, RU, YU, SA.

STERILE EO (NHT (NEX) (1370) Medical Device class IIa





20 m



21G - 0.8x38 mm box of 50

# HYPODERMIC NEEDLES AND SCALP-VEIN SETS - STERILE

A line of hypodermic needles and scalp vein sets ensuring minimal trauma during penetration thanks to the triple bevelling. Each element of the needle is treated for painless injection. 23785

The needles are in stainless steel AISI 304 with triple bevelling and totally non-toxic

23820

23821

Hypodermic needle Hypodermic safety needle

	HYPODERIMIC NEEDLES						
Standard	Safety	Needle	Colour	Minimum order			
23757		18G - 1.2x38 mm 19G - 1.1x38 mm 20G - 0.9x38 mm 21G - 0.8x38 mm 22G - 0.7x32 mm 23G - 0.6x25 mm 25G - 0.5x16 mm 26G - 0.4x12.7 mm 27G - 0.4x12.7 mm	Pink Cream Yellow Green Black Turquoise Orange Brown Grey	box of 100 (standard needles) box of 50 (safety needles)			

and non-pyrogenic. Needles have Luer-slip cone, can be mounted on syringes with Luer-slip or Luer-lock. The scalp vein set needles are provided with soft flexible grained wings. The tube is made of 30 cm PVC with luer-lock. Individually packaged in blister. Box and instructions: GB, FR, IT, DE, ES, PT, GR, RU (Scalp-vein sets) GB, IT, ES, PT (Hypodermic needles).



		N SE I S		
Standard	Safety	Needle	Colour	Minimum order
23766	-	19G - 1.1x19 mm	Cream	box of 100
23767	-	20G - 0.9x19 mm	<ul> <li>Yellow</li> </ul>	box of 100
23768	23774	21G - 0.8x19 mm	<ul> <li>Green</li> </ul>	box of 100
23769	-	22G - 0.7x19 mm	<ul> <li>Black</li> </ul>	box of 100
23770	23776	23G - 0.6x19 mm	<ul> <li>Turquoise</li> </ul>	box of 100
23771	-	25G - 0.5x19 mm	<ul> <li>Orange</li> </ul>	box of 100

# 5 ml SYRINGE - RETAIL BOX



5 ml SAFETY SYRINGE - RETAIL

• 23796 SAFETY SYRINGE 5 ml With needle 23G 0.60x25 mm. Sterile, packed in single blister. Box of 5 syringes. Minimum order:





# BD EMERALD™ SYRINGES ■ BD PLASTIPAK™ SYRINGES

Minimizes Waste Disposal Flange Size and Shape To provide stability and To reduce slippage during Has up to 30% less material comfort during use than other syringes administration € 0318 mluuluuluul 2

Green Stopper and **Bold Scale Markings** To aid in setting an accurate dose

CÍear Barrel Robust Retaining Ring To allow for To help prevent accidenta visualization of fluid plunger rod pullout

BD EMERALD™ SYRINGES							
GIMA code	BD code	Capacity	NEEDLE	Minimum order			
SYRINGES WITHOUT NEEDLES - LUER SLIP CENTRIC TIP							
23863	307727	2 ml		box of 100			
23864	307731	5 ml		box of 100			
23865	307736	10 ml		box of 100			
	SYRINGE	S WITH I	NEEDLES - LUER SLIP CENTRIC	TIP			
23868	307728	2 ml	22G - 0.7x30 mm	box of 100			
			22G - 0.7x30 mm	box of 100			
23870	307737	10 ml	21G - 0.8x40 mm	box of 100			






	order			BD PL	.ASTIPAK'" SYRINGES			
ΓF	box of 100	GIMA code	BD code	Capacity	MODEL	Minimum order		
	box of 100		SYRINGES WITHOUT NEEDLE - LUER LOCK					
	box of 100	23873	301229	30 ml	Luer - lock	box of 60		
IC	TIP	23874	300865	50 ml	Luer - lock	box of 60		
	box of 100		SYRING	<b>ES WITH</b>	<b>OUT NEEDLE - CATHETER CO</b>	NE		
	box of 100	23877	300867	50 ml	Catheter cone	box of 60		
	box of 100	23878	300605	100 ml	Catheter cone	box of 25		

# BD MICROLANCE™ NEEDLES

GIMA code	BD code	BD MICROLANCE™ NEEDLES	Minimum order
23739	304622	18G - 1.20x40 mm - pink	box of 100
23740	301500	19G - 1.10x40 mm - white	box of 100
23741	301300	20G - 0.90x40 mm - yellow	box of 100
23742		21G - 0.80x40 mm - green	box of 100
23743		22G - 0.70x30 mm - black	box of 100
23744	300800	23G - 0.60x25 mm - blue	box of 100
23745	300600	25G - 0.50x16 mm - orange	box of 100
23746	303800	26G - 0.45x13 mm - brown	box of 100
23747	300635	27G - 0.40x13 mm - grey	box of 100
23748	304000	30G - 0.29x13 mm - yellow	box of 100



# BD MICRO-FINE™ INSULIN NEEDLES AND SYRINGES



GIMA code	BD code	BD MICRO-FINE™ NEEDLES	Minimum order			
23850	320140	BD Micro-Fine needles 4 mm - 32G	box of 100			
23851	320594	BD Micro-Fine needles 5 mm - 31G	box of 100			
23852	320592	BD Micro-Fine needles 8 mm - 31G	box of 100			
Compatible with most of insuline pens available on the market (Sanofi-Aventis, Eli Lilly,						
Novo Nordisk, Owen Mumford)						

#### BD MICRO-FINE™ SYRINGES 23860 | 324826 | BD Micro-Fine syringes 0.3 ml - 8 mm - 30G | box of 100 23861 324825 BD Micro-Fine syringes 0.5 ml - 8 mm - 30G box of 100

# INSULIN SYRINGE INSU/LIGHT



Available with assembled needle or fixed needle both with no-dead space. Insulin syringes with fixed needle have the needle directly fixed on the cone and have a double protection (needle cap and plunger cap), assuring the sterility of the device. Non-toxic and non-pyrogenic, made of transparent polypropylene with graduated insulin scale. Needle in stainless steel AISI 304 with triple bevelling.

GIMA	INSULIN SYRINGE NO DEAD SPACE -	Minimum	GIMA insulin per
code	ASSEMBLED NEEDLE	order	GIMA insulin per GIMA insulin per
23802	Insulin syringe 1 ml - 25G - 0.5x16 mm	box of 100	GIMA insulin per
	INSULIN SYRINGE NO-DEAD SPACE		le with most of insulin pe
23805	Insulin syringe 0.5 ml - 30G - 0.3x8 mm	box of 100	li Lilly, Owen Mumford)

# INSULIN PEN NEEDLES



Insulin Pen Needles are disposable, sterile needles used with insulin pens to control high blood sugar in adults and children with diabetes mellitus. With a fine design to minimize the discomfort of injection, ultra-thin needles provide painless and a non traumatic injection due to a silicone film. Pyrogen free.

GIMA code	GIMA INSULIN PEN NEEDLES - UNIVERSAL	Minimum order
23840	GIMA insulin pen needles 4 mm - 32G	box of 100
		box of 100
		box of 100
		box of 100
Compatib	le with most of insulin pens available on the market (Sanofi-A	ventis, Novo

# MESO-RELLE MESOTHERAPY AND SCLEROTHERAPY NEEDLES



Meso-relle disposable hypodermic needles are multiple sharpened to facilitate penetration. Stainless steel AISI 304 cannula and polypropylene connection for syringe.

Sterilized with ethylene oxide. Sold in individual blister made of medical paper. Made in Italy.

			$\cdot$ $\cdot$					
	GIMA code	MES	MESOTHERAPY LUER NEEDLES					
	code	Gauge	Ø mm	Length mm	Colour	order		
	23670	27G	0.40	4	grey	box of 100		
	23671	27G	0.40	6	grey	box of 100		
	23672	30G	0.30	4	yellow	box of 100		
	23673	30G	0.30	6	yellow	box of 100		
	23674	31G	0.26	4	light blue	box of 100		
	23676	32G	0.23	4	pink	box of 100		
	23678	33G	0.20	4	green	box of 100		
SCLEROTHERAPY/FILLER LUER NEEDLES								
	23680	30G	0.30	12	yellow	box of 100		
	23682	31G	0.26	12	light blue	box of 100		

pink box of 100

# MICRO-MESOTHERAPY

# MESO-RELLE MULTI-INJECTORS

0.23



## MESO-RELLE MICRO-MESOTHERAPY

Microtherapy, an evolution from mesotherapy, is a recent technique for administration of drugs via superficial intraderma injection, and it is an additional technique to intramuscular intra-venereal and

Single use device with the shape of a reversed cone with in its centre a special ultrafine needle subcutaneuous injections

GIMA code	MICRO	Minimum				
code	Type	Gauge	Ø mm	Length mm	Colour	order
23690	Needle	27G		2.5	white	box of 25
23691	Needle	30G		2.5	yellow	box of 25
23694	S.I.T.*	31G	0.26	2.5	white	box of 25
in Injection Thorany						



32G

23684

23700 23701 MESO-RELLE MULTI-INJECTOR CONNECTORS

Meso-relle disposable mesotherapy multiinjectors connectors are sterilized with ethylene oxide.

They are packed in individual, transparent blister, are colourless and transparent to enable full examination of the inner chamber and are perfectly resistant to high pressure.

ı	GIMA	MULTI-II	MULTI-INJECTOR CONNECTORS			
	code	Type	Way-out	Taper	order	
	23700	Straight	3	Luer	box of 50	
	23701	Straight	5	Luer	box of 50	
	23703	Circular	5	Luer	box of 50	

# I.V. CATHETERS WITH STRAIGHT HUB OR SIDE PORT - STERILE



force by 25 to 3	0%		suturing or tap	ing	
Conventional	Safety	I.V. CAT			
no protection		Gauge	Gauge mm	Colour	order
23720	23725	18G	45 mm (1¾")	Green	box of 50
23721	23726	20G	32 mm (11/4")	Pink	box of 50
23722	23727	22G	25 mm (1")	Blue	box of 50



um	Conventional no protection	Safety	I.V. CA	THETER WITH	SIDE PORT	Minimum
r	no protection		Gauge	Gauge mm	Colour	order
50	23730	23735	18G	45 mm (1¾")	Green	box of 50
50	23731	23736	20G	32 mm (11/4")	Pink	box of 50
50	23732	23737	22G	25 mm (1")	Blue	box of 50

# BD VENFLON™ IV CATHETERS - STERILE

#### BD VENFLON™ IV CATHETERS

I.V. Cannula Luer-Lock with a plug attached to the flow control plug. Designed to gain access to peripheral veins of the patient's blood system for rehydration, parenteral nutrition, medication delivery, blood transfusion, and monitoring

GIMA	BD	BD	$\textbf{VENFLON}^{\text{\tiny{TM}}} \textbf{ I.V.}$	CATHETE	RS	Minimum
code	code	Gauge		Flow rate	Colour	order
23715	391453	18G	45 mm (1¾")	80	Green	box of 50
23716	391452	20G	32 mm (11/4")	54	Pink	box of 50
23717	391451	22G	25 mm (1")	31	Blue	box of 50
53						

Flash Back Function - During the insertion of the cannula, blood flow is visualized by blood flash back in the hub of the cannula









# INFUSION SET

# INFUSION SETS

Infusion set includes: ABS spike with air vent, PVC chamber PVC tube 150 cm, ABS roller. ABS luer lock terminal without needle. latex free injection site.

needle-less closed circuit.

Sterilized by Ethylene oxide.

26069 INFUSION SET - polybag - box of 500
 26064 INFUSION SET - blister - box of 360 (18 box of 20)

**NEEDLE-LESS VALVE** 

• 26059 NEEDLE-LESS VALVE - sterile - box of 500

Device for I.V. infusion and/or withdrawal

male luer-lock standard connections. PVC free This closed and self-sealing protection system allows to infuse or

For protection of vascular access and of

all infusion systems equipped with

# INFUSION SET FOR PUMP

• 26073 ARIES I.V INFUSION SET -box of 150 (6 bags of 25) Infusion set for the administration of solution into the human body with pump



# BD SPINAL NEEDLES

Single use latex free sterile BD quincke point spinal anesthesia needles.

Multilanguage box and instructions.





inject fluid, make w	rithdrawals ( C 0123					
1	eliminating the risk of accidental	1000	GIMA code	BD code	BD QUINCKE POINT SPINAL ANESTHESIA NEEDLE - STERILE	Minimun order
	puncture to operators and reducing the risk of contamination to patients. Medical Device Class I.	26059	23707 23709 23710	405253 405256 405240	18G 3.50 IN 1.2x90 mm - pink 20G 3.50 IN 0.9x90 mm - yellow 22G 3.50 IN 0.7x90 mm - black 23G 3.50 IN 0.64x90 mm - turquoise	
			73711	405257	25G 3 50 IN 0 5x90 mm - orange	hox of 2

# MARGHERITA FINGERGUARD FOR HYPODERMIC NEEDLES



THE PROBLEM: there are 960,000 accidental syringe stick injuries every year in Europe. The total cost estimate resulting from syringe needle stick injuries exceeds 1 billion Euros

LEGISLATION: European Directive 2010/32/EU requires Member States to adopt more effective provisions to protect workers from accidental needle stick injuries from syringes.

THE SOLUTION: margherita allows total safety to operator and to healthcare workers responsible for the disposable of sharps.

#### • 23798 MARGHERITA FINGERGUARD

Margherita is a Class I Medical Device that allows the operator to recap and remove the syringe needle in complete safety, eliminating the risk of accidental needle sticks to both healthcare workers and those responsible for the disposal of sharps. **Sterilizable:** autoclavable (121°C for 15 min. or 135°C for 5 min.) Ecological: promotes waste sorting as it enables just the needle to be disposed of in the sharps bin. Raw materials are biocompatible.

Safe: complete protection against accidental syringe needle sticks. Economical: last 4 years, reducing costs by at least 50,000 € per year for a small hospital and over 200,000 € per year for a

medium/large hospital. NEEDLE UNCAP









# GIMA SECURITY SYSTEM TO FUSE NEEDLES UP TO Ø 1.6 mm

#### • 25820 SECURITY SYSTEM - needle destroyer

To avoid accidents from used injection needles, GIMA has developed and patented Security System.

This Needle Destroyer generates a temperature of 1,000°C, hot enough to destroy stainless steel and all known bacteria/viruses. It fuses in 1-2 seconds needles up to a diameter of 1.2 mm and with some more seconds needles up to 1.6 mm

# Safe for nurses, doctors, cleaning staff and patients. Most of accidents by punctures with needles take place in the

following circumstances that are avoided using the Needle Destroyer: placing the needle in its protective sheath, discarding a needle from a used syringe, carrying hospital residues.

Destroyed needle material is sterilized and stored in a drawer at the bottom of the unit.

#### Long life and easy maintenance

It is sturdy, over 4 kg weight, and manufactured in best quality material. Only necessary maintenance is to change fusing spare parts every 4,000 needles.
• 25821 FUSING SPARE PARTS minimum order: 2 pcs.

#### TECHNICAL SPECIFICATIONS

Size: cm 22x14x h 9 Weight: 4 kg Operating voltage: 220 V - 50/60 Hz Fusion temperature: 1.000°C

Power: 90 Watt Fuses: 2x2,5 A T Norms: CEI 62-5 - IEC 601-1 Made in Italy: GIMA S.p.A.



# GIMA SHARPS CONTAINERS





- easy to use with just one hand

- maximum filling level indicator

- temporary and permanent closure

the incineration process

possible side fastening

- double opening system: needles and

insulin pen removal, entire syringe disposal

- no emission of any harmful gas during

- pocket size

- ergonomic shape









Wide opening



opening with just one hand

voluminous material

the incineration process

insulin needles

- wide opening for the disposal of

- mechanism for the unhooking of

- maximum filling level indicator

Indents for





25790

Indents for

needles removal

with safety fins

25793



25795

25792

Temporary closure Definitive closure

- anti-defluxion wings that prevent the outflow of the waste

- mechanism for unhooking insulin

- maximum filling level indicator

- no emission of any harmful gas during - no emission of any harmful gas during the incineration process

GIMA code	POCKET SHARPS CONTAINER	Minimum order	GIMA code	PBS SHARPS CONTAINERS	Minimum order
25780	Pocket 0.4 I - 12.3x6.2x16.5h cm	box of 70	25790	PBS 0.6 I- Ø 10x14.5h cm	box of 100
	CS LINE SHARPS CONTAINERS			PBS 1.5 I- Ø 14x16.7h cm	box of 100
	CS 3 l - 16.7x16.7x22.2h cm CS 4 l - 16.7x16.7x28.5h cm	box of 50 box of 40	25793	PBS 2 I - Ø 14x21h cm PBS 5 I - Ø 23x19.5h cm PBS 7 I - Ø 24.8x19.5h cm	box of 75 box of 55 box of 40
CERTIFI	CATIONS 💮 🐠 🛱 FDA K	071517		PBS 12 I - Ø 24.8x31.34h cm	box of 25

# WASTE CONTAINERS - 30-50-60

#### WASTE CONTAINERS - 3 sizes

- extremely solid and shock resistant at high and low temperature
- hermetic seal by peripheral adhesive on the lid (single or double)
- lateral handles
- excellent stacking possibilities

GIMA	WASTE CONTAINERS							
code	Tide	Lid	Max load kg	Size				
25774	Container 30 I	single	15	40x30x39 cm h				
25775	Container 30 I	double	15	40x30x39 cm h				
25776	Container 50 I	single	20	40x30x56 cm h				
25777	Container 50 I	double	20	40x30x56 cm h				
25778	Container 60 I	single	25	40x30x65 cm h				
25779	Container 60 I	double	25	40x30x65 cm h				



# **BD SHARPS CONTAINERS**


#### SHARPS CONTAINERS BECTON-DICKINSON

Space saving containers, autoclavable at 121°C, with safety cover. Conform to BS7320:1990, NF x 30-500, ADR UN 3291 • 25822 BD SHARPS CONTAINER 1.5 I - 16.5x16xh 20.5 cm

- 25823 BD SHARPS CONTAINER 3 I 18.2x18.1xh 26 cm
- 25827 WALL SUPPORT for 25823
- 25828 BD SHARPS CONTAINER 7 I 30.4x22.2xh 25.5 cm
- 25829 BD SHARPS CONTAINER 22.7 I 32x22.7xh 44.5 cm



# Tourniquets in Latex, Rubber-Cotton and Latex-Free



#### **GIMA TOURNIQUETS**

Gima provides efficient and simple solutions

for professional medical use with its range of tourniquets. Latex: Ø 5 mm, for manual use

Velcro: for easy fastening

Velcro "D" buckle: self applicable made of a nylon band threads through plastic "D" buckle

Lock system: self applicable with a quick release system. Multilanguage box (excluding 25733): GB, FR, IT, DE, ES, PT, GR, Arab

veic	io system				
D. (		LCRO /			
	Colour	Length	Fa	stening systems	Origin

GIMA code	TOURNIQUETS	Material	Colou	r	Length cm	Fastening systems	Origin
2573	TUBOLARE Tourniquet - box of 200	Latex	Yellow		33	Manual	Europe
2572	I GIMA Tourniquet	Rubber-cotton	Yellow		40	Velcro	Asia
2572	STRIP-VELCRO Tourniquet	Velcro	Green		45	Velcro+ring: use with one hand	Asia
2572	7 FAST Tourniquet	Rubber-cotton	Red		40	Single lock system: quick release	Asia
2572	FAST Tourniquet	Rubber-cotton	Green		40	Single lock system: quick release	Asia
2572	FAST Tourniquet	Rubber-cotton-latex free	Blue		40	Single lock system: quick release	Asia

# JETPULL 2 WITH GRADUAL ADJUSTMENT - MADE IN GERMANY



#### JETPULL 2 WITH GRADUAL ADJUSTMENT

Easy to use, allows single-hand operation.

The patented 2 button system allows an easy opening of the fastening with 2 choices: smooth or fast, even when under tension. Fastening device is made using recycled plastics (PVC free). Ribbon is in special material to avoid any skin bruises. Blood proof Washable at 60/90° C and autoclavable. Made in Germany.

ope	tighten	slow release
of.		

GIMA code	TOURNIQUETS	Material	Colour	Length cm	Fastening systems	Origin
25722	JETPULL 2 Tourniquet	Rubber-cotton	Blue	56	Double lock system: quick and slow release	Germany
25723	JETPULL 2 Tourniquet	Rubber-cotton -latex free	Green	56	Double lock system: quick and slow release	Germany
25724	JETPULL BABY Tourniquet	Rubber-cotton	Child design	56	Double lock system: quick and slow release	German

# SHARPS CONTAINERS UP TO 72 CM LONG SHARPS CONTAINERS

Disposable containers for the elimination of long objects up to 72 cm, such as biopsy forceps and sharps. Large opening, for elimination of bulky

objects, temporary and definitive closure, ergonomic handle.

		25797	257
GIMA code	LONG SHARPS CONTAINERS		
25798	Magnum 6.3 l - 17.2x12x62.1 cm Magnum XL 8.3 l - 17.2x12x85.3 cm Fixing system* - horizontal or vertical		
* Suitable	for wall or trolley		

# TAPE TOURNIOUET

• 25740 TAPE TOURNIQUET - latex free - disposable Latex free disposable tape tourniquet made in TPE. Each box contains 25 pre-cut tourniquets 42x2.5 cm (18"x1") with 0.5 mm thickness.

latnull system



25722

# HIGH QUALITY LEATHER BAGS - MADE IN ITALY



27126 PRIMATO prime leather - colour: leather

2 inside partitions, one with articles-holder, and large zipfastener pocket. External large zip-fastener pocket, burnished



· 27110 TEXAS leather - colour: chestnut Rigid bottom, inside pocket with button fastening, burnished



- 27115 SUPERTEXAS leather colour: black
- 27116 SUPERTEXAS leather colour: chestnut
- 27118 SUPERTEXAS leather colour: bordeaux

With outer pocket and inside zip fastener pocket, 2 burnished locks, inside transversal partition 8 cm from side, large central

27120

# OUALITY LEATHER BAGS



- 27122 FLORIDA leather colour: black
- 27123 FLORIDA leather colour: brown Rigid bottom, inside zip fastener central pocket, lateral inside pocket, burnished lock.



colour: leather

Rigid bottom, inside zip-fastener



# KANSAS BAGS - 5 COLOURS • 27095 KANSAS skav - black

• 27096 KANSAS skay - chestnut

• 27097 KANSAS skay - electric blue

• 27098 KANSAS skay - ochre

• 27099 KANSAS skay - brown Rigid bottom, outer velcro pocket inside partition, inside zip pocket, lock with key.

Made in Asia - Italian design. **AVAILABLE IN** 

**ANY COLOUR** minimum order 200 pcs

57

External dimensions 42x20xh 24 cn 27095 27097 27096 27098 27099

# SIMULATED LEATHER BAGS - MADE IN ITALY



• 27100 TEXAS skay - colour: black • 27101 TEXAS skay - colour: cognac

Rigid bottom, inside pocket with button fastening, burnished lock



• 27108 LARGE POLUS skay - colour; cognac Rigid bottom, inside zip fastener folding pocket, elasticated retainers for instruments on both inside sides.

SHIVER COOLBOX 30 I

#### • 27214 SHIVER COOLBOX 30 I External size: 29.7x39.5xh 48.5 cm Inner size: 33x24xh 42 cm

- Equipped with ice packs 2x400 ml
- box of 2

# TECHNICAL SPECIFICATIONS Material: polypropylene

Insulation: high density expanded polyurethane foam Lid featuring built-in 2x400 icepacks holder with swing locking system Vertical space for up to six 2-litres

Gasket between body and lid for improved sealing



• 27104 INFERMIERA skay - colour: cognac Rigid bottom, inside zip fastener pocket and inside folding pocket, burnished lock



• 27105 SUPERTEXAS skay - colour: cognac With outer pocket and inside zip fastener pocket, 2 burnished locks, inside transversal partition 8 cm from side, large central area.

# PROFESSIONAL VACCINE CARRIER

#### • 27211 PROFESSIONAL VACCINE CARRIER

Compact, extra strong with special insulation by high density PU foam • 27206 THERMAL ICE PACK - spare suitable for transportation of vaccine. Comes complete with 8 empty ice-packs 400 ml suitable for a cold life of 40 hours at 8°C with external temperature of 43°C without opening.

Vaccine storage capacity: 2.6 l. Body and lid with gaskets for better insulation.

External size: 28.5x25.5xh 32 cm. Internal size: 22x18xh 24 cm. Made in Italy.



# 67 CERTIFIED, TOUGH, DURABLE CASES - MADE IN ITALY



GIMA CASES

5 - Holes for double

- Stackable interlocking 8 - Thick body material 9 - Extra fixing points 10 - Fully length hinges

1 - Nylon pins, corrosion

the bottom and convolu-

ted foam in the lid 13 - Screen printing space

Pick N Pluck foams in

GIMA cases are IP67 certified tough, reliable 2 - Automatic pressure and extremely durable in any condition. release valve 3 - Easy to open double They offer superior protection from the throw latches 4 - Load tested soft grip elements, water, dust and impacts, making them suitable for a wide range of applications. Can be supplied with or without internal foam. padlocking 6 - Holes for shoulder strap

	13							
GIMA	CASES WITHOUT INTERNAL FOAM							
code		Internal size	External size					
27220 27221 27222	Medium - orange Medium - black Large - orange	426x290x159 h 426x290x159 h 500x350x194 h	464x366x176 h 464x366x176 h 555x428x211 h					

CASES WITH INTERNAL FOAM Medium - orange 426x290x159 h | 464x366x176 h 27227 Medium - black 426x290x159 h 464x366x176 h 500x350x194 h 555x428x211 h 27228 Large - orange

# PROFESSIONAL COOL BAG MEDI-TRAVEL COOL BAG



• 27210 MEDI EXECUTIVE PROFESSIONAL INSULATED COOL BAG • 27253 MEDI-TRAVEL COOL BAG - 23x11xh 21 cm Professional bag studied for lab samples and medicine transportation. Two compartments separated by inner removable panel; one for documents and one for medicines. Comes with 2 cube cases and 3 soft ice cooling cushions included. Size 38x25xh 31 cm. Capacity 26 l.





Compact cool bag for medicines. High quality insulating material and finish. Waterproof zips. Internal pocket with zip. Removable insulated base indipendently usable for storing 3 insuline or thermolabile medicines. Supplied with 2 reusable gel cushions.

• 27217 SOFT ICE TEMPERATURE PACK - display of 12

# MEDIPOCKET AND MEDINSULINE INSULATED COOL BAGS



**INSULATED COOL BAGS** 

Compact insulated bags for insulin and thermolabile medicines transport. High quality insulating material and finish. Waterproof zips. Internal pocket with zip.
Supplied with 1 reusable gel cushion.





Red/ Blue/ DarkGrey/ INSULATED white BAGS beige beige 27252 27207 27208 Medi Pocket 27201 27202 27203 Medinsuline 27217 Soft ice temperature pack - display of 12

# THERMAL BAG



• 27209 THERMAL BAG - Colour vellow - nvlon Thermal bag with pockets. Its temperature pack maintains cold or hot temperature for prolonged periods. Beautifully crafted, durable, insulated bag with detachable shoulder straps. 3 temperature packs included. Internal size: 30x23x21 cm. Made in Italy. 27206 • 27206 THERMAL BAG TEMPERATURE PACK - pack of 2

# DIABETIC BAG



• 27255 DIABETIC BAG - empty - blue

• 27254 MINI DIABETIC BAG - empty - blue Thermal pharmaceutical bags designed specifically for carrying medicines that must be kept at cool temperatures, ideal for

diabetics. Temperature pack included to provide a temperature of about 10°C for up to 10 hours. Exterior material is a water repellent vinyl nylon with a foam backing. Made in Italy.



• 27128 PROFESSIONAL BAG - empty

Practical doctor bag for easy transport of instruments and medications, provided with 8 internal movable divisions, 3 external pockets, 8 elasticated retaining, 1 internal pocket with zip. 1 removable mini bag (17x3xh 24 cm). Size: 36x22xh 25 cm.



MEDICAL BAGS

Professional versatile bag, designed for general practitioners and any professional. It includes: 3 detachable transparent pouches with velcro. 1 ampoule holder with 23 elastic bands with velcro. 1 large pouch with 4 dividers with velcro, clip paper board. document holder, various pockets. Shoulder strap, handle, hidden straps to carry on back. External size: 42x35x15 cm. Weight: 3.3 kg. Maximum recommended contents weight: 5 kg.

# For 9 large and AL BAGS 13 small phials

• 27129 MAXI VIAL BAG - red - 600D polyester - 29x24xh 7 cm The best way to protect, identify and organize up to 46 phials of any size. Made of two parts, with elastic strips for holding 9 big and 37 small ampoules.

• 27133 MEDICATION BAG - blue - 600D polyester - 34x24xh 7 cm Compact bag made in water-proof anti-scratch 600D polyester: 2 internal zip pockets and 9 elasticated retainers.

# THERMIC CUBE CASES

• 27204 THERMIC CASE small - 16.5x8.5xh 13.5 cm • 27205 THERMIC CASE medium - 16.5x8.5xh 18.5 cm Light and compact insulated bag, ideal for thermolabile medicines. Can be used alone or as accessory to cool



# PRO SPIKE FOR USED NEEDLES

#### 27149 PRO SPIKE

boxes and bags.

Pro spike is a small disposable plastic container for the separate collection of spiky and cutting wastes (needles, scalpels) on the operation

a clip so you can attach it to belts and backpacks. Made in plastic material. It can be disposed of

It has a clever lid with a safe closing system and with the contents. Size: 90x54x185 mm Weight: 88 q 27149

# DIATERMO BAG



• 27139 DIATERMO BAG - black - 600D polyester Designed to carry small electrosurgical units, audiometers, spirometers, ECG with their accessories. One division to separate device from accessories and one zip pocket.

# INSTRUMENT AND VIAL BAGS





GIMA	VIAL INSTRUMENT BAGS*	Size	Coloui	For
25745 26650	Vials bag Mini Vials bag Instrument bag Mini Instrument bag	19.5x15xh3 cm 18x14xh2 cm 19.5x15xh3 cm 18x14xh2 cm		12 vials 6 vials 12 instrum. 8 instrum.

\*Made in 600D polyester (external)

# SMART EMERGENCY BAGS



# POLYESTER WITH OUTER PVC COATING





Rubber bottom with feet Shoulder strans



Padded hottom and frontal nackat

27157

Large pocket

on top

SMART BAGS: polyester or polyester PVC coated - empty

Professional emergency bags extremely capacious with internal adjustable compartments which permit personalized organization of the space. Provided with external pockets, internal divisions, and one (2 for code 27153) removable pouch with transparent window. All bags are made in strong, water resistant 600D polyester. Available also with outer PVC coating (27155-8). Provided with double vellow reflective strips. Internal lining is removable for easy cleaning. Waterproof rubber bottom to prevent water infiltration. May be carried on shoulder or hand.

					110110	ui pocket
Polyester	Polyester PVC coated	Model	Colour	Size	Internal modular spaces	External pockets
27150	27155	Small	red	45x28xh 28 cm	3	4
27151	-	Medium	red	55x35xh 32 cm	6	4
-	27157	Medium	red	55x35xh 38 cm	6	5
27152	-	Medium	blue	55x35xh 32 cm	6	4
-	27158	Medium	black	55x35xh 38 cm	6	5
27153	-	Large	red	65x35xh 35 cm	6	5

Removable

lining

for easy

# EMERGENCY BAGS - POLYESTER OR POLYESTER PVC COATED



• 27165 EMERGENCY BAG - polyester - red - 35x45xh 21 cm

• 27166 EMERGENCY BAG - polyester PVC coated - red - 35x45xh 21 cm

• 27167 EMERGENCY BAG - polyester PVC coated - blue - 35x45xh 21 cm Capacious bag, despite the compact size. Large central compartment, 1 front and 3 lateral pockets. May be carried on shoulder (braces) or hand (2 handles).

2 lateral pockets 22x18 cm and 11x18 cm 27167 Lateral pocket 32x18 cm Made in strong, water resistant

material (600D polyester). Available also with outer PVC coating (27166-7). Provided with yellow reflective strips and rubber bottom.



• 27163 CUBO EMERGENCY BAG - polyester PVC coated - red Portable emergency bag with internal and external zip pocket and 2 removable pouches with transparent window. Made in strong, water resistant 600D polyester with outer PVC coating. Provided with double reflective yellow strip. Size: 28x34x13 cm.

# ■ CUBO EMERGENCY BAG ■ LIFE-2 EMERGENCY BAG



• 27161 LIFE-2 EMERGENCY BAG with 5 coloured pouches 2 section first-aid bag with double opening zip: bottom side with shockproof inner basin, upper side with 5 removable coloured pouches (model E1) with transparent window. Made of strong, water resistant 600D polyester material and provided with reflective yellow strips. Shoulder or hand portable. Size: 47,5x33xh 30 cm.

# MEDICATION BAG



 27132 MEDICATION FIRST AID BAG - 31x22x11 cm First aid bag provided with 2 internal transparent pockets, one external pocket, internal division with 2 zips on both sides, handle and carrying belt.

# **HOLSTERS**

**GIMA HOLSTERS - EMPTY** 21x12xh 6.5 cm 27147 27148 Large Holster - with pocket 19x14xh 1 cm **27145** Flat Holster

# POUCHES WITH VELCRO



#### POUCHES WITH VELCRO

All pouches are provided with a large strip of female velcro on back.

Made in 600D polyester.



,			_		20 27 200				
Model	Size - cm	RED	BLUE	YELLOW	GREEN	Standard with			
E1	20x11x8	27180	27181	27182	27183	27161			
E2	28x12x10	27184	27185	27186	27187	27170/1/4/5, 27150-8			
E3	28x15x11	27188	27189	27190	27191	27171			
E4	33x15x11	27192	-	27194	-	27151/2/7/8, 27175			
E5	29x19x11	27196	27197	27198	27199	27174			
E6	38x10x5	27200	grey c	olour					

# NYLON BAGS IN 5 COLOURS

	NYLON	BAGS - 22x1	15.5 cm	
Blue	Green	Red	Black	Grey
32791	32793	32794	32795	32796
32792	Same as abov	e with inner	foam	32796





POLYESTER

27171

 27170 LOGIC-1 RUCKSACK - polyester - medium - 40x20xh 47 cm Supplied with 5 coloured pouches with transparent window and velcro strips, 2 frontal pockets and 2 lateral pockets. Internal velcro strips and elastics, to retain instruments. Provided with yellow reflective strips



NRUCKSACKS▲



■ AMBULANCE RUCKSACK ■ SILOS-2 RUCKSACKS



• 27174 AMBULANCE **RUCKSACK** - polyester Modular extra large Rubber bottom rucksack provided with 8 internal pouches, 4 coloured with handle (model E5) and 4 coloured with transparent window (model E2). Velcro internal strips for pouches fixing. Provided with double yellow reflective strip. Size: 40x30xh 57 cm



DUTER PVC COATING

• 27168 SILOS-2 RUCKSACK - polyester - blue - 38x24xh 50 cm

• 27169 SILOS-2 RUCKSACK - polyester PVC coated - red - 38x24xh 50 cm Professional rucksacks made in strong water resistant 600D polyester and with PVC outer coating (27169 only) - removable compartment with 4 transparent pockets and many

elastic strips

- central storage space with 3 pockets, velcro strips and elastic strips - two external pockets with elastic strips and velcro strips:

one 35x16 cm, one 35x32 cm with 4 internal transparent pockets rubber bottom with 4 feet

two removable external plates for printing name comfortable back shoulder straps and plastic handle on both sides.

# GIMA PODOSCOPE WITH POLARIZED LIGHT



#### 27363 GIMA LED PODOSCOPE

The GIMA Podoscope with polarized light allows operators to observe the foot plant highlighting the points with the heaviest pressure. The patient stands on the methacrylate platform, an excellent light conductor, provided with an inner light source to detect variations of colour intensity on the foot plant, corresponding to higher or lower plant charge.

#### POSTURAL ANALYSER Adjustable unner mirror Devices for analysing posture in the frontal, rear and lateral planes. The patient stands with feet in the positions indicated on the platform. It includes a platform, elastic grid, two aluminum side bars, measuring indicators with plumb line for postural reference (Barré's vertical evaluation) and 27352 adjustable mirror on top. The image reflected in this upper mirror allows observation of any rotation of the shoulders. 80x72xh 225 cm Manual: GB, IT. On request ES. Capacity: 135 kg

# • 27387 NEW POSTURAL ANALYSER

• 27352 POSTURAL ANALYSER Adjustable upper mirror

# PLUMBING WEIGHT ...

• 27355 PLUMBING WEIGHT Made of stainless steel (magnet) with wire length 150 cm. Supplied in wooden case. Size: 6.2x2.3 cm. Weight: 140 g.



## Highly resistant, easy maintenance

The GIMA Podoscope with polarized light has been designed for a long lasting duration. High-quality material and components, serial assembly and control checks constantly performed during production and at final test, provide superior accuracy. Its structure is resilient and can bear charges up to 135 kgs - 297 lbs. Its green-light LED has a life of 25,000 hours (duration indicated by the manufacturer).

Easy to use, light and practical

The GIMA podoscope becomes operative at once simply switching it on. Just after the patient has stepped on it, in real time you can proceed with the study. The device is meant to be practical and easy to use. Since methacrylate is light and resistant at the same time, the device can be comfortably moved from a place to another, also thanks to its limited dimensions. The step is low: 22 cm from ground level, so that even elderly patients can easily step on it.

#### **TECHNICAL SPECIFICATIONS**

Capacity: 135 kg - 297 lbs Dimensions: 43.5x42.5xh 22 cm - 17.12x16.75x8.67 inches Weight: 8 kg - 17.63 lbs

Operating voltage: 220 V-50/60 Hz - Schuko plug (British plug available on request) Green light LED stripe with 25,000 hours of life

# LED PODOSCOPE



of the feet. It has a lacquered wooden structure and a crystal top with an inclined mirror below it for a real view of the sole of the feet, which highlights the points of greatest and least load. Double lateral illumination with high level effect lamps. Max Load 200 kg. Strong reliable and professional product, made in Italy.

## Weight: 15.5 kg

Power: 100-240 V, 50/60 Hz

# SCOLIOMETER

#### • 27351 SCOLIOMETER

Plastic instrument for the evaluation of the scoliosis (deviation of the spinal column on the lateral, left and right planes). The instrument detects the anomaly and its gravity. It also allows to compare reports during the time and define the evolution of the measured pathological process, thus reducing

the need of frequent radio graphical tests. The small sphere oscillating within an air space indicates the spine inclination degree, compared to the horizontal plane.



# SMEDLEY HAND DYNAMOMETER



Size: 60x66xh 220

Capacity: 200 kg

• 28791 SMEDLEY HAND **DYNAMOMETER - aluminium** Spring type hand dynamometer used to measure grip strength. Adjustable handle comfortably accommodates any hand size. Dial indicator remains at maximum until reset and is calibrated both in kg (0-100) and pounds (0-220) Manual in: GB, FR, IT, ES.

# HAND GRIP METER



• 28790 HAND GRIP METER - plastic Indicator remains at maximum until reset and is calibrated 0-75 kg. Size 20x15 cm Sold in a blister.

Manual in: GB, FR, IT, ES.

# STAINLESS STEEL GONIOMETERS



• 24900 FINGER GONIOMETER 6" - 15 cm Finger goniometer measures range of motion of finger joints. Linear scale in inches and centimeters on arms. 180° scales marked in 5° increments.




• 24903 360° GONIOMETER 14" - 35 cm This goniometer has two opposing 180° scale and one 360° scale all marked in 1° increments. Sturdy adjustable knob, controlling tension of arms.

• 24902 180° ROBINSON

GONIOMETER 7" - 17.5 cm Pocket size 180° Robinson goniometer for doctor and therapist. Linear scale marks 5° increments. • 24904 180° EXTRA LONG ARMS GONIOMETER 14" - 35 cm Extra long arms, useful for measuring all joints. Arm has a linear scale marked in 1° increments.

# GONIOMETERS

Used by orthopaedic surgeons to measure the range of movement of joints: elbows, knees and fingers.



• 27340 GONIOMETER -205x45 mm With circular scale used to check the size of hip joints and the angle of the femoral neck on X-rays.

Personalisation with your logo for minimum 2,500 pcs.

• 27339 GONIOMETER WITH PAIN SCALE RULER -203x45x7 mm



• 27338 GONIOMETER WITH ARMS (tolerance 1°) Measures analytical motility

of various body segments in degrees (from 0 to 360 clockwise or anti-clockwise direction) Consists of two perspex arms (3 mm thick) that will remain

open at any given position due to the friction at the joint between them.

Two graded scales: one increasing scale and one decreasing scale.

# **BMI TAPE**



• 27341 BMI -

27339

Tape Measure Pocket retractable tape measure 150 cm. BMI (Body Mass Index) calculator on front panel. • 27342 BMI -

**Tape Measure** Economical version of 27341.



**BODY TAPE** 

• 27343 BODY TAPE MEASURE Track your body measurements and progress. Measures any body part: arm, thigh, calf, chest, waist, hip... Measures in inches and centimeters: total measurement length: 60 inches / 152 cm. Sturdy vinyl tape.

Push-button retraction and locking feature ensures easy measurement and superior accuracy.



**BMI CALCULATOR** 



 27336 BMI CALCULATOR - box of 10 Used in hospital and surgeries gives an indication of general health through the ratio of weight to height. Made of 2 rotating discs: 108 mm diameter (base) and 76 mm (top). Can be personalized with your logo for a minimum of 1,000 pieces.

# PROFESSIONAL BODY - HEAD TAPE

27347 PROFESSIONAL BODY TAPE


• 27350 PROFESSIONAL BODY TAPE with pediatric gauge box

Patented, professional body tape measure approved by the Italian Ministry of Health for adult and pediatric use. Tape is coloured on both sides to help to identify metabolic risk in

abdominal measure for male and female. Length of tape: 8-150 cm. Thanks to its rounded shape, it can be used also as a head measure tape. Packed in single box.

Body tape with pediatric gauge box (27350) Specific tape for pediatric use. Supplied in a box with a

ruler to compare the measured head circumference with the standard percentiles of children's growth from 0 to 36 months. Suitable for both sexes.




27350

Multilanguage manual: GB, FR, IT, DE, ES, GR, PT, Arabic.


27347

# MEASURING MAT FOR BABIES SECA INFANTOMETER



 27329 SECA 210 - BABY MEASURING MAT Mobile measuring mat for babies and toddlers. Kind to the skin, washable, foldable.

The space saving solution for easy and precise measurement of baby length. Range 10-99 cm. Graduation: 5 mm.



#### 27331 GIMA BABY MEASURING MAT

Washable and foldable measuring mat for babies and toddlers, easy to carry. For easy and precise measurement of baby length. Size: 121x30 cm. Measuring range: 10-99 cm. Graduation: 5 mm.





#### 27316 SECA 416 - INFANTOMETER

Size: 110x16.9x40.2 cm. Weight: 3.8 kg.

Infantometer for measuring babies and toddlers in hospital. The sturdy construction and stability of the infantometer makes it quick and easy to measure babies and toddlers up to two years old. The board is generously designed and the raised and softly rounded sides guide the baby easily and safely into the right position. Permanently mounted with rollers on two guide rails, the footpiece slides smoothly along the scale. Because the footpiece is lockable, the baby can be removed and the result noted later. All parts are tough and durable. Measuring range: 33-100 cm. Graduation: 1 mm.

# GIMA PEDIATRIC MEASURING INSTRUMENTS

€ 0476

27326

#### • 27326 BABY MEASURE "CALIBRO"

Made of oxidized aluminium, metric graduation 0-900 mm, division 5 mm. Certified by Italian "weights and measure institute". Weight: 300 g.

#### • 27327 CRANIOMETRO - HEAD MEASURE

Made of special, soft, non stretchable plastic.

Measures child head girth up to 60 cm.

• 27337 ORCHIDOMETER - wood

Used by pediatricians for screening of children's testicles





wooden beads of increasing size from about 1 to 25 mm used to

# **HEIGHT MEASURE**

• 27335 TAPE HEIGHT MEASURE Clear scale 0-200 cm. Easy wall fixation. Supplied with screw for wall mounting.



# ELECTRONIC HEIGHT ROD LCD digit



• 27333 SOEHNLE ELECTRONIC HEIGHT ROD Measuring range: 50-240 cm (20-94.5 inches), division: 1 cm. Manual in: DE, GB, FR, ES, IT, GR, CZ.

# **BONE MEASURE** 27325 BONE MEASURE

Slide-knot caliper in anticorodal to measure knee, shoulder, wrist, elbow...

Burner length: 100 mm.





• 27264 SOEHNLE BABY HEIGHT ROD Digital and mechanical rod 35 to 80 cm, division 1 cm. LCD display, digit height 16 mm. Manual in 23 languages.

66

# PROFESSIONAL SKINFOLD CALIPERS: MECHANICAL AND DIGITAL



• 27320 PLICOMETRO - Professional skinfold caliper - mechanical • 27346 PLICOMETRO - Professional skinfold caliper - digital with PC cable for data transfer USB

This high precision instrument measures the thickness of a fold of skin with its underlying layer of fat giving physicians the situation of the subcutaneous tissues of the patient. Possibility of re-calibration

Produced to meet International Standards, the Gima "Skinfold caliper" has springs which exert a pressure of 10 g/mm<sup>2</sup> on the skinfold and an accurate scale which measures thickness in mm. With possibility of re-calibration of the pressure it solves the major problem of traditional skinfold caliper that is reduction of the tension of the spring in the time.

#### Easy to use and read

With double reading scale (27320) or digital display (27346), it is supplied with picture showing advised positions for measurements. Tables will help obtain correct % of body fat from measured data and make a correct evaluation of the patient. Stylish and user-friendly

A special nylon finish makes the device feel skin, avoiding trouble of contact with metal. Made in metal and sold in an attractive wooden box (19x36xh 6 cm). Made in Italy, provided of medical device CE certification. User manual in GB, FR, IT (both models), ES, DE, (27320 only).

#### Data management on PC (only 27346)

For immediate data transfer on most programmes (Excel, Word, Open Office, ...). Requirements: Windows 2000, XP (Service Pack 2), 7, Vista, USB 2.0 minimum.

# FAT-2 SKINFOLD CALIPER



 27349 FAT-2 SKINFOLD CALIPER Aluminium, light weight skinfold caliper to measure body fat. Large, easy to read 67 mm scale. Supplied with a protective carrying case and measuring procedure. Multilinguage manual in: GB, FR,

Size 16.5x10x0.5 cm.

Supplied into a polybag

Weight 22 g.

in a paper box.

# **BODY FAT CALIPER** • 27318 BODY FAT CALIPER - plastic 27318

BKINFOLD CALIFER

27346

# FAT-1 SKINFOLD CALIPER

• 27344 FAT-1 SKINFOLD CALIPER Economic but precise and accurate skinfold caliper for professional use, made in Italy. Measures the thickness of skin folds over the body, based on the characteristics developed by Tanner and Whitehouse:

pressure on the fold: approx 10 g/mm² contact surface on the fold: approx 6x11 mm It allows a correct evaluation of the nutritional status and the sectoral distribution of adipose tissue. Raise a fold of skin with your fingers and measure its thickness by the forceps (max opening 4 cm): on the top edge a scale in millimeters and an arrow measure the skin fold (triceps, subscapular muscles, etc...) with

an accuracy of about ±2 mm. The coloured bands placed near the scale allow a simultaneous comparison of the measured value with referential percentages related to men and women. This information is included in the manual provided with the unit and facilitate the interpretation of the values. Advised in dietetics, cardiology, sports medicine, aesthetic medicine, gynaecology, pediatrics, ecc... Multilanguage manual: GB, FR, IT, DE, ES, GR.

# OMRON BF511 BODY COMPOSITION MONITOR

• 27293 OMRON BF511 BODY COMPOSITION MONITOR

OMRON BF511 provides full body measurement with clinical accuracy, it is validated and classified as a medical device, even

It offers a comprehensive set of readings including body and visceral fat, skeletal muscle level, BMI and resting metabolism. Measurement with 8 sensors on both hands and feet for complete body measurement.

It uses the Bioelectric Impedance (BI) method, fat is shown as a percentage of body weight.

Multilanguage package and manual (GB, IT, FR, DE, NL, RU,

Battery operated: 4xAA (included).



number of calories needed to sustain vou everv day OMROF



27344

# **BODY FAT ANALYZER** WITH CARRYING CASE

#### • 27322 GIMA BODY FAT ANALYZER

Ideal for dieticians, gymnasia and sports centres, it is perfect also for homecare. It helps manage nutrition, fitness and weight control and can indicate if you are at the right weight and also whether you are nutritionally healthy.

Advanced technology in your hands.

GIMA Body Fat Analyzer measures the flow of electrical signals (total body electrical resistance or impedance) as they pass through FAT, LEAN (muscle, bones, vital organs) or WATER. When the amount of fat, lean or water changes, so does the Body Fat signal, giving you a highly reliable and accurate measure of the amount of each of these components that make up your total weight. Specifically, 4 electrodes are placed over metacarpus and metatarsus where a 50 kHz current is introduced. The detected signal level will be an index of total body water and fat free mass. Only 2 minutes for an essential and easy test

Testing and results take less than two minutes and have the same accuracy as other more expensive devices.

A lot of meaningful data

**FAT:** actual weight of fat on the body

LEAN: actual weight of lean, mostly muscle and vital organs WATER: water content in the body

% FAT: percentage of fat weight in total body weight % LEAN: percentage of lean weight in total body weight BMR: basal metabolic rate

Target Weight: weight goal under optimal condition Target % Fat: normal percent for sex and age

Portable, for performing test everywhere Small size and light weight for portability.

FITNESS SCALE

Fitness scale for measurement of muscle, fat and

water components, BMI and caloric needs per day

- simple self-explanatory menu guide on the glass

- impedance measurement through hands, no need to

- no limit on measurement for over- and underweight

• 27286 SOEHNLE 7850 FITNESS SCALE

Body Fat Analyzer helps get and stay fit. It helps maximize personal level of fitness if you want to lose weight, build muscle, tone and trim, or simply be sure you are maintaining your current level of fitness:

- enables you to check effectiveness of weight loss programme. telling exactly where your weight loss is coming from (fat-lean-
- it helps monitoring improvements in muscle mass as a result



of exercise and/or diet

- establishes a baseline for your body composition, so that nutritional and fitness improvements can be regularly monitored. Frequent calibration (code 27324 calibration kit) is necessary for accurate results in the time. Supplied with a carrying case, kit of 2 sensor cables, sensor pads (box of 20), 2x9 V batteries, transformer and manual (GB, IT, FR, ES)

- 27321 SPARE SENSOR CABLES (kit of two)
- 27323 SENSOR PADS (box of 20) replacement
- 32205 9V ALKALINE BATTERY
- 27324 CALIBRATION KIT

#### **TECHNICAL SPECIFICATIONS**

Size: 66x176x208 mm Weight: 1,500 g (unit, battery and probe) Test frequency: approx. 50 kHz Test current: less than 1mA Power source: two 9 Volt DC batteries or 230 V (by transformer)

#### Glass surface easy to clean Large Backlit LCD display with 17 mm high digits Aluminium USB port opposite to LCD for direct connection to S O E H N L E PC for customize set-up (charging logo, ...) Print-out can he ntegrated printe with your logo in 17 languages

**TECHNICAL SPECIFICATIONS** 180 kg 100 q / 0.2 lb

100-240 V. 50/60 Hz

365x490xh 1,290 mm - 15.8 kg 365x480xh 45 mm

- clothing weight value seasonally adjustable - print-out of data/time, weight, data analysis and

recommendations for nutrition and fitness activities

- CD-Rom with software included to edit the print-out and settings in DE, GB, FR, NL, ES, IT,

HU, CZ, FI, SE, NO, DK, GR, PL, SI, RU, TR. - kg/lbs/st selection function

take off the shoes

surface

people

Manual in: GB, FR, IT, DE, CZ.

• 33250 PAPER ROLL 57mm x 25m -

box of 5 Extra large weighing platfori

# **BODY FAT SCALES**

• 27088 LIBRA BODY FAT SCALE - white 27089 LIBRA BODY FAT SCALE - black

Multi function scales, for measuring body fat, water, muscle and bone mass. Supplied in a 4 colour box with multilanguage manual (GB, FR, IT, ES, PT, PL)

- equipped with 4 precision G sensors

- 8 user memories

- auto off in 30 seconds - auto-on function

3 touch buttons for easier usage

TECHNICAL SPECIFICATIONS

150 kg / 330 lb - minimum 5 kg LCD Size: 62.5x62 mm Sensitivity: 100 g / 0.2 lb Batteries (included) 310x310x18.8 mm



Canacity:

Sensitivity:

Platform size:

Power supply



Weight and analysis of results shown on scale

GIMA BIG DIAL SCALES

• 27239 GIMA BIG DIAL SCALE Mechanical scale with classic design: a large and clear dial, a robust housing made of steel. Supplied in multilingual gift box. Made in Europe.



• 27240 GIMA DIGITAL BIG DIAL SCALE Digital scale with extra large, easy to read LCD display (65 mm). Strong and durable steel construction, comfortable platform. Lb/kg/st switchable by user. Supplied in multilingual gift box.

Made in Europe. 8 language manual and box: GB, FR, IT, ES, DE. PT. GR. Arabic

TECHNICAL SPECIFICATIONS

27240

Capacity: 200 kg Sensitivity: 100 d Minimum measuring weight: 2 kg Power: lithium battery (included) Dimension: 430x380x70 mm

CAPACITY

200 KG

GIMA BATHROOM DIGITAL SCALES



**TECHNICAL SPECIFICATIONS** 

Weight: 3 kg

Capacity: 160 kg Dial Ø: 180 mm

Minimum measuring weight: 5 kg

Dimension: 430x380x70 mm

Sensitivity: 1,000 g

70 80 90 100 110

20 10 0 150

120

130

140

60

50

27262 DIGITAL SCALE

Electronic bathroom scale with plastic platform. 4 sensor high precision system. Auto-on function, low battery and overload indicator. Lb/kg/st switchable. 9 languages colour box and manual: GB, FR, IT, ES, DE, PL, PT, GR, Arabic

#### TECHNICAL SPECIFICATIONS

Capacity: max 150 kg (330 lbs) - min. 3 kg (6.6 lb) Sensitivity: 100 g = (0.2 lb)Dimension: 299x297x32 4 mm Power: 1xCR2032 lithium battery - not included

Warranty: 2 years

Ultra slim design only 19 mm height 9 languages colour box 27249 and manual: GB FR IT ES. DE. PL. PT. GR. Arabic • 27249 DIGITAL GLASS SCALE - grev • 27248 DIGITAL GLASS SCALE - black

Electronic bathroom scale with 6 mm thick tempered glass platform. 4 high precision G sensors. Automatic on and off function. Lb/kg/st switchable by user.

#### **TECHNICAL SPECIFICATIONS**

Capacity: max 150 kg (330 lb) - min. 2 kg (4.4 lb) Sensitivity: 100 g (0.2 lb) Dimension: 300x300x19 mm Power: 1xCR2032 lithium battery - not included Warranty: 2 years

precision G sensors. Automatic on and off function. Lb/kg/st switchable by user. TECHNICAL SPECIFICATIONS

Electronic bathroom scale with 6 mm

thick tempered glass platform. 4 high

Capacity: max 150 kg (330 lb) - min. 2 kg (4.4 lb) Sensitivity: 100 g (0.2 lb) Dimension: 300x300x19 mm Power: 1xCR2032 lithium battery - not included

# 27230

27230 MECHANICAL SCALE

Analogue bathroom scale with stable construction and plastic cover. 18 languages box and manual instruction: GB, FR, IT, ES, PT, DE, GR, HR, HU, SI, RO, EE, LT, LV, CZ, PL, RU, Arabic. **TECHNICAL SPECIFICATIONS** 

Capacity: 125 kg (275 lb) Sensitivity: 1,000 g (2 lb) Warranty: 2 years

# MECHANICAL SCALE SOEHNLE AND OMRON DIGITAL SCALE Large LCD



Digital bathroom scale with large and economic platform and bright LED digits. Automatic on and off function. TECHNICAL SPECIFICATIONS

Capacity: 150 kg (330 lbs) Sensitivity: 100 g (0.2 lbs) Power: 2x1.5 V AAA batteries - included Packing size: 38x6x36.3 cm Weight: 2.4 kg

Warranty: 5 years

180 ka Weight difference function helps to accurately measure the 27091 weight of your need of manual OMRON calculation 27091 OMRON HN288 DIGITAL SCALE

Unique technology makes it easy to weigh persons but even, luggage and babies. Four integrated sensors for a reliable reading, up to 180 kg.

#### TECHNICAL SPECIFICATIONS

Capacity: 180 kg Sensitivity: 100 g Power: 2x1.5 V AAA batteries - included Packing size: 38x6x36.3 cm Weight: 2.4 kg

# 27241

**TECHNICAL SPECIFICATIONS** Capacity: 150 kg - 330 lbs

Weight: 3.5 kg Size: 317x117x477 mm

SECA MECHANICAL SCALES

• 27241 SECA 750 SCALE

Mechanical flat scale with sturdy, powder coated steel casing. Pretty and stable with its white powder coated lacquer.

A hard wearing synthetic white leather covers weighing platform. Made in Europe. User manual in: GB, FR, IT, ES, DE, PT, PL.

- 27280 SECA 761 SCALE medical use Class IIII
- 27285 SECA 762 SCALE

Traditional model with large easy-to-read dial. Pointer professional scale in strong metal structure white painted. Consistent accuracy on any surface.

Spacious platform design with no slip rubber mat, stable for safety. Tare function.

User manual in: GB, FR, IT, ES, DE, PT, PL.



Capacity: 150 kg - 330 lbs Sensitivity: 500 g ± 2 g (27285) - 1,000 g (27280) Size: 305x120x470 mm



Analysis of results shown on APP

• 27090 LIBRA BODY SCALE with Bluetooth 4.0 - white Multi function scales, for measuring body fat, water, muscle and bone mass. Equipped with 4 precision G sensors, 8 user memories, auto off in 30 seconds, auto-on function. TECHNICAL SPECIFICATIONS

100 g / 0.2 lb

150 kg / 330 lb - minimum 5 kg LCD Size: 62.5x62 mm Batteries (included) 310x310x18.8 mm

# GIMA BLUETOOTH SCALE AND BLUETOOTH SCALE



• 27256 AND UC-351PBT-Ci HEALTH SCALE - Bluetooth

Advanced health scale designed for ease of use and accuracy. This device will facilitate your daily weight management. At the end of measurement, data is automatically sent from this scale to the receiver device through Bluetooth.

TECHNICAL SPECIFICATIONS

Size:

150 kg / 330 lb 350x350x39 mm Sensitivity: Weight:

100 g < 100 kg > 200 g 2.3 kg

# **IHEALTH WIRELESS AND BODY ANALYSIS SCALES**



See specifications at page 3



• 23508 IHEALTH CORE HS6 WIRELESS BODY ANALYSIS SCALE See specifications at page 3

# PRECISION SCALE



 27246 PRECISION SCALE With temperated glass Ø 160x4 mm, tare function, kg/lb-oz.

#### **TECHNICAL SPECIFICATIONS**

Capacity: 5 kg (11 lb) Sensitivity: 1 g LCD display: 35x15 mm Size: 185x158xh 50 mm Battery: 1xCR2032 - not included



# **BODY FAT SCALE**

• 27229 EXACTA DELUXE SCALE Measuring body weight, fat,

TECHNICAL SPECIFICATIONS

Capacity: max 180 kg (400 lb, 28 st) min 3 ka (6.6 lb) Sensitivity: 100 q (0.2 lb) LCD Display: 31 mm Safety glass: 310x310x22 mm Rattery: 2x CR2032 - included Warranty: 3 years

water, muscle content and daily caloric consumption.

# **TECHNICAL SPECIFICATIONS**

· 27284 SECA 756 - mechanical with

Tradition combined with modern design.

With a very sensitive precision mechani-

a well visible red pointer on the circular

User manual in GB, FR, IT, ES, DE, PT, PL,

sm to show weight through the aid of

height rod - (60-200 cm) - class III

Capacity: 160 kg Sensitivity: 500 a Weight: 18.5 kg

NL. GR. DK. SE. FI. NO.

Dimensions: 628x360x1,000 mm Platform: 360x350 mm with wheels

Keys to symbols: M = Metrological Approval for use in medical field

( = Calibration according to class III sensitivity required by 90/384/EEC

# SOEHNLE PROFESSIONAL DIGITAL SCALES

• 27276 SOEHNLE 7831 with height rod and BMI display

• 27277 SOEHNLE 7730 ( € M Class III

The new range of Soehnle professional personal scales with stand is a special highlight with its gently curved glass indicator. While stepping on the scale, the display is activated automatically and the weight is shown with red backlighted numbers. It does not require any operation and is perfectly suitable for simple weighing in medical institutions, wellness areas and pharmacies. Scale with integrated height rod Soehnle 7831 (27276) with stand and height rod switches automatically from kg to cm if the height rod is raised.

Thus, patients can be simultaneously weighed and measured.

- indication of weight, height and BMI (27276 only)

- integrated height rod from 120 cm to 202 cm (27276 only)
- simple to use, tare key on the back of the display
- glass scale indicator (glass thickness 8 mm)

- bright LED display: 5 digits, height 15 mm

Capacity

Weight:

Sensitivity:

Dimension mm

Power Supply

Made in Germany.
Manual in: DE, GB, FR, ES, PT (only 27277), IT, NL, DK, FI, SE, NO, GR, TR, CZ, SK, PL, RU.

**TECHNICAL SPECIFICATIONS** 250 kg 250 kg

100 a 100 g 365x490x890 14.1 kg

365x490x1,280 17.2 kg -230 V - 50-60 Hz (available on request 110 V)

27277 250 kg 50/100 g 365x490x890 14.1 kg

height rod 27276 No kevs on the glass plate Large tread 364x405 mm 27277 Antislin surface

SOEHNLE

PROFESSIONAL

Integrated



 27296 SECA 711 - mechanical with height rod (60-200 cm) - class III

#### • 27297 SECA 700 - mechanical with height rod (60-200 cm)

Mechanical column scale with weight adjustment at eve level. Weight can be measured in a conventional way: by aligning two chrome plated indicators. User manual in GB, FR, IT, ES, DE, PT, PL, NL. GR. DK. SE. FI. NO.

• 27298 SECA 220 HEIGHT ROD - spare

#### **TECHNICAL SPECIFICATIONS**

Capacity: 220 kg Sensitivity: 100 g (27296) - 50 g (27297)

Weight: 21.7 kg Dimensions: 520x1,556x520 mm Platform: 350x360 mm

( € 0109 = Approved scales according to 93/42 EEC

Sensitivity: 100 g < 150 kg > 200 g

Dimensions: 294x831x417 mm

Platform: 272x280 mm

Capacity: 200 kg

Weight: 6.3 kg

Versatile, low maintenance and site

of the nutritional conditions of the

independent with economic battery

operation, ideal for daily use in hospital

and doctors practices. Column scale is easy

to move around with its transport castors.

BMI function permits a reliable evaluation

patient. Equipped with several fuctions:

TARE, HOLD, weighing range switch-over,

automatic switch off. User manual in GB.

FR, IT, ES, DE, PT, PL, NL, GR, DK, SE, FI, NO.

**TECHNICAL SPECIFICATIONS** 





# DIGITAL CHAIR SCALE

TECHNICAL SPECIFICATIONS

200 kg

6V 5AH

36 hours

100 g 535x275x1,060 mm

110-240 V - 50/60 Hz

372x275 mm



#### • 27273 CHAIR SCALE SOEHNLE 7802

• 27281 POWER SUPPLIER - spare

Operating time when fully charged:

Capacity:

Sensitivity:

Platform:

Weight:

Dimensions

Power supply

Battery accumulator:

Recharging time:

Fully electronic scale: no wear and tear parts, no maintenance. Easy to read display with 20 mm high figures. Zero setting, taring and hold functions.

Tiltable arms for easy access of bed-ridden and frail patients. Powered by either mains or rechargeable batteries. Cable for recharging batteries included.

Manual in: DE, GB, FR, NL, ES, IT, PT, CZ, FI, SE, NO, DK, GR, PL, TR.

Rechargeable batteries

TECHNICAL SPECIFICATIONS

Capacity: 200 kg (440 lb) 100 a Sensitivity: Total weight: 25 kg 580x1,100x930 mm Power supply: 230 V / 50-60 Hz, 10 mA, 2.2 VA

Made in Germany

# MULTIFUNCTION SCALE



- Manual in: DE, GB, FR, NL, ES, IT, GR, FI, NO, SE, DK, CZ, RU.
- 27244 DRIVE-ON RAMP
- 27245 ADIPOSITY HANDRAILS + BRACKET FOR INDICATOR
- 27251 SUPPORT HANDRAILS + BRACKET FOR INDICATOR
- 27278 MULTIFUNCTION SCALE SOEHNLE 7708 ( M Class III

(complete with 27244+27251) - manual in: GB, FR, DE Multifunction scale prepared for easy (and later) mounting of support handrails, adiposity handrails, bracket for indicator, drive-on ramps. Movable by means of 2 rollers and handle. Large LCD display, digit height 20 mm. Made in Germany.

TECHNICAL SPECIFICATIONS

300 kg 840x880x55 mm Sensitivity: 100 g Dimension 230 V - 50-60 Hz (available on request with rechargeable battery or Class III)

VETERINARY SCALES SEE PAGE 366



#### • 27267 SECA 376 HOSPITAL SCALE - digital class III

- high-quality Seca scale technology with fine 5-gram graduation
- TARE, HOLD, auto-HOLD and BMIF for extra convenience - extra large and ergonomic tray for safe weighing
- adjustable damping
- large display for easy reading
- network-capable with seca 360° wireless technology

#### **TECHNICAL SPECIFICATIONS**

Capacity: 20 kg Sensitivity: 5 g up to 7.5 kg, 10 g from 7.5 kg up Dimensions - weight: 620x190x358 mm - 3.7 kg Platform: 615 x 130 x 275 mm Battery operated

#### WIRELESS TECHNOLOGY - optional

With the seca 360° wireless technology the seca 376 can transmit measurements to the optional seca 360° wireless printer. With the network-capable software seca analytics 115 and wireless USB adapter seca 456, your PC can receive and analyze measurements and forward them to an Electronic Medical Records (EMR) system. Thus the seca 376 is EMR-integrated and ready to handle digital patient records and all the demands the future will bring More information about EMR integration is at www.seca.com

# HOSPITAL DIGITAL BABY SCALE | HOSPITAL DIGITAL BABY SCALE



• 27263 SOEHNLE 7725 HOSPITAL SCALE - digital - Class III A two-range scale with high precision and reliability suitable for hospital use (approved class III, MPG class I). The damping and hold function guarantee a stable weight indication. With high stability for safe weighing of our babies. Easy to clean plastic and ergonomic forms allow a simple and hygienic cleaning.

- high-contrast LCD display with 20 mm high figures

- large reading angle

- automatic zeroing at switch-on - tare function key (laid on pad can be tared) - hold function

Manual in: DE, GB, FR, ES, IT.

• 27264 BABY HEIGHT ROD Digital and mechanical rod, 35 to 80 cm, division 1 mm. Manual in 23 languages.



Capacity: 15 kg Sensitivity: 2 g up to 6 kg, 5 g from 6 kg up Dimensions - weight: 60x35x12 cm - 4.6 kg Operating voltage: 220-235 V/50-60 Hz or rechargeable batteries

SECA MECHANICAL BABY SCALE

# **SECA** ELECTRONIC BABY SCALES



• 27283 SECA 384 - electronic - ( M Class III

Two scales in one: with a comfortable tray to weigh in a reclining position, easily detachable to be converted into a floor scale. Breast-milk-intake function determines how much milk the baby has suckled. Other functions: tare, auto-hold, kg/lbs switch over automatic switch off, BMIF. User manual: GB, FR, IT, ES, DE (27282-3), PT, PL, NL, GR, DK, SE, FI, NO (27283 only).

#### **TECHNICAL SPECIFICATIONS**

Capacity: 20 kg Dimensions: 552x156x332 mm Batteries operated

Sensitivity: 10 g < 10 kg > 20g Weight: 2.3 kg (27282), 2.8 kg (27283) Made in Asia

#### TECHNICAL SPECIFICATIONS

The sturdy classic: with its softly curved weighing tray, the

weights, this model is the indestructible original baby scale.

stable all-steel casing and the precise, smooth running

Capacity: 16 kg Dimensions: 550x180x290 mm Made in Asia

27299 SECA 725 - mechanical

User manual: GB, FR, IT, ES, DE, PT, PL.

• 27294 SECA 745 - mechanical - CEM Class III

Sensitivity: 5 g (27299) 10 g (27294) Weight: 6 kg

27263+

27264

27299



# **PAPER SHEET FOR BABY SCALES**

• 25250 PAPER SHEET for baby scales - flow pack of 25 Pure wedding of cellulose, 2 plies (30+30 g/m<sup>2</sup>) + high density polythene (10 g/m<sup>2</sup>)

# FOLDABLE BABY SCALE HOME CARE BABY SCALE



#### 27266 SOEHNLE 8320 FOLDABLE BABY SCALE

Foldable baby scale for easy transport. Folding mechanism with magnetic lock. Easy to open: remove the base and pull the handles apart. Taring function: pads, blankets placed under

the baby are tarable. Steady weight display through filtering and hold function.

Large LCD display easy to read. Switchable to kg/lb.

Manual in: DE, GB, FR, ES, IT, GR, CZ, Arabic.

Alkaline battery 2x1.5 V AAA - not included

• 27271 CARRYING BAG

Capacity: 15 kg

Weight: 1.9 kg



#### SCALE Well-designed, easy to handle baby scale made out of

easy to clean plastic.

- détachable baby tray
- suitable to weigh children up to 20 kg removing baby tray
- easy to read LCD-display with 13 mm figures
- simple operation with one button
- fully-electronic scale: no wear and tear parts, no maintenance
- tare function to calibrate for baby blankets/textiles - hold function: weight value will be held for 10 seconds after unloading
- automatic power-off to save battery capacity
- manual in: DE, GB, FR, IT, ES, NL, DK, SE, HU, FI, PT.

## • 27307 TRAY FOR 8352 - spare

TECHNICAL SPECIFICATIONS 20 kg Canacity Dimensions: 601x346x92 mm Sensitivity: 10 g Weight: 3.5 kg Rattery operated: 9 V

TECHNICAL SPECIFICATIONS

Dimensions: 395x315x105 mm (closed) - 740x315x53 mm (open)

Warranty: 2 years





#### • 27312 BABY AND CHILD DIGITAL SCALE

Multifunctional scale for babies and children with removable light plastic tray. It can be used with tray for babies or without for children. Weight difference display function with memory: you can see the gain of weight of the baby after feeding. Precise scale with easy-to-read LCD display. Auto zero, auto tare, auto hold function. Automatic switch off and low battery indicator. Switchable to kg/lb/st. Manual: GB, FR, IT, ES, PT, DE. Made in Europe.

**TECHNICAL SPECIFICATIONS** 

Tray dimensions: 525x305x63-95 mm Pack dimension: 540x300x110 mm Capacity: 20 kg Sensitivity: 10 g Battery operated: 2xCR2032 lithium batteries

Handy, reliable and well-designed electronic baby scale

Provided with large LCD display 66x28 mm and kg/lb switch. Supplied with height tape meter and washable sheet.



**TECHNICAL SPECIFICATIONS** 

Capacity: Dimensions: 20 kg / 44 lbs 595x340x90 mm Sensitivity: 10 g Weight: 4 kg Auto-off function Battery operated: 4x1.5 V AA

# **FAMILY** BABY SCALE

# • 27301 FAMILY BABY SCALE

Baby scale suitable for domiciliary use. Capacity 20 kg/44 lbs

Scale division: - 50 g (0-10 kg) - 100 g (10-20 kg)

Plastic tray. Dialplate in kg and lbs. Manual zero adjustment. Multilanguage manual: GB, FR, IT, ES, PT, DE, Arabic.



# VISIOFOCUS® AND VISIOFOCUS® PRO "NON CONTACT" THERMOMETERS

to precisely measure body temperature. Totally hygienic, without touching the skin, VisioFocus® reads infrared radiation naturally emitted by the

urface of the skin and calculates the whole body temperature.

• 25573 VISIOFOCUS®

• 25574 VISIOFOCUS® PRO

High accurate "non contact" thermometer that projects the temperature on the forehead.

# Advantages of VisioFocus®:

- exclusive patented aiming system guarantees correct point and distance
- projection of the temperature on the forehead
- face button automatically adjusts forehead temperature to the environment (room) temperature for accurate result
- exclusive and patented AOCS and MOCS systems to maintain correct and constant temperature of device during long periods of use or when moving between rooms with different temperatures
- clinically tested
- totally hygienic for patients and users: no touch & no disposables
- no laser: absolutely safe for travellers and users, no harm if the person eyes are open while measurement is taken
- CE, FDA, Koseisho, TGA, CFDA (VisioFocus®), CE (VisioFocus® Pro)
- instantaneous: gives temperature in less than 1 second

Visiofocus® is supplied with batteries and manual (GB, FR, IT, ES) 25573

of measurement that allows to reduce the number of thermometers and of operators necessary for a wide screening Made in Italy

Nurs and Doct functions (only 25574) for pandemic situations:

allow to take temperature of up to 1,000 travellers per hour. Nurs

has obliged MQCS every 30 minutes, Doct has automatic AQCS

low using cost thanks to the long battery life and speed

Visiofocus® Pro is supplied in a case with lanyard hatteries and manual (GB, FR, IT, ES)



BACKLIGHTED DISPLAY IN 5 DIFFERENT COLOURS, ONE FOR EACH FUNCTION



#### TECHNICAL SPECIFICATIONS

Forehead measuring range Measuring range (apart from forehead) Room temperature working range

1.0/80°C (33.8/ 176°F) 16/40°C (50/104°F) Can work also in environments with a temperature between 10 and 16°C (50/60.8°F)

and between 40 and 45°C (104/113°F) but in this case the accuracy is reduced Resolution Accuracy level Distance of operation: Batteries (included)

According to ASTM E 1965-98:2009 About 6 cm (2.36") 4 AAA/LR03 type (preferably alkaline) <30,000 measurement

34.0 /42.5°C (93.2/108.5°F)

Batteries life Measurement time Time between consecutive measurements <2 seconds

# NON CONTACT THERMOMETER



• 25591 INFRARED NON CONTACT THERMOMETER Multifunctional infrared non contact thermometer for body and objects.

Effective distance 5-15 cm. Body temperature with fever teller Wide range 32.0-42.9 °C (89.6-109 °F) and green, yellow, red backlight.

Object temperature 0-100 °C (32-212 °F) Body object function for ambient temperature, milk or bath surface temperature.

Fever alarm 32 memories

Instant response time: 1 second Auto/manual power off. Supplied with 2AA batteries.

Size 160x95x46 mm. Display 30x31 mm.

Reading scale °C/°F switchable Multilanguage box and manual: GB, FR, IT, ES.

#### **FEVER TELLER**







☐ FOREHEAD THERMOMETER • 25585 INFRARED MULTI-FUNCTION

#### FOREHEAD THERMOMETER • 32212 SPARE BATTERY

Multifunctional innovative infrared thermometer with 5 applications: forehead temperature, room temperature, scan mode for surface temperatures (bath water or milk), real time clock, stopwatch.

- friendly 3 LED zone indicator to get fever status

- instant measurement
- large LCD to read easily
- detailed 9 memories with time/date & site
- fever alarm with beeper - selectable °C/°F mode
- small size to carry when travelling - accurate: ± 0.2/0.3 °C
- self-diagnosis warning when device is abnormal

Packed in deluxe card board box.

#### **TECHNICAL SPECIFICATIONS**

Measurement range: - forehead: 34.0 °C~42.2 °C (93.2 °F~108.0 °F) scan mode: -22/80 °C (-7.6-/76 °F)

Response time: 5-30 sec Time between measurements: > 5 sec Display Model

CR2032 (32212) Dimension (LxWxH) - Weight: 14x3.8x3 cm - 70 g Norms: IEC60601-1. IEC60601-1-2 (EMC). ASTM E1965-98



25585

# THERMOFOCUS® PROFESSIONAL "NON CONTACT" THERMOMETERS

THERMOFOCUS THERMOMETERS The most advanced thermometers

in the world! Thermofocus reads infrared radiations emitted by the surface of the skin and calculates accurately the body temperature.

- without touching: never in contact allows to immediately find correct to avoid any risk of infection

- non invasive: does not require patient collaboration.

recommended for children - accurate: a sophisticated microprocessor ensures high precision

- economic: no need of expensive probes

- fast: takes the temperature in less than one second

- 1 °C-55 °C: for measurement of wide range of objects

- body temperature scan (25571/2): can be done quickly

• 25570 THERMOFOCUS - mod. 0700A2 - 2 buttons - blister FOR FAMILY For the private user who needs an easy, fast and precise thermometer. Simply press the ON button, hold it perpendicular to the centre of the forehead and release the button as soon as the two red lights converge in a single point. It can also be used to take the temperature of objects such as a baby's feeding bottle. Not recommended for doctors and hospitals.

• 25571 THERMOFOCUS - mod. 1500 - 6 in 1 - 3 buttons FOR DOCTORS For the family or the private doctor who require maximum accuracy and flexibility of the temperature taking. Same as 25570 with an additional button ("home") to read the ambient temperature and the skin temperature (professional use), as well as the temperature of objects and liquids within a range from 1 to 55 °C (33.8 to 131 °F). Provided with the exclusive Manual Quick Calibration System (MQCS) technology through which you can always perfectly stabilize the thermometer to the ambient temperature.

• 25572 THERMOFOCUS - mod. 1500A/ H1N1 3 buttons HOSPITAL-EMERGENCY Specifically studied for hospitals. airports, schools, factories, etc. in case of emergency and/or pandemic situations. Ouick, accurate and easy to use, allows a fast and hygienic temperature reading for thousands of consecutive measurements. Same as 25571, but with



System), through which you can always perfectly stabilize the thermometer to the ambient temperature, ready to take series of measurements. Supplied with a lanyard to be, worn around the neck

compulsory MQCS technology (Manual Quick Calibration

• 32200 "AAA" BATTERIES





#### TECHNICAL SPECIFICATIONS

Forehead measuring range: Measuring range (apart from forehead): Ambient temperature working range Precision:

Accuracy level according to ASTM E 1965-98: from 34 to 35.9 °C (93.2/96.6 °F)= from 36 to 39 °C (96.8/102.2 °F)= from 39.1 to 42.5 °C (102.4/108.5 °F)

±0.3 °C (±0.5 °F) Distance of operation: 3 cm (1.2 inch) fixed through optical signal The termometer can work also in environments with a temperature between en 5 and 16 °C (41/60.8 °F), but we do not guarantee the accuracy. Battery: 4xAAA (1.5V) included Weight: 99 g Size: 165x40x22 mm Manual: GB, IT, FR, ES only for 25570-1. On request: PL Soft manual available on request: FR, ES, DE, DK, NO, NL, PT, FI, S , TR, GR, RU, AR, KR









34.0/42.5 °C (93.2/108.5 °F) 1.0/55.0 °C (33.8/131 °F)

16/40 °C (60.8/104.0 °F)\*

0.1 °C (0.2 °F)

±0.3 °C (±0.5 °F)

±0.2 °C (±0.4 °F)





# For use in emergency and pandemic situations

0 0 0 100 H

PROFESSIONAL THERMOMETER EAR THERMOMETER

• 25580 IR EAR THERMOMETER

• 25581 PROBE COVERS - box of 40 pcs.

• 32212 SPARE BATTERY

- fully meet "ASTM" standard and CE EN 12470-5 (only few brands passed it) in measurement accuracy

(35.5 °C to 42 °C  $\pm$  0.2 °C, others  $\pm$  0.3 °C).

- unique and handy design

- one-second measurement, fast and easy - 9 memory for temperature comparison and evaluation, fever alarm, easy reading LCD

- self-diagnostic and infrared measurement





25580

34.0 °C~42.2 °C (93.2 °E~108.0 °F) Measurament Range Response time: 1 second Display Model CR2032 (32212) Battery Type: Dimension (LxWxH): - Weight: 14x3.8x3 cm - 70 a

Norms: IEC60601-1, IEC60601-1-2 (EMC), ASTM E1965-98

• 25575 PROFESSIONAL INFRARED EAR

THERMOMETER 25576 PROBE COVERS - box of 200 pcs. (5 tubes of 40 pcs.)

 25577 PROBE COVERS LOADER HOSPITAL with 40 PROBE COVERS

- special design for hospital use

 durable probe for cover replacement up to 100,000 times

probe cover ejector and probe cover detector one-second response time: fast and easy

- neck strap and 1 probe cover included - fever alarm

- selectable °C/°F

Accuracy:

Memory

Needs probe covers for use 25577 Probe cover ejector Prohe cover loade







Large LCD



Measurement range ±0.2 °C (0.4 °F) during 35.5~42 °C (95.9~107.6 °F), ±0.3 °C (0.5 °F) for other range 25 sets

Ruzzer: CR2032 1 (Gima code 32212) Battery:



• 25551 ECOLOGICAL OVAL THERMOMETER - box of 12

**HEALTH CARE - PATIENT AIDS** 

• 25587 SHAKER for ecological thermometers - box of 24 Mercury free clinical thermometer with gallium alloy instead of mercury. Safe, precise and functional.

• 25586 ECOLOGICAL OVAL THERMOMETER with shaker - box • 25589 ECOLOGICAL OVAL THERMOMETER with shaker display box of 24 pcs.

Same as 25551 but supplied with a shaker to help shake down

# POCKET EAR THERMOMETER • 25579 POCKET EAR THERMOMETER

Small, easy to clean, cover free design ear thermometer. Home use.

TECHNICAL SPECIFICATIONS 34-44 °C (93.2-111.2 °F) - ±0.2 °C (±0.4 °F) Measurement Range: Response time: 1-2 seconds Battery:

Lithium 3 V (CR2032) - life approx 4,000 measurements 114x35x40 mm - 35 g (including batteries)



# ■ WIRELESS THERMOMETER 25548 TEMP SITTER - baby wireless thermometer

Accurate and innovative thin thermometer. Transmission to mother smartphone APP (iOS and Android). To be placed under baby armpit. High temp alarm can be set in the APP. Waterproof and material of safe quality. Supplied with 10 adhesives to fix thermometer to baby armpit.

• 25547 ADHESIVE TO FIX TEMP SITTER box of 10 - spare

25548 **TECHNICAL SPECIFICATIONS** 

Battery life: 3,000 hours, not replaceable Measurement range: 25-45 °C (±0.05 between 35-38.5 °C)

25548

# **BABY THERMOMETERS**



• 25555 PANDA DIGITAL THERMOMETER °C - hang box water-proof, fever alarm



• 25566 FROG DIGITAL THERMOMETER °C - hang box - flexible tip

€0051

termometro febbre fevertest

25599

# NIPPLE-LIKE DIGITAL THERMOMETER

• 25569 NIPPLE-LIKE DIGITAL PACIFIER THERMOMETER °C Individually packed in cardboard box, memorizes last temperature. Auto power-off. Display range 32.0°C - 42.0°C, with accuracy ±0.1°C.



GB. IT

25600

fevermonitor

25601

# LIQUID CRYSTAL THERMOMETERS

Non toxic, mercury free, safe, unbreakable, reliable, long lasting, easy to read, liquid crystal thermometers. 10 languages manual. Made in Italy. REUSABLE FOREHEAD THERMOMETERS

• 25599 FEVERTEST - bag of 10 blister

It indicates the normal temperature or fever in 15 seconds. 25596 FEVERTEST BULK - box of 100 - hospital use

 25600 FEVERCONTROL - bag of 10 blister It indicates temperature in 15 seconds with graduation

BODY TEMPERATURE MONITOR • 25601 48h FEVER MONITOR - bag of 10 blister of 3 pcs. Innovative "continual" fever indicator for 48h monitoring.



# DIGITAL THERMOMETERS



• 25564 GIMA VALUE DIGITAL THERMOMETER °C - box - rigid tip



- 25559 GIMA DIGITAL THERMOMETER °C box 30 seconds Sold in a counter display of 36 pcs. (GB - IT)
- 25560 GIMA DIGITAL THERMOMETER °C hang box -60 seconds
- 25561 GIMA DIGITAL THERMOMETER °F hang box -60 seconds (89,6-107,6 °F)



• 25557 FLEXI JUMBO 2 DIGITAL THERMOMETER °C - hang box, flexible tip, water-proof resistant, fever alarm



• 25562 W-P DIGITAL THERMOMETER °C - hang box water-proof



• 25563 FLEXI DIGITAL THERMOMETER °C - hang box flexible tip, water-proof



25552

 25552 WIDE SCREEN DIGITAL THERMOMETER - box flexible tip, large diplay 27x22 mm. Battery 1.5 V button size



• 25553 BL1 WIDE SCREEN DIGITAL THERMOMETER - box flexible tip, water-proof, backlight after measurement, wide display (27x22 mm). Battery 3 V button size. Low battery indicator.

# BATH THERMOMETER



°C - Star Measures water temperature in 90 sec.

Measurement range 0 to 70° C. € 0476 Supplied in hang blister.



Available in °C or °F, provide accurate and quick read-out. Safe and easy to use with clear and large display.

- display range: 32.0-42.9°C (25556-7, 25559-60, 25562-4, 25552-4) 32.0-42.0°C (25558)

- accuracy ±0.1°C (±0.2°F)
- memory: last reading - beeper function and auto shut-off - plastic case
- multilanguage manual and box (GB, FR, IT, ES, PT, GR) 25556, 25557 have also PL, Arab
- 25549 BATTERY 1.5 V LR/41 box of 20 for all thermometers except 25558, 25553, 25554



• 25558 FLEXI JUMBO DIGITAL THERMOMETER °C - hang box flexible tip, water-proof, fever alarm, backlight jumbo display (31x14 mm size). Battery CR1220 3 V.





 25556 INSTANT DIGITAL THERMOMETER °C - hang box. flexible tip, water-proof, fever alarm, large display



Battery 3 V button size



Lower than 37.1 °C will show green. Between 37.2 and 37.9 °C will show Between 38.0 °C and 43.9 °C will



• 25554 BL3 WIDE SCREEN DIGITAL THERMOMETER - blister flexible tip, water-proof, red/orange/green backlight after measurement, wide display 29.3x15.3 mm. Low battery indicator

# BASAL THERMOMETER

• 25567 BATH THERMOMETER • 25608 DIGITAL BASAL THERMOMETER °C - hang box water-proof

With 4 digits, 2 decimals, for fertility control



25608

#### **HEALTH CARE - PATIENT AIDS**

# MANUAL AND ELECTRIC LICE COMB

Natural, ecologic method to eliminate completely lice and nits without any harm. any 10 blister Ideal for allergy sufferers and children.

• 24400 MANUAL LICE COMB - blister Ergonomic comb with long metal teeth and a detachable cleaning brush with built-in magnifier. The long, delicately closed teeth of the comb are designed specifically to detach lice and their nits (tiny eggs). The round form of the touching point respects the growth direction of the hair without harming its texture. Multilanguage blister: GB, FR, IT ES.

24400



• 24402 ELECTRIC LICE COMB

batteries.

This innovative product removes and kills lice and nits with a quick increasing electrical discharge of 130-180 Volts from the teeth, imperceptible and harmless to humans Auto switch off. Provided of buzzer indicator and cleaning brush. Supplied with 2 AAA

# STOPLICE ANTI-LICE AND NITS SHAMPOO

• 24404 STOPLICE ANTI-LICE AND NITS SHAMPOO - 250 ml - box of 20

Detachable cleaning brush

with huilt-in magnifier

Stoplice Shampoo is designed with special formula to get rid of nits and lice. The mechanical effect of tea tree oil, helps eliminating lices and nits. D-panthenol and aloe vera take care of hair and prevent the deterioration of the scalp. This product is suitable for all hair types. Apply by foaming and gentle massage, leave on hair for 10-15 minutes and rinse with warm water. Hair should be combed carefully to make sure all the nits and lices are cleaned. It is recommended to have at least two applications. Seven days after the first application, if necessary (if you come across nits again) repeat treatment.

**DENTAL HYGIENE** 



DEVICES AGAINST INSECTS, MEDUSAE, SNAKE BITES



TICK TWEEZER



 25773 ECOSAVE Electronic stimulator against snake bites or poisonous stings of insects and fishes Few electric shocks are enough to reduce toxic reaction.

€ 0051

# ■ UNSTINGER®

# 36655 GERMORAL MOUTHWASH - bactericidal

mouthwash One display contains 12 bottles of 300 ml

For daily oral hygiene, Germoral prevents and acts against the formation of bad breath because it stops fermentation in the oral cavity. It performs an essential antiplaque and hygienic action. Particularly suitable for smokers, prothesis or paradontic teeth users or after dental surgery for disinfecting the oral cavity.

If regularly applied it prevents and acts against inflammations, gingival disorders, dental plaque





GLASS 2X - 8 cm

# • 24395 UNSTINGER®

Insect poison extraction tool. An easy and painless way to avoid the discomfort that follows from bites and stings by bees, wasps, hornets and even scorpions or snakes.

Reusable one-hand operated vacuum pump which easily and painlessly extracts poison and venom from a sting or bite.



78

24390 TICK TWEEZER

# PHARMADOCT FIRST AID, MEDICATION AND WELLNESS



25360



25351

















25335









All products are in blister with 7 languages package (GB, FR, IT, ES, DE, PT, GR) except 25332, 25380/82/90 (only GB, FR, IT, ES, DE)

25352

GIMA code	PHARMADOCT LINE	Pieces per box	Minimum order*	GIMA code	PHARMADOCT LINE	Pieces per box	Minimum order*
25300	Classic plasters - 7x2 cm	20	12 box	25316	Herpes patch	15	12 box
25301	Classic plasters - 5 assorted sizes**	30	12 box	25318	Nasal strips	10	12 box
25302	Classic plasters - 6 assorted sizes***	100	12 box	25372	Ear plugs	4	12 box
25305	Hypoallergenic plasters - 5 assorted sizes**	30	12 box	25350	Corn plasters	10	12 box
25307	Hypoallergenic plasters - 2 (7.5x7.5), 2 (7.5x10)	4	12 box	25351	Oval corn plasters	9	12 box
25310	Children plasters "tattoo" 10 (6x2), 6 (7x3.8)	16	12 box	25352	Blister plasters	5	12 box
25312	Plasters with hemostatic gauze	20	12 box		Dental floss	1	12 box
25314	Hand plasters - 5 (12x2), 5 (7x2), 4 (butterfly)	14	12 box		Lip balm classic	1	12 box
25320	Dressing strip 100x6 cm	1	12 box		Lip balm strawberry	1	12 box
25322	Cloth roll - fabric - 5 mx1.25 cm	1	18 box		Nail scissors	1	12 box
25324	Cloth roll 5 mx2.5 cm	1	12 box	25361	Cuticle clipper	1	12 box
25335	First aid - kit of 8 different products	8	8 box	25362	Nail file	1	12 box
25330	Cotton gauze swabs 18x40 cm	6	12 box	25363	Tweezer	1	12 box
25332	Elastic bandages 4 mx6 cm	2	6 box		Small nail cutter	1	12 box
25337	Adhesive elastic compression bandage 2.5 m x 6 cm	1	6 box	25390	Condoms	12	8 box
*Minimum	order is carton of " " hoves each one containing " " nieces		10 (7×2) 10 (	1/11 2/38	(v3.8) 1 (7v2.1) 1 (01.2.5)		

\*10 (7x2), 10 (4x1), 2 (3.8x3.8), 4 (7x2.4), 4 (Ø 2.5) "30 (7x2), 20 (4x1), 20 (7x2.4), 10 (Ø 2.5), 14 (6x2), 6 (3.8x3.8)

# QUALITY PILL SPLITTERS AND PILL PULVERIZERS

Blade guard

Pill grip holds pills

securely in place

for double safety

These easy tools are ideal for elderly people, children and hospital attendants. Useful also for medicating pets. They avoid dispersion of medicine and guarantee integrity of the dose. Easy to clean, also in dishwasher. Made in non-toxic, unbreakable material.

• 25729 PILL SPLITTER - bulk

Quality stainless steel blade allows

Pill storage

an easy cut

 $\epsilon$ 

- 25730 PILL SPLITTER with box
- 25743 ULTRA PILL SPLITTER blister

Accurately divide tablets, large and small pills for reduced dosage or easier ingestion. Simple to operate.

Top quality products, made in Europe (25729-30), USA (25743)

• 25747 DISPLAY FOR SPLITTER (25730) PULVERIZER (25731) - empty (English language)

Suitable for 4 pill splitters and 4 pill pulverizers. Available in any language on request

• 25731 PILL PULVERIZER - with box • 25744 ULTRA PILL PULVERIZER blister

Powerful pulverizing point, powders pills of any shape and size, with an easy twist of the wrist.







25744

Multilanguage box and instructions: GB, FR, IT, ES, DE, PT, PL, GR

# MIXED COLOURS PILL SPLITTERS - BOX OR DISPLAY



25748 PILL SPLITTER - box of 12 pcs This box includes 12 pill splitters in 4 colours: light blue, green, transparent lavender and transparent

• 25749 PILL SPLITTER - display box of 12 pcs Counter display box including 12 pill splitters in 4 colours (light blue, green, transparent lavender and transparent orange) in a single cardboard box.

# COMBO SPLITTER-CRUSHER PILL BOX TIMER

# • 25765 PILL BOX TIMER

Pocket pill box timer in ABS material, size 90x50x19 mm, supplied in cardboard box with

Double pill box space to store pills and tablets. It reminds when you have to take your medication with a countdown up to 19 hours and 59 minutes





# VIALS OPENER

Water cup 25766

• 25766 COMBO PILL MANAGER 4 IN 1 Four functions in a practical device: pill splitter, pill crusher, pill box and water cup.

Pill splitter

81

• 25739 VIALS OPENER - box of 20 A practical tool to help opening vials in a safe way.





8x5.5x1.5

box/blister

7x5x2

blister

Size cm

Package

13x2.5x2

Supplied with a set of labels with day in 6 languages (English, French, German, Italian, Portuguese, Spanish) and 1 white label for compartment for individual marking.

17x12x2

box



• 28950 EASY OPENER

safety for the user.

This all in one product easily

opens bottle caps, pull tabs,

box tops! Designed to provide

and even those impossible

• 28912 SOCK AID NOTCH

Soft terry cloth on one side

nylon on the other side

reduces friction, allowing

your foot to slip in easily.

Two long loop handles are

pulling the sock onto your

easy to hold and assist with

foot. Ideal for those who have

the use of only one hand or with decreased strength or

coordination.

grips the sock, while smooth

 28925 SPOON & FORK HOLDERS - pack of 2 pcs. These portable, stylish holders tea and table spoon). Made fit onto virtually any style in stainless steel with thick, spoon and fork providing a ribbed rubber handle (10 cm) secure grip (spoon and fork for easy grip



• 28951 JAR OPENER & CLOSER This uniquely designed product concentrates hand nower to remove lids and turn facets effortlessly.

28911

For those with weak or

arthritic fingers, there's

This unique product

into position

probably no more difficult

task than fastening a button!

eliminates the frustration by

pulling the button or zipper

Folds to half-length to fit

easily into pocket or purse.

PULLER

28911 ZIPPER AND BUTTON



CARRIER This product provides an effort-free handle that regardless of bag loads



• 28966 DRINKING GLASS -

Capacity 250 ml graduated by

25 ml. Autoclavable. Can be

disinfected in washer. Not for

Drinking glass made of

polypropylene with a

separated tap and a lip.

box of 210

microwaves

remains constantly supportive, needed, yet small enough to



• 28941 MULTIPLE KEY TURNER Designed to assist person arthritis or other limited hand mobility can manipulate keys most car keys (without plastic head covers) fit into the slots and are held by a single screw.



 28940 EASY KEY TURNER pack of 2 pcs

These enlarged key turners are designed with the turning effort already begun, so completion of the turn is accomplished with minimal effort. Two different colours per package.



28901 PENCIL GRIP -

Rubber grip for pens or

pencils. Helpful aids for

elderly or disabled people.

in both shape and density

to alleviate stress while

providing a secure grip.

These cushions are designed

28906 MAGNIFYING GLASS

Magnifies two times larger

pack of 2 pcs.

with limited wrist strength or movement. People with with ease. House keys and



Lightweight sponge feature soft polyfoam attached to a plastic handle. Available with contoured sponge.



• 28960 GRASPING TOOL - 3 WAYS - 66 cm Aluminium body, PP handle. Three grasping ways steel hook, magnetic tip, rubber head.



• 28963 GRASPING TOOL - foldable Your extended reach grasping tool will

help you to eliminate bending or climbing for those hard-to-reach items. Length: 80 cm, foldable in 2. Locking tab holds the item in place.

15.5x3x2

82

9.5x2x2

21x14.5x3.5

box

18.5x9.5x3

box

# SOAPED SPONGE, SOAPED AND NON SOAPED WASH GLOVE



 36660 SOAPED SPONGE - box of 500 Disposable sponge in foam soaked with anallergenic, neutral PH soap. Ideal for patient cleaning and hygiene. Individually packed. Size: 7.5x12xh 2.5 cm

# **SKIN SOAP**

• 36671 FRAGRANCE SKIN SOAP - 1,000 ml Delicate skin protective. Fragrance soothing bath and shower with moisturizer RAGRANCI active agents, respects the lipid mantle and it is delicate on skin leaving it fresh and pleasantly soft. It is used for daily hygiene as a normal liquid soap, suitable for personal hygiene, bath, shower and shampoo. Suitable for frequent washing and very sensitive skins too, it

protects and soothes sensitive skin of children and elderly people. Fast to be rinsed leaves a fresh cleanness sensation. Sold in box of 12 pcs, only 2 pieces come with dispenser pump.

HOT-COLD GEL

36690 DISPENSER PUMP

• 34114 HOT-COLD THERMO GEL

Special gel keeps temperature (hot or

Size: 14x28 cm - box of 30 pcs.

cold) for long time.

Individually packed in single box

34114



 36663 SOAPED WASH GLOVE - box of 50 Disposable mitten to wash patient. Made in non woven and sponge, soaked with liquid soap with neutral PH and anallergenic. Ideal for patient cleaning and hygiene.

# **GERMELI**

• 36672 GERMELLA - 1.000 ml Germella is a skin-protecting liquid detergent combining the properties of three extraordinary medical plants: Camomile, Sage and Aloe. Camomile and Sage and have moisturizing and soothing qualities. Aloe Vera's main property is soothing Moreover Aloe makes your skin soft and velvety. Thanks to the Camomile, Sage and Aloe extracts. Germella is a delicate detergent, which

respects the natural defence of skin and mucous membranes. Thanks to its natural ingredients Germella is also particularly suitable for daily intimate care. Sold in box of 12 pcs, only 2 pieces come with dispenser pump.



 36661 WASH GLOVE - box of 1,000 Disposable wash glove to clean patients. Made in special airlaid, which allows to soap and rinse patient, and waterproof PE. Embossed surface allows a deep cleaning, Size: 16.5x22 cm. Made in Italy,

# **BIBS WITH POCKET**



 36666 BIBS WITH POCKET - box of 600 Disposable bibs made of 1 ply of highly absorbent wadding of cellulose and 1 ply of waterproof blue polyethylene. Box of 600 (6 bags of 100). Made in Italy.

# HOT WATER BOTTLES



• 28600 HOT WATER BOTTLE - British standard - blue 100% made of rubber, latex free.

• 28601 HOT WATER BOTTLE 2 I - red 25% made of rubber, latex free. Both are two side ribbed. Packed in plastic bag with multilanguage user manual (GB, FR, IT, DE, ES, PT, GR).



- large top cap O.D. 8.78 cm, I.D. 6 cm - light blue

Made of polyester fabric + PVC, latex free. Single packed in carton box, with multilingual manual (GB, FR, IT, DE, ES, PT, GR). • 28606 ICE BAG - Ø 28 cm - small top cap O.D. 7.15 cm, I.D. 4.7 cm - blue

Made polyester fabric + PVC. Single packed in transparent bag with multilingual manual (GB, FR, IT, DE, ES, PT, GR)

# **ELECTRIC HEATING PAD**

• 28655 ELECTRIC HEATING PAD Suitable for many applications. • 28656 ELECTRIC "SAND" HEATING PAD

The use of purified marine sands make it possible to naturally transmit their beneficial warmth.

Heating: position 1 up to 42°C in 30 min, position 2 up to 66°C (max 56°C first hour, up to 66°C following hours) External cover in cotton (94%) and nylon, internal bag in PVC Operating power: 230 V - 50/60 Hz - 75 W (28656) - 55 W (28655)



# GRADUAL COMPRESSION, UNISEX, COTTON SOCKS

#### UNISEX GRADUAL COMPRESSION COTTON SOCKS

High quality knee socks made from soft cotton combined with elastic fibres to provide proper gradual compression. Special attention was dedicated to the development of this cotton product line in order to ensure maximum fibre quality, along with an extremely soft elastic cuff that offers high levels of expandibility: all to ensure maximum comfort and wellness throughout the day.

This product line also offers two different compression levels (medium and strong) and is available in two colours (black and blue). On request, for quantities (minimum 100 socks) available also light and extra strong compression and beige and grey

Medium compression level: 14-16 mm/Hg at the ankle To help prevent discomfort and heaviness in the legs. Composition: 67% cotton, 26% polyamide, 7% elastane. High compression level: 15-21 mm/Hg at the ankle To help prevent the onset of venous disease. Composition: 63% cotton, 27% polyamide, 10% elastane. It is a Medical Device. Made in Italy.









OD, 111, 11, LJ, 11,	DL, GN, 110			-						
(	GRADUAL (	COMPRESS	ION COTTO	N SOCKS						
	MEDIL	JM COMPR	ESSION SO	CKS						
Colour	Small	Medium	Large	X-Large	XX-Large					
Black	41220	41221	41222	41223	41224					
Dark blue	41225	41226	41227	41228	41229					
	STROI	NG COMPR	<b>ESSION SO</b>	CKS						
Black	41240	41241	41242	41243	41244					
Dark blue	41245	41246	41247	41248	41249					
Shoe size										
European	37 - 39	39 - 41	41 - 43	43 - 45	45 - 47					
US - Men	5 - 61/2	61/2 - 8	8 - 91/2	9½ - 11	11 - 121/2					
US - Women	6½ - 8	8 - 10	10 & over	-	-					

# ☐ SUPPORT SHEER LINE

Knee Socks, Stockings and Tights designed for dynamic women Strong compression level: 140 den - 15-21 mm/Hg at the ankle who need the preventive action of elastic compression but don't want to compromise on style.

This elegant product line features a true heel, an anti-shrink cuff and extremly soft fabrics. This line offers two different compression levels (medium and

strong) and is available in beige or black. Medium compression level: 70 den - 10-14 mm/Hg at the ankle

Ideal for those who would like to initiate a prevention programme, but are mainly interested in the comfort and wellbeing offered by elastic compression stockings.

Composition: 84% polyamide, 16% elastane (Stay ups. Pantyhoses). 85% polyamide, 15% elastane (Knee-highs).

Ideal for those suffering from the initial signs of ankle swelling and discomfort This level of compression is also highly indicated in case of

initial onset of varicose veins. The product's compression level supports and massages the leg, thus providing effective relief throughout the day. While this product line boasts an extremely elegant design, particular attention has also been dedicated to maximum elasticity, which is ensured through the use of a honeycomb fabric (net fabric).

It is recommended to ask the advice of a physician prior to use. Composition: 79% polyamide, 21% elastane.

These products are Medical Devices. Made in Italy.



Knee-high with a gradual compression,

KNEE-HIGHS									
MEDIUM COMPRESSION									
Colour	Small/Medium	Large/X-Large							
Black	41100	41101							
Beige	41102	41103							
	STRONG COMPR	ESSION							
Black	41106	41107							
Beige	41108	41109							



Stay ups with gradual compression

	silicone lace	top, honey	comb mesh								
	STAY UPS										
	MEDIUM COMPRESSION										
Colour	Small	Medium	Large	X-Large							
Black		41121		41123							
Beige	41124	41125	41126	41127							
	STRONG COMPRESSION										
Black	41132	41133	41134	41135							
Beige	41136	41137	41138	41139							



Pantyhose with gradual compression, reinforced body, honeycomb mesh

	PANTYHOSES											
	MEDIUM COMPRESSION											
Colour Small Medium Large X-Large XX-Large												
Black	41150	41151	41152	41153	41154							
Beige	41155	41156	41157	41158	41159							
	STRO	NG COI	<b>MPRESS</b>	ION								
Black	41165	41166	41167	41168	41169							
Beige	41170	41171	41172	41173	41174							

# ANTI-EMBOLISM ELASTIC STOCKINGS - MADE IN ITALY

A line of stockings dedicated to prophylaxis of thromboembolism before, during and after surgery Thanks to their descending graduated compression, these stockings represent an excellent means of preventing increased blood viscosity, which can lead to the formation of

In order to guarantee a good fit and properly graduated compression, a great deal of attention has been dedicated to ensuring the high elasticity of the fabrics.

Multilanguage

instructions: GB. FR. IT. ES.

PT, DE, GR, HU

bag and

- a valid aid in preventing thromboembolisms linked to surgical interventions.

- treatments associated with post-traumatic therapies.





	-							
THIGH LENGTH								
COMPRESSION mm/Hg 18-20 (at the ankle)								
Length	Small	Medium	Large	X-Large				
60-70 cm	41316	41317	41318	41319				
70-80 cm	41320	41321	41322	41323				
80-90 cm	41324	41325	41326	41327				

#### - bruises, sprains and hydrostatic edemas Contraindications:

- localized dermatitis, erythema, necrosis - stripping, pulmonary edema, grafts
- vascular disorders of cardiac origin
- legs of larger circumference

- decreasing compression from the ankle to the thigh
- true anatomic heel
- extremely soft and elastic fabric, hypoallergenic (latex free)
- inspection opening on top of the foot Composition: 82% polyamide, 18% elastane.

These products are Medical Devices.



# **SOFFISOF INCONTINENCE PADS - MADE INITALY**

Multilanguage package: GB. FR. IT. ES. DE. PT. Arabic

AIR BREATHING



36701 - 36705

SOFFISOF CLASSIC AND AIR DRY INCONTINENCE PADS Elasticated incontinence pads

below knee

stocking with

inspection hole

anatomically shaped, for moderate to high incontinence level. Air dry pads have breathable backsheet. These high absorption incontinence pads offer maximum comfort thanks to their special shape, especially designed to fit perfectly Medium Large SOFFISOF CLASSIC

**BELOW KNEE** 

COMPRESSION mm/Hg 18-20 (at the ankle)

 Length
 Small
 Medium
 Large
 X-Large

 38-43 cm
 41310
 41311
 41312
 41313

3670136702Moderate incontinence-day3670436705Heavy incontinence-night367043671036711Heavy incontinence-night

36707

user's body. Lateral borders guarantee maximum security against any liquid leak and adhesive tapes make it easy to wear and use. Odour control thanks to combination of a last generation polymer and special kind of cellulose, 100% PEFC certified cellulose. Moderate incontinence: box of 90 (6 boxes of 15) Heavy incontinence: box of 60 (4 boxes of 15)

SOFFISOF AIR DRY

AIR BREATHING

Suitable for auto nomous people who live an active life: ideal also for patients during their recovery phase or during neuromotorial rehabilitation

# SOFFISOF PANTS/PULL-UP -

Practical disposable absorbable pant wearable as normal underwear for moderate to high incontinence level. Made of soft breathable non woven fabric to guarantee maximum comfort. It fits suser's body to offer discreet and

Medium Large SOFFISOF PANTS/PULL-UP 36715 36716 Moderate incontinence-day

# SOFFISOF ABSORBENT BED PADS

- 36720 SOFFISOF ABSORBENT BED PAD 60x90 cm box of 90 (6 boxes of 15) • 36721 SOFFISOF ABSORBENT BED PAD - 80x180 cm - box of 90 (6 boxes of 15)

Absorbent bed pads in 2 different sizes.

100% PEFC certified cellulose.

They assure high absorption and protection to bed

# 36715 - 36716 box of 84 (6 boxes of 14)

high protection against leakages.

# **BATH/SHOWER CHAIRS**



#### • 27730 SHOWER CHAIR with backrest

Aluminium frame, seat and backrest in plastic material. Height adjustable (35-45 cm), non slip end. Load: 100 kg.



#### 42906 REINFORCED SHOWER 42907 SHOWER CHAIR with CHAIR with backrest Aluminium frame, seat and

backrest in plastic material. Height adjustable (42-52 cm), non slip end. Load: 150 kg.



#### backrest and armrest Aluminium frame, seat and backrest in plastic material.

Height adjustable (41-54 cm). Load: 100 kg.



• 42920 BATH STEP - 1 step

• 42921 BATH STEP - 2 steps Stainless steel frame and plastic steps. Size: 27x41xh 14 cm

(42920). Size: 51x41xh14-29 cm (42921). Load: 100 kg

# SHOWER COMMODE WHEELCHAIR

#### • 42915 SHOWER COMMODE WHEELCHAIR Foldable shower

commode wheelchair with aluminium frame and plastic seat. Flin-up armrest and lockable front castors. Size: 75x44x48 cm Weight: 6 kg. Load: 100 kg

#### BATH CHAIR • 27755 SWIVEL BATH CHAIR Revolving bath chair at 360° with 4 positions for easier

access to bath Polypropylene seat Frame in painted steel, rotation system in stainless steel. Load: 100 kg.

Weight: 5.5 kg Made in Italy.



# BATH SEAT

• 42910 BATH SEAT - adjustable Aluminium frame and plastic seat (41x23 cm) Load: 100 kg.



73-78 cm adjustable

# **BATH/SHOWER STOOLS**

42915



#### SWIVEL STOOL WITH HANDLE

- easy tool-free installation - swivel seat with 90 degree position lock at every right angle location
- non-slip central seat pad and soft under-covers
- load 135 kg (300 lbs)



#### 42900 SHOWER STOOL fixed

Shower stool with aluminium frame and plastic seat 50x30 cm. Height adjustable 35-45 cm. Non slip end. Load: 100 kg



#### • 42901 SHOWER STOOL foldable

Shower stool with aluminium frame and plastic seat 50x30 cm. Height adjustable 44-47.5 cm. Non slip end. Load: 100 kg



# • 42903 SHOWER STOOL

Shower stool with aluminium frame and plastic seat Ø 32.5 cm Height adjustable 38-56 cm. Non slip end. Load: 100 kg



RAISED TOLLET SEATS - MADE IN EUROPE



• 27750 RAISED TOILET SEAT height 12.5 cm with fixing system (front screw) and fixed armrest made in anodized aluminium. Max load 130 kg (286.6 lb). Packing: 410x165x468 mm



• 27741 ARES RAISED TOILET SEAT - 10 cm with lateral fixing system. Max load 225 kg (495 lb). Packing: 373x128x410 mm



• 27751 RAISED TOILET SEAT height 12.5 cm with fixing system (back and front screw) and anodized aluminium reclining armrest. Max load 130 kg (286.6 lb). Packing: 410x165x468 mm



• 27740 ARES RAISED TOILET SEAT - 14 cm with lateral fixing system. Max load 225 kg (495 lb). Packing: 373x165x410 mm



• 27756 CLIPPER RAISED TOILET SEAT - 11 cm Easily adapt to any toilet bowl. Totally made of injected plastic, 4 fixation clips to secure strongly the seat on the toilet bowl. Max load 185 kg (407 lb).



 27735 ARES RAISED TOILET SEAT with LID - 10 cm • 27737 ARES RAISED TOILET SEAT with LID - 14 cm with lateral fixing system. Max load 225 kg (495 lb).

Packing: 373x128x410 mm (27735) 373x165x410 mm (27737)

SAFETY SUCTION GRAB BARS



28972 SAFFTY GRAB BAR - 443 mm 28973 SAFETY GRAB BAR - 545 mm • 28974 SAFETY DOUBLE GRAB BAR - 929 mm

Innovative line of GRAB BAR, can be quickly installed everywhere without need of drilling and screwing. Patented suction cups (Ø 93 mm). Holds up to 60 kg (28972/3) or 85 kg (28974) vertical and 45 or 60 kg (28974) lateral weight (tested by SGS). Ideal solution to support elder people during daily bathroom use. Top quality product made of heavy duty ABS, with patented "green/red" suction indicator for better safety.

# PLASTIC RIBBED GRAB BAR



- 28975 PLASTIC RIBBED GRAB BAR 30 cm
- 28976 PLASTIC RIBBED GRAB BAR 45 cm
- 28977 PLASTIC RIBBED GRAB BAR 60 cm

Ribbed plastic grab bar in Medical PVC, complete with ABS mounting plates and screw covers. Wall screws not included. Electrically isolated. The ribbed bars offer excellent anti-slip grid and are warm to the touch. Can be mounted either horizontally or vertically. Tube Ø 3.5 cm.

Max user weight 120 kg (205 lb). Manual: GB, IT. Made in Italy.

# □ U-SHAPE STEEL GRAB BAR



• 28979 U-SHAPE STAINLESS STEEL GRAB BAR - 70 cm White powder coated wall mounted lift up toilet support.

Designed to help getting up or transferring to and from the toilet. It can be folded upwards for easy accessibility.

Max user weight 125 kg (275 lb). Supplied without wall screws. Manual: GB, IT. Made in Italy.



WALKING STICKS



• 27779 "T" HANDLE ALUMINIUM WALKING STICK - bronze

• 27780 "T" HANDLE ALUMINIUM WALKING STICK - silver

• 27781 "T" HANDLE ALUMINIUM WALKING STICK - black

• 27782 FOLDABLE ALUMINIUM WALKING STICK - coffee

27784 CURVED HANDLE ALUMINIUM WALKING STICK

Adjustable height: 72-94 cm - weight 0.4 kg - max load 120 kg

Adjustable height: 67-90 cm - weight 0.3 kg - max load 100 kg

Adjustable height: 77-100 cm - weight: 0.32 kg - max load 100 kg

• 27795 RUBBER TIP int. Ø 19 mm - grey for 27780-2, 27793 - bag of 5

• 27796 RUBBER TIP int. Ø 15 mm - grev for 27790, 43070 - bag of 5

• 43060 STICK WITH SEAT - silver

Aluminium walking stick with seat, height 84 cm, weight 0.9 kg

**OUADRIPODS AND STICK WITH SEAT** 

• 43065 TRIPOD - silver Adjustable height: 71-94 cm - weight 0.36 kg - max load 100 kg

43060

Adjustable height 74-97 cm, weight 0.8 kg

43065

 43070 QUADRIPOD Q1 with PU handle - aluminium - silver Adjustable height 74-97 cm, weight 0.9 kg

• 43071 QUADRIPOD Q2 with small base and PU handle - silver Adjustable height: 65-88 cm, weight 0.8 kg

Adjustable height: 80-90 cm - weight 0.37 kg - max load 100 kg • 27783 FOLDABLE ALUMINIUM WALKING STICK - cashmere pattern • 43072 QUADRIPOD Q3 with PU handle - bronze Adjustable height: 86-96 cm - weight 0.36 kg - max load 110 kg

Adjustable height: 70-88 cm - weight 0.5 kg Maximum load for tripod

and quadripods: 100 kg

• 27796 RUBBER TIP int. Ø 15 mm grey for 43065, 43070/72 - bag of 5



43070





43071

QUALITY STICKS MADE IN FRANCE

**QUALITY STICKS** MADE IN ITALY



#### **BEECHWOOD STICKS:**

- 27760 GIOTTO CURVED HANDLE man brown
- 27761 GIOTTO CURVED HANDLE woman brown • 27762 RAFFAELLO "T" HANDLE - man - brown
- 27763 RAFFAELLO "T" HANDLE woman brown
- 27764 TIZIANO CURVED HANDLE unisex brown • 27765 TIZIANO "T" HANDLE - unisex - brown
- 27768 LEONARDO METAL CURVED HANDLE unisex black
- 27769 LEONARDO METAL "T" HANDLE unisex black

• 27772 TIEPOLO CHROMED "DUCK" HANDLE - unisex - black Max load for wooden sticks: 100 kg. Height: 92 cm\*. \*Depending on rubber tip and handle can change from 90 to 94 cm



#### WOODEN STICKS

• 27773 "T" HANDLE - wooden - maximum load 120 kg

• 27774 CROOK - chestnut - maximum load 100 kg

#### SYNTHETIC STICKS

- 27776 "T" HANDLE black load 120 kg
- 27777 CROOK amber style load 100 kg • 27778 CROOK - horn style - load 100 kg

# ADVANCED WALKING STICK

• 27771 "T" ADVANCE - grey

Aluminium height adjustable cane 745-975 mm with comfortable gel-grip to reduce hand stress. Maximum load 110 kg



# ELBOW CRUTCHES MADE IN FRANCE T-BAR AND ELBOW CRUTCHES LOAD 150 KG

43110

43115

- 43100 EVOLUTION CRUTCHES black/grey pair
- 43101 EVOLUTION CRUTCHES blue/grey pair

43100 43101 43102

- 43102 EVOLUTION CRUTCHES orange/grey pair Ergonomic handle and brachial support to enhance safety and quality of arm support while moving around. • 43110 PROGRESS 2 CRUTCHES - light grey/grey - pair
- For tall and heavy-weight adults, the handle adjusts from 22 to 29 cm. This crutch is suitable for adults whose height is comprised between 160 and 215 cm.
- 43115 TIKI CRUTCHES blue/orange pair
- For children or teenagers. The handle adjusts from 17.5 to 20 cm.
- 43120 RUBBER PVC TIP inside Ø 19 mm grey bag of 10

TECHN	ICAL SPECIFI	CATIONS	
Model	EVOLUTION	PROGRESS 2	TIKI
Weight kg:	0.5	0.5	0.5
Height handle to floor cm:	76-100	76-100	52-74
Material of handle:		—Polypropylene—	
Diameter upper/down pipe mm		22/19	22/19
Number of adjustment of heigh	nt: 10 time	s adjustable every	/ 20 mm
Finishing/material:	grey	anodization/alum	inium
Certified and tested for kg:	130	150	100
Standard used for testing:		EN ISO 11199-1	
Adjustable handgrip:	-	4 times	3 times
Handgrip size: Ø x l x h mm	35x100x235	35x100x220/290	32x100x175/200



#### • 27793 FOREARM CRUTCH

Lightweight aluminium tube. Anatomic handgrip.

Height adjustable 96-119 cm. Weight 0.55 kg. Max load 100 kg • 27792 T-BAR CRUTCH - small

Stainless steel type.

Adjustable height: 95-115 cm. Max load 100 kg

• 27798 T-BAR CRUTCH - medium

Stainless steel type.

Adjustable height: 112-132 cm. Max load 100 kg

• 27799 T-BAR CRUTCH - large

Stainless steel type

Adjustable height: 119-139 cm. Max load 100 kg

• 27770 T-BAR CRUTCH - extra adjustability

Aluminium crutch with adjustable height 100-130 cm. Max load 100 kg

• 27797 RUBBER TIP int. Ø 22 mm grey for 27792/8/9 - bag of 5

# SKID-PROOF STICKS WITH LIGHT STICKS WITH LIGHT AND ALARM





2 down to light



2 LED, up to 5 lumen - ABS hand grip and aluminium frame Supplied - 100 dB warning siren carrvino adjustable height: 10 positions from 78 to 100.5 cm and stra extra wide 360° pivoting base (43052 only) - stands on its own (43052 only) Works with 2 AAA batteries, not included. 43050 43052 Maximum load: 110 kg

# **ROLLATORS**



 27721 ROLLATOR Size 54x57 cm with adjustable height 52-87 cm

Weight: 8 kg - Load: 100 kg.



 43132 ROLLATOR WITH SEAT Blue painted steel adjustable height 79-93 cm frame with padded seat. Size: 52x49 cm. Weight 6.4 kg - Load: 100 kg.

# WALKING FRAME



non-slip end and padded handgrips. Size 47x60 cm foldable with adjustable height 78-96 cm.

Weight: 2.4 kg - Load: 100 kg.

• 27794 RUBBER TIP Ø 28 mm grey for 27722-3 - bag of 5 pcs.

# WALKING FRAMES WITH WHEELS



• 27723 WALKING FRAME - 2 WHEELS Made of lightweight aluminium tubing, with padded hand grips, 2 non-slip ends and 2 with wheels. Size 51x64 cm, foldable with adjustable

height 79-97 cm. Weight: 3 kg - Load: 100 kg.

• 27794 RUBBER TIP Ø 28 mm -

grey for 27722-3 - bag of 5 pcs.



• 43129 WALKING FRAME -2 INTERNAL WHEELS

Made of lightweight aluminium tubing with padded hand grips, 2 non-slip ends and 2 with wheels. Foldable. Size 51x58 cm


Adjustable height 80-90 cm. Weight: 2.5 kg - Load: 100 kg.

brakina 43130 • 43130 WALKING FRAME - 4 WHEELS

Made of lightweight aluminium tubing, 2 front swivel wheels, 2 rear wheels with

stop, with foam grips. Size 55x65 cm foldable with adjustable height 83-93 cm. Weight: 3.5 kg -Load: 100 kg.

FOLDING SHOULDER WALKER 
ROTATING SEAT CUSHION





Detachable

seat and



• 43140 3 WHEELS ROLLATOR - blue Blue painted steel, adjustable height frame. With 3 solid castors (2 fixed rear with brake and 1 swivel front). Supplied with shopping basket and tray. Weight: 7.7 kg - Load: 100 kg.

• 43142 IDEAL ROLLATOR - blue Blue painted steel, adjustable height foldable frame. With 4 solid castors (2 fixed rear and 2 swivel front). Ergonomic and adjustable handle and hand brakes. Supplied with padded seat, shopping basket and trav.

Weight: 12.5 kg - Load: 100 kg. Carton size: 590x290x680 mm





#### • 27724 COMFORT ROLLATOR WITH SEAT - foldable

With seat, large front basket and brakes on wheels. Size 68x61 cm. Adjustable height 78-90 cm. Seat at 46 cm. Seat size: 32x35x4 cm. Weight 7.4 kg - Load: 100 kg.



#### • 43143 SILVER ROLLATOR WITH SEAT foldable

With seat, large front basket and brakes on rear wheels. Size 68x61 cm.

Adjustable height 78-90 cm. Weight 7.4 kg - Load: 100 kg.



• 43145 LEISURE ROLLATOR - foldable Powder coated aluminium frame, grey colour. Comfortable cotton belt backrest and nylon seat. Height adjustable handles from 84 cm to 95 cm. Up-down bidirectional brake. Solid tires Ø 20 cm (8"). Provided with nylon shopping bag.

Weight: 8.2 kg - Load: 100 kg.

PEDAL EXERCISERS These pedal exercisers are compact exercise bikes. The regular use stimulate blood circulation and increase muscle



• 43150 BASIC PEDAL EXERCISER Supplied disassembled with screw and key for easy assembling. Multilanguage box and manual: GB, FR, IT, ES, PT, DE, PL, GR

strength: it is a great way to enjoy a moderate cardiovascular workout. Can be placed on a tabletop to exercise arms



• 43151 DISPLAY PEDAL EXERCISER Folding type to save space when not in use. Provided with 5 function display: exercise time, rotation count, rotations per minute, calories burned and scan.



**EXERCISER** Display indicator: scan. mode, calories, time, Reps, total Reps. Power 220 V - 50 Hz - 65 W.

# 43201 • 43201 ELITE 110 COMMODE - 42 cm

handle

- blue, washable, flame retardant
- plastic pan
- 4 pivoting wheels Ø 8 cm (2 with brake)
- adjustable height footrest can be placed over WC

- chromed steel frame



• 43203 ELITE 200 COMMODE - 43 cm • 43204 ELITE 200 COMMODE - 53 cm

- chromed steel frame
- blue, washable, flame retardant leatherette

- plastic pan
   4 wheels Ø 20 cm (2 with brake)
   adjustable length and raising footrest - removable armrest
- reclining backrest



Same features as 43201 with adjustable heiaht. without

43199 Universal tray 43210

- 43212 WHEEL Ø 20 cm front spare
- 43213 WHEEL Ø 20 cm rear spare
- 43216 BELT
- 43217 BELT with strap

Sturdy and washable polypropylene belts. Quick mounting.

#### TECHNICAL SPECIFICATIONS

	ELITE 50	ELITE 110	ELITE 200
Size (cm):	52x60xh 70/78	52x80xh 100	54x88xh 105
Seat height	46/54 cm	50 cm	53 cm
Seat width	42 cm	42 cm	43 or 53 cm
Weight	20 kg	20 kg	21 kg
Load	90 kg	90 kg	100 kg

# COMMODE CHAIRS • 27701 COMMODE CHAIR - chromed steel

Chromed steel chair frame, with plastic detachable commode seat.

• 27702 COMMODE WHEELCHAIR - painted Powder coated steel frame, detachable armrest and footrest, solid rear castors with lock, plastic commode seat. 27703 COMMODE WHEELCHAIR

stainless steel Stainless steel chair frame, detachable

armrest and footrest, rear castors with lock, plastic commode seat.

• 27699 FOOTREST for 27702 - pair • 27700 FOOTREST

for 27703 - pair • 27766 PLASTIC WC BOWL spare - Ø 26xh 15 cm





code 27702/3 100 42 54x53x53 17 18 27701 44 47 43 56 38

# WC - SHOWER COMMODE

# ☐ COMFORT COMMODE CHAIR



• 27758 BATH BENCH with backrest

Aluminium frame and padded seat. Removable plastic bowl WC. • 27766 PLASTIC WC BOWL - spare

• 27759 WC - SHOWER COMMODE Suitable also as raised toilet seat Adjustable height 45-55 cm (hack 78-88 cm)

• 27766 PLASTIC WC BOWL - spare



removable seat offers this chair the best comfort and high level of hygiene. Pan is removable from both sides and from the top. 43190 COMFORT

COMMODE CHAIR - blue

 43191 COMFORT COMMODE CHAIR - height adiustable - blue

Made in France. MAX LOAD 130 kg

Total height: 86 or 86/97 cm Width between armrests: 51.5 cm Total width: 60.5 cm

Height armrest-floor: 72 or 72/83 cm

**TECHNICAL SPECIFICATIONS** Height seat-floor: 52 or 52/63 cm Height seat-backrest: 38 cm Seat plate depth: 39 cm Total depth: 58 cm

43191

Veight:

6.8 ka

# LIGHTWEIGHT ALUMINIUM FOLDING WHEELCHAIRS

43250 OUEEN ALUMINIUM

WHEELCHAIR - 46 cm seat -

- fixed armrest, cloth pad

- 15 cm (6") front solid castors

- locking brakes on rear wheels

- fixed flip-up footrest with leg strap

- 30 cm (12") pneumatic rear wheels

Large pocket on back CE

Aluminium

light blue tissue

- folding back

Locking brakes

- 46 cm seat - black tissue

double cross bar

- double cross bar



## • 27708 PAEDIATRIC WHEELCHAIR -

#### 35 cm seat - black tissue

- single cross bar
- padded flip-up armrest
- fixed footrest, flip-up foot plate with leg strap
- 15 cm (6") solid front castors
- 56 cm (22") pneumatic rear wheels
- locking brakes on rear wheels - folding back
- large pocket on the back



#### 43240 CLASSIC ALUMINIUM WHEELCHAIR - 46 cm seat - black tissue

- single cross bar

- 61 cm (24") solid rear wheels with quick
- release axles
- 2 small wheels



anti tipper system with 2 small wheels and 2 carrying wheels

27720



# 43251 PRINCE ALUMINIUM

#### WHEELCHAIR - 46 cm seat - black tissue

- double cross bar
- fixed armrest, PU pad
- extra light aluminium frame only 9.5 kg - flip-up footrest with leg strap
  - locking brakes for rear wheels
  - 51 cm (20") PU rear wheels

  - 15 cm (6") solid front castors
  - folding back
  - pocket on the back



#### • 27720 KING ALUMINIUM WHEELCHAIR • 27717 DELUXE WHEELCHAIR -46 cm seat - black tissue

- double cross bar
- flip-up height adjustable
- armrest, PU pad
- detachable footrest, flip-up plate with leg strap
- 61 cm (24") solid PU rear wheels
- 15 cm (6") solid front castors
- locking brakes on rear wheels
- anti tipper system with 2 small wheels

Z Jillul	VVIICC					2 31111	an vviice	is arra a	L curryii	ig willed	.13		cibber :	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
Wheel	SPA	RE - A	CCESSOF	RIES							1			121	0		3	2
chair	Rear wheel	Front wheel	Foot- rest pair	IV stand	HH	1	1	(D)	Ob	Ob.	0	<b>S</b>	凸				NW	6W
27708	27742	-	27710	27705	52	32	35	56	15	48	90	97	36	40	75	85x33x73	13	15
43250	43252	43253	43254	-	60	-	46	30	15	48	90	100			100	71x28x72	9.5	11
43251	43248	27789	43249	27705	63	-	46	51	15	48	91	-	-	-	100	84x31x74	11.8	13.5
43240	43244	43243	43242		68	30	46	61	20	50	96	106	42	46	120	81x30x80	15	17.5
27720	27787	27791	27728	27705	63	-	46	61	15	50	89	-	-	-	100	83x28x91	17.2	19.4
27717	27748	27791	27714	27705	67	36	46	61	15	51	91	105	40	45	100	80x33x93	17	19

# FOLDING STEEL WHEELCHAIRS



#### • 43220 VALUE WHEELCHAIR -46 cm seat - nylon black tissue

- double cross bar
- fixed armrest, PVC pad
- fixed footrest, flip-up plate, with leg strap
- 20 cm (8") solid front wheels - 61 cm (24") solid rear wheels
- locking brakes on rear wheels
- pocket on the back



27709

- double cross bar
- plate, with leg strap
- 15 cm (6") solid front wheels

27715 ROYAL WHEELCHAIR -

46 cm seat - black tissue

- flip-up armrest, PU pad

flip-up plate with leg strap

- large pocket on the back

- 61 cm (24") pneumatic rear

wheels with quick relase system

- 15 cm (6") solid front castors

- locking brakes on rear wheels

- chromed steel frame

- detachable footrest,

double cross bar

- folding back

- 30 cm (12") pneumatic rear wheels
- locking brakes on rear wheels handles brakes for rear wheels
- folding back
- pocket on the back



#### • 43230 NARROW WHEELCHAIR 41 cm seat - black tissue

- single cross bar
- fixed armrest, PU pad
- detachable footrest, flip-up plate, with leg strap

Wheelchair

43230

43230

passing through

narrow transit

- 20 cm (8") solid front wheels 52 cm (20") pneumatic rear wheels
- · locking brakes on rear wheels
- adjustable distance from 43225
  - foot plate to front seat 46-56 cm





#### 27716 EXTRA LARGE WHEELCHAIR -

# 27715 56 cm seat - black tissue

- double cross bar

  - powder coated steel frame
  - super width 56 cm seat
  - flip-up armrest, PU pad detachable footrest, flip-up
  - plate with leg strap
  - 20 cm (8") rubber foam front castors
  - 61 cm (24") pneumatic rear wheels

- large	pocket	on 1	the	back
---------	--------	------	-----	------

Wheel		SPA	RE - AC	CESSOI	RIES								1			In	A.		3	2
chair	Rear wheel	Front wheel	Foot- rest pair	IV stand	Table*	PVC" backrest	国門		Ob	Ob	Ob1	Œ	Ct.	Ж	凸	Δ		NW	6W	
43220	43221	43222	43223	-	-	-	59		46	59	20	47	91				100	95x27x93	15	17
43225	43226	43227	43228	-	-	-	63		46	53	15	49	91				100	76x30x76	14	16.3
43230	43231	43232	43233	-	-	-	51	30	41			56	98.5	100	45	38	100	77x31x100	15.8	
27709	27744	27788	27711	27705	27706	-	64	24	46	58	20	49	87	106	40	45	100	94x23x89	17	19.2
27715	27746	27789	27712	27705	-	27707	64	28	46	61	15	51	94	106	40	45	100	80x28x78	15.8	18.6
27716	27747	-	27713	27705	27706	-	73	32	56	62	20	54	93	109	45	46	125	83x33x93	21.5	24.1

\*\* Fire retardant PVC backrest and seat

\* Size of table: 32x55 cm

• 27709 STANDARD WHEELCHAIR -

46 cm seat - blue tissue

- fixed armrest, PVC pad

- fixed footrest, flip-up plate

- 20 cm (8") solid front castors

- 61 cm (24") solid rear wheels

- large pocket on the back

- locking brakes on rear wheels

- single cross bar

- chromed frame

with leg strap

**BASIC CARE** 

# **FOLDING WHEELCHAIRS**





- 43261 ESSEX WHEELCHAIR 46 cm black tissue • 43262 ESSEX WHEELCHAIR - 51 cm - black tissue
- blue powder coated steel frame
- rear solid PU wheels Ø 30.5 cm (12")
- front solid PU wheels Ø 20 cm (8")
- locking brakes on rear wheels
- front powder steel fork
- padded flip-up armrest
- detachable aluminium footrests with 6 height adjustable clips, flip-up plate, heel straps
- black nylon seat and back
- manual: GB, FR, IT, ES
- 43263 ALUMINIUM FOOTPLATE pair spare



- 43270
- 43271
- 43272
- blue po
- pneun (24") wi
- and quic - front so
- manua 43274
- 43275
- Same as above, but with solid PU rear wheels Ø 61 cm (24") and anti tipper system.
- 43276 PLASTIC FOOTPLATE pair spare • 43277 PNEUMATIC REAR WHEEL - spare for 43270-2
- 43278 SOLID PU REAR WHEEL spare for 43274-5

Flaps length: 50+50 cm (top + bottom)  28564
BUBBLE MATTRESS Designed for the treatment and prevention of stage I in short-term and domiciliary therapies. The PVC mattress is composed of 130 7 cm-high particularly comfortable. Fixable to bed by extr top and bottom side. Cold-resistant -30 degree PUMP SYSTEM
Special silent pump for an excellent
pressure regulation by a knob on the front panel. It can be hung to any kind
of hospital bed frame by means of two
adjustable hooks. For use with bubble
or alternating cell mattresses. 28565
TECHNICAL SPECIFICATIONS - PUMP  28565  Size: —— 25x12xh 10 cm —  Operating voltage: —— 220 V, 50 Hz —  Working pressure: 40-100 mmHg Air output: 6-7 liter/min

Wheelchair		#	F	OB.	Ò.	Òd!		À.	A	丛	Δ		NW.	SW GW
43260	58	24	43	30.5	20	50	92	94	40	41	120	70x23x95	16	18
43261	61	24	46	30.5	20	50	92	94	40	41	120	70x23x95	16	18
43262	66	24	51	30.5	20	50	92	94	40	41	120	70x23x95	16	18
43270	60	26	43	61	20	50	92	102	40	41	120	82x26x85	18	20
43271, 43274	63	26	46	61	20	50	92	102	40	41	120	82x26x85	18	20
43272, 43275	68	26	51	61	20	50	92	102	40	41	120	82x26x85	18	20

# POWERED WHEELCHAIR • 27729 POWERED WHEELCHAIR - 41 cm seat

Powered wheelchair, easy to use, for daily indoor use. The user can move the powered wheelchair forwards, backwards or turn round in the same place only by the controller. When the power is not enough, it can be used as a transit wheelchair. The seat cushion is detachable. Powder coated steel frame, adjustable armrest pad, detachable sideboards, detachable strong footrests, adjustable backrest inclination, rubber foam castors and drive wheels, with safety lamp. Size: 1,090x630x970 mm, weight: 64 kg (including batteries). Load: 110 kg. Speed: 0-6 km/h.

Power: 2x12 V=24 V (20 km distance with fully charged batteries) Battery charger 100-240 V, 50/60 Hz included.





#### **EN71 MEDICAL** Cells are fixed by means of **GRADE PVC** pressure stud and can easily be 28567 replaced in case of breakage INTERCHANGEABLE CELL-MATTRESS Recommended for the prevention and treatment of pressure of pressure sore sore stage I and II in medium-term and domiciliary therapies. gh bubble cells, The 20 9.5 cm-high Nylon+PVC cells provide superior comfort. tra flaps on both GIMA MATTRESSES AND PUMP code 28564 Bubble mattress 28565 Pump for 28564 **28566** Kit bubble mattress+pump (28564+28565) 28567 Interchangeable cell mattress 28568 Pump for 28567 28569 Kit cell mattress+pump (28567+28568) 28570 Spare cell for 28567 Manual and box in 10 languages: GB, FR, IT, ES, DE, PT, PL, HU, GR, Arabic **TECHNICAL SPECIFICATIONS - MATTRESS** 28568 28564

40-110 mmHa

6-7 liter/mir

12 min

ANTI-DECUBITUS AIR MATTRESSES WITH PUMP - STAGE LAND II

# THERAPEUTIC ANTI-DECUBITUS MATTRESSES - STAGE III AND IV

Total size

Material:

Thickness:

Number of cells:

Cell height:



-Taiwan chimei ABS -

-TUV-CF JFC/FN60601-1: 60601-1-2 ---

6 min

• 28575 KIT 5010 ALTERNATING PRESSURE MATTRESS + PUMP Valuable overlay system designed for prevention and treatment of patients at moderate to intesive risk of pressure ulcers. Pressure is periodically redistributed by inflating and deflating cells in order to mimic natural sleep movement patterns and avoid long term pressurization of tissue. Manual in: GB, IT.

• 28576 CELL for 28575 - spare

Cycle time:

Plastic casing

ALTERNATING FUNCTION Alternating function (Group A and Group B as shown in the picture). The pump will inflate and deflate the cell with cyclicity, to change the contact position between the patient and the bed, to promote the blood circulation to prevent the bedsore and recovery the bedsore, reducing the patient's pain and the nursing labor intensity.
Pillow function (28578 only). The cell of the head position

Air output:

Alternating function of 28578 won't be alternating, for more comfort to the patient. TECHNICAL SPECIFICATIONS - PUMPS (28575 and 28578) Cell height: 12.5 cm (5") Working pressure: 55-120 mmHg Size: 30x13.5xh 11 cm Operating voltage: 220 V, 50 Hz 12 min Cycle time 7-8 liter/min

TUV-CE IEC/EN60601-1; 60601-1-2 PUMP 28578 only

Flame retardant ABS Static Mode, low pressure alarm, quick connector, transfer function



200x90x7 cm

7 cm (2.7")

PVC

0.32 mm

130

28567

200x86x9.5 cm

9.5 cm (4")

Nvlon+PVC

0.32 mm

20+1 spare

 28578 KIT 8050 ALTERNATING PRESSURE MATTRESS + PUMP Advanced systems of alternating pressure mattress. The multi-mode pump offers.

- alternating mode: the pressure is periodically redistributed by inflating and deflating cells in order to mimic natural sleep movement patterns and avoid long term pressurization of tissue. - constant static mode: the pressure is about 2/3 lowered when compared to the same pressure level from alternating mode by means of immersion and envelopment. Visual alarms notify the caregiver unusual situation, reducing the risk of human error. Suitable for the prevention and treatment of all stages

of pressure ulcers. Manual in: GB, IT. • 28579 CELL for 28578 - spare

TECHNICAL SPECIFICATIONS - MATTRESS								
	28575	28578						
Total size:	200x90x12.8 cm	200x90x22 cm						
Alternating		oup A and B) ———						
Cell height:	12.8 cm (5")	22 cm (8.66")						
Cover material:	Nylon PU with button	Nylon+PU with cotton lining						
Thickness:	0.4 mm	0.3 mm						
Cells material:	nylon PVC	TPU						
Suitable for persons up t	o: 150 kg	180 kg						

Case material:

# ANTI-DECUBITUS AIR MATTRESSES - MADE IN ITALY

#### • 28483 KIT MASTER (AIR MATTRESS 28492 + MASTER PUMP 28482)

#### 28492 AIR MATTRESS WITH BUBBLES

Air mattress with bubble sections which inflate and deflate alternatively latitudinally through the alternative compressor. The continual movement given by the pressure pumped inside is useful to prevent minor bedsore problems.

#### **TECHNICAL SPECIFICATIONS MATTRESS - 28492**

Total size: 190x85 cm Inflatable size: 160x85 cm Weight: 3 kg

PVC thickness: 0.4 mm Suitable for persons up to: 90 kg



• 28495 RINT PLUS AIR MATTRESS - interchangeable cells Rint Plus Mattress is made of a strong and soft PVC, realized with 17 big interchangeable bars. The integrated CPR function (Cardio Pulmonary Reanimation) allows the immediate emptying of the 17 bars. Supplied with bi-elastic, liquid proof and permeable to water-steam cover.

 28496 INTERCHANGEABLE CELL - spare for 28495 • 28497 COVER - spare for 28495

**TECHNICAL SPECIFICATIONS MATTRESS - 2849** Total size: 195x85x10.5 cm Inflatable size 5.5 kg Weight: PVC thickness: 0.4 mm Number of elements

• 28482 MASTER PUMP SYSTEM - with pressure adjustment Made of stiff and strong ABS with control handle for easy pressure regulation. Air amount is adjustable to suit patient weight from 40 to 90 kg (28492) or 120 kg (28495). The mattress should inflate totally in about 20 minutes. Air output 2.5 l/min. Master pump can be used with bubble or interchangeable section mattress. Flame retardant PVC. • 28481 MEMBRANE - spare for pump 28482/3

TECHNICAL SPECIFICATIONS FOR MASTER PUMP - RINT PLUS PUMP

Size: 315x150x120 mm Weight: 1.95 Kg Operating voltage: 230 V - 50 Hz on request 110 V - 60 Hz

Power Consumption: 8 W Working pressure: 30-120 mm/Hg Regulations: IEC-601-1 class II Type B



• 28498 RINT PLUS PUMP SYSTEM - with pressure adjustment Same as Master pump (28482) but with special valve for use with Rint Plus Mattress.

28481 MEMBRANE - spare for 28498



# ANTI-DECUBITUS PVC WATER MATTRESS

Suitable for persons up to:

It is made in PVC with a stabilising inflatable external structure to prevent excessive water "wave motion" and of 3 independent units. The water mattress distributes the total pressure on the whole supporting surface, making this less than the average arterial pressure, avoiding the exposure of the skin to pressure risk. Easy to use, it is placed over the usual mattress and it is washable. It is sold with a manual pump,

120 kg

2 disinfectants and an inflation tube

Size: 190x85 cm.

Weight 4 kg. PVC thickness 0.4 mm **MADE IN ITALY** 

# **PVC WATER MATTRESS**

# 28502 VALUE PVC WATER MATTRESS

It helps movement and distributes pressure on the whole supporting surface. Double sealed seams provide maximum strength and durability. Highly resistant PVC material

construction easy to clean with any mild detergent. Air frame + 3 water

elements. Supplied with hand pump and hose.

28502

**TECHNICAL SPECIFICATIONS** 

Material: PVC 0.40 mm thickness Size of outer air frame: 200x93x11.5 cm

Size of each element: 69x60x11.5 cm

• 28507 SHAMPOO BASIN Inflatable shampoo basin ideal for personal in-bed hair care needs. It supports the head, neck and shoulders during shampooing. A 20 cm deep basin helps prevent splashing. Drain hose efficiently removes water and foam. Supplied with water bag with shower head in clip. Size: 53x61x20 cm

Capacity: 10 l 28509 WATER BAG

# SHAMPOO BASIN

28509 ater bag for easy water nsport when water source is not easily accessible 28507

98

28499

VC rigid edge

inflatable with air

# ■ ANTI-DECUBITUS CUSHIONS - MADE IN FRANCE






GIMA line of seat cushions is designed to prevent decubitus risk for patients on wheelchair or permanently on chairs. All cushions in Gel or Foam are supplied with a waterproof PU cover with zipper and handle.

• 28530 BULGEL CUSHION 41x41x3 cm 28531 BULGEL CUSHION 43x43x3 cm This anti-decubitus cushion is made of a flame-resistant pocket including a PE foam core covered by an aqueous gel.



 28534 VISCO-MOUSS CUSHION 41x41x6 cm • 28535 VISCO-MOUSS CUSHION 43x43x6 cm Pre-shaped moulded cushion made of viscoelastic foam with memory effect. Memory foam is pressure sensitive and moulds quickly to the shape of a body pressing against it, returning to its original shape once the pressure is removed. Anatomical shape with raised lateral edges and front-back slope improves positioning, stability and comfort when seated. Foam density: 86 kg/m3





 28538 GEL AIR 2D CUSHION 41x41x7.5 cm
 28539 GEL AIR 2D CUSHION 43x43x7.5 cm Made of a contoured moulded viscoelastic foam base (i.e. Visco Mouss) connected to a polyurethane gel insert. The viscoelastic fluid gel (blue pad) ensures maximum pressure relief of vulnerable bony areas while the regular gel and the foam increase the contact surface and maximize pressure relief. The cushion's shape ensures a good posture while seating and prevents from sliding forward. Foam density: 86 kg/m<sup>3</sup>

# AIR CUSHIONS

- 28544 GIMA AIR CUSHION 40x40x6 cm • 28546 GIMA AIR CUSHION - 45x45x6 cm with polyester cover, pump and repair kit
- single compartment
- air cells, 64 or 81, prevent pressure sores - maximizes pressure distribution and blood flow
- conforms to the body's shape
- adjust to body changes over time. Max load: 150 kg

Multilanguage manual: GB, FR, IT, ES, PT, GR, PL, DE



# HEEL PROTECTOR

• 28548 HEEL PROTECTOR - 50x22x16 cm It relieves the heel pressure and prevents decubitus ulcer by increasing the contact

surface. The visco elastic foam has an anatomical shape including a bactericide and fungicide agent to provide better

hygiene and disinfection.

Density: 90 kg/m

# ANTI-DECUBITUS CUSHIONS AND NECK PILLOWS - MADE IN ITALY

Products to prevent low decubitus risk, made of silicone fibre, coated with 100% preshrunk\_cotton cover. Main property of



28550 SHAPED CUSHION WITH HOLE



• 28555 TRAVEL NECK PILLOW

silicone fibre is to maintain original shape also after strong pressure. This allows to maintain comfort and proper weight



• 28551 3-SECTION CUSHION

All cushions and pillow are supplied with multilanguage instruction GB FR IT FS 32x12 cm

28556 HEEL CUSHION

distribution in the time. Breathable cotton cover provides maximum cool comfort. Washable at 30-40°C.



28552 CUSHION WITH CONCAVE CENTRE



28557 HEEL CUSHION PLUS

### **RELAXING ARMCHAIR** WITH 1 OR 2 ENGINES - MADE IN ITALY



### RELAXING ARMCHAIRS

Relaxing multifunctional armchair adaptable to any need. 2 models (Beatrice and Betty), 1 or 2 engines and 10 colours. Fabric 100% polyester. Load 120 kg.

One engine: two button control for synchronized movement of leg section and back.

1 engine	2 engine	BEATRICE ARMCHAIRS
45150	45155	Beatrice - colour on request**
45151	45156	Beatrice - beige 2

"Product available in 15-20 days



Two engines: four button control for independent movement of leg section and back.

.111 1110101 230	0 - 30 112.	
1 engine + l	ifting up	2 engines + lifting up
11	4	
1 engine	2 engine	BEATRICE ARMCHAIRS
45160	45165	Betty - colour on request**
45161	45166	Betty - blue 11

**BED-TRAYS** - FOLDING LEGS

### **INVALID RINGS**



Ouality invalid rings made of latex-free rubber. 28614 Internal

hole Ø	14 cm.
GIMA code	INVALID RUBBER RINGS LATEX - FREE
20640	Incomplied winess ON DE anno

**28610** Invalid ring Ø 35 cm 28611 Invalid ring Ø 40 cm 28612 Invalid ring Ø 45 cm 28614 Pump for invalid ring

### Bed-trays with anti-scratch surface and containing edge. Folding legs. Size: 60x40x24 cm. Made in Italy. • 44750 BED TRAY - white • 44753 SERVOPLUS BED TRAY -3 position - walnut 44750 44753 Weight: 3.2 kg

### **DINING TABLE**



#### 27449 DINING TABLE

Patient dining table with polished aluminium tubular structure. White laminated wooden top, easy to clean, with anti-shock rubber PVC band. It is mounted on two rubber feet and two plastic wheels Ø 40 mm to allow movability and comfortable use. Delivered in kit form. Made in Italy.

### OVERBED TABLES



Chrome plated/epoxy glass finish square steel tube.

Tiltable and sliding serving tray made of thermoformed anti-shock plastic material with retaining edges and pre-formed bottle, glass and cutlery holder. Base with 4 Ø 50 mm castors (2 with brake). Delivered in kit form. Made in Italy.

frame and high density board. Base with 4 Ø 50 mm (2.5") removable castors (2 with brake). Adjustable height and angle Board size: 41x61 cm. Carton size: 65x7x67 cm.

Delivered in kit form.

### HYDRAULIC AND ELECTRICAL LIFTERS



Electric patient lifter,

adiustable base

Max load 170 kg

Sling support max h 167 cm Adjustable base 68-118 cm

### 27749 • 27749 HYDRAULIC LIFTER max load 200 kg

Lifting movement through a hydraulic pump operated by adjustable side control lever. Descent movement by independent exhaust-valve. Adjustable base 68 to 118 cm controlled by a manual device for an easy access to narrow places. Painted steel frame. Anti trauma pushhandle. 2 rear castors Ø 100 mm.

with independent brake and 2 front castors Ø 70 mm. Equipped with sling with head support (27754). Made in Italy 27752 ELECTRICAL LIFTER 170 - max load 170 kg 27753 ELECTRICAL LIFTER 200 - max load 200 kg

Same as code 27749 but with electrical controls. Up and down movements through an electric motor 24V D.C. and push button. Battery fed with current transformer with an emergency push-button for the immediate stop of the movement and free up/down piston-stroke. Supplied with universal sling (27752) or sling with head support (27753).

• 27757 UNIVERSAL SLING - spare - load 170 kg

• 27754 SLING with head support - spare - load 250 kg Mesh fabric sling.

### LIFTING STAND



#### • 27645 LIFTING STAND

Tubular painted steel frame with adjustable chromed steel joint. Can be fully disassembled to reduce size. Three main height adjustments. Triangle hangs from belt with adjustable length.

### **SHOWER MATTRESS**

#### • 27836 SHOWER MATTRESS

It allows bed-ridden, elderly or disabled patients to be washed and cared for in their personal hygiene with running water directly on their bed, without any need for transfer/lift. Inside the "Shower Mattress", the patient can be showered with water coming from the tap via an extension hose or using the special pressurized water tank provided with flexible hose and shower head

Once finished, the water is drained into a suitable container. Complete with plug and flexible hose for quick water drain. • 27837 WATER TANK - 10 I

Pressurized water tank complete with flexible hose 4 m and shower head operated by button.

• 27838 SHOWER EXTENSION HOSE

Flexible, 6 m hose complete with button-operated shower head and tap adapter.



# SHOWER TROLLEY - HYDRAULIC OR ELECTRIC HEIGHT ADJUSTMENT

### • 44770 SHOWER TROLLEY - hydraulic

Shower stretcher can be used for both transport and showering, and is the ideal solution for treatment of patients in assisted baths of hospitalization or retirement home.

Easy to move thanks to rubber castors with individual brake and one with directional lock to facilitate transport in long linear

Automatic progressive tilting to allow a gradual water drainage Safety side rails with one-hand folding/locking system. Supplied with PCM foam padded waterproof matress made with fire-resistant auto-extinguishing Class 2 PVC. trapezoidal pillow, same specifications as mattress, and extendable and flexible drain hose (Ø 40 mm - length 1.5 m)

• 44771 SHOWER TROLLEY - electric

Same as 44770 but with electric lifting system (Linak actuator, 6,000N, DC 24 V, 4.5 A).

IP x 5 control box	with emergency stop	١.	
	TECHNICAL SPECIFIC	ATIONS	
Max working load:	190 kg 93 ka	Directional system: Collapsible head end rail:	yes
Weight: Size:	2,000 x 746 x h 753/1,108 mm		yes 20 cm
Castor diameter:	12.5 cm		7°
Castor braking system:	Individual on each castor	Discharge hose length:	150 cm





Bed tray/bookrest tilting

in 3 positions.






- 27690 MATTRESS 190x80x12 cm
- 27680 MATTRESS 195x85x14 cm
- Polyurethane foam mattresses, density 30 kg/mc
- 27693 100% COTTON COVER FOR MATTRESS 27690



#### 27682 MATTRESS WITH COVER 195x85x14 cm Polyurethane foam mattress, density 30 kg/mc with flame retardant, 100% breathable polyester cover. Class 1



#### 44806 AMYLIFE MATTRESS WITH COVER 195x85x14 cm Mattress with polyurethane foam base and viscoelastic high density top. Density 35 kg/mc (base), 60 kg/mc (top). Non deformable, antibacterial, antifungal and autoclavable. Supplied with TEKMA polyurethane cover with zip fastener.

Fire retardant.

• 27642 COVER LIFTER

Can be disassembled.

Chromed steel tubular frame.



• 27696 PILLOW 45x75x10 cm Polyurethane foam, transpirant, pillow, density 21 kg/mc with polyester, fire retardant, cover. Washable at 95°C, autoclavable.





• 44825 BACKREST - blue Painted steel tubular frame. Adjustable in 5 positions.




#### • 27692 DAMA MATTRESS 195x85x14 cm

Expanded polyurethane mattress, density 30 kg/mc, Fire proof and latex free. Antibacterial, hypoallergenic and antifungal. Autoclavable at 135 °C.



#### • 44804 HNF MATTRESS WITH COVER 195x85x14 cm Polyurethane foam mattress, density 35 kg/mc. Non deformable, antibacterial, antifungal and autoclavable at 135°C.

Supplied with TEKMA polyurethane cover with zip fastener.



#### 44803 MATTRESS WITH COVER 195x85x18 cm

Polyurethane foam mattress, density 35 kg/mc. Non deformable, antibacterial, antifungal and autoclavable at 135°C. Supplied with TEKMA polyurethane cover with zip fastener.



 44812 SWEET DREAM • 27681 POLYESTER COVER PILLOW 50x80x18 cm 195x85x14 cm - white Polyester padding and polyester Transpirant polyester fireproof cover for mattresses (27680, cover washable at 40°C. 27682, 27692)

Class 1IM.



 27695 TEKMA POLYURETHANE COVER - 195x85x18 cm - white Soft, fire retardant, transpirant and waterproof cover. Universal (up to h14 cm) with elastic. Washable. Autoclavable at 134°C.

### A4 AND A3 RECORD HOLDERS



- 27647 A4 INOX RECORD HOLDER 37x25x5 cm With transparent plexiglass. Suitable for sheets 34x23 cm.
- 44820 A4 PVC WHITE RECORD HOLDER 24x32 cm
- 44821 A3 PVC WHITE RECORD HOLDER 43x32 cm



- 27601 BED WITH 1 ARTICULATION with wheels
- Painted steel frame with net

1 Pipe frame with net for head movement, 200x85 cm. 2 Heads in chromed pipe complete with MDF bilaminated coated panel. Movement by a crank. Protection of end run. Rubber wheels of Ø 100 mm, with brakes (only for code 27601)

Size: 206x89xh 90 cm. Height of frame from bottom 52/55 cm. Size of frame: 200x85 cm. Weight 32 kg.



BED WITH ADJUSTABLE HEAD AND FOOT SECTION

- 27610 BED WITH 3 ARTICULATIONS
- 27611 BED WITH 3 ARTICULATIONS with wheels

Painted steel frame with net.

- 3 bed frames with nets in painted steel pipe, 200x85 cm. 2 Heads in chromed pipe complete with MDF bilaminated coated panel. Movement by 2 cranks. Protection of end run. Rubber wheels of Ø 100 mm, two of which with brake (only 27611) Size 206x89xh 90 cm. Height of frame from bottom 52/55 cm. Size of frame: 200x85 cm.
- Weight 42 kg. Made in Italy
- 27605 STANDARD BED no castors
- 27606 STANDARD BED Ø 50 mm castors
- Simple bed made of epoxy coated steel. Head and foot ends with plastic feet. Rigid mesh mattress platform.
- 27607 STANDARD PLUS BED no castors
- 27608 STANDARD PLUS BED Ø 100 mm castors Chrome-plated steel bed ends. Laminated plastic panels. Rigid mesh mattress platform. Adjustable back-rest Size: 206x89xh 90 cm. Made in Italy.
- 27841 I.V. STAND 5 wheels trolley

# **BEDSIDE TABLES** - MADE IN ITALY



BEDSIDE TABLES

Epoxy powder coated steel sheet tube

Thermoformed ABS top and drawer. Laminated plastic drawer face and door (27665 and 27666 only) 10 mm thick. Bedside table with door has inner removable shelf and is available in left (L) or right (R) version.

- 27669 BEDSIDE TABLE WITH DRAWER • 27665 BEDSIDE TABLE WITH DRAWER AND LEFT DOOR
- 27666 BEDSIDE TABLE WITH DRAWER AND RIGHT DOOR



**FEBO BEDSIDE TABLES** 

Epoxy powder coated steel sheet 8/10 body. Towel holder and lateral bottle holder (27662 only). Soft rubber antitrauma handle. Sliding drawer with removable ABS tray. Inner removable shelf. 4 revolving castors (2 with brake) • 27674 FEBO BEDSIDE TABLE - blue avio

**RAL 5014** 27675 FEBO BEDSIDE TABLE - other colours\*

Available in 30 days. Minimum order 10 pcs. 27662 FEBO BEDSIDE TABLE WITH **BOTTLE HOLDER - blue avio RAL 5014**  Four revolving castors Ø 60 mm (2 with brake

DOUBLE FACE


with bumpers Ø 100 mm

#### BEDSIDE TABLE WITH DRAWER, DOOR, **BOTTLE - GLASS HOLDER, OVERBED** TABLE

Epoxy powder coated steel sheet body. Thermoformed ABS top with towel holder, lateral bottle and glass holder. Sliding drawer with removable ABS trav. Laminated plastic drawer face and door 10 mm thick. Anti-trauma handles. Revolving, extensible, adjustable height cm 90/110 ABS overbed table top. Removable inner shelf. Plastic grid at bottom.

- 27678 BEDSIDE TABLE DOUBLE FACE
- 27679 BEDSIDE TABLE SINGLE FACE

# PATIENT BEDS WITH 1 OR 3 JOINTS, MANUAL OR ELECTRIC



- 1 joint/2 sections or 3 joints/4 sections

- manual movement by 1 or 2 cranks with retractable handles - legs fitted with 4 revolving directional rubber/steel castors with independent brake or plastic feet.





27658 3 JOINTS BED - 2 cranks - variable height - castors

• 27659 3 JOINTS BED - electric - castors • 27660 3 JOINTS BED - electric - variable height - castors

- 3 joints/4 sections beds adjustable by means of 2 independent cranks (27658) or electric motor 24 V DC and push botton - height adjustable by hydraulic foot pump (27658) or electric

Legs and		atures as	27652						
	TECHNICAL SPECIFICATIONS								
		27652/3	27656/7	27658	27659	27660			
Size of plat		-	9	00x2,000 m	m —	<del></del>			
Platform h		475	475	400/800	475	400/800			
Height of b				- 950 -		<del></del>			
External m	easuremen	t:	9	10x2,060 m	m —				
Packing siz			60x145x2,0			20x2,070⊣			
Movement		1 crank	2 cranks	2 cranks	electric	electric			
Max patier	Max patient load kg: + 135								
GIMA code		ACCESS	ORIES FO	R PATIEN	TS BEDS				
27663 27667 27668 27661	Infusion Lifting p	pole wit	ort - coup h univers slot in sys	al clamp stem	0				

### SPECIALISTIC BED 3-JOINTS/4 SECTIONS, ELECTRICAL, ADJUST. HEIGHT



27672

• 27673 SPECIALISTIC BED with Trendelenburg - 40-80 cm

• 27672 SPECIALISTIC LOW BED with Trendelenburg - 23-63 cm

Three-joints, four sections bed with adjustable height from 40 to 80 cm or 23-63 cm with full electrical movements.

All welded mainframe made of rectangular steel tube 50x25x2 mm. Mattress platform with flexible wooden staves, complete with mattress-hold guides. Backrest-section and leg-section adjustable by means of two independent electric motors 24V D.C. and push-button. Foot-section adjustable by means of a rack device. Fixed pelvis-section. Removable head and foot-end frames made of natural beech finish wood with solid corners and edges.

Comes complete with 2 vertical sliding bars with upper/lower lock/ unlock keys and lifting pole.

Legs fitted with 4 castors Ø 100 mm with independent brake.

TECHNICAL SPECIFICATIONS Size of platform: 900x2,000 mm

Platform height: 400-800 mm (27673) 230-630 mm (27672)

External measurement: 1,030x2,140 mm Height of hed end from mattress platform: 50 mm Max load: 135 kg Operating power: 230 V - 50 Hz

83° 80 80 40.3


• 27676 WOODEN BEDSIDE TABLE - height adjustable, tiltable tray Manufactured by quality laminated wooden panel. Particularly functional: with drawer, 2 doors (can be used from both sides) and

lateral height adjustable (73-100 cm) tiltable tray at 90° (27676) or swing type tray (27677). Size: 50x33xh 85 cm. Lateral trav: 58x33 cm (27676), 72x36 cm (27677).

4 revolving castors (2 lockable). ABS border. • 27677 WOODEN BEDSIDE TABLE - extractable tray

104

### I.V. STANDS



\*Maximum load 2 kg each hook

**SWADDLING TABLE** 

27400

27848

Made in Italy.

# NEONATAL CRADLE

• 43500 NEONATAL CRADLE with trolley • 27400 SWADDLING TABLE - beige Transparent unbreakable plastic cradle Baby changing table with Italiumag tubular frame with 2 shelves. with round edges and ventilation holes. Padded worktop 115x60 cm in soft Epoxy powder painted mainframe made washable fireproof (Class 1 IM) simulated of curved and welded tubular steel. leather and lower shelf 100x40 cm, Shape of trolley allows horizontal and in laminated chipboard panel. Trendelenburg inclinations and bedside Max load: 60 kg positioning. Legs fitted with 4 synthetic Size: 115x63xh 85 cm rubber castors Ø 75 mm, two with brake. Weight: 28 kg Dimensions: 83.5x52.5xh 90 cm. Delivered disassembled. Weight: 15 kg. Max load: 10 kg. Delivered disassembled. Made in Italy.

Stainless steel AISI 304 bottle holder. Capacity 2.5 kg

• 43501 CRADLE - spare

27685 MATTRESS 63x37x5.5 cm - fireproof



### HYPODERMOCLYSIS STAND



• 27856 HYPODERMOCIYSIS STAND Stand with hydraulic height adjustment for hypodermoclysis, for washing and surgical irrigation. Hydraulic pump with pedal for height adjustment and gripping handle for easy transport.

### PEDIATRIC BED

• 27399 PAFDIATRIC BFD 1-4 years 200°C epoxy powder painted mainframe made of steel tube Ø 30 mm, ready to be hooked into the mattress platform. Mesh mattress platform made of oval tube 40x20 mm, fixed to the mainframe with removable bolts. Side rails 62 cm h. sliding on chromed steel guides, with safety device. Legs with 4 castors Ø 80 mm, two with brake. Weight 35 kg. External measurement 140x70xh 130 cm Inner size 130x65xh 63 cm. Made in Italy



•27688 COVER - water proof

### AN INTEGRATED SYSTEM OF TREVIRA® CURTAINS





#### A COMPLETE SEPARATION SYSTEM

A complete system to create separations inside hospital rooms or outpatient wards.

### System includes

- 4 STRUCTURES include rings
- window curtain rails - cabin curtain rail
- trolleys with 1 or 2 curtains - adjustable wall arms 3 SIZES TREVIRA® CURTAINS IN 6 COLOURS - do not include rings Window curtains rails

Available in 2 sizes: 160 cm (45492) need curtains 175xh 145 cm and 210 cm (45493) need curtains 225x145 cm

#### Cabin curtain rails

Size: 80x80 cm, need curtain 225xh 180 cm

### Swing arm curtains - manual or electrical

Swing arm curtain is adjustable horizontally (180°) and can be bent down to 90° (45501 only) when not in use.

Telescopic tubular arm extension: open 210 cm, closed 88 cm (45500 and 45503) or 100 cm (45501).

Rings allow curtains to slide smoothly.

### Trolley curtains - 1 or 2 curtains

Trolley made of stainless steel AISI 304 with 4 revolving castors (2 lockable). It allows the use of 1 curtain 225xh 145 cm (45505) or 2 curtains (45506), 1 long 225xh 145 cm and 1 short 175xh 145 cm. Arm can be bent down to 90° when not in use

and curta	in remains tied up.
GIMA code	STRUCTURE: ARM OR TROLLEY WITHOUT CURTAINS
45492	Window curtain rail 160 cm
45493	Window curtain rail 210 cm
45495	Cabin rail 80x80 cm
45500	Adjustable arm
45501	Adjustable foldable arm
45503	Electric adjustable arm*
45505	Trolley for 1 curtain - foldable
45506	Trolley for 2 curtains - foldable
*Adjustable hi	orizontally (180°) by electrical control

Trevira® curtains Trevira® curtains are flame-proof (Class I), antiallergic, avoid bacterial growth, waterproof and highly resistant to abrasion Thick weft to avoid dust infiltration and improve privacy, washable up to

+45535 45525 + 45535

45492

60°C. Available in 6 colours to match any need.

Custom-made curtains are available on request. Made in Italy. TREVIRA CURTAINS

45505

+ 45525

+ 45535

	IIIL VIIIA C	CINIAIIVO				
FOR WALL ARN AND CABIN		FOR TROLLEYS AND WINDOWS				
225xh 180 cn	Long trolley arm/rail: n 225xh145 cm	arm/rail:	COLOUR			
45510	45520	45530	Light blue			
45511	45521	45531	Blue			
45512			White Beige			
45513	-					
45514	-	-	Green			
45515	45525	45535	Peach			
Light blue	Blue White	Beige Gree	en Peach			
	SET OF 18 RIN	NGS - SPARE	(1)			
45508 45509	Open rings for wind Closed rings for wa	low rails and cabin Il arms and trolleys				
	_		45508 45509			

OTHER WING SCREENS see page 137



### PROFESSIONAL WARD STRETCHER



GIMA WARD STRETCHER ACCESSORIES - not included Side rails (couple) with automatic locking device 44761 44762 I.V. Stand with two hooks Basket - chrome plated steel

Oxygen bottle holder\* - chrome plated steel Fireproof simulated leather mattress - class I - 182x64x4 cm

\* for oxygen hottle up to 41 cm Ø 15 5 cm

#### • 44760 WARD STRETCHER

Main features:

- Platform: all-welded mainframe made of semi-oval steel tube 50x25x2 mm.

- Push/Pull handle: Made in steel tube Ø 30x1.5 mm.

- Surface finish: Epoxy gloss finish standard grey 7040

- Mattress platform section: Two section mattress platform fitted with removable chrome-plated grids made of 5 mm. Ø steel rods and square mesh 50x50 mm.
- Backrest: Square cross section 25x25x1.5 mm, adjustable by means of a rack device (5 positions).
- Castors Four castors Ø 200 mm made of grey synthetic rubber two of which with independent brake.

- Bumpers: Four bumpers at the (not included) corners made of anti-acid and anti-shock grey resin.

Supplied disassembled. External size: 202x71xh 90 cm Wired net height: 78 cm Load: 135 kg.

Manual: GB, FR, IT, ES, PT. Made in Italy.



### PROFESSIONAL PATIENT TROLLEY - ADJUSTABLE HEAD SECTION

• 27804 PROFESSIONAL PATIENT TROLLEY with adjustable head

section, side rails and oxygen cylinder holder

• 27805 PROFESSIONAL PATIENT TROLLEY - RADIOTRANSPARENT FRAMI with adjustable head section, side rails and oxygen cylinder holder Innovative, stylish comfortable trolley easy to use.

Trolley made in sturdy tubular frame for optimal stability. Supplied with 4 wheels Ø 200 mm

(2 with brake), bumpers, push handle. Detachable frame with adjustable head section (27804) or fixed frame, 12 mm thickness, with adjustable head section (27805).

Size: 196x76xh 75 cm. Net size: 193x68 cm Maximum load: 200 kg.

Weight: 70 kg. Made in Italy.

• 27807 MATTRESS - 186x68xh 8 cm - black Simulated leather.

Fire retardant. Class I IM.

• 27808 IV STAND with 2 plastic hooks.





### ADJUSTABLE HEIGHT PATIENT TROLLEY WITH TR AND RTR

• 27806 PATIENT TROLLEY - with adjustable height, TR and RTR Stilish sturdy and comfortable trolley with innovative design allowing operators to easily treat patients.


Adjustable in height by means of hydraulic pump with pedal placed on both sides. The lateral sides are very comfortable, easy and fast to fold. The upper wire mesh is removable to guarantee a better hygiene. Equipped with push handles, 4 bumpers at he corners and a universal hold-cylinder. Reclinable cushion thanks to two racks that can be easily actuated by the grip handle. Wheels: 200 cm diam. with total and simultaneous central brake; one of 4 wheels is equipped with directional brake; their activation is made by means of 4 lateral pedals. The joints of the structure rotate on self-lubricating sintered threaded inserts.

The trolley can reach the Trendelemburg and anti-Trendelemburg position very quickly thanks to a handle placed on the upper lateral side: it activates a gas spring (600N) that offers millimetric adjustability.

The entire structure made in rectangular and round tubular is epoxy painted in grey and white colour. Size: 201x76xh 52/87 cm (without mattress).

Load: 130 kg. Weight: 90 kg • 27807 MATTRESS - 186x68xh 8 cm - black Simulated leather, fire retardant, Class 1M

• 27808 IV STAND



### PROFESSIONAL PATIENT TROLLEYS WITH ADJUSTABLE BACKREST

• 27827 PROFESSIONAL PATIENT TROLLEY - with adjustable backrest and side rails Trolley made of anodized aluminium with steel

perimetral frame with rigid PVC profile. Coated with epoxy powder RAL 1013 ivory. Rigid mattress platform made of powder coated steel welded mesh.

Main frame, side rails and shove handle bar made of anodized aluminium.

Nylon components with handle shape. Swivelling castors Ø 200 mm, 2 of which with brake. Delivered in kit from. Made in Italy.

- 27830 IV STAND fixed height 100 cm 2 plastic hooks
- 27831 STEEL BASKET 56x38xh 9 cm
- 27832 OXYGEN BOTTLE HOLDER Ø 18x37 cm
- 27834 FIRE RETARDANT MATTRESS 7 cm black -185x58xh 7 cm




### ADJUSTABLE HEIGHT PATIENT TROLLEY WITH TR AND RTR

• 27828 ADJUSTABLE HEIGHT PATIENT TROLLEY with Trendelenburg (TR), Reverse Trendelenburg (RTR) and side rails. Platform composed by two epoxy powder coated steel RAL 1013 ivory welded mesh sections, detachable for cleaning, fitted on nylon supports and placed on steel crossbar covered with rigid PVC profile. Raising and lowering by gas spring with lever set on the same section. Trolley structure with a rounded section profile coated with epoxy powder RAL 1013 ivory. Adjustable height by oleodinamic pump from 50 cm to 80 cm with foot control lever. TR-RTR position controlled by handle at the foot of the trolley. Mechanical braking, Inclination and platform check by a level bubble. TR 14° RTR 11°. Swivelling castors Ø 200 mm, one of which directional. Simultaneous braking with foot control lever with 3 positions: total brake, swivelling total, swivelling and directional. Made in Italy,

- 27830 IV STAND fixed height 100 cm 2 plastic hooks 27833 OXYGEN CYLINDER HOLDER (max. 7 l) and WIRE BASKET - multifunction
- 27835 FIRE RETARDANT MATTRESS 10 cm 2 sections -185x58xh 10 cm



### TRENDELENBURG PATIENT TROLLEY - STRETCHER



• 27850 TRENDELENBURG TROLLEY

Made of steel-alloy, oven painted ral 9010, with chrome plated handles.

Adjustable height from 50 to 70 cm, with oleodinamic pump. Trendelenburg up to 9°.

Anti-Trendelenburg up to 14° (with gas pump).

Plastic bumpers at four corners. Maximum load: 120 kg. 4 wheels of Ø 200 mm (2 with brake).

Size: 65x184 (internal) x h 50-70 cm, 72x191 cm (external).

GIMA code	ACCESSORIES
27810 27853 27854 27855	Side rails (couple) 100xh 28 cm I. V. Stands Oxygen bottle holder Mattress - black sky 3 cm thick in flame retardant material - 184x64x3 cm

# HEIGHT ADJUST. ELECTRIC BED



#### • 44800 HEIGHT ADJUSTABLE ELECTRIC BED

3 joint, 4 section Hospital bed, with electronic adjustment of height and platform, Trendelenburg and Reverse Trendelenburg positions (15°). All steel components are epoxycoated with anti-microbial additive. Back section regulation using electric actuators with anti-crushing and rototranslation function to avoid abdominal crushing. Both bed sides have CPR manual levers for emergency manoeuvres.

Foot rest adjustment by click mechanisms allowing 6 positions. Internal side rails controls for patient use and caregiver. Remote control to maintain position or disable by magnetic

The keypad allows adjustment of backrest, bed surface height, legs and foot rest, comfort position, Trendel and reverse Trendel.

- 44801 LIFTING POLE
- 44802 IV POLE
- 44803 FLAME RETARDANT MATTRESS with waterproof cover Load 280 kg. Density 35 kg/m<sup>2</sup>. Size 85x195x18 cm.

#### **TECHNICAL SPECIFICATIONS**

Minimum/maximum height surface: 380-780 mm

Maximum backrest regulation: 70°

Maximum leg/foot height regulation: 30°

Trendelenburg/reverse trendelenburg: 15°

Minimum/maximum height: 835-1235 mm

Maximum total width/length: 1010/2260 mm (bumpers and siderails included)

Worksurface width/length dimension 880/2000 mm

Power supply: 160-230 V - 50-60 Hz

Dynamic lift capacity: 230 kg SWL: 270 kg

IEC protection class: I / B

IP code (protection rating): IP66

Made in Italy

### BARIATRIC ELECTRIC BED Sections, heigh



- Four section electrically driven bed frame in durable steel construction with adjustable height and TR-RTR. Made in Italy.
- Trendelenburg 18° and Reverse Trendelenburg 18°
- mattress platform positioning: backrest 0°-52°, legrest 0°-24°
- manual handset with locking key+supervisior to adjust sections
- electric CPR function - armchair position with excellent comfort
- carer controlled lock out function for all controls
- battery backup - central braking system with a three position pedal on foot
- side for greater control: steering / swivelling / braking
- 3X standard twin castors Ø 15 cm and 1 antistatic and
- steering twin castor - 4 multi position and removable siderails, colour co-ordinated
- to hed frame
- 27638 LIFTING POLE with integrated IV hooks 27639 RETRACTABLE BLANKET TRAY
- 27640 IV POLF
- 44810 FLAME RETARDANT BARIATRIC MATTRESS 4 pieces with waterproof transpirant cover. Load 300 kg. Density 40 kg/m<sup>2</sup>. Size 90x200x18 cm (2 sides 15x200x18, 1 foot 15x120x18)





#### TECHNICAL SPECIFICATIONS - fully retracted - 226x105 cm (bumpers included)

Electrical shock protection:

Bed weight

- fully extended - 242x135 cm (siderails included)

Mattress platform adjustments: - fully retracted - 200x90 cm

- intermediate position - 200x105 cm

fully extended - 200x120 cm

foot extension - from 200 to 220 cm 41-81 cm Lowest-Highest position

175 kg

Load capacity: 400 kg

Class 1 Liquid ingress protection: IP 66



#### STAINLESS STEEL, RADIOSURGICAL OPERATING TABLES

Designed to satisfy surgical functionality, practicality, quickness and easy maintenance. They allow, with proper accessories, to satisfy every basic surgical activity

#### - Table top

Divided in 5 sections (head, back, pelvis, 2 indipendent leg sections) with stainless steel structure and plexiglass to allow x-ray permeability and easy cleaning.

Table top is pre-arranged for the insertion of x-rays holders all over its length. Accessories holder (25x10 mm) in stainless steel, covers table top length on both sides.

#### - Telescopic column

Square and of limited size, covered by anodized aluminium (27560) or stainless steel (27562/4/5/6)), it allows up and down movement (approx. 70-100 cm) by a foot pedal placed at the base through a closed oleodynamic circuit with oil-tight pump avoiding any oil leakage (27560/2/4) or by remote control (27565/6)

#### - Mattresses

They cover all the table top lenght, made in a long lasting material, sterilizable in autoclave, x-ray translucent and elastics. They are independently removable.

For Solaris, it is moveable by four large antistatic castors, 2

directional and 2 pivoting with brake. For Gima and Gima TR						
GIMA code	OPERATING TABLES					
27560	Solaris operating table - mechanical					
27562	Gima operating table - mechanical					
27564	Gima TR operating table with longitudinal					
	translation of table top - 100% radiotransparency					
27565	Gima operating table - semiautomatic - need 27559					
27566	Gima TR operating table - semiautomatic					
	with longitudinal translation of table top - 100%					
	radiotransparency - need 27559					
ACCESSO	ORIES FOR ALL OPERATING TABLES - 100% stainless steel					
27568	Wristlet with clamp - couple					
27569	Rectangular s/s gynaecological basin - 200x320x150 mm					
27570	Two-hook adjustable IV stand (needs clamp 27571)					
27571	Clamp for IV stand					
27572	Arm holder adjustable 90-180° with cushion and clamp					
27573	Drape support with adjustable height with 2 clamps 27576					
27576	Clamp for drape support - spare					
27574	Leg holder with radio transparent valve and					
	cushion - couple (needs 2 clamps 27575)					
27575	Clamp for leg holder					
	SSORIES FOR SEMIAUTOMATIC TABLES (27565-6)					
27558	Infrared control					
27559	Battery charger					

(mechanical and semi-automatic) base is completely made of stainless steel to ensure perfect stability. It is provided with a locking system to the floor through a foot bar. Transport is allowed by 3 antistatic wheels, one pivoting and 2 directional.

27560

#### - Movements

For Solaris: Trendelenburg and Reverse/Trendelenburg with lateral tilt right-left 20° by crank. For Gima and Gima TR same table movements as above, work through a mechanical system moved by two cranks, positioned at the side, easily retractable, for semiautomatic by remote control.

#### - Longitudinal translation

27566

Both Gima TR models offer manual longitudinal translation of table top of about 300 mm to allow total elimination of column encumbrance for 100% transparency of top.

- Full range of accessories. All tables come with mattress included semiautomatic also includes control (with 1 m cable) batteries and crank for emergency of engine.



	2/300	2/302-2/304	2/303-2/30
Table top size	200x48 cm	200x48 cm	200x48 cm
Height	70-100 cm	75-105 cm	75-105 cm
Lifting system	Mechanical	Mechanical	Electric
- Trendelenburg	30°	35°	35°
- Reverse Trendelenburg	30°	25°	25°
- Lateral tilt right-left	20°	25°	25°
Table top composition			
- Head section	extractabl	e and inclinable (+2	5° -90°)
<ul> <li>Back section inclination</li> </ul>	-40° +80°	-20° +80°	-20° +80°
	by gas spring	by gas spring	mechanical
		size 48x51 cm	
- Pelvis section size		size 48x49 cm	
- Leg section	divided in	two independent s	sections
	with follo	wing manual move	ements
• 0	pening right/left	of 0°/90°	
• ir	nclination +30° -9	90°	
	oth parts are eas	sily independently e	extractable
Table weight:	90 kg	160 kg	160 kg
Operating table capacity:	200 kg	250 kg	250 kg
Made in Italy			

27562-27564

# ISO SERVICE TROLLEYS - MADE IN ITALY 65x47xh 100 cm



• 27935 ISO SERVICE TROLLEY - empty

Service trolley for "ISO" travs or baskets (not included) made in epoxy powder painted steel. Supplied 27935 with 5 height adjustable 1x27924 runners for 3x27938 ISO 1x27939

trays/baskets. Both side basket pulling out with

### • 27934 AURION MINI 600 - ISO trolley

Basic body made in Baydur Polyurethane -Bayer AG: it can be washed and disinfected. It does not react with diluted acids, alkali and solvents. Self-extinguishing according to class UL VO - Latex Free. For safety, handles are moulded into the body on both sides, trolley top has a 4-sided moulded containing rim to avoid any spilling/falling of materials. No sharp edges. All around bumper. Lightweight and easy to move.

27924 Handle fe transpor 27938 Equipped with key lock and doors kit 27938 made in transnarent polycarbonate Side plastic runners for "ISO" trays or baskets 27936 (baskets and trav not included

 27936 ISO TRANSPORT TROLLEY - empty Transport trolley

Antistatic castors for ISO trays and Ø 125 mm (2 with brake) baskets (not included). Made in stainless steel AISI 304 sheet, scotch brite finishing. Anti-dust gasket. Internal side with plastic runners for ISO

trays or baskets. Supplied with handle for transport.

### ISO FORMAT UNIVERSAL MODULAR TRAY SYSTEM

IS	O MODULA	R TRAYS	Intelligent solutions for storing all kind	11111	2799
	GREY A	BS	of drugs, bandages, accessories and small	·	-
Closed	Open	SIZE mm	components in a space saving and clear	2799	5
27924	-	600x400x50	manner.	GIMA	DIVIDERS
27925	27938	600x400x100		code	
27928	27939	600x400x200	THE REAL PROPERTY OF THE PARTY		400x50 mm
	TRANSPARE	NT PC	27020		600x50 mm 400x100 mm
Closed	Open	SIZE mm	27938		600x100 mm
27957	-	600x400x50			400x200 mm
27958	27965	600x400x100			600x200 mm
-	27966	600x400x200	27925 27965		Drawer stropper
			2,323		

### INOX WORKING TABLE OPERATING THEATRE INSTRUMENT TABLES



 27909 INOX WORKING TABLE Working table, equipped with two drawers (47x30x12 cm) each side, to work on both sides. Stainless steel AISI 304 frame, structure made of square tubular, table top and lower shelf made of smooth stainless steel. Mounted on 4 castors Ø 100 mm, two with brakes. Weight 50 kg. Size 120x70xh 95 cm. Max load (x shelf): 40 kg Delivered in kit form 122x35x72 cm

Safety protecti on 3 sides 27913

• 27913 INSTRUMENT TABLE 2 SHELVES Operating room instruments table made of stainless steel AISI 304 scotch brite finish.

125 mm Ø revolving castors (2 with brake) Weight: 28 kg. Load for shelf: 40 kg. Size: 120x65xh 95 cm. Delivered in kit form (123x13x68 cm). Made in Italy.



 27914 INSTRUMENT TABLE 1 SHELF Operating room instruments table made of stainless steel AISI 304, scotch brite finish. 125 mm Ø revolving castors (2 with brake). Weight: 21 kg. Load: 40 kg. Size: 120x65xh 95 cm. Delivered in kit form (123x13x68 cm). Made in Italy.

Made in Italy.

### OPERATING ROOM INOX CABINETS PAINTED STEEL CAB



• 27917 INOX CABINET Made of AISI 304 stainless steel. Two lockable doors (10/10 thickness). 4 adjustable shelves (8/10 stainless), 4 adjustable feet, with stainless steel cover. Size: 100x48xh 190 cm. Weight: 130 kg.

Made in Italy.



• 27918 GLASS-INOX CABINET Made of AISI 304 stainless steel with two lockable doors in temperated glass 5 mm thick, 4 shelves in temperated glass 6 mm thick and 4 adjustable feet. Size: 100x48xh 190 cm. Weight: 105 kg. Made in Italy.



• 27916 PAINTED STEEL CABINET Epossidic powder painted steel cabinet with 4 adjustable shelves, lockable doors, 4 adjustable feet. Size: 100x50xh 200 cm. Made in Italy.

### STAINLESS STEEL, INSTRUMENT AND DRESSING TROLLEYS



• 27430 INOX TROLLEY AISI 304 Stainless steel trolley with plastic Size: 60x40xh 81 cm - weight 8 kg drawer internally divided in 4 sectors. 2 shelves with upstands (3,5 cm) on four sides. Revolving rubber castors Ø 80 mm (two with brake). Size: 70x50xh 82 cm.

Max load (x shelf): 25 kg. Delivered in kit form. Made in Italy.



• 27433 MEDICAZIONE TROLLEY - small • 27434 MEDICAZIONE TROLLEY - medium handle. Size: 70x50xh 82 cm - weight 9 kg

• 27435 MEDICAZIONE TROLLEY - large Size: 90x60xh 85 cm - weight 15 kg AISI 304 stainless steel trolleys, with push handle, 2 shelves with upstands (3,5 cm) on four sides, 4 revolving rubber castors Ø 60/80/90 mm. Max load (x shelf): 25 kg.



• 27431 TER TROLLEY AISI 304 Stainless steel trolley, with push

3 shelves with upstands (3,5 cm) on four sides, 4 revolving rubber castors Ø 80 mm. Size: 70x50xh 82 cm - weight 13 kg Max load (x shelf): 25 kg Delivered in kit form. Made in Italy.

27436

• 27436 DRESSING TROLLEY Dressing trolley made of AISI 304 stainless steel with 2 shelves (70x50 cm), 1 drawer (40x50xh 15 cm), basin holder and basin. 4 revolving castors Ø 100 mm. Size: 70x50xh 85 cm - weight: 18 kg. Max load (x shelf): 25 kg. Delivered in kit form. Made in Italy.

45800

 45800 MEDICAZIONE PLUS TROLLEY With removable trays Stainless steel frame mounted on castors

Ø 80 mm. Size: 61x43xh 78 cm. Weight: 10 kg. Maximum load (x shelf): 10 kg. Delivered in kit form. Made in Italy.



With removable trays Stainless steel frame, mounted on castors

Ø 80 mm Size: 49x30xh 78 cm. Weight: 9 kg. Maximum load (x shelf): 10 kg. Delivered in kit form. Made in Italy.

# LANCART: STAINLESS STEEL TROLLEY TO BUILD UP

• 45810 LANCART TROLLEY - small Size: 60x40xh 80 cm • 45811 LANCART TROLLEY - medium

Size: 70x50xh 80 cm Stainless steel trolley mounted on castors Ø 80 mm. Maximum trolley load: 60 kg.

Delivered in kit form. Made in Italy. You can add following accessories: • 45815 SET OF SIDERAILS (for 1 shelf)

• 45816 SET OF SIDERAILS (for 1 shelf)

for 45811 45817 BOTTLE RACK

45818 WASTE BIN

113

60x40xh 80 cm 45810



• 27908 SHELVING SYSTEM Shelving system, made of AISI 304 stainless steel, scotch brite finish. With 5 stainless steel reinforced shelves

at fixed position. Possibility to fix together several shelving systems. Size: 100x50xh 200 cm Load x shelf: 25 kg Weight: 30kg Made in Italy.

# SHELVING SYSTEM INSTRUMENT TROLLEY ANAESTHETIC TROLLEY



• 27442 INSTRUMENT TROLLEY Made of satined welded AISI 304 stainless steel. With 4 sliding drawers (internal, 49x33xh 18 cm) Top drawer lockable, upper shelf with safety edges to carry instruments. 4 revolving castors Ø 80 mm Size: 60x40xh 110 cm Weight: 37 kg Made in Italy.

27442



 27437 ANAESTHETICS TROLLEY Made of satined AISI 304 stainless steel, with 6 drawers (internal 26x37xh 7 cm), a lockable vertical compartment and an open space. Top with 3.5 cm upstand. 4 revolving castors Ø 80 mm Size: 60x40xh 110 cm

Weight: 39 kg

Made in Italy.

### ANODIZED ALLOY OR ALUMINIUM TROLLEYS REX TROLLEY



62x42 cm

Size: 65x45xh 80 cm

stainless steel shelves.

Delivered in kit form.

Made in Italy.

- 27429 GIMA 2 TROLLEY
- small: 60x40xh 77 cm weight 11 kg
- 27425 GIMA 2 TROLLEY

- medium 70x50xh 78 cm - weight 14 kg Practical trolleys with aluminium body and handles. With 2 white bilaminated shelves 18 mm thick, black PVC bordered, with guard-rail. Two large lateral handles 4 revolving rubber castors Ø 80 mm. facilitate transport or lift up of the trolley. Max load (x shelf): 15 kg. 4 revolving nylon castors Ø 80 mm. Max load (x shelf): 40 kg.

• 27426 GIMA 3 TROLLEY

- medium 70x50xh 78 - weight 15 kg. Same as GIMA2, but without guard rail. Delivered in kit form. Made in Italy.



• 27439 REX TROLLEY

Supplied with 3 shelves, waste bin, drawer, support for bottles, quard rails on the two bottom shelves, 4 wheels, Ø 100 mm (2 with brakes).

Delivered in kit form (75x52x112 mm). Drawer 64x43xh 9.5 cm. Made in Italy.

Complete stainless steel dressing trolley. Size: 79x50xh 120 cm (handle included).



### **BOWL STANDS**

• 27456 SINGLE BOWL STAND

• 27457 DOUBLE BOWL STAND Chrome plated steel stand with stainless steel base and 5 plastic wheels, one with brake. Adjustable height from 60 to 95 cm Stainless steel bowl Ø 32 cm, 4 l capacity included. Available with one or two bowls. Delivered in kit form.

• 27459 S/S BOWL Ø 32 cm - spare

# **MAYO TABLES**



• 27453 MAYO TABLE - 5 spokes S/s tray, 5 spokes with castors, Ø 50 mm

and adjustable height.

Delivered in kit form. Made in Italy. 27453 27454 S/S tray size: 68x46 cm 68x46 cm Adjustable height: 70-110 cm 70-110 cm

• 27455 MAYO TABLE - s/s base and pump With removable s/s tray, s/s AISI 304 base with 4 castors (50 mm) and adjustable I Italy. height. Delivered in kit form. Made in Italy.
TECHNICAL SPECIFICATIONS

• 27454 MAYO TABLE - s/s base

27454

• 27461 DELUXE TROLLEY with drawer

Top quality trolleys made of lightweight

anodized special alloy, with detachable

27455 45830-45832 70x45xh 1.8 cm 70x45xh 1.7 cm 85-120 cm 90-115 cm 12 kg 20 kg Weight: 8 kg 19 kg 10 kg Load: 20 ka 25 ka 10 ka

27455



• 45830 MAYO TABLE - U-SHAPE

• 45832 MAYO TABLE - 5 spokes Stainless steel base with castors Ø 50 mm: 5 spokes (45832) or U-shape (45830). Stainless steel frame and removable tray Adjustable height.

Delivered in kit form. Made in Italy.

### **BAG HOLDER TROLLEYS**



• 45905 BAG HOLDER TROLLEY - 2 bags • 45906 BAG HOLDER TROLLEY - 3 bags Bag holder trolleys with pedal operated opening. Rigid, sturdy,

self-supporting ABS plastic base with edges. The bag holding ring (35x25.5 cm) is made of glass reinforced nylon with a rubber gasket to hold the bag in place. Two vertical tubes made of AISI 304 stainless steel are

Made in Italy.

pedal operated brake).

• 45910 PUSH HANDLE

• 27466 WRAPPING BAG - vellow strip • 27462 WRAPPING BAG - blue strip • 45908 WRAPPING BAG - green strip White synthetic bag with strip, washable

holding ring. Non marking grey rubber

swivelling wheels Ø 80 mm (two with

up to 200 times. Size 57xh 103 cm. Made in Italy. 45905+27462+27466+45910

• 45900 SHUT BAG HOLDER - 70 I Trolley suitable for carrying one 70 l bag

(not included). Stainless steel AISI 304 structure. Equipped with swivelling castors with brake and

For use with standard 70 l plastic bag. Can use also wrapping bag (27462, 27466, 45908) Made in Italy.



SHUT BAG HOLDER

### AUNDRY TROLLEYS



27465 + 27462 27464 LAUNDRY TROLLEY - painted steel

• 27465 LAUNDRY TROLLEY - stainless steel These trolleys allow to collect dirty laundry while distributing clean linen at the patient bedside. Stainless steel or painted steel frame. Equipped with 4 Ø 125 mm castors (2 with brake) and 4 rubber bumpers at corners.

Size: 135x65xh 102 cm. Made in Italy.

• 27463 SIDE PANEL - painted steel 27466 WRAPPING BAG - vellow strip

• 27462 WRAPPING BAG - blue strip washable up to 200 times, 57xh 103 cm





• 45915 LAUNDRY TROLLEY - laminated Closed trolley with doors, 3 shelves plus top and 2 bag holders.

Laminated particle board body and stainless steel AISI 304 structure. Equipped with swivelling castors, 2 with brake and bumpers.

Size: 110x66x132 cm. Made in Italy. • 27462 WRAPPING BAG - blue strip

• 27466 WRAPPING BAG - vellow strip White washable laundry synthetic bag with yellow or blue strip.

Size: 57xh 103 cm Made in Italy.



### **SOILED LINEN**



• 27467 SOILED LINEN TROLLEY

• 27468 DOUBLE SOILED LINEN TROLLEY Chrome plated frame with 3 or 4 castors Ø 80 mm. Removable bag. Size: Ø 46xh 90 cm. Delivered in kit form



Wheel load:

SMART CART - grey/white RAL 7035

4 castors Ø 80 mm (2 with brake).

Carts with 3, 4 or 5 wide, sturdy shelves

27874

code

27895

27896

27897

dynamic charge: 70 kg

SMART CARTS

Cart h80 cm 3 shelves 40x36 cm

Cart h90 cm 4 shelves 40x36 cm

Cart h115 cm 5 shelves 40x36 cm

paint sheets

### MULTIFUNCTIONAL CARTS - MADE IN ITALY SMART CARTS



SUPER EASY CART: A new stylish and quality cart you can build according to your needs
TECHNICAL SPECIFICATIONS

Dimensions: 47x42x79 cm Shelf: 32x26 cm or 40x36 cm Load capacity: total load 120 kg shelf 10 kg

4 castors Ø 80 mm(2 with brake) Material: - extrusions in aluminium

plastic parts in ABS

#### 27874 27873 GIMA SUPER EASY CARTS - WITH HANDLE

27870 Cart with 1 shelf (32x26 cm) Cart with shelf (40x36 cm), monitor support Cart with large shelf (40x36 cm) **ACCESSORIES for all SUPER EASY CARTS** 

Extra shelf 32x26 cm 27873 Basket 27874

27875

27888

27870

27873

27870

27872

Infusion stand Extra shelf 40x36 cm 27874 Infusion stand Cardio arm for ECG Cardio arm for ECG

27869

### DOUBLE FACE PHARMACY TROLLEY - MADE IN ITALY



• 27499 DOUBLE FACE PHARMACY TROLLEY - 3 large, 30 small drawers Two trolleys in one: 3 large drawers on

one side, 30 (6+9+15) monodose cassettes on other side; with locking system.

Size of cassettes: - 6 cassettes 115x290xh 75 mm

- 9 cassettes

115x290xh 45 mm - 15 cassettes 70x290xh 45 mm Size of trolley: 920x590xh 810 mm Provided with 4 revolving castors Ø 125 mm (3 with

brake, 1 of trolley,

antistatic).





• 45730 DOUBLE FACE PHARMACY TROLLEY - 3 large, 22 small drawers Two trolleys in one: 3 large drawers on one side, 22 (6+6+10) monodose cassettes

Size of cassettes: - 6 cassettes

115x290xh 75 mm - 10 cassettes

115x290xh 45 mm Size of trolley: 920x590xh 810 mm Provided with 4 revolving castors Ø 125 mm (3 with brake, 1 of trolley, antistatic)





• 45731 DOUBLE FACE PHARMACY TROLLEY - 62 small drawers

Two trolleys in one: 31 (6+10+15) monodose cassettes on both sides: with locking system.

Size of cassettes: - 6 cassettes

115x290xh 75 mm

- 10 cassettes

115x290xh 45 mm

- 15 cassettes

antistatic)

70x290xh 45 mm Size of trolley: 920x590xh 810 mm Provided with 4 revolving castors Ø 125 mm (3 with brake, 1 of trolley,



### TRIS TROLLEY



#### • 27438 TRIS TROLLEY

A practical trolley for ECG. Electrosurgical unit or any other device, with 4 nylon castors and 2 lateral handles for easy moving. Revolving castors Ø 50 mm. Size: 49x37xh 77 cm. Shelf size: 40x30 cm. Colour: RAL 9002 Delivered in kit form. Made in Italy.

### **EASY CARTS - MADE IN ITALY**



#### **EASY CART**

A complete line of stylish and sturdy carts with 3, 4 or 5 shelves and with power.
TECHNICAL SPECIFICATIONS

Dimensions (WxDxH): 50x45x79/88/112 cm total load 140 kg Load capacity: shelf 25 kg

4 castors Ø 80 mm (2 with brake) Material vertical aluminium extrusions - plastic parts in ABS steel sheet epoxy powder coated

### **EASY CARTS** 27880 Cart h79 cm 3 shelves 40x36 cm Cart h88 cm 4 shelves 40x36 cm 27882 Cart h112 cm 5 shelves 40x36 cm Cart power h79 cm 3 shelves 40x36 **ACCESSORIES EASY CARTS** Basket 30x16xh 14.5 cm

Infusion stand 27884 Extra shelf 40x36 cm

27888 | Cardio arm for ECG 116

# DOCTOR TROLLEY EXCEL TROLLEY PROFESSIONAL KARTS



• 27446 DOCTOR TROLLEY

Useful trolley made of plastic material (ABS) provided with 9 drawers of different sizes.

Height of drawers: two 8.5, five 5.5, two 2.7 cm. Size: 38x30xh 72 cm. Made in Europe.

117



• 27440 EXCEL TROLLEY -

3 shelves (60x45cm) Size: 67x69xh 80 cm.

• 27441 EXCEL TROLLEY -

4 shelves (60x45cm) Size: 67x69xh 110 cm Maximum load: 80kg

Delivered in kit form. Made in Italy

supplied with cable pipe inside lateral columns 27887 27873

• 27885 PRO CART 2 shelves - h 80 cm • 27887 PRO CART 2 + keyboard, moni-

tor support

27883 BASKET

• 27884 INFUSION STAND **TECHNICAL SPECIFICATIONS** 

Load capacity: - total load 240kg Base: 60.8x50 cm 2 shelves 50x50 cm + base Shelves: vertical extrusions in aluminium

plastic parts in ABS

Made in Italy

### DRUGS & MEDICINE TROLLEYS - MADE IN ITALY




- 27494 PHARMACY TROLLEY small with 15 3-compartment partition
- 27495 PHARMACY-TROLLEY standard
- with 20 3-compartment partition • 27497 PHARMACY TROLLEY - large

with 30 3-compartment partition

A portable pharmacy, allowing to manage daily or weekly treatment of patients, with 15/20/30 3 compartments small drawers for easy drug storage (45-60-90 spaces). Painted steel frame, technopolimer surface and panels. Can be completely closed by safety key lock. Provided with 4 revolving castors Ø 125 (2 with brake);

• 27498 PARTITION -

3 compartments - spare



### DRUGS & MEDICINE CABINETS - MADE IN ITALY






- 2 external lockable doors turning through 180° with 8 medicine compartments each (extendable to 10 compartments)
- perimetrical anti-dust gaskets
- inside 2 containers with 8 medicine compartments each side (extendable to 10 compartments) turning through 90°
- dangerous drugs compartment

	provided with lock											
GIMA code						Material					Colour	
			melamine particle board				white					
27944	Medicine cabinet					bi-laminated board				white any colour*		
27945	Medicine cabinet				bi-laminated board							
27946	Com	partr	nent	for i	m	edici	ne					
Colours:	412	431	441	452	2	482	484	499	854	861	1818	







- made in bilaminated board 20 mm thick - epoxy powder painted steel base frame with 4 adjustable feet Ø 50 mm Right side

- 1 external lockable door turning through 180° with 8 medicine compartments each (extendable to 10 compartments)

- perimetrical anti-dust gaskets
- inside 1 container with 8 medicine compartments each side (extendable to 10 compartments) turning through 90° provided with lock Left side
- glass door, internal side with runners for ISO trays
- 3 drawers on the bottom Supplied with 6 ISO trays different heights (2xh 5 cm, 3xh 10 cm and 1xh 20 cm) and 1 shelf
- 27946 COMPARTMENT FOR MEDICINE - spare

118

### MULTI-FUNCTIONAL TROLLEYS: BASIC AND DRESSING

#### MULTIFUNCTIONAL TROLLEYS: BASIC - DRESSING

These multifunctional professional trolleys have painted steel structure and external plastic finishing. Basic and Dressing are available in 3 different sizes (small, standard, medium). Provided with 4, 8 or 9 drawers, one lateral basket and one extra lateral table. Four swivelling rubber castors Ø 125 mm (2 with brake). 45701

DRESSING







27481 Standard



Small

**BASIC TROLLEY - 3 sizes** Standard version without accessories

- **DIVIDER KIT size: 20/35/50x43xh 7 cm** • 27470 KIT for drawer 30 cm - 8 comparts
- 27471 KIT for drawer 45 cm 20 comparts
- 27472 KIT for drawer 60 cm 25 comparts

**DRESSING TROLLEY - 3 sizes** 

Same as Basic, but equipped with instrument trav and upper dispenser (10 tilting bins).

BASIC		DRESSING		Size Size of trolley (cm)		Number of	Size of drawers cm					
Yellow	Blue	Yellow	Blue	Type	(without accessories)	drawers	45x48xh13	45x48xh27	60x48xh13	60x48xh27	30x48xh13	30x48xh27
27477	45700	27478	45701	Small	67x64xh 100	4	3	1	-	-	-	-
27480	45702	27481	45703	Standard	82x64xh 100	4	-	-	3	1	-	-
27476	45704	-	-	Standard	82x64xh 100	9	-	-	-	-	8	1
27483	-	27484	-	Medium	102x64xh 100	8	3	1	-	-	3	1
27486	-	-	-	Large	115x64xh 100	8	-	-	3	1	3	1

### RECORD HOLDERS AND X-RAY FILM HOLDERS TROLLEYS



• 27492 RECORD HOLDERS TROLLEY - 2 large drawers

Record trolleys are designed to hold clinical reports in A3/A4 format or specific format. Frame in epoxy painted steel, working surface and panels in technopolimer plastic. Equipped with 4 Ø 125 mm swivelling rubber castors (2 with brake). Bumpers around the perimeter. Made in Italy. Size: 820x640xh 1.000 mm (code 27491 and 27490) 820x640xh 1,150 mm (code 27492).

• 27493 FILE RACK A3 special

This trolley has 32 extractable compartments, a wide top surface, 4 side document holders, and a sliding out writing surface. Frame is in painted steel with sliding-in bilaminated doors with a 270° opening. Base and lateral cabinets are made in technopolimer material. Equipped with 4 Ø 125 mm swivelling rubber castors (2 with brake). Size 820x640xh 1, 200 mm. Made in Italy.

• 27489 COMBO FILES AND X-RAY FILM HOLDER

Same as above, but with 15 X-ray compartments and drawer that holds up to 25 files (not included).

### **EMERGENCY TROLLEYS**

### EMERGENCY TROLLEYS - small and standard

Professional trolley with painted steel structure and external plastic finish equipped with 4 drawers, one lateral waste container, one extra lateral table, I.V. stand, defibrillator holder (plexiglass tray), oxygen holder up to 5 litres (back), 2 antistatic rubber castors.

- 27479 EMERGENCY TROLLEY small 67x64xh 100 cm
- 27471 DIVIDER KIT for 27479 (drawer 45 cm)
- 27482 EMERGENCY TROLLEY standard 82x64xh 100 cm • 27472 DIVIDER KIT for 27482 (drawer 60 cm)
- DISPOSABLE SEALS
- 27473 DISPOSABLE SEALS box of 100
- 27474 DISPOSABLE NUMBERED SEALS box of 100





- 4 swivellling castors Ø 125 mm - 2 antistatic (only 45688/9)

- lateral waste container 15 I with lid and catheter holder

### KS MULTIFUNCTIONAL TROLLEYS

MULTIFUNCTIONAL TROLLEYS: BASIC, DRESSING, EMERGENCY Professional trolleys in 2 sizes (small and standard) and 3 models (Basic, Dressing and Emergency)

- antimicrobial epoxy painted body with seal lock (Emergency) or key lock (Basic and Dressing)
- top surface with 4-sided rim
- top surface with built-in compartment
- ball-bearing full-extension sliding drawer with self-closing system



- built-in handle

and with brake

(Dressing and Basic only)
- size: small 760x714xh 1,022 mm

standard 911x704xh 1,075 mm

- 45680 BASIC TROLLEY small
- 45681 BASIC TROLLEY standard
- 45684 DRESSING TROLLEY small • 45685 DRESSING TROLLEY - standard Dressing trolley is supplied with upper

dispenser (10 tilting bins).

- 45688 EMERGENCY TROLLEY small
- 45689 EMERGENCY TROLLEY standard Emergency trolley is supplied with rotating defibrillator/monitor tray, height adjustable I.V. pole with 2 hooks.

# AURION MULTIFUNCTIONAL TROLLEYS - TOP QUALITY

Well-designed

Single piece

Life saving

2 utility

Waste bin

CPR massage

Oxygen bottle

Sliding working surface

Drawer with stainless

Clear plastic swinging pockets

Shelf for suction pump

(for IV bottles/patient files) Ampoule opené

hooks

drugs drawei

Raydur structure

A multifunctional and revolutionary line of carts with innovative design, superior quality and complete accessories. Made in Baydur® polyurethane

Baydur® Polyurethane is a high performance material that combines the best characteristics of plastics

and metals. Light, sturdy, high resistance to scratching and impact. Resistant to UV rays. Chemical inert, doesn't react to acids, organic and inorganic, alkali and solvents (DIN 68861/1). Rotating stainless stee

defibrillator holder trav

rim. Every drawer is equipped with a label holder. Easy to move Lightweight structure combined with the high quality nonmarking and anti corrosion castors. Every wheel is mounted on ball bearings with sealed lubrification (2 per wheel), 3 with

Catheters compartments

brake, 1 antistatic. Hygienic and safe Flectric plug

IV nole - adjustable

locking

Drawer

h 100

Drawer:

h 150

Ø 125 m

3 with brake

45750

Used needle bucket/used

cotton waste contained

The smoothly shaped design, without edges, guarantees safety to the user and avoids dirty and bacterial accumulation points. Easy to clean and disinfect also with aggressive detergents.

Fire resistant, self-extinguishing (Class I, UL94 V-O). Non-toxic,

customizable and upgradable over the years. The handles are

moulded and integrated into the body as well as the worktop that has large surface and perimetrical anti-drip containing

in case of combustion it doesn't produce dioxin.

The Aurion trolleys are ergonomic, modular, highly

Safe and secure All-around soft rubber bumper help to avoid damages to hospital staff, patients, objects or to the trolley itself. Central locking device with key (45740-45746) or with seal (45750-45751).

Size 775x710xh 920 mm



 45755 AURION AMAGNETIC TROLLEY - yellow - 5 drawers with amagnetic wheels, without locking system

45746

• 45751 AURION EMERGENCY TROLLEY - dark blue - 5 drawers

45751

• 45750 AURION EMERGENCY TROLLEY - red - 4 drawers with IV stand, defibrillator tray, suction unit shelf (45751 only), CPR massage board, electric plug (45751 only).



• 45740 AURION THERAPY TROLLEY - green - 4 drawers • 45741 AURION THERAPY TROLLEY - light blue - 5 drawers with IV stand (45751 only), upper drawers, bin (45741 only) • 45744 AURION DRESSING TROLLEY - blue - 5 drawers • 45746 AURION MONODOSE TROLLEY - brown - 2 drawers

+ 2 monodose cassettes (10 small drawers each)

45668

### MULTIFUNCTIONAL AND EMERGENCY KARTS

#### MULTIFUNCTIONAL KARTS

High quality aluminium multifunctional and emergency carts with superior features.

- work-top in high performance copolymer, with perimetric edge for liquid containment

- extruded aluminium frame, with superficial silver antioxidant treatment offering more lightness, resistance and reliability
  - ergonomic stainless steel handles, fitted on both sides for easy handling
- drawer structure built in steel sheets, epoxy powder coated
- full pull-out sliding drawers
  - interchangeable drawer position - aluminium drawer handle with "hook/ unhook" system to prevent accidental
- opening of drawers entralizeo lockina system 45662 **3** 45660 + 45661
- 45660 COMPACT KART 5 drawers blue weiko Size: 634x605xh 975 mm • 45661 UPPER DRAWERS (9+5) - blue for 45660
- 45662 MEDIUM KART 5 drawers blue Size:804x616xh 975 mm
- 45663 UPPER DRAWERS\* (9+5) blue for 45662

• 45677 PARTITION KIT for compact kart drawers h2/h3

45677 Slim LED X-ray illuminator viewing area 42x36 cm. See other specifications at page 144, code 44700 45671 45672

 45671 VIEWER KART Compact kart with slim LED viewer, 2 small drawers and 2

Available colours

viewer, 2 small and 1 medium folder holders. drawers. 10 compartments for • 45678 HANGING FILE FOLDERS\* folders (44x48xh 43,8 cm).

\* Box of 25 hanging file folders 365 x 240 mm

• 45650 PERSONALIZED KART: CONFIGURATE YOUR KART SELECTING COLOUR, DRAWERS AND MODEL - available in 45 days Medium Large Available drawers 1/10 h 2/10 h

45672 VIEWER KART 2

Compact kart with slim LED

3/10 h

Folder holder 4/10 h

Pediatric compact kart with 2

medium and 2 large drawers. • 45657 UPPER DRAWERS (9+5)

- sum of selected drawers should be 10/10 h

- high drawers capacity: 20 kg (35 kg for drawer h-200-283 mm) - centralized locking system with front key or single use seals

(emergency karts only) - 6 integrated side pockets (3+3) to hold bottles or small items - swivelling wheels Ø 125 mm (two with brake) in thermoplastic rubber with threadguards, hub on precision ball bearings.

### TECHNICAL SPECIFICATIONS COMPACT: 654x605xh 975 mm MEDIUM: 804x616xh 975 mm Drawer size Compact/Medium: small h1= 1/10 Front width/height 490/640xh 64 mm 490/640xh 137 mm 490/640xh 210 mm 432/582x448xh 58 mm 432/582x448xh 131 mm 432/582x448xh 204 mm medium 490/640xh 283 mm 432/582x448xh 270 mm Infusion stand holder has safety anti-release system and 2 kg capacity per hook. Made in Defibrillator holder shelf with strap

45665

- 45665 EMERGENCY COMPACT KART 5 drawers red 45666 EMERGENCY COMPACT KART 4 drawers orange Size: 654x605xh 975 mm
- 45667 EMERGENCY MEDIUM KART 5 drawers red • 45668 EMERGENCY MEDIUM KART - 4 drawers - orange

Size: 804x616xh 975 mm Holder for cylinder Supplied with infusion stand holder 4 hooks, Ø 120-150 mm defibrillator holder tray, cylinder holder (double for 45667/8) and CPR board (only 45666/8)

27473 DISPOSABLE SEALS - box of 100 27474 DISPOSABLE NUMBERED SEALS - box of 100



• 45674 MULTIPURPOSE KART Compact kart with 2 small drawers and 2 folder holders.
• 45675 UPPER DRAWERS (9+5)

45678 HANGING FILE FOLDERS\*

You can choose your drawers considering: - interchangeable position of drawers

### 122

### PAINTED OR STAINLESS STEEL MODULAR TROLLEYS SYSTEM



#### MODULAR TROLLEYS SYSTEM

Modular trolleys made of painted steel or stainless steel, onepiece structure, with wide technopolymer plastic worktop with borders on 3 sides to be cleaned easily, no sharp corners, ergonomic tubular push-handle.

Different drawers (small-yellow, medium-blue, large-red), depending on model with enoxy painted panels and

depending on model, with epoxy painted panels and								
Painted	Stainless steel	TROLLEYS						
45600	45620	Trolley with 7 small drawers						
45601 45602	45621 45622	Trolley with 1 small, 3 medium drawers						
45602	45623	Trolley with 2 small, 1 medium, 1 large drawers Trolley with 1 small drawer, 1 compartment with shelf						
45604	45624	Trolley with 2 medium, 1 large drawer						
ACCESSORIES FOR ALL MODULAR SYSTEM TROLLEYS								

45640 IV stand

45641 Upper drawers (5 medium + 4 large)

Partition h 4 cm for yellow drawer (49x48x10 cm) 45645 Partition h 14 cm for blue drawer (49x48x20 cm)

45646 Partition h 20 cm for red drawer (49x48x30 cm)

integrated handle grip, silent sliding with end-run block. Possibility to remove the drawers from the guides for an easy cleaning and disinfection. Central lock key. Overall bumpers and 4 antistatic 125 mm castors, 2 with brakes. Size: 67x63x104 cm. Weight: 53 kg.

Made in Italy Personalization for minimum 10 pcs: drawers in your colour.



#### • 45410 WASH-BASIN PUMP SYSTEM white

Automatic wash-basin with round bowl in satin stainless steel, non-connected to the water mains. The system ensures the availability of water when it is expensive or impossible to lay drain-pipes in the walls



# WASH-BASIN - PUMP UTILITY TROLLEY



• 45595 UTILITY TROLLEY - blue avio 45597 UTILITY TROLLEY - other colours\*

RAL 1013 6019 \*Available in 30 days. Minimum order 5 pcs.

Smart and strong steel structure painted with epoxy powder. Technopolymer plastic one-piece top with border, without sharp corners, with compartment for accessories. Ergonomic push handle. 3 medium drawers 45.1x48.5xh 15 cm and 1 large drawer 45x49.5xh 22.5 cm with silent sliding and end-run block. Central lock key. Size: 60x50xh 100 cm

Overall bumpers and 4 antistatic 125 mm Blue Avio RAL 5014 swivelling castors. 2 with brake. Made in Italy



45393



Multi-purpose wall unit to organize dispensers of disposable products. All components and slots are modular and can be organized to match professional user needs. Available in 2 sizes: standard (103x20xh 40 cm) and large (153x20xh 40 cm) and 8 colours. Melamine particle board door with vertical opening. Supplied with automatic soap dispenser, cups dispenser and 5 (standard) or 7 (large) slots.



Slot for napkins or cannule Roll holder

Slot for dispenser of disposable products	ST
	Di:
	Slo
	Slo
and the second second	Slo
	Ro

45405

# TANDARD ACCESSORIES

		wipes											
0	45295		MULTIFUNCTIONAL WALL UNITS										
3	45298 1 1	Model	white light		ster yellow hite	blue	green	orange					
	3	Standard	45290	+	4529	3* -		<b>→</b>					
	1	Large	45295	-	4529	8* -		<b>→</b>					
	2	*Available in 60	days, please sp	ecify colour wit	th order								

### GIMA WORKTOPS AND MOBILE UNITS



4529

The key principle in the design of this system is a total separation of the work surface (fixed) from the mobile units. The worktop set in a fixed position allows to bring together all electric and electronic wiring, as well as plumbing and waterpipes into a single location. The work surface remains free to place instruments and electric appliances, can incorporate a sink and serves as a desk. All mobile containers have wheels and are the dynamic part of the system. They can be easily placed under the work surface, or moved by the user wherever needed in the working environment. Units are interchangeable and can be freely moved between rooms. Work surfaces are made in a waterproof material covered with a high-quality melamine particle board, which ensures long durability, scratch and wear resistance. A range of 4 containers, in 8 different

45396

colours with ergonomic full-length handles. Made in Italy.						
GIMA code	STANDARD WORKTOPS - WHITE					
45300 45301 45302 45303 45304 45305	Worktop 180 cm - right washbasin Worktop 180 cm - left washbasin Worktop 180 cm - without washbasin Worktop 232 cm - right washbasin Worktop 232 cm - left washbasin Worktop 232 cm - without washbasin					
GIMA code	ACCESSORIES					
45401 45402 45403 45405	Tray 33x43.5xh6.5 cm 3-compartment tray 33x43.5xh6.5 cm 11-compartment tray 33x43.5xh6.5 cm Chromed mixer tap					



45396 45397



Model	white	light blue	grey	oyster white	yellow	blue	green	orange
S1	45350	45360	+		<del></del>	390° —		
S5	45353	45363	+		<b></b> 453	393° —		
S9	45356	45366	-		<b>—</b> 453	396° —		
S10	45357	45367	-		<b>—</b> 453	397" —		
*Available	in 60 days, p	lease specify	colour w	ith order				

### 1 OR 3 ENGINES GYNAECOLOGICAL CHAIRS AND STOOLS



having a power supply at 24 V. The electric actuators enable the movement up and down from 57 cm off the floor ("0" position) up to a maximum of 96 cm. The backrest is supplied with adjustable headrest and paper roll holder. The legrest can be indipendently adjusted and it has an automatic-locking device.

The chair can be flattened to a bed position for examination activity, the armrest can be removed and independently oriented. The electric control of the chair for upright position is operated by means of a foot pedal.

aacca.y.		
	<b>TECHNICAL SPECIFICA</b>	TIONS
	GYNEX	GYNEX PROFESSIONAL
Power supply tension:	230V - 50 Hz (110	OV - 60 Hz on request)
Motor tension:	24 V	24 V
Lifting motor push:	6,000 N	6,000 N
Backrest push:	800 N (gas spring)	2,500 N (motor)
Legrest motor push:	-	2,500 N
Lifting capacity:	180 kg	180 kg
Maximum power:	90 VA	90 VĀ
Fuses protection:	1.6 A	1.6 A

	GYNEX CHAIRS AND STOOLS										
	Light blue Parigi	Green Toronto	Blue Chicago	Orange Rotterdam	Metal Apricot	Metal Sea blue	Colour on request				
Gynex professional	27514	27512"	27513	27512**	27515	27512"	27512"				
Gynex	27521	27522	27523	27524	27525	27526	27520"				
Stool with ring	27531	27532	27533	27534	27535	27536	27530"				
Stool without ring 27527  27528"											

"Available in 60 days, specify colour with order

an electromechanical lifting device,

	COLOUR ON REQUEST: CLASSIC COLOURS											
White Helsinki	Beige Roma	Beige Tunisi	Orange Praga	Red Mosca	Pink Malaga	Bordeaux Bangkok						
Green	Green	Green	Green	Green	Green	Violet	Violet	Light blue				
New Delhi	David	Melbourne	Irlanda	Honolulu	Caracas	Nizza	Ankara	Palm beach				
Blue	Blue	Blue	Grey	Grey	Grey	Black						
Berna	Baltico	Anversa	Oslo	Amburgo	Londra	Odessa						
	COLOUR ON REQUEST: METALLIC COLOURS											
Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal				
Ice	Silver	Bronze	Gold	Lemon	Red	Sky Blue	Blue	Dust Grey				



#### **GYNEX PROFESSIONAL - GYNAECOLOGICAL CHAIR**

Gynex professional chair offers functionality, aesthetics, ergonomics. It can satisfy all patient and user needs for a professional gynaecologic visit. Gynex professional is provided with versatile accessories; back paper-roll dispenser, metal basin, leg-supports. 3 engines allow, in addition to lifting, electric backrest and legrest movements. The combined movement of backrest and seat by means of self-balancing system (operated by a silent low tension actuator of 2,500 N) grants maximum comfort to the patient. The padded and pelted armrests allow a relaxing protecting sitting position, armrests are individually revolving and removable. Backrest is provided with removable height-adjustable headrest. The wide and soft backrest has independent adjustment movement through silent low tension actuator. This chair is moved by a silent low tension engine which allows a vertical excursion of 40 cm from zero position. The electrical drives are controlled by an ergonomic hand switch control, connected to the chair by a cable. Gynex professional can be easily transformed into an examination bed (horizontal position).



4 antistatic pivoting wheels

Made in Italy

### GYNAECOLOGICAL AND DELIVERY BEDS









- 27500 DELUXE GYN BED quality leg holders
- 27501 GYNAECOLOGY BED standard leg holders Strong chrome-plated structure. Rectangular steel tube. Adjustable head and leg sections. Simulated leather, black colour, washable upholstery, self extinguishing. Load: 100 kg. Complete with s/s bowl Ø 31 cm and leg-holders. Made in Italy.
- 26586 S/S BOWL Ø 31 cm spare

- 27510 DELUXE DELIVERY BED quality leg holders Same as 27500, but with three sections with independent controls and Trendelenburg position, Load: 120 kg.
- 27503 STANDARD LEG HOLDERS couple spare • 27504 QUALITY LEG HOLDERS - couple - spare
- Kit leg holders includes 2 leg-holders and arms.
- 27418 COUCH ROLL HOLDER

### 3- SECTION MULTIFUNCTIONAL AND GYNAECOLOGICAL BEDS

in kit form

Seat: 62x60 cm



- 27502 3-SECTION MULTIFUNCTIONAL BED blue
- 27505 3-SECTION GYNAECOLOGICAL BED blue

Strong and stylish structure in oval tube 50x25 mm, painted with epossidic powder, metallic grey colour. The three sections top has high density padding, covered with washable, fire proof, leatherette material Class 1 IM. Back-rest and leg-rest section are fully adjustable by self mechanical sytem. Back-test and regress section are runy adjustable by set interest special set of Gynaecological bed is supplied with 2 foam padded leg holders and stainless steel bowl Ø 32 cm. Maximum load: 150 kg - Weight: 36 kg. Made in Italy.

- 27508 STANDARD LEG HOLDER couple spare
- 27509 OUALITY LEG HOLDER couple
- Kit leg holder, includes 2 leg-holders and arms.
- 27511 COUCH ROLL HOLDER for 27502-5
- 27919 DESK with 2 drawers 130x71xh 80 cm Strong structure in oval tube 40x20 painted with epossidic powder, metal grey colour. White work top with rubber edge and round corner.
- 27979 FOOT STOOL 2 steps







### 3-SECTION DELIVERY BED WITH TRENDELENBURG

- 27538 3-SECTION DELIVERY BED with Trendelenburg structure made of epoxy painted oval steel tube
- three sections with independent control and Trendelenburg position
- padding made of high density polyurethane foam, fireproof Class 1 IM
- covering made of washable, plastic material (leatherette) fireproof Class 1 IM
- adjustable rubber feet

Size: 185x60xh 85 cm

Size: 181x60xh 80 cm

Carton size: 75x20xh 196 cm. Maximum load: 150 kg.

Net weight: 43 kg.

Supplied with a pair of height-adjustable, padded, anatomic leg-holders, a couple of shoulder rests, handgrips, a paper roll holder and a stainless steel basin Ø 32 cm. Delivered in kit form.

Made in Italy

• 27509 QUÁLITY LEG HOLDER - couple

# **DONOR ARMCHAIR**

- 27557 DONOR ARMCHAIR blue mechanical
- 27563 DONOR ARMCHAIR blue electrical
- 27567 DONOR ARMCHAIR WITH WHEELS white

Strong and stylish armchair with structure made with oval, round and square metal section tubing (legs oval tubing 50x25x1.5; central frame square tubing 30x30x1.5,

cushions round tubing 20x1.5 diam.).

Structure fully coated with white epoxy powder.

High density polyurethane foam platform with wooden base covered by leatherette upholstery.

Both materials are flame resistant Class 1 IM.

Synchronized adjustment of the two cushions by a gas spring, cylinder/piston, (27557, 27567) or by a linear actuator (27563)

with a push-button panel, allow a guick moving into TR/RTR position. The backrest inclination ranges from +60° to -5° in Trendelenburg position.

lea rest from -80° to +5°. The arm-rests can be height adjusted and

are reclinable. When removed, they can be rotated up to 180°. Four adjustable feet ensure maximum

stability (27557 and 27563) or 4 castors, 2 with directional brake (27567) ensure mobility. Load: 150 kg. Size: 175x55xh 51 cm. Made in Italy.

27553 IV STAND

• 27556 COUCH ROLL HOLDER



WITH WHEELS

White ral colour 9003 structure. minimum thicknes 70/80 micron Glossy finish.

27557



# **DONOR WHEELCHAIR**

• 27561 DONOR WHEELCHAIR

Donor wheelchair with structure made of epoxy painted oval and round steel tube.

Backrest adjustable by gas pump

Padded leg rest manually adjustable.

Metal footrest extractable. Armrest with articulations. manually adjustable in height.

Padding made of high-density polyurethane foam, fireproof Class 1 IM. Covering made of washable, plastic material (leatherette), fireproof Class 1 IM.

Back push handle. Mattress overall size: 166x55 cm. Carton size: 185x67xh 58 cm Four wheels Ø 100 mm, 2 directional and 2 with brake. Net weight: 53 kg. Gross weight: 55 kg. Maximum load: 150 kg. Supplied with blanket tray with belts to fix oxygen bottle,





Blanket tray with belt to fix oxygen bottle (hottle not included)

### HEIGHT ADJUSTABLE GYNAECOLOGICAL BED

27567

• 27506 HEIGHT AD JUSTABLE GYN BED - green • 27507 HEIGHT ADJUSTABLE GYN BED - blue

IV stand and chart holder support. Made in Italy.

 27496 HEIGHT ADJUSTABLE GYN BED - any colour\* \*Available in 20 days see below available colours

Strong and solid structure in oval tube 50x25x2 mm painted with epoxy powder, white colour. The three sections top has high density

padding, covered with washable, fire proof. leatherette material class 1 IM.

Full adjustable

Height, up to 95 cm, is adjustable by electric engine (6000 N power) with foot control, head section is adjusted by a gas cylinder (400 N power), central section by a gas cylinder (600 N power) up to 65°. This gyn bed is supplied with 2 quality foam leg holders, stainless steel tray and couch roll holder.

Maximum load: 150 kg. Weight: 70 kg. Made in Italy. • 27509 QUALITY LEG HOLDER - couple - spare

Kit leg holder includes 2 leg holder and arms. Suitable for 27496, 27505, 27506, 27507.




















127



- 27546 OTO/PV ENT CHAIR with head support green Melbourne 27551 OTOPEX ENT CHAIR with head support blue Chicago
- Patient chair with Peltex-lined seat and backrest.

Electric up and down movements by silent engine controlled through foot switch.


Back-rest can be adjusted up to 180° by a gas spring. Chair rotates 360° and is provided with a rotation locking device placed at the bottom. Power: 230 V - 50 Hz (Available 110 V - 60 Hz). Made in Italy.

• 27547 OTO/PV ENT CHAIR with head support - sky blue Parigi • 27552 OTOPEX ENT CHAIR with head support - green Toronto ENT chair designed also for ambulatory operations.

Moved by very silent electrical engines operated by joystick foot-control. Also provided with button to re-set to previously selected working position. Upholstery made of simulated leather, high density undeformable foam padding (50 kg/cm<sup>3</sup>). Seat and leg-rest are joined in a single piece.

Power: 230 V - 50 Hz (Available 110 V - 60 Hz). Made in Italy.

# **ENT CABINETS**



#### • 27540 OTOPLUS - ENT UNIT

The E.N.T. unit has rubber pivoting castors, a working surface made of scratch-proof rolled sections, 2 small and one large drawers provided of removable internal partitions, one drawer with inside germicidal lamps to keep instrument sterilization. Otoplus is provided with a silent suction pump of 34 l/min, with power supply complete with dim adjustment device for Clar/Storz lamp, larynx-mirror warmer, twin-cylinder dry compressor for tubal insufflation, 2-litres distilled water tank with acoustic signal for reserve level. The articulated arm with instrument holding tray is complete with terminal suction cannula and terminal insufflation cannula, ear rinsing syringe with automatic water temperature control, (a microprocessor keeps temperature at a constant level of 37 °C).

Power 230 V - 50 Hz (Available 110 V - 60 Hz). Made in Italy.

#### • 27539 OTOPLUS COMPLETE

Same as code 27540 with included vasister drawers (code 27541) and endoscope support (code 27543).

Otoplus unit with additional column, to be used for diagnostic equipment (light source, camera or printer) and a support pole for monitor

#### • 27555 OTOPLUS DC ENT UNIT - complete

Same as code 27554 with included hopper frame drawers (code 27541) and endoscope support (code 27543)

- 27541 HOPPER FRAME DRAWERS 2 indipendent drawers • 27543 ENDOSCOPE SUPPORT - 2 transparent plastic tubes 1 tube 50 cm long and 1 tube 25 cm long both closed at the
- 27542 SYRINGE MEDICATION KIT composed of 1 syringe, 2 atomizers (1 for liquid and 1 for powder) and 3 ampoules in dark glass. To be ordered with ENT unit.

### • 27544 LED LIGHT SOURCE

Makes cold white light (5500 °K, 200 lumen) for endoscopy use. It can be connected to endoscopes without need of F.O. cable. Handle LCD display connect directly to 12 8x6 4 cr rigid endoscopes (Storz connection). Size: 30x25x12 cm

### HYDRA PODOLOGY CHAIR - MADE IN ITALY

### • 28033 HYDRA PODOLOGY CHAIR - green David

28035 HYDRA PODOLOGY CHAIR - any colour\*

Functional and compact podiatry chair. The up/down movement, activated by a foot switch is synchronized to the seat inclination in order to easily lift the patient foot to the optimal working position, allowing the operator to keep the correct posture during the whole therapy. One silent electric actuator activates the up/down movement allowing a vertical lift range of 40 cm (min height

	COLOUR ON REQUEST: CLASSIC COLOURS*											
White	Beige	Beige	Brown	Yellow	Orange	Red	Pink					
Helsinki	Roma	Tunisi	Perugia	Parma	Praga	Mosca	Malaga					
Bordeaux	Green	Green	Green	Green	Green	Orange	Violet					
Bangkok	New Delhi	Melbourne	Irlanda	Honolulu	Caracas	Rotterdam	Nizza					
Violet	Light blue	Blue	Blue	Blue	Grey	Grey	Grey					
Ankara	Palm beach	Berna	Baltico	Anversa	Oslo	Amburgo	Londra					
Black Odessa	Light blue Parigi	Green Toronto	Blue Chicago									
	COLC	UR ON F	REQUEST	: METAL	LIC COLO	DURS*						
Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal					
Ice	Silver	Bronze	Gold	Lemon	Red	Sky Blue	Blue					
Metal Dust Grey	Metal Apricot	Metal Sea blue										

55 cm/max height 95 cm). Combined to the seat inclination movements, it permits the heel rest to reach the height of 120 cm from the floor. The backrest is manually adjustable to 180° through a powerful gas spring. The upholstered ergonomic parts grant high comfort to the patient. The double legrests swivel horizon-

tally and the extendable heel rest holds the foot in various working positions. Comfortable padded arm rests. Lifting capacity: 180 kg. Chair's weight: 80 kg. Power supply: 230 V - 50/60 Hz.



Angle 50-90°

28033

28020

### PODOLOGY CHAIRS



backrest and seat inclination, by foot switch or push button panel. Head rest can be inclined, arm rests are movable. Operating power: 220-240 V - 50/60 Hz. Size: 186x56x58/89 cm Maximum load: 170 kg Net/Gross Weight: 83/96 kg

- 45232 STOOL blue
- 45242 STOOL WITH BACKREST blue

45241 28020 PODOLOGY CHAIR - mechanical This chair can move up and down and rotate. Backrest and footrests are adjustable. Heavy round base provides maximum stability. Size: 180x80xh 51/65 cm Maximum load: 170 kg Weight: 41 kg

- 45231 STOOL white
- 45241 STOOL WITH BACKREST white

Rotatio

0°~90

# **GAMMA/PODOLOGICAL CABINETS** - MADE IN ITALY

• 28030 GAMMA1 CABINET - 61x45xh 77 cm - small

• 28031 GAMMA3 CABINET - 108x45xh 77 cm - large

Practical service cabinet, equipped with tabletop in scratchresistant wood, drawers and doors, specifically designed to keep tools and accessories sterile. Base with castors to facilitate movement. Supplied with connections to the mains: germicide compartment, lampholder and other electric sockets.

Power supply: 220 V - 50/60 Hz.

			S	IZES		
	Cab	inet	Table	e top	Germicide	Large
	28030	28031	28030	28031	compartment	compartme
Length: Width:	61 cm	108 cm	61 cm	108 cm	28 cm	28 cm
	45 cm	45 cm	42 cm	42 cm	38 cm	28 cm
Height:	77 cm	77 cm			4 cm	15 cm



' Available in 15 days

#### **ELECTRIC CHAIRS WITH FOOT CONTROL - 3 MOTORS** Size: 186x86xh 58-88 cm Net weight: 86 kg Net weight: 79 kg Max load: 170 kg Max load: 170 kg Angle 0° to 85° Extension 8 cm Headrest extension Angle from Angle 0° to 10° -4° to 10' nale 0° to 80 Angle 0° to 75° Anale 0° to 90' 58-89 c 58-100 cm Height adiustme Footrest Rotation extension up to 240° Footrest extension 14 cm 45233 adjustable by gas lift pump 28045 28040 • 28040 CLEOPATRA ELECTRIC CHAIR - 3 motors - beige • 28045 NEFERTITI ELECTRIC CHAIR - 3 motors - green Electrically controlled 3 motors chair to adjust separately Electrical chair with very stable structure and high comfort. height, backrest and seat inclination by foot switch or push Specially designed to optimize the workspace due to 240°

button panel. Footrest adjustable by gas lift pump. Reversible arms and adjustable headrest. Operating power: 220-240 V - 50/60 Hz.

• 45234 STOOL - beige

• 45244 STOOL with backrest - beige

rotation. 3 motors control height, backrest and seat inclination by foot switch or push button panel. Footrest adjustable by gas lift pump, reversible arms and adjustable headrest. Operating power: 220-240 V - 50/60 Hz. • 45233 STOOL - green

• 45243 STOOL with backrest - green



Chair can move up and down and rotate 360° Backrest and footrest 28005/28006

are adjustable. STOOLS

• 45231 STOOL - white

• 45232 STOOL - blue

STOOLS with backrest • 45241 STOOL - white

• 45242 STOOL - blue See page 141.

Electrically controlled chair to adjust separately height, backrest or footrest. Hand and foot control. Armrest and headrest are flexible. Operating power: 220-240 V - 50/60 Hz. Available on request 100-120 V.



#### GIMA ADJUSTABLE HEIGHT ELECTRIC TABLE • 27632 GIMA TREATMENT TABLE - any colour\*\* • 27633 GIMA TREATMENT TABLE - blue ■adjustable • 27634 GIMA TREATMENT TABLE - cream 6 COLOURS • 27628 GIMA TREATMENT TABLE - green • 27635 GIMA TREATMENT TABLE - black Sturdy and highly stable examination and treatment table. Adjustable height by electric foot switch. Fixed leg-section and manually adjustable 2 Blue head-section with mouth-nose hole. 3 Grey Fire proof padding. Lifting capacity: 140 kg. 4 Greer 64 to Length: 193 cm. Made in Italy. 5 Crean STOOLS: matching stool at page 141 6 Aprico 27629 COUCH ROLL HOLDER • 27630 MOUTH-NOSE HOLE PLUG - any colour\* • 27631 MOUTH-NOSE HOLE PLUG - blue • 27620 MOUTH-NOSE HOLE PLUG - cream • 27625 MOUTH-NOSE HOLE PLUG - green • 27621 MOUTH-NOSE HOLE PLUG - black

### **ELECTRIC OR HYDRAULIC HEIGHT-ADJUSTABLE TABLES**

AVAILABLE IN 24 COLOURS



#### BRUXELLES TABLES - electric or hydraulic

Examination and treatment table with high stability. Electric height adjustment by a foot-switch (low tension 24 V) or manual by hydraulic piston. Features: one mobile section, gas-spring supported adjustment of the head-section (with mouth-nose hole) and fixed leg-section.

The large head-section can be adjusted positively and negatively and serves as back-rest. Safe working load 200 kg. Power 230 V - 50/60 Hz. Made in Italy.





Sturdy frame with all moving

parts having self-lubricating

components to avoid early

wear and noise

- 27602 THER TRENDELENBURG TABLE electric any colour\*\* • 27603 THER TRENDELENBURG TABLE - electric - blue (3)
- 27604 THER TRENDELENBURG TABLE hydraulic any colour Examination and treatment tables with electric height adjustment by a foot switch (low tension 24 V) or hydraulic height adjustment by a piston. Features: three mobile sections adjustable by gas spring. The table can easily assume the "flexion", "relax" and "trendelenburg" position even if the patient is lying on the table. The large head-section (with mouth-nose hole) can be adjusted positively and negatively. Chair position. Safe working load 200 kg.

Power 230 V - 50/60 Hz. Supplied with mouth-nose hole plug. Made in Italy.

GIMA code	ACCESSORIES FOR ALL TA	BLES
27591	Couch roll holder for rolls 50 to 63 cm Wheels set Mouth-nose hole plug - any colour** for 27587-9, 27595-6, 27582-4	7
**Available	n 30 days	Wheels set - optional

Upholstery colour code



### VARIABLE HEIGHT EXAMINATION COUCH WITH TR/RTR

44510 LORD VARIABLE HEIGHT EXAMINATION COUCH - water green - 5
 44516 LORD VARIABLE HEIGHT EXAMINATION COUCH - any colour' available in 20 days, see below available colours

Stable and sturdy examination couch made in high quality tubular for furniture. Very practical and user friendly. Height adjustable thanks to the two electrical columns that can move simultaneously or separately (allowing the Trendelenburg/Reverse Trendelenburg position) by a push-button panel.

Under the top frame, an ergonomic lever actions a gas spring that reclines





#### KING EXAMINATION COUCH KING EXAMINATION COUCH Strong and stilish structure in oval tube 50x25 mm painted with metallic grey epoxy powder. Top in washable, fire proof, leatherette material class 1 IM with high density padding. Head section adjustable by mechanical system. Maximum load: 150 kg. Size: 190x60xh 80 cm. Delivered in kit form. Made in Italy GIMA 27616 KING EXAMINATION COUCH Code 27614 King examination couch - water green - 5 27615 King examination couch - white - 7 27616 King examination couch - blue - 9 27617 King examination couch - black - 6 44486 King examination couch - any colour\* KING EXAMINATION COUCH WITH HOLE 27618 King examination couch - green 27619 King examination couch - white available in 20 days, see below available colou WIDTH: 60 cm MAX LOAD 150 kg 27619 27978 27511 Couch roll holder 27978 Foot stool - 1 step 27979 Foot stool - 2 steps KING PLUS EXAMINATION COUCH • 44490 KING PLUS EXAMINATION COUCH - blue - 9 • 44491 KING PLUS EXAMINATION COUCH - beige - 2 • 44496 KING PLUS EXAMINATION COUCH - any colour "available in 20 days, see below available colour Same as King examination couch, but with extra thick 7 cm mattress with lateral white band 2 Orange Beige Red Water MAX LOAD 150 kg 44491 44490 10 **ELITE EXAMINATION COUCH** • 44500 ELITE EXAMINATION COUCH - blue - 9 LOAD 200 KG • 44503 ELITE EXAMINATION COUCH - any colour\* \*available in 20 days, see below available colours Stylish, comfortable and innovative examination couch available in 10 colours with lateral white band. Realized with high quality furniture tubing that quarantees stability and robustness The couch is made with rectangular and rounded tubing, Uni 7947/81 and 8913, DIN 2394. Fireproof rubber padding covered with class 1 IM fireproof woven imitation leather. Adjustable head section through 2 cogwheels. The roll holder, included, can be placed in the feet or in the head side. 4 adjustable feet. Size 193x68xh 78 cm. Padding size 190x68xh 7 cm.

44503

Max. load 200 kg. Weight 70 kg. Disassembled, very simple to assemble.

44505 RETRACTABLE/REMOVABLE WHEELS

Made in Italy

### COUCH PAPER ROLLS

A complete range of hygienic and resistant couch paper manufactured in Italy in pure cellucotton or cellucotton/ polythene. Each roll is individually packed in plastic bag for best protection. Atoxic. Available with standard 38 or 40 cm perforation or 190 cm perforation (full person size).

#### • 27418 COUCH ROLL HOLDER

Adjustable roll holder suitable for round (Ø 27-30 mm) or square (27-30 mm x 27-30 mm) metal couch leg.

# OTHER SIZES OF COUCH ROLL PAPER AVAILABLE ON REQUEST

COUCH PAPER ROLLS												
MATERIAL		cotton ossed		Microembossed glued mikrogepragt verleint - gauffré collé						Pure wadding of cellulose ply coated with a polythene protection		
GIMA code	27410	27411	27412	27424	27427	27428	27432	27419	27414	27413	27415	
Colour	white	white	white	white	white	white	white	white	light blue	white	white	
Ply	1 ply	2 ply	2 ply	2 ply	2 ply	2 ply	2 ply	2 ply	14 g/m² polyth.	14 g/m² polyth.	8 g/m² polyth	
Weight	30 g/m <sup>2</sup>	2x20 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	26/28 g/m²,	26/28 g/m²,	26/28 g/m <sup>2</sup>	
Length	95 m	47.5 m	46 m	50 m	100 m	50 m	80 m	80 m	50 m	50 m	50 m	
Height	50 cm	59 cm	50 cm	50 cm	50 cm	59 cm	59 cm	59 cm	50 cm	50 cm	60 cm	
Number of sheet	250	125	135	132	263	132	210	42	132	132	125	
Perforation	38 cm	38 cm	34 cm	38 cm	38 cm	38 cm	38 cm	190 cm	38 cm	38 cm	40 cm	
Rolls per box	6	6	9	9	6	9	6	6	6	6	6	

27415

27411

27410

27414

#### Backrest adjustable 0° to 55° through different positions EXAMINATION COUCHES Couch size • 27401 EXAMINATION COUCH - chromed - black 180 x 61 x h 75 cr 27401 • 27402 EXAMINATION COUCH - white painted - grev • 27444 EXAMINATION COUCH - white painted - green STOOLS: see matching stools page 141 Suitable for medical office or small surgeries. Easy to assemble, following enclosed instructions Comes complete with mattress. Upholstery in two sections: one 130x61xh 5.5 cm fixed and a 50x61xh 5.5 cm backrest adjustable through different positions. Delivered in kit form. Universal couch roll holder (code 27418, not included) Made in Italy. Simulated leather, black/grev colour • 27418 COUCH ROLL HOLDER washable upholstery in two sections Adjustable roll holder suitable for round (Ø27-30 mm) or square (27-30 mm x 27-30 mm) • 27404 CLASSIC EXAMINATION COUCH - chromed - beige • 27405 CLASSIC EXAMINATION COUCH - chromed - blue - backrest with hole • 27445 CLASSIC EXAMINATION COUCH - chromed - apricot Chromed mainframe and legs constructed in chrome-plated steel. Legs fitted with plastic feet.

27405

### **EXAMINATION AND TREATMENT TABLE - HIGH LOAD**

- 27622 STANDARD TREATMENT TABLE any colour\* 27623 STANDARD TREATMENT TABLE blue\*
- 27624 STANDARD TREATMENT TABLE cream\*
- 27626 LARGE TREATMENT TABLE any colour\*\* • 27627 LARGE TREATMENT TABLE - blue\*

Professional examination and treatment table with one movable section and manual adjustment.

Sturdy detachable metal structure painted with scratch-proof, non corrosive epoxy powder.

The section trim facilitates reaching the patient.

The head section has an extended mouth-nose hole.

Load 180 kg (standard), 200 kg (large). Made in Italy

- 27629 COÚCH ROLL HOLDER
- 27630 MOUTH-NOSE PLUG any colour\*\*
- 27631 MOUTH-NOSE PLUG blue
- 27620 MOUTH-NOSE PLUG cream

1 Black 4 Green 2 Blue 5 Cream 3 Grev 6 Apricot 80 cm 27622

AVAII ARI F IN cover finish made of high-quality ireproof simulated leather. Vinvl is resistant to disinfectants, urine. and blood WIDTH 80 cm 27627 MAX LOAD - 200 kg 78 cm

Adjustable 0 to 349

### WOODEN COUCHES

#### WOODEN COUCHES

 $\epsilon$ 

27402

27404

134

Comfortable couches, ideal for physical therapy, cardiology and wellness centres. Superior quality wood. Back rest

adjustable in 13 positions. Resilient foam padding covered with washable weave. Padding in beige colour. Size: 190x70xh 70 cm. 27416 lverage hole 08 cm Maximum load 27417+27409 Mouth nose hole plua included

- 27416 WOODEN COUCH beech
- 27417 WOODEN COUCH with face hole beech
- 27443 DANTE WOODEN TROLLEY beech
- 27409 COUCH ROLL HOLDER for 27416 and 27417

Couch roll holder included with 27450 and 27451. Delivered in kit form. Easy assembly, tool provided. Made in Italy.



- 27450 FIRENZE WOODEN COUCH wenge
- 27451 FIRENZE WOODEN COUCH with face hole cherry wood

**ALUMINIUM SUITCASE COUCH** 

• 27452 DANTE WOODEN TROLLEY - cherry wood

### SUITCASE COUCH



### • 27406 ALUMINIUM SUITCASE COUCH with hole (22x12) Light, foldable, two sections, suitcase couch with aluminium

frame. Central double legs for improved safety and block system on the hinges. Head rest with mouth/nose hole. Upholstered and covered with simulated leather.



material.

Backrest fully adjustable.

washable and fire-proof plastic

Available in beige, blue, apricot colour. Other colours on request, minimum 10 pieces.


Size: 180x57xh 73 cm.

Maximum load 100 kg. Delivered in kit form.

Made in Italy. • 27408 MOUTH-NOSE HOLE PLUG for code 27405 - blue STOOLS: see matching stools page 141

The two-section top has resilient foam padding covered with

### FOLDABLE MASSAGE TABLE - WOOD OR ALUMINIUM



- Headrest 44000 2-SECTION WOODEN MASSAGE TABLE black
  - 44001 2-SECTION WOODEN MASSAGE TABLE blue
  - 44002 2-SECTION WOODEN MASSAGE TABLE turquoise
  - 44003 2-SECTION WOODEN MASSAGE TABLE cream Two-section foldable height adjustable massage table with German beech wood frame and PVC vinyl cover with 5 cm foam thickness.

Tables are supplied with headrest, hanged armrest, mouth-nose plug and carrying bag. Product open size: 185x70xh 62/87 cm Carrying Packing size: 95x20xh 75 cm bag for all

Maximum working load: 227 kg (500 lbs)

Net/Gross weight: 14/17 kg Manual: GB, FR, IT, ES, PT, DE

• 44011 3-SECTION WOODEN MASSAGE TABLE - blue • 44013 3-SECTION WOODEN MASSAGE TABLE - cream

Three-section foldable height adjustable massage table with German beech wood frame and PVC vinyl cover with 5 cm foam thickness. Tables are supplied with headrest, armrests. hanged armrest, mouth-nose plug and carrying bag. Product open size: 185x70xh 62/87 cm

Packing size: 95x20xh 75 cm Net/Gross weight: 16/19 kg Maximum working load: 227 kg (500 lbs)

Manual: GB, FR, IT, ES, PT, DE



- 44020 2-SECTION ALUMINIUM MASSAGE TABLE black
- 44021 2-SECTION ALUMINIUM MASSAGE TABLE blue

• 44024 2-SECTION ALUMINIUM MASSAGE TABLE - white Two-section foldable, height adjustable massage table with aluminium frame and PVC vinvl cover with 5 cm thickness. Tables are supplied with headrest, side armrests, hanged armrest, mouth-nose plug and carrying bag.

Product open size: 186x70xh 59/80 cm Packing size: 95x20xh 75 cm Net/Gross weight: 13/16 kg Maximum working load:



### WING SCREEN WITH TREVIRA CURTAINS



SCREEN WITH TREVIRA CURTAINS Build up the screen you need choosing among 4 frames and 6 colours of Trevira curtains.

#### Wing screen

Aluminium alloy tubular frame mounted on feet or castors (Ø 50 mm). Size: 150xh 170 cm (3 wings) or

200xh 170 cm (4 wings) Trevira curtains are flame-proof (Class I), antiallergic, avoid bacterial growth, waterproof and highly resistant to abrasion.

Thick weft to avoid dust infiltration and improve privacy, washable up to 60°C. Available in 6 colours to match any need. Custom-made curtains available on request.



code	without curtain			
45560 45561 45562	3 wing screen 3 wing screen with castors 4 wing screen			
45563	4 wing screen with castors			
	CURTAINS* IN TREVIRA 45xh 132 cm			
GIMA code				

WING SCREEN FRAME

trevira

45573 Curtains - beige 45574 Curtains - green 45575 Curtains - peach you have to buy 3 or 4 curtains

depending on frame you choose



### 3 OR 4 WINGS SCREEN WITH PLASTIC CURTAINS



- 27970 3 WINGS SCREEN
- 27971 3 WINGS SCREEN with castors
- 27972 4 WINGS SCREEN
- 27974 4 WINGS SCREEN with castors Aluminium alloy tubular frame. Weight 5 kg (3 wings), 8 kg (4 wings). Fire-retardant, foldable washable white plastic curtains mounted on feet or castors (Ø 50 mm).

Size:150xh 170 cm - 3 wings (50 cm each) 200xh 170 cm - 4 wings (50 cm each) Made in Italy.

SEPARATION SYSTEMS AND CURTAINS see page 106

# MASSAGE BED WITH HOLE

44024

44011

#### • 27421 MASSAGE BED

Comfortable massage bed, with face hole and removable pillow.

Ideal for physical therapy and wellness centres. Adjustable back rest 0 to 45 degree Supplied with couch roll holder.

Product size: 183x61x75 cm Packing size: 188x17x66 cm Net/Gross weight: 28/31 kg Maximum load: 175 kg



### **FOLDABLE MASSAGE CHAIR**

#### • 44050 FOLDABLE MASSAGE CHAIR Comfortable foldable massage chair ideal for

physical therapy and wellness centres. Made in PVC vinyl with 5-6 cm foam thickness Metal frame

Packing size: 106x27xh 50 cm Net/Gross weight: 7/13 kg Maximum working load: 160 kg

WOODEN 3-SECTIONS

**ALUMINIUM 2-SECTIONS** 

27421





### 2 OR 3 WINGS WARD SCREENS WITH TREVIRA OR COTTON CURTAINS



- 45578 2 WINGS SCREEN white cotton cloth
- 45579 2 WINGS SCREEN light blue Trevira • 45580 3 WINGS SCREEN - white cotton cloth
- 45581 3 WINGS SCREEN light blue Trevira Exclusive 2 or 3 wings ward screens with

sturdy structure in oval tube (30x15 mm), painted with epoxidic powder metal

Light blue Trevira curtains or white washable cotton cloth. Equipped with 4 adjustable feet that

ensure increased stability. Class I Medical Device complying with

European Directive 93/42 Made in Italy.

### CABINETS FOR MEDICINES AND INSTRUMENTS - MADE IN ITALY



- 27898 VALUE CABINET 1 door
- 27899 VALUE CABINET 2 doors

Cabinets made of enamelled steel sheet with tempered glass doors. Hinged glass door with lock and key. Three stainless steel shelves adjustable in height. Delivered in kit form.

- 27900 VALUE CABINET 4 doors (hinged)
- 27902 VALUE CABINET 4 doors (2 hinged, 2 sliding) Cabinets made of enamelled steel sheet with 2 overlapped compartments. Upper compartment with 2 tempered glass door (hinged door 27900 or sliding door 27902), lock with key and 2 stainless steel, height adjustable shelves. Inferior compartment with 2 doors made of enamelled steel plate and 1 enamelled steel sheet shelf. Delivered in kit form.

### CABINETS WITH 1, 2, 4 DOORS AND WALL CABINETS



GIMA CABINETS Choice of cabinets with epoxy coated steel structure and tempered glass. Rack-mounted adjustable glass shelves. Rubber feet.

	,				
TECHNICAL SPECIFICATIONS	27901	27905	27903	27911	27912
Door:	1	2	4	2	2
Adjustable glass shelves:	3	4	3	2	2
Weight kg:	30	47	45	16	18
Size cm:	53x36xh 144	75x38xh 169	75x38xh 169	60x30xh 60	80x33xh 45



Hanging cabinet to keep medicine with 2 glass tempered doors and 2 tempered glass shelves adjustable on master rack to be hanged by two holes on the back

Hanging cabinet with 2 lockable doors.

removable shelves,

removable shelf.

27911

- 27901 CABINET 1 door
- 27905 CABINET 2 doors
- 27903 CABINET 4 doors
- 27911 WALL CABINET glass sliding door
- 27912 WALL CABINET painted door All cabinets are made in Italy.

DOCTOR CABINET



27903

EN 60598-1 EN 60598-2-4


> frame with fixed height 100 cm and flexible arm

MA ode	Product	Description	Size	Weight
920	DESK - with 2 drawers	Desk with 2 side drawers with locking top drawer and enamelled tubular steel frame	120x70x78	31
403	EXAMINATION COUCH	Single-hinged examination table with aluminium tubular frame. Comes complete with simulated leather mattress (grey), backrest adjustable throught different positions. Delivered in kit form.	176x60x78	22
989	COAT HANGER	Free-standing coat hanger with chromed steel frame with 8 knobs and umbrella holder		5
990	LIGHT	Not medical. 100 W. Aluminium tubular frame with 5 spoke base on 50 mm castors.  Adjustable height thanks to flexible arm. Lamp not included		3

# STACKABLE CHAIRS 45003 45006 • 45001 STACKABLE CHAIR - blue

- 45002 STACKABLE CHAIR grey
- 45003 STACKABLE CHAIR peach
- 45006 STACKABLE CHAIR with arms blue

Chromed steel frame, self-estinguishing plastic seat. Stackable up to 20 chairs. Weight 5 kg (45001-3), or 6.8 kg (45006). Self-estinguishing Class 1. Made in Italy.



**CHAIRS** 

Stainless steel white painted frame chair with grey padded seat and back. Stackable. Load 120 kg.

• 27933 CHAIR padded seat with armchairs Same as 27932 but with padded arm-rests. Made in Italy.

### S/S WASTE BINS WITH PEDAL

• 27984 WASTE BIN 9.5 I - with pedal - Ø 25xh 35 cm Made of enamelled steel with plastic inner bucket - weight: 2 kg 27985 S/S WASTE BIN 9.5 I - with pedal - Ø 25xh 35 cm Made of AISI 304 stainless steel with plastic inner bucket weight: 2 kg

• 27986 S/S WASTE BIN 12 I with pedal - Ø 32xh 36 cm Made of stainless steel AISI 430. Metal handle for easy emptying. Removable inner plastic bucket. Made in Italy.


 27983 S/S WASTE BIN 70 I with pedal - Ø 42xh 72 cm Made of stainless steel. Non-slip rubber pedal.

Two lateral handles avoid fingers pinching. Galvanized inner bucket with handle. Made in Italy.



27984 27985

### **DOCTOR CABINET**



### **DESK**

#### • 27919 DESK with 2 drawers

Desk with 2 lockable side drawers with strong structure in oval tube painted with epossidic powder, metal grey. White work top with rubber edge and round corner. Size 130x71xh 80 cm

Made in Italy



#### TROLLEY 27921 TROLLEY Structure in oval tube. painted with epossidic powder metal grey. White shelves with PVC edge, side-rail on 3 sides. 27921 Size 50x60xh 80 cm Maximum load: 30 kg Made in Italy

### ■ FOOT STOOLS - 1 OR 2 STEPS

- 27980 FOOT-STOOL one step aluminium
- 27982 FOOT-STOOL two steps painted

Mounting steps with painted tubular frame and plastic foot board. Load 90 kg.

Non slipping grey platform 40x20. Size: 40x51xh 25 (27980),

Made in Italy.



• 27978 FOOT-STOOL - one step

• 27979 FOOT-STOOL - two steps Structure in oval tube 30x15 painted with epossidic powder. Non slipping black platform.

Size: 45x26xh 20 cm 44x40xh 22/45 cm



• 27976 FOOT-STOOL - one step - disassembled

• 27977 FOOT-STOOL - two steps - disassembled

Structure made of chrome plated steel tube with rubber feet. Non slipping black plastic platform.

Size: 40xh 24 cm (27976) 40xh 42 cm (27977) Delivered in kit form.



### HEIGHT ADJUSTABLE STOOLS - MADE IN ITALY

# AVAILABLE IN 6 COLORS

- 45200 STOOL 1 black
- 45201 STOOL 2 blue
- 45202 STOOL 3 grey 45203 STOOL 4 - green
- 45204 STOOL 5 beige
- 45205 STOOL 6 apricot Padded simulated leather seat Ø 30 cm.
- Height adjustable 50 to 60 cm. Fire proof.

Metal base with 5 castors.







 27950 STOOL - feet • 27951 STOOL - castors Stainless steel seat AISI 304 Ø 32 cm. Height adjustable 47-59 cm (27950). Plastic base. Made in Italy.



32 cm. Height adjustable 47-59 cm. Aluminium base with feet. Made in Italy.



• 45210 STOOL - black • 45211 STOOL - blue

• 45212 STOOL - white Padded simulated leather seat Ø 36 cm.

Height adjustable 50-60 cm



• 45220 STOOL - black • 45221 STOOL - white

Plastic base with 5 castors.



• 27952 STOOL - grey Washable padded simulated leather seat Ø 31 cm. Height adjustable 50-62 cm. Plastic base with foot. Made in Italy.



• 27953 STOOL - grey Washable padded simulated leather seat Ø 31 cm. Height adjustable 54-66 cm. Plastic base with 5 castors. Made in Italy.

27953

### HEIGHT ADJUSTABLE STOOLS

### ERGONOMIC HEIGHT ADJUST. STOOLS

3 adjustments

Adjustment of height



- 45230 STOOL black
- 45231 STOOL white
- 45232 STOOL blue
- 45233 STOOL green • 45234 STOOL - beige
- Padded simulated leather seat Ø 33 cm
- Height adjustable 53 to 68 cm • 45228 CASTORS - spare
- 45240 STOOL black
- 45241 STOOL white
- 45242 STOOL blue
- 45243 STOOL green
- 45244 STOOL beige Padded simulated leather seat Ø 33 cm with backrest. Height adjustable 53 to 68 cm
- 45228 CASTORS spare

45250

- 45250 ERGO STOOL black
- 45251 ERGO STOOL white • 45252 ERGO STOOL - blue
- Ergonomically designed comfortable stool with saddle-shaped seat and height adjustment with a gas piston.
- Height adjustable 52 to 67 cm • 45228 CASTORS - spare
- 45260 ERGO B STOOL black • 45261 ERGO B STOOL - white • 45262 ERGO B STOOL - blue

45261

Ergonomically designed comfortable stool with saddleshaped seat. Three levers with a gas piston allow adjustment of height, backrest angle and seat. Height adjustable 62 to 78 cm

45228 CÁSTORS - spare

### OFFICE CHAIRS WITH OR WITHOUT ARMREST - MADE IN ITALY



armrests and polypropylene swivel base, movable backrest with permanent contact.

CUNEO CHAIR without armrest									
	Red	Grey	Blac	k	Blue	Any colour*			
Fabric	-	-	-		45060	45063			
Leatheret	te -	-	4506	55	-	45069			
C	CUNEO CHAIR with armrest								
Fabric	45070	45071	-		-	45073			
Leatheret	te -	-	4507	75	45076	45079			
Available in	30 days. N	1inimun	n orde	er i	2 pieces				
Select coloui	Select colour on www.gimaltaly.com and indicate with order								
Weight	Backrest height	hei	ght		Width	Depth			
12 kg	98/111 cn	n 42/52	2 cm		56 cm	49 cm			

TIT OIL VVIIIIO	
80	5083
	45081 45082
45082	45083

Superior quality chair with neat linens, upholstered seat and backrest for greater comfort, swivel base, armrests, permanent contact movement of the backrest

High density foam. UNI EN 1335/1/2/3. Maximum load: 110 kg.

CREMONA CHAIR with armrest							
	Red Grey					Blue	
Fabric	45083		45081		45082		
Weight	Backrest height	h	Seat v		th	Depth	
12 kg	90/107 cm			52 cm 58 cm		44 cm	

# 45091 45095 45092 45096

Quality chair with upholstered seat and backrest, permanent contact movement of backrest and swivel base. Maximum load: 110 kg. UNI FN 1335/1/2/3

1.	VARESE CHAIR without armrest								
		Re	d	Blue					
	Fabric	450	91	45092					
	VARESE CHAIR with armrest								
	Fabric	450	95	45096					
	Weight	Backrest height	Seat height	Width	Depth				
	11.6 ka	94/112 cm	46/59 cm	60 cm	47 cm				



- 45030 ISO fabric red
- 45032 ISO fabric blue
- 45035 ISO leatherette black
- 45036 ISO leatherette blue

Comfortable upholstered chair with 4 legged frame.

Can be used for patient and waiting rooms, with Cuneo, Cremona and Varese

Comfortable seat made of expanded polyurethane hit injected heliocell foams. Maximum load: 110 kg.

Weight	Backrest height	Seat height	Width	Depth
7 kg	82 cm	45 cm	53 cm	43 cm

### VISITOR CHAIRS EXECUTIVE CHAIRS



 45120 SALISBURGO executive swivel chair - leather - black

• 45122 SALISBURGO visitor cantilever chair - leather - black High and low back stylish executive

chairs. Refined lines and maximum comfort. 2 positions tilting movement, swivel base, polypropylene armrests, height adjustable by gas pump. Maximum load: 110 kg.

GIMA code	Weight	Backrest height	Seat height	Width	Depth
45120	17 kg	118/128 cm	43/53 cm	62 cm	55 cm
45122	14 kg	95 cm	45 cm	62 cm	55 cm



**ELITE EXECUTIVE CHAIR** Executive low-backed or high-backed armchair. Fabric or leatherette. Steel and chrome plated base and arms.

Height adjustable by gas pump. ELITE low-backed chair - 83-93 cm Red Black Beige Any colour Fabric 45124 Leatherette - 45127 45128 45132 ELITE PLUS high-backed chair - 101-111 cm Leatherette - 45136 -

'Available in 30 days. Minimum order 4 pieces. Select colour on www.gimaltaly.com and indicate with order Weight Backrest height Seat height 14.5 kg 83/93 cm 39/49 cm 51 cm Width \*Low-backed chair

### X-RAY ILLUMINATORS - LIGHT BOXES

GIMA light boxes are designed according to clinical standards for an extra white light for an accurate and precise reading of any detail. They incorporate a 3 mm acrylic screen compliant with safety norms (fuses, Schuko plug, green light On/Off, ...). Can be used on the table placed horizontally or vertically, depending on model or wall mounted. Body made of oven-fired epoxy powder coated aluminium and injected ABS (colour RAL 7035).

#### TECHNICAL SPECIFICATIONS

CE

Colour temperature: Cool white 6,500 °K Power supply: 230 V - 50 Hz (60 Hz available with surcharge) Protection fuse: 2x1A Bipolar light switch

Schuko plug with 2 m cable

All components UL, DVE, IMQ approved

Made in	Italy							
GIMA code	X-RAY ILLUMINATORS - LIGHT BOXES	External dimensions (cm) Length Height Depth Weight				Types		
27364	Light box 38x38 cm	43	43	12	6		1 panel	
27365	Light box 38x62 cm	67	43	12	8	-	1,5 panel	
27366	Light box 38x92 cm	97	43	12	11		2 panels	
27367	Light box 38x122 cm	127	43	12	14		3 panels	
27368	Light box 38x153 cm	158	43	12	18		4 panels	
27369	Light box 76x122 cm	127	2x43	12	28		2x3 panels	
27370	Light box 76x153 cm	158	2x43	12	36		2x4 panels	
27372	Light box 92x38 cm	43	97	12	11		2 panels vertical	
27373	Light box 122x38 cm	43	127	12	14		3 panels vertical	
27378 27379	Neon tube for 27364 Neon tube for 27366, 2733	72						


### VALUE FOR MONEY LIGHT BOXES



GIMA X-ray illuminators have been designed according to clinical recommendations for an extra white light to give an accurate and precise reading of any detail. Manufactured with metacrylate screen, and according to safety norms (fuses, Schuko plug, green light on/off, ...). The unique film gripping system gives full use of viewing area. White colour. Made in Italy. **AVAILABLE ALSO WITH** 

GIMA code	X-RAY ILLUMINATORS - LIGHT BOXES		Exter nensio Height	ns (cn	n) Weight		Types
	36.5x40 cm 36.5x40 cm - adjustable		43.5 43.5		5.4 5.4	_	1 panel 1 panel
	75x40 cm Round fluorescent light - spare	77	43.5	11	11		2 panels

### ILLUMINATED AND NOT ILLUMINATED OPTOMETRIC CHARTS



MONOYER MIXED DECIMAL ARMAGNAC CHILDREN ANIMALS 3m 3m 5.5m • 27381 • 27382 • 27380 • 27383 • 27384

See economic optometric charts at page 227.

GIMA luminous optotypes have been designed according to clinical recommendations for an extra white light to give an accurate and precise reading of any detail. Manufactured with acrylic screen, and according to safety norms (fuses, Schuko plug, green light On/Off,...)


ADJUSTABLE LIGHT

OPTOMETRIC CHARTS	Illuminated GIMA code	Not illuminated GIMA code
Armagnac - 5 m	27380	27390
Monoyer - 3 m	27381	27391
Mixed decimal - 3m	27382	27392
Children - 3 m	27383	27393
Animals - 5 m	27384	-
Spare Tube 700	27388	-

TECHNICAL SPECIFICATIONS					
Viewing Area: 24 x 62 cm 24 x 61 c					
External dimensions:	29.5x67.5x12 cm	29 x 66 x 2.5			
Weight:	6 kg	2 kg			
Power supply: 230 V - 50 Hz (60 Hz on request) only 2738					

Other specifications like x-ray illuminators 27364-72

### ■ LED ULTRA SLIM X-RAY ILLUMINATORS - DESKTOP AND WALL



colour temperature of 7,200°K for superior viewing and reading of radiography.

Complete elimination of light flickering and 3,500

cd/mg luminance for more uniform light diffusion. Frame in antiscratch anodized aluminium. Film gripping system incorporated.

Dimmer for luminance adjustment from 30% to 100%. - FAS: automatic switching on/off at the positioning/ removal of the film.

Economic advantages:

- LED life 80,000 hours, with low maintenance costs - low energy consumption compliant with European law Double support for horizontal or vertical wall mounting or desktop.

### Fully adjustable desktop model:

Position of panel can be totally adjusted:

- height adjustment 13 cm
- inclination 35° (+25°/-5°)
- vertical or horizontal positioning (44705 only)

- horizontal rotation 10° (270° for 44705 only)














All components UL, DVE, IMO approved

GIMA WALL LED SLIM VIEWERS External size - cm Weight

Light box 42x108 cm | 118 | 50.5 | 3

GIMA DESKTOP LED SLIM VIEWERS External size - cm Weight Switches

Length Height Depth kg

Length Height Depth kg

**TECHNICAL SPECIFICATIONS** 

46 50.5 3

viewing area

44701 Light box 42x72 cm 82 50.5 3

**44703** Light box 42x144 cm | 154 | 50.5 | 3

44705 Light box 42x36 cm x1 46x1 50.5 3

44706 Light box 42x36 cm x2 46x2 50.5 3

**44707** Light box 42x36 cm x3 46x3 50.5 3

Conformity to Electro Magnetic compatibility 2004/108/CE Conformity to EEC directive 2007/47 medical Device Class I

Colour temperature: Cool white 7,200°K Power supply: 110-230 V - 50/60 Hz Conformity to Low Voltage Directive 2006/95/CE

44700 Light box 42x36 cm



12

26



1 panel

2 panels

1 panel

2 panels

3 panels

4 panels

3 panels

### LED ULTRA SLIM OPTOMETRIC CHARTS

#### LED LITRA SLIM OPTOMETRIC CHARTS

New generation of optometric charts with same specifications as above X-ray illuminators. Made in Italy,

GIMA	LED ULTRA SLIM OPTOMETRIC CHA		RTS - WALL
code		Viewing area	External size
44710	Armagnac - 5 m	25.5x63 cm	34x72x4 cm
44711	Monoyer - 3 m	25.5x63 cm	34x72x4 cm
44712	Mixed decimal - 3m	25.5x63 cm	34x72x4 cm
44713	Children - 3 m	25.5x63 cm	34x72x4 cm



### AIR COMPRESSION THERAPY SOLUTIONS

All human body is supplied by peripheral circulation of blood and lymph


Our systems help patients to recover from their disease by improving blood and lymph circulation and metabolism.

Our systems consist of air chambers and an air pump offering air compression massage to legs, arms or waist.



 28430 MAYLEA GIMA DIGITAL COMPRESSION MASSAGE with 2 legs (98x38 cm) - 4 chambers, 1 single and 1 double hose and 2 plastic feet guides

Skip function to choose directly the parts to be massaged. Fully digital management. Autocalibration functions. Manual: GB, FR, IT, ES. This system can operate with 3 compression modes (A, B, C).



digital timer (10, 20, 30, 40 min) digital pressure gauge (10~180 mmHg)

one touch connection hose plug body size: 190x250x210 mm - bodý weiaht: 3 ka

(28437)

• 28435 LFG 93x32 cm

• 28434 LEG EXTENSION ZIPPER - 10 cm extra extension Waist cuff 130x38 o

• 28440 DOUBLE HOSE - to use two leg cuffs at the same time - spare

• 28436 ARM CUFF unique size - 86x29 cm



#### • 28441 MK400L PROFESSIONAL COMPRESSION SYSTEM with 2 legs (XL), and 2 single hoses

MK400L is a professional air compression therapy system with essential functions for different kinds of patients. This system provides 3 compression modes (wave, squeezing, double squeezing), reverse compression settings, skip functions to select directly part to be pressurized and compression speed controller. Touch key pad display. Manual: GB, IT, ES.

#### TECHNICAL SPECIFICATIONS

Pressure range: 10~200 mmHg Use time: 1~90 minutes Automatic pressure detection Body size: 415x310x160 mm Operating voltage: 220-240 V, 50/60 Hz, 50 VA - Body weight: 6.5 kg



#### Medical indications

- Lymph edema
- Post-paralytic
- Limb convulsion
- Venosclerosis Chronic venous insufficiency (CVI)
- Post-mastectomy
- Post-trauma Spinal cord injury
- Varicose veins
- Sciatica
- Sprains
- Diabetes
- Arterial insufficiency

- Home care indications DVT (Deep Vein Thrombosis) Lymph edema
  - Diseases caused by interrupted blood circulation
  - Cellulitis fat dissolution
  - Pregnant woman's limb treatment
  - Benumbed feet or hands
  - · Cold feet or hands
  - Settlement of stress
  - Exercise effects
  - Insomnia
  - · Healthier body and elastic skin · Old age, weakness and fatigue





• 28442 LEG CUFF L - 6 CHAMBERS - spare • 28443 LEG CUFF XL - 6 CHAMBERS - spare

• 28444 LEG EXTENSION ZIPPER XL - 10 cm extra extension for 28443 • 28445 SINGLE HOSE - spare

• 28446 ARM CUFF - 6 CHAMBERS - universal

• 28447 WAIST CUFF - 6 CHAMBERS - min-max girth 94-125 cm A mode 

The selected air chamber inflates and deflates by one chamber sequentially from foot up to thigh. B mode (Squeezing) After all the selected air chambers inflate sequentially from foot up to thigh the inflated

#### chambers deflate at once. C mode (B mode two times +

Reverse A mode 1 time) The selected air chambers inflate and deflate by two chambers sequentially from foot up to thigh Reverse setting: it allows to change automatically the selected mode to reverse mode




_										
1	Cuff		Leg dimension (cm)							
	Size	Α	В	c	D	E	F	G		
	L	64,0	49,5	40,5	34,5	75,0	38,0	28,0		
	XL	73,5	55,0	42,0	35,5	85,0	43,0	31,0		

### CR200 - PROFESSIONAL TECAR THERAPY

#### 28364 CR200 TECAR THERAPY

Diathermy, also known as TECAR Therapy (meaning Capacitive and Resistive Energy Transfer), is a therapy stimulating the physiological healing process by accelerating the recovery time of motor function. Diathermy stimulates tissues endogenous heat production through the interaction of electromagnetic field and tissue. The heat is increased in a uniform controlled way. The electromagnetic interaction results in a ionic flow and consequently increases blood flow in the treated area. This process stimulates endogenous substances release (in particular cortisol and endorphins) that are necessary to reduce inflammations, pain and edemas. The new CR200 resistive/ capacitive diathermy is a modern and highly performing device easy to use by professionals. Preset programmes help use the device from the start. Moreover the device can set parameters (power, time therapy, capacitive/resistive modes) according to therapeutic needs. It allows the memorization of customized programmes. In this way patient protocols are easily consulted by therapists at any time. Equipped with a wide graphic display showing therapy parameters and different working modes. Selectable software language (GB, FR, IT, ES).

#### • 33251 TECARTHERAPY CONDUCTIVE CREAM 1 I Moisturizing conductive cream ideal for Tecar therapy




#### Capacitive mode

Electrode coated with ceramic material (mobile) and return plate (fixed). Indicated especially for soft tissues (muscle mass and lymphatic/vascular system) Benefits: specific intervention easy control of the treated area.

tissues with greater resistance (bones joints, tendons, ligaments, cartilages) Renefits: high level of diathermy: chronic diseases with fibrosis and degeneration

#### STANDARD ACCESSORIES



Non isolated electrode (mobile) and return plate (fixed). Indicated especially for

- 1 multi-function probe for capacitive and resistive mode 2 electrodes Ø 35 mm (1 resistive + 1 capacitive) with 9.61 cm<sup>2</sup> effective working area 2 electrodes Ø 60 mm (1 resistive + 1 capacitive) with 28.26 cm<sup>2</sup> effective working area 1 integrated support for probe 1 steel plate
- Bottle of conductive cream 1 kg User Manual: GB, IT, ES, FR



Skeletal-muscle pathologies

Osteoarticular pathologies Muscle contractures, bruise, muscle

stretching, sprain, haematomas, ten-don injury, superficial massage, deep

massage, muscle recovery, muscle

10 SPORT PROGRAMMES

#### 24 REHAB PROGRAMMES knee arthrosis, arthrosynovitis, bursi-

tis, cervicalgia, patellar chondropathy, bruises, coxarthrosis, sprain, articular pain, oedema, epicondylitis, epitro-chleitis, spinal disk hernia, plantar fasciitis, gonarthrosis, ACL, lymphedema back pain, meniscopathy, neuropathy, periarthritis, muscle sprain, acute

### **TECHNICAL SPECIFICATIONS**

Power supply: 100-240 V, 50/60 Hz Max power consumption: 300 W (50 ohm load) Carrier frequency: 485 kHz

Adjustable power: 0-100%

sprain

# I-TECH LA 500 LASER THERAPY

Power supply cable

#### • 28410 I-TECH LA 500 LASER THERAPY

Laser therapy device equipped with a new probe with an emitting diode that allows beam laser application directly to the treatment area.

I-TECH LA 500 is able to stimulate deep tissues by promoting a rapid cellular regeneration thanks to 500 mW power output and 810 nm wavelength. Professional user can adjust power output therapy time and operation mode (continuous or

I-TECH LA 500 guarantees a fast intervention for the treatment of inflammatory and degenerative pathologies in orthopedic, neurologic and dermatologic area.

Thanks to its high performance healing time is significantly reduced. Supplied with probe, belts for probe fastening and safety glasses.

Manual in: GB, IT, FR, ES.

#### LASER THERAPY

The laser therapy uses the effects of energy produced by the light source penetration into the tissues.

Riochemical reactions are activated across the cellular membrane

- It has been observed that right doses of Laser light can stimulate cellular functions, in particular into the cells damaged by functional deficits. The main effects of Laser therapy are:
- improved blood flow; capillary and artery vasodilatation that results in local heat increase
- biostimulation: accelerated tissues repair, stimulation of protein synthesis. ADP production, electrolyte changes in the intra- and extra-cellular fluids and mitosis of fibroblasts, increase of collagen and elastin
- anti-inflammatory effect
- anti-oedema effect: lymphatic drainage stimulation



#### **TECHNICAL SPECIFICATIONS**

Power supply: 230 V, 50-60 Hz, ±10% Maximum laser output: 500 mW ± 20% Adjustable laser power output: 0%-100% Laser diode wavelength: 810 nm Beam divergence angle: 260 mrad Continuous output emission Fixed emission frequency

Fixed width duration Continuous or pulse mode of operation Pointing red light
Diode probe (with reserved connection)
Adjustable therapy time: 0-30 minutes
Diameter of laser beam: <10 mm

#### MAIN TREATMENTS

Polyarthritis - Epicondylitis/Epitrochleitis - Knee pain - Myositis - Oedema - Sciatalgy/Lumbago - Articular sprains - Chronic Tenosynovitis -Muscle strains - Overcharge pathologies - Ecchymosis - Bursitis - Degenerative arthritis - Adhesive capsulitis - Arthrosis pains - Post-traumatic disorders

### I-TECH UT2 - PROFESSIONAL ULTRASOUND THERAPY



#### APPLICATIONS

Tendinitis - Bursitis/Capsulitis - Hematomas and tissue reconstruction Muscle contractures/Cramps - Neuralgias - Periarthritis - Cervicalgias -Sciatalgy/Lumbalgy - Carpal tunnel syndrome - Epicondylitis/epitrochleitis Contusions/sprains - Chondropathy - Massage - Arms/abdomen/legs/gluteus cavitation - Acne

#### STANDARD ACCESSORIES

- 1 handle with 5 cm<sup>2</sup> probe 1 handle with 1 cm<sup>2</sup> probe 1 power supply cable
- 1 power supply 15 V, 3 A 1 ultrasound gel

- 28358 I-TECH UT2 ULTRASOUND THERAPY 2 probes Professional ultrasound device equipped with 2 handles respectively with 5 cm<sup>2</sup> and 1 cm<sup>2</sup> probe. Its equipment and parameters setting allow high performance suitable for professional users.
- It is provided with 10 preset programmes within which professional user can adjust following parameters:
- Frequency (1 or 3 MHz)
- Effective intensity (up to 3 W/cm²)
- Duty cycle (10%÷100% stepping 10)
- Therapy time (up to 30 minutes)

#### **TECHNICAL SPECIFICATIONS**

Operating voltage: 100-240 V, 47/63 Hz, 1.35A, output 15V 3A max Ultrasound frequency: 1 MHz  $\pm$  10% and 3 MHz  $\pm$ 10% Output power: 0.5-10 W ± 20% when duty cycle ≥ 80% for 5 cm² ultrasound head

0.5-15 W ±20% when duty cycle ≤ 70% for 5 cm² ultrasound head 0.1-2 W  $\pm 20\%$  when duty cycle  $\geq 80\%$  for 1 cm² ultrasound head 0.1-3 W ±20% when duty cycle ≤ 70% for 1 cm² ultrasound head

Max Power: 3 W/cm² ± 20% (1 MHz); 3 W/cm² ± 20% (3 MHz)

Working frequency: 100 Hz Duty cycle: 10%-100% stepping 10%

Maximum adjustable therapy time 30 minutes

Effective radiating area 5 cm<sup>2</sup> ± 20%; 1 cm<sup>2</sup> ±20% Collimated beam type

Ultrasound head (material) aluminium Direct contact and water immersion use

Size: 350x186x86 mm

### GIMA UT AUTOMATIC: ULTRASOUND THERAPY UNIT



Treatment time: programmable from 1 to 30 minutes

Selectable pulse/time%: 10%-20%-30%-50%-100% Pulse frequency: 2 pulses/second Max. intensity: 3 W/cm Operating voltage: 115/230 V - 50/60 Hz - switchable Electrical safety class I BF - Norms: EN 60601, EN 60601-2-5

• 28310 GIMA UT AUTOMATIC ultrasound therapy unit without head







Gima UT is recommended for: ultrasound lipoclasia, sports medicine, arthritis, arthrosis, neuralgia and backpain. Supplied with power cord and user's manual. Made in Italy.

- 28312 1 MHz ULTRASOUND HEAD Ø 60 mm
- 1 MHz frequency is recommended for physiotherapy. • 28313 3 MHz ÚLTRASOUND HEAD Ø 60 mm
- 3 MHz frequency is recommended for aesthetics

### GIMA UTC 2: COMBINED ULTRASOUND AND ELECTROTHERAPY UNIT

### • 28301 GIMA UTC 2 AUTOMATIC

UTC 2 is a programmable driver unit for ultrasound transducers with working frequencies from 1 up to 3 MHz together with 2 channels of electrotherapeutic current. UTC 2 delivers continuous or modulated ultrasound with programmable intensity and delivery time, suitable for thermo therapeutic deep treatment of different pathologic conditions. UTC 2 transducer handpieces can be used under water. UTC 2 delivers Dyadinamic, Faradic, Galvanic, Impulsive, T.E.N.S. and Bipolar electrotherapeutical currents.

- high brightness graphic touchscreen display
- intuitive icons interface
- controls of unit by multifunction knob, keys or touchscreen
- possibility to upgrade - wide range of preset protocols
- customized programmesmulti frequency handpieces
- automatic identification of the connected accessory
- continuous or pulsed delivery
- combined with electrotherapy
- sequence of treatment phases planning for each channel - independent channels - safety control blocks the output current in case of accidental
- disconnection of electrodes. 6 language software: GB, FR, IT, ES, DE, PT. Made in Italy. 28302 1-3 MHz ULTRASOUND HEAD Ø 15 mm

- 28303 CONNECTING CABLE for electrotherapy spare
- 28304 CLIP RUBBER ELECTRODES 120x80 mm box of 12 • 28305 CLIP RUBBER ELECTRODES 45x60 mm - box of 12
- 28323 VELCRO ELASTIC BAND 100x8 cm spare

28301



#### TECHNICAL SPECIFICATIONS

Output frequency (MHz): 1.0 to 3.0 Max intensity (W/cmq): 3.0 ET channels: 2 Electrical input power (VA): 70

Max output direct current (mA): 30 Max output pulse current (mA): 70 Max output voltage (Vdc): 100 Power supply (Vac/Hz): 90-240 / 50-60

#### STANDARD ACCESSORIES

1-3 MHz ultrasound head Ø 35 mm

Connecting cable for electrotherapy 1-2 (28303) 4 rubber electrodes 120x80 mm: 4 rubber electrodes 45x60 mm

3 velcro elastic belt: 8x40, 8x60, 8x100 cm Power cable 2 m

28401

• 28381 IONOPHORESIS KIT - spare

4 connection cables (8 connectable electrodes)

maximum intensity 240 mApp, with 1 mA step regulation

(1 elastic band, 2 silicone conductive electrodes, 2 sponges)

Kit of pre-gelled self-adhesive electrodes (square, rectangular, round)

Electrode position manual and user manual (GB, FR, IT, ES). On request DE

Internal Ni-Mh rechargeable battery pack and battery charger

• 28351 PRE GELLED ELECTRODES 40x40 cm with cable - box of 4

28373 PRE GELLED ELECTRODES 45x80 cm with cable - box of 4

STANDARD ACCESSORIES

Ionophoresis kit: elastic belt, 2 silicone electrodes, 2 sponges, carrying bag (28402 only)

C €0476

### T-ONE COACH AND T-ONE MEDI SPORT - 4 CHANNELS ELECTROTHERAPY

Size: 150x90x35 mm

• 28401 T-ONE COACH ELECTROTHERAPY - 4 channels A high performant muscle stimulator designed to improve your physical activity. Thanks to easy to use programs, it represents the ideal device for not professional athletes and for sports lovers in general. It is not only a muscle stimulator equipment. It is supplied by TENS protocols for pain relief and injuries recovery.

• 28402 T-ONE MEDISPORT ELECTROTHERAPY - 4 channels Professional equipment specifically designed for sport specialist users. Thanks to its muscle stimulation specialized programs it improves the sport performance. It is not only intended to increase your strength, it helps the recovery of sport injuries with specific treatment protocols. Main features

- constant current generator (can guarantee a constant current even when skin condition changes, the device automatically stops in the event of accidental electrodes disconnection)
- four independent channels unit (up to 8 connectable electrodes) personalized programs for man and woman - compensated biphasic square wave: current quantity from positive pole to negative one is constant to avoid polarization effect:
- monophasic wave generator (only for iontophoresis programs)
- 2+2 users programs
- backlight graphic colour display
- user feedback: the device recognizes patient connection
- soft-touch easy to use keyboard
- on-line 5 languages guide (GB, FR, IT, ES, DE) on display for fast instructions
- 4,8 V rechargeable battery pack

BEAUTY	REHA	TENS	NEMS	MEM	2+2
28401 and 28402	10 programmes only 28402	16 programmes 28401 and 28402	14 programmes 28401 and 28402	Only 28402	28401 and 28402
Toning up lor Definition lor Modelling MM Microlifting H8 Lipolysis abdomen Oe Lipolysis thighs Te Lipolysis glutei and hips Te Lipolysis glutei and hips At	onophoresis M inophoresis H IENS microcurrent aematomas edema ens sequential ens Burst trophy prevention trophy	Tens endorphinic Tens max values Inflammatory Neck pain Backache/Sciatic pain Sprains/Bruise Vascularization Muscle relaxant Hand and wrist pain Plantar stimulation Epicondylitis Epitroclea Periarthritis Tens Burst Microcurrent	Resistance strength Basic strength Fast strength Explosive strength Deep capillarization Muscle recovery Agonist/Antagonist Sequential tonic contractions Sequential phasic contractions Muscle recovery	Tens mem 2 Tens mem 3 Tens mem 4 Tens mem 5 NEMS mem 1 NEMS mem 1 NEMS mem 2 NEMS mem 3 NEMS mem 4 NEMS mem 4 NEMS mem 4 NEMS tens tens tens tens tens tens tens tens	Tens rapid Tens endorphinic Firming up Toning up Definition Modelling Microlifting Muscle relaxant Massage Capillarization Only 28402 Inflammatory Resistance, Resistance strength Basic strength, Fast strength Explosive strength, Hypetrophy Face Microlifting Handy Trode Perseat Microlifting Handy Trode Decolleté Microlifting Handy Trode Forewhealt Handy Trode Forehead Wrinkles Handy Trode Forehead Wrinkles Handy Trode

# MIO-SONIC ULTRASOUND THERAPY DEVICE - 9 PROGRAMS

28309

Adhesions

Brachialov

Capsulitis

Stretch marks

Epycondilitis

Bursitis

Algodystrophy

### 28309 MIO-SONIC ULTRASOUND THERAPY

Innovative and high performance device both for home use and professional use. It combines compactness and high performances in a small , light and easy to use applicator. The lightness and handiness allows a continuous use without any difficulty.

Mio Sonic can be used for the following applications:

- · pain therapy;
- sport injuries;
- · aesthetic treatments. Supplied with gel bottle, carrying and storage bag, medical power supply

and multilanguage manual: GB, FR, IT, ES. On request DE.

Periarthritis Tendinitis Neuralgias Pubalgy Tallonitis Cervicalgias Sciatalgy Contusions Sprains Chondropathy Cruralgy Microlifting

### **TECHNICAL SPECIFICATIONS** 9 programs;

1 MHz ultrasound, maximum output power 6.4 W, maximum intensity 1.6

Collimated ultrasound beam for an optimal penetration beam; 3 ultrasound beam intensity levels 0,08 W/cm2 (low) - 0,8 W/cm2 (medium) -1,6 W/cm2 (high); Medical power supply; Direct contact device (not suitable for water immersion) Size-weight: 200x47x69 mm - 190 g

Venous stagnation



Phonophoresis

**TREATMENTS** Arms cavitation Abdomen cavitation Muscular contracture Cramps Massage Limb cavitation Gluteus cavitation Drainage Modelling Lumbalgy Carpal Tunnel Hematoma Oedema Acne

# ORTHQMAG LOW FREQUENCY MAGNETOTHERAPY - 2 PROGRAMMES

Biostimulation

28298

28402

• 28298 ORTHOMAG low frequency magnetotherapy kit A professional low frequency magnetotherapy (PEMF) device that can be used everywhere. Lightweight, comfortable and flexible, fitting your body shape. Battery powered for dynamic use or power socket for use at home or in the office. Orthomag includes 2 programmes (75 Hz and 50 Hz) indicated for bone tissue pathologies,

joint diseases and pain management. Up to 25 Gauss per programme. Supplied with rechargeable lithium battery 3.7 V 900 mAh, wall mount charger (cable 1.5 m), universal flexible applicator (cable 1.5 m), test emission magnet, 2 elastic bands (S and L), carrying bag, manual (GB, FR, IT, ES). On request DE.



28296

■ MAG 700 LOW FREQUENCY, HIGH INTENSITY MAGNETOTHERAPY

• 28296 MAG 700 MAGNETOTHERAPY - 1 channel New portable magnetotherapy ideal for home therapy. MAG 700 offers a high level of professional performances and it's indicated for several pathologies. It allows comfortable home therapy through its basic accessories. MAG 700 has 7 pre-setted programmes for the treatment of several pathologies, 3 programmes identified by the working frequency (from 5 to 20 Hertz) and an Autoscan programme with

continuous frequency variation for the treatment of both hard and soft tissues at the same time. Possibility to adjust the magnetic field intensity for all

programmes up to 70 Gauss. Working frequencies are between 5 and 100 Hertz. Supplied with elastic therapeutic belt with 2 solenoids, power supply, carrying bag and manual (GB, FR, IT, ES).

11 PROGRAMMES 7 pre-set programmes 3 working freg.+autoscan Osteoarthritis 5 Hz Osteoporosis 10 Hz Arthritis 20 Hz Fractures Articular pain

Muscle pain

Anti-inflammatory

MAG 2000 LOW FREQUENCY, HIGH INTENSITY MAGNETOTHERAPY

28300 MAG 2000 MAGNETOTHERAPY - 2 channels - 300 Gauss
28311 **C** € 0476 28311 MAG 2000 PLUS MAGNETOTHERAPY - 2 channels - 400 Gauss Ideal devices for domiciliary and professional magnetotherapy. 35 programmes: 20 pre-set programmes for the treatment of 180x110x50 m several pathologies, 14 programmes identified by the working frequency (from 1 to 100 Hertz) and an Autoscan programme with continuous frequency variation for the treatment of both hard and soft tissues at the same time. MAG2000 PLUS has also the possibility to store 10 user memories choosing the frequency up to 120 Hz, intensity and therapy time: a great possibility for the professional user who need to use a specific treatment for each patient. Possibility to set the intensity of magnetic

field for all the programmes up to 300 Gauss (150 Gauss each channel) for MAG 2000 or up to 400 Gauss (200 Gauss each channel) for MAG 2000 Plus to easily treat different body parts through elastic therapeutic belt with 3 solenoids.

Operating power 110-240 V.
Supplied with elastic therapeutic belt with 3 solenoids, couple of professional solenoids (28311 only), power supply, carrying bag and manual (GB, FR, IT, ES). On request DE

• 28299 ELASTIC THERAPEUTIC BELT - spare

Belt with cable with 3 solenoids for low frequency treatments.

• 28316 COUPLE OF PROFESSIONAL SOLENOIDS Couple of professional solenoids Ø 11 cm for high intensity therapy.

35 PROGRAMMES (28300) - 45 PROGRAMMES (28311) 20 pre-set programmes 14 working freg.+au Osteoporosis Intercostal Contusion Arthrosis 3 Hz Lumbalay Arthritis Lumbar pain 5 Hz Cervical arthrosis Shoulder arthrosis 10 Hz 80 Hz Articular pain Knee arthrosis 15 Hz 90 Hz Periarthritis 100 Hz 20 Hz Cervical pain Sprains Coxarthrosis Muscular Atrophy Fractures 40 Hz **Epicondylitis** Muscular contracture 10 memories (28311 only) Epitrocleitis

Couple of

### OSTEOMAT 2000: MATTRESS FOR LOW FREQUENCY MAGNETOTHERAPY TREATMENTS

 28307 OSTEOMAT 2000 MATTRESS FOR MAGNETOTHERAPY Osteomat has 4 sectors (2 active and 2 passive) linked with velcro straps to create a real mattress.

The two active sectors allow the biostimulation of a wide body part through 6 professional solenoids. The two passive sectors create a planar surface where patient can lay down. Each active sector can be personalized according to

therapeutic needs by choosing solenoids positions.

The basic configuration of Osteomat 2000 stimulates the body zones (shoulders, column, pelvis) that are more affected by bone mass reduction. This is typical of osteoporosis disease Suitable for MAG 2000 and MAG 2000 PLUS programmes.



### MT BASE: MAGNETOTHERAPY

### • 28321 GIMA MT BASE PLUS - magnetotherapy

Magneto Base Plus + is an ELF low frequency magnetotherapic unit designed for domiciliary applications. The most important effects of the magnetic fields are: Antiedemigen / Analgesic / Antiphlogistic / Regenerative and have applications in: traumatology, rheumatology, angiology, neurology, dermatology, endocrinology. The magnetic field produced is impulsive. The internal generator produces square waveform electrical current with frequency varying from 10 to 99 Hz and impulse time varying so to obtain a field's intensity determinated from 10 to 80 Gauss. Internal sound sensor of magnetic field and safety system in case of short-circuit. Two transducers can be connected at the same time (the field produced by each transducer is half of the total).

- 28322 PLATE TRANSDUCER 70x120 mm spare • 28323 VELCRO ELASTIC BAND 100x8 cm - spare
  - STANDARD ACCESSORIES

Power cable 2 plate transducers 80 gauss - 120x70 mm
ABS carrying case
1 velcro elastic band 60xh 8 cm
Manual (GR. IT)

1 velcro elastic band 100xh 8 cm



#### **TECHNICAL SPECIFICATIONS**

Intensity of magnetic field: 80 Gauss (8mT) Waveform: square Max. ratio emission/pause: 50% Operating voltage: 230V/50-60 Hz Selectable magnetic field from 10 to 80 Gauss Size: 193x138xh 68 mm Weight: 1 kg Selectable frequency; from 10 to 99 Hz Safety class; II BF - Norms; EN60601-1 (CEI)

### IONO BASE PLUS - GALVANIC IONOPHORESIS

### • 28306 IONO BASE - PLUS - 2 channels

Local administration of medicines by lonophoretics, electric osmosis and treatment of hyper hydrosis (sweating disease) and cellulitis. Current generator for hydro galvanization, aesthetic shaping and against cellulitis slight blemish. Microprocessor controlled, with selection of parameters and internal programs. Simple and safe to use, although it maintains characteristics of a professional equipment. Made in Italy.

- 28335 RUBBER ELECTRODES 50x50 mm box of 10
- 28336 SPONGE BAGS for electrodes 50x50 mm box of 10 TECHNICAL SPECIFICATIONS

Operating Voltage: 230 V - 50/60 Hz Size: 138x68x193 mm Absorbed Max Power: 10 VA Max Output Current: 20 mA Safety class: II BF - C & 93/42/EEC. Made in Italy.







Internal

spring

allows

different

positions

28653

balanced

28652

### INFRARED THERAPY LAMP - 250 W

### • 28652 INFRARED THERAPY LAMP - 250 W - desk with table clamp

• 28653 INFRARED THERAPY LAMP - 250 W - trolley

The infrared light relieves the suffering caused by sore muscles and joints ankylosis. The comfortable warmth created by infrared light penetrates deep into the skin, stimulates blood circulation and warms the muscles. While the muscles are relieved. they automatically stretch and relax. At the same time, the blood circulation helps your body get rid of impurities and guickly sends oxygen-rich blood to stressed or aching muscles, causing an effective pain

relief. Class II Electric. 28654 SPARE BULB - 250 W



# INFRAREX: THERAPEUTIC HEATING DEVICE

MIM5AL

- 28650 INFRAREX 230 V 50/60 Hz
- 28651 SPARE BULB 7.5 W

Infrarex is a modern scientifically electronic therapeutic heating device which provides deep, infrared heat that can penetrate far below the surface of the skin to produce a shooting, comforting effect upon the nerves. It relieves muscular tension, reduce inflammation and provides pain relief without medication for many conditions such as: arthritis, bursitis, sinusitis, tennis elbow, back ache, neuralgia, muscular pains, aches, sprains, and other musculoskeletal aches. Infrarex provides pain relief without medication, you will experience pain relief within 10-15 minutes. No concern for side effects, simple to be used.

### MOMERT INFRARED LAMP 100 W

#### • 28648 MOMERT INFRARED LAMP 100 W

The lamp's deep penetrating infrared heat relaxes the muscles and stimulates the blood circulation. The pleasant heat expands the capillary veins, resulting in a better oxygen and nutrition supply to the tissues. Can be used for rheumatic diseases, allergies, cold diseases, alternative medicine (detoxification), beauty care. Operating voltage: 230 V - 50 Hz. Multilanguage manual and box (GB. FR. IT. ES. PT. DE. HU. SK. LV. CZ. EE. PL. RU. BG).

• 28649 SPARE BULB - 100 W Philips



### SMART TENS - EMS

#### • 28355 SMART TENS

TENS is a therapeutic technique mainly used for analgesic purposes in physiotherapy. Suitable for a wide variety of pain therapies: acute or chronic pain, muscular pain, post-operative pain and also pains caused by pregnancy. It's usually divided according to its action mechanism

in tens conventional, tens endorphinic, tens sequential, tens maximum value, tens Burst.

EMS is a stimulating technique activating muscular contractions through electrical impulses.

As in TENS stimulation, impulses are applied to patient through electrodes placed next to the muscles to be treated. In physiotherapy EMS is used for post-trauma and post-operative muscular rehabilitation and also as a complementary aid in sports activity and aesthetic treatments.

Basic programmes used in TENS treatments together with EMS classic protocols are combined in this product, SMART TENS offers a wide possibility to treat acute and chronic pains (TENS) and muscular strengthening and stimulation (EMS). Supplied with 2 connection cables for electrodes, 4 pre-gelled electrodes with cable, belt clip, 4xAAA size batteries, user

manual (GB, FR, IT, DE, ES) in a carrying bag.

**TECHNICAL SPECIFICATIONS** 

combined electrotherapy unit with 2 independent channels compensated biphasic square wave: current quantity from positive pole to negative one is constant to avoid hazardous thermal effect of polarization

keyhoard

- 6 TENS stored programmes 5 EMS stored programmes
- 2/120 Hz waveform frequency
- 60 mA maximum intensity size: 68x110x31 mm
- 1 EMS free programme 50/400 µs width impulse
  - power supply 4 batteries AAA Size

28355

On line quick

### weight: 85 g (without batteries)

1 TENS free programme

### GIMA TENS - ELECTRICAL MUSCLE STIMULATORS Size: 162x10.7x120 mm LCD size: 31x37 mm



### • 28342 GIMA 9 TENS - 2 channels

Pocket TENS with 9 programmes and 2 channels. 9 adjustable

Relieves muscle pain and stimulates blood circulation. Frequency: 2-80 Hz.

Supplied in a nylon bag with 2AAA batteries and 4 electrodes.

- 28351 GELLED ELECTRODES 40x40 mm pack of 4 spare
- 28343 CABLES pack of 2 pcs spare

4 CHANNELS 30 PROGRAMME Weight: 200 a Manual: GB, FR, IT, ES, PT.

#### • 28365 GIMA 30 TENS - 4 channels

Portable electrical muscle stimulator with 4 channels and 30 programmes. Backlit LCD display. Frequency: 2 to 2000 Hz

- Supplied in a nylon bag with 4AA batteries and 8 electrodes
- 28366 ELECTRODES pack of 8 spare
- 28367 CABLES pack of 4 pcs spare
- 28368 AC ADAPTOR 230V 50Hz

### DISPOSABLE GELLED ELECTRODES FOR ELECTROTHERAPY



**DISPOSABLE GELLED ELECTRODES WITH CABLE - latex free** High material flexibility allows easy application of electrodes on treated areas. Solid gel maintains the electrode adhesion and conductivity unchanged during procedure. The electrodes are equipped with 10 cm long cable, with 2 mm socket.

- 28384 GELLED ELECTRODES with cable 45x35 mm bag of 4 • 28351 GELLED ELECTRODES with cable 40x40 mm - bag of 4
- 28372 GELLED ELECTRODES with cable 46x47 mm bag of 4
- 28373 GELLED ELECTRODES with cable 45x80 mm bag of 4



DISPOSABLE GELLED ELECTRODES AND ADAPTORS - latex free High material flexibility allows easy application of electrodes on treated areas. Solid gel maintains the electrode adhesion and conductivity unchanged during procedure.

- 28387 GELLED ELECTRODES 45x35 mm bag of 4 • 28388 GELLED ELECTRODES 46x47 mm - bag of 4
- 28317 GELLED ELECTRODES 45x80 mm bag of 4 • 28390 2 mm CLIP ADAPTORS - black - box of 10
- 28391 2 mm CLIP ADAPTORS red box of 10
- 28392 4 mm CLIP ADAPTORS black box of 10
- 28393 4 mm CLIP ADAPTORS red box of 10



# ■ MIO-CARE - 2 CHANNEL TENS

• 28370 MIO-CARE TENS - 20 medical programmes • 28376 MIO-CARE FITNESS - 55 programmes (20 medical + 15 beauty + 20 fitness programmes) • 28377 MIO-CARE PRO - 63 programmes

(14 medical + 15 beauty + 21 fitness + 13 free memories)

- 2 independent channels stimulator
- compensated biphasic square wave: avoids hazardous thermic effect of polarization
- easy to use, digital keyboard
- remaining therapy time and programmes
- instruction shown on graphic display - internal rechargeable battery pack
- maximum intensity 200 mAh
- compliance with 93/42/EEC MDD

Supplied in a carrying bag with 2 connection cables with splitters, user manual (GB, FR, IT, DE, ES), 8 adhesive pads, internal rechargeable battery with battery charger.

• 28372 GELLED ELECTRODES with cable 46x47 mm - bag of 4

• 28373 GELLED ELECTRODES with cable 45x80 mm - bag of 4



#### 14 MEDICAL PROGRAMMES (all)

Tens conventional (rapid) Tens endorphinic (delayed) Tens maximum values nflammatory Neck pain/cervicogenic headache Backache/sciatic pain Sprains/bruises

Plantar stimulation Epicondylitis Enitroclea

+6 MEDICAL PROGRAMMES (28370, 28376)

Haematomas Atrophy (trophism rehabilitation) Hand and wrist nain

Vascularization

Muscle relaxant

Stress incontinence

Firming up - upper limbs and trunk Firming up - lower limbs

Toning up - upper limbs and trunk Toning up - lower limbs Definition - upper limbs and trunk Definition - lower limb Modelling

Lipolysis - abdomen

#### 15 BEAUTY PROGRAMMES (28376, 28377)

Lipolysis - thighs Capillarization

Warming up Lipolysis - glutei and hips Resistance-upper limbs and trunk Resistance-lower limbs Resistant strength - upper limbs and trunk Resistant strength - lower limbs Basic strength - upper limbs and trunk Basic strength - lower limbs Fast strength - upper limbs and trunk Fast strength - lower limbs sive strength - upper limbs and trunk

Muscle relaxant Explosive strength - lower limbs Deep massage +1 FITNESS PROGRAMME (28377 only)

20 FITNESS PROGRAMMES (28376, 28377)

Deep capillarization

and trunk

Agonist - antagonist Sequent. tonic contract. - upper limbs

Sequential tonic contractions - lower limbs

Sequential tonic contractions - lower limbs and trunk

Sequential phasic contractions -lower limbs

#### • 28382 I-TECH PHYSIO PROFESSIONAL STIMULATOR

Professional stimulator with 2 indipendent channels

- compensated biphasic square wave: current quantity from positive pole to negative one is constant to avoid hazardous thermal effect of polarization

- monophasic square wave
- incontinence and ionophoresis programmes
- denervated treatment
- programmable TENS EMS memories
- adjustable frequency, width impulse, time, ramp
- remaining therapy time and programmes instructions

shown on the LCD - maximum intensity 200 mApp;

Can use same gelled electrodes with cable as Mio-Care • 28381 IONOPHORESIS KIT - spare

(1 elastic band, 2 silicone conductive electrodes, 2 sponges)

# I-TECH PHYSIO PROFESSIONAL 2 CHANNELS STIMULATOR

- Supplied in a carrying bag with: rechargeable battery and battery charger
- 1 set of 4 pregelled electrodes 48x48 mm ( € 0476
- 1 set of 4 pregelled electrodes 50x90 mm
- 2 silicon conductive electrodes 60x90 mm
- 2 sponges 70x100 mm
- 1 elastic belt for electrodes fastening
- 2 cables, 2 mm connection male plug

4 cable splitter 2 mm male and female plug



keyboard

### MIO IONOTENS, 2 CHANNELS

#### • 28380 MIO-IONOTENS 37 programmes

2 channel stimulator for the customers who need an easy to use device with high output power and a complete list of TENS programmes, rehabilitation programmes and free memories. Portable and easy to use device with backlit display and digital keyboard. It is equipped with internal rechargeable battery (long-lasting) and belt clip. MIO-IONOTENS has 14 TENS programmes, 10 rehabilitation programmes including 3 ionophoresis treatments and 13 free memories (adjustable frequency, width impulse and time). Supplied in a carrying bag, with 2 cables, ionophoresis kit, 1 set of 4 pre-gelled electrodes (41x41 mm), 1 set of 4 pre-gelled electrodes (40x80 mm), belt clip, internal rechargeable battery, battery charger, user manual

### • 28381 IONOPHORESIS KIT - spare

(1 elastic band, 2 silicone conductive electrodes, 2 sponges)





# LATEX-FREE RESISTIVE EXERCISE BANDS

Latex-free bands available in 7 colour-coded levels of resistance and 3 lengths (1.5, 5.5 and 45 m).

These reliable and effective bands are ideal to improve strength. range of motion.

Use of these bands for resistive exercise provides force on the muscles. Excellent for upper and lower body

Latex-Free Exercise Bands provide the same benefits as regular bands.























# LATEX TONE LOOPS

### • 47040 SET OF 4 TONE LOOPS

The closed-loop flat band fits comfortable around the upper and lower legs. It helps to exercise the muscles of hips and legs. 47040 Set includes 4 below loops; each in

a different colour-coded level. Tone loop 18 mm x 58 cm x 1.4 mm Tone loop 24 mm x 58 cm x 1.4 mm

Tone loop 24 mm x 58 cm x 1.6 mm Tone loop 30 mm x 58 cm x 1.6 mm







### EXERCISE MATS • 47070 EXERCISE MAT 180x60xh 1.6 cm - light blue • 47080 EXERCISE MAT WITH HANG RING - 180x60xh 1.6 cm -

Thick mats with sponge-like foam structure offer comfortable feeling. The closed-cell foam structure resists moisture. Easy roll for storage.



### **RESISTIVE EXERCISE TUBING**

Tubing is an affordable and convenient training tool which provides effective upper and lower-body workout. Elastic properties for resistive and strengthening exercise.



GIMA Code	LATEX EXERCISE TUBING	Thickness	Strength	Length
47060	Latex tube	1.5 mm	0	25 m
47061	Latex tube	2 mm		25 m
47062	Latex tube	2.5 mm	•	25 m
47063	Latex tube	3 mm		25 m
47064	Latex tube	3.5 mm	•	25 m



	GIMA Code	LATEX TUBE WITH TPR HANDLES	Strength	Length
4	7050	Latex tube with TPR handles	0	125 cm
4	7051	Latex tube with TPR handles		125 cm
4	7052	Latex tube with TPR handles	•	125 cm
4	7053	Latex tube with TPR handles	•	125 cm
4	7054	Latex tube with TPR handles		125 cm

153

Digital


easy

to use

### HAND/FINGER/WRIST EXERCISERS



- 47131 GRIP TRAINER light
- 47132 GRIP TRAINER medium • 47133 GRIP TRAINER - heavy
- 47134 GRIP TRAINER X-heavy Releases typing and mousing tension. Improves hand and finger flexibility. Excellent for finger and wrist strenghte-



- 47170 TPR FLEX BAR light
- 47171 TPR FLEX BAR medium • 47172 TPR FLEX BAR - heavy

Flex bar is a flexible, durable resistance device with ridge surface for enhanced arip during use.

It is used to improve grip strength by bending, twisting or vibrating.



 47160 SET OF 3 FINGER EXERCISERS Unique design for rehabilitation, excellent stress-reliever for users. Simply insert fingers into circles and stretch Multiple resistance level available, set of light, medium and heavy resistance.



- 47180 POWER GRIP light • 47181 POWER GRIP - medium
- 47182 POWER GRIP heavy

Develop finger flexibility, strength and coordination.

Increase hand, wrist and forearm strength. Improve the injured finger recovery.



- 47140 SQUEEZE EGG X-soft • 47141 SQUEEZE EGG - soft • 47142 SQUEEZE EGG - medium • 47143 SQUEEZE EGG - firm
- 47144 SQUEEZE EGG X-firm These gel-filled eggs offer variable resistance training for hands and fingers. Help grip strengthening and reduce



• 28790 HAND GRIP METER - plastic Indicator remains at maximum until reset and is calibrated 0-75 kg. Size 20x15 cm. Sold in a blister. Manual in: GB, FR, IT, ES.

### NASAL WASH




 28083 SINUS C SALINE NASAL SPRAY 20 ml - for children - box of 48 • 28084 SINUS A NASAL WASH - for

adult - bottle 120 ml + 12 saline sachets Nasal wash helps to remove the sinus symptoms such as runny nose, nasal dryness and nasal congestion. By performing a nasal wash, you can remove particles such as pollen and dust in order to reduce the mucous membranes inflammation and make it more resistant to allergies.

ACCESSORIES FOR NEBULIZER

### HUMI-RAINBOW VAPINAL INHALER

Mist output can be (360° rotative head) and speed (adjustable knob)





28070 HUMI-RAINBOW HUMIDIFIER

A cold-mist ultrasonic humidifier with an actractive design and cromatic 7-led colours change

 28071 BALSAMIC **ESSENCE** - pine • 28072 BALSAMIC

ACCESSORIES FOR ANY BRAND OF NEBULIZER

28140

**ESSENCE** - citrus

28070

TECHNICAL SPECIFICATIONS Power feeding: AC 110-240V / 50-60 Hz Max mist output: 280 ml/h Water Tank capacity: 2.8 l Suitable for room size: min 10, max 25 m2 Max operating hours (non-stop): 10 hours

Size (individual box): Ø 19xh 30 cm - Weight: 1.4 kg



• 28110 VAPINAL THERMAL WATER INHALER Warm jet mineral water inhaler ideal for home spring water inhalation treatment. It delivers hot humid steam through a nozzle working with the Venturi system and mixing the steam with the principles of thermal water. Equipped with stainless steel boiler working with resistance at 230V-50 Hz. Supplied with polycarbonate ampulla. Made in Italy.

#### • 28112 VAPINAL AMPULLA - spare part TECHNICAL SPECIFICATIONS

Capacity: 800 ml Steam boiler in stainless steel Security valve and thermostat Operating voltage: 230 V - 50 Hz - 600 Watt Heating time: 5-8 min Inhalation time (for 1 l): 12-15 min

# BALANCE AND WEDGE CUSHION



47090 • 47090 BALANCE CUSHION • 47095 WEDGE CUSHION

Non allergic, non toxic air filled cushions made of soft, pliable material free of latex, PVC, phthalates and chloride. Both have two surfaces: smooth and bubbled which provide two kinds of user

experience. Great for improving intramuscular coordination as well as balance training ergonomic sitting and rehabilitation.

# Gima offers different nebulizer bulbs with their line of accessories, suitable for any brand of nebulizer. 28158 28157 Includes mouth piece and nasal prong Canacity: 16 ml

28147 Standard accessories with Corsia Eolo

GIMA **NEBULIZER ACCESSORIES** To be used with Standard accessories with Famiglia, Corsia, Eolo 28158 PVC connection tube - 1m all nebulizers all nebulizers 28139 Nebulizer bulb 28146 Facemask - adult\* - replaces 28143 bulb 28139/28140 28147 Facemask - paediatry\* - replaces 28144 bulb 28139/28140 bulb 28139/28140 28157 Mouthpiece - nasal prong 28138 Nebulizer kit all nebulizers adult and pediatric facemask, pvc-tube, bulb, nasal prong, mouthpiece 281//0 Nebulizer bulb all nebulizers

FASTERJET BULB

with Valve System A new designed Jet Nebulizer capable of delivering any medication in a very short time with a high amount of respirable particles. The Valve System makes therapy extremely efficient by reducing the amount of wasted medication while optimizing the output to the patient.

TECHNICAL SPECIFICATIONS FASTERJET For delivering Neh rate: 0.60 ml/min Respirable volume: <5 µm 80% any medication Residual volume: 0.8 ml MMAD (Mass Median Aerodinamic Diameter): 2.7 µm

in a very short time 28163 + 28165

28164 28166 28145 GIMA **NEBULIZER ACCESSORIES** To be used with 28163 Fasterjet bulb\* all nebulizers with Valve System Nebiet bulb \*\* all nebulizers with Double Venturi Effect 28165 Mouthpiece bi-valve bulb 28163 bulb 28164, 28166 Mouthpiece

28167 Nasal Prong bulb 28164, 28163 bulb 28164, 28163 28168 Facemask-adult\*\*\* 28169 Facemask-pediatry\*\*\* bulb 28164, 28163 28145 Filter - spare 28130/1/2/3/4/5

\* Standard with Happyneb II, Hospyneb \*\* Standard with Happyneb I, III, Betaneb \*\*\*Without elastic

# RESISTANT BALLS

- 47102 BURST RESISTANT BALL Ø 55 cm • 47103 BURST RESISTANT BALL - Ø 65 cm • 47104 BURST RESISTANT BALL - Ø 75 cm
- Designed for dynamic workouts that incorporate moderate level of resistance.

Deflate slowly if punctured. 300 lb burst resistance level

136 ka burst resistance level

47103



MASSAGE BALLS 47104







### FAMILY AND PINGOO ULTRASONIC NEBULIZERS



Family ultrasonic nebulizer 28106 28117 Pingoo ultrasonic nebulizer 28113 Re-chargeable battery Ni MH 12 VDC - Family - optional Re-chargeable battery Ni MH 12 VDC - Pingoo - optional 28115 Spare Kit: includes adult and paediatric facemask. 28114 nasal prong, mouthpiece and tube 28121 Medication cups Family (box of 15 pcs.) 28122 Medication cups Pingoo (box of 15 pcs.)



• 28075 MESH NEBULIZER

Small, handy, lightweight

nebulizer for the treatment

of respiratory diseases such as



MESH NEBULIZER

28078 MESH 2 NEBULIZER since 2018

can operate with 2xAA standard batteries or optional AC adaptor 100x240 V.

- portable, handheld design (only 120 mm height)

- maximizes the benefits of medicine

- ultra-low noise and ultra-light design

- for adult and child: noiseless use and

compact design allow to make inhalation

child mask, mouthpiece, 2xAA batteries,

Supplied with cover\*, connector\*, adult and

- one-button operation for easy use

even while children are sleeping

\*Only 28078

- multilanguage box: GB, IT, FR, ES

carrying bag, manual (GB, IT, FR, ES)



.

ON

### **ULTRASONIC NEBULIZERS**

Thanks to the innovative electronic technologies these easyto-use ultrasonic nebulizers provide a quiet, fast and portable operation with optimal particle size.

Portable: small and lightweight, it allows patients to perform treatments anytime and anywhere.

Optimal particle size: particle size determines the extent to which the medication can be inhaled by the patient into the deep lung tissue.

Approx 90% of particles generated by Family or Pingoo have the optimal 1-5µ (microns) size.

Fast treatment: with its high-efficiency design,

it allows a quick treatment time, most within 6 minutes, with limited power consumption.

Low noise level: treatments are not only fast but are virtually silent due to its advanced ultrasonic technology. Rechargeable battery - optional

8 languages user manual: GB, FR, IT, DE, ES, PT, GR, SA.

28106

#### TECHNICAL SPECIFICATIONS

Operating voltage: 220-240 V 50/60 Hz Power: 10 W Ultrasonic frequency: 2.5 MHz Nebulization time: 0.2-0.7 ml/min depending on medication density Medication cups capacity: max 8 ml Family, max 4.5 ml Pingoo Automatic switch-off

Particle size: 5 µ (microns) average Three programmable flow levels Noise level: <40 dB



Adult facemask (only Family) Paediatric facemask Nasal prong, Mouthpiece

Medication cups Transformer (220-240V-12V DC) Carrying bag

### MYNEB NEBULIZER

• 28073 MYNEB NEBULIZER - piston Compact, fast and silent nebulizer. Suitable for the treatment of the respiratory tract diseases, bronchial and asthmatic diseases, allergies. Ideal for nebulizing any medicine, ever oily ones such as cortisones essentials oils, and active ingredients with solid elements (suspensions). Supplied with carrying bag, fasterjet bulb, adult and

pediatric mask, air tube, mouthpiece and nosepiece. Multilanguage box and

manual: GB, FR, IT, ES, DE. Class IIa. Made in Italy.

• 28093 FILTÉR spare - box of 3

AC adapter:

COMPAC

### 28076 RESPIRATORY ACCESSORY KIT (adult and child mask, mouthpiece and connector) - spare for 28075 • 28077 AC-DC ADAPTER 100-240 V - optional • 28079 RESPIRATORY ACCESSORY KIT

(adult and child mask, mouthpiece) - spare for 28078

**TECHNICAL SPECIFICATIONS** Power supply: 2xAA batteries or adapter (AC-DC 3V 1A) - 2 W approximately 140kHz Ultrasonic frequency:

28078 Nebulizer rate: ≥0.2ml / min Max. / min. liquid volume: 8ml / 0.5ml MMAD approximately 5µm Nebulizing head life: 180 hours 90 minutes with two AA alkaline hattery Battery life: Automatic shutdown automatic shutdown without liquid Safety level:

#### TECHNICAL SPECIFICATIONS input 100-240 V - 50/60 Hz - 0,6 A output 12 V - DC 2A

Operating cycle 30/30 min ON/OFF 51 dB Noise level: 0.45 ml/min with NaCl 0.9% Nebulization rate Air Flow: 12 l/min

165 kPa/1 65 har Max pressure: 75% < 5 µm (NaCl 0.9%) Particle size: Size and weight 132x140xh 60 mm - 450 c

### HAPPYNEB NEBULIZERS FOR DOMESTIC USE - PISTON

• 28132 HAPPYNEB II NEBULIZER - piston 230V- Faster-Jet • 28135 HAPPYNEB III NEBULIZER - piston 230V

Happyneb stylish and portable piston nebulizer for a guick and efficacious aerosol therapy. Made in Italy.

Reliable, practical and safe.

Noiseless and lubrication free. Unit includes an air filter to be replaced every 70 applications, and handle for easy carrying.

It is built in accordance with European Standard EN 60601-1 5 languages box and manuals:

GB, FR, IT, ES, DE • 28145 FILTER - spare



### NEBULIZER TECHNICAL DATA

Happyneb III with Nebjet Happyneb II with Fasterjet

Capacity: 12 ml 16 ml Respirable volume < 5 um 75% 80% MMAD (Mass Media Aerodinamic Diameter) 2.7 µm Neb rate 0.45 ml/min 0.60 ml/min Residual volume 0.7 ml 0.7 ml

#### STANDARD ACCESSORIES

Adult and pediatric face mask Nasal prong

Mouthpiece Fasterjet bulb (28132 only)

28132



Class of risk - norms

**TECHNICAL SPECIFICATIONS** 28132 - HAPPYNEB II 28135 - HAPPYNEB III Voltage: 230V/50 Hz Maximum pressure: 280 kPa 250 kPa 110 kPa Operating pressure 90 kPa Air flow: 15 l/min 14 l/min Dimensions 31x22x13 cm 2.3 kg 2 kg Weight: Noise leve 58 db 58 db Temporary use: 30/30 min ON/OFF Continuous use

### ATOMIZER 2 SPEEDS, PISTON NEBULIZER FOR FAMILY USE

• 28094 ATOMIZER NEBULIZER - 2 speeds

Piston-type compressor with 2 speeds for family use. With accessory compartment separated from cord compartment for improved hygiene. Made in Italy.

• 28093 FILTER - spare - box of 3

### TECHNICAL SPECIFICATIONS

Operating voltage: 230 V - 50 Hz Operating cycle: speed 1: 45 kPa - speed 2: 60 kPa Operating pressure:

Air Flow: speed 1: 8 l/min - speed 2: 11 l/min Nebulization rate: speed 1: 0.2 ml/min - speed 2: 0.35 ml/min

1.85 bar / 185 kPa Max pressure: Weight: 1.4 kg

C € 0476

28097

Class of risk: Ila Noise level:



Air tube and 3 air filte

Duty cycle: 20 min on /

tubing and air filter.

40 min off

STANDARD ACCESSORIES Nebiet bulb with connector Adult and child mask Mouth piece and nose piece

Compact portable nebulizer for home use.



IIa - Class II. Type B

### MISTRAL NEBULIZER - PISTON • 28102 MISTRAL NEBULIZER - piston

### EOLO NEBULIZER - PISTON • 28097 EOLO NEBULIZER - piston

• 28091 EOLO NEBULIZER - piston - UK plug Innovative, portable, easy to use nebulizer for home use, recommended to nebulize antibiotics and bronchodilator drugs. Plastic body with high thermal insulation. Supplied

with adult and pediatric face mask, bulb, mouthpiece, air tubing, air filter. Multilanguage user manual (GB, FR, IT, DE, ES, PT, RU).

Made in Italy. 28095 FILTÉR - box of 20 pcs.

### TECHNICAL SPECIFICATIONS

28097 EOLO 28102 MISTRAL Operating voltage: 230V - 50/60Hz - 170VA 230V/50 Hz - 170VA 110V or 60Hz on request Operating pressure Air flow 14 l/min 14 l/min Nebulization rate 0.4 ml/min 0.35 ml/min Particle size < 5 um < 5 um Max Pressure 2.5 bar 2.5 bar Dimensions: 22x14.5x12 cm - 1.7 kg 13x8.9x14.6 cm - 1.5 kg 60 db

Noise level (EN 13544-1) 55 db Class of risk insulation class, Type B insulation class, Type BF Origin: Italy Italy

Supplied with Hi Flo bulb, adult and pediatric mask with string, mouthpiece, nosepiece, air **C** € 0476 • 28088 FILTER - box of 20 28102

### NEBULIZERS FOR PROFESSIONAL AND HOSPITAL USE



Piston compressor nebulizers for professional and home care use. They embodies all the dictates of modern aerosol therapy techniques. Reliable and simple to use, also by inexperienced users, Manual: GB, FR, IT, DE, ES, Made in Italy.

GIMA code	PROFESSIONAL NEBULIZER	Voltage				
28134	HOSPYNEB PROFESSIONAL	230 V - 50/60 Hz				
28137	HOSPYNEB PROFESSIONAL	110 V - 60 Hz				
28090	COMP-A NEB PROFESSIONAL	230 V - 50 Hz				
28089	NASALJET	-				
28176	COMPRESSOR - spare for 28134	230 V - 50/60 Hz				
28145	FILTER - spare					
28105 CORSIA PROFESSIONAL NEBULIZER - piston 28092 CORSIA PROFESSIONAL NEBULIZER - piston - without manometer						

Piston-type compressor nebulizers designed for continuous use. High perfomance with any type of drug, ideal for intensive hospital and clinic use. Recommended for atomizing antibiotics and bronchodilator

with high thermal CONTINUOUS

drugs. Manufactured

Nasaliet (only with 28090) and electric insulation plastic chassis in accordance with the latest European Safety regulations. The oil-free piston compressor has long durability and is equipped with the highly efficient HI-FLO jet nebulizer to guarantee quick and accurate

• 28104 FILTER - spare - box of 2

Fasterjet nebulizer with valve system

Nosepiece irrigation (polypropylene) Mouthpiece (polypropylene) with valve (silicone)

Adult and child mask (PVC DEPH free) Air tube (PVC DEPH free) and spare filter

Max pressure

MDD class:

Operating pressure:

#### **TECHNICAL SPECIFICATIONS**

28x19xh 17 cm

350 kPa (3.5 bar)

60 dRA

0-130 kPa (0-1.3 bar)

4.1 kg

STANDARD ACCESSORIES

Operating Voltage: 220-230 V - 50/60 Hz Power consumption: 184 VA Max pressure: 250 kPa (2.5 bar) Air flow: 16 l/min Operating pressure: 130 kPa (1.30 bar) Operating air flow: 5.2 l/min at 130 kPa Nebulization rate: 0.50 ml/min with 4 ml solution MMAD: 3.25 μm GSD: 3.45 Weight: 2.2 kg Size: 255x190xh 105 mn

drug delivery. Easy to handle and transport.



HI-FLO Jet bulb Mouthpiece Air tube and air filter Adult and child mask Multilanguage user manual: GB, FR, IT, ES, DE, PT

### NEBULIZER FOR INTENSIVE HOSPITAL USE

28105

### • 28060 CLINIC-AIR NEBULIZER - piston

High performing piston nebulizer for administration of any kind of drug, ideal for intensive hospital and clinical use. Its structure is made of a high thermal and electrical insulated plastic in accordance to safety European standards. Long life dry piston compressor and bulb with a valve system that

allows to adjust the nebulization speed.

Class IIa - Insulation class (EN60601-1); Class II Type B. TECHNICAL SPECIFICATIONS

Operating Voltage: 230 V - 50/60 Hz Max pressure: 250 kPa (2.5 bar) Operating pressure: 130 kPa (1.30 bar) Nebulization rate:

Power consumption: 110 VA Operating air flow: 5.2 l/min at 130 kPa

Made in Italy



• 28064 FACE MASK pediatric - spare • 28104 FILTER - spare box of 2

#### STANDARD ACCESSORIES Bulb with valve

Adult and child mask Air tube and air filter Multilanguage user manual: GB, FR, IT, ES, DE



MEDICAL GRADE SILICONE TUBES FOR EXTERNAL USE



SILICONE TUBES for external medical use - silicone 100% Suitable for autoclaving (135°C - 2.2-2.5 bar) and Gamma Sterilization. Resistant to hot air up to 200°C. Infra-red vulcanization.

Hours treatment at 200°C temperature in special oven. Anti-adherent, avoid incrustation and coagulation. Medical Grade - Transparent - Odourless

TECHNICAL SPECIFICATIONS
Raw material: HTV-R-401/60 S - WACKER (D) Colour: translucent Colour: translucent Hardness: 60° ±5% Shore - DIN 53505 Density: 1.17 g/ccm - DIN 53479A Tensility: 10.8 N/mm² - DIN 53504 S1 Stretch: 490/530% - DIN 53504S1 Tear resistance: 34-35 N/mm - ASTM D 624 B Reverse pull elasticity: 51% - DIN 53512 Compression set: (22h/175°C): 30-15% - DIN 53517

Made in European Union according to: US PHARMACOPOEIA XXI EUROPEAN PHARMACOPEA DIN 58367 - DIN 58362 - DIN 13098- FDA 177.2600 - BGA XV part A and B - BGA IX part B

### MADE TO ORDER SILICONE TUBES

We can manufacture any size (minimum order 500 m - delivery 30 days)



GIMA code	Internal diameter x external diameter	Thickness mm	Minimum order
25450	1x3 mm	1 mm	roll of 100 n
25451	2x4 mm	1 mm	roll of 100 n
25452	3x5 mm	1 mm	roll of 100 n
25453	4x6 mm	1 mm	roll of 100 n
25455	6x8 mm	1 mm	roll of 30 m
25458	3x6 mm	1.5 mm	roll of 30 m
25459	4x7 mm	1.5 mm	roll of 30 m
25460	5x8 mm	1.5 mm	roll of 30 m
25461	6x9 mm	1.5 mm	roll of 30 m
25462	7x10 mm	1.5 mm	roll of 30 m
25466	4x8 mm	2 mm	roll of 30 m
25467	5x9 mm	2 mm	roll of 30 m
25468	6x10 mm	2 mm	roll of 30 m
25469	8x12 mm	2 mm	roll of 30 m
25470	10x14 mm	2 mm	roll of 30 m
25474	5x10 mm	2.5 mm	roll of 30 m
25475	7x12 mm	2.5 mm	roll of 30 m
25476	8x13 mm	2.5 mm	roll of 30 m
25477	10x15 mm	2.5 mm	roll of 30 m
25480	6x12 mm	3 mm	roll of 30 m
25481	7x13 mm	3 mm	roll of 30 m
25482	8x14 mm	3 mm	roll of 30 m
25483	9x15 mm	3 mm	roll of 30 m
25484	10x16 mm	3 mm	roll of 30 m
25485	12x18 mm	3 mm	roll of 30 m
25488	8x15 mm	3.5 mm	roll of 30 m
25491	10x20 mm	5 mm	roll of 30 m
25495	made t	o order	500 m

### ACCESSORIES FOR ANY SUCTION ASPIRATOR



Set of 7 uterine aspiration cannulas for abortion: 4 cannulas with side suction end (Ø 5, 6, 8, 9 mm), 3 cannulas with

front suction end (Ø 7, 10, 11 mm) and one handle

SILICONE VACUUM SUCTION See page 172

SUCTION CATHETER See page 43

S/S FRAIZER SUCTION CANNULA See page 34

S/S ROSEN SUCTION CANNULA See page 34

S/S NOVAK SUCTION CANNULA See page 33

### **BREAST PUMP - MAMILAT GIMA**

• 28148 MAMILAT - BREAST PUMP - 230 V - 50 Hz Easily transportable from one maternity ward to another, or for use at home. To be used for mother's milk suction. Made of highly heat-resistant, electrically insulated plastic material in conformity with the latest European safety standards. Supplied with 2 polycarbonate milk bottles (150 cc and 250 cc) antibacterial and hydrofobic filter, set of tubes 6x10 mm, breast shield. PVC air tube. Suction adjustment knob. Working time: 20 minutes ON. 40 OFF.

• 28229 HYDROPHOBIC ANTIBACTERIAL FILTER - spare

• 28149 SPARE KIT

Includes two plastic bottles (125 cc and 250 cc) nipple shield, filter and tubes.

#### TECHNICAL SPECIFICATIONS

Regulator for suction intensity - max suction -0.33 bar Operating voltage: 220-230 V - 50/60 Hz - available on request 110 V - 60 Hz Max flow (air litres/min): 14 l/min Power consumption: 184 VA

Size: 235x190x165 mm Weight: 2.2 kg Norms: CEI 62-5 (IEC601-1), Made in Italy



IT GR FS FR DF 28149

28148

C €0434

COMP-A NEB

110 V - 60 Hz on request

19.6x35.7xh 18.5 cm

250 kPa 55 dBA

0-110 kPa

2.5 kg

28092

230 V - 60 Hz on request

### ■ RES-Q-VAC FILTERED HAND SUCTION

28124 RES-O-VAC (FILTERED) SUCTION

This lightweight and hand held suction unit requires no batteries or electricity and yet provides powerful suction whenever and wherever vou need it

It offers ultimate safety and ease of use for the professional and fits easily into any emergency bag or ambulance. Key Features:

- portable Hand Powered Suction one hand operation
- hospital suction level performance >600mmHg
- always ready to go, no set up required, no batteries to recharge
- patented 0.22 equivalent micron filter for ultimate infection control
- full stop protection filter prevent fluid overflow
- easy snap on replacement canister sets with Adult and Child catheters
- each unit 100% tested for reliability



Kit includes: Res-q-Vac pump, canister 300 ml with filter, soft cannula Ø 12.7 mm x 20.3 cm length

- 28128 SPARE ADULT KIT with filter Includes canister 300 ml and wide soft adult style vankauer, Disposable.
- 28129 SPARE PEDIATRIC KIT with filter Includes canister 300 ml and 2 pediatric catheters with different length: 356 mm for paediatric and 88.9 mm for neonatal applications. Disposable.



### TECHNICAL SPECIFICATIONS

Weight: 143 g Size: 114x180x55 mm Max vacuum: > 600 mmHc Min. vacuum after 2 activations: > 400 mmHg Volume per stroke: 30 ml Capacity before full: 290 ml Inner Ø of adult catheter: 9.53 mm Length of adult catheter: 272 mm

Pump is suitable for cold or ETO sterilization





### HAND/FOOT/KNEE SUCTION PUMP 📕 HAND SUCTION PUMP

• 28220 TOBI MANUALE - manual suction aspirator Independent of any power source, Tobi Manuale is simple to operate pressing pedal by foot, hand or knee. It is used to clear patient's airways safely and efficiently, anytime, anywhere. Precision and solidly built to assure long service life. Polycarbonate suction bottle

with capacity 400 cc, autoclavable at 120°C and spill-over protection. Bacterial filter included.

Multilanguage user manual: GB, FR, IT, DE,

• 28219 BOTTLE

0.4 I - spare • 28229

**HYDROPHOBIC** ANTIBACTERIAL FILTER - spare

**C** €0476

Size: 225x165x85 mm

28220 **TECHNICAL SPECIFICATIONS** 

Max suction -0.40 bar Bottle capacity: 400 cc Suction power: 22 l/min Made in Italy

#### • 28180 HAND SUCTION UNIT

Designed to provide guick and effective pharyngeal and tracheal suction for emergency use.

The adjustable stroke knob provides different suction pressure. Supplied with 250 ml bottle and 2 sterile adult

cannulas 26 and 40 cm • 28181 SPARE ADULT KIT Includes 250 ml bottle and 2 sterile adult cannulas 26 and 40 cm.



### **TECHNICAL SPECIFICATIONS**

Max vacuum: -450 mmHg Weight: 260 g Peak free airflow: >20 l/min Size: 185x70x168 mm External diameter of catheter connection: 13.35 and 8.67 mm

### SPENCER JET COMPACT 300D PORTABLE SUCTION UNIT

lar 400 ml

#### • 28177 JET COMPACT PORTABLE SUCTION UNIT

Extremely compact suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container. Easy view of the setted vacuum thanks to the LED indicators. Classification ISO: high vacuum / high flow. Supplied with 12 V power cable, battery, disposable container with filter, disposable patient tube.

28178 DISPOSABLE CONTAINER 300 ml with filter

0.75 A max: 12 VDC

• 28179 POWER ADAPTER

requirement

#### TECHNICAL SPECIFICATIONS

Dimensions 245x70x185 mm Weight: 1.60 ka Vacuum range: from 50 to 550 mmHq Flow (free flow) Noise level: 70 dB 100-240 VAC 47-63 Hz Flectrical connector

IP grade 12 V DC Ni-MH Battery: Battery operative time: 30 min ON, 30 min OFF Battery recharging time: 5 h Container canacity: 300 ml Patient tube length: 1 m



Class IIa Medical Device according to Dir. 93/42/CEE

### MINIASPEED BATTERY EVO PROFESSIONAL SUCTION ASPIRATORS

• 28282 MINIASPEED EVO BATTERY SUCTION - 1 I

• 28283 MINIASPEED EVO BATTERY SUCTION - 1 I for ambulance

• 28284 MINIASPEED EVO BATTERY SUCTION - 2 I

Professional portable high flow - high vacuum aspirators with integrated rechargeable batteries. It works at 12 V power supply with rechargeable batteries or directly by mains supply, continuously at 110-230 V while recharging batteries. Up to 45 minutes of autonomy with fully charged battery. Made in Italy.

• 25480 SILICONE TUBE 6x12 mm - roll of 30 m

• 28254 ADAPTER FOR CATHETER

• 28255 HYDROPHOBIC 99% BACTERIAL FILTER

• 28258 AUTOCLAVABLE JAR 1000 ml (with cover)

28259 DISPOSABLE SUCTION LINER

28294 AUTOCLAVABLE JAR 2,000 ml (with cover)

#### **TECHNICAL SPECIFICATIONS**

with battery DC 12 V with power supply 100÷240 V ~ 50/60 Hz - 14 VDC 4,28A

max 50 W 134x378xh 263 mm Weight: 4.7 kg (5 kg version for ambulance) Bottle capacity 1,000 or 2,000 ml

30 air litres/min Sound level: 65 dBA at 1 m Operating cycles: continuous (45 minutes battery autonomy)

MAX vacuum 0 + 85 kPa12 VDC 4A h lead hermetic

Battery autonómy

about 45 minutes, recharging time approx 6 hours MDD 93/42/EEC (Class IIa - annex IX) EN60601-1(IEC 60601-1) / EN60601-1-2 (IEC 60601-1-2) UNI EN ISO 10079-1/ UNI CEI EN ISO 14971

Degree of protections against ingress of liquids: IP34d (IEC 529)

status Space for accessories

#### 28282 STANDARD ACCESSORIES

Autoclavable 1 or 2 l jar with safety valve Sterile disposable cannula CH14 Sterile disposable manual regulator Disposable silicone liner 1 I (28282-3 only) Silicone tubing set Ø 6x12 mm 2 bacterial hydrophobic filters Cigarette lighter power cord (28282, 28284 only) User manual: GB, IT, FR, DE, ES

Power supply cord - 2 m Shoulder carrying bag Multivoltage battery charger Support bracket for ambulance (only 28283)

### SUPERVEGA EVO BATTERY AMBULANCE ASPIRATOR PROXIMITY

Courtesy lamp

28182 SUPERVEGA EVO AMBULANCE BATTERY ASPIRATOR

• 28183 SUPERVEGA EVO BATTERY ASPIRATOR

Supervega Evo is an electric medical device for the nasal, oral and tracheal aspiration of body fluids in children or adults. Two or three options of operation: by 100-240V power feeding (28183 only), 12 V car adapter or internal rechargeable battery. Large LCD for clear reading of vacuum values along with soft keys for vacuum adjustment increase the accuracy of aspiration. Smart operation thanks to the combination of the lightweight lithium-ion battery with the innovating FEEDBACK system that controls and manages the power of aspiration, providing a long autonomy of the battery and quiet noise level during operation. The PROXIMITY function to switch ON or OFF the device without touch prevents and avoids cross-contamination in-between patients. Equipped with a long-life brushless motor eliminating any type of smell and coal residuals. Various options of jar: standard autoclavable polycarbonate (121°C), optional FLOVAC® disposable liners or APEC® that can resist up to 143°C, see at page 163. Complies with EN 60601- 1-11 only 28183 "for use in the home healthcare environment" and carries IP21 degree of protection. Made in Italy.

#### TECHNICAL SPECIFICATIONS

Motor Oil-less and maintenance-free piston pump Internal rechargeable Lithium battery (14.8 V - 5.2 A) - Autonomy 70 min Car-ambulance adapter (12 V - 4 A) - only 28183 AC/DC adapter 110-230 V, 50-60 Hz - only 28183

Recharge from support bracket - only 28182
Max vacuum (adjustable): -0.75 Bar; -75 kPa; -563 mmHg
Max free air flow rate: 26 l/m Size: 35x19x15 cm
Duty cycle: non stop operation (by mains or 12 V only) Weight: 2.7 kg

STANDARD ACCESSORIES Polycarbonate jar 1,000 ml with overflow valve system Suction cathete



Antibacterial filter Silicone tube set with conical connector Universal power adaptor (100-240V - 50/60 Hz) (only 28183) 12V car adapter (only 28183) Support bracket for ambulance 20x16x16 cm (only 28182) Carrying bag (only 28182) User Manual GB, FR, IT, DE, ES.



### SUPER VEGA BATTERY SUCTION ASPIRATOR ON TROLLEY



• 28193 SUPER VEGA BATTERY on trolley - suction 2x2 l

Portable suction unit for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. For professional use and with a powerful aspiration of max 36 l/min. It comes with double collection jars and on a stand with five castors for easy transport.

Two different working options: AC/DC adapter, rechargeable battery make it a versatile suction unit approved for NON-STOP operation without overheating.

Provided with visual and acoustic alarm indicating low battery level, vacuum-meter (bar & kPa) and vacuum regulator.

### TECHNICAL SPECIFICATIONS

32x30xh 99 cm - 7.9 kg Operating voltage: 100-240 V - 50/60 Hz
Internal rechargeable Pb battery: 12V - 4A

Battery autonomy: 60 min User manual:

Recharging: 240 min Temporary use: 120 on - 60 off

# BATTERY SUCTION ASPIRATORS

 28243 SUPER VEGA BATTERY - plastic case - 16 l/min. • 28190 SUPER VEGA BATTERY - plastic case - 36 l/min.

28213 TROLLEY FOR SUPER VEGA

28242 BATTERY FOR SUPER VEGA/TOBI (28243\*/28240) - spare

28251 BATTERY FOR SUPER VEGA (28190/28243\*\*) - spare

\*Up to S.N. 2141 (3 LEDs) "Since S.N. 3000 (1 LED) With incorporated rechargeable batteries. It can operate at 12 V power supply at rechargeable batteries and, thanks to an electronic system, at 230 V while recharging batteries.

Autonomy: approx 45-50 min (28243), 60 min (28190) Recharging time: 120-150 minutes. Max suction: -0.75 bar (28243) -0.80 bar (28190)

Suction power: 16 or 36 air litres/min It has unbreakable 1,000 ml standard bottle (2,000 ml optional) autoclavable at 120°C with safety float control valve to prevent overflow.

#### TECHNICAL SPECIFICATIONS SUPER VEGA

Operating Voltage: 220-230 V - 50/60 Hz AC - 12 V DC (28243) 100-240 V - 50/60 Hz (28190)

Size: 350x210x180 mm Weight: 4.9 kg Max suction -0.75 bar (563 mm/Hg) (28243), -0.80 bar (28190) Suction power: 16 air litres/min (28243), 36 air litres/min (28190) Norms: IEC 601-1 - Class II Type B. Made in Italy



power adapter STANDARD ACCESSORIES

Bottle 1 I - autoclavable at 120°C Silicone tubing set Suction catheter User manual (GB, IT, FR, DE, ES)

28190

**C** €0476

AC/DC universal adapter Anti-bacterial filter Cable to recharge batteries from car

36 l/min.

• 28206 MINI ASPEED BATTERY PRO - metal case - 30 l/min High vacuum portable medical device for professional surgical

- it can operate at 12 V (car) power supply, rechargeable batteries or directly by mains supply

- its two cylinders électro-compressor ensures high performances and long life

- up to 45 min. of autonomy with fully charged battery

- with 99% antibacterial hydrophobic filter

- equipped with autoclavable jar with safety valve, disposable suction liner and carrying case.

• 25480 SILICONE TUBE 6x12 mm - roll of 30 m

28254 ADAPTOR FOR CATHETER

• 28255 HYDROPHOBIC 99% BACTERIAL FILTER

28255 HYDROPHOBIC 99% BACTERIAL FILTER

 28258 AUTOCLAVABLE JAR 1000 ml (with cover) liner inside

 28259 DISPOSABLE SUCTION LINER autoclavable iar

### TECHNICAL SPECIFICATIONS MINI ASPEED

Operating Voltage: 100-240 V 50/60 Hz AC - 14 V DC 4.28 A Size: 370x100x240 mm Weight: 5.8 kg (include kit) Max suction: - 0.85 bar

Suction power: 30 air litres/min. Norms: MDD 93/42/ECC (class IIa - annex IX)

IEC 60601-1 LINI ENISO 10079-1



#### STANDARD ACCESSORIES

Autoclavable iar 1000 cc with safety valve Silicone tubing set Ø 6x12 mm Disposable suction liner


Anti-bacterial hydrophobic filter Multivoltage battery charger Cigarette lighter power Shoulder carrying bag

# 28259

on trolley

### SUPERVEGA SUCTION ASPIRATOR ON TROLLEY

28243



28259 28258

• 28191 SUPER VEGA on trolley - suction 2x2 l jar • 28192 SUPER VEGA on trolley - suction 2x2 l jar with footswitch

Continuously adjustable vacuum, with indicator. Silicone connection tube. 2 jars 2 litres, made of sterilizable polycarbonate (autoclavable at 120°C). Working time: 120 min ON, 60 min. OFF. Suction power: 40 air litres/min. Steel painted frame, fitted with 5 star base.

Norms CEI 62-5 (IEC 601-1) - Class II - Type B
• 28239 HYDROPHOBIC 99% BACTERIAL FILTER

25482 SILICONE TUBE - 8x14 mm - roll of 30 m

#### **TECHNICAL SPECIFICATIONS**

Size: 32x30xh 90 cm Weight 6.2 kg
Operating voltage: 220-230 V - 50/60 Hz; other on request Power consumption: 110 VA Maximum suction: -0.80 bar (600 mm Hg) Flow: 40 air litres/minute

Operating cycle: continuous Norms CEI 62-5 (IEC 601-1) - C € 93/42 EEC User manual (GB, FR, DE, IT, ES)

1 | policarbonate autoclavable jai with overflow safety valve Supervega disposable 28252 iars 28272/3 and 28274/5. Adaptor to connect cathete to silicone tube Autoclavable jar (1 or 2 I) with overflow valve system Antibacterial and hydrophobic filter Set of silicone tubes 6x10 mm Conical connector for probes

### VEGA SUCTION UNITS, HIGH VACUUM, LOW AND HIGH FLOW



28209 VEGA LINO

220-230 V - 50/60 Hz

184 W

1.000 m

15 l/min

2.2 kg

continuous

25x19x16.5 cm

110 V - 60 Hz (on request

-0.75 bar (563 mm/Hg)

#### **VEGA SUCTION UNITS**

A line of stylish, compact and reliable aspirators for small surgery. Silent, high flow and maintenance - free pumps allow long product life and durability.

Recommended for nasal aspiration, oral aspiration, tracheal aspiration of body liquids (mucus, catarrh or blood) in adults or children. Equipped with vacuum regulator continuously adjustable, vacuum indicator, unbreakable 1,000 ml or 2,000 ml bottle, autoclavable

at 121°C, with safety float control valve to prevent overflow. Optional bottle autoclavable at 134°C. Manufactured in electric and thermal

insulated plastic body.

Made in Italy

Autoclavable and disposable collection system: In addition to standard autoclavable jar is available a disposable collection system composed by a rigid reusable container and a polyethylene disposable liner with cover, hermetically sealed, and hydrophobic, antireflux, bacterial filter operating as an overflow valve.

STANDARD ACCESSORIES

28211 28213

28209

Operating Voltage

Flow (air litres/min)

Bottle capacity:

Operating cycle:

Max suction:

Weight

93/42/ECC 93/42/ECC 93/42/ECC GIMΔ Operating **VEGA SUCTION ASPIRATOR** code 28209 Vega Uno 220-230 V - 50/60 Hz 15 l/m 28210 Vega 220-230 V - 50/60 Hz 16 l/m 28211 Super Vega 1 220-230 V - 50/60 Hz 40 l/m 28212 Super Vega 2 220-230 V - 50/60 Hz 40 l/m 28189 Super Vega 1 110 V - 60 Hz 40 l/m

28210 VEGA

184 W

1.000 ml

16 l/min

2.5 kg

continuous

35x21x18 cm

220-230 V - 50/60 Hz

-0.75 bar (563mm/Hg)

110 V - 60 Hz (on request)

28211 SUPERVEGA

220-230 V - 50/60 Hz

1,000 ml or 2,000 ml

-0.80 bar (600mm/Hg)

or 110 V - 60 Hz

106 W

40 l/min

3.6 kg

continuous

35x21x18 cm



### SPARE ACCESSORIES FOR VEGA AND TOBI LINE

28229 Hydrophobic, 99% antibacterial filter 121°C autoclavable jar 1 l with cover and overflow system 121°C autoclavable jar 2 I with cover and overflow system

Cover and overflow valve system for 28226 and 28236 28185 | 134°C autoclavable jar 1 | with cover and overflow system 134°C autoclavable jar 2 I with cover and overflow system

Cover and overflow valve system for 28185 and 28186 Disposable liner 1 I (cover + bag) 28270 Container for disposable liner 1

Disposable liner 1 I (cover + bag) - box of 50 28273 Disposable liner 2 I (cover + bag)

Disposable liner 2 I (cover + bag) - box of 50 28272 Container for disposable liner 2 l Ø 13 cm top, 9.5 cm bottom

Silicone tube 6x10 mm - roll of 30 m 28252 Adaptor to connect catheter to silicone tube

Suction catheter - see at page 43 28213 Trolley for Vega and Super Vega (not for Vega Uno)

6 languages user manual (GB, FR, IT, DE, ES, PT) 28229 28276 Vacuum indicator for Vega and Super Vega (not for Vega Uno)



#### ASPEED PROFESSIONAL SURGICAL ASPIRATORS

Piston-type continuous cycle electric aspirators give high performance and great durability. Equipped with a protective thermal cut-out relay. They require no maintenance or lubrication. A motor-protector cap totally prevents aspirated

GIMA code	ASPEED ASPIRATORS	Power	Pump	Case
28244	Aspeed 15 I	230 V	single	metal
28245	Aspeed 22 I	230 V	double	metal
28246	Aspeed 22 I	110 V	double	metal
28280	Aspeed 2 15 I	230 V	single	plastic
28281	Aspeed 2 22 I	230 V	double	plastic

Adjustable vac

Case material:

Weight:

STANDARD ACCESSORIES Autoclavable policarbonate jar 1,000 cc with safety valve (overflow protection)

Disposable suction liner 1 l 99% Antibacterial hydrophobic filter Sterile disposable cannula Sterile manual flow regulator Set of atoxic sterilizable silicone tubes

• 28222 TOBI - suction aspirator

220-230 V - 50/60 Hz

Power Cable User Manual GB. FR. IT. DE. ES

code 28255 28258 28259

**TECHNICAL SPECIFICATIONS** ASPEED ASPEED 2 28245/6\* 28281 Operating voltage 230 V-50 Hz 230 V - 50/60 H 110-60 Hz other voltage on request Bottle capacity low flow high flow High vacuum: low flow low flow 22 l/min 22 l/min Air flow: 15 l/min 15 l/min



28244-6

ACCESSORIES AND SPARES FOR ASPEED

liquids or secretions from reaching and damaging the vacuum

Hydrophobic 99% bacterial filter

Silicone tube 6x12 mm - roll of 30 m

Adaptor to connect catheter to silicone tube

Autoclavable jar 11 with cover

Adaptor kit to use iar 11 (28258)

Disposable suction liner

3.2 kg

regulation knob

pump. Ideal for clinical use.

Made in Italy.

28261

0 - - 0.85 har (0 - - 85 kPa)

2.5 kg

55 dBA

Max suction: -0.75 bar

1 | Autoclavable lar

# 65 dBA SUCTION ASPIRATORS HIGH VACUUM, LOW AND HIGH FLOW

4.5 kg

3.5 ka

55 dBA

• 28224 SUPER TOBI - suction aspirator 220-230 V - 50/60 Hz Portable suction aspirators, ideal for tracheotomy and small surgery. Vacuum continuously adjustable with vacuum indicator. Have unbreakable 1,000 ml standard bottle (2,000 ml optional) autoclavable at 120°C with safety float control valve to prevent overflow. Silicone connection tube 28222 ABS plastic case. Made in Italy

> Silicone tube 6x10 mm (see page 159) Adaptor for catheter (code 28252)

### STANDARD ACCESSORIES

Bottle 1,000 ml with cover Antibacterial Filter Suction catheter Silicon Tube set

Operating voltage: ower consumption: Bottle capacity: Flow (air litres/min) Max suction Working time: minutes Size (cm): Weight:

TECHNICAL SPECIFICATIONS 28222 Tobi 220-230 V - 50/60 Hz 184 W 1,000 ml

-0.75 har (563mm/Hg) 20 ON / 40 OFF 37x22xh 21 cm 3.5 ka

28224Super Tobi 220-230 V - 50/60 Hz 106 W

HIGH FLOW

1,000 ml 40 l/min -0.80 bar (600mm/Hg) 120 ON / 60 OFF 37x22xh 21 cm 5.25 kg

HIGH VACUUM, HIGH FLOW HOSPITAL SUCTION ASPIRATOR



Clinic Plus and Hospi Plus with foot switch and electronic flow direction regulator New innovative range of high vacuum, high flow aspirator ideal for hospitals. Pump piston type, lubrication and maintenance free. Supplied with hydrophobic 99% bacterial filter, vacuum gauge for control of vacuum and 2 autoclavable iars (2 or 4 litres) made in makrolon with 200/400 ml graduation and double security valve. Available on request 2 or 3 litre disposable liners. Range includes version with foot

TECHNICAL SPECIFICATIONS

Clinic plus Hospi plus Operating voltage: 110 V or 230 V - 50/60 Hz 230 V - 50/60 Hz - 110 V on request Maximum suction: - 0.90 bar (675 mmHg) - 0.90 bar (675 mmHg) Operating cycle: continuous continuous Power 300 VA 230 VA CFI 62-5 (IEC 601-1) CFI 62-5 (IEC 601-1) 93/42 FFC. Made in Italy 93/42 FFC. Made in Italy



switch and flow direction regulator, 110 and 230 V. Four antistatic castors, two of which with brake, allow a perfect mobility. User manual in GB, FR, IT, ES, DE. See spare accessories at page 159, 166. Made in Italy.

GIMA code	CLINIC PLUS / HOSPI PLUS	Jar	Power	Foot switch	Flow direction diverter*
28194	CLINIC PLUS aspirator	2x2 l	220-230 V	-	-
28196	CLINIC PLUS aspirator	2x4 l	220-230 V	-	-
28198	<b>CLINIC PLUS aspirator</b>	2x4 l	220-230 V	yes	yes
28200	<b>HOSPI PLUS aspirator</b>	2x2 l	220-230 V	-	-
28199	HOSPI PLUS aspirator	2x2 l	110 V	-	-
28201	HOSPI PLUS aspirator	2x4 l	220-230 V	-	-
28203	HOSPI PLUS aspirator	2x2 l	220-230 V	yes	yes
28204	<b>HOSPI PLUS aspirator</b>	2x4 l	220-230 V	yes	yes
*Allow to	direct suctioned liquids to any o	f the 2 ja	rs		

### MAXI ASPEED HIGH FLOW ASPIRATOR FOR HOSPITAL USE







#### **TECHNICAL SPECIFICATIONS**

Operating voltage: 230 V - 50/60 Hz. Available on request 110 V - 60 Hz 60 or 90 l/mir Operating cycle: continuous

0-0.90 bar (0-90 kPa) Adjustable vacuum level: Size: 470x580x560 mm 15 kg (60 l), 17 kg (90 l) Weight MDD class

### MAXI ASPEED SURGICAL ASPIRATORS

Surgical aspirators for aspiration of body liquids in operating theatres and hospitals.

#### Easy to carry

Equipped with 4 antistatic wheels (2 with brake) and carrying telescopic handle.

#### Developed to run continuously

Made in highly heat resistant, electrically insulated plastic material in conformity with latest European safety standards. Vacuum regulator with BAR/PSI vacuometer and automatic flow direction regulator to easily switch from a jar to the other. Supplied with 2 autoclavable polycarbonate iars with safety valve (overflow protection), set of atoxic sterilizable silicone tubes, 99% antibacterial hydrophobic filters (2) and multilanguage manual (GB, FR, IT, DE, ES). Made in Italy.

code	MAXI ASPEED	Jar	Power	switch	direction regulator		
28285	Maxi Aspeed 60 l	2x2 l	230 V	-	yes		
28286	Maxi Aspeed 60 I	2x2 l	230 V	yes	yes		
28288	Maxi Aspeed 60 l	2x4 l	230 V	yes	yes		
28289	Maxi Aspeed 90 l	2x2 l	230 V	-	yes		
28291	Maxi Aspeed 90 I	2x4 l	230 V	-	yes		
28292	Maxi Aspeed 90 l	2x4 l	230 V	yes	yes		
ACCESSORIES							

28294 Autoclavable jar 2 I with safety valve 28295 Autoclavable jar 4 I with safety valve Hydrophobic 99% antibacterial filter Silicone tube - 8x14 mm - roll of 30m




28224

**C** € 0476

Air flow:

### HIGH VACUUM, HIGH FLOW HOSPITAL SUCTION ASPIRATOR



Ideal for hospital, these suction aspirators are manufactured in ABS. Four antistatic castors, two of which with brakes, to allow perfect mobility. Vacuum gauge for the control of vacuum (1 bar). 2 or 4 litre jar made of autoclavable makrolon, with 200/400 ml graduation. Each jar with double security valve. Pump piston type, lubrication and maintenance free. With anti bacterial filter. Available model with footswitch and other operating voltage (110 V).

User manual in GB, FR, IT, ES, DE. Made in Italy.

GIMA code	TOBI CLINIC / HOSPITAL	Jar	Power	Foot switch
28231	TOBI CLINIC - suction aspirator	2x2l	220-230 V	-
28214	TOBI CLINIC - suction aspirator	2x2l	220-230 V	yes
28215	TOBI CLINIC - suction aspirator	2x4l	220-230 V	-
28216	TOBI CLINIC - suction aspirator	2x4l	220-230 V	yes
28232	TOBI HOSPITAL - suction aspirator	2x2l	220-230 V	-
28202	TOBI HOSPITAL - suction aspirator	2x2l	220-230 V	yes
28233	TOBI HOSPITAL - suction aspirator	2x4l	220-230 V	-
28234	TOBI HOSPITAL - suction aspirator	2x4l	220-230 V	yes
28235	TOBI HOSPITAL - suction aspirator	2x2l	110 V	-

LOZJJ TOBI HO	SPITAL - SUCCION aspirator   2	XZI 110 V -
	TECHNICAL SPECIFICATION	ONS
	Hospital (28202-28232/3/4/5)	Clinic (28214/5/6, 28231
Size:	55x45xh 65 cm	46x42xh 60 cm
Weight:	20 kg	13 kg
Operating voltage:	110 V or 230 V - 50/60 Hz	110 V or 230 V - 50/60 H
Maximum suction:	- 0.90 bar (675 mm/Hg)	- 0.90 bar (675 mm/Hg)
Operating cycle:	continuous	continuous
Flow:	90 l/min	60 l/min
Norms:	CEI 62-5 (IEC 601-1)	CEI 62-5 (IEC 601-1)







GIMA code	ACCESSORIES FOR CLINIC/HOSPITAL, CLINIC PLUS, HOSPI PLUS	To be used with			
28237 28239	Hydrophobic, 99% bacterial filter Hydrophobic, 99% bacterial filter	Hospital/ Hospi plus Clinic/Supervega Trolley			
28236 28227 28228 28223 28186 28184 28187	121°C autoclavable jar 2l with overflow system Cover 2l with overflow valve system 121°C autoclavable jar 4l with overflow ystem Cover 4l with overflow valve system 134°C autoclavable jar 2l with overflow system 134°C autoclavable jar 5l with overflow system 134°C autoclavable jar 5l with overflow system	28228 All 2 l aspirators 28186			
28272 28273 28274 28275	Container for disposable liner 2l Disposable liner 2l cover+bag Container for disposable liner 3l Disposable liner 3 l cover+bag	All 2 I aspirators 28272 Clinic/Hospital/ Hospital plus 2 I 28274			
25482 28253 28276 28277	Silicone tube 8x14 - roll of 30 m Adapter to connect catheter to silicone tube Suction catheter see at page 43 Vacuum indicator Ø 50 mm Vacuum indicator Ø 60 mm	Clinic/Hospital 25482 28253 Clinic Clinic plus/Hospi Plus			
28265 28266 28267	Bottom base Bottom base Bottom base	Hospital Clinic plus/Hospi Plus Clinic Hospital			

### GIMA LED COLPOSCOPE

• 29600 COLPY - GIMA LED COLPOSCOPE Easy to use LED colposcope mounted on a

5 wheels base (Ø 41 cm).

COLPOSCOPE TECHNICAL SPECIFICATIONS Magnifying: 8.2X with standard 10X eyepieces

Field: 35 mm Optic system: stereo with inter-pupil adjustment and optic head at 45° Illumination: LED bulb

Working distance: 28 cm Interpupillary distance: 48-77 mm Green filter

Operating voltage: 100-240V, 50-60 Hz Norms: CLASS I Type B - IEC 601-1 CE 93/42/EEC. Made in Italy

 29601 CAMERA CONNECTOR for 29602 To connect a camera with standard "C mount" to GIMA colposcope • 29602 MC1 PAL CAMERA - for Colpy

Fit the camera to one eyepiece and connect the video cable to a high definition monitor. Needs 29601.

• 29603 DL1 DIGITAL - USB 2.0 CAMERA with grabbing software for Colpy Fitted on one eyepiece, allows to show image on PC through USB connection, becoming a high definition videocolposcope.

**TECHNICAL SPECIFICATIONS - 29602** Camera sensor: 1/3 CCD Resolution: 480 lines Power: 230 V - 50/60 Hz RCA video composite output 3 m cable

Head size: 38x40x70 mr

Main features:

vertically (E-flip).

**TECHNICAL SPECIFICATIONS - 29603** 

• 29620 COLPRO LED VIDEO COLPOSCOPE • 29622 COLPRO LED VIDEO COLPOSCOPE - FULL HD

The digital video colposcopes COLPRO are the perfect combination

of an advanced video technology and the feedback received from

gynaecologists, users and stakeholders. They are known for their ruggedness and versatility and they provide high resolution images of

cervix and genital area for effective colposcopy diagnosis and treatment.

5 levels of light intensity to observe finest changes in tissue structure.

Electronic Green Filter: 4 different grades (5 for HD) ensure an optimal

Mirror and E-flip image: facility to change the direction of the image

from left to right horizontally (mirror) or from upward to downward

Magnification up to 55 times and Auto-focus: the colposcope focuses

Remote control allows to control the functions even from a distance.

Height adjustable to have best positioning for colposcopy procedure.

• 72708 SONY LMD LCD MEDICAL MONITOR - 15" - support included

Freedom of connectivity: can be connected to a TV or a monitor and to PC

via USB. 2 video outputs can be taken on 2 different screens simultaneously

User friendly design: ergonomic and user friendly design, easy to move

Gamma processor: assures high quality image processing for better

5 image colours settings that guarantee best colour differentiation in epithelium.

CMOS /3" sensor Max resolution pictures 1280x1024 pixels

observation without any light loss.

visualization of vessels and tissue structure.

Maintenance free, shadowless LED light source

#### ALLTION LED COLPOSCOPE • 29612 ALLTION LED COLPOSCOPE - 9X adiustable • 29613 ALLTION LED COLPOSCOPE eyepieces

for measuring

reen filte

activator

Head tilt

and fine

adjustment

29613

heiaht

adjustment

3,75X, 7X, 15X - > 28,000 LUX High quality and complete colposcopes, with excellent optics and cold, longlife white light. Compact, lightweight and easy to use offers superior

quality at a competitive price. A special universal Teflon® ball joint gives user 360° easy motion for gross focus. Comes assembled, adjustment handle

ready for use.

 $\epsilon$ 

Adjustable

observation

73-104 cm

heiaht

TECHNICAL SPECIFICATIONS

Gross heigh Magnification 9X (29612) or 3,75X, 7X, 15X (29613) adjustmen Focus length: 316 (29612) or 300 mm (29613) knob Field of view: diameter 22 mm or 30.93/15.50/7.64 Depth of field: > 4 mm (29612) or 18/4/2 mm (29613) Light intensity: > 28.000 lux Interchangeable adjustable eyepiece 12.5X

Illumination: longlife 5.9V / 5W LED Superior optics with individually adjustable eveniece Built-in rheostat for brightness adjustment Easily changeable, LED bulb

User-selectable built-in green filter Two (gross/fine) focus adjustment handles Two (gross/fine) height adjustment handles (838-1194 mm)

Smooth action control Main Power: 110V/220V

29620

Roller base for DIGITAL LED VIDEO COLPOSCOPES

**TECHNICAL SPECIFICATIONS** 

 $\epsilon$ 

Sony Japan colour CCD Pixels 1.200.000 (29620) 2,000,000 (29622) Resolution 825 TV Lines (29620) 1,000 TV Lines (29622)

Mirror image Electronic Shutter: automatic

>48 db (29620), >50 db (29622) S/N ratio: Illumination: high MCD super bright white shadowless LED light

Colour temperature: 7.000° K Test timer: Multigrade green filter: yes (4 grades, 5 for HD)

Blue filter: automatic and manual Focus: Focus distance 20-30 cm

1-55X (29620), 1-45X (29622) Zoom: Viewing area: Ø 170 mm - 10 mm Depth of view: Ø 200 mm - 5 mm

Magnification display: Yes Average LED lamp life: 50,000 hours
Video output: BNC and SVHS (both)

YPBPR and DVI (29622 only) Safety standard: complies to IEC 60601

100-240 VAC, 50/60 Hz

EMI/EMC Made in Australia

# **COLPOSCOPY** IMAGE, VIDEO & PATIENT DATA MANAGEMENT SOFTWARE

• 29621 COLPOSCOPY SOFTWARE FOR COLPRO COLPOSCOPE AND COLPY WITH DIGITAL CAMERA

even if the patient moves. 1-55X (29620), 1-45X (29622).

A powerful IT tool in the hands of our busy gynaecologists to manage not only videos, images, clinical data and details of the patients, but also to provide them an opportunity to store, edit, burn on CD or DVD, print the detailed reports and use graphical data for presentation. Multilanguage software (GB, ES, IT, DE, FR, PT). Footswitch for capturing and saving images.

Compatible with Windows 7 (64-bit) / XP / Vista, Windows 8 and 10 Operating Systems

Fasy to install and maintain

casy to histan and maintain.

Password protected log-in to ensure data privacy.

Enormous level of live recording facilities and image capturing at very high pixels simultaneously with just a click.

Various kinds of colposcopy video clippings. movies, images for reference and education purpose have been incorporated in the software. Print out of reports with relevant details can be prepared for future follow-up

tested

of the patient Comparison mode with linked images Forensic examination & sexual abuse Leep/Lleitz approach to treat high grade dysplasia

tistical data representation with graph Multiformat 1-2-3-4 images diagnosis report HAMMOND graph (biopsy graph) Marking and highlighting



167

### SONOST 3000 - ULTRASOUND BONE DENSITOMETER

#### • 33996 SONOST 3000 with integrated software Waterless Ultrasound Bone Densitometer (BMD).

Sonost 3000 is a portable, economic solution for evaluating the risk of osteoporotic fracture. Its high accuracy assists in the first diagnosis of osteoporosis monitoring bone changes. It provides fast, convenient and easy-to-use informations on bone quality and fracture risk.

It can be connected to a keyboard to a monitor for data reading and to an external printer for A4 printing Main features:

- superior precision
- full dry and stand alone system
- fast measurement (only 15 seconds)
- auto positioning probe
- permanent coupling pad
- over 10,000 memories
- Manual: GB, IT (ES on request).

33250 THERMAL PAPER 57 mm x 25 m (pack of 5 rolls)





#### TECHNICAL SPECIFICATIONS

Measurement site: Calcaneus (Heel bone) Scan Time: 15 seconds

Measurement

In Vivo:

Weight:

Transducer

Estimated Index:

Estimated heel BMD and Bone Quality Index (BQI) Obtained from measured Broad band Ultrasound Attenuation (BUA) and Speed of Sound (SOS) BUA (C.V.%) 1.5 SOS (C.V.%) BQI (C.V.%) 1.5

0.2 25 mm - 100 mm Automatic adjustment 10,000 patient information Separation range: Storage capacity coupling gel (water not used) 6.4 inch TFT LCD (65536 colour) Coupling method: Display: User Interface: Touch screen

USB for connection to mouse or keyboard Thermal Printer AC 100V~240V - 50/60Hz - 130W Operating voltage

30x62x39 cm

### AC-2311 LED VIDEO COLPOSCOPE WITH CAMERA

### • 29624 AC-2311 LED VIDEO COLPOSCOPE WITH CAMERA

- Superb optical features:
- The excellent optical design allows:
- high resolution
- 2 real 3-dimensional precise image reproduction
- large depth of field
- 4 wide field of view
- 5 good contrast

Apochromatic optics design can correct the chromatic aberration of three types of coloured light effectively. It ensures the reduction and saturation of image colour and improves resolution, contrast and view depth of image.

- 3-step magnification:

3-step magnification (3.75X - 7.5X - 15X) provides larger magnifying range and more selection from lowest magnification for an overview to high magnification for precise and close inspection and treatment.

- Two optical circles for quick measuring size or tissue

- Integrated green filter

It can help to recognize blood vessels

- LED illumination

LED coaxial illuminator provides pure white colour light similar to sunlight to show real colour. Bulb life over 10,000 hours/10 years for long lasting performance. It saves your cost for the spare bulbs & electric charge.

- Integrated camera

The images from integrated video camera can be transferred directly into a monitor or a TV, into a computer with USB adapter or stored into a hard disk recorder.

- Ergonomic design for comfortably long time precision operation
- It is supplied completely assembled and ready for use
   29621 COLPOSCOPY SOFTWARE see page 167



#### TECHNICAL SPECIFICATIONS

Total magnification 3.75X, 7.5X, 15X 300mm focal length Field of View: Ø 79 mm, 39 mm, 19 mm Depth of Field: 4.5 mm, 1.13 mm, 0.76 mm Light intensity >25,000 LUX Individually adjustable eyepiece 16.7X Right eyepiece with built-in two circles to measure the size of the problem you see Built-in rheostat for brightness

adjustment User-selectable built-in green filter for enhanced contrast LED bulb is easily changeable Working height: 975 mm to 1,135 mm Fine focus adjustment handles Two (Gross/Fine) height adjustment Main power supply: 100 V to 240 V Weight: 11 kg

### PC-8000 PRO HOSPITAL FOETAL MONITOR



• 29550 PC-8000 PRO SINGLE FOETAL MONITOR

• 29551 PC-8000 PRO TWINS FOETAL MONITOR Maternal foetal monitor suitable for hospital use. Main features:

- 12.1" High-brightness TFT display (800x600 pixel)

- parameters: ECG, SpO<sub>2</sub>, NIBP, TEMP, RESP, PR, FHR, TOCO & FM - rotatable screen viewed from different directions and 5 different styles of operation display

- equipped with reliable, high sensitivity, 12-element pulse doppler transducer

- FHR and TOCO trend review

- store and view of 48-hours


monitoring data built-in Linux operation system

built-in high-speed thermal printer

internal rechargeable Li-ion battery

visual and audible alarms

selectable internal software: GB, FR, IT, ES, PT, PL, RU, TR.



#### 29552 US probe (ultrasonic probe) - spare 29553 UC/TOCO probe - spare

29554 Event marker (foetal movement probe) - spare

29555 Abdominal belt - spare

**29556** Z-fold paper 112x100 mm for 29550 - 20 boxes of 150 sheets **29557** Z-fold paper 150x100 mm for 29551 - 25 boxes of 150 sheets

PC 8000 PRO ACCESSORIES

33297 3M RED DOT™ electrodes Ø 6 cm - box of 1.000

#### **TECHNICAL SPECIFICATIONS**

Foetal monitoring:

Ultrasonic coupling gel

Ultrasonic probe

Abdominal belt

ECG cable

Ultrasonic working frequency: 1 MHz tolerance: ±5%

ISATA: ≤10 mW/cm

Foetal heart rate measuring range: 50 - 240 bpm ±2 bpm FHR alarm: when the FHR value exceeds the preset value, the monitor will send an alarm for 30 s that will stop by pressing alarm key

STANDARD ACCESSORIES

Blood pressure cuff

Power cable

Grounding wire

Blood oxygen probe

Disposable electrode

User Manual (GB, IT)

Body temperature probe

TOCO probe Zero setting mode: manual

TOCO measuring range: 0 ~ 100% tolerance: ±10%

Marker mode Mode: Manual and AUTO

ECG/RESP Monitoring:

ECG amplification bandwidth:

US probe (ultrasonic probe) 1 (29550 only)

US probe (ultrasonic probe) 2 (29551 only)

UC/TOCO probe (uterine contraction probe) 1

Event marker (foetal movement probe)

Monitoring mode: 1 - 40 Hz (+0.4 db -3 db) Diagnostic mode: 1 - 75 Hz (+0.4 db -3 db)

HR range:  $30 \sim 300$  bpm ( $\pm 1\%$  or  $\pm 1$  bpm, whichever is greater)

CMRR (Common-Mode Rejection Ratio): ≥80 dB

Time constant: Monitoring mode: ≥0.3 s, Diagnostic mode: ≥3.2 s ECG gain: X1/2 5 mm/mV ±5%, X1 10 mm/mV ±5%, X2 20 mm/mV ±5% RESP monitoring range: 0-100 rpm (±5% or ±2 rpm, whichever is greater)

NIBP Monitoring: Measuring technology: Automatic measurement by smart oscillating method

Initial cuff inflation pressure: adult mode 180 mmHg Max. inflation pressure allowed: adult: 300 mmHg

Accuracy: ±10% or ±10 mmHg, whichever is greater Factory-set measuring mode: manual

Measuring intervals: 1-240 minutes adjustable, interval tolerance: <10s Monitoring range: Systolic pressure: 50 ~ 240 mmHg

Mean arterial pressure: 25 ~ 200 mmHg Diastolic pressure:15 ~ 180 mmHg

Measurement accuracy ±8 mmHg

SpO<sub>2</sub>/Temperature Monitoring:

Pulse oxygen saturation range: 0 - 99% (75 - 99% ±2%, 50 - 74% ±3%)

Pulse rate: 30 - 240 bpm (±2% or ±2 bpm, whichever is greater) Temperature response time: ≤150 s

Other Technical Information and Parameters:

Mains power supply: 100 ~ 250 VAC, 50/60 Hz <100 VA Internal power supply: Li-ion, rechargeable battery

6 hours to full recharge during monitoring 4 hours to full recharge when monitor is off

Display mode: TFT display Alarm: audible & visible alarm

Networking interface: Net port

Printing paper Z-Fold, 112x90 mm Protection against electric shock: Class I Weight: 4 kg


Size: 36x30xh 12 cm **Built-in thermal printer** 

1/2/3 cm/min real time printing speed, fast print speed (stored traces) Record message ID, name, age, date, time, print speed etc.

### GIMA FOETAL MONITOR PAPER FOR DIFFERENT BRANDS

GIMA Code	FOETAL MONITOR manufacturer and model	Standard FHR rate/BPM**	Туре	Width mm	Length mm or m*	Sheet	Grid***	Min. order
		BIG	ONET					
29528	Fetalcare FC/1400	Int 60/200	roll	152	25	-	green	10
29522	Fetalcare FC/700	US 60/240	roll	215	23	-	green	5
29544	Fetatrack 310	US 60/240	pack	114	100	150	blue	20
		co	MEN					
29556	Star 5000/C	Int 60/210	pack	112	100	150	or/red	20
29558	Star 5000/D	Int 60/210	pack	151	100	150	or/red	25
29557	Star 5000/D	US 30/240	pack	151	100	150	or/red	25
		CORO	METRI	CS				
29561	4305-BAO mod. 116-145-150- 151-118	Int 60/200	pack	152	90	150	or/red	25
29562	4305-BAO mod. 116-145-150- 151-118	US 30/240	pack	152	90	150	or/red	25

١			<u> </u>	-171		ט ו	11/	<u> 1111</u>	<u> フン</u>
	GIMA Code	FOETAL MONITOR manufacturer and model	Standard FHR rate/BPM**	Туре	Width mm	Length mm or m*	Sheet	Grid***	Min. order
			EI	DAN					
	29570	Cadence II F/6-F/9 Cadence II	US 30/240 Int 60/200 Int 60/200	roll pack roll	112 152 112	90 90 90	150 150 150	or/red or/red or/red	20 25 20
			HEWLET	T PACE	KARD				
	29575	9270-0630 - 8040/A, 8030/A, 8020/A	Int 60/200	pack	151	100	150	green	25
	29576	M1911A	Int 60/200	pack	151	100	150	green	25
			SHENZE	V CREA	ATIVE			_	
		PC-8000 PRO single PC-8000 PRO twins PC-8000 PRO twins	Int 60/210	pack	112 151 151	100 100 100	150 150 150	or/red or/red or/red	20 25 25
	SONICAID								
	29580	Meridian/800 - Team	White paper	pack	143	150	300	white	10
	···or/red	: grid could be orang	e or red colo	ur					



1 MHz probe USB function memory storage Wi-Fi conver Yellow/areen LED alarm for easier recogniton of device and patient status BG 10-100 BX

Toco probe

Dimensions

Thermal array printer

Li-ion battery (option)

Foetal heart rate

Uterine contraction

Auto CTG analysis

Display

Power



1 MHz to minimize broken FHR waveforms even if the fetus moves 29520 and 29516-7 Printout

CTG interpretation report

- both standard and A4 size paper usable - normal fax paper usable

Other advantages

Wi-Fi central monitoring up to 16 beds (Option) PC compatible - internal battery lasting 2-hours (Option)

power adapter 100-240 V, 50-60 Hz - multilanguage internal software: GB, FR, IT, ES, PT, DE, PL, RO, RU, CZ, HU, BG, TR, KR, CN. Recommended after week 30

**TECHNICAL SPECIFICATIONS** 296x97.5xh 305.5 mm - Approx. 2.9kg 7" TFT Wide LCD screen (800x480) print speed: 1, 2, 3 cm/min (real time) paper feeding function

input: 100-240 V, 1.5-0.7 A, 50-60 Hz output: +18 V = 2.8 A 4 hours (charging) - 2 hours (discharging) LAN, Wi-Fi, USB memory

input signal: ultrasound pulsed doppler ultrasound frequency: 1.0 Mhz, 975 Khz ultrasound power: <10 mW/cm<sup>2</sup> FHR detection method: autocorrelation FHR range: 50-210 bpm ±1 bpm (120-160)

0123 Foetal movement measurement detection source; ultrasound pulsed doppler event marker input source: external transducer with load cell reference control: one touch switch, auto zer measurement range: 0-99

Adjustable

29519

height

average baseline FHR number of UC variable deceleration high episode number of acceleration low episode number of deceleration short term variability signal loss

Easy-to-use

easy setup

- one- touch operation and

- s/w upgrade via internet

- alarm function (FHR high-low)

### COST-EFFECTIVE SINGLE FOETAL MONITOR

• 29520 FOETAL MONITOR GIMA FC 700

Cost-effective single foetal monitor Extreme ultrasound doppler sensitivity high-accuracy with 1 Mhz frequency - automatic/manual Foetal Movement detection - auto NST (Nonstress test) function from 10 min. to 1 hour 29520

### Data printout

External link

Foetal heart rate

Uterine contraction

- CTG analysis printing

- A4 size chart paper with perforation line - plain thermal fax paper usable

- print speed 1, 2, 3 cm/min

TECHNICAL SPECIFICATIONS 296x92.5xh 305.5 - approx. 2.9 kg 7 segment LED - 2 channels (FHR. UC) Dimensions Display print speed: 1, 2, 3 cm/min paper feeding function input: 100-240 VAC, 50-60 Hz, 1.2 A Thermal printer

output: 18 VDC, 2.5 A RS-232C input signal: ultrasound pulsed doppler ultrasound frequency: 1.0 Mhz ultrasound power: <10 mW/cm²
FHR detection method: auto correlation FHR range: 50-240 bpm ±1 bpm (120-160) reference (zero) control: one touch switch

measurement range: 0-99 units Foetal movement measurement detection source; ultrasound pulsed doppler average baseline FHR

number of UC number of acceleration number of deceleration (late, early, variable) Tachycardia (moderate, severe) Bradychardia (moderate, severe)

### ACCESSORIES FOR FC700 AND FC1400 FOETAL MONITORS

For 29520	For 29530-31	For 29516-17	ACCESSORIES FOR FOETAL MONITORS	29527 WIRELESS CENTRAL STATION FOR FOETAL MONITORS
29522 - 29523 29524 29529 -	29528 29532 - - 29533	29528 29538 - - 29539	Paper roll - 215 mm x 23 m Paper roll - 152 mm x 25 m US doppler probe - spare UC/Toco probe up to S/N FF07XXX UC/Toco probe since S/N FF08XXX Toco transducer - spare	Central station (PC, monitor, software, wireless, connection kit) to manage up to 16 monitors.  Wireless bluetooth 16 beds central system (distance 10-100 m)
29519	29519 29534	29519 - 29536	Trolley with 2 baskets (adjustable height) Battery NI-MH, 12 V, 2,600 mA Li-Ion battery	STANDARD ACCESSORIES (29516, 29517, 29520, 29530, 29531) 1 US doppler probe (2 for 29517 and 29531) 1 ultrasonic gel 1 power cord 2 (29520) or 3 fixing belt (29516-7) 1 stand 1 user manual
33747 29525	33747 29525	33747 29525	AC adaptor Belt 5.3x148 cm	1 TOCO probe 2 paper rolls 1 marker for lying-in women 1 adaptor

### GIMA FOETAL POCKET DOPPLERS - MADE IN U.K.



#### 29502 GIMA FOETAL DOPPLER G2002

Interchangeable

probe - with carrying bag

batteries with battery charger

without probe - with carrying bag

2MHz waterproof probe - gynaecology

3MHz waterproof probe - gynaecology

4MHz waterproof probe - vascular

8MHz waterproof probe - vascular

water proof

probes

GIMA

29493

29496

29497

29498

29499

Small, lightweight, high sensitivity pocket Doppler, with 2 MHz foetal probe, ideal for General Practitioner's or Midwife's use for routine antenatal foetal detection.

Pocket Doppler can be used to detect the beating foetal heart from about 10th week of gestation. It may be used to locate the position of the placenta, thus aiding in the early diagnosis of placenta praevia, to survey blood flow of the umbilical cord and to diagnose multiple pregnancies. Foetal signals are easily located using the lightweight narrow beam transducer while internal signal processing minimizes noise artefacts. Audio foetal heart signals are available to the user via the built-in loudspeaker or option headset, with output level controlled by rotary volume control.

LCD display

(29493 only

Up to 4 hours

continuous use

Weight: 290 g (including battery)

Heart rate range: 50-210 bpm

Auto average and manual mode

Recording length: 480 s / 240 s

Auto power-off to save power

Manual: GB. IT - on request: DE. ES. FR. PT.

29499

COMMINICA

29496

• 29511 ON/OFF MEMBRANE SWITCH for code 29502

#### 29503 GIMA FOETAL DOPPLER D2003 with display

Pocket foetal doppler with same specification as code 29502 but with built-in foetal heart rate processing. Foetal heart rate (FHR) is displayed on a large LCD display whilst internal signal process minimises noise artefacts.

#### 29505 GIMA FOETAL DOPPLER D2005 with display and waterproof probe

Same as code 29503 but waterproof probe and sealed electronics.

All units are supplied in a nice bag with a tube of coupling gel and user manual in English, Spanish, French, German, Italian, Greek, Portuguese.



29512 ON/OFF MEMBRANE SWITCH for codes 29503, 29505

#### TECHNICAL SPECIFICATION (CODES 29502 - 29503 - 29505)

Frequency: 2 MHz continuous wave Transducer: 2 crystal narrow bean Output power: <10mW/mm2 SATA Audio Response 300Hz -1 KHz

autocorrelator (only code 29503 and 29505) FHR (Fetal heart rate): 50-210 bpm (29503, 29505) 60-210 bpm (29502)

resolution ± 1 bpm, accuracy ± 2 bpm Keys: 1 Key (for unit on/off)

Controls: rotary volume Indicators 3 digit FHR LCD display (codes 29503, 29505) FHR pulse icon (codes 29503, 29505), Battery low icon

Battery 9 V Alkaline Manganese Expected battery life: 8 hours

Headset: Audio output to optional headset Serial: RS232 interface (codes 29503, 29505)-jack 35 mm

Material: ABS / Noryl Size: 150 mm by 75 mm. Weight: 295 g (with transducer) Classification: Class I Type B - IEC 60601-I C € 0120

Warranty: 2 years (probe and cable included)

SONOTRAX DOPPLERS

29493

Size: 32x85x138 mm

Resolution: 1 bpm

Accuracy: ± 3 bpm

DOPPLERS AND INTERCHANGEABLE PROBES -

LATEX FREE

SONOTRAX LITE DOPPLER - without probe - with bag

SONOTRAX BASIC DOPPLER - with display - without

SONOTRAX PRO II DOPPLER with backlighted

display built-in audio recorder and rechargeable



### **BABY SOUND GIMA DOPPLER** • 29506 BABY SOUND GIMA FO-

interchangeable 1MHz probe portable and lightweight

built-in speaker to hear fetal heartbeat numeric and trend curve display for FHR

- automatic power-off function backlight LCD display

date, time, battery status display audible & visual FHR alarm

8-hour data storage

audio-out interface

fetal monitor DSP technology high-sensitivity probe

1 MHz or 2/2.5 working frequency store and recall FHR, up to 16 hours of FHR date storage recording function It allows hearing regularly the

heartheat of a foetus since 20 weeks, and warns in case of serious problems of the fetus (can monitor FHR during 10-12 weeks not regularly). For home and hospital use. Supplied with gel bottle, 3 AA batteries and user manual

29507 2.0/2.5 MHz DOPPLER PROBE

29508 1 MHz FOETAL MONITOR PROBE

The Fetal Doppler can be used as a portable Fetal Monitor if it works with 1MHz Fetal Monitor probe. It is suitable

for long-term monitoring and will be more accurate than with the Doppler probe TECHNICAL SPECIFICATION

Ultrasound working frequency: 1MHz + 5% 50-210 bpm Fetal heart rate: range: resolution 1 bpm

accuracy: Δlarm high limit: Ultrasound intensity: Dimension: 145x74x29 mm

Power supply

± 2 bpm 160 bpm < 5 mm/cm<sup>2</sup> 3 AA Batteries

Weight: 350 g

120 hpm

low limit

### SONOLINE "C" COLOUR SCREEN DOPPLER - FOETAL OR VASCULAR

- portable and lightweight
- built-in speaker
- TFT-LCD, real-time display of FHR
- three working modes: real-time FHR, average FHR and manual calculation
- display of FHR, bar graph and heartbeat waveform, red alarm for abnormal FHR
- low power consumption, continuously work for more than 8 hours with two "AA" batteries
- indication for probe-off and low
- battery - range of probes for foetal or vascular use: 2, 3, 4, 8 MHz probe Suitable for use after the 12th week of pregnancy

### TECHNICAL SPECIFICATIONS Ultrasound working frequency: 2 MHz ± 10% Fetal heart rate: 50-240 bpm 151 range: resolution: 1 bpm accuracy: ± 2 bpm Alarm high limit: 160 bpm low limit: 120 hpm Ultrasound intensity: < 5 mm/cm Auto power off after 1 minute no signal 0 135x92x29 mm Dimension: Weight: 245 g 2 AA Batteries LR6 - 1.5 V DC Power supply

	GIMA code	SONOLINE "C" COLOUR SCREEN DOPPLER
--	--------------	------------------------------------

29480 | SONOLINE "C"Colour screen doppler - without probe 29481 2 MHz waterproof probe - gynaecology

JAMNIOCENTESIS NEEDLES

For transabdominal sampling of amniotic fluid (usually between 15<sup>th</sup> and 18<sup>th</sup> pregnancy well) for prenatal diagnosis

cytogenetic and biochemical studies. Accurate sharpening

Its mandrel is provided with an ultrasound detectable tip

allowing an echo-guided insertion, and it is colour coded

for an easy identification of the needle size. The needle is

provided with an adjustable stopper to determine insertion depth, and with a female luer lock connector to collect the

**AMNIOCENTESIS NEEDLES - STERILE - box of 25** 

of the needle allows an easy and atraumatic insertion.

of genetic disorders of the foetus. It is also used for

amniotic fluid through a syringe. Made in Italy.

Needle 20 G x 100 mm

Needle 20 G x 120 mm

Needle 20 G x 150 mm

Needle 20 G x 180 mm

Needle 21 G x 120 mm

Needle 21 G x 150 mm

29482 3 MHz waterproof probe - gynaecology 29483 4 MHz waterproof probe - vascular 29484 8 MHz waterproof probe - vascular

### LATEX PROBE COVERS



- 29510 LATEX PROBE COVERS transparent bag of 100 pcs bulk
- 29513 LATEX PROBE COVERS transparent box of 50 • 29514 LATEX PROBE COVERS - transparent - box of 500
- Probes for ecography and doppler, Length 17 cm. Ø 3.3 cm Individually packed in single plastic bag, except 29510.

### OBSTETRIC STETHOSCOPES

GIMA

29636

29637

29638

29639

29640

29641

- 32501 SHORT OBSTETRIC STETHOSCOPE beech-wood • 32502 LONG OBSTETRIC STETHOSCOPE - beech-wood These stethoscopes are hand-craft manufactured, made in
- beech-wood accurately selected and seasoned for at least 3 years. They have a perfect finish with a special transparent varnish. Packed in single box. Made in Germany.
- 32505 PINARD STETHOSCOPE aluminium



### SUCTION CUPS

- 29980 SILICONE SUCTION CUP Ø 60x210 mm
- 29981 SILICONE SUCTION CUP Ø 70x210 mm Made in medical grade silicone.

Compatible with Gima aspirators, preferably over 20 l/min. Pressure to be adjusted by professional.

Soft suction cup for eas oint for Blue quideline for positioning

### SCHULTZE SALPINGOGRAPH

3 interchangeable cones (small-medium-large)

### • 29780 SALPINGOGRAPH

Instrument for hystero-salpingography and tubal insufflation, Prof. Gunter K. F. Schultze from Berlin type. Made in Germany.

• 29782 WATCH FOR SALPINGOGRAPH

• 29785 HYSTERO SYRINGE - 20 cc - LUER LOCK - spare ( Riester

HYSTEROSALPINGOGRAPH: STANDARD ACCESSORIES Watch for hystero Hystero syringe 20 cc Luer Lock

172

Instrument can also be read in the dark thanks

### **DELIVERY SETS**



• 38953 DELIVERY PACK - sterile - 7 pcs

2x Spencer Wells artery forceps - straight - 13 cm Umbilical scissors - 10.5 cm - US model Mayo gynaecological scissors - straight - 17 cm 2x Umbilical cord clamps. Super crepe sheet



26966 MINOR DELIVERY SET - 25 pcs

Kidney Dish 20 cm (8") - medium Kidney Dish 25 cm (10") - Jame Gallipot 150 ml - 6 oz - medium Brown Sadler episiotomy scissors - 14 cm Kocher artery forceps straight - 16 cm Kocher artery forceps straight - 18 cm Kocher artery forceps curved - 16 cm

Dissecting forceps toothed 1x2 - 14 cm 2 operating scissors sharp/blunt - straight - 15 cm 2 operating scissors sharp/blunt - curved - 15 cm 2 rampley sponge holding forceps - str. - 24 cm Museux Vulsellum forcens 8 mm - str. 24 cm 3 Cusco vaginal specula - small, medium, large 3 Sims vaginal specula - small, medium, large English TOE dissecting forceps plain - 14 cm Umbilical scissors USA Patent - 10.5 cm English TOE dissecting forceps plain - 18 cm Instrument tray with lid 45x30x6.2 cm

### S/S UMBILICAL SCISSORS




26827 S/S UMBILICAL SCISSORS

### UMBILICAL CLAMP



 29942 X-SAFE UMBILICAL CORD CLAMP - sterile - box of 500 Disposable umbilical cord clamp to allow a proper clamping of all umbilical cords and prevent their outcoming from the closing comb. Individually packed in coupled cellophane (nylon/ polyethylene) and medical paper to ensure safe hygienic conditions to user. Sterilized by ethylene oxide. Made in Europe

### **GYNAECOLOGY SET - STERILE**



• 23641 GYNAECOLOGY SET - sterile - box of 8

- 1 table cover 150x200 cm with central absorbent band
- 1 Mayo stand cover 80x145 cm
- 1 gynaecology drape for lithotomy position 290x240 cm with adhesive hole, built-in leggings, bag for liquid
- collection with filter and drain valve 1 drape 75x90 cm incision film 35x50 cm 3 adhesive strips 10x50 cm

4 towels 35x40 cm

- 23644 SET FOR CESAREAN SECTION sterile box of 8 1 table cover 150x200 cm with centra
- absorbent band 1 Mayo stand cover 80x145 cm

260x200x310 cm with incision film and bag for liquid collection 1 drape "baby blanket" 75x90 cm See picture at page 28

### MEMBRANE PERFORATOR

• 29945 AMNIOTIC MEMBRANE PERFORATOR - sterile - box of 600 Disposable amniotic perforator. This system is thought to be completely safe to avoid lesions to the foetus. ( 60373 Supplied in single sterile envelope.

### JI.D. BRACELET



GIMA code	I.D. BRACELET	Colour	Minimum order
29936	Newborn	light blue	box of 100 pcs.
29937	Newborn	pink	box of 100 pcs.
29938	Mother	light blue	box of 100 pcs.
29939	Mother	pink	box of 100 pcs.

### CUPS FOR HYSTEROGRAPHY AND SIFT SCREW SYRINGE



29920 CUPS FOR HYSTEROGRAPHY - 25 mm - sterile

• 29921 CUPS FOR HYSTEROGRAPHY - 30 mm - sterile • 29922 CUPS FOR HYSTEROGRAPHY - 35 mm - sterile

• 29923 CUPS CONNECTOR - sterile

Rigid, transparent tapered cup with a central conical cannula. Equipped with a 25 cm long flexible, pliable manipulator joined to the cup and two tubes equipped with clamps. One of these provides the vacuum, while the other injects the radiopaque medium. Perfect adhesion to the cervix by selfcentering is ensured by the tapered shape of the cup and the progressive application of a vacuum to the cup. The suction cup/ cannula unit is radiotransparent and allows the proximal area of the endocervix to be controlled. The radiologist is able to manipulate at a distance from the radioactive field while at the same time comfortably immobilizing the uterus. Latex free.

• 29928 SIFT SCREWTHREAD SYRINGE FOR CUPS - sterile Contrast medium is injected by turning the position of the syringe which is equipped with a thread, to enable easy and regular injection of the contrast medium.

If cup is used on our sift syringe, connector is not needed.

The disposable anoscope and rectoscope are sold in a paper and polyethylene envelope sterilized in ethylene oxide. Made in transp. atoxic, dust resistant plastic. Latex and phthalate free.

25947 - anoscope - 10 cm

Wolf / ACM

25944

25945

**ADAPTOR** 

included

Wolf/Acmi/Storz

Wolf/Acmi/Storz

Wolf/Acmi/Storz

Wolf/Acmi/Storz

Wolf/Acmi/Storz

25953

25 cm -

25949 - rectoscope - 25 cm

### DISPOSABLE ANO/PROCTO/SIGMOIDOSCOPES

### • 25953 F.O. ILLUMINATION HEAD

Perfectly fits and illuminates GIMA, HEINE, WELCH ALLYN, GPS disposable anoscopes, rectoscopes, proctoscopes. It can be connected to a light source by a F.O. cable or to a LED illumination system. See at page 195.

• 25947 DISPOSABLE ANOSCOPE - sterile - box of 60

Length 10 cm, with stylet diameter 15 mm, suitable for treatment of haemorrhoids. Atoxic, phthalate and latex free.

• 25949 DISPOSABLE RECTOSCOPE - sterile - box of 50

Length 25 cm, with stylet diameter 15 mm, graduated external scale in cm. Internal black tube allows accurate lighting. Atoxic, phthalate and latex free.

Disposable proctoscope see at page 152.

HEINE UNISPEC DISPOSABLE TUBES

- 25944 HEINE UNISPEC DISPOSABLE ANOSCOPE 85x20 mm
- E-003.19.911 box of 25
- 25945 HEINE UNISPEC DISPOSABLE PROCTOSCOPE 130x20 mm
- 25946 HEINE UNISPEC DISPOSABLE SIGMOIDOSCOPE 250x20 mm



### ILLUMINATION OF F.O. ANO/PROCTO/SIGMOIDOSCOPES



• 30799 ILLUMINATED HANDLE 6.0 VOLT • 30800 HALOGEN BULB - spare for 30799 Placed between the instrument and F.O. cable. Indipendent light source for F.O. instruments. Direct connection to all F.O. instruments.

• 30801 GIMA LIGHT SOURCE - see page 195

To connect anoscopes/rectoscopes/sigmoidoscope to Gima light source (30801) you need: F.O. cable (30818-30826), adaptor 30830) to connect cable to light source, 2 adaptors (30840, 30844) to connect sigmoidoscope to F.O. cable.

### F.O. ANOSCOPES, PROCTOSCOPES | F.O. SIGMOIDOSCOPES

code



GIMA code	F.O. ANOSCOPES - PROCTOSCOPES	included
29400	F.O. Anoscope Ø15x70 mm - with obturator	Wolf/Acmi/Storz
29401	F.O. Anoscope Ø20x70 mm - with obturator	Wolf/Acmi/Storz
29402	F.O. Anoscope Ø25x70 mm - with obturator	Wolf/Acmi/Storz
29403	Set of 3 F.O. anoscopes in a case	Wolf/Acmi/Storz
29405	F.O. Proctoscope Ø 20x130 mm -	Wolf/Acmi/Storz
	with obturator with 2.0X	

30840 ENDO STORZ ADAPTOR - to connect with Gima F.O. cable



### 30840 ENDO STORZ ADAPTOR - to connect with Gima F.O. cable S/S ACCESSORIES FOR F.O. ANOSCOPES, PROCTOSCOPES, SIGMOIDOSCOPES code 29420 Handle for Biopsy forceps 29421 Biopsy forceps 3.5x8 mm Cup Jaws - 420 mm 29422 Biopsy forceps 4 mm - Cutting Jaws - 420 mm 29425 Sponge Holding forceps - 400 mm 29426 Suction Tube - 400 mm

F.O. SIGMOIDOSCOPES WITH 1.5X MAGNIFICATION SWIVEL LENS

29410 F.O. Sigmoidoscope - 12x200 mm **29411** F.O. Sigmoidoscope - 16x250 mm

29412 F.O. Sigmoidoscope - 21x200 mm

29413 F.O. Sigmoidoscope - 21x250 mm

**29414** F.O. Sigmoidoscope - 21x300 mm

29427 Twin Bellow Insufflator

### **AMNIOSCOPE**: TUBES AND SET

 29970 AMNIOSCOPE SET includes 29971/2/3/5 and 30840 Set of three amnioscope tubes with shutter 200 mm length, 12, 16 and 20 mm diameter, and a clamp for fibre optic light. All tubes are graduated in centimetres, have a rounded end and are sterilizable by any method. Supplied in a cordura bag (27129). To light amnioscope set you can use GIMA 150 light source (code 30801), adapter (code 30830), F.O. cable (code 30818). Single tube needs adapter for clamp (code 30840) and clamp (29975).

• 29971 AMNIOSCOPE TUBE 12x24x200 mm 29972 AMNIOSCOPE TUBE 16x24x200 mm • 29973 AMNIOSCOPE TUBE 20x24x200 mm 29975 ANGLED CLAMP FOR LIGHT CONNECTION



### DISPOSABLE STERILE VAGINAL SPECULUM



SIDE SCREW SPECULUM - with gradual adjustment - sterile Disposable sterile speculum with gradual screw-action adjustment. Available in 3 sizes.

Mad		


GIMA code	SIDE SCREW VAGINAL SPECULUM - STERILE	Minimum order
	SIDE SCREW speculum - small Ø 20 mm	box of 100
	SIDE SCREW speculum - medium Ø 28 mm	box of 100
29985	SIDE SCREW speculum - large Ø 33 mm	box of 100
29986	SIDE SCREW speculum - mixed* sizes	box of 100

\*mixed box includes 20 small, 70 medium, 10 large vaginal speculur



Three different models of disposable sterile speculum. Sold in mixed box containing 3 sizes; small, medium, large. Made in China

GIMA	CENTRAL PIN / MIDDLE SCREW / TACHE	Minimum
code	STERILE	order
29995	CENTRAL PIN Speculum - mixed* sizes MIDDLE SCREW Speculum - mixed* sizes TACHE Speculum - mixed* sizes	box of 100 box of 100 box of 100



CUSCO SPECULUM - with gradual adjustment - sterile Disposable speculum with gradual screw-action adjustment. It is manufactured with the best non-toxic transparent material, comes in a single transparent vacuum pack and is sterilized with ethylene oxide. Sterilization is guaranteed by the special quality control label on each pack. Available 3 sizes distinguishable through screw colour. Made in Europe.

GIMA code	CUSCO VAGINAL SPECULUM - STERILE	Minimum order
29976	CUSCO Speculum - small 85 x 20 mm	box of 120
29977	CUSCO Speculum - medium 90 x 28 mm	box of 120
29978	CUSCO Speculum - large 100 x 36 mm	box of 108



PERNO SPECULUM - with central key adjustment

For dilation of the vaginal canal to expose the uterus neck. It allows the adjustment of the vaginal opening by positioning the blades and locking the central key. The smooth surface and rounded edges aid a comfortable introduction. The central key can be bent down for an easier introduction of cumbersome instruments. Available 3 sizes distinguishable through key colour. Made in Europe.

GIMA code	PERNO VAGINAL SPECULUM - STERILE	Minimum order
29947	PERNO Speculum - small Ø 20 mm PERNO Speculum - medium Ø 26 mm PERNO Speculum - large Ø 30 mm	box of 120 box of 120 box of 120

### STAINLESS STEEL VAGINAL SPECULUM - CUSCO AND COLLIN



GIMA code	STAINLESS STEEL SPECULUM
	Cusco stainless steel speculum - small 75x32 mm
	Cusco stainless steel speculum - medium 85x35 mm
	Cusco stainless steel speculum - large 100x37 mm
	Cusco stainless steel speculum - virgin 75x17 mm
29763	HF Cusco stainless steel speculum - medium
	with insulation for HF applications and suction connector
29768	Collin stainless steel speculum - medium 100x35 mm

### STERILE PAP TEST KITS



### • 29702 PAP TEST KIT - sterile - box of 100 pcs.

Pap-Test is a painless examination to detect the presence of any anomalous cells on the cervix.

It allows an early diagnosis of uterus neck cancer. The functional configuration of the kit allows a ready to go

The kit includes: two latex gloves, one perno speculum (medium size), one brush, one Ayre spatula (wooden), two slides and one box for them. Individually packed in sterile pouch.

### LUBRIGIMA: LUBRICANT GEL

• 29960 LUBRIGIMA - 250 ml Facilitates instruments insertion during gyn. examinations. Its special composition and high transparency do not alter the visual image when optical instruments are used. It does not contain spermicides and does not grease or stain.

It has acid Ph and good electrical conductivity. Water soluble

Well absorbed by the skin, does not irritate the mucosa. LATEX FREE.



### KLY LUBRICATING GEL

• 29704 PAP TEST KIT - sterile - box of 50 pcs

Ayre spatula A size (wooden), two slides.

Individually packed in sterile pouch. • 29703 PAP TEST KIT - sterile -

The kit includes: one pair latex glove, one side-screw

speculum (medium size), one GIMA brush ball, one

• 29957 KLY LUBRICATING GEL sachet 5 q - box of 100

Same as 29702 but without

box of 100 pcs

speculum.

- 29959 KLY LUBRICATING GEL tube 82 q - 1 tube
- 29958 KLY LUBRICATING GEL tube 42 g - sterile and paraben-free - 1 tube

Hypoallergenic lubricating gel, does not irritate skin, dissolves in water and is easily cleaned. It does not contain oil or oily substances. It has no toxic effects or odour. It is used in



Multilanguage box and manual (29958-9 only):

29703

Each 100 g contains 14 g

## TRAVEL ENEMA



• 28720 TRAVEL ENEMA - 2 I capacity Supplied in cardboard box with

2 cannulas (vaginal, anal), tap with opening lever, tube and

carrying bag. Multilanguage box: GB, FR, IT, ES.



### AYRE SPATULA - BIRCH WOOD AYRE SPATULA - PLASTIC

### CENTE DISTRICT AND IN IN 29745 Minimum **AYRE SPATULA - WOOD** 29743 Avre Spatula A 18 cm 500 pcs. 5 box of 100 pcs = of 500 pcs 29745 Sterile Ayre Spatula A 18 cm 100 pcs. Individually packed in sterile pouch, in box of 100




### GIMA BRUSH - MADE IN ITALY GIMA BRUSH - STERILE

### 22222222222 hrush Ø=6 mm ( € 0123 20 cm € 29739-29740


- 29739 GIMA BRUSH conical bag of 25 pcs.
- 29740 GIMA BRUSH conical box of 400 pcs.

These single-use endocervical brushes are an efficient method of collecting vulval, endocervical and nasal surface samples for cytological/microbiological examinations. Non sterile. Packed in plastic bags of 25 units, in carton of 400 units.

• 29742 GIMA BRUSH - conical - STERILE - box of 500 pcs As code 29740, individually packed in sterile plastic bag. Both codes are made in Italy.



- 29735 GIMA BRUSH B sterile box of 100 pcs.
- 29736 GIMA BRUSH BALL sterile box of 100 pcs. Each brush is packed in a single sterile pouch and box of 100 pouches.



### **COTTON SWABS**



### WALLACH PAPETTE, GIMA COLLECTOR



Wallach papette Plastic 16 cm Packed in bag of 100 pcs Sterile GIMA collector Plastic 19.5 cm 100 pcs. Packed in a single sterile pouch in box of 100 pouches





GIMA	"KARMAN" STYLE CURETTES	Minimum
code	FLEXIBLE - SINGLE USE - STERILE	order
29858	Karman Curette N° 4 - 4 mm x 24 cm	box of 20
29859	Karman Curette N° 5 - 5 mm x 24 cm	box of 20
29860	Karman Curette N° 6 - 6 mm x 24 cm	box of 20
29861	Karman Curette N° 7 - 7 mm x 24 cm	box of 20
29862	Karman Curette N° 8 - 8 mm x 24 cm	box of 20
29863	Karman Curette N° 9 - 9 mm x 24 cm	box of 20
29864	Karman Curette N° 10 - 10 mm x 24 cm	box of 20
29865	Karman Curette N° 11 - 11 mm x 24 cm	box of 20
29866	Karman Curette N° 12 - 12 mm x 24 cm	box of 20
20019 C	LICTION SYDINGS - 60 ml - one-way solf-blog	rkina valvo

Syringe with adaptor for use with Karman and Berkeley curettes.



GIMA	"REKKELEY" STATE COKELLES	Minimum
code	CURVED - RIGID - SINGLE USE - STERILE	order
29870	Berkeley Curette N° 7 - Ø 7 mm x 20 cm	box of 20
29871	Berkeley Curette N° 8 - Ø 8 mm x 20 cm	box of 20
29872	Berkeley Curette N° 9 - Ø 9 mm x 20 cm	box of 20
29873	Berkeley Curette N° 10 - Ø 10 mm x 20 cm	box of 20
29874	Berkeley Curette N° 11 - Ø 11 mm x 20 cm	box of 20
29875	Berkeley Curette N° 12 - Ø 12 mm x 20 cm	box of 20
	•	

29918	20 cm long	( <b>€</b> 0120
Si	rale use and sterile 60 ml cana	city

### CANNULAS FOR ENDOMETRIAL SAMPLING




• 29826 PIPELLA 1 hole - disposable, sterile - box of 100 • 29827 PIPELLA 4 holes - disposable, sterile - box of 100 For endometrial cytologic sampling.

It allows a painless and easy routine screening of the endometrium avoiding dilation and traction of the uterus neck

Hole: Ø 2.0-2.5 mm External diameter: 3.1 mm Length of cannula: 23.5 cm Length of handle: 26.5 cm

• 29940 ENDOGYN - disposable, sterile - box of 25 For cytologic endometrial sampling. It allows a painless and easy routine screening of the endometrium avoiding dilation and traction of the uterus neck. An outer sheath covers a mandrel with asymmetrical "V" shaped blades on the top. Each arm features fine toothings and thin cutting edges which are able to remove and keep more endometrial tissue. The head of one of the two arms features a hemispherical head which, when it goes back inside the sheath, allows for previously removed tissue to be aspirated.



### ■ FLEXIBLE HYSTEROMETERS - SINGLE USE - STERILE

With slider	Without slider	HYSTEROMETER SINGLE USE - STERILE - LATEX FREE	Minimum order
29930	29933	Hysterometer CH 10 - 29 cm	25 pcs.
29931	29934	Hysterometer CH 12 - 29 cm	25 pcs.
29932	29935	Hysterometer CH 14 - 29 cm	25 pcs.

Calibrated reading on the handle		<b>( €</b> 0459
	29930-32	
	29933-35	

### SPRAY FOR CITOLOGY FIXATION AND SLIDES



GIMA code	MICROSCOPE SLIDES  Size 76x26 mm, 1.0-1.2 mm thick 45° corners minimum order: pack of 200 pcs. (4 boxes of 50 pcs.)
29774	Plain side, ground edges
20775	Single and frosted candblasted hand ground add

29777 Twin frosted in both ends, ground edges, sandblasted band



• 29776 BOX FOR SLIDES Plastic, transparent box for storage of up to three slides.

29778 GIMAFIX SPRAY FOR CITOLOGY FIXATION

Fixer for cytology. Composition: isopropanole, poly-ethylenglycole. It does not contain propellants deleterious for the ozone. 250 cc bottle.



PREGNANCY TESTS: MIDSTREAM AND STRIP TYPE

market (self test) and for professional use in hospital or doctor's

All products are packed in cardboard boxes with multilingual user manual (GB, IT, ES, FR, GR, PT).

Main features of pregnancy tests:

- each test is individually packed in sealed pouch
- very quick, in 3 minutes. Some positive can be detected in 1 min - early detection: it can be used since the first day you miss your period (three days before for 29103)
- reliability: 99%
- sensitivity:
- 25 mlU/ml (29100, 29104, 29107, 29108) 1 min
- 10 mlU/ml (29103) 3 min
- Clinically tested



PREGNANCY TESTS Type Package 29103 SELF TEST midstream box of 1 pc (large wipe) 29104 SELF TEST midstream box of 1 pc 29107 SELF TEST midstream box of 2 pcs PROFESSIONAL TEST midstream box of 25 pcs 29100 PROFESSIONAL TEST | strip 4 mm box of 50 pcs

> PERSONALIZED BOX, MANUAL AND APPROVAL ( • 0197 FOR SELF TEST minimum 3000 pcs.





**OVULATION - FERTILITY TEST:** Easy to use test for professional use or OTC self test market. Early detection test, 99,9% accurate and clinically tested. Sensitivity: 40 mlU/ml.

All products are packed in cardboard boxes with multilingual user manual (GB, IT, ES, FR, GR, PT).

GIMA code	OVULATION TESTS	Туре	Package
29112	SELF TEST	midstream	box of 5 pcs
29114	SELF TEST	strip 4 mm	box of 6 pcs
29113	PROFESSIONAL TEST	strip 4 mm	box of 50 pc

### PREGNANCY DISC

YOUR LOGO HERE minimum 1,000 pcs.



 29099 PREGNANCY DISC Forecasts the forthcoming date of birth. Used by obstetrician and practitioners. Useful for assessment of drug administration.

2 rotating discs riveted in the center: 108 mm diameter (base), 76 mm diameter (top). Can be personalized with your logo for minimum 1,000 pcs.

SEE BASAL THERMOMETER FOR FERTILITY CONTROL -PAGE 78

179

178

• 29131 DISPLAY -

English - empty

• 29130 DISPLAY

Italian - empty

suitable for all gynaecology

Display is

self tests.

### • 29117 CHLAMYDIA TEST - box of 20 tests Provide accurate results in 10 minutes, giving doctors immediate diagnosis. High sensitivity and specificity. Each box includes 20 tests, reagents, female cervical swabs, tubes, droppers, pipette and user manual. For professional use. Male/Female swab specimen Add reagent A and B to specimen - Add 3 drops of extracted specimen - Read results after 10 minutes Male urine specimen Add reagent B and A to specimen Add 3 drops of extracted specimen Read results after 10 minutes


### CHLAMYDIA RAPID TEST CANDIDA ALBICANS TEST

### • 29105 CANDIDA TEST - box of 20 tests

Rapid, immunochromatographic test on vaginal smear. Easy to perform, able to identify by specific antibodies the presence of Candida in only 10 to 20 minutes. Validated by external studies, found to have a sensitivity of over 98% and specificity of over 94% when compared with reference methods for microbes identification (such as BD Affirm, USA). The reproducibility is at the highest level of rapid tests. As Candida affects 50% of

life and symptoms can be mistaken for those of Bacterial Vaginosis or other Vaginitis, the use of this test together with the vaginal pH test (see code 29110) allows discriminate between the two For professional use.

### **VAGINITIS TEST KIT**



### • 29111 VAGINITIS TEST KIT

A unique, easy-to-use and revolutionary test for gynecologists and operators. Finds the causes of the inflammation/vaginal infection in just 10 minutes. It replaces traditional bacterial tests that take days and costs only a tenth. When necessary dilute vaginal fluid specimen in a buffer solution and then transfer to reagent pad. The instruction manual contains a result guide and can be used to recognize: Trichomoniasis, negative gram bacteria, Gardnerella, Chlamydia, serious bacterial vaginitis. For professional use.

### VAGINAL PH TEST



women at least once in their



### • 29110 VAGINAL PH TEST - box of 10 pcs.

Quick test to determine vaginal PH. An easy routine test to check vaginal PH in just 1 minute to make sure it is within the physiological limits (< 4.7). An increase in the Ph level may indicate a change in the vaginal environment.

This could mean there is a possible vaginitis. The test is ideal for pregnant women and for women with particular diseases such as diabetes. For professional use.

### RUBBER AND SILICONE PESSARY FOR UTERINE PROLAPSE - LATEX FREE



29882	Rubber Pessary Ø 55 mm
29963	Rubber Pessary Ø 60 mm
29964	Rubber Pessary Ø 65 mm
29965	Rubber Pessary Ø 70 mm
29966	Rubber Pessary Ø 75 mm
29967	Rubber Pessary Ø 80 mm
29968	Rubber Pessary Ø 85 mm
29969	Rubber Pessary Ø 90 mm
29884	Rubber Pessary Ø 95 mm
SILIC	ONE PESSARY - autoclavable*
29892	Silicone Pessary Ø 55 mm
29893	Silicone Pessary Ø 60 mm
29894	Silicone Pessary Ø 65 mm
29895	Silicone Pessary Ø 70 mm
29896	Silicone Pessary Ø 75 mm
29897	Silicone Pessary Ø 80 mm
29898	Silicone Pessary Ø 85 mm
29899	Silicone Pessary Ø 90 mm
29900	Silicone Pessary Ø 95 mm
BLUE SI	LICONE PESSARY - autoclavable*
29905	Blue silicone Pessary Ø 70 mm
29906	Blue silicone Pessary Ø 75 mm
29907	Blue silicone Pessary Ø 80 mm
*Autoclavable	

RUBBER PESSARY - autoclavable

### DIATERMO MB 122 AND MB 160 MONO-BIPOLAR - 120 W - 160 W



• 30538 DIATERMO MB 122 VALUE\* - mono-bipolar - 120 W • 30540 DIATERMO MB 122 - mono-bipolar - 120 W

• 30541 DIATERMO MB 160 - mono-bipolar - 160 W

MB 122 and 160 are HF electrosurgical units suitable to perform middle monopolar or bipolar electrosurgery.

By selection of the modes of operation they provide pure cut, coagulated cut, forced coagulation, soft coagulation and, with forceps, bipolar coagulation. The use of either split or normal neutral plate is allowed. MB 160 is recommended in case of damp operational fields, for instance mucous, with consequent need to have reserve of usable power. For these reasons, MB 160 is suggested for Gynecological and orthopedic surgery. Leading-Edge Technology. This advanced concept device enables

highly professional surgery intervention thanks to ergonomic and safety features derived from high power theatre apparatus. Complete safety. Open Circuit (OC) Alarm warns the user that connection into the neutral plate has not been made or that the cable is disconnected or the neutral plate is not in contact with the patient. The alarm is signaled by an intermittent beep together with a flashing red light on the front panel. In this case HF emission for cut and coagulation operation is switched off. **OVT Alarm.** The unit includes an internal circuit protection warning when the current delivery is exceeding.

### STANDARD ACCESSORIES

MB single-use two button handle MB operative foot-switch 30577 (usable as alternative to handle) (30540-1 only)

MB flat neutral plate with cable 30564 (30540-1 only) Power cable 2 m Kit of 6 (MB 122) or 10 (MB 160) short autoclavable electrodes, diam. 2.4 mm User manual: available in GB, ES, IT, FR, PL

Does not include foot switch and MB flat neutral plate with cable

TECHNICAL SPECIFICATIONS											
MB122 MB160											
				Factor							
Minimum preselectable power	0		0								
Level step	1		1								
Maximum output power CUT (W)		250Ω	160	250Ω	1.5						
Maximum output power BLEND (W)	90	200Ω	120		2.1						
Maximum output power COAG FORCED (W)		150Ω	100		2.0						
Maximum output power COAG SOFT (W)	60	100Ω	80	100Ω	1.7						
Maximum output power BIPOLAR (W)	40	100Ω	60	100Ω	1.5						
Working frequency	600	kHz	600	kHz							
Weight kg	7		7								
Size LxHxD mm	260x	110x265	260>	(110x26	5						
Operating voltage (switchable)	115	-230	115	-230							
Mains frequency (Hz)	50-6	0	50-6	0							
Fuses 230Vac (5x20) TIMED	2x 3.	.15A	2x 3	.15A							
Fuses 115Vac (5x20) TIMED	2x 6	.3A	2x 6	.3A							
Electrical input power (VA)	300		350								
Electrical input current (230 Vac) (A)	1.3		1.5								
Electrical input current (115 Vac) (A)	2.6		3								
Five steps adjustable sound level											
(from 55- to 75dBA)	•		•								
Self-check	•		•								
Power accuracy output warning	•		•								
Split or not split patient plate allowed	•		•								
Last working condition storing	•		•								
Electrical Class (EN60601 - 1)	I CF		I CF								
MDD 93/42/EEC Class	IJЬ		IJЬ								
Patient circuit	F		F								

### MONOPOLAR ELECTROSURGERY UNIT - 50 W



• 30516 DIATERMO 106 - 50W - monopolar

This HF electrosurgery unit is particularly suitable for small operations and is recommended for dentistry, first aid and dermatology work. It offers precision of cut and immediate coagulation and give excellent results in a wide range of applications: from uterine coagulation to microcoagulation in dermatology. The modes of operation, CUT, COAG or

### TECHNICAL SPECIFICATIONS Output power: CUT 50 W/400 ohm

COAG 40 W/400 ohm RLEND 45 W/400 ohm Working frequency: 600 kHz ±10%

Size: 180x180xh 100 mm Weight: 2.8 kg Operating Voltage: 115/230 V - 50/60 Hz switchable Electric input power: 90 VA Fuse: 2x1 ΔT

Alarm for overheating Footswitch operating Norms: EN60601-1 Class I CF, EN60601-2-2 93/42/EEC (Class IIb) Warranty: 12 months

### STANDARD ACCESSORIES KIRKY single-use handle without buttons

Standard foot-switch (30577) Flat neutral plate with cable (30564) Kit of 6 short autoclavable electrodes, Ø 2.4 mm, length 5 cm Power cable 2 m - Schuko plug User manual: available in GB, IT, ES, FR

BLEND. can be easily selected by a switch on the front panel. The complete isolation between patient and the unit and strict respect of international norms guarantee total safety.

### MONO-BIPOLAR ELECTROSURGICAL UNITS 80W, 120W, 160W



CASUALTY SURGERY PEDIATRIC SURGERY PLASTIC SURGERY\* VASCULAR SURGERY DERMATOLOGY FIRST AID

OTORHINOLARYNGOLOGY UROLOGY\* GYNAECOLOGY VETERINARY DENTISTRY\*

\*Diatermo MR160 only \*Diatermo MB120 only





• 30628 DIATERMO MB 120D - mono-bipolar - 120 W

• 30629 DIATERMO MB 160D - mono-bipolar - 160 W

Diatermo MB are high frequency electrosurgical units suitable for minor and medium surgery.

MB allow pure CUT, cut-coagulation BLEND, superficial coagulation FORCED COAG, deep coagulation in absence of necrosis SOFT COAG and, with forceps, BIPOLAR coagulation. The digital reading of delivered power and the monitoring of operative function by microcontroller guarantees absolute reliability of working conditions.

MB allow a highly professional surgery through ergonomic and safety features. The connection of neutral electrode is constantly monitored. Safety control of patient/plate contact using split neutral electrode.

Possibility to control the output functions and the delivery of output power by the handle, allows the surgical operation without diverting attention from the surgical field. Features:

- minimum invasive surgery
- possibility to use bipolar forceps
- possibility to use split neutral electrodes - memorization of the last used settings
- power activation by pedal and/or handle
- digital adjustment and indication of the output power
- adjustment of the acoustic indicator intensity.



### TECHNICAL SPECIFICATIONS

	MB 80D	MB 120D	MB 160D
Max output power CUT	80 W-250 Ω	120 W-250 Ω	160 W-250
Max output power BLEND	60 W-250 Ω	90 W-200 Ω	120 W-200 9
Max output power FORCED COAG	50 W-150 Ω	80 W-150 Ω	100 W-150
Max output power SOFT COAG	40 W-100 Ω	60 W-100 Ω	80 W-100 Ω
Max output power BIPOLAR	30 W-100 Ω	40 W-100 Ω	60 W-100 Ω
Working frequency	600 kHz	600 kHz	600 kHz
Patient circuit	F	F	F
Selectable input voltage	115 - 230 Vac	115 - 230 Vac	115 - 230 Va
Mains frequency	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz
Electrical input power	230 VA	300 VA	350 VA
Size WxHxD mm	254x104x288	254x104x288	254x104x28
Weight	5 kgs	5 kgs	5 kgs
Controls: Patient/Plate circuit mor	nitoring, Outpu	at power monit	toring,
Salf chack control	J		_

EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class; I CF. MDD 93/42/EC Class: II b

### STANDARD ACCESSORIES

MR single use two button handle

Waterproof foot-switch 30577 (usable as alternative to handle) MB flat neutral plate with cable (30564)

Kit of 10 short autoclavable electrodes, diam. 2.4 mm.

Max output power CUT

User manual: GB, IT, available on request FR, ES, PL

80 W-400 Ω

### MONOPOLAR ELECTROSURGERY UNITS 50W AND 80W



DERMATOLOGY UT PATIENT SURGER FIRST AID VETERINARY\* VASCULAR SURGERY \*Diatermo 80 only

MED

Safety:

• 30625 DIATERMO 50 - monopolar • 30626 DIATERMO 80 - monopolar DIATERMO 50 and 80 are radiofrequency electrosurgical units 0051

suitable for minor monopolar surgery. Diatermo 50 through the function selection makes pure cut, cut coagulation (CUT 1 - CUT 2) and pure coagulation possible. Diatermo 80 has a multifunction selector which makes cutting (CUT), cut coagulation (BLEND), coagulation (COAG) and microcoagulation (MICRO) possible. The one-board microcontroller and digital display guarantee high safety and reliability under any conditions. They offer outstanding professional surgical results due to their ergonomic and superior safety features.

### Max output power CUT/COAG1 45 W-400 O Max output power CUT/COAG2 40 W-400 Ω 60 W-400 Ω Max output power BLEND Max output power COAG 40 W-400 Ω 50 W-400 Ω Max output power MICRO 20 W-600 O Working frequency 600 kHz 700 kHz Selectable input voltage 115 - 230 Vac 115 - 230 Vac Mains frequency 50 - 60 Hz 50 - 60 Hz Electrical input power 200 V/A 230 V/A Size WxHxD mm 190x85x239 190x85x239 2.5 kg Patient/Plate circuit monitoring, Output power monitoring, Self check control

EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF,

**TECHNICAL SPECIFICATIONS** 

50 W-400 O

### STANDARD ACCESSORIES

Single use handle Waterproof foot-switch (30577) MB flat neutral plate with cable (30564) Kit of 6 short autoclavable electrodes, Ø 2.4 mm, length 5 cm (30501/2/4/7/9/10) see page 187 Power cable 2 m - Schuko plug User manual: GB, IT, available on request FR, ES

### MONO-BIPOLAR ELECTROSURGICAL UNIT 200W



**ENDOSCOPY** FIRST AID GASTROENTEROLOGY GENERAL SURGERY GYNAECOLOGY NEUROSURGERY ORTHOPEDICS **OTORHINOLARYNGOLOGY** PEDIATRIC SURGERY PLASTIC SURGERY PNEUMOLOGY UROLOGY VASCULAR SURGERY VETERINARY

**OUTPATIENT SURGERY** 





### • 30630 DIATERMO MB 200D - 200 W

MB 200D is a high frequency electrosurgical equipment suitable for light and medium surgery, allows minimally invasive surgical procedure of resection, evaporation and coagulation.

MB 200D allows pure CUT, Cut-Coagulation BLEND, incision with reduced production of eschar ENHANCED, superficial coagulation FORCED COAG, deep coagulation in absence of necrosis SOFT COAG and BIPOLAR coagulation. Digital reading of delivered power and surveillance through microcontroller of the operational functions, assure absolute reliability of working conditions.

MB 200D allows a highly professional surgery through ergonomic and safety features. The connection of neutral electrode is constantly monitored. Safety control of patient/plate contact using split neutral electrode. Possibility to control the output functions and the delivery of output power by the handle, allows the surgical operation without diverting attention from the surgical field.

- patient-to-plate contact control
- split return electrode use

### STANDARD ACCESSORIES MB two-button autoclavable handle (30536)

Waterproof MB foot-switch (30577) MB flat neutral metal plate with cable (30564) Kit 10 short standard electrodes, diam, 2.4 mm

3 needle + 3 blade + 3 ball electrodes 7 cm Manual: available in GB, IT Power cable 5 m

- minimally invasive surgical treatment allowed

- monopolar and Bipolar indipendent output

- auto Start/Stop in Bipolar Coag

working condition planning power delivery by pedal and/or handle

digital regulation and indication of the output power

sound level control

adjustable power increment

TECHNICAL SPECIFICATIONS Maximum output power CUT Maximum output power ENHANCED 200W - 250Ω 120W - 250Ω Maximum output power BLEND 120W - 200Ω Maximum output power FORCED COAG 150W - 150Ω Maximum output power SOFT COAG 90W - 100Ω Maximum output power BIPOLAR COAG 80W - 50Ω Working frequency 600 kHz Patient circuit Mains voltage . 115-230 Vac Mains frequency 50-60 Hz

350 VA Electrical input power Size WxHxD mm 370x144x319 6 kgs Controls: Patient/Plate circuit monitoring, Output power monitoring,

Self check control EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class; I CF.

### DIATERMO MB 200 - MONO-BIPOLAR - 200W



MB two-button autoclavable handle (30536) MB waterproof foot-switch 30577 (usable in alternative to handle) MB flat neutral metal plate with cable (30564)

Kit 10 short standard electrodes, diam, 2.4 mm Power cable 2 m Manual: available in GB, IT

### • 30542 DIATERMO MB 200 - 200 W

DIATERMO MB200 is a HF electrosurgical unit suitable to perform middle monopolar or bipolar electrosurgery. The available waveforms and peak voltage value, as well as the accurate HF leakage current operation for polypectomy, TURP, intrauterine resections, endometriosis excision, etc. The units allow the accurate preset of the output power with as low as 1 Watt resolution and to perform coagulation by high crest factor current, to get an elevated thermal effect, as well as with low voltage low crest factor current, to get coagulation in absence of carbonization. Ten different programs related to ten different operative conditions could be stored and easily recalled by the surgeon. The use of either split or normal neutral plates are allowed. A special electronic circuit (Skin Plate Electronic Control) continuously checks if the plate is safely connected to the patient and detects unwanted short circuit in the connecting cable. An over time warning (OVT) is provided to prevent excessive heating of the tissue around the surgical target due to too long current delivery time.

TECHNICAL SPECIFICATIONS										
	Crest factor	Weight kg	8							
250Ω	1.5	Size LxHxD mm	360x150x265							
250Ω	1.6	Selectable mains power(Vac)	115 -230							
250Ω	1.7	Mains frequency (Hz)	50-60							
250Ω	1.8	Fuses 115Vac - 230Vac (5x20) TIMED	2x 6.3A - 2x 3.15A							
200Ω	2.1	Power accuracy output warning system	•							
150Ω	2.0	Split or not split patient plate allowed	•							
100Ω	1.7	Electrical Class (EN60601 - 1)	I CF							
100Ω	1.5	MDD 93/42/EEC Class	II b							
250Ω	1.5	Patient circuit	F							
Z		Duty cycle (action/pause) in seconds	10/30							
	250Ω 250Ω 250Ω 200Ω 150Ω 100Ω 100Ω 250Ω	Crest factor           2500         1.5           2500         1.6           2500         1.7           2500         1.8           2000         2.1           1500         2.0           1000         1.7           1000         1.5           2500         1.5	Crest factor         Weight kg           250Ω         1.5         Size LxHxD mm           250Ω         1.6         Selectable mains power(Vac)           250Ω         1.7         Mains frequency (Hz)           250Ω         1.8         Fuses 115Vac - 230Vac (5x20) TIMED           200Ω         2.1         Power accuracy output warning system           150Ω         2.0         Split or not split patient plate allowed           100Ω         1.7         Electrical Class (EN60601 - 1)           100Ω         1.5         MDD 93/42/EEC Class           250Ω         1.5         Patient circuit							

M

OUTPATIENT SURGERY DERMATOLOGY VASCULAR SURGERY GYNECOLOGY DENTAL \* OTORHINOLARYNGOLOGY

PEDIATRIC SURGERY\*\*

FIRST AID PLASTIC SURGERY\*\*

**ENDOSCOPY** 

OPHTHALMOLOGY

NEUROSURGERY\*\*

PODIATRY\*\* PNEUMOLOGY\*\*

UROLOGY\*\*

VETERINARY

GASTROENTEROLOGY ORTHOPEDICS\*\*

\* Diatermo MB 120 only

\*\*Diatermo MB 200 only

MED

### MONOPOLAR AND BIPOLAR ELECTROSURGICAL UNITS 120W AND 200W



 30631 DIATERMO MB 120 FLASH • 30633 DIATERMO MB 200 FLASH

MB FLASH are a High Frequency ElectroSurgical equipment suitable for precision monopolar and bipolar surgery and micro-surgery without tissue alterations.

MB FLASH allow surgical treatments with programmable times operations up to milliseconds or with traditional mode.

MB FLASH allow pure CUT, cut-coagulation BLEND, incision with reduced production of eschar ENHANCED, superficial coagulation FORCED COAG, deep coagulation in absence of necrosis SOFT COAG and BIPOLAR coagulation. Digital reading of delivered power and the surveillance through microcontroller of the operational functions, assure absolute reliability of the working conditions.

MB FLASH allow a highly professional surgery through ergonomic and safety features.

### **TECHNICAL SPECIFICATIONS**

	MB 120F	MB 200F
Max output power CUT	120 W-250 Ω	200 W-250 Ω
Max output power BLEND	90 W-200 Ω	120 W-200 Ω
Max output power ENHANCED	90 W-250 Ω	120 W-250 Ω
Max output power FORCED COAG	80 W-150 Ω	150 W-150 Ω
Max output power SOFT COAG	60 W-100 Ω	90 W-100 Ω
Max output power BIPOLAR COAG	60 W-50 Ω	80 W-50 Ω
Working frequency	600 kHz	600 kHz
RF power pulse emission time	10ms - 30sec	10ms - 30sec
RF power pulse interval	1 - 9	1 - 9
Patient circuit	F	F
Selectable input voltage	115 - 230 Vac	115 - 230 Vac
Mains frequency	50 - 60 Hz	50 - 60 Hz
Electrical input power	300 VA	350 VA
Size WxHxD mm	370x144x319	370x144x319
Weight	6 kg	6 kg
Controls: Patient/Plate circuit monitoring (	Output power m	onitoring.

Connection of neutral electrode is constantly monitored.

Safety control of patient/plate contact using split neutral electrode. Possibility to control the output functions and the delivery of output power by handle, allows surgical operation without diverting attention from the

### surgical field. Features:

- patient to plate contact control
- split return electrode use allowed
- minimally invasive surgical treatment allowed - Monopolar and Bipolar independent output
- auto Start/Stop in Bipolar Coag
- working condition planning
- power delivery by pedal and/or handle
- digital regulation and indication of the output power
- sound level control
- adjustable power increment
- RF power pulse emission time setting
- RF power pulse interval setting

### STANDARD ACCESSORIES

MB two-button autoclave handle (30536) Waterproof MB footswitch (30577) MB flat neutral plate with cable (30564) 2 disposable ground pads (30562)

Kit 10 short standard electrodes Ø 2.4 mm 3 needle + 3 blade + 3 ball electrodes 7 cm Power cable 5m

Microsurgery handle (30552) Microsurgery needles 10 pieces Manual: GB, IT





### **ELECTRODEPILATOR**

Safety: EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF,

### 28340 ELECTRO-DEPILATOR 400 This device ensures a definitive depilation with thermolitic

MDD 93/42/FC Class: II b

method. It delivers a current of radiofrequency to cause the heating and consequent coagulation of the papilla, reached through the introduction of a needle into the follicle of the hair. Provided with highly reliable electronic integrated components, with RF intensity adjustable with continuity and luminous working signal.

It comes complete with footswitch, handpiece for depilation. depilation needle and power cable (2 m).

### TECHNICAL SPECIFICATIONS

RF output frequency: 1.9 ±10% MHz Modulation: sinusoidal Maximum output power: 7 +2Watt Size: 260x265xh 110 mm

Weight: 4 kg Operating voltage: 115/230 V - 50/60 Hz switchable Norms: CEI 62-39 Class: I-BF

# CSQ MED

30552 HANDPIECE FOR DEPILATION

• 30577 FOOTSWITCH

### HOSPITAL HF ELECTROSURGICAL UNITS 240 AND 380 WATT



CSQ

30690

CONTEMPORARY DUAL MODE MB 240 and 380 car be used in the same time in monopolar

• 30690 DIATERMO MB 240

• 30692 DIATERMO MB 380

These HF electrosurgical units can be used to execute monopolar and bipolar surgery when high precision and reliability are essential, as in the endoscopic surgery. EASY TO USE

Graphic icons allow an easy selection of the operation mode. All operating conditions and selected output controls are represented by bright digital indications.

The monopolar cut can be performed by pure sine current to obtain an incision with a minimum damage for the adjacent tissues and sure recovery for first intention.

Two different modes of modulation allow to reduce bleeding during monopolar cut. In the bipolar mode the cut can be effected by pure sine current.

### HEMOSTASIS

When the surgical action requires the obliteration of a blood vessel the availability of currents with different coagulative powers enables this type of work both with monopolar and bipolar surgery

### FULGURATION

When it is necessary to cause a superficial necrosis of wide areas, protecting the deeper tissues, a special coagulant current that dehydrates the superficial layer of the tissue and reduces the possibility to damage those beneath is available for the operation.

### OUTPUT CONTROL

(accessories not included)

Norms: IEC 601-2-2 - IEC 601-1 CE, 93/42/EEC

Output power levels are adjustable through incremental

A special electronic circuit (Skin Plate Electronic Control) continuously warns the plate to patient contact safety and unwanted short circuit in the connec-

encoders that allow the exact pre-sets and repetition of the values. The output function is linearized and controlled by ultra-modern electronic micro-controllers which will interrupt power if any alarm condition happens.

### SAFETY OF USE

Circuits dedicated to the safety of operator and patient are the priority. This ensure the leakage current is kept well under the international requirements values, whatever the output condition. Monopolar and bipolar output circuits are completely floating and the use of the defibrillator is allowed while the reference plate patient is connected.

### RELIABILITY

DIATERMO MB uses all solid state electronic circuits and is made with interchangeable units for a fast and effective maintenance. Automatic control circuits protect the units from damage also in case of repeated improper use.





### STANDARD ACCESSORIES


- Power supply cord SIEM-CEE 5 m Two-button autoclavable handle (30536) Two-button single use handle
- Cable for disposable plate Disposable plate Water proof double foot switch
- Short, general surgery blade electrode
  Long, general surgery blade electrode
  Short, general surgery needle electrode
  Short, general surgery ball electrode

- 3 Short, general surg

### - User manual (IT, GB, ES) - Service manual (IT, GB)

### LAPAROSCOPIC ELECTRODES

Cut output



90W

0.5 kV 0.5 kV

100 Ohm

### HIGH POWER ELECTROSURGICAL UNITS 300 AND 400 WATT



### 30634 DIATERMO MR 300D

• 30635 DIATERMO MB 400D DIATERMO MB300D and MB400D are high frequency electrosurgical equipments suitable to deliver current for monopolar cut and coagulated cut (with different levels of coagulation),

bipolar cut and coagulation. TWIN OPERATIVE ACTIVITY

- two output channels for monopolar cutting
- two independent setting and output channels for the most frequent monopolar coagulation

### CONTROLLED CUTTING PROCEDURES

- enhanced cutting current for eschar free incision
- cutting current with selectable coagulating property for bleeding controlled dissection
- low capacitive coupling by slow BLEND current for endoscopic procedures

### TWIN CONTROLLED COAGULATION PROCEDURES

- SPEEDY coagulation and DEEP coagulation available to two operators
- SPRAY coagulation by hand switch or foot switch controls **EXTENSIVE BIPOLAR FÉATURES**
- bipolar cutting current with selectable bleeding control
- slow BLEND cutting current

### - automatic Start/Stop coagulation functions SURGEON AND PATIENT TOTAL SAFETY

- acceptability of contact impedance between patient body and return electrode continuously monitored by Skin Plate Electronic Control (SPEC)
- H.F. Leakage currents continuously monitored
- mains fluctuation automatically compensated before delivery of HF nower

### PERSONALIZED PROCEDURES

- independent choice of coagulation currents and power levels by each of two operators

### - up to 10 procedures can be configured and re-called EXTENSION DRIVER AND INTERLOCK SIGNALS

- driven output connection to external Argon Plasma unit and Smoke Evacuator unit

### **AUTOMATIC SELF DIAGNOSIS**

- automatic diagnostic control of the complete functionality of electronic unit and connected accessories with coded report of

SUITABLE IN: OUTPATIENT SURGERY GENERAL SURGERY PAFDIATRIC SURGERY PLASTIC SURGERY THORAX SURGERY DERMATOLOGY GASTROENTEROLOGY GYNAECOLOGY NEUROSURGERY ORTHOPEDICS OTORHINOLARINGOLOGY PNEUMOLOGY UROLOGY VETERINARY

## GIMA 30634

TECHNICAL SPECIFICATIONS MB300/MB400

MB 400 MB 300 300 W - 300 Ω 400 W - 300 Ω 350 W - 300 Ω Maximum out power monopolar pure CUT Maximum out power monopolar cut-coag CUT80% 250 W - 300 Ω Maximum out power monopolar cut-coag CUT60% 200 W - 300 Ω 250 W - 300 Ω Maximum out power monopolar cut-coag CUT40% 150 W - 300 Ω 200 W - 500 Ω 200 W - 300 Ω 250 W - 500 Ω Maximum out power monopolar cut ENHANCED Maximum out power monopolar cut-coag BLEND 200 W - 300 Ω 250 W - 300 Ω Maximum out power monopolar coag SPEEDY 100 W - 500 O 120 W - 500 O 120 W - 200 Ω Maximum out power monopolar coag DEEP 100 W - 200 Ω Maximum out power monopolar coag SPRAY 70 W - 2000 Ω 100 W - 2000 Ω Maximum out power monopolar coag SPRAY ARGON 70 W - 2000 Ω 100 W - 2000 Ω Maximum out power bipolar CUT 95 W - 150 Ω Maximum out power bipolar cut-coag CUT80% 95 W - 150 O 95 W - 150 O Maximum out power bipolar cut-coag CUT60% 95 W - 150 Ω 95 W - 150 Ω Maximum out power bipolar cut-coag CUT40% 60 W - 150 Ω 60 W - 150 Ω 90 W - 150 O Maximum out power bipolar cut-coag BLEND 90 W - 150 O Maximum out power bipolar cut-coag BLEND Working frequency monopolar / bipolar 425 kHz / 525 kHz 425 kHz / 525 kHz Patient circuit Selectable input voltage 115-230 Vac . 115-230 Vac Mains frequency Electrical input voltage 50-60 Hz 50-60 Hz 1000 VA Size WxHxD mm 470×150×400 470×150×400

Controls: Patient/Plate circuit monitoring, Output power monitoring, Self check control

Safety: EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: LCE MDD 93/42/EC Class: II b


17.5 Kas

17.5 Kas

### STANDARD ACCESSORIES

- 1 Power supply cord 5 m
- 1 Two-button autoclavable handle (30536)
- Two-button cold sterilizable handle (30551)
- 1 Cable for flat plate (30559)
- 5 Rem disposable ground pads (30493)
- 2 HP double Water proof foot switch
- Short, general surgery blade electrode 7 cm
- 3 Long, general surgery blade electrode 16 cm Short, general surgery ball electrode Ø 4 mm, 6 cm
- 1 Flectrode brush
- User manual (IT, GB)





### LOOP ELECTRODES Ø 2.4 mm 📕 ELECTRODES AND HANDLE Ø 4 mm



- electrodes with 3 m silicone cable and blade electrode.
- 30482 NEEDLE ELECTRODE Ø 4 mm
- 30483 BLADE ELECTRODE Ø 4 mm
- 30484 BALL ELECTRODE Ø 4 mm
- S/S electrodes autoclavable 100 times. Sold in box of 5. Length 5.5 cm.

8 9 10 15 16 17

15 cm

35 36 37

AUTOCLAVABLE

20 TIMES

### AUTOCLAVABLE ELECTRODES Ø 2.4 mm

	<u> </u>	<del></del>				_ ~		<u> </u>	<u></u>					
GIMA code	Reference number	AUTOCLAVABLE ELECTRODES Ø 2.4 mm	Reference number	GIMA code	1	_ 2	. 3	4	5	6	7	8	9	٠
leng	th 5 cm	minimum order: 6 pcs.	length	10 cm		5 cm	long	g elect	rodes	- ret	eren	ce nur	nbei	ſ
30501	1	Electrode wire 0.2 - straight	21	30521										
30502	2	Electrode wire 0.2 - angled 45°	22	30522	1	1		1	1			1		1
30503	3	Electrode bend - Ø 4 - straight	23	30523			- 1	- 1		_/		- 1		-
30504	4	Electrode bend - Ø 8 - straight	24	30524			- 1	- 1			-	-	- (	
30505	5	Electrode hook - angled 45°	25	30525			- 1					-	ш	
30506	6	Electrode wire 1 mm angled 45°	26	30526			- 1	- 1				-	ш	
30507	7	Electrode straight slip-knot - straight	27	30527			- 1	- 1				-	ш	
30508	8	Electrode angled slip-knot - straight	28	30528			- 1					-	ш	
30509	9	Electrode ball point - Ø 3 mm - angled 45°	29	30529										
30510	10	Electrode ball point - Ø 3 mm - straight	30	30530	I		- 1							
30500	SET	Set of 10 electrodes	SET	30531						1	-10		- 1.	
lengt	h 7 cm	minimum order: 10 pcs.	length	15 cm		10 cr	n lor	ig elec	trode	s - re	ferer	nce nu	mbe	er
30511	15	Needle electrode	35	30532	21	22	23	24	25	26	27	28	29	
30512	16	Blade electrode	36	30533			A L LT	OCLA	V/AR	IF 1	оо т	INTES		
30513	17	Ball electrode	37	30534			AUI	OCLA	VAD		00 1	IIVILJ		

### SINGLE USE STERILE FLECTRODES Ø 2 4 mm

GIMA code	Reference number	SINGLE USE ELECTRODES Ø 2.4 mm	Reference number	GIMA code	30670 30671
leng	th 7 cm	Sterile electrode - box of 24	length	15 cm	
					30672
30670	13	Needle electrode - sterile electrode	33	30674	
30671	11	Blade electrode - sterile	31	30675	30678
30672	12	Ball Ø 4 mm electrode - sterile	32	30676	30674
1		Sterile electrode - box of 10	length	12 cm	30074
		Sterile electrode - box or ro	length	13 (111	
-	-	Loop electrode - 15 mm x8 mm	34	30678	

### NON-STICK SINGLE USE STERILE ELECTRODES Ø 2.4 mm

GIMA code	NON-STICK SINGLE USE ELECTRODE Ø 2.4 mm	Length	30420	
30420	Blade electrode - sterile	7 cm	30422	
30422	Blade electrode - sterile	10 cm		
30425	Needle electrode - sterile	10 cm	30425	
30429	Ball electrode - sterile	13 cm	30429	9

### BALLET STERILE DISPOSABLE ELECTROLYSIS NEEDLES



### 3-PIN MONOPOLAR HANDLES FOR ELECTRODES Ø 2.4 mm

VALLEYLAB CONNECTOR HANDLES with 2 "click" push-buttons GIMA autoclavable electrosurgery pencils with CUT-COAG switch have been studied and tested to offer maximum reliability and functionality to the operator. MB handles are provided with a 3 Pin plug Valleylab type fitting all Gima mono-bipolar Diatermo MB (120, 122, 132, 160, 200, 202, 240, 250, 380, 400) and most of bipolar electrosurgical units: Aspen Lab, ES Generator, EMC Statome, Danieli, Braun, Berchtold, Ohmeda, Ritter, Conmed, Eschmann, Bovie, Martin, Kontron, Bard, Birtcher 771, Cobi, Valleylab, Led, Erbe...

### **AUTÓCLAVABLE HANDLES**

• 30554 MB AUTOCLAVABLE HANDLE - 100 times Autoclavable handle with 2 large "click" push-buttons, provided with a 3 meter long silicone cable and a blade electrode.

It can be autoclaved up to 100 times (electrode 20 times). • 30545 MB AUTOCLAVABLE HANDLE - 100 times

Same as code 30554 but with a 5 m long silicone cable

• 30550 PRIMA MB AUTOCLAVABLE HANDLE - 60 times Autoclavable handle with 2 large "click" push-button, provided with a 3 meter long silicone cable and a blade electrode. It can be autoclaved up to 60 times.

• 30548 STAR AUTOCLAVABLE HANDLE - 30 times Same as code 30554 but autoclavable up to 30 times (electrode is autoclavable up to 20 times).

• 30539 ORION PLUS AUTOCLAVABLE HANDLE - 100 times Same as 30554, but with a screw clamp locking system ensuring a safe contact and adapting to slightly different electrode diameters. High insulation to prevent liquid damage.

• 30536 SURGEON AUTOCLAVABLE HANDLE - 100 times Autoclavable, waterproof handle with ergonomic grip. Coloured ring that indicates CUT and COAG push buttons. Provided with 3 m cable and blade electrode.

### SINGLE USE HANDLE

• 30551 KIRKY SINGLE-USE HANDLE - STERILE Single-use handle with "click" push-buttons for cut and coag. Includes blade electrode.

• 30553 GIMA SINGLE-USE HANDLE - STERILE Same as 30551 with 3 m cable.



### ■ 1-PIN MONOPOLAR HANDLES FOR ELECTRODES Ø 2.4 mm

1 pin plug HANDLES for diatermo 50, 80, 106, 108

These handles are provided with a 1 Pin socket (4 mm) fitting all Gima Diatermo and most of electrosurgical units in the market. These handles do not have push-buttons.

• 30515 SURGEON 1 PIN AUTOCLAVABLE HANDLE - 100 times Autoclavable, waterproof handle with ergonomic grip. Provided with 3 m cable and blade electrode

• 30519 AUTOCLAVABLE 50-80-106-108 HANDLE Autoclavable handle without buttons, provided with

a 3 meter long cable and a blade electrode. It can be autoclaved up to 50 times.

• 30518 KIRKY SINGLE-USE 50-80-106-108 HANDLE - STERILE Single-use handle without button with blade electrode with 4 mm PIN connection.



### HANDLES FOR ELECTROLYSIS NEEDLES Needle handles for all GIMA Diatermo and electro-depilators 30415


• 30552 HANDLE for electrolysis needles

• 30415 PROFESSIONAL HANDLE for electrolysis needles

see electrolysis needles at page 187



Disposable sterile radiopaque abrasive tip cleaner pad. Box of 100



30552


=== 1 pin (Ø 4mm)

plug for above handles

### BIPOLAR CABLES FOR MAJOR BRANDS

Recommended ETO sterilizion for max extended life. Suitable

Quality highly flexible silicone bipolar cables. Autoclavable at 134°C for minimum 20 times. 3 m long (10"). for most generators, with connector for European or US forceps.



SINGLE USE, METAL AND RUBBER PLATES



30563 (cable) 30575 (cable) 30561 30564 30566 (metal plate 30573 (rubber plate 20x15 cm) 30574 (rem rubber plate)

- 30492 DISPOSABLE GROUND PADS WITH SOLID GEL adult • 30490 DISPOSABLE GROUND PADS WITH SOLID GEL - pediatric
- 30493 REM DISPOSABLE GROUND PADS WITH SOLID GEL adult
- Adult ground plate with solid gel. Single use plate individually packed

• 30563 CABLE FOR PLATES - 5 m

Universal cable to connect plates (30490-30495) to diatermo. Safety lock with universal connection - bipolar Ø 6.3 mm plug.

• 30494 DISPOSABLE NON WOVEN GROUND PADS - adult/ped

• 30495 REM DISPOSABLE NON WOVEN GROUND PADS -

• 30573 RUBBER PLATE 20x15 cm - without cable

• 30574 REM RUBBER PLATE 20x15 cm - without cable

• 30575 CABLE FOR RUBBER PLATES

• 30566 METAL PLATE - without cable

• 30563 CABLE FOR PLATES - 5 m

• 30559 CABLE FOR PLATES - 2.5 m

• 30564 SURGEON NEUTRAL PLATE 16x12 cm - with cable

• 30561 ROD NEUTRAL PLATE with cable

### 3M ELECTROSURGICAL GROUNDING PADS WITH SAFETY

- 30496 3M 9160 SPLIT GROUNDING PAD box of 100
- 30497 3M 9160F SPLIT GROUNDING PAD box of 200 (40 pouches of 5 pieces)
- 30498 3M 9165 SPLIT GROUNDING PAD precorded box of 40 The 3M 9160, and 9165 Universal Grounding Pads all have a conductor area of 15 square inches and come with the patented 3M Green Safety Ring technology which allows them to perform the same as grounding pads that are up to 33% larger in conductor area. Green Ring allows adult and pediatric use.

In addition, they have fluid resistant, non-woven backing which allows heat to pass through up to 25% faster than foam, and they have no minimum age or weight limit



30498



 $C \in$ 

### UNIVERSAL HIGH QUALITY INSULATED BIPOLAR FORCEPS



GIMA	Model	Connector	Leng	ıth	Tip style	Application	Tip size	
code		5	cm	inches			•	Straight tip
30645	BINNER	EU	22 cm	81/2"	ANGLED	ENT	-	
30646	BINNER	EU	18 cm	7"	STRAIGHT	ENT	-	
30647	BINNER	EU	18 cm	7"	ANGLED	ENT	-	
30648	BINNER	EU	19 cm	7 "	ANGLED 45°	ENT	-	
30650	STRAIGHT	EU	18 cm	7"	STRAIGHT	GENERAL	1 mm round points	Straight forceps
30656	STRAIGHT with irrigation	EU	18 cm	7"	STRAIGHT	GENERAL	1 mm round points	
30651	STRAIGHT	EU	20 cm	7¾"	STRAIGHT	GENERAL	1 mm round points	
30658	STRAIGHT	EU	20 cm	7¾"	STRAIGHT	GENERAL	2 mm round points	
30652	STRAIGHT	EU	18 cm	7"	ANGLED	GENERAL	1 mm round points	30656
30653	STRAIGHT	EU	20 cm	7¾"	ANGLED	GENERAL	1 mm round points	
30657	BAYONET	EU	16.5 cm	61/2"	STRAIGHT	GENERAL	1 mm round points	
30654	BAYONET	EU	18 cm	7"	STRAIGHT	GENERAL	1 mm round points	Irrigation
30655	BAYONET	EU	20 cm	7¾"	STRAIGHT	GENERAL	1 mm round points	
30659	BAYONET	EU	22 cm	8¾"	STRAIGHT	GENERAL	1 mm round points	UNIVERSAL
30663	BAYONET	EU	24 cm	91/2"	STRAIGHT	GENERAL	1 mm round points	EUROPEAN
30660	STRAIGHT	EU	18 cm	7"	ANGLED	GENERAL	0.3 mm points	CONNECTION
30661	STRAIGHT	EU	18 cm	7"	STRAIGHT	GENERAL	0.3 mm points	Our forceps are provided with a standard
30662	STRAIGHT	EU	20 cm	7¾"	STRAIGHT	GENERAL	0.3 mm points	European connection
30664	ADSON	EU	12.1 cm		STRAIGHT	GENERAL	1 mm round points	enabling their use with GIMA
30665	JEWELER 5	EU	11.5 cm		STRAIGHT	OPHTHALMIC/MICRO	0.25 mm points	Diatermo and electrosurgery
30666	JEWELER 5	EU	11.5 cm		ANGLED	OPHTHALMIC/MICRO	0.25 mm points	units from the main European
30667	STRAIGHT	EU	15 cm	6"	STRAIGHT	OPHTHALMIC/MICRO	0.5 mm points	manufacturers.
30668	STRAIGHT	EU	15 cm	6"	ANGLED	OPHTHALMIC/MICRO	0.5 mm points	
30669	Mc PHERSON	EU	10.2 cm	4"	STRAIGHT	OPHTHALMIC/MICRO	0.5 mm points	

### US CONNECTOR BIPOLAR FORCEPS

			_ =				
30621	SEMKIN		30	622	CUSHING	3062	23 JANSEN BAYONET
GIMA	Model	Connector	Len	gth	Application	Straight tip	<b>( €</b> 0120
code		ē	cm	inches		Size	
30620	ADSON	US	12.1 cm	4¾"	GENERAL/PLASTIC	1 mm round points	30620
30621	SEMKIN	US	14 cm	51/2"	GENERAL/PLASTIC	0.5 mm points	ADSON
30622	CUSHING	US	15.9 cm	61/4"	GENERAL/PLASTIC	1 mm round points	UNIVERSAL US
30623	JANSEN BAYONET	US	17.8 cm	7"	GENERAL/PLASTIC	1 mm round points	CONNECTOR

### EUROPEAN NON-STICK BIPOLAR FORCEPS

### NON-STICK BIPOLAR FORCEPS

Thanks to new Ag-Tech non-stick technology, the forceps stay clean, virtually eliminating the need for cleaning during

GIMA	Model	Connecto	Len	gth	Tip style	Tip size
code		5	cm	inches		
30460	STRAIGHT	EU	15	6"	STRAIGHT	1 mm
30461	STRAIGHT	EU	18	7"	STRAIGHT	1 mm
30462	STRAIGHT	EU	20	73/4"	STRAIGHT	1 mm
30464	STRAIGHT	EU	18	7"	ANGLED	1 mm
30465	STRAIGHT	EU	20	73/4"	ANGLED	1 mm
30468	BAYONET	EU	18	7"	STRAIGHT	1 mm
30469	BAYONET	EU	20	73/4"	STRAIGHT	1 mm
30472	JEWELER	EU	11.5	4.5"	STRAIGHT	0.7 mm
30473	JEWELER	EU	11.5	4.5"	ANGLED	0.7 mm
30474	ADSON	EU	12.1	43/4"	STRAIGHT	1 mm

coagulation. A tip material with excellent thermal properties prevents the sticking of tissues. The non-stick effect is permanent and will not reduce with the use of forceps.




### FOOTSWITCHES AND BOARDS

FOOTSWITCHES FOR 50, 80, 106, MB 120, 122, 132, 160, 200, 202

30577 30578	Waterproof MB footswitch - 2m cable Waterproof MB footswitch - 3m cable	
	ANTIEXPLOSION FOOTSWITCH FOR MB 120, 122, 132, 160, 200, 202	305//
30602	Double antiexplosion, water proof MB footswitch	
	ANTIEXPLOSION FOOTSWITCHES FOR MB 240, 250, 300D, 380, 400, 400D	
30603 30604	Double antiexplosion, water proof footswitch - MB240-380 Double antiexplosion, water proof footswitch - MB250-400-300D-400D	
	MAIN BOARD	
30557 30558	Main board - specify model and serial number of diatermo with order Output board for MB 240, 250, 380, 400 - specify as above	300023

It allows selection from pedal of CUT and COAG functions Antiexplosion and waterproof.

### MONOPOLAR FORCEPS, SCISSORS AND CABLES



### ELECTROSURGERY SMOKE EVACUATOR

### • 30450 SMOKE EVACUATOR

An aspiration and filtering system for the smokes produced during the surgical procedures.

The smokes, generated during the surgical procedures, have a bad, strong and persistent smell. These smokes consist of water vapour, organic gas, visible or invisible solid particles and viral parts. So a good aspiration and filtration eliminates bad smells, reduce the bacteriological and/or viral risks, and improves vision of the zone of the operation area during the laparoscopic procedures.

Activation of the aspiration can be:

- Automatic, through the remote electronic system of automatic survey of the activation of the high frequency electrosurgical unit
- Manual
- Through a foot switch (optional)

The aspiration flow can be adjusted to suit the specific needs. For laparoscopic procedures there is a specific function L,

### TECHNICAL SPECIFICATIONS 230 V (115 V on request) Mains voltage Mains frequency 50/60 Hz Electrical input power 800 VA Max vacuum flow rate 1000 LPM (35 CFM) Max static suction 250 mbar (83 in H<sub>2</sub>O) ULPA with active carbons Filter type Filter efficency 99,999% Particles diameter 0.12 micror 370x144x319 mm

### 4 kg STANDARD ACCESSORIES

ULPA filter (5 hours) blue
Aspiration kit (filter + pipe Ø 22 mm, length 2.4 m)
4 handle aspiration kit (adapter 10 mm/22 mm, pipe Ø 10 mm, length 1.8 m,
clip to fix the pipe to the handle, adapter to the handle)
Power cable

quickly selectable. Smoke evacuator has an electronic control of the aspiration with the indication of the wearing status of the filters. There are two different kinds of quickly replaceable ULPA type filters, with active carbons: the BLUE filter is the first filter and it is included with the unit for an initial time of use (5 hours), the RED filter is an optional spare part, developed for a long time use (20 hours).

They have connector of 7/8".

- 30452 ULPA FILTER (20 hours) RED spare
- 30453 ASPIRATION KIT box of 6
- 30454 HANDLE ASPIRATION KIT sterile box of 12
- 30577 WATERPROOF MB FOOTSWITCH 2 m





Weight

### CHANGE-A-TIP™ CAUTERIES WITH HIGH TEMPERATURES

### **BOVIE CAUTERIES**

- interchangeable sterile tips

- reusabl		590	Do	Replaced to To A Replace this field	ary of '
- no ster	ilization necessary (Fine INTERCHANGEABLE TIP CAUTERIES	tip, not sterile, included)  Recommended	-		
code	MINIMUM ORDER: 10 TIPS	for:	30595		
30590	Cautery handle "AA" (tip included)	All tips	-		
30593	High temp loop tip - sterile	DER/ENT	20504		
30594	High temp 2" flex loop tip - sterile	GYN/ENT	30594		
30595	High temp 5" loop tip - long size - sterile	GYNAECOLOGY			
30596	High temp fine tip - sterile	DER/CARDIO	-		
30597	High temp elongated tip - sterile	VASECTOMY	30596	30593	305


### ■ REUSABLE HIGH TEMPERATURE CAUTERY WITH REPLACEABLE TIP

### CAUTERIES - 1,200°C (2,200°F) - made in Italy

- interchangeable tips with nickel-chrome wire
- replaceable batteries
- reusable handles

Wide application in gynaecology, orthopedy, ear/nose/throat, dermatology, plastic and

reconstruction surgery.				
GIMA	INTERCHANGEABLE TIP CAUTERIES			
code	MINIMUM ORDER: 10 TIPS			
30598 30599	Cautery handle "AA" (tip not included) High temp long fine tip - sterile - box of 1			
30600 30601	High temp large tip - sterile - box of 10 High temp fine tip - sterile - box of 10			



### HIGH TEMPERATURE ELECTROCAUTERIES

• 30580 ELECTROCAUTERY - 1,200 °C - fine tip - made in Italy Electrocautery is a sterile bipolar battery operated disposable device for the cauterization of small vessels; the temperature of the tip

is 1,200°C. With a fine tip required in most of the surgeries • 30582 GYNAECOLOGY CAUTERY - 1,200°C - fine tip

Same as 30580 but with the tip fixed on a 12 cm long shaft.

• 30581 ELECTROCAUTERY - 600 °C - fine tip Same as 30580 but with lower temperature = 600°C. Expecially designed for ophthalmology.

• 30583 EMERGENCY ELECTROCAUTERY - 800°C - Thick tip Same as 30580 but with "thick tip" for the perforation of nails in case of haematoma



### CARTS FOR ELECTROSURGICAL UNITS

Trolley designed to hold and carry electrosurgical units (including Argon units). Ergonomics has been particularly considered for the design, for example the height of 900mm with inclined top shelf allows easy reading of the unit's display.

The trolley is provided with a second shelf with antiskid raised edges, two drawers placed at the base and a rear space with securing straps to hold two Argon cylinders. The upright stands holding the shelves are designed to take possible optional accessories. All parts of the trolley are made of epoxy-painted, tempered steel and aluminum.

Available version with 4 socket group, fuses box, independent grounding plug, power cable 3m.

### TECHNICAL SPECIFICATIONS

- Total load 200 kg - Inclined shelf 50 kg Load capacity 42x45 cm (27864/6) 50x50 cm (27865/7) Inclined shelf: Drawers and shelf: 42x31 cm (27864/6) 50x36 cm (27865/7)

CARTS FOR ELECTROSURGICAL UNITS

27864 DIATERMO CART - medium

27865 DIATERMO CART - large

27866 DIATERMO CART with power - medium

27867 DIATERMO CART with power - large

## All professional carts are supplied with cable pipe inside lateral columns TOP OUALITY with 27866/7

### **CAUTERY & ELECTROSURGERY**

### HISTOFREEZER® CRYOSURGICAL SYSTEM

% of resolution\*

94%

86%

100%

100% - facial

99% - non facial

89%

95%

100%

93%

91% - facial

CHARGE

custom applicator

press valve until

droplets start to

• 30591 HISTOFREEZER® - kit with applicator 2 mm Two 80 ml aerosol bottles and 60 applicators 2 mm.

• 30592 HISTOFREEZER® - kit with applicator 5 mm

Two 80 ml aerosol bottles and 52 applicators 5 mm. • 30589 HISTOFREEZER® - large kit mixed applicators

Two 80 ml aerosol bottles, 24 applicators 2 mm, 36 applicators 5 mm.

• 30585 HISTOFREEZER® - mini kit mixed applicators One 80 ml aerosol bottle, 16 applicators 2 mm, 16 applicators 5 mm.

The Histofreezer® portable cryosurgical system is a low cost, highly effective cryosurgical agent that provides safe and effective treatment for warts and other common benign skin

This therapeutic treatment makes use of local freezing for the controlled destruction or removal of living tissue. Suitable for adults and children

Effective use on 9 benign lesion types

- Verruca Vulgaris (Common Warts) - Verruca Plantaris (Plantar Warts)
- Molluscum Contagiosum - Lentigo (Age Spots)
- Condyloma(Genital Warts) - Seborrheic Keratosis
- Acrochordon (Skin Tags)
- Verruca Plana (Flat Warts)
- Actinic keratosis (Facial and Non-Facial)

87% - non facial \*Summary of resolution rates by type of lesion from a number of clinical trials obtained with histofreezer + post-treatment of 27% salicylic acid / 17% lactic acid

Supplied with box and manual in: GB, FR, IT, DE, ES, NL, PL From web you can download: GR. PT. TH. Arab.

applicator for small

5 mm disposable

applicator for large

lesions

Saturated 2 mm applicators will stay









3059



APPLY

seconds.

a frozen applicator

to lesion for 15-40

INVFRT

seconds for

canister for 15

optimal freezing

### BIOLOGICAL MICROSCOPES - MAGNIFICATION 40X-1600X

- 31002 LED BIOLOGICAL MICROSCOPE 40X to 1600X High level microscope with high resolution and transmission Main features:

- infinite optical system
   wide field eyepiece WF 10X/20
   infinite semi-plan achromatic objectives 4X, 10X, 40X, 100X
- Abbe condenser
- backward quadruple nosepiece
- double layers mechanical stage (size: 150x139 mm, move range 75x52 mm)
- adjustable brightness
- power supply: switchable 110-220 V, 50 Hz



- 30° compensation free binocular head - eyepiece 10X (Field 18 mm)
- eyepiece ToX (reid 18 min) achromatic objectives 4X, 10X, 40X(S), 100X (S, oil) semi plan achromatic objective 40X, 100X, 400X, 1000X, interpupillary distance adjustment: from 55 to 75 mm
- mechanical stage, double layers (size: 125x135 mm, move range: 75x35 mm)
- Abbe condenser with iris diaphragm and filter
- halogen lamp 6 V, 20 W brightness adjustment
- power supply: switchable 110-220 V, 50 Hz
- 31005 SPARE BULB for 31000



Fine focusing knob

30580

LOUPES, VISION & ENDOSCOPY

### GERMAN FLEXIBLE NOSEPHARYNGOSCOPE

### • 71602 FLEXIBLE NOSEPHARYNGOSCOPE with cable

The high precision multi-lens optics creates an optimal image The thin insertion tubes are exceptionally maneuverable and have a special wide angle lens whereby a precise tip control and a remarkable depth of focus are reached. Exacting workmanship and high quality materials create

absolutely homogeneous illumination.

The handpiece is ergonomically formed and the insertion tube is especially comfortable for the patient.

This naso-pharyngoscope, with its proven design, is guaranteed to bring years of trouble-free service.


- wide angle, multi-lens objectives for excellent image quality
- excellent ergonomics allows one hand operation



### **TECHNICAL SPECIFICATIONS 71602**

Resolution: 7,000 pixels Working Ø: 3.2 mm Length of tip deflection: 20 mm Direction of view: 0° Weight: 260 a

Working length: 300 mm Tip deflection: up 140°, down 140° Depth of focus: 6 -1.000 mm Field of view: 70° Made in Germany





71610 ENDOSCOPY

Disposable bite blocks

Supplied in lightweight aluminium rigid case with fibre optic cable, leakage tester and user manual (GB. IT)



### OTOSCOPES



- 72004 OTOSCOPE Ø 4x45 mm 0° non autoclavable
- 72007 OTOSCOPE Ø 2.7x107.5 mm 0° non autoclavable
- 72008 OTOSCOPE Ø 2.7x107.5 mm 30° non autoclavable

.ARYNGOSCOPE

### SINUSCOPES

MOUTHPIECE - bag of 20 pcs



- 72010 SINUSCOPE Ø 4x175 mm 0° non autoclavable
- 72011 SINUSCOPE Ø 4x175 mm 30° non autoclavable
- 72012 SINUSCOPE Ø 4x175 mm 70° non autoclavable
- 72013 SINUSCOPE Ø 4x175 mm 45° non autoclavable

### LIGHT SOURCE HANDLE



- 30795 FLYER HALOGEN HANDLE 2.5 V light source for endoscopes
- 31478 BULB for 30795
- 30794 FLYER LED HANDLE 2.5 V light source Powerful handheld light source for endoscopes.
- 72021 LARYNGOSCOPE Ø 8x170 mm 70° non autoclavable 60,000 lux. Both flyer handles need 2xAAA batteries.

### Wi-Fi/USB CAMERA FOR ENDOSCOPES AND MICROSCOPES

Lens standard

Li-lon battery

Power source:

Software features:

OS support:

ACMI / WOLF / STORZ /

OLYMPUS fitting

- 32185 MICFIEYE Wi-Fi/USB CAMERA (C-mount)
- 32186 C-MOUNT F18 ADAPTER FOR ENDOSCOPES
- 32187 MICROSCOPE ADAPTER Ø 23 mm

MICFIEYE is a Wi-Fi camera with C-mount and allows to digitalize the image on tablets, smartphones and PC using dedicated Apps and Softwares. MICFIEYE needs an adapter



Fach camera is supplied with LISR cable (1.2 m), LISR AC adapter, user manual (GR, IT FR FS DF) software can be downloaded free of charge from web

to be compatible with all optical devices such as microscopes, endoscopes, boroscopes, fiberscopes, C-mount lenses etc.

### **TECHNICAL SPECIFICATIONS**

Camera Type: Colour CMOS camera Sensor 1/4 Imax CMOS Resolution 1.3 MP Image pixel

320x240, 640x480, 1280x1024 C-CS mount CCTV lens

Automatic optical features: Gamma correction, exposure, white balance, black reference, flicker avoidance, defect identificati colour saturation

yes for Wi-Fi and USB mode **Rutton snanshot** Ø 36x75 mm Dimension: Wi-Fi transmission distance

1.3 MP, 320x240, 640x480, 1280x1024 Video resolution Frequency range

2,400-24,835 GHz Continuous working time - approx 2.5 hours 5 V / 1A or USB (use only USB wall adaptors certified according the CE and/or FCC regulations) iOS / Android / Windows / Mac

USB and Wi-Fi MIC-fi: snapshot, video recording, calibration and measurement. Take time lapsed picture, (only USB Micfieye)

### 150 W HALOGEN LIGHT SOURCE F. O. HEAD LIGHTS



### • 30801 GIMA HALOGEN LIGHT SOURCE 150 Watt

Compact, lightweight, powerful light source for endoscopic use. A low noise fan positioned behind the halogen bulb provides the necessary cooling inside the metallic structure of the light source. A variable-intensity regulator enables selection 50 to 150 W. User manual in GB, ES, FR, IT, GR, PT.

code	DIFFERENT CABLES
30810	STORZ cable connector
30811	WOLF cable connector
30812	OLYMPUS cable connector
30815	PENTAX cable connector
30816	FUJINON cable connector
30808	Spare lamp 150W

• 27544 LED LIGHT SOURCE

to rigid endoscopes

(Storz connection).

to endoscopes without need of

F.O. cable. Handle connect directly

LCD display.

12.8x6.4 cm

### CONNECTORS FOR GIMA TECHNICAL SPECIFICATIONS Input for GIMA, SCHOLLY and LUT cables

Dimension: 21x20x h 11 cm Max power absoption: 170 Watt Two protection fuses: 1.6 A.T. Power supply: 230V-50 Hz Norms: IEC 601-1 - 93/42/EEC

(Class: I - Type: BF) Made in Italy: GIMA S.p.a.





- 30850 WIDA FIBRE OPTIC HEAD LIGHT
- 30854 WIDA PLUS FIBRE OPTIC HEAD LIGHT

### fibre optic cable complete with head light system


WIDA illumination systems are available in two versions: one with simple headband and standard illumination head, the other with professional headband, easily adjustable, and thin head. Both include F.O. cable with adaptor (30830) for connection to GIMA light source (30801).

Here below are available connectors to other light sources. Light beam can be focused through

a focusing ring. • 30852 FOCUS DEVICE for 30850

(since lot 14 - may 2012)

It reduces light in a very luminous spot Ø 10 mm.



An exceptionally bright headlight with an llumination head for naxial shadow-free illumination of the viewina area



Headband is padded and fully adjustable in circumference and height.

### SURGICAL FIBRE OPTIC LIGHT CABLES AND ADAPTORS







- . 30833 OLYMPUS light source ad-30834 ACMI light source adaptor
   30835 HEINE light source adaptor
- 30836 FUJINON light source adaptor
   30837 PENTAX light source adaptor

**2** ENDOSCOPE ADAPTORS - on the cables to connect endoscopes to GIMA F.O. cables <del>(100)</del>


30840 ENDO STORZ adaptor 30841 FNDO WOLF adapto

• 30842 ENDO ACM.

- 30817 FIBRE OPTIC CABLE 3.5 x 1.800 mm • 30818 FIBRE OPTIC CABLE 4.8 x 1,800 mm
- 30822 FIBRE OPTIC CABLE 3.5 x 2.300 mm
- 30823 FIBRE OPTIC CABLE 4.8 x 2.300 mm
- 30826 FIBRE OPTIC CABLE 4.8 x 3,000 mm

High transmission surgical light cables, armoured but highly flexible with unique features:

- no burn outs
- strain relieved and protected by silicone hose
- steam autoclavable with warranty (12 months)
- light source end temperature resistant up to 300°C
- kink resistant
- no electrical interferences with endoscopic surgery units
- surgical stainless steel end fittings resist wear and corrosion
- stainless steel adaptors enables our cables to be used with other manufacturers
- halogen light sources/instruments • 29975 FIBRE OPTIC CLAMP
- SENDOSCOPE ADAPTORS on the endoscope to connect endoscopes to GIMA F.O. cables
- 30844 STORZ/LUT ENDOSCOPE ADAPTORS







Quality head mirrors Ø 55 or 100 mm to perfectly illuminate the examination area in every situation. Long life 6 V lamp provides bright and natural light, quality silver coated mirror allows optimum light reflection.

Mirror and light beam can be eas	sily and prec	isely adjuste	ed.
STANDARD ACCESSORIES	LUX AC/DC TRANSFORMER	LUX BATTE	RY*
	31110-31111	31107-31109	31112
Mirror with head band	•	•	•
Long life bulb	•	•	•
Head band mounted battery case**			
for 2 x 3V CR-123A		•	
Plug in transformer* 100/240 V -			
50/60 Hz with cable	•		
Pocket battery case			•
Sturdy plastic case			•
Cordura bag	•	•	
Extension cable 80 cm and on/off switch			
30 cm cable			
*Supplied with interchangeable LIK_LIS_ELL plu	ıras "Ratten	not included	

31108 LUX-55 battery\*\* head mirror - Ø 55 mm - 6 V **31112** LUX-55 battery\*\*\* head mirror - Ø 55 mm - 6 V 31109 LUX-100 battery\*\* head mirror - Ø 100 mm - 6 V 31107 LUX-100 battery\*\* LED head mirror - Ø 100 mm - 6 V 31110 LUX-55 AC/DC transformer head mirror - Ø 55 mm - 6 V 31111 LUX-100 AC/DC transformer head mirror - Ø 100 mm - 6 V 31114 Mirror for LUX-55 - spare 31115 Mirror for LUX-100 - spare 31116 Bulb for LUX mirrors - spare

LUX ENT MIRRORS

31119 Carrying bag for LUX mirrors - black 31117 Battery case for LUX mirror 31112/3 - spare 31124 Connecting cable 30 cm for 31107-9 - spare 31118 Plug in transformer\* 100-220 V - 50/60 Hz with cable spare for 31100-1 - optional for 31107-9
Supplied with interchangeable UK, US, EU plugs "Battery mounted on head mirror band"
"Pocket battery case connected to head mirror"

### HEAD LOUPE AND MAGNIFYING GLASSES



• 31170 HEAD LOUPE two magnifying systems (2.2X and 3.3X)

The system is mounted on an adjustable webbing head band and provided with two separate lenses. The first lens provides a 2.2X magnification, moving down the second lens, we reach a total 3.3X magnification. The superior quality of this lens permits high precision examinations. It can be used in combination with

any kind of glasses. Working distance: 17 cm with 2.2X lens, 9 cm with 3.3 lens. Made in Japan.

### • 30861 DANAE MAGNIFYING • 30848 SMART MAGNIFYING GLASSES Adjustable GLASSES Light, only 83 c

Compatible with TETI protective shield (see page 16, 198,

- optical system with 3 magnifying glasses (2X, 2.5X, 3X)

- can fit over your glasses - adjustable to any face shape

Spectacle frame with magnifying glasses useful to physician whenever it is necessary to have a magnified view of the visual field and be able to use both hands. Lightweight, it folds up, and can be worn over spectacles. 2.5X zoom lens which can be tilted to achieve optimum

30848



### • 31142 ZIEGLER MIRROR -Ø 90 mm

Concave back-silvered mirror, 90 mm diameter with 13 mm diameter hole, on adjustable band. Special mount permits replacement of glass mirror in event of breakage. Made in Germany.

### 1 W LED HEADLIGHTS

### • 30858 LED HEADLIGHT

Run time: High mode: 3 hours - Low mode: 22 hours Luminous intensity: 120 lumens (high) or 30 lumens (low) 30 feet drop test, super bright CREE cool white LED MCU control push switch (High/Low/Off) 60° pivoting head.

test. IPX4 water resistant 10,000 switch cycle life Lighting leakage design when forget to turn off switch. 3AAA batteries included.

• 32200 "AAA" ALKALINE BATTERIES - blister of 4 pcs - spare

Passed extreme temperature shock Compact and lightweight headlight only 65 g



Adjustable range Fluctuation distance: 12.5 mm

Angle range: vertical ± 25° adjustable Weight of headlight (excluding head band): 69 g

7 hours continuous

Illumination source: extremely bright light, 5 W LED, life 20,000 hours Battery: 7.2 V/4,600mAH lithium battery

Battery run-time: not less than 7 hours continuous run-time on a fully charged battery (charging time: 5 h) Voltage: 100-240 VAC, 50-60 Hz

Maximum input power: 15 W Power adapter output: DC 12 ±0.5 V, 1.5 A

Electrical safety standard: IEC60601.1, class II type BF equipment

### GIMA LED HEADLIGHT

- 30940 GIMA LED LIGHT 5W black
- 30941 BATTERY PACK for 30940 and 30890° (need adaptor) spare \*Old Gima Led light - light blue
- 30942 ADAPTOR BATTERY PACK\*\*

"Only for use of battery pack (30941) with old Gima head light (30890) Led lamp without the heat of traditional halogen

headlight. With a colour temperature of 5,500 °Kelvin, it provides bright, white, shadow-free light allowing the doctor to see tissue characteristics without distortion

Flexibility of operation using the rechargeable lithium battery, instead of direct power source. Comfortable lightweight headlights suitable for all kinds of surgery, ENT or dental applications. The headlight can be used when it is charging, it also has low-battery indicator

light. Adapts to GIMA binocular loupes (codes 30892-8, 30910-5). Smart design, convenient for mobile diagnosis. Supplied in aluminium box with rechargeable 7.2 V / 4,600 mAH lithium battery and recharger. Manual: GB, FR, IT, ÉS, DE, PT, GR, Arabic.



### **GIMA BINOCULAR LOUPES**

### BINOCULAR LOUPES:

Light weight, ergonomically superior Galilean-style flip-up loupes. Can be used independently or mounted on 30890, 30940. Multi-coated and high grade glass lenses provide clean and sharp image. Evepiece with wide field of view.

Deep focus to see object stereoscopically.

Loupes angles can be easily adjusted between 0° and 40° to minimize fatique even after prolongued use. 6 mm up and down displacement.

Adjustable pupil distance to fit different face types.



	-	Charles III		7
GIMA code	BINOCULAR LOUPES	Magnification	Working distance	Field of view Ø
30892	Binocular Loupe	2.5X	340 mm	80 mm
30894	Binocular Loupe	2.5X	420 mm	100 mm
30897	Binocular Loupe	3.5X	340 mm	60 mm
30898	Binocular Loupe	3.5X	420 mm	72 mm

### STYLE BINOCULAR LOUPES:

Line of binocular loupes with same features of traditional line



GIMA code	STYLE BINOCULAR LOUPES	Magnification	Working distance	Field of view Ø
30910	Style binocular Loupe	2.5X	340 mm	80 mm
30911	Style binocular Loupe	2.5X	420 mm	100 mm
30914	Style binocular Loupe	3.5X	340 mm	60 mm
30915	Style binocular Loupe	3.5X	420 mm	72 mm

### RIESTER RI-FOCUS LED HEADLIGHT

• 30881 RI-FOCUS LED HEADLIGHT - with rechargeable batteries High performance LED headlight with battery compartment for fast and easy change of battery. Flexible hinge for a comfortable one-hand use of the LED illumination body.

- more efficient diagnosis due to white and high performance LED with up to 100,000 LUX and 50,000 hours lifetime

- wireless headband with built-in battery compartment - particularly comfortable with balanced headband and one-hand operation
- focusable LED lamp at a distance of 40 cm approx Ø 40 mm to 200 mm infinitely focusable
- white LED with 6,000 °Kelvin, 140 lumen - significantly less heating and energy loss
- rechargeable battery operation: approx 90 min with fully charged batteries

Rechargeable AAA batteries and plug in 230V charger included



Distance

Lux max

Circle of light min Ø:

Weight 210 g

Removable and

inner padding

washable

400 mm 200 r 10 000 23 000 Circle of light max Ø: 200 mm

Made in Germani 120 mm

### HEINE LED HEAD LIGHT 50,000 LUX SIT) HQ 30884 30884 HEINE ML4 LEDH HEAD LIGHT - J.008.31.413 - LED in HQ; defining optimal light intensity (50,000 lux at 250 mm), brightness and homogeneity from edge to edge, and colour rendering (4,500 k, CRI >90, R9 > 75). This ensures true colour tissue for the most accurate diagnosis. - Coaxial illumination: ensures a completely shadow-free image and allows for excellent illumination of difficult to see areas. Lithium Battery: for up to 8.5 hours of continuous working. - LED Thermal Management: guarantees consistent quality and performance throughout the LED's lifetime (50,000 hours).

Adjustable illumination spot size: 30 to 80 mm spot size range

Comfortable and secure fit: multiple adjustment points and soft

(at 420 mm working distance) to fit any examination situation.

padding for comfort and stability even during long procedures.

- Illumination Intensity Control: for precise brightness setting Rechargeable battery pack and direct mains transformer included.

• 30883 HEINE ML4 LED<sup>10</sup> HEAD LIGHT with DV1 DIGITAL VIDEOCAMERA and mPack® UNPLUGGED - 1-008.31.470

Same as above with high resolution digital videocamera 1.3 megapixel

• 30886 HEINE BINOCULAR LOUPE 2.5X-340 mm - J.000.31.370

• 30887 HEINE BINOCULAR LOUPE 2.5X-420 mm - J.000.31.371

30888 P2 POLARIZATION FILTER FOR ML4 AND 2.5X LOUPES - J.000.31.326

TECHNICAL SPECIFICATIONS

direct mains transformer 50,000 lux at a working distance of 250 mm

HEINE BINOCULAR LOUPES





Set content: optics, S-frame with i-View loupe mount, detachable protective lenses, 2 sterilizable swivel levers, retaining cord cleaning fluid carrying case

### HEINE® S-FRAME® WITH BINOCULAR LOUPES

- Achromatic optics: crisp, bright image with colour-correction. - Multi-coated, scratch-resistant silica glass lenses - produce crisp, clear images. High magnification with a large field of view and excellent depth of field.
- Water resistant
- Flexibility for precise adjustment: indipendently adjustable Pupillary Distance controls ensure precise alignment of the optics, for a stereoscopy view.

- i-View loupe mount; provides any angle of view and the possibility flips up and down the optics to exclude or reinclude the magnification during any procedure.

Different magnification and working distance.

GIMA code	BINOCULAR LOUPES	Magnification	Working distance	HEINE code
30930	Heine binocular loupes	2.5X	340 mm	C-000.32.355
30931	Heine binocular loupes	2.5X	420 mm	C-000.32.356
30932	Heine binocular loupes	4X	340 mm	C-000.32.431

- 30888 P2 POLARIZATION FILTER FOR ML4 AND 2.5X LOUPES J.000.31.326
- 30935 HEINE LED LOUPELIGHT with mPack® LL and plug-in transformer - C-008.32.264

HEINE LED in HQ (50,000 lux at 250 mm, 4,500 k, CRI>90, R9 > 75) provides the best coaxial, intense, accurate and homogeneous LED illumination. 17 hours continuous ON time at full power with mPack LL. LED

Thermal Management ensures consistent quality and performance of the illumination S-frame binocular loupes throughout the LED's lifetime rating of up to 50,000 hours.

30935

### **IUKO VISION MODULAR SYSTEM**

Iride is supplied with a compact,

light, rechargeable power bank

(hattery) a 15 cm cable for use

mPack® Rechargeable Battery Pack with Li-ion battery and

### GALILEAN TELESCOPE

Spot adjustment: 30 mm to 80 mm illuminated field diameter (at 420 mm)
Colour temperature: 4,500°K Made in Germany

- 30864 CALLIOPE Galilean telescope 3X dental (working
- distance 35 cm)
   30865 CALLIOPE Galilean telescope 3X surgical (working distance 45 cm)
- 30866 CALLIOPE Personalized Galilean telescope: magnification from 2X to 3X, working



- magnifying optical system with Galilean telescopes
- waternroof telescone
- compatible with TFTI

Power supply:

LED operating life: 50,000 hours

### ADJUSTABLE PROJECTOR

- 30867 IRIDE LED light projector
   30876 BATTERY PACK spare
- on head band and one 1 m cable for use from pocket **IRIDE 30867**  adjustable LED light projector adjustable EED light projector
   adjustable brightness intensity (10,000 and 40,000 lux at 25 cm, autonomy 6 and 4 hours) • 6,500°K temperature
- autonomy 4 hours at maximum nowe
- battery pack placeable on the head band
   compatible with TETI, see page 16

### TELESCOPE + PROJECTOR

- 30870 NIKE Galilean telescope 3X (35 cm) + projector
- 30871 NIKE Galilean telescope 3X (45 cm) + projector • 30876 BATTERY PACK - spare



### SHIELD + TELESCOPE and/or PROJECTOR

30860 TETI - protective shield (2 shields included)



### PENTALED 63N THEATRE LIGHTS

63N 160,000 LUX Pentaled 63N is a high-tech product designed to guarantee excellent performance levels. PENTALED 63N has 72 elliptical reflectors split into 8 modules, each containing 9 LEDs. The modules are mechanically focused by rotating the sterilizable handle. The multiplicity of the luminous sources and the elliptical geometry of the parabolas studied to reflect in the depth the light beams generated by the LEDs, grant scialytic light for a threedimensional illumination without shadows. Comfortable use

Thanks to the principle of indirect light, the lamp oriented towards different positions does not dazzle the surgeon and the assistants. The size of the lit field is adjusted mechanically through handle

according to the light required by the surgeon.

### Superior lighting features

- Membrane keyboard activates the following functions:
- selection of the colour temperature 5,000°K and 4,500°K
- adjustment of the light intensity up to 160 Klx

 endoled light with colour selection (comfortable light for endoscopy intervention) The colour temperature of 5,000°K stimulates the surgeons' concentration, does not strain their sight, reproduces the colour of the tissues faithfully and increases the definition of the edges.

### Reliable and long lasting performances

The modular construction of the electronic board that feeds the LEDs guarantees continuous light, even in the unlikely event that a LED or board component should fail. The lighting body is protected by tempered glass screen, covered by a special film avoiding any fallen down splinters in case of break Fasy manoeuvrability

The reduced dimensions and the light reflector provide extreme manoeuvrability and stability. Smooth 360° rotation. The extremely light structure, the aluminium treated bar attached to the upper front of the cupola, the ultra-thin dome (only 13 cm) allow simple movements. Battery group, TVCC camera, monitor holding camera on request Every lamp can be supplied with an emergency battery group with automatic charger (hours autonomy: 2.5 (49200), 2.5 (49201), 2 (49202)). TVCC camera or monitor holding arm.

Complies with European Directives 93/42/EEC

49207 IR remote control - double lamp

anu 200	1141/EC Class 1 - Medical Device CE marking. Made in ita
GIMA code	PENTALED 63N THEATRE LIGHTS - CEILING*
49200	PENTALED 63N - 160,000 LUX
49201	PENTALED 63N+30N double - 320,000 LUX - compact
49202	PENTALED 63N+63N double - 320,000 LUX - plus
	*Ceiling >3.80 m needs 49220
	ACCESSORIES
	Autoclavable handle - spare
49205	Monitor holding arm - stand alone
49206	IR remote control - single lamps


	ACCESSORIES TO BE ORDERED WITH LIGHT
49210	Battery group with automatic charger for 63N
49211	Battery group with automatic charger for 63N+30N
49212	Battery group with automatic charger for 63N+63N
	STD TVCC camera for 63N - including lamp setup
	HD TVCC camera for 63N - including lamp setup
	Monitor holding arm - integrated with lamp
	Special structure for high ceiling (>3.8 m)


### Monitor holding Monitor r included 49205

RIMSA

TECHNICA	L SPECIFICATIONS

	TECHNICAL SPECIFICATION	S		
			63N	30N
Performance	Light intensity at 1 m distance (Ec)	klx	160	160
	Colour temperature: double selection	°K	4,500/5,000	4,500/5,000
	Colour rendering index (CRI)	Ra	96	96
	Light field diameter adjustable from/to	cm	21-42	18-30
	Total radiated energy Ee where	W/m <sup>2</sup>	543	543
	the illumination reaches max level			
	Number of LED		72	30
	Diameter and focus adjustment		manual	manual
	Depth of illumination IEC 60601-0-41 L1+L2 at 60%	cm	46	55
	Depth of illumination IEC 60601-0-41 L1+L2 at 20%	cm	108	115
	Control of illuminance	%	25-100	25-100
	Endo LED light intensity min-max	klx	5-20	9-25
Electrical data		V	100-240	100-240
	Operating power Vdc	V	24	24
	Electrical absorbed power	VA	145	70
	Frequency	Hz	50/60	50/60
	Average LED life	h	50,000	50,000
General data	Colour	RAL	9003	9003
	Minimum height of the room	cm	260	260
	Outer reflector diameter	cm	63	40
	Useful lighting surface	cm <sup>2</sup>	1710	712
	Weight	kg	45	35







IEC 60601-2-41 - 93/42/EEC

### GIMALED O.T. LED LIGHTS - 160.000 LUX

GimaLed light with 81 Led: sophisticated design which combines excellent lighting features with exceptional mechanical characteristics for extra soft movement. Deep light: 27 inner fixed Leds for central illumination and 54 Leds (six modules of nine Leds each) moved by servo-motor, allow surgeon to adjust light field diameter.

Shadowless light: 81 Leds arranged on a round surface grant the best light emitting surface and avoid any shadow effect caused by any interposition between light beams and lighted

Bright light: two colour selections, 4,000K and 4,600K, made of white Leds only, no coloured shadow effect. Light intensity of 160,000 Lux.

### Major features

- collimated light beams for a working distance from 70 to 160 cm
- high colour rendering index (CRI) 95, R9 >90 optimisation of LED thermal management by heat dissipation convection to avoid illuminance reduction during surgery
- PMMA optical lenses and polycarbonate protective screen - Zener to grant light in case of even one Led failure
- reduced consumption, high efficiency
- optional pre-wired system for Wi-Fi HD camera

GIMA code	GIMALED
49180	GimaLed-mobile
49181	GimaLed-mobile with battery group and automatic charge
49182	GimaLed - ceiling"
49183	GimaLed - ceiling* - double
49197	Autoclavable handle
49205	Monitor holding arm - stand alone
49220	Special structure for high ceiling (>3.8 m)
49185	GimaLed wall remote control
49186	Set up kit for HD Wi-Fi camera**
49187	HD Wi-Fi camera - need 49186
	Battery group available on request for all models
*Cailing >3	80 m needs 19220 "Installation must be done by Gima at the order

Small overall Eraonomic arip in the dimensions of cupola and in the cupola, perfectly balanced, ensure to hold and move stable adjustment the lamp GIMA Motorised light field dia meter adjustment through 49183 Thin and easy-totouch sensitive sterilisal adiust reflector handle or touch pad at the side of the cupola 0 160,000 LUX 49180 TECHNICAL SPECIFICATIONS Light intensity at 1 m distance (Ec) Klx 160 2 Colour temperature - switchable °K 4,000 and 4,600 Colour rendering index (CRI) Light field Ø (adjustable) Ra 95 11-35 cm Light field Ø where illuminance reaches 10% of Ec (d10) 260 mm Light field Ø where illuminance reaches 50% of Ec 150 mm Total radiated energy Ee where illumination reaches max level 556 W/m Average LED life hours 50,000 100-240 V - 50-60 Hz - 61-71 W Power supply:

### PENTALED 30E SURGERY LAMP 160,000 LUX

Made in Italy

### LED LIGHT INNOVATIVE TECHNOLOGY

A compact size hi-tech product that guarantees great performance levels. It has 30 elliptical reflectors split into 6 modules each containing 5 LEDs, providing 160,000 LUX - selectable 4,500 °K - 5,000 °K. By simply pressing the digital key, the surgeon can choose two different white light temperatures

- E-view. Innovative lens allows the surgeon to expand/ narrow the illuminated operating field electronically, without altering intensity of light.

- E-comfort. The indirect LED's creates 3D shadowless illumination of the operating field, no risk of dazzling - E-white. Only white LED's to avoid risk of perception
- of colour temperature variations or coloured shadows
- E-deep. Centre of light is fitted with extra LEDs module specifically designed to reflect deep light. This means that surgeon can work with perfect 3D lighting.

Battery and high definition camera on request. Optional battery group with automatic charger (4 hours autonomy) and high definition integrated camera (for ceiling and wall models only)

deminio	definition integrated camera (for centing and wan models only).					
GIMA code	PENTALED 30E					
30780	Pentaled-mobile					
	Pentaled-mobile with battery group and automatic charger					
30781	Pentaled - wall					
30782	Pentaled - ceiling*					
30783	Pentaled - ceiling* - double					
30785	Autoclavable handle - up to serial number 12071					
30738	Autoclavable handle - since serial number 12072					
49205	Monitor holding arm - stand alone					
49220	Special structure for high ceiling (>3.8 m)					

Battery group available on request for all models

### **TECHNICAL SPECIFICATIONS**

Adjustable light intensity at 1 m distance (Ec) Klx 160 Colour temperature - switchable °K 4,500 to 5,000 Colour rendering index (CRI) Ra 96 Light field (electronically adjustable) 16-30 cm Light field Ø where illuminance reaches 10% of Ec (d10) mm 160 Light field Ø where illuminance reaches 50% of Ec

\*Ceiling >3.80 m needs 49220



### TRIS LED LIGHTS - 130,000 LUX switch SHADOWLESS THEATRE LED LIGHT Shadowless lamp with exceptional technical performance and flexibility of use. Suggested for small surgery, gynaecological **€** 93/42 EEC friction < and first aid surgeries. Cupola with four inner modules, each with 7 LEDs (total of 28 LEDs) displayed in a radial layout with mounted on lenses allowing shadowless and deep light. every articulation of the LEDs modules guarantee continuous light, even in the unlikely event that a LED should fail. Extremely easy to handle and stable in position. Focusing and adjusting the diameter of the illuminated area takes place by rotating the sterilizable handle at the centre of the reflector Battery group with charger: 4 hours autonomy, 6 hours recharging. TECHNICAL SPECIFICATIONS 49114 Light intensity: 130,000 lux at 1 m distance Diameter of the reflector: 40 cm Adjustable diameter of illuminated field: 26-38 cm Depth of illumination IEC 60601-2-41 (L1+L2) at 20%: 148 cm Depth of illumination IEC 60601-2-41 (L1+L2) at 60%: 82 cm 28 LEDs - life 50,000 hours Colour temperature: 4,300° K ± 5% CRI 96 (Chromatic Rendering Index) Power supply: 100-240V - 50/60 Hz - 70 VA 49110 Total radiated energy Ec 460 W/m Total radiated energy Ec 460 W/m² Weight (ceiling, mobile, wall) kg: 35 - 32 - 27 Minimum height of the room (ceiling version): 260 cm Norms: IEC 60601-1, IEC 60601-2-41 - MDD 93/42/EEC Continuous Continuous rotation Made in Italy Warranty: 12 months mechanical components warranty: 10 years 49113 GIMA TRIS SCIALYTIC LED LIGHTS 49110 Scialytic light - mobile stand 49111 Scialytic light - mobile with battery group and automatic charger 49112 Scialytic light - wall 49113 Scialytic light - ceiling\* Continuou 49114 Scialytic light double - ceiling\* 4 antistatio rotation 49220 Special structure for ceiling >3.80 m rubber castor. 49110 30738 Spare autoclavable handle - for scialytic 3 bulbs (2 with brakes) Battery group available on request for all models\*

### SATURNO LED LIGHTS - 30,000 LUX

30705

360° rotation

49102

Load bearing

Same for 19102

and 49103

in aluminium with tubing

Ø 45 mm facilitates installation

for any type of ceiling or wall

49100

4 antistatic

201

rubber castors

49103

# Autoclavable handle

### SATURNO LED MINOR SURGERY LAMP

SATURNO is a shadow-less type lamp suitable for small surgery, gynaecology and examination.

Available in three versions: mobile with castors, wall and ceiling.

- light beams are generated from 9 LEDs 2.5 W each
- heat is dissipated through aluminium cover reflector
- selection of 2 different white light temperatures: 5,000 °K and 4,500 °K
- light intensity adjustable at 6 different levels through front digital panel luminous intensity 30,000 LUX at 1 m. Diameter of illuminated field 28 cm
- adjustable friction bearing are mounted on every articulation of the lamp
- thanks to optical concept, no need to be focus adjusted

### Battery group with charger: 4 hours autonomy, 6 hours recharging

TECHNICAL SPECIFICATIONS		
Light intensity at 1 m distance	Lux	30,000
Colour temperature adjustable	Κ°	4,500/5,000 ± 5%
9 LEDs	W	2.5 each
Average LED life	hours	50,000
CRI (chromatic rendering Index)	Ra	96
Diameter of illuminated field	Ø cm	28
Depth of illumination IEC 60601-2-41 (L1+L2) at 20% of Ec	cm	228
Depth of illumination IEC 60601-2-41 (L1+L2) at 60% of Ec	cm	136
Total radiated energy Ec	W/m <sup>2</sup>	105
Diameter of the reflector	cm	19.5
Useful lighting surface of the cupola	cm <sup>2</sup>	65
Weight (ceiling, mobile, wall)	kg	12 - 14 - 13
Power requirements	V, Hz	100-240, 50-60
Minimum height of the room (ceiling version)	cm	244
Standards: IEC 60601-1 IEC 60601-2-41, MDD 93/42 CEE, media	cal device	of Class I

Standard	n height of the room (ceiling version)  s: IEC 60601-1 IEC 60601-2-41, MDD 93/42 CEE, medical device of Class I y 12 months - mechanical components warranty 10 years  Made in Italy
GIMA code	SATURNO LED LIGHTS
49100	Saturno LED light - mobile stand
49101	Saturno LED light - mobile stand with battery group
49102	Saturno LED light - wall
49103	Saturno LED light - ceiling*
49105	Special structure for high ceiling (>3.20 m)
30797	
	Battery group with automatic charger available on request for
	all models (to be installed at order)
	*Ceiling >3.20 m needs 49105

### PENTALED 12 - 100,000\* LUX, PENTALED 28 - 120,000 LUX

30792

49119

Light intensity at 1 m distance

CRI (Chromatic rendering Index)

Depth of illumination (L1+L2) at 60%

Weight (ceiling, mobile, wall, double)

Standards: IEC 60601-2-41, 2007/47/EEC, medical device of Class I

Diameter of illuminated filed

Total radiated energy Ec

Colour temperature LED

Average LED life

30790

49117

Antistatic wheels with brake

**TECHNICAL SPECIFICATIONS** 

Lux 100,000

K° No. 4.500

Ra 96

cm

kg

Ø mm 160

W/m<sup>2</sup> 350

30789

PENTALED 12 PENTALED 28

4,500/5,000

92 (5,000K)

96 (4,500K)

135-270

404

-18-13-12-20-

----100-230V, 50-60Hz--

50,000

30787

### Pentaled Digital control for light intensity isual signal of intensity set up The 2 opposite handles allow to direct the light from every position


### Pentaled 12

- 100,000° Lux at 1 m
- indirect light with 12 elliptic reflectors. They reflect the light rays emitted by the LEDs. Does not dazzle and does not strain

Since January 2018. 70,000 Lux up to December 2017

### Pentaled 28

- 120,000 Lux at 1 m
- direct light with 28 LED lens
- double colour selection: 4,500 or 5,000 K
- light field adjustment



30787

49115

### PENTALED

PENTALED is a perfect combination of technological developments, innovation, ergonomy and compact design, ultra-light and handy structure.

Five versions available (trolley, ceiling, ceiling double, trolley with battery group and wall) and technical performances make PENTALED suitable for precision operations, diagnostic use, surgical rooms and small surgeries.

Battery group, with an autonomy of 3 hours, is available on request also for wall and ceiling models.

### Cold LED light

Bright and cold light reproduces colours faithfully, assuring excellent definition of details.

### Ergonomic

- PENTALED can be easily positioned by rotation on 4 axes:
- the dome has a full-circle 360° rotation
- the arm moves vertically thanks to a spring balancing system - the reflector can be rotated on the vertical and horizontal axis. Movements are possible through the sterilizable handle.

### 50.000 hours life time

The low power supply current and the heat dispersion through aluminium dome allow the LED a 50,000 hours lifetime.

### Light intensity adjustment

Light intensity adjustable through digital control



The ultra-flat lighting body is equipped with ultra-resistant polycarbonate screen which guarantees protection against accidental collisions



code	PENTALED 12 LEDS
30787 30789	Pentaled 12 - trolley Pentaled 12 - ceiling* (for ceiling 2.57 to 3.33 m)
30790	Pentaled 12 - wall
30791	Pentaled 12 - trolley with battery group and automatic charger
30792	Pentaled 12+12 - ceiling* double
30788	Special structure for ceiling > 3.34 m
30793	Autoclavable handle - spare
GIMA code	PENTALED 28 LEDS
49115	Pentaled 28 - trolley
49116	Pentaled 28 - ceiling* (for ceiling from 2.57 to 3.33 m)
49117	Pentaled 28 - wall
49118	Pentaled 28 - trolley with battery group and automatic charger
49119	Pentaled 28+28 - ceiling* double
30788	Special structure for ceiling > 3.34 m

30793 Autoclavable handle - spare Ceilina >3.34 m needs 30788

### PRIMALED COLD LIGHT LAMP - 80,000 LUX AT 50 cm

The following functions are controlled by the keys

on/off

on the membrane keyboard

6-level adjustment of the light intensity

selection of the 5,000°K and 4,500°K colour temperatures

30778

### PRIMALED COLD LIGHT LAMP WITH 9 LED LENSES

Appealing design and advanced technology.

Design: the round and ultra-flat shape of the light makes the product ergonomic and suitable for any type of installation, from the doctor's surgery to the intensive-care unit.

Ergo-Spring: the movement of the articulated tubular arm

is servo-assisted by a torsion spring which ensures ease of movement and stability.

80,000 lux: unique performance with 80,000 lux at 50 cm

Light intensity adjustment: six different adjustment levels by the keys on the frontal panel.

4,500-5,000 °K Colour temperature selection: the comparison between the two colours (K) increases the visibility of details. Shadow suppression: the radial layout of the lenses and the large-diameter lamp (195 mm) allow shadow suppression and

three-dimensional lighting. **Adjustable courtesy-light:** integrates ambient light with traditional concentrated light.

Sterilizable removable grip: allows best asepsis.

Cold light: the reduced emission of IR rays by the LEDs as well

as the low power consumption allow minimum heat emission. **Disinfection:** the smooth and rounded shape of the dome and structure make it easy to clean and disinfect. 50,000 hours LEDs life: the top aluminium dome allows

heat exchange, thus reducing the work temperature and considerably increasing the life cycle of the single LEDs. Fully certified: complies with IEC 60601-1 and 60601-1-2 general medical standards and to special standard IEC 60601-2-41 93/42 EEC and 2007/47 EC and is CE marked as a Class I medical device. Mechanical testing and user safety: die-cast aluminium and tubular steel structure. The articulated arm has undergone mechanical testing for 40,000 continuous movements to ensure maximum safety for the user during use.

**Light continuity:** the modular design of the LED power circuit

ensures light continuity even in case of a LED fault.						
GIMA code	PRIMALED					
30753 30778 49105 30784 30786	Primaled light - trolley Primaled flex light - trolley Primaled flex light - teriling' (for ceiling 2.44 to 3.20 m) Special structure for high ceiling (>3.20 m) Primaled light - wall Primaled light - rail (25x10) and clamp Autoclavable handle Battery group available on request					
	*Ceiling >3.20 m needs 49105					
TECHNICAL SPECIFICATIONS						

LED life: 50,000 hours Light intensity: 80,000 lux at 50 cm, 20,000 lux at 1 m Colour temperature: 4,500-5,000 °K Colour reno Illuminated field at 50 cm: Ø 140 mm External diameter of the reflector: 190 mm Colour rendering index: 95 Ra

Temperature increase in the operating area at 1 m: 1°C
Adjustable height with castors: 600 mm - max 1,600 mm
Power supply: 80-240V - 50/60 Hz
Weight: 10 kg (trolley included)

Made in Italy

### RI-MAGIC® HP LED LIGHT


- 49050 RI-MAGIC® HP LED desk 49051 RI-MAGIC® HP LED trolley
- 49052 RI-MAGIC® HP LED wall
- High performance medical LED light for examination and procedures.
- high performance LED, 6,500 °K - lifetime of the lamp up to 50,000 hours
- significantly reduced heating and energy loss - focusing device at the front of the
- light head - highly flexible, long special arm can be bent in all directions
- rheostat handle for infinitely variable regulation of light intensity. Manual in: GB, FR, IT, ES, DE, RU. Made in Germany

TECHNICAL SPECIFICATIONS Distance: 1,000 mm 800 mm 600 mm 15,000

Circle of light max Ø: 340 mm Circle of light min Ø: 40 mm Operating voltage: 100-240 V,

20,000 30,000 270 mm 215 mm 35 mm 30 mm 50-60 Hz





### HALOGEN AND LED LIGHTS FOR EXAMINATION AND MINOR SURGERY





- 30747 SOLESUD 2 on trolley halogen • 30748 SOLESUD 2 wall - halogen ®
- Suitable for gynaecology, examination and head-bed. Aluminium reflector equipped with 2 halogen dichroic bulbs, 20W 12V 10° IRC protected by a tempered glass, hermetically sealed against dirt and fluid spray and with ergonomic handle for movement. Bulbs switch on simultaneously and, in case one breaks, light is always assured. Arm movement servo-assisted by a torsion spring provides lightweight movement and stability of position. A light beam of 180 mm diameter at a distance of 50 cm allows precise and reliable examinations.

Base with 5 rotary spokes, 900 mm high 3 Pin British Plug available on request. Made in Italy.

- 30769 SPARE TROLLEY base Ø 61 cm
- 30775 RAIL CONNECTION WITH CLAMP • 30764 SPARE BULB SOLESUD 2 - 20 W



30775	<u>-0</u> -						
Model	SOLESUD 2	SIMPL	-EX	LUXIFLEX		MINIMED	2
Type of lighting	halogen	halogen	LED	halogen	LED	halogen	LED
Consumption (Watt)	2x20	35	3x1.4	35	10	50	7
Life of the bulbs (hours)	5,000	5,000	50,000	5,000	25,000	7,000	30,000
Light intensity at 50 cm (lux)	40,000	30,000	35,000	50,000	15,000	37,000	20,000
Light intensity at 1 m (lux)	8,000	8,000	13,000	-	-	-	-
Colour temperature ± 5% at 1 m (K)	3,000	3,000	4,200	4,000	3,000	3,100	7,000
Light field size at 50 cm (Ø mm)	180	100	140				
External Ø of the reflector (mm)	140	105	86			60	60
Colour	white	white	white	white	white	cold white	cold white
Norms	IEC 60601-1	IEC 598-2-25	IEC 60601-1	⊢EN 6060	1-1-2 —	— IEC 60	0601-1
Marks	CE 93/42	CE 2006/95	CE 93/42	CE 93	/42	CE 93/42	CE 93/42
Weight (kg)	6	5	5			9	9
Operating voltage V	230	230	100-230	<b></b> 23	0 ——	<b></b> 230 −	+ 190-265 -
Operating Hz	-	50/60		<b></b> 50		<b></b> 50	/60
Operating voltage on request V-Hz				<b>├</b> 110-	60* —		-

50,000 LUX - Halogen GB, FR, IT, DE, ES, PT 15,000 LUX - LED MIMSAL 30754 Heiaht 50 cm (arm) + 95 ci (trolley) 30754 30756

• 30754 LUXIFLEX on trolley - halogen

procedures in health-centres, clinics and

hospitals. Suitable also for veterinary

Safe low voltage operation without

transformer lodged at the bottom of

the lamp. Flexible arm and 5 castors

trollev allow easy use and movability.

• 30757 SPARE BULB LUXIFLEX - halogen

• 30756 LUXIFLEX on trolley - LED

Stylish and versatile light for

examination and minor surgery

examinations and procedures.

infrared radiation. Electronic

Class II. Made in Europe.

• 30760 SIMPLEX on trolley - halogen

Adjustable

60-160 cn

30760

• 30761 SIMPLEX wall ® - halogen • 30762 SIMPLEX table with clamp (9)

30760

• 30763 SIMPLEX rail © - halogen

Versatile lamp equipped with a halogen dichroic bulb 35W 12V placed inside the aluminium reflector and protected by a tempered glass.

Electronic transformer integrated in the base with lead retainer with spiral protection and bipolar light switch with green indicator light.

Ceramic fuse offers extra protection. • 30759 SIMPLEX on trolley - LED

- 30749 SIMPLEX wall ® LED
- 30752 SIMPLEX table with clamp (a) LED Thanks to 3 independent light sources shadow can be reduced and provide a deep cylindrical light with highly reduced heat irradiation. Each LED integrates a resistance to ensure the continuous operation of the lamp even in the rare case of a LED fault. Other specifications as halogen model. Made in Italy.
- 30766 SPARE BULB SIMPLEX IRC 35 W

\*minimum 50 pcs

• 30768 SPARE TROLLEY - base Ø 62 cm • 30775 RAIL CONNECTION WITH CLAMP

30712 35 cm flexib 4 hours on, 30 min off 37,000 LUX 30714 30714 Continuous use Schuko plug 20,000 LUX

- 30712 MINIMED 2 ON TROLLEY halogen • 30714 MINIMED 2 ON TROLLEY - 12 LED
- Low voltage and high definition, intense light. Flexible arm for versatile use. Supplied on a sturdy 5 castors stand for easy movability. Made in Italy.
- 30744 SPARE BULB 50 W halogen

### MAGNIFYING FLUORESCENT COLD LIGHTS - 3 DIOPTRES

the light source.

Magnifying glass self-illuminating fluorescent cold light 3 dioptres (0.75X). Suggested for dermatology and whenever magnifying is required. It is equipped with a biconvex magnifying lens in optical glass Ø 120 mm. The cold fluorescent light allows

prolonged use. Polycarbonate screen for protection of

Available also with wall support. Medical device Class I.

### **TECHNICAL SPECIFICATIONS**

fluorescent

Type of lighting 22 W Consumption Life of the bulbs 6.000 hours Light intensity at 50 cm 550 lux Colour temperature 4.550 °K External diameter of the reflector 230 mm Temperature increase at 1 m 0°C IFC-60601-2-41 Norms Marks CE 93/42 Weight 7 kg Operating voltage V-Hz 220-240 V, 50 Hz Adjustment height with castors base: 60-180 cm





### LED MAGNIFYING LAMP - 5 DIOPTRES

- 30737 LUPA LED MAGNIFYING LIGHT -
- 30739 LUPA LED MAGNIFYING LIGHT desk with clamp

Smartly designed cold light LED lamp with 5-dioptres magnification. Generates a light without shadow. 5 wheels base and articulated arm allow easy movement.

Manual in GB, FR, IT, ES, PT, DE. Medical device Class I

Made in Europe

### TECHNICAL SPECIFICATIONS

Type of light: 80 LED - HF 8 W Dioptres: Ø 12 7 cm Colour temperature: 6,500 °K Operating voltage: 230 V - 50 Hz Electrical security: UNI EN 60601-1 (1990) Electromagnetic compatibility: EN 60601-1-2 (1993)



### LED MAGNIFYING LAMP - 3 DIOPTRES 30736 DERMALED MAGNIFYING LAMP

Cold light LED lamp with 3 dioptres magnifying lens and brightness adjustment It comes with a high stability 5 wheels

base and an articulated arm for easy movement and fixing of the lamp. Made in China.

### **TECHNICAL SPECIFICATIONS**

Type of light: LED Voltage: 8 W Dioptres: 3 (large glass) Colour temperature: 8 000-9 000 °K Light intensity at 20 cm: 2,000 lux 100-240 V - 50/60 Hz Operating voltage: Net/Gross weight 10-12 kg





### 🛘 VISTA WOOD BLUE LIGHTS: TROLLEY AND MANUAL 📕 MACRO LENS 12X

• 31196 VISTA WOOD LAMP - handle

• 31197 VISTA WOOD LAMP - trolley A Wood lamp is a diagnostic tool to diagnose the condition of skin. Different skin conditions under ultraviolet rays of the Wood lamp appear in different colours. These models have polished glass magnifying lens 10x6 cm -

3 dioptres. 9W special compact fluorescent tube at approximately 360 nm wavelength. Operating voltage: 230 V - 50 Hz.

Manual in GB, FR, IT, ES, PT, DE. Made in Spain





### • 31155 SMARTPHONE MACRO LENS 12X Macro lens 12X for allergists, dermatologists, phlebologists, aesthetic surgeries. Can be mounted on any smartphone to take magnified images. Supplied with clip compatible with any smartphone, 10x10 cm wipe and multilanguage manual (GB. FR. IT. ES. PT. DE. PL. GR) 31155 Smartnhone not included

### ECONOMIC WOOD LAMP. POCKET WOOD LIGHT



31200 WOOD LAMP Ultraviolet light for skin condition analysis. Size 30x21x7 cm.

• 31202 FLUORESCENT TUBE - spare

database, image comparison and medical referts

polarized filter

Magnification:

Operation system

Power consumption

Photo and video resolution

Light source:

Frame rate

• 32181 Wi-Fi DERMATOSCOPE with

32182 PROFESSIONAL SOFTWARE for 32181

DERMATOSCOPE SPECIFICATIONS

8 adjustable white LED

High definition microscopy lens

5X to 200X



Basic software for acquisition of photos, videos, measurements

 31189 POCKET WOOD LIGHT Pocket ultraviolet light, to detect skin disorders. Provided with replaceable fluorescent lamp. Power 6 V. Works with 4xAA batteries with 4-6 hours autonomy.

• 31190 FLUORESCENT TUBE - spare

google/apple applications included.

Designed in Italy, manufactured in China.

Directive 93/43/CEE - Medical device Class I

### DIGITAL Wi-Fi POLARISED DERMATOSCOPE, CAPILLAROSCOPE, MICROSCOPE

An innovative line of handheld colour digital microscopes: dermatoscope with polarized filter, capillaroscope and iridoscope with Wi-Fi wireless transmission. Small, easy to operate light and portable.

They can be used with all the most popular smartphones, tablet and PC.



(only 32181 and 32183).

• 32183 Wi-Fi CAPILLAROSCOPE

32184

CAPILLAROSCOPE SPECIFICATIONS

Magnification: 500X to 600X 8 adjustable white LED Light source: Lens: High definition microscopy lens

TECHNICAL SPECIFICATIONS

Windows (XP and following), Mac (OSX 10.7 following), iOS, Android (it can be used by Wi-Fi or USB) 1.3 MPixels - 1280x1024 (MJPG) 640x480 (MJPG), 320x240 15 fps 1,280x1,024, 30 fps 640x480 320x240

Wi-Fi wireless transmission distance Max 2.5 W

Li-ion battery full charging time - appx. 2 hours DC 5.0V / 1A - Ø 36x142 mm - 88 g Power source - Size - Weight

CAMERA

Camera sensor CMOS 1/4" Optical features Exposure: Auto, Gamma: Auto, White balance: Auto, Black reference: Auto

Continuous working time - appx. 2 hours, PROFESSIONAL SOFTWARE Operation system: Windows XP and next Software language: GB, IT

### 32184 Wi-Fi MICROSCOPE Adviced for iris scanning

MICROSCOPE SPECIFICATIONS Magnification: 30X Light source:

2 adjustable white LED+ 2 adjustable yellow LED High definition microscopy lens

STANDARD ACCESSORIES Caps of contact (only for 32181)

USB AC adapter USB cable Ouick manual Plastic stand Line calibration ruler Manual (GB, FR, IT, ES, DE) CD basic software Win (GB, IT, ES, DE, PT, RU, BG, TH, JP, KR), Mac (GB)

### HEINE DELTA 20® T LED™ DERMATOSCOPES 10X - 16X

• 31165 HEINE DELTA 20® T LED<sup>HQ</sup> DERMATOSCOPE 2.5V for polarization and immersion - K-262.10.118

• 31161 HEINE DELTA 20® T LED<sup>HQ</sup> DERMATOSCOPE 3.5V (Li-ion) for polarization and immersion with rechargeable handle for mains socket and USB cable - K-262.28.388

Precision HEINE Optics - high quality, achromatic optical system provides unsurpassed sharpness and resolution. Focusing system provides from 10X to 16X magnification for detection of even the smallest details and structures.

LED in HQ - the new standard in LED illumination defining optimal light intensity, homogeneity and colour rendering for each individual examination - Colour temperature: 5.000 K, Colour Rendering Index (CRI) > 80 on a scale of 100. This ensures true tissue colour for the most accurate diagnosis. Toggle between polarised and non-polarised illumination modes - conveniently alternate between two modes with the press of a button - no exchange of contact plates necessary. Allows recognition of the "Blink Sign" when observing

crystalline structures and presence of milia cysts, increasing diagnostic function. Optional small contact plate for difficult to access lesions. Digital documentation capabilities - Heine SLR photo adapter allows to connect any Delta 20 dermatoscope to major brands of digital cameras.

LED Thermal Management - ensure long-term performance and product stability. Carefully selected and applied heatdiffusing materials guarantee up to 50.000 hours.

• 31184 HEINE MINI 3000 XENON-HALOGEN

Pocket dermatoscope with high-quality optics, 10X magnification with focusing optics, metal head.

Xenon Halogen bulb. Concentrated, bright light for uniform illumination with exact colour rendering. High quality colour-neutral optic system with

Supplied with dermoscopic compendium and oil.

Operates with AA batteries or rechargeable bat-

• 31160 HEINE MINI 3000 LED<sup>HQ</sup> DERMATOSCOPE

High-performance bright and homogeneous LED

illumination with an excellent colour rendering

Twice brighter light compared to Xenon Halogen

Fade-out function: reduces illumination intensity with battery

10X - D-008-78-109 - same as 31184, with the

(index >95). Colour temperature 4,000 K.

level to let you know when to replace.

• 31692 HEINE MINI 3000 NT CHARGER

• 31693 BATTERY+BASE - X-001.99.487 +

Up to 10 hours operation time.

teries (31693) + Mini 3000 NT charger (31692) not

DERMATOSCOPE 10X - D-001.78.107

acromatic lenses, provides sharp images.

Contact plate without scale.

Maintenance free.

X-001.99.484

X-001.99.488

HEINE MINI 3000 DERMATOSCOPES

5 YEARS WARRANT LED NOW IN HEINE QUALITY 31161 31165

Supplied with hard case, dermatoscopy compendium, 10 ml oil.

• 31162 HEINE DELTA T LED DERMATOSCOPE HEAD with contact plate with graduated scale - K-008.34.221 (can be used with any Heine Beta handle). Supplied with compendium.
• 31179 SMALL CONTACT PLATE Ø 8 mm - K-000.34.205

• 31171 SLR PHOTO ADAPTOR - for Canon

• 31173 SLR PHOTO ADAPTOR - for Nikon

• 31174 SLR PHOTO ADAPTOR - for Olympus • 31169 ADAPTOR CORD - 1.30 m

• 31169 ADAPTOR CORD - 1.30 m • 31183 DERMATOLOGY OIL - box of 4 bottles of 12.5 ml

### HEINE NC1 LED DERMATOSCOPE • 31158 HEINE NC1 LED<sup>HQ</sup> DERMATOSCOPE - D-008.78.132

LED thermal management - LED illumination systems require thermal management. Carefully selected heat-diffusing materials guarantee consistent quality and performance for up to 50.000 hours. Aluminium frame - more stability to the device for a long working life.

Non-Contact Dermatoscope - examining patients without touching the skin saves time and provides more professional distance between examiner and investigation area. Polarised Illumination for detailed views of the crystalline and vascular structures. Allows examinations without contact liquids.

Precision HEINE Optics with 6X magnification - highquality, aspherical optical system provides unsurpassed sharpness and resolution.

LED in HQ - optimal light intensity, homogeneity and colour rendering for each individual examination Colour temperature: 5,000 K, Colour Rendering Index (CRI) 80, special index for red colours (R9) 35 on a maximum scale of 100. This ensures true tissue colour for the most accurate diagnosis.

Optional Contact Plate with additional magnification - adding the contact plate transforms NC1 in a contact dermoscopy, increasing magnification (9X) plus offering a scale. It combines the speed and ease of use of non-contact dermoscopy with the detail and precision of a contact device.

31158

• 31159 CONTACT PLATE WITH SCALE - D-000.78.115

## 31692

### GIMA XENON HALOGEN SKIN SURFACE MICROSCOPE 10X

• 31187 GIMA XENON HALOGEN DERMATOSCOPE 2.5 V - 10X Advanced skin surface microscope offers long-lasting halogen illumination for the true tissue colour and 10X magnification for greater details, allowing accurate diagnoses of pigmented skin lesion. Supplied in a useful bag, with spare autoclavable contact plate with 0-10 mm scale. Latex free.

• 31183 DERMATOLOGY OIL box of 4 bottles of 12.5 ml

• 32203 "C" BATTERIES - blister of 2 pcs. • 31479 XENON HALOGEN BULB - 2.5V - spare

• 31185 SKIN LESION GAUGE - 21x5 cm Available with your logo for min. 2,000 pcs.

### **TECHNICAL SPECIFICATIONS**

Battery: 2x"C" or rechargeable battery (34479) + charger (31542) Reticle contact plate Easy to focus, with large focus ring





2.4" colou

Video out por

320x240 pixels

Size: 8x20 cm

 $\epsilon$ 

FDA

US pat. n° 8206290

32175

(2.5"x8")

nage freeze

Lightweight

218 g

Battery

lifespan:

4 hours

### MD SCOPE VIDEO OTOSCOPE

### MD SCOPE VIDEO OTOSCOPE

### Instant View

A clear and sharp image can be acquired and displayed instantly on a built-in screen. Just press a single button and wait for 3 seconds.

### Real Time Interaction

The medical image can be captured and shared simultaneously with patients. A true improved interaction between the health professionals and the patients. Electronic medical record

### A medical image is automatically generated to support most of the stand-alone health information system. Simply plug the cable into the video-out socket to

retrieve the image.



### • 32160 ELITE PACK MD Scope with

- 1 camera probe 45 mm Ø 5.2 mm
- RCA video cable
- 24 disposable specula
- 2 AA alkaline battery



Basic software included for acquisition

of photos, videos, measurements,

google/apple applications



- 32162 DELUXE ZIPPER PACK 4 cameras
- MD Scope with
- 2 camera probes 45 (Ø 5.2 mm)/150 (32161)
- 4 camera probes 45 (Ø 5.2 mm)/
- 75/150/300 mm (32162)
- image dongle (32162 only)
- cable set (32176): USB and RCA cable,
- adaptor for image dongle
- 24 disposable specula
- 2 AA alkaline batteries



DIGITAL Wi-Fi & USB VIDEOTOSCOPE + SOFTWARE

Li-ion battery:

Power source

Camera sensor Optical features

Magnification: Focus range: Object distance:

Software interface

Light source:

Otoscope

### GIMΔ ACCESSORIES AND SPARE PARTS code **32165** Camera probe 45 x Ø 5.2 mm **32166** Camera probe 47 x Ø 4.2 mm **32167** Long camera probe 75 x Ø 5.2 mm 32168 Flexible camera probe 150 x Ø 5.2 mm 32169 Long flexible camera probe 300 x Ø 5.2 mm 32172 Disposable rigid specula Ø 5.5 mm

for 32165 - box of 250 32173 Reusable silicone specula Ø 4.2 mm for 32166 - box of 24

32175 Cradle for video otoscope

32176 Cable set (USB and RCA cable, adaptor)

### Operation system: Photo and video resolution Frame rate: Wi-Fi wireless transmission distance: Power consumption:

• 32180 MIC Wi-Fi & USB VIDEOTOSCOPE with software Innovative, handheld colour digital Otoscope with Wi-Fi wireless transmission. Small, easy to operate, light and portable. It can be used with all the most popular smartphones, tablets and even with PC.

Designed in Italy, made in China. • 31491 DISPOSABLE MINI EAR SPECULUM Ø 2.5 mm - black box of 100

• 31492 DISPOSABLE MINI EAR SPECULUM Ø 4 mm - black box of 100

Suitable also Mini Ear Speculum 31485-8, 31495-9 at page 220

### TECHNICAL SPECIFICATIONS

10.7 and following), iOS, Android 1.3 MPixels - 1.280x1.024 (MJPG).

640x480 (MJPG), 320x240 15 fps 1280x1024, 30 fps 640x480 320x240 up to 5

max 2.5 W continuous working time - approx. 2 hours, full charging time - approx. 2 hours DC 5.0 V / 1A

Ø 36x142 mm - 88 a

CMOS 1/41 Exposure: Auto. Gamma: Auto. White balance: Auto, Black reference: Auto

8-60 mm 1-160 mm 4 adjustable white LED high definition microscopy lens Mic-Fi Apps for Android and iOS system

### and Mic-Fi softwares for PC and MAC STANDARD ACCESSORIES

USB AC adapter and cable Manual (GB, FR, IT, ES, DE) Plastic stand Line calibration ruler CD basic software Win (GB, IT, ES, DE, PT, RU, BG, TH, JP, KR) Mac (GB)

### HEINE OMEGA® 500 INDIRECT OPHTHALMOSCOPE

• 31753 HEINE OMEGA 500 XENON-HALOGEN INDIRECT OPHTHALMOSCOPE 6V - C-004.33.539 With mPack pocket battery, plug-in transformer, headband rheostat and 90° angled adapter

- clearer, crisper views: a new illumination system with Xenon Halogen Technology bulb produces less reflexes off the cornea and clear, high resolution bright images of the fundus.

- enhanced variable pupil function: allows for the precise, synchronized selection of observation and illumination optics for any pupil size. It provides stereopsis in pupils ranging from 10 mm to 1 mm.

- fully featured: 3 Spot sizes: Large, Medium and Small. Integrated diffused light filter.

3 Integrated Filters: Red-free, Cobalt Blue, and Yellow.

- Omega headband comfort: articulating Rear Hinge provides vertical adjustment of the rear band of the headband for individual placement. • 31756 HEINE OMEGA 500 UNPLUGGED LED<sup>HQ</sup> INDIRECT OPHTHALMOSCOPE 6V - C-008.33.535

With mPack battery integrated in headband, plug-in transformer, headband rheostat and 90° angled adapter. Same feature as 31753 with in addition:

- LED technology: absolutely homogeneous, uniform illumination, up to 100% brighter compared with XHL (Xenon technology)
- rechargeable battery integrated on the headband

- mPack rechargeable battery: charging time 2 hours, operating time 8 hours

 31757 HEINE OMEGA 500 LED<sup>TO</sup> INDIRECT OPHTHALMOSCOPE WITH DV1 DIGITAL VIDEO CAMERA - C-008.33.561 with mPack UNPLUGGED with plug-in transformer

1280 x 960 imaging: capable of capturing High-Resolution video

- simple operation: digital imaging without any additional adjustments.
- comfortable and balanced fit: headband perfectly distributes the low weight of the camera and optics

integrated focus adjustment

- interface and software: will plug into any laptop or computer via USB 2.0 interface. Supplied with

software program for video recording and image capture. For more information see http://dv1.heine.com - **cable-free power source:** system with mPack UNPLUGGED rechargeable battery.

### WELCH ALLYN MACROVIEW™ OTOSCOPE

• 32100 MACROVIEW™ HEAD - 23810

31757

• 32101 LITHIUM ION HANDLE WITH AC CHARGING MODULE 3.5 V - 71902

This next-generation otoscope features advanced optics that increase magnification while giving you a nearly full view of the tympanic membrane - virtually eliminating the need for panning. With its easy-to-focus eyepiece, MacroView allows for enhanced visualization to help see past wax, locate fluid behind the eardrum, and even perform exams without your glasses. - twice the field of view

- 30% greater magnification than a traditional otoscope
- nearly a full view of the tympanic membrane
- better clarity and definition of landmarks
- ability to adjust focus for variable ear canal lengths or farsighted eyes
- 32106 KLEENSPEC® ADULT DISPOSABLE EAR SPECULA
- 4.25 mm box of 850 pcs 52434-UB 32105 KLEENSPEC® PEDIATRIC DISPOSABLE EAR SPECULA
- 2.75 mm box of 850 pcs 52432-UB
- 32135 SPARE HALOGEN BULB 3.5 V 06500 U

Adjustable focus wheel allows to accomodate for variable ear canal lengths and farsighted eyes a full view of the tympanic membrane

Default focus position (the dot and the line) Advanced ontics

give you 2X the field of view and 30% greater magnificatio than a conventional

undilated eye

Patient Eyecup

distance,

allows proper viewing

provides image stability,

around the retina, helps

with orientation, and

screens out ambient

light. The evecup is

serves as a pivoting

point for panning



32100 Insufflation port for

Tip grip ensures ear specula is fastened and easily disposed



charger module all Welch Allvi 351

**NARRANT** 

Light weight

32101

Welch Allyn 3.5 V Power

### I WELCH ALLYN PANOPTIC™ OPHTHALMOSCOPE

### • 32110 PANOPTIC OPHTHALMOSCOPE HEAD - 11810 32101 LITHIUM ION HANDLE WITH AC CHARGING MODULE

3.5 V - 71902

PanOptic is a breakthrough concept in ophthalmoscopy. Thanks to an innovative, optical design known as Axial PointSource™ Optics, it will greatly enhance your funduscopic examinations. - fast easy entry into small, undilated pupils

- 5X larger field of view than you see with standard
- ophthalmoscopes in an undilated eye - 25° field of view versus the 5° field of view of standard ophthalmo's
- a 26% increase in magnification, making it easier to see

retinal details
- greater distance between practitioner and patient means greater comfort for all

32127 SPARE HALOGEN BULB - 3800 U

FIELD OF VIEW





Patented Axial Halogen HPX™ Lamp: PointSource™ Optics: makes it easy to enter undilated pupils and provides a 25° field of view, resulting in a view of the

System: prevents interference from unwanter

provides whiter, brighter light Sources: compatible with any standard 3.5 V Glare Extinguishment power source including. desk charger handles, convertible battery handles



ergonomically designed for maximum comfort balance, and access to controls.

Aperture Dial: allows you to select micro, small, and large spot sizes. Also includes red-free filter and slit aperture. half-moon aperture for corneal exams

Focusing Wheel adjusts the focus in a continuous, smooth action for more precise control and optimum view Available focusing range is -20 to

+20 diopters

209

### HEINE ORIGINAL BULBS 📙 RIESTER ORIGINAL BULBS

HEINE BULBS	NE BULBS HEINE GIMA Compatible with follow ref. code HEINE products		Compatible with following HEINE products
Xenon 2.5 V	035	31769	Transilluminator Finoff alpha* F.O. and F.O. SP Laryngoscopes - Sanalon handle Glaucotest
Xenon 2.5 V	037	31771	K100 and Beta® 100, Beta® 100 vet otoscopes Laryngeal mirrors F.O. mini 2000 otoscope Alpha® and Alpha F.O. otoscopes Mini/mini 3000/Alpha/Beta tongue holders
	038	31773	Miroflex ophthalmoscope HFR2 spot retinoscope Delta®10 dermatoscope
	041	31774	Fibralux mini otoscope Mini 2000 combilamp Mini 2000 cliplamp Mini 1000 cliplamp
arm)	042	31780	Alpha® ophthalmoscope Mini 2000 ophthalmoscope Alpha® Focalux Mini Miroflex ophthalmoscope Mini 2000 Focalux
	056	31770	Minilux otoscope Mini 2000 otoscope
Courses.	057	31785	Mini 2000, Mini 3000 laringeal mirrors
AND STATE OF THE PARTY OF THE P	069 31781 Beta® 200, 200 M2, 2005 - XHL 2.5 V		Beta® 200, 200 M2, 200S ophthalmoscopes - XHL 2.5 V
Xenon 2.5 V	077	31772	Beta® 200, 200 VET, 400; K 180 otoscopes Lambda 100 retinometer Delta®10 plus dermatoscope
Xenon 2.5 V	084	31782	K180 <sup>®</sup> ophthalmoscope - 2.5 V
( and and	105	31776	Mini 3000 F.O. otoscope
-	106	31777	Mini 3000 ophthalmoscope
9	107	31778	Mini 3000 combilamp and cliplamp - XHL 2.5 V
The same of the sa	109	31779	Mini 3000 dermatoscope
	110	31775	Mini 3000 otoscope
	070	31783	Beta 200, 200 M2, 200S ophtalmoscopes - XHL 3.5V
- maritain	078	31784	Beta 200, 200 Vet, KI80 otoscopes lambda 100 retinometer otoscopes - XHL 3.5V

RIESTER BULBS	RIESTER ref.	GIMA code	Bulb	Compatible with following RIESTER products
Fliester 27 Y	10421	31850	Vacuum 2.7 V	Otoscope uni <sup>e</sup> /speculight
Faster 37.V	10424	31851	Vacuum 2.5 V	May-ophthalmoscope uni®
=	10487	31825	XL 3.5 V xenon	Otoscope ri-scope® L1
=	10488	31852	Vacuum 2.7 V	Pen-scope® and e-scope® otoscope
	10489	31560	HL 2.5 V	Otoscope pen-scope®/ ri-scope® L1 and e-scope®
•	10590	31853	HL 2.5 V	Otoscope uni®
Sinnin sheep	10600	31854	XL 2.5 V	Otoscope ri-mini <sup>®</sup> , ri-scope <sup>®</sup> L2/L3 and e-scope <sup>®</sup>
Alexan Z.5 V	10605	31562	HL 2.5 V	Ophthalmoscope ri-mini/ ri-scope® L1, L2, L3, e-scope®, ri-derma®
	10607	31855	XL 3.5 V	Ri-scope® otoscope L2, L3
MAL roude	10608	31826	XL 3.5 V	Ri-scope® ophthalmoscope L1, L2, L3
1	14041	31561	LED 3.7 V	E-scope F.O otoscope
	14051	31563	LED 3.7 V	E-scope ophthalmoscopes









### WFICH ALLYN BULBS

		<u> </u>	IN DOLDS
WELCH ALLYN BULBS	W. A. ref.	GIMA code	Compatible with following WELCH ALLYN products
MIDS SILVE	00200-U	32120	Anoscopes: 38800, 380, 385, 395 Illuminators: 41000, 26030 Old products: 235, 77900, 26000, 20100, 21600, 42700, 40510
	03000-U	32123	Ophthalmo: 11710, strabismoscope: 12400, episcope: 47300 Old ophthalmo: 11600, 11605, 11610 Retinoscope: 18000
	03100-U	32124	Otoscopes: 25020, 21700, 20200 Handle: 73500, holder: 28100 Illuminators: 27000, 27050, 26530, 41100, 43300 Old otoscopes: 25000, 25200, 20000
	03300-U	32125	Ophthalmo: 11511-11500
MICH ALTH	03400-U	32126	Otoscopes: 24011-24020-24000-24031-21110/1 Handle: 73550, Illuminators: 27200-27250-41110
	03800-U	32127	Pan optic: 11810-11820-11800
C STATE OF	04100-U	32128	Exam light: 48400-48410
-	04200-U	32129	Exam light: 48600, 48610-48625-48635, 48700
WELCH ALLYN	04400-U	32130	Ophthalmoscopes: 11400-11411-11470-11475
4	04700-U	32131	Laryngo: 680, 690, 692 (size 1-2) Old laryngo: 634, 664, 674, 684, 694 (check size)
11 15	04800-U	32132	Laryngo: 680 (size 2-4), 690, 692 (size 3-4) Old laryngo: 634, 640, 664, 674, 684, 694 (check size)
WITCH ALLTON DED	04900-U	32133	Ophthalmo: 11720, 11730, 11735, 11620, 11630
	06000-U	32134	Laryngo handles: 60813, 60814, 60713, 60815, 60803, 60804
-	06500-U	32135	Macroview otoscope: 23810, 23820

07800-U 32136 Handle: 73211, 73210, 78000, 73200

### COMPATIBLE GERMAN BULBS

	/II / \IIDEL	<u> </u>	INIVIA NI DOLDO					
GIMA BULBS GIMA Compatible with the code following products								
LA	RYNGOSCOPE BU	LBS - MA	ADE IN GERMANY					
	Conventional laryngoscope SMALL bulb 2.7 V	34324	Gima, Riester, And, Kawe, Timesco Truphatek and most of conventional laryngoscopes in the market (generally used for blades N° 00, 0, 1)					
	Conventional laryngoscope LARGE bulb 2.7 V	34325	Gima, Riester, And, Kawe, Truphatek, Timesco and most of conventional laryngoscopes in the market (generally used for blades N° 2, 3, 4)					
	Xenon halogen bulb for F.O. Laryngoscope and otoscope	34485	Gima, And, Kawe and most of F.O. laryngoscopes in the market. Compatible for products that use Heine Bulb # 035					
OTOSCOPE-O	PHTHALMOSCOPE	BULBS -	MADE IN FRANCE-GERMANY					
	Xenon halogen otoscope bulb	31795	Heine mini 3000 otoscopes					
	Xenon halogen F.O. otoscope bulb	31796	Heine mini 3000 F.O. otoscopes					
	Otoscope bulb 2.5V	31449	Parker otoscopes and some otoscopes of Riester, Timesco and Kawe					
-	Ophthalmoscope bulb 2.5V	31446	Parker ophthalmoscope Parker diagnostic sets					
	Xenon halogen bulb for otoscope 2.5V	31478	Gimalux otoscopes, Kawe and Riester mini otoscopes Compatible for products that use Heine bulb #037					
	Halogen bulb for ophthalmoscope and dermatoscope 2.5V	31479	Parker halogen ophthalmoscope					
	Xenon halogen ophthalmoscope bulbs 3.5 V	31428	Gima Xenon - halogen diagnostic sets - ophthalmoscope					
OTO-OPHTH	HALMO-DERMATO	SCOPE E	BULBS - OTHER COUNTRIES					
	Halogen Dermatoscope bulb 2.5 V	31188	Gima dermatoscope Compatible for products that use Heine Bulb #038					
	Xenon halogen otoscope bulbs 3.5 V	31427	Gima Xenon - halogen diagnostic sets - otoscope					

### HEINE MINI 3000® XHL AND LED™ OTO AND OPHTHALMOSCOPE



MINI 3000 F.O. XENON OTOSCOPES

- Powerful pocket otoscope in a unique compact design.
- Xenon halogen bulbs for bright illumination and accurate colour rendering.

- 20,000 on/off switch cycles guaranteed.
   distal Fiber Optic (F.O.) Illumination: Reflex-free illumination of tympanum and ear canal.

  - viewing window with 3X magnification and optimized
- casing surface for razor-sharp images and minimal reflection. Swivelling viewing window built into instrument.
- pneumatic testing of the tympanum mobility by using the insufflation port and an optional connector.
- attachment clip with integrated on/off switch.
- replaceable batteries: size AA or optional rechargeable battery (31693) with mini NT table charger (31692).\* - 2-piece handle and head. Easy to maintain, flexible.

### Compatible with other handles. MINI 3000 F.O. LEDHO OTOSCOPES

- All features of F.O. Xenon otoscopes with the addition of: - maintenance-free, no need to ever change the LED.
- LED thermal management for a consistent light output throughout the whole working life.

  High-performance-LED: bright and absolutely homogeneous illumination with excellent colour rendering colour temperature 4,000°K, colour rendering index >95, and >90 rendering index of the colour red.
- twice as bright as Xenon Halogen instruments.
- exclusive Battery Performance Indicator
- exclusive fade-out function reduces illumination intensity with battery level to let you know when to replace. - operation time up to 10 hours

MINI 3000 OTOSCOPES 2.5 V							
	BLA	ACK	BLUE				
	GIMA code	HEINE code	GIMA code	HEINE code			
Standard	31680	D-001.70.210	31681	D-001.70.210			
F.O. Xenon	31684	D-001.70.110	31685	D-001.70.110			
F.O. LED <sup>HQ</sup>	31676	D-008.70.110	31677	D-008.70.110			
MINI 300	00 OTOSCOPE	2.5 V - RECH/	ARGEABLE HA	ANDLE**			
F.O. Xenon	31682	D-001.70.301	-	-			
F.O. LED <sup>HQ</sup>	31683	D-008.70.301	-	-			
Above otoscopes a		x with 5 disposable		n and 5 Ø 2.5 mm			
	MINI 3000 O	TOSCOPE 2.5	V - hard case				
F.O. LED <sup>HQ</sup>	31678	D-885.20.021					
		speculum Ø 4 mm,	5 Ø 2.5 and 4 reus	able speculum			
31503 Dispenser of 250 pcs. 31516 Bax of 1,000 speculum							
code		BLE MINI EAR	SPECULUM*	Minimum order			

code	HEINE DISPOSABLE MINI EAR SPECULUM*	order
31501	HEINE dispenser for mini speculum - empty	-
31502	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	dispenser of 250
31503	HEINE disposable Allspec® speculum Ø 4 mm - grey	dispenser of 250
31515	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	box of 1000
31516	HEINE disposable Allspec® speculum Ø 4 mm - grey	box of 1000
	*Compatible with Heine Mini 2000/3000, K180, Beta 200, Beta	400

Modern pocket ophthalmoscope with fixation star aperture. Excellent optics and best colour rendering in minimum size. - XHL Xenon Halogen Technology. Concentrated bright light for perfect illumination, a brilliant image and accurate colour

- rendering.

   the HEINE optics produce crisp, clear images of the whole area under examination and minimize the reflections.
- 5 different apertures. A full-function instrument incl. fixation star.
- grev filter for light sensitive patients.
- range of lenses: 18 lenses from -20 D to +20 D.
- easy workflow, because ophthalmoscopy is possible without dilation of the pupils.
- attachment clip with integrated on/off switch.
- replaceable batteries. Size AA or optional rechargeable battery (31693) with mini NT table charger (31692).

### MINI 3000 LED<sup>HQ</sup> OPHTHALMOSCOPES

All features of Xenon ophthalmoscope with the addition of: - maintenance-free, no need to ever replace the LED.

- LED thermal management for a consistent light output throughout the whole working life.
- high-performance-LED: bright and absolutely homogeneous illumination with an excellent colour rendering - colour temperature 4,000°K, colour rendering index >95, and >90 rendering index of the colour red.
- exclusive battery performance indicator
   exclusive fade-out function reduces illumination intensity with battery level to let you know when to replace.
- operation time up to 10 hours.

MINI 3000 OPHTHALMOSCOPES 2.5 V							
	BLA	ACK	BLUE				
	GIMA	HEINE	GIMA	HEINE			
	code	code	code	code			
(enon	31686	D-001.71.120	31687	D 001.71.120			
.ED <sup>HQ</sup>	31688	D-008.71.120	-	-			
MINI 3000 OPHTHALMOSCOPES 2.5 V - RECHARGEABLE HANDLE**							
O. Xenon	31694	D-001.71.200	-	-			
O. LED <sup>HQ</sup>	31695	D-008.71.200	-	-			
MINI 3000 OTO-OPHTHALMO SET - hard case							
(enon Set	31689	D-873.11.021	-	-			
.ED <sup>™</sup> Set	31696	D-886.11.021	-	-			
Both set (Xenon or LED) include one F.O. otoscope head, one							

ophthalmoscope head, 2 handles, 4 reusable specula (Ø 2.4, 3, 4, 5 mm), 5 disposable specula Ø 4 mm and 5 Ø 2.5 mm in hard case.

NiMH rechargeable battery with bottom insert for Mini 3000 handles.



GIMA code	HEINE code	CHARGER AND ACCESSORIES
31691	D-000.80.101	MINI 3000 connector for pneumatic test
31692	X-001.99.484	HEINE MINI 3000 NT charger
31693	X-001.99.487 +	BATTERY + BASE
	X-001.99.488	

"Need Heine Mini 3000 NT charger (31692)

Large circle

Small circle Red free filter Blue filter

USB port (31572 only)

### SIGMA F.O. DIAGNOSTIC SETS

SIGMA otoscopes and ophthalmoscopes are high quality pocket diagnostic instruments designed for professional use in ENT and ophthalmoscopy. Light weight and manufactured from impact resistant re-enforced plastic.

Supplied in deluxe rigid plastic cases or pouch (31524)

with 14 disposable specula (7 with Ø 2.5 mm, 7 with Ø 4 mm). • 31524 SIGMA F.O. OTOSCOPE 2.5 V - pouch - black

- 31523 SIGMA F.O. OTOSCOPE 2.5 V pouch blue
- 31525 SIGMA F.O. OTOSCOPE 2.5 V case black • 31526 SIGMA F.O. LED OTOSCOPE 2.5 V - case - black
- 31518 SIGMA F.O. LED OTOSCOPE 2.5 V case blue

Manufactured with high quality materials and top-notch

workmanship ensures excellent reliability in every examination Battery life with Led bulb (31526) 6 time longer than with traditional bulb

- distal fibre optic illumination with super bright Xenon/Halogen light or LED light.
- swivel type window with 3X magnification lens for sharp images and minimal reflection - insufflation port for pneumatic testing of tympanic mobility.

  Connector port (code 31532) and insufflation bulb (code 31500) should be ordered separately.
- 31527 SIGMA F.O. OPHTHALMOSCOPE 2.5 V case black
- 31529 SIGMA LED OPHTHALMOSCOPE 2.5 V LED light 85.000 LUX bulb estimated life 50,000 hours - case - black

Top quality ophthalmoscope with 5 different apertures for almost all ophthalmic

examinations. High quality optics in mini format makes this instrument ideal for house calls and rounds.

- enhanced xenon/halogen super bright light

- 5 different apertures

Large spot: for normal fundoscopy Small spot: for reduced reflection with small pupils Semi circle: for reduced reflection with small pupils Fixation star: for determination of central or eccentric fixation, suitable for examining children

Red-free filter: for contrast-enhancement when assessing fine vascular disorders

- range of lenses from -20 D to +20 D

• 31533 SIGMA F.O. OTO-OPHTHALMOSCOPE SET 2.5 V - case with 1 handle - black

- 31528 SIGMA F.O. OTO-OPHTHALMOSCOPE DELUXE SET 2.5 V case with 2 handles black
- 31534 SIGMA F.O. LED OTO-OPHTHALMOSCOPE DELUXE SET 2.5 V case with 2 handles Oto-ophthalmo sets are supplied with oto and ophtalmo head, 1 handle (31533) or
- 2 handles (31528, 31534) and 14 disposable speculum (7x2.5 and 7x4 mm)

34485 OTOSCOPE BULB - xenon - halogen 2.5 V

31531 OPHTHALMOSCOPE BULB - xenon - halogen 2.5 V 31532 PNEUMATIC CONNECTOR PORT

• 31500 INSUFFLATION BULB





**LED** features

- 85.000 LUX

colour temperature: 5,000°K

 real colours definition bulb estimated life 50,000 hours

### HEINE BETA® 200 RETINOSCOPE

• 31745 HEINE BETA 200 RETINOSCOPE - slit - 2.5 V - C-034.10.118 With ParaStop® for finding the neutralization point (US pat. 5,859,687): precise, easy selection of a parallel beam

- dustproof: maintenance free

31527

31524

31525

DR FO LED

- single control for vergence and rotation; comfortable operation
- Integrated polarisation filter: eliminates stray light
- and internal reflexes for a brighter pupilling reflex - streak or spot retinoscope: simply by changing the bulb
- XHL (xenon halogen technology): bright, white light. Bright
- fundus reflex, easy recognition of neutralization point
- ergonomic shape: protects the examiner's orbit from stray light



### E-SCOPE®: RIESTER OTO-OPHTHALMOSCOPES



### LUXAMED AURIS LED OTOSCOPES - MADE IN GERMANY

• 31570 LUXAMED AURIS LED 2.5V OTOSCOPE - black • 31571 LUXAMED AURIS LED 2.5V OTOSCOPE - blue • 31572 LUXAMED AURIS LED 3.7V USB OTOSCOPE - black Innovative otoscopes that combine best handicraft production with selected materials with the most modern technology. Two-components handle (aluminium/fibre-glass reinforced) with electronic ON/OFF switch. Features: - LED-Ring illumination with 6 LEDs (concentric), no fibre

- optic, field of vision is not restricted, with the theoretical failure of a single LED, the functionality is not affected (patent DE202013104278U1) **LUXAMED®**
- dimmer
- automatic switchoff after 3 minutes
- approx. 100,000 hours life expectancy of LEDs

• 31561 E-SCOPE® OTOSCOPE - LED 3.7 V BULB

• 31562 E-SCOPE® OPHTHALMOSCOPE - XENON 2.5 V BULB

• 31817 RI-SCOPE® EAR SPECULUM Ø 2.5 mm - autoclavable

• 31819 RI-SCOPE® EAR SPECULUM Ø 4 mm - autoclavable

• 31563 E-SCOPE® OPHTHALMOSCOPE - LED 3.7 V BULB

- approx. 10,000 Lux intensity of illumination
- approx. 4,000 K colour temperature
- pivoting 3-fold magnifying glass with locking function insufflation port for pneumatic test

Supplied with 2xAAA alkaline batteries (31570/1) or lithium-ion rechargeable battery 3.7V (31572) 20 disposable ear funnels (10x2.5 mm and 10x4.0 mm) and manual (GB, IT, DE). See page 219-220 for compatible ear speculum.



Recharger with USB plug - 3 adapters (EU. UK. US)



31571

LED-Rina

Technology

### HEINE K100 HALOGEN OTOSCOPE HEINE K180 OTO-OPHTHALMO



• 31720 HEINE K 100 HALOGEN OTOSCOPE - 2.5 V - B-245.10.118 • 31740 HEINE K180 - F.O. OTO-OPHTHALMO SET - 2.5 V - A-279.10.118 Otoscope with BETA battery 2.5 V handle with rheostat, highimpact polycarbonate housing and 3 reusable specula (Ø 3.5, 4.5. 5.5) in nylon pouch. XHL (Xenon Halogen Technology), extremely bright, white light. Acrylic viewing window with 3X magnification, insufflation port for tympanic test.

• 31771 HEINE 037 OTOSCOPE BULB 2.5 V - spare - X-001.88.037 28 lenses from -35D to +40D supplied in pouch

Otoscope and ophthalmoscope K180 with BETA battery 2.5 V handle and a set of single use specula. Supplied in hard case. • 31782 HEINE 084 OPHTHALMO BULB 2.5 V - spare - X-001.88.084

• 31772 HEINE 077 OTOSCOPE BULB - spare - X-001.88.077

31741 HEINE K180 OPHTHALMOSCOPE - 2.5 V C-182.10.118



### HEINE BETA 200 F.O. OTOSCOPES



F.O. Otoscope with BETA battery 2.5V handle with rheostat.

spare bulb. Supplied in hard case. Solid all metal construction,

• 31726 HEINE BETA 200 F.O. OTOSCOPE - 3.5V Li-ion L - B-141.29.420

Same as code 31725 but with 3.5V rechargeable handle with

charging status display, Li-ion battery and charging station (34449).

a set of single use specula, a set of reusable specula and a

• 31772 HEINE 077 OTOSCOPE BULB - spare - X-001.88.077

a quality instrument with fibre optic illumination

• 31784 HEINE 078 OTOSCOPE BULB - X-002.88.078

Large, scratch-resistan 31728 glass viewing window with 3x magnification





• 31728 HEINE BETA 400 LED F.O. OTOSCOPE - B-143.24.420 Exclusive 4.2X magnification. LED in HQ with continuous brightness control.

All metal housing and scratch resistant glass lenses. Colour temperature: 3,500 K. Colour rendering index (CRI) >97. Exceptional depth of field, provides sharp spatial image. LED otoscope with rechargeable handle supplied with 4 reusable speculum, 5 of both All Spec disposable speculum 2.5 and 4 mm  $\emptyset$  in a case with NT4 table charger (34374).

### EINE BETA 200 AND 200S OPHTHALMOSCOPES



1 0 0 0 v 6 standard diaphragms; slit, fixation star with polar co-ordinates, cobalt blue filter, large spot, small spot, hemi spot

6 diaphragms with green filte

+ in 1 D steps 1 - 10 | 15 | 20 | 40 | D - in 1 D steps 1 - 10 | 15 | 20 | 25 | 35 | D

31730 HEINE BETA 200 HALOGEN OPHTHALMOSCOPE - 2.5 V - C-144.10.118

The unique aspherical optic system eliminates corneal and iris reflexes. The illuminated area of the retina remains fully visible even in case of small pupil (bright light). BETA 200 has 6 diaphragms with separately "green filter". It is recommended for small or expanded pupils; suitable for slit or fluorescent ophthalmoscopy as well as for fixation test. Range -35D to +40D. Supplied in hard case with replacement bulb.
• 31731 HEINE BETA 200 F.O. OPHTHALMOSCO-

PE - 3.5 V Li-ion - C-144.27.388

Same as 31730 but with USB rechargeable handle for mains socket and Li-ion batteries. • 31783 HEINE 070 OPHTHALMOSCOPE BULB 3.5 V - X-002.88.070

- 31735 HEINE BETA 200S OPHTHALMOSCOPE 2.5 V C-261.10.118 • 31781 HEINE 069 OPHTHALMO BULB - 2.5 V - spare - X-001.88.069 • 31737 HEINE BETA 200S LED OPHTHALMO - 3.5 V with USB
- rechargeable handle C-261.28.388 Superior aspherical optics and 74 single-diopter steps - optical system: corneal and iris reflexes are eliminated.
- A full view is guaranteed even with small pupils.
- XHL (Xenon Halogen Technology) or LED: bright, white light. - recessed, multi-coated viewing window:
- avoids stray light.
- optics mounted on precision metal chassis. ergonomic shape: instrument fits the orbita comfortably in any position.
- 7 apertures with separate red-free filter: - lens range: perfect focus even with high refractive errors.

- exact colour rendering



fixation star with polar co-ordinates, large spot, small spot, pinhole, slit,

With red-free filter: Cobalt blue filter, fixation star with polar coordinates. large spot, small spot.



### VISIO 2000 F.O., XENON OTO, OPHTHALMO, ENT SETS - 3.5 V

Professional diagnostic sets with fiber optic illumination system, Xenon light 3.5 V, rheostat to adjust the intensity of light. Powered by rechargeable Li-ion batteries.

All products are made of impact resistant re-inforced plastic and durable easy locking system for hospital long term use. Supplied in deluxe case, should be used with charging station 31542 and Li-ion rechargeable battery (31541). Only plug-in set (31537) as direct AC connection and need battery 31547.

• 31535 VISIO 2000 F.O. XENON OTOSCOPE - 3.5 V

• 31536 VISIO 2000 F.O. XENON OPHTHALMOSCOPE - 3.5 V

• 31537 VISIO 2000 F.O. XENON OTO-OPHTHALMOSCOPE PLUG-IN SET - 3.5 V - 2 pin plug

• 31538 VISIO 2000 F.O. XENON OTO-OPHTHALMOSCOPE - 3.5 V

• 31539 VISIO 2000 F.O. XENON DIAGNOSTIC SET - 3.5 V • 31428 OPHTHALMOSCOPE BULB - spare

• 31544 OTOSCOPE BULB - spare

• 31541 LI-ION RECHARGEABLE BATTERY

• 31547 LI-ION RECHARGEABLE BATTERY 3.5 V PLUG-IN HANDLE for 31537

• 31542 ZOOM **CHARGING STATION** Supplied with EU 2 pin, UK and US plug 31542

Swivel type window with 3X 6 apertures to magnification for sharp image. select from: and minimal reflection o spot aperture Small aperture Large aperture ixation aperture Red-free filter Distal FO illumination with supe bright xenon ligh Durable easy Enhanced Xenon locking systen super bright light 31541 31547 31535 31536



F.O. Xenon otoscope set 3.5 V FO otoscope head hattery handle with bayonet lock, 1 set of 5 reusable eartips (2.5, 3.5, 4.5, 5.5 & 9.0 mm), tube of 14 disposable eartips (2.5 & 4.0 mm), spare bulb in a rigid case

F.O. Xenon ophthalmoscope set 3.5 V F.O. ophthalmoscope head, battery handle with bayonet lock, spare bulb.

31537

F.O. Xenon oto/ophthalmo plug-in set 3 5 V

F.O. otoscope head, F.O. ophthalmoscope head, one battery handle with bayonet lock and plug-in, 1 set of 5 reusable eartins (2.5.3.5.4.5.5.8.9.0 mm) tube of 14 disposable eartips (2.5 & 4.0 mm), spare oto and ophthalmo bulbs, rechargeable Li-ion battery in a rigid case

F.O. Xenon oto/ophthalmo set 3.5 V EO otoscone head EO onhthalmoscone head, two battery handles with bayonet lock, nasal illuminator with F.O. light, 1 set of 5 reusable eartips (2.5, 3.5, 4.5, 5.5 & 9.0 mm), tube of 14 disposable eartips (2.5 & 4.0 mm), spare oto and ophthalmo bulbs in a rigid case.

F.O. Xenon ENT diagnostic set 3.5 V FO otoscope head FO onbthalmoscope head, battery handle with bayonet lock, nasal illuminator with F.O. light, curved illuminator with bulb, plain mirror 20.0 mm plastic tonque depressor 1 set of 5 reusable eartips (2.5, 3.5, 4.5, 5.5 & 9.0 mm) tube of 14 disposable eartips (2.5 & 4.0 mm), spare oto and ophthalmo bulbs

### GIMA VISIO 2000 WALL DIAGNOSTIC STATION - 3.5 V

### • 31545 GIMA WALL DIAGNOSTIC STATION - 3.5 V

Perfect solution for everyday clinical and hospital life. The unit has a centralized electrical supply, eliminating the need for conventional or rechargeable batteries. Wall station is equipped with two handles one with Visio 2000 otoscope Xenon light head and one with Visio 2000 ophthalmoscope Xenon light head. Main features:

- automatic ON/OFF switching of the handles, the instrument turns off automatically once the handle is placed in the cradle
- non-slip ergonomic handle design
- handle with a brightness control mechanism for light adjustment - spiral cable enables working at 3 metres

Power: 115-230 V, 50-60 Hz. Disposable ear speculum see page 220



### RI-FORMER® THE MODULAR DIAGNOSTIC STATION 3.5V



### RI-FORMER MODULAR DIAGNOSTIC STATION

The modular diagnostic station can be individually combined according to requirements and the room situation, it is variably extendable to the right and the left.

The basic ri-former® module is available with one handle and can be supplemented with up to 4 further handle modules. - 3.5V Xenon or LED illumination creates lighting conditions similar to daylight

- optimum electronic efficiency using an adjustable dimmer

- constant output voltage independent from the mains supply prolongs the service life of the lamps and guarantees optimum light intensity

- automatic switching on/off of handles when removing or replacing them in the handle unit saves energy and increases the service life of

- non-slip, ergonomically designed handles with rheostat: infinitely variable regulation of brightness as well as manual switching on/off possible on the handle

- spiral cord expandable up to 3 m

developed and manufactured in Germany.



GIMA code	MODULAR DIAGNOSTIC STATION - XENON
31800	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-standard (include 2 handle oto and ophthalmo head, ear specula dispenser, clock)
31805	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-large (include 31800 + sphygmomanometer) **available on request 120V - 50/60 Hz

	MODULAR DIAGNOSTIC STATION - LED
31801	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-standard (include 2 handle, LED oto and ophthalmo head, ear specula dispenser, clock
31806	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-large (include 31801 + sphygmomanometer)

	available off request 120v - 30/00 Fiz						
	RI-FORMER MODULES AND HEADS						
31809	Basic diagnostic station 1 handle 3.5 - 230V* 50/60 Hz						
31810	Extension module 1 handle						
31811	Ri-scope L2 otoscope head - Led 3.5V						
31812	Ri-scope L1 otoscope head - Xenon 3.5V						
31813	Ri-scope L1 ophthalmoscope head - Xenon 3.5V						
31814	Ri-scope retinoscope head - Xenon 3.5V						
31815	Ri-scope dermatoscope head - Led 3.5V						
31817	Ri-scope L1, L2 ear speculum Ø 2.5 mm** - autoclavable 134°C						
31819	Ri-scope L1, L2 ear speculum Ø 4 mm** - autoclavable 134°C						
31820	Ri-spec ear specula dispenser - specula not included						
31822	Sphygmomanometer with basket						
	31810 31811 31812 31813 31814 31815 31817 31819 31820						

Xenon ophthalmoscope L1, L2, L3 bulb 3.5V - spare

Ri-thermo N infrared thermometer with 40 covers

Xenon L1 otoscope bulb 3.5V - spare 'Available on request 120V - 50/60 Hz

Probe cover for 31823 - box of 100 - spare





31814

31823

31824

31825







LED illumination: bright, white light with a nearly unlimited lifetime! With its monochromatic white light (4,000° Kelvin) the lamp in the ri-scope®L provides cold light and true-colour. CRI > 90. Lamps with LED technology have a lifetime of at least 10,000 hours (compared to 20-30 hours with halogen and Xenon lamps) and are extremely energy-efficient.

Li-ion batteries - greatest power in the smallest space! Considerably higher charging capacity, longer lifetime, lightweight, these are the big advantages of Li-ions batteries; wich provide sustained high performance for up to 1200 charging cycles. LEDs powered by lithium batteries can burn for up to 50 hours.

### • 31830 RI-SCOPE L2 LED OTOSCOPE - 3,5 V

The newest generation ri-scope®L otoscopes with optical glass and reduced reflection combines excellent optical properties and unparalleled performance with the reliability and efficiency of LED/lithium-ion technology.

- optimal beaming and transmission of the light.
- bi-directional swivelling, sealing optical glass 3X

Suitable for pneumatic test (supplied without ball). (i) Riester - C handle runs Li-ion batteries, not included

Supplied in deluxe hard case with one spare lamp, 4 reusable ear specula and 3 disposable ear specula Spare ear speculum: use above 31817-31819 (autoclavable) or

31485 to 31499 (disposable) page 220.

### • 31832 RI-SCOPE L2 XENON OPHTHALMOSCOPE - 3,5 V

The enhanced basic model with separately engageable redfree, blue and polarization filters for each aperture.

- Diopter wheel with 29 corrective lenses Plus 1-10, 12, 15, 20, 40 Minus 1-10, 15, 20, 25, 30, 35

- Easy-to-operate aperture hand-wheel with semi-circle, small/ medium/large circle, fixation star, and slit medium/large Circle, Tixation Star, and Sits
  - Includes filter wheel engageable for all apertures with symbol
  display, red-free filter, blue filter and polarization filter

  • 31826 XENON L1/L2/L3 OPHTHALMOSCOPE BULB 3,5 V - spare
- 31834 RI-SCOPE L2 LED OTOSCOPE + L2 XENON
- **OPHTHALMOSCOPE 3.5 V C handle**
- 31841 "C" SIZE Li-ion BATTERY • 31840 RI-CHARGER L 230 V

Table recharge station (with wall holder) recharge 2 "C" handles with Li-ion batteries.




### **GIMA OTOSCOPES: PARKER LINE**



### PARKER OTOSCOPES

- reliable and indestructible high quality instrument
- suitable for everyday ear nose and throat examinations - easily adjustable 2.5 V vacuum light (made in Germany)
- quality 3 times magnifying lens available with Plug in and snap (bayonet locking) or knurled screw type otoscope heads
- ideal for pneumatic tympanic membrane tests, can also be used for rhinoscopic examinations
  - supplied with 3 autoclavable ear funnels in
- a colour coordinated zip bag.





**VETERINARY OTOSCOPES AND** 

(minimum 100 pcs.)

31440 Parker - black Screw Ø 2.5, 3.5, 4.5 mm 31441 Parker with rechargeable handle Bayonet Ø 2.5, 3.5, 4.5 mm 31442 Parker veterinary - black Screw Ø 4 5 7 mm 31449 Spare bulb 2.5 V for Parker otoscopes 31435-6-7,31440-1-2 31542 Charging station for 31441 34467 Rechargeable Li-ion battery 2.5 V / 2,200 mAh

Ophthalmoscope head

### PARKER DIAGNOSTIC SETS

### • 31471 PARKER DIAGNOSTIC SET

Lightweight, semi rigid nylon case with one Parker otoscope 2.5 V with rechargeable handle, 3 autoclavable ear speculum (Ø 2.5, 3.5 and 4.5 mm), 2 laryngeal mirrors (size 3 and 4), bent arm throat lamp, tongue spatula, adjustable nasal speculum.

• 31473 PARKER LARGE SET WITH OPHTHALMO Same as code 31471 with an ophthalmoscope head, support for single use tongue depressors

and 2 tubes of single use specula.

• 31446 VACUUM BULB FOR OPHTHALMOSCOPE

• 31449 VACUUM BULB FOR OTOSCOPE

• 32203 "C" ALKALINE BATTERIES - blister of 2 pcs 31471







LED OTOSCOPE - PEN LIGHT

### • 31300 COMBL SET

Dual function instrument features convertable diagnostic pen light and mini-otoscope with 3 different sizes of funnels or specula

White Led light. Packed in a gift box. Pupil gauge and dual slide rule printed on the penlight.

Supplied with batteries (2xAAA).

- 32200 "AAA" ALKALINE BATTERIES blister of 4 pcs
- 31345 REUSABLE EAR SPECULUM 2.0 mm bag of 25
- 31346 REUSABLE EAR SPECULUM 4.0 mm bag of 25



### XENON-HALOGEN OTO AND OPHTHALMOSCOPE SET



31475 XENON-HALOGEN PARKER OTOSCOPE

Same as PARKER Otoscope code 31440 but with halogen 2.5V bulb, and bayonet connection system. Supplied with 3 autoclavable ear funnels in a soft bag. Requires 2xC batteries (not included) or rechargeable battery.

• 31474 HALOGEN OPERATIVE PARKER OTOSCOPE

Same as 31475 but with operative head.
• 31476 HALOGEN PARKER OPHTHALMOSCOPE

2.5V halogen light for true tissue colour and consistent, long lasting illumination 24 colour coded lenses -25 to +40 dioptres for excellent resolution (green for +, red for -). Rubber eye brow rest to prevent scratching of eye-glasses. Illumination lens dial for clear identification of dioptre setting. Supplied in a semi-rigid

• 31477 HALOGEN OTO-OPHTHALMOSCOPE PARKER SET Diagnostic set including one handle, one halogen otoscope head and one halogen ophthalmoscope head, all in a plastic case.

• 31478 XENON-HALOGEN BULB FOR OTOSCOPE 2.5V 31479 XENON-HALOGEN BULB FOR OPHTHALMOSCOPE 2.5V

• 34467 RECHARGEABLE LI-ION BATTERY 2.5 V / 2,200 mAh

31542 CHARGING STATION

• 32203 "C" ALKALINE BATTERIES - blister of 2 pcs







nvlon bag with multilan-

guage box and manual

1, 2, 3, 4, 5, 6, 8, 10, 12, 15, 20, 40 1, 2, 3, 4, 5, 6, 8, 10, 15, 20, 25

### XENON-HALOGEN DIAGNOSTIC SETS IN RIGID CASES

• 31480 XENON-HALOGEN DIAGNOSTIC SET - 3.5 V

31475

 31482 XENON-HALOGEN OPERATIVE DIAGNOSTIC SET - 3.5 V Both xenon-halogen sets are supplied in plastic rigid case containing: one rechargeable handle, one otoscope head (operative for code 31482) one ophthalmoscope head, 3 autoclavable speculum Ø 2.5, 3.5, 4.5 mm, two laryngeal mirrors (size 3 and 4), adjustable nasal speculum, bent throat lamp, tongue spatula. Should be used with 31541 + 31542

• 31427 XENON-HALOGEN OTOSCOPE BULB 3.5V

• 31428 XENON-HALOGEN OPHTALMO BULB 3.5V



Insufflation

31542 CHARGING STATION - 100-240 V - 50/60 Hz

See details at page 327.

31541 RE-CHARGEABLE LI-ION BATTERY 3.5V







FIBRE OPTIC XENON-HALOGEN OTOSCOPES

31520 GIMALUX F.O. OTOSCOPE - black • 31521 GIMALUX F.O. OTOSCOPE - blue • 31522 GIMALUX F.O. OTOSCOPE - green

High professional plastic otoscopes with extra bright halogen

light provided by fibre optic system. Quality 3 times magnifying movable lens. Output for pneumatic membrane test. Supplied with 14

single use mini speculums (7 Ø 2.5 and 7 Ø 4 mm) in a colour coordinated nylon bag. For mini ear-

speculum see at page 220. All latex free.

• 34485 XENON-HALOGEN BULB 2.5V

Old model with chrome insufflation adapter need below bulb • 31478 XENON-HALOGEN BULB 2.5V for old models



### DISPOSABLE EAR-SPECULUM FOR "TRADITIONAL" OTOSCOPES

GIMA code	DISPOSABLE EAR - SPEC OTOSCOPES OF DIFFEREN		Colour		To be used with		Minimum order	
31313 31315 31316	Disposable ear-specului Disposable ear-specului Connector for 31313-31	m Ø 4 mm		Gowllands Riester (son Gowllands	(with connector 31316) ne models)		of 200 pcs. of 200 pcs.	
31504 31505	Disposable ear-speculus Disposable ear-speculus	ulum Ø 2.5 mm Heine Beta 100, K100 and Eurolight,				cs. (20 pack of 50) cs. (20 pack of 50)		
31506 31507	Disposable ear-specului Disposable ear-specului	um Ø 4 mm			dispense	dispenser of 250 pcs. dispenser of 250 pcs.		
31508 31509	Disposable ear-specului Disposable ear-specului	m Ø 4 mm			Welch Allyn: Pocket-pro; Pocket scope Series 200, 250		dispenser of 250 pcs. dispenser of 250 pcs.	
		Suitable for HEINE		Λ	Suitable for RIESTER	Suitable for WELCH-ALL	YN A	
31316		31504-3150	)5		494			
31313	31315				31506-	31508-		

### WELCH-ALLYN KLEENSPEC DISPOSABLE EAR SPECULUM

GIMA code	WELCH-ALLYN KLEENSPEC Disposable ear-speculum	Colour	To be used with	Minimum order	WelchAllyn
	KleenSpec ear-speculum Ø 3 mm KleenSpec ear-speculum Ø 4 mm		20202, 21600, 21700	box of 100 (4 packs of 25 pcs.) box of 100 (4 packs of 25 pcs.)	
	KleenSpec ear-speculum Ø 2.75 mm KleenSpec ear-speculum Ø 4.25 mm		Welch-Allyn, Macroview Riester Ri-scope L2, L3	box of 850 box of 850	

### ALKALINE, LITHIUM AND ZINC-AIR "ACOUSTIC" BATTERIES



32200

32201














FOR GENERAL USE APPLICATIONS

VARTA ALKALINE Blister Type HIGH ENERGY BATTERIES AAA 4 pcs. Varta ministilo H.E. - alkaline Varta stilo H.E. - alkaline AA 4 pcs. Varta half torch H.E. - alkaline C 2 pcs. 32204 Varta torch H.E. - alkaline D 2 pcs.

32203	Varia 9V n.c alkaline	90	i pc.
GIMA code	VARTA ENERGY ALKALINE BATTERIES - BULK	Туре	Box
32202	Varta Energy Stilo - alkaline	AA	24 pcs.

FOR ELECTRONIC **VARTA LITHIUM BATTERIES - BUTTON** code 32210 Varta 2016 - lithium button 1 pc. 32211 Varta 2025 - lithium button 1 pc. 32212 Varta 2032 - lithium button 1 pc. GIMA **RAYOVAC ZINC- AIR** Blister code "ACOUSTIC BATTERIES" - mercury free 32220 Rayovac 675 - zinc air - acoustic 6 pcs. Rayovac 13 - zinc air - acoustic 6 pcs. 32222 Rayovac 312 - zinc air - acoustic 6 pcs. 32223 Rayovac 10 - zinc air - acoustic 6 pcs.




### GIMA DISPOSABLE EAR-SPECULUM FOR MINI OTOSCOPES OF DIFFERENT BRANDS

	GIMA	GIMA DISPOSABLE SPECULUM FOR MINI OTOSCOPES - LATEX FREE		Compatibility	Minimum
ı	code			Direct fit Fit with connector 31493	order
	31485 31486 31487 31488 31491 31492 31495 31496 31497 31498 31499	Disposable Mini ear-speculum Ø 2.5 mm - grey Disposable Mini ear-speculum Ø 4 mm - grey Disposable Mini ear-speculum Ø 2.5 mm - black Disposable Mini ear-speculum Ø 4 mm - black Disposable Mini ear-speculum Ø 4 mm - blue Disposable Mini ear-speculum Ø 2.5 mm - blue Disposable Mini ear-speculum Ø 2.5 mm - green Disposable Mini ear-speculum Ø 2.5 mm - green	-	Gima 31520-22, 31525-26, 31535, 31545 Heine mini 2000, 3000, K180/Beta 200 Riester Ri-Mini, Ri-scope L1-L2, E-scope, Pen-scope Kawe (Picolight, Combilight F030, Eurolight F030) Holtex Colson Luxamed	
п					

CONNECTORS FOR MINI EAR SPECULUM To be used with GIMA codes 31493 Connector to GIMA Parker otoscope for Mini ear-speculum ALLIGATOR connector (supplied with 100 ear speculum) 31435, 31436, 31437, 31440, 31441, 31442, 31471, 31473, 31475, 31477 31435, 31436, 31437, 31440, 31441, 31442, 31471, 31473, 31475, 31477 Alligator pediatric Includes 500 ear speculum







### EINE DISPOSABLE MINI EAR-SPECULUM 31501 Wall dispenser of mini speculum

	emp	oty
GIMA code	HEINE DISPOSABLE MINI EAR SPECULUM*	Minimum order
31501	HEINE dispenser for mini speculum - empty	
31502	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	dispenser of 250
31503	HEINE disposable Allspec® speculum Ø 4 mm - grey	dispenser of 250
31515	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	box of 1,000
31516	HEINE disposable Allspec® speculum Ø 4 mm - grey	box of 1,000

Compatible with Heine Mini 2000/3000 K180. Beta 200

### RIESTER AUTOCLAVABLE MINI EAR-SPECULUM



### RELISABLE CANNILILAS AND FAR SPECILLUM


GIMA code	AUTOCLAVAI OTOS	SLE SPECUL COPES - LA			Colour		To be used	with GIMA	A code		Also compatible with	Minimum order
31447 31448 31451 31453 31500	Kit 3 autoclavable Kit 3 autoclavabl Kit of 5 autoclavab Kit of 3 metal ca metal specula (Ø Pneumatic bulb f	e speculum le speculum Ø nnulas (Ø 4, 7.5 and 9.4	Ø 2.5, 3.5 ) 2.5, 3.5, 4 5, 6 mm) mm)	, 4.5 mm .5, 5.5, 9 mm		31435-37, 3 31435-37, 3 31435-37, 3	31440-42, 3147 31440-42, 3147 31440-42, 3147 31440-42, 3147 37/40/42/71/73	, 31473, 3 , 31473, 3 , 31473, 3	1475, 3147 1475, 3147 1475, 3147	7,31480 7,31480 7,31480	Heine, Kawe, Riester Heine, Kawe, Riester Heine, Kawe, Riester Heine, Kawe, Riester Heine, Kawe, Riester	One kit One kit One kit
made froi smooth a	lavable ear speculum 314 m resilient thermoplast nd shiny surface ensur payonet lock for positiv	tic material e easy cleaning	31447			<b>⊚ G</b>	IWA			openi instru	ted models with 60 mm ng and round edges, id mentation, atraumatic	leal for insertion
fit to otosc - autoclava	ope ble at 134°C 4.0 mm	5.0 mm	7.0 mm	3	31448		2.5 m	31451	n	31	7.5 mm 1 6.0 mi	9.4 mm
La	atex bulb			2.5 mm	3.5 mm	4.5 mm	4.5 mm	A	3.5 mm	4.0 mm		1
A	31500						A		A	A		
Length 30 cm	一件	<b>(</b>	1					9 mm	-		inner surface to reduce of reflection	2

### OTOSCILLO® ELECTRICAL IRRIGATION DEVICE

• 25815 OTOSCILLO®

### 25800 PROFESSIONAL OTOSCILLO®

Otoscillo® is designed for automated ear rinsing both in hospitals and during private consultations. Innovative, compact, efficient and rapid, the Otoscillo® combines the most sophisticated operating qualities with the best security guarantees, all in a single device Anywhere, anytime



• 25816 SPARE SET (2 reusable tips + disk) for 25815

• 25817 SPARE HANDLE + TUBE

• 25814 DISPOSABLE TIPS SET (100 disposable tips, 1 disk, connector) for 25800 and 25815

25818 DISPOSABLE TIPS for 25800 - box of 100





nozzle, 1 short nozzle, 1 splash quard) carrying

### GLASS-METAL, ALL-METAL AND SINGLE-USE EAR SYRINGES



### **GLASS-METAL JANET RECORD SYRINGES**

High quality, reliable and accurate glass-metal syringes. Janet Record come complete with 2 cannulas, one conical, one oval. Individually packed in cardboard box. Made in Germany.

	,
GIMA code	GLASS-METAL SYRINGES COMPLETE WITH 2 CANNULAS
25801 25802 25803 25804 25805	Janet Record 50 cc - 13 x Ø 3.5 cm Janet Record 100 cc - 14 x Ø 4.7 cm Janet Record 200 cc Spare cannula for Janet Record (conical shape) Spare cannula for Janet Record (olive shape)


### ALL-METAL SCHIMMELBUSCH SYRINGES

High quality, reliable and accurate syringes. Schimmelbusch come complete with 3 cannulas and ear bowl. Individually packed in cardboard box. Made in Germany.

code	COMPLETE WITH 3 CANNULAS AND EAR BOWL
25806	Schimmelbusch 50 cc
25807	Schimmelbusch 100 cc
25808	Schimmelbusch 200 cc
25809	Spare cannula for Schimmelbusch (conical shape)
25812	Spare cannula for Schimmelbusch (olive shape) small
25813	Spare cannula for Schimmelbusch (olive shape) large

ALL-METAL SYRINGES

### HIGH CAPACITY POLYPROPYLENE SYRINGES



HIGH CAPACITY POLYPROPYLENE SYRINGES - sterile Sterile, single use, latex free syringes for ear and other purposes. Box in GB, FR, IT, ES, DE, PT, GR, RO, RU, YU, SA. Medical Device class IIa

GIMA code	HIGH CAPACITY, POLYPROPYLENE SYRINGES STERILE - CATHETER CONE	Minimum order
23820	Syringe 60 ml	box of 20
23821	Syringe 100 ml	box of 25


### OTOCLEAR® EAR IRRIGATION SYSTEM



• 25858 OTOCLEAR EAR SPRAY WASH

- manual, intermittent lavage
- delivers greater volume compared to syringes or other manual devices
- efficient design allows for two handed procedure

### • 25861 OTOCLEAR EAR IRRIGATION TIPS single use - box of 40 - spare



 25862 EAR IRRIGATION BASINS box of 3 - spare



to the soft "gentle touch" design water temperature



### LOOP-SPOON EAR CURETTES

• 31470 GIMA EAR CURETTES - box of 10 pcs

25858




Spoon side

### LIGHTED EAR CURETTES

• 31450 KIT MIXED LIGHTED CURETTES Kit is composed by 50 lighted curettes

(8 FlexLoop and 7 of each of below other





InfantScoop<sup>6</sup>

WaveCurette™









Lighted ear curette 3 mm tip with LED illuminator

Ear curette tip has a 90° range of motion. It articulates to assist in removal of cerume from the ear canal

with LED illuminator

• 31465 KIT INFANTSCOOP

• 31466 KIT ANGLELOOP 31468 KIT VERSALOOP

31461 KIT MICROLOOP

• 31463 KIT FLEXLOOP

All kits are composed by 50 lighted curettes + LED light source + magnification lens

era phone to see

• 31458 LIGHTED FORCEPS - box of 10 + magnification lens + LED illuminator

• 31459 LIGHTED ARTICULATING CURETTES - box of 25 + magnification lens + LED light source



INFANTSCOOP:









scoop works better 4 mm wide tip  $\epsilon$ 

MICROLOOP:

added strength


8 mm wide tip

For compact cerumen

Tip can be angled for

More rigid construction

Rounded tip for comfort



• 31464 INFANTSCOOP - light blue - box of 50 pcs • 31460 MICROLOOP - green - box of 50 pcs

• 31467 CERASPOON - yellow - box of 50 pcs

Our four styles of curettes give you the most effective, economical and safe way to remove cerumen - whatever the size of ear or consistency of cerumen.

Patient comfort: Metal curettes are cold, hard and sharp. BIONIX ear curettes with rounded plastic tips reduce trauma and risk of laceration. Latex free.

Effectiveness: Ear curettes can duplicate the effectiveness of

metal curettes in almost any situation and their polypropylene composition makes them virtually unbreakable

Disposability: Ear curettes don't require expensive and time-consuming sterilization and eliminate the risk of cross-contamination.



WOOD TONGUE DEPRESSORS



Quality tongue depressors manufactured with selected high quality smooth birch wood. Edges accurately finished. 150x18x1.6 mm. Individually packed in a paper envelope and sterilized.

GIMA code	WOOD TONGUE DEPRESSOR - STERILE
25511	Tongue depressor - box of 50
25512	Tongue depressor - box of 2,000
	(40 boxes of 50 pcs)

Wooden medical tongue depressors made of quality birch wood. Edges accurately finished. Size: 150x18x1.6 mm Made in PRC.

IMA ode	NON-STERILE
	Tongue depressor - box of 100 Tongue depressor - box of 5,000 (50 boxes of 100 pcs)

### THROAT SCOPE®



### PLASTIC TONGUE DEPRESSORS



• 25505 PLASTIC COLOURED TONGUE **DEPRESSORS** Plastic tongue depressor

animal shaped with bright colour. Each tongue depressor is individually packed in transparent pouch. Packed in box of 50 pieces. 25516 Tongue depressor - box of 1,800 (20 boxes of 90 pcs)

peel-ope	peel-open pack (ethylene oxide).					
GIMA code	PLASTIC TONGUE D					
	NON-STERILE	CE				
25513	Tongue depressor -	box of 100				
	STERILE	CE 0120				
25515	Tongue depressor -	box of 90				

€ 0476

### 1 handle + 3 blades - blister

Throat Scope is an illuminated tongue depressor that allows the clinician a one handed operation for oral cavity examination. The light is guided by the blade to illuminate the mouth for a quick examination by the clinician. Light is automátically activated when you insert single use blade into the handle.

• 25499 THROAT SCOPE® DISPOSABLE

BLADES - box of 100 - non sterile



### STERILE ENT KITS

 31456 STERILE ENT KIT A - box of 25 pcs. Kit includes one plastic nasal speculum, one plastic

tongue depressor and two (adult and pediatric size) plastic ear funnels in single sealed pouch.



### • 31457 STERILE ENT KIT B - box of 10 pcs.

Kit includes one plastic nasal speculum, one plastic tonque depressor, two (adult and pediatric size) plastic ear funnels, two plastic laryngeal mirrors, one plastic forceps, six cotton tip applicators, one napkin, all packed in a sterile plastic tray.



The use of stainless steel speculum can be a chilling experience for the patient. Now you can combine patient comfort with effective treatment. Smooth, warm tips make disposable Nasal Speculum more comfortable and less alarming to the patient.

• 31469 DISPOSABLE NASAL SPECULUM - box of 48 Innovative plastic, disposable nasal speculum with handle: allows superior view of nasal cavity. Helps extract foreign objects from nasal cavity. Facilitates packaging of cauterizing of bleeding ( € 0123 noses. Latex free.



223

### WELCH ALLYN HALOGEN PROFESSIONAL PENLIGHT

• 25622 W.A. HALOGEN PENLIGHT with 2 x AAA batteries Bright white halogen light. Durable solid brass construction.

• 25618 BULB for W.A. PENLIGHT - spare

Welch Allyn\*



Germany

blue

### TOP OUALITY BULB OR LED PENLIGHTS - MADE IN GERMANY

Professional penlights, also suitable for diagnostic, with bulb or Argenta and Elegance made of anodized aluminium, Nova in topwhite LED with quick clip shifter mechanism or push button (25634). quality ABS plastic housing. Supplied with 2x1.5V AAA batteries.



### **BULB OR LED TORCHES PENLIGHTS**

metal



### DELTA PENLIGHTS WITH TONGUE DEPRESSOR HOLDER



### **NEUROLOGICAL REFLEX PERCUSSORS - LATEX FREE**



GIMA code	PERCUSSORS	Colour	Handle	Pin	Brush	Weight	Length	
31270 31251 31252 31271 31254 31255 31256 31257 31258 31260 31272	Buck Gima 2000 Buck Classic Buck colour-yellow Dejerine Gima 2000 Dejerine Colour Babinsky - Ø 4.5 cm Queens - Ø 5 cm Troemner Pinwheel Babinsky-Gima 2000	green silver yellow blue silver red silver silver silver silver green	plastic/stainless steel chromed brass brass colour coated plastic/stainless steel stainless steel brass colour coated chrome plated flexible plastic stainless steel chrome plated plastic	yes yes yes yes yes yes no no no	yes yes yes yes yes no no no no	85 g 90 g 90g 110 g 140 g 125 g 170 g 100 g 200 g 50 g 80 g	18 cm 18 cm 18 cm 21 cm 21 cm 21 cm 24 cm 33 cm 23 cm 18 cm 24 cm	
31273	Taylor Gima	red	plastic/stainless steel	no	yes	70 g	20 cm	31258

# 31273 31257

### NEUROLOGICAL KIT



MONOFILAMENT - SENSORY EVALUATOR

• 31265 NEUROLOGICAL KIT - 3 hammers This kit includes 3 metal hammers in a foam box: Taylor hammer, Buck hammer and Babinsky hammer.

Diagnostic tool for detecting

Plastic retractable monofilament with 3 spare

monofilaments. Evaluates both diminishing

status. Monofilament is calibrated at 10 g.

• 31281 KIT OF 3 MONOFILAMENTS - spare

Size: 13x2.5 cm + 4 cm monofilament

31282 MONOFILAMENT TOOL -

### THERMO FEEL

### • 31278 THERMO FEEL

Useful tool for diagnosis of neuropathy in diabetes patients. Both sides (one stainless steel and one plastic) are alternatively put in contact with foot skin of the patient. Patient perception of cool or warm allows a first diagnosis of diabetes.

### TWO POINTS DISCRIMINATOR

### • 31279 TWO POINTS DISCRIMINATOR

Plastic (ABS) caliper with scale printed on aluminium plate. Two point discrimination is the ability to discern that two nearby objects touching the skin are truly two distinct points, not one.

It is often tested with two sharp points during a neurological examination



and reflects how finely innervated an area of skin is. Reliable and widely used technique for determining tactile gnosis.

### TRIGONAL MONOFILAMENT

• 31277 TRIGONAL MONOFILAMENT Trigonal shape diabetic monofilament with 3 different monofilament diameters: 0.4. 0.5 and 0.7 mm



31282

sensory evaluator

31246

### GERMAN-MADE DIAPASONS - TUNING FORKS



### ENT TUNING FORKS:

All made in Germany, with age-long craftsmanship experience, All made in a special alloy and supplied with base. in special alloy that ensures maximum sound precision

GIMA code	ENT TUNING FORKS
31232 31233 31234	Tuning fork 128 Hz* - with weight Tuning fork 256 Hz* - with weight Tuning fork 512 Hz Tuning fork 1024 Hz Tuning fork 2048 Hz Tuning fork 4096 Hz Set of 5 tuning forks in a stylish lined case (contains 128 Hz*, 256 Hz*, 512 Hz, 1024 Hz, 2048 Hz). Tuning forks with asterisk * are supplied with weight

31245 31247 ENT/NEUROLOGY TUNING FORKS

GIMA code	ENT/NEUROLOGY TUNING FORKS
	Tuning fork a1-440 Hz - ENT - 90 g
31246	Tuning fork - LUCAE - 85 g adjustable from c128 to h240 with foot
31247	Tuning fork C64, c128 - RYDEL SEIFFER detachable slider either C64 or c128 - 130 g
31249	Hammer neurotone 5 in a lined case

Neurotone hammer: set of 5 components for a complete neurological examination: percussion hammer + tuning fork 256 Hz with weight + pin + brush. All fitted in a stylish case

### **ALUMINIUM ALLOY DIAPASONS - TUNING FORKS**

• 31225 ALUMINIUM TUNING FORK 128 Hz • 31226 ALUMINIUM TUNING FORK 128 Hz - with foot Made of finest aluminium alloy and precisely shaped to meet highest requisites (standards in medical field. 31226 - 22 cm long 31225 - 20.4 cm long

### NYSTAGMUS SPECTACLES - DR. FRENZEL - MADE IN GERMANY

• 31204 NYSTAGMUS SPECTACLES - DR. FRENZEL - black Easy to use in the search of spontaneous or provoked nystagmus. Fixed, biconvex lens + 18.0 diopters. Nystagmus spectacles should be connected only with < 4.2 V transformer as per safety norms 93/42/EEC.

See code 31203 or 31214 31214 BATTERY handle for 31204

Offers mobility during examination 31214 Needs 3x1.5 V CLR14 batteries (not included)

• 31203 PLUG-IN TRANSFORMER for 31204

- 31206 BATTERY NYSTAGMUS SPECTACLES DR. FRENZEL black This model allows wireless working and is provided with power through the adjustable battery placed above the spectacle. Requires three 1.5 Volt batteries, size C LR14/AM-2 (baby cells). Illumination can be adjusted through a turn of the switch.
- 31208 NYSTAGMUS BULB spare for 31204, 31206
- 4 Volt 0.230 Ampere, 1 Watt threading Ø 3.5x0.35 mm
- 31207 LED BATTERY NYSTAGMUS SPECTACLES white
- Same as 31206 with LED and inner function that makes easier watching the rashes within a particular time period (30, 60, 90 seconds).
- 31209 LED POWER SUPPLY NYSTAGMUS SPECTACLES white Same as 31204 with LED and rechargeable power supply.




### USB VIDEONYSTAGMOSCOPE SYSTEMS

• 31213 VIDEO-NYSTAGMOSCOPE - USB - mask with Ir camera and USB cable Facilitate to view and register the Nystagmus through standard vestibular tests (both position and instrumental proof).

This system allows to view on the monitor or PC/Notebook images of patient eyes during tests and to make Visual Suppression Test (VST) through a green LED light inside the mask to allow fixation. Innovative technology allows to get quality images. Power 12V DC.





		31302 31303 31304	1 .3.130	)/. m 8	3130	0 - 11	31309	1310
	GIMA code			Working distance		GIMA	LOCAMINES VILLA ACUTY DART	
	31301	SNELLEN eye chart with red/green bar visual acuity test	10 feet	3 m	23x35.5	12	Transaction (	TOW.
	31302	TUMBLING "E" colour vision chart-visual acuity screen	20 feet	6.1 m	23x35.5	100.00	COHZV	***
	31303	SNELLEN eye chart for visual acuity and colour vision test	20 feet	6.1 m	23x35.5	44.00	SZNDC	
		SLOAN colour bar visual acuity chart	20 feet	6.1 m	23x35.5		VKCNR	++ +
	31307	TUMBLING "E" eye chart	20 feet	6.1 m	28x56		KCRHN	
	31308	TRADITIONAL SNELLEN eye chart	20 feet	6.1 m	28x56	00.00	ZKDVC	00 PW 01
	31309	MIXED DECIMAL chart	10 feet	3 m	28x56		# M G G N	
	31310	EWING illiterate test chart	20 feet	6.1 m	28x56	##_		
			16 inches	40 cm	18x23	##-	31311	_##
*	*Polypropylene natural white sheet, approx. thickness 0.8 to 1.0 mm							

LEA SYMBOLS AND NUMBERS VISION CARDS AND CHARTS



This test measures near visual acuity with proportionally spaced (logMAR) lines on the front and lines with 25% and 50% spacing on the back. Response key printed on test card. Includes training cards and instructions.

Card measures 20.3x25.4 cm (8x10").

• 31323 LEA SYMBOLS 15-LINE DISTANT CHART - 3 m (10 feet) This test is designed for vision screening at schools and assessment of vision of children with special needs beginning with age of 3 years. Has a hole for hanging the chart on the wall. Includes response key, training cards, and instructions. 43x53.4 cm (17x21"). Folds to 43x26.7 (17x10.5").

• 31324 LEA NUMBERS NEAR VISION CARD - 40 cm (16 inches) Designed to measure visual acuity with a standard line test and with three tighter spaced tests; 50%, 25%, and 12.5%, which often reveal difficulties in seeing tightly crowded details. Card measures 20.3x25.4 cm (8x10")

• 31325 LEA NUMBERS 15-LINE DISTANT CHART - 3 m (10 feet) This test is designed for vision screening at schools and assessment of vision of children with special needs beginning with age of 5 years. Has hole for hanging on the wall.

31274

31276

45.7x50.8 cm (18x20"). Folds to 45.7x25.4 (18x10").

LOW CONTRAST CHARTS




 31317 CONTRAST SENSITIVITY CARD - NEAR VISION 40 cm size 40x34 cm


 31318 CONTRAST SENSITIVITY CHART - FROM A DISTANCE 3 m size 77x61 cm

It checks for the ability to distinguish light and dark 170x200x3 mm vision problems. Also useful • 31276 FUN FROSTED OCCLUDER GLASSES

OCCLUDERS 154 x Ø 47 m Multiple 31275 • 31275 EYE OCCLUDER · (contrast). It can detect • 31274 OCCLUDER - 154 x Ø 47 mm

to reveal in time regression Set of two tiger fun frosted glasses to be or progression of the cataract used as occluder during children examinations disease. one to occlude each eye.





### **OPTOMETRIC PENCILS**

• 31319 OPTOMETRIC PENCILS - set of 2 pcs Set of two wooden puppets (red and white) used to capture attention during vision evaluation in young non-verbal children. Can also be used for test of convergence.

31295

### ISHIHARA COLOUR TEST

### ISHIHARA Colour TEST

These series of plates are designed to provide a test which gives a quick and accurate assessment of colour vision deficiency of congenital origin. This is the most common

form of colour vision disorders. Most cases of congenital colour vision deficiency are characterized by a red-green deficiency which may be of two types: a protan type which may be absolute (protanapia) or partial (protanomalia), and a deutan type which may be absolute (deuteranopia) or partial




31291 Book of 24 plates

31292 Book of 38 plates

### STEREOPSIS TESTS

• 31283 FLY STEREO ACUITY TEST

• 31284 BUTTERFLY STEREO ACUITY TEST Designed to rapidly test for amblyopia and strabismus using gross to fine stereopsis (4800 to 20 sec of arc): - graded circle test from 400 sec now down to 20 sec



- includes pair of standard polarised

• 31285 RANDOM DOT STEREO ACUITY TEST Designed to rapidly test for amblyopia and strabismus in early and non-readers and non-verbal children and adults

 expanded random dot lea test (500. 250, 125, 63 sec of arc)

- graded circle test now down to 12.5 sec

- answer key on back cover

- includes pair of standard polarised



### STEREOPTIC TEST

### • 31293 STEREOPTIC TEST

This test is performed at a distance of 30-40 cm and allows evaluation of the cooperation between the two eyes to form a single image to the brain from the two image provided separately by each of the two eyes.

It can be used for children from the age of one year and adults if you suspect strabismus, amblyopia or visual reduction of one



### GIMA COLOUR TEST

• 31287 GIMA ADULT COLOUR TEST - 15 plates

• 31286 GIMA PEDIATRIC COLOUR TEST - 10 plates Single plates packed in a practical aluminium box.

### WORTH LED LIGHT TEST

• 31289 WORTH LED LIGHT TEST - with red/green glasses The Worth 4 dot test, is a clinical test for suppression of either the right or left eye. Suppression occurs during binocular vision, when the brain does not process the information received from either of the eyes. This is a common adaptation to strabismus, amblyopia, and

aniseikonia. Battery not included, glasses included. 31294

### LANG STEREO • 31294 LANG STEREOTEST I • 31295 LANG STEREOTEST II


Stereotest I was created to simplify stereopsis screening in children. It is based on two principles: on random dots and on cylinder gratings. Stereotest II is a further development and helps the assessment of binocular vision.



31297 • 31297 LANG FIXATION CUBE - whi 31298

• 31298 LANG FIXATION CUBE - red

### SCHIÖTZ TONOMETER



• 31220 SCHIÖTZ TONOMETER - straight scale

• 31222 SCHIÖTZ TONOMETER - inclined scale

A masterpiece of precision mechanism, measures intraocular pressure according to Prof. Schiötz standards.

Vital parts are made of stainless steel. High quality agate bearing for extremely long service life

Set  $\tilde{3}$  weights included (5.5-7.5-10 a). Scale specification 5. In black deluxe case with velvet-look inserts.

Perfect reading of the scale with red pointer, Made in Germany



31220 straight



31222 inclined

228


### TRAD STETHOSCOPES - GOOD VALUE FOR MONEY



TRAD STETHOSCOPES: adult, pediatric Traditional aluminium stethoscopes. lightweight and reliable. Chestpiece diaphragm Ø 43.5 mm (Ø 35 for pediatric model), bell Ø 30 mm (Ø 26.5 for pediatric model) external sizes.

Brass binaural, non chill ring. Tubina: length 62 cm, int, Ø 4 mm, ext. Ø 8 mm.

Supplied in cardboard box. Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.



GIMA code a Code and a
32559 TRAD single head - pediatric - light blue 32555 TRAD double head - pediatric - black 32560 TRAD single head - black 32561 TRAD single head - red
32559 TRAD single head - pediatric - light blue 32555 TRAD double head - pediatric - black 32560 TRAD single head - black 32561 TRAD single head - red
32555 TRAD double head - pediatric - black 32560 TRAD single head - black 32561 TRAD single head - red
32560 TRAD single head - black 32561 TRAD single head - red
32561 TRAD single head - red
32562 TRAD single head - blue
32563 TRAD single head - yellow
32564 TRAD single head - purple
32558 TRAD single head - dark green
32565 TRAD double head - black
32566 TRAD double head - red
32567 TRAD double head - blue
32568 TRAD double head - dark green
32678 Diaphgram Ø 44 mm - spare

### COVERS FOR STETHO

GIMA COVERS FOR STETHOSCOPES*				
32653 Pig cover for stethoscopes				
32654 Dragon cover for stethoscopes				
32652	Cow cover for stethoscopes	0.0		



### SPARF PARTS AND ACCESSORIES FOR STETHOSCOPES

اد 🔔	TAIL TAILTS AND ACCES.			
GIMA code	QUALITY "Y" TUBING	Minimum order		
32620	"Y" tubing mixed colours	box of 20		
32621	"Y" tubing - black	box of 20		
32622	"Y" tubing - green	box of 20		
32623	"Y" tubing - blue	box of 20	ı	
32624	"Y" tubing - red	box of 20	h	
32625	"Y" tubing - orange	box of 20	B	
32626	"Y" tubing - light blue	box of 20	1	
32627	"Y" tubing - yellow	box of 20		
32628	"Y" tubing - purple	box of 20		
32629				
32645	"Y" tubing - other colours on request*	box of 20		
*Over 20 col	ours available: frosted green/lilac/blue/mel/pink, lavender, teal, l	ice blue, grey,	Г	
	BINAURAL - DIAPHRAGM - HEADS		П	
32655	One head chest piece - black ring	10 pcs.	П	
32656				
32665				
32666	BERTA binaural - fixed	1	П	
32678				
	EARTIPS AND ADAPTORS			
32659	Standard eartips - rigid - universal	10 pieces	П	
32663	Mushroom eartips - universal	10 pieces	Ш	
32664	Rigid eartips screw-type - for Classic, Wan, Yton, Duca, Regalite	10 pieces	1	
32660				







### WAN ADULT STETHOSCOPES

Features a chrome-plated zinc-alloy chestpiece, a screw-on plastic retaining ring, outer spring binaural and colour matched moulded PVC tubing with non-chill ring. Assure optimum acoustic performances. Chestpiece: Ø 45 mm, bell Ø 30 mm.

Tubing: length 63 cm, int. Ø 4.2 mm, ext. Ø 8 mm. Supplied in a cardboard box.

Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.

GIMA code	WAN STETHOSCOPES - LATEX FREE			
32569	69 WAN single head adult - black			
32570	WAN single head adult - blue			
32571	WAN single head adult - burgundy			
32572	WAN single head adult - orange			
32574	WAN double head adult - black			
32575	WAN double head adult - blue			
32576	WAN double head adult - burgundy			
32577	WAN double head adult - orange			
32678	Diaphgram Ø 44 mm - spare			

### WAN STETHOSCOPES - ADULT PEDIATRIC-NEONATAL STETHOSCOPES



### WAN PEDIATRIC AND NEONATAL STETHOSCOPES:

Features a chrome-plated zinc-alloy chestpiece, a screwon plastic retaining ring, outer spring binaural and colour matched moulded PVC tubing with non-chill ring. Assure optimum acustic performances.

Chestpiece: Ø 35 mm, bell Ø 30 mm, (pediatric) or Ø 22 mm, bell Ø 19 mm (neonatal). Tubing length: 63 cm. Supplied in a cardboard box. Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.

Same as standard with inner spring binaural, superior tubing quality and 2 pair of soft colour coordinated ear tips in different size.

GIMA code	WAN STETHOSCOPES - LATEX FREE			
32508	WAN double head neonatal - red			
32509	WAN double head neonatal - grey			
32513	WAN double head pediatric - light-blue			
32515	WAN double head pediatric - red			
	WAN PLUS double head pediatric - pink			
32506	WAN PLUS double head pediatric - black			

### DESIGN STETHOSCOPES



• 32527 DESIGN STETHO - transparent blue • 32528 DESIGN STETHO - transparent purple High quality single head stethoscope with fashionable design diaphragm and "Superflex TM" binaural. Provides high acoustic performances thanks to its quality components. Head and tube are in

transparent coordinated

colour.



### YTON STETHOSCOPES



### YTON STETHOSCOPES:

WAN PLUS:

Chestpiece Ø 45 mm, bell Ø 30 mm (for double head), with colour coordinated plastic retaining ring. "Duracote" finished. Supplied in cardboard box.

Manual and box in 11 languages: GB, FR, IT, DE, ES, PT. GR. PL. SE. HU. Arabic.

	GIMA code	YTON STETHOSCOPES - LATEX FREE
	32514	Yton single head - green teal colour
	32530	Yton double head - green teal colour

### JOTARAP STETHOSCOPE: DOUBLE-HEAD, DOUBLE TUBE



Gima Sprague Rappaport type double-head, double-tube, latex free stethoscope at the price of a standard stethoscope. 5 in 1, five way convertible type stethoscope

This convertible stetho, zinc alloy treaded with chrome plated chestpiece drum fitting with different sized chestpieces bells, provides versatile acoustics for infants and adults for the detection of a wide range of heart and lung sounds.

GIMA code	JOTARAP STETHOSCOPE
32579	JOTARAP - purple
32580	JOTARAP - black
32581	JOTARAP - blue
32582	JOTARAP - neon orange
32583	JOTARAP - green
32584	JOTARAP - neon yellow
32585	JOTARAP - light blue
32586	JOTARAP - fuchsia
32587	JOTARAP - transparent pink
32590	ACCESSORY KIT - spare

Chestpiece with small and large diaphragm. Double tubing for individual sound transmission

Two separate 56 cm (22") thick latex free wall tubing provide individual sound transmission from chestpiece to both sides of the ear. Complete in cardboard box with accessory kit (32590)

It is supplied with an accessory pouch containing:

Small diaphragm - Ø 25 mm

3 interchangeable plastic black non-chill bells, adult and pediatric spare diaphragm, one pair clear neoprene eartips, one pair black mushroom eartips.

10 languages manual (GB, FR, DE, IT, ES, PT, GR, PL, HU, Arabic).

### LINUX STETHOSCOPES



• 32518 LINUX STETHOSCOPE - blue

• 32524 LINUX STETHOSCOPE - black

• 32529 LINUX STETHOSCOPE - red

Single head stethoscope with lightweight zinc alloy chestpiece plated with an attractive satin finish. The special design assures better performances by pushing the back of the head.

Non-chill diaphragm retaining rim for patient comfort. Stainless steel binaurals fixed at 15° angle for greater comfort and acoustic seal. Soft and flexible PVC tubing. Supplied in deluxe box with one pair of plastic eartips and PVC eartips. Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.

231

### CARDIOLOGY STETHOSCOPES PROFESSIONAL STETHOSCOPE

- 32550 CARDIOLOGY CLASSIC STETHOSCOPE blue
- 32551 CARDIOLOGY CLASSIC STETHOSCOPE burgundy
- 32552 CARDIOLOGY CLASSIC STETHOSCOPE black

Cardiology Classic offers acoustical excellence in a traditional design with superior durability. Its innovative features include: - stainless steel chestpiece (diameter 33-44 mm) with extra deep cone-shaped bell for a superb low frequency response

- stainless steel double inner spring binaural - ultra-sensitive diaphragm for unsurpassed amplification
- durable, elegantly moulded 55.5 cm (22") PVC tubing (int. Ø 6.5 mm, ext. Ø 12 mm)

Manual and box in 11 languages: GB, FR, DE, IT, ES, PT, GR, PL, HU, SE, Arabic. Colour coordinated







non-chill ring and diaphragm

lined hox with 2 extr set of PVC eartips

• 32526 REGALITE - black Top quality single head stethoscope.

Patented multi-frequency "ringo-raised™" diaphragm system. Chromed plated chestpiece with "SUPERFLEX" inner spring binaural and 1 piece moulded, latex free, PVC tubing. Supplied in deluxe box, with spare soft eartips and one spare diaphragm. Manual and box in 7 languages:

GB, FR, IT, ES, PT, GR, Arabic.





### LYNX MULTI-FUNCTIONAL VISUAL STETHOSCOPE

• 32596 LYNX MULTI-FUNCTION STETHOSCOPE with SpO. probe, USB cable and adapter

• 32598 SpO, PROBE - spare

Multi-function visual stethoscope with real time display of ECG waveform, heart rate and pulsoximeter.

- compact and portable, easy to use
- adjustable screen contrast
- adult SpO, sensor
- alarm function for SpO, and Pulse rate
- low power consumption

Accuracy:

Multilanguage box and manual: GB, FR, IT, ES

### **TECHNICAL SPECIFICATIONS**

Heart rate Measurement range: 30 - 300 bpm Accuracy: Pulse rate Measurement range: 30 - 250 bpm ±2 bpm or ±2% (select larger)

Accuracy: Other Power supply Display:

SpO<sub>2</sub> Measurement range: 0% - 100%

70% - 100% ±2%, <70% unspecified

Rechargeable lithium battery DC 3.7 V 2.7" LCD

### MULTI-FUNCTIONAL VISUAL STETHOSCOPE

### • 32597 MULTI-FUNCTION VISUAL STETHOSCOPE with SpO, probe, USB cable and adapter, earphone • 32598 SpO. PROBE - spare

The device includes stethoscope function and displays ECG waveform, heart rate, SpO<sub>2</sub>, pulse and pulse waveform. Suitable for hospital, clinic, medical community and family.

- compact, light and portable, easy to use
- earphone output and adjustable volume - alarm for SpO, and pulse rate exceeding limits
- real-time detecting, data storage and review - real-time clock
- recorded data can be transferred to PC
- PC analysis software

- low power consumption Multilanguage box and manual: GB, FR, IT, ES

Stethoscope Heart: Lung: Heart rate Measuring range:

Accuracy

100 - 800 Hz 20 - 800 Hz 30 - 300 hpm Pulse rate Measuring range: Accuracy: SpO\_ Accuracy

±2 bpm or ±2% (select larger) 0% - 100%

Other Battery Display

3.7 V rechargeable lithium battery 2.4" colour TFT 110x60x14 mm

32596

# **( (** 0123 32597

### **TECHNICAL SPECIFICATIONS**

70 - 100% (±2%) <70% unspecified

### ACOUSTIC EXCELLENCE DOUBLE HEAD STETHOSCOPES



**CLASSIC STAINLESS STEEL STETHOSCOPES - Adult and Pediatric** High quality stethoscope with stainless steel chestpiece, stainless steel double inner spring binaural and durable, elegantly moulded PVC tubing for unsurpassed acoustic

performance. The colour coordinated flexible 55 cm (22") PVC "Y" tubing, non-chill ring and diaphragm retaining ring provide excellent patient comfort, while adding attractiveness. It comes in a foam lined box with 2 extra sets of soft eartips. Chestpiece: Ø 45 mm (adult), Ø 35 mm (pediatric)

Manual and box in: GB, FR, DE, IT, ES, PT, GR, PL, HU, SE, Arabic



spare for Classic/Wan/Yton/Duca/Regalite

32532 Classic adult - orange Classic adult - light blue 32533 32534 Classic adult - black 32535 Classic adult - burgundy 32536 Classic adult - dark blue 32537 Classic adult - green 32538 Classic adult - red 32539 Classic adult - pink 32540 Classic adult - royal blue 32541 Classic adult - lilác CLASSIC DOUBLE HEAD S/S **TEACHING STETHOSCOPES** 32542 Classic Teaching - black CLASSIC DOUBLE HEAD S/S

CLASSIC DOUBLE HEAD S/S STETHOSCOPES - ADULT

STETHOSCOPES - PEDIATRIC

32512 Classic pediatric - light-blue 32516 Classic pediatric - black

32531 Classic adult - dark green

### RIESTER DUPLEX® 2.0 STETHOSCOPES, SIMPLY BETTER HEARING



Duplex® 2.0 sthetoscopes are distiguished by outstanding acoustic performance.

They have been completely new constructed to meet the challenges of daily diagnostic practice. Special design tube for better auscultation of adults, children/babies or new-borns. - precision double chest-piece made of stainless steel with innovative membrane support

- anatomically shaped binaural with internal multiple spring for adjusting the contact pressure
- extra-soft, replaceable and pivotable ear-tips for perfect sealing at the ear canal and enhanced wear comfort
- innovative acoustic system with extraordinary auscultation for all frequency ranges

with novel non-chill rims for improved adaptation on the skin

Supplied with name plate, replacement ear-tips and membrane.

GIMA	Riester	RIESTER DUPLEX® 2.0 - STAINLESS STEEL -			L -
code	code		LATEX FREE		
		DUPLEX® 2.0 ADULT	Membrane	Length	Weight
		Duplex® 2.0 - black		74 cm	151 g
		Duplex® 2.0 - white	Ø 44 mm	74 cm	151 g
		Duplex® 2.0 - blue	Ø 44 mm	74 cm	151 g
32336	4210-04	Duplex® 2.0 - red	Ø 44 mm	74 cm	151 g
		<b>DUPLEX® 2.0 PEDIATRIC</b>			
32338	4220-02	Duplex® 2.0 - white	Ø 32/23.5 mm	69 cm	124 g
		<b>DUPLEX® 2.0 NEW-BORN</b>			
32340	4230-02	Duplex® 2.0 - white	Ø 24/17.5 mm	69 cm	105 g

### ERKA FINESSE STHETOSCOPES - MADE IN GERMANY



### FINESSE STETHOSCOPES

With the reversible double chest-piece you'll be prepared for all eventualities in everyday medical practice. The membrane side guarantees optimal auscultation for the entire frequency spectrum and the open bell side is specifically designed for low frequencies.

### FINESSE<sup>2</sup> STETHOSCOPES

The reversible, combined chest-piece has two membrane sides, each making the full frequency range perfectly audible. The large membrane is suitable for auscultation of adults and

FEATURES	Finesse Light	Finesse <sup>2</sup>
Pre-tensioned ERKA. convex membrane provides excellent resonance and sound.	Х	Х
Non-chill ring ensures highest patient comfort.		Х
Superior polish, chromium-plated, non- porous surface and brass chest-piece ensure perfect surface hygiene.	x	Х
Two internal channels run parallel in the stethoscope tubing preventing any noise caused by friction of two separate tubes.		х
Through the separately integrated spring in the tube, there is no acoustic loss from the chest-piece to the ear.		Х
Ergonomic design and super soft tips provide excellent acoustic seal against external noise interference and maximize user's comfort.	х	х
Standard 15° inclined binaurals can be individually adapted to the specific ear canal of the user.	х	X

es H	ERKA.	
		Ai
	32265	



	GIMA	ERKA		ERKA STETHOSCOPES -	
	code	code		tubing length - 55 cm	
FINESSE LIGHT ADULT			HT ADUI	LT - head Ø 44.5/33.5 mm	
	32250	520 000 00		Finesse light - black	
	32251	520 000 20		Finesse light - navy blue	
	32252	520 000 55		Finesse light - dark green	
		FINESSE PI	EDIATRI	C - head Ø 31/26.5 mm	
	32256	549 000 00		Finesse pediatric - black	
	32257	549 000 25		Finesse pediatric - light blue	
	32258	549 000 35		Finesse pediatric - pink	
		FINESSE A	ADULT -	head Ø 44.5/33.5 mm	
	32262	550 000 00		Finesse adult - black	
	32263	550 000 05		Finesse adult - dark grey	
	32264	550 000 20		Finesse adult - navy blue	
	32265	550 000 55		Finesse adult - dark green	
	32266	550 000 60		Finesse adult - burgundy	
		FINESSE <sup>2</sup> P	<b>EDIATRI</b>	C - head Ø 30/21.3 mm	
	32270	536 000 00		Finesse <sup>2</sup> pediatric - black	
	32271	536 000 35		Finesse <sup>2</sup> pediatric - pink	
	FINESSE <sup>2</sup> ADULT - head Ø 47/30 mm				
	32275	535 000 00		Finesse <sup>2</sup> adult - black	
	32276	535 000 05		Finesse <sup>2</sup> adult - dark grey	
	32277	535 000 20		Finesse <sup>2</sup> adult - navy blue	

### **ERKAPHON STETHOSCOPES - MADE IN GERMANY**



### **ERKAPHON STETHOSCOPES:**

High quality precision stethoscopes for excellent acoustics, made in Germany.

All stethoscopes are equipped with 56 cm long Y tube, brass chrome-plated binaural and chest-piece (32350, 32358) or aluminium (32344-7), membrane Ø 44 mm, bell Ø 30 mm (32358 only).

GIMA code	ERKA code	ERKAPHON STETHOSCOPES
	ERKAPHON	I FLAT CHESTPIECE - aluminium
32344	544 000 10	Erkaphon flat chestpiece - black
32345	544 000 20	Erkaphon flat chestpiece - navy blue
32346	544 000 25	Erkaphon flat chestpiece - light blue
32347	544 000 30	Erkaphon flat chestpiece - red
	ERKAPHO	N FLAT CHESTPIECE - chromed
32350	543 000 10	Erkaphon flat chestpiece - black
	ERKAPHON	DOUBLE CHESTPIECE - chromed
32358	541 000 10	Erkaphon double chestpiece - black

### 3M™ LITTMANN® STETHOSCOPES USER GUIDE

### LITTMANN STETHOSCOPES

3M Littman stethoscopes offer exceptional acustic features. Each model has been created for a specific professional need.

The following guide will allow customers to select the model more suitable to his profession and preferred colour.

3M   @				Cla	ssic		(	Cardiology	,	Electronic
Littmann® Stethoscopes  Authorized Distributor	9	3	0	0	0	0	0	0	8	
OCCUPATION	Lightweight	Select	Master Classic II	Classic III	Classic II SE	Classic II Paediatric or Infant	Master Cardiology	Cardiology IV	Cardiology III	3200 3100
Emergency Physician			••	•••	••					
General Practitioner			••	•••	••					•••
Pediatrician			••	•••	••	••				
Medical Student			••	•••	••					
Veterinarian			••	•••	••					
Neurologist			••	•••	••					
Nurse	••	••		•	•					
Cardiologist							••	••	••	•••
Anesthesist							•	••	••	•••
Respiratory Specialist							•	••	••	•••
Internist							•	•	•	•••
BLACK BURGUNDY NAVY BLUE HUNTER GREEN	CHOCOLATE	LIGHT BLUE	RASPBERRY	ORANGE METAL GREEN	LILAC ROYAL BLUE	OCEAN BLUE	CORAL PINK CORAL PINK OLIVE GREEN	SAND	TURQUOISE LIME	EMERALD PINK

### ] 3M™ LITTMANN® SELECT | \_ | 3M™ LITTMANN® LIGHTWEIGHT II



32400

code

32396

235

32397 2292

32398 2294

32400 2298

32401 2293

32403 2290 32282 2291



3M™ LITTMANN® SELECT

STETHOSCOPES - length 71 cm

Littmann® Select - pearl pink Littmann® Select - violet

Littmann® Select - ocean blue

■ Littmann® Select - royal blue Littmann® Select - burgundy
Littmann® Select - black

■ Littmann® Select - raspberry

Littmann® Select - caribbean blue

Littmann® Select - colour on request\*







GIMA code	3M code	3M™ LITTMANN® LIGHTWEIGHT II S.E.
32389	2452	Littmann® Lightweight II S.E caribbean blue
32390	2450	■ Littmann® Lightweight II S.E black
32391	2451	■ Littmann® Lightweight II S.E burgundy
32392	2454	Littmann <sup>®</sup> Lightweight II S.E ceil blue
32393	2453	Littmann® Lightweight II S.E lilac
32394	2455	Littmann® Lightweight II S.E metal green
32395		Littmann® Lightweight II S.E colour on request*
		*Minimum order 3 pieces

### LITTMANN® MASTER CLASSIC II

### OTHER COLOURS ON REQUES AVAILABLE IN 20 DAY

\*Minimum order 3 nieces





GIMA code	3M code	length 69 cm - head Ø 44 mm
		■ Littmann® Master Classic II - burgundy
32426	2144L	■ Littmann <sup>®</sup> Master Classic II - black
32427	2147	■ Littmann <sup>®</sup> Master Classic II - navy blue
32364	2630	■ Littmann® Master Classic II - caribbean blue
32366	2633	Littmann® Master Classic II - ceil blue
32367	2632	■ Littmann <sup>®</sup> Master Classic II - violet
32471	2141	■ Littmann® Master Classic II - "black edition"
32365		Littmann® Master Classic II - colour on request



The 3M<sup>™</sup> Littmann<sup>®</sup> Classic III<sup>™</sup> Stethoscope offers high acoustic sensitivity for exceptional performance 32305 5829 Littmann® Classic III - lime green when doing general physical assessments. It features dual tunable diaphragms and updated design. high acoustic sensitivity
 dual single-piece tunable diaphragms

(pressure sensitive) versatile adult and pediatric two-sides chestpiece

- small-side diaphragm prevents debris in open bell - snap tight soft-sealing eartips

 next generation longer-life tubing - small side converts to open bell



CLASSIC II SE

Littmann<sup>,</sup>



32317 5868 Littmann<sup>®</sup> Classic III - burgundy - black finish CLASSIC III - RASPBERRY - RAINBOW FINISH 32318 5869 Littmann® Classic III - caribbean blue - black finish

I3M™ LITTMANN® CLASSIC III STETHOSCOPES 3M™ LITTMANN® STETHOSCOPES - length 69 cm code code CLASSIC III - head Ø 43/33 mm 32290 5620 ■ Littmann® Classic III - black 32291 5622 Littmann® Classic III - navy blue 32292 5626 Littmann® Classic III - raspberry 32293 5627 Littmann® Classic III - burgundy 32294 5639 Littmann® Classic III - rose pink 32295 5832 Littmann® Classic III - lavender 32296 5835 Littmann® Classic III - turquoise 32297 5839 Littmann® Classic III - lemon - lime 32298 5840 Littmann® Classic III - emerald 32299 5621 Littmann® Classic III - grey 32300 5623 Littmann® Classic III - caribbean blue 32301 5624 ■ Littmann® Classic III - hunter green 32302 5629 Littmann® Classic III - orange 32303 5630 Littmann® Classic III - ceil blue 32304 5633 Littmann® Classic III - pearl pink

32306 5831 Littmann® Classic III - plum CLASSIC III SPECIAL EDITION - head Ø 43/33 mm 32308 5870 ■ Littmann® Classic III - black - rainbow finish 32309 5871 ■ Littmann® Classic III - raspberry - smoke finish 32310 5803 ■ Littmann® Classic III - black edition 32311 5809 ■ Littmann® Classic III - chocolate - copper finish 32312 5806 ■ Littmann® Classic III - raspberry - rainbow finish 32313 5807 Littmann® Classic III - caribbean blue - rainbow finish 32314 5811 ■ Littmann® Classic III - black - smoke finish 32315 5812 Littmann<sup>®</sup> Classic III - dark olive green - smoke finish 32316 5867 ■ Littmann® Classic III - navy blue - black finish

### LITTMANN® CLASSIC II STETHOSCOPES



**OTHER COLOURS** ON REQUEST Available in 20 days Please indicate 3M code

Minimum order 3 pieces









# Littmann®

3M 3M™ LITTMANN® STETHOSCOPES - length 69 cm code CARDIOLOGY IV - head Ø 43/33 mm ■ Littmann® Cardiology IV - black 32607 6153 Littmann® Cardiology IV - burgundy 6154 Littmann® Cardiology IV - navy blue 6155 ■ Littmann® Cardiology IV - hunter green 6156 Littmann® Cardiology IV - plum 32611 6157 Littmann® Cardiology IV - raibbean blue 32612 6158 Littmann® Cardiology IV - raspberry 32613 6161 Littmann® Cardiology IV - rose pink

I3M™ LITTMANN® CARDIOLOGY IV STETHOSCOPES The 3M™ Littmann® Cardiology IV helps you to catch more of

> the new design, more versatile than ever. - better audibility of high-frequency sounds

- tunable diaphragms for hearing both high and low frequency sounds without turning over the chestpiece (pressure sensitive) - adult and paediatric sides for more versatility

the subtle critical sounds, thanks to the improved acoustics and

- single-piece diaphragm, easier to attach and clean

because the surface is smooth without crevices.

- next generation longer-life tubing

- snap tight soft-sealing eartips. GIMA 3M

CARDIOLOGY IV SPECIAL FINISHES - head Ø 43/33 mm 32631 6162 Littmann® Cardiology IV - black - smoke finish 32632 6163 Littmann® Cardiology IV - black edition 32633 6164 Littmann® Cardiology IV - black - brass finish 32634 6165 Littmann® Cardiology IV - black - rainbow finish 32635 6166 Littmann® Cardiology IV - plum - smoke finish 32636 6168 Littmann® Cardiology IV - navy blue - black finish 32637 6171 Littmann® Cardiology IV - turquoise - smoke finish 32638 6178 Littmann® Cardiology IV - raspberry - smoke finish CARDIOLOGY IV MIRROR FINISH - head Ø 43/33 mm 32646 6169 Littmann® Cardiology IV - carribbean blue - mirror fin. 32647 6170 Littmann® Cardiology IV - burgundy - mirror finish

32648 6177 Littmann® Cardiology IV - black - mirror finish

32649 6179 Littmann® Cardiology IV - black/champagne - smoke fin.

3M™ LITTMANN® STETHOSCOPES - length 69 cm

### 3M™ LITTMANN® CARDIOLOGY STETHOSCOPES









MASTER CARDIOLOGY - head Ø 51 mm 32435 2160 Littmann® Master Cardiology - black 32436 2163 Littmann® Master Cardiology - burgundy

32437 2164 Littmann® Master Cardiology - navy blue

32361 2178 Littmann® Master Cardiology - caribbean blue

MASTER CARDIOLOGY SPECIAL EDITION - head Ø 51 mm

2161 Littmann® Master Cardiology - black edition

2183 Littmann® Master Cardiology - hunter green

32360 2176 ■ Littmann® Master Cardiology - black smoke ed

CARDIOLOGY TRADITIONAL

■ Littmann® Traditional - black

32439 2167 Littmann® Master Cardiology - plum

32331 3142 Littmann® Traditional - navy blue

32332 3143 Littmann® Traditional - burgundy



CARDIOLOGY III BLACK EDITION

32362

32473

32363

32359

32330

MASTER CARDIOLOGY 3M™ LITTMANN® STETHOSCOPES - length 69 cm

Littmann® Master Cardiology - colour on request

Littmann® Master Cardiology - colour on request

code	code	3M™ LITTMANN® STETHOSCOPES - length 69 cm			
CARDIOLOGY III - head Ø 43/33 mm					
32371	3138	■ Littmann® Cardiology III - caribbean blue			
32372	3148	■ Littmann® Cardiology III - raspberry			
32429	3149	Littmann® Cardiology III - coral pink			
32430	3128	■ Littmann® Cardiology III - black			
32431	3129	■ Littmann® Cardiology III - burgundy			
32432	3130	■ Littmann® Cardiology III - navy blue			
32433		■ Littmann® Cardiology III - plum			
32434	3134	■ Littmann® Cardiology III - hunter green			
32443	3146	Littmann® Cardiology III - light blue			
32444		■ Littmann® Cardiology III - red			
		GY III SPECIAL EDITION - head Ø 43/33 mm			
32369		Littmann® Cardiology III - lime - smoke finish			
		■ Littmann® Cardiology III - black edition			
		■ Littmann® Cardiology III - chocolate - copper finish			
32475	3128BRS	■ Littmann® Cardiology III - black - brass finish			



CARDIOLOGY III





MASTER CARDIOLOGY





brown finish

### 3M™ LITTMANN® 3100 AND 3200 ELECTRONIC STETHOSCOPES

### **ELECTRONIC STETHOSCOPES**

3M™ Littmann® Electronic Stethoscope Model 3100 and 3200 exceptional sound capabilities deliver an exceptional auscultation experience. Clinical evidence shows that, it is easier to detect difficult-to-hear heart sounds like S3 gallops and aortic regurgitation murmurs, as well as abnormal lung sounds. Here's why: Ambient Noise Reduction Technology

It cancels out, on average, 85% of ambient background noise that can interfere with the auscultation Operates on single

experience, without eliminating critical body sounds. Acoustic Seal Eartips and Tubing They create an excellent acoustic seal. It means a tighter seal from ambient noise entering through

tubing and eartip connections. State-of-the-Art Sound Sensor Positioned at the base of the tubing, the sensor brings the sound more naturally to your ears. Retro

Useful for obese LCD interfac Ergonomically designed chest piece for easy, one-hand

Designed to visualize what you are hearing, allow playback when and where convenient facilitate storage of sounds in patient records or transfer to

- colleagues for further analysis - connects wirelessly to the Bluetooth® - display and print sounds as phonocardiogram
- play recordings at slow speed - save patient information send as an e-mail attachment







GIMA code	3M code	3M™ LITTMANN® ELECTRONIC STETHOSCOPES
32490	3100BK27	■ Littmann® Electronic 3100 - black
32491	3100BU	■ Littmann® Electronic 3100 - burgundy
32492	3100NB	■ Littmann® Electronic 3100 - navy blue
32495	3200BK27	■ Littmann® Flectronic 3200 - black

32496 3200NB Littmann® Electronic 3200 - navy blue

32497 3200BU ■ Littmann® Electronic 3200 - burgundy

### 3M™ LITTMANN® ACCESSORIES

GIMA	3M				
code	code	3M™ LITTMANN® ACCESSORIES			
code	code	DIAPHRAGM + RETAINING RING - box of 5 pcs			
32449	36572	■ For Cardiology III (small side) - black	(CO)	((()))	660
51443	36573	For Cardiology III (small side) - grey		(X)	
32450	36556	For Classic II S.E., Select, Master classic, Cardio III (large side) - black			
32464	36557	For Classic II S.E., Select, Master classic, Cardio III (large side) - grey			
32452	36554				
32605	36555		32450	32464	32449
32453	51185		15000		
32433	31103	DIAPHRAGM OR RETAINING RINGS			
51450	36550		(200		AGOZOLA
51451	36551	Retaining ring for Pediatric Classic II - grey - box of 5	((4)		
		■ Diaphragm for Electronic 3200 - black			
		■ Diaphragm for Electronic 3200 - black ■ Diaphragm for Electronic 3100 - dark grey			
		■ Diaphragm for Electronic 3100 - dark grey	-		
		■ Diaphragm for Pediatric Classic II - box of 10	36560	51450	51445
31432	30300	NEOPRENE RINGS			
32476	36547	■ Neoprene black ring - infant - box of 5		3M	
32455	36569	Neoprene grey ring - infant - box of 5		Littm	
51455	36546	■ Neoprene grey ring - infant - box of 5  ■ Neoprene black ring - pediatric - box of 5		Stethoscor	
32456	36568				
32459	36544	■ Neoprene grey ring - pediatric - box of 3  ■ Neoprene black ring - Classic II, Lightweight - box of 10	22456 224	Auth	orized Distributor
51456			32456 324	59	
31430	30343	EAR TIPS for all models - box of 10			100
32451	37812	Ear Tips - grey - soft - large	20	790	
32465	37809		200 0		
32466	37811	■ Ear Tips - black - soft - small of tips is		AD DEED	
32467	38742				
32467		Ear rips - grey - rigid - small	32451 324	65 32466	32468
		■ Ear Tips - grey - rigid - large	200		32469
51490		■ Ear Tips - black - small and large	9		No.
51491 32460		Ear Tips - grey - small and large			EFFINGER
		■ Binaural Classic II SE, ped., infant, Select - black	0	32460	OER
		■ Binaural Cardiology III and Master Cardiology - black ■ Binaural Master Classic, Classic III - black			
32469	2170		_		
51494	40007				
51495		■ Name tag - grey			SEED
		HRAGMS AND RIM ASSEMBLY + NON CHILL BELL SLEEVES + EARTIPS	51460	51461	STATE OF THE PARTY
51460		■ For Cardiology III™ - black - blister			
51461		■ For Cardiology III™ - black - blister			
		HRAGM AND RIM ASSEMBLY + NON CHILL BELL SLEEVES + EARTIPS			(0.00
51464	40005		51464	51465	Section 197
51465		For Classic II S.E black - blister  For Classic II S.E grey - blister	21707	31703	
51466		For Lightweight - black - blister		A POR	
51400		TUNABLE DIAPHRAGM + RIM ASSEMBLY + EARTIPS			
51470		■ For Master Cardiology - black - blister	-		-
51470	40011	For Master Cardiology - Black - Blister  For Master Cardiology - grey - blister	51470 5	1471 51472	51473
51471	40018				
51472		■ For Cardiology 3.1.C black - blister  ■ For Master Classic <sup>™</sup> - black - blister	( DA)		
314/3	-10022	TUNABLE DIAPHRAGM + 2 RIMS ASSEMBLY			15 m
51477	40012	■ For Classic II <sup>TM</sup> - Paediatric - black - blister	51477	51478	ALCOHOL: N
51477		■ For Classic II™ - Paediatric - black - blister  ■ For Classic II™ - Infant - black - blister		31470	
314/0		TUNABLE DIAPHRAGMS + RIM ASSEMBLY + EARTIPS			
51482		■ For Classic III <sup>TM</sup> - black - blister	51482		CORN
51483		■ For Classic III™ - black - blister  ■ For Classic III™ - grey - blister	31482	51483	Total Control
31403	40017	I of Classic III - grey - blister		51405	

### YTON ANEROID SPHYGMOMANOMETERS

ONE PIECE CUFF

LATEX FREE

32692

### YTON ANEROID SPHYGMOMANOMETERS

Economic sphygmomanometers with nylon cuff with velcro closure, reliable manometer with clip to be fixed on the cuff. Scale 0-300 mmHg. Air release at closed tap max 4 mmHg/minute.

Manual setting of deflation possible up to 2/3 mmHg/sec. From 260 mmHg to 15 mmHg max deflation time 10 sec. Scale graduated every 2 mmHg.

Floating zero (the pointer has no stop point but swings freely), nylon velcro cuff, latex bulb with chromium plated valve.

Chromium-plated air tap with air release regulation by screw valve. Supplied with a simulated-leather soft pouch with zip in a carton box. Available in 5 versions: standard, with one piece cuff, latex free, with incorporated stethoscopes or kit (sphygmomanometer+stethoscope).

iviuitiian	Multilanguage box and manual: GB, FR, 11, ES, P1, DE, GR, Arabic.				
GIMA code	YTON SPHYGMOMANOMETERS				
32720	YTON - black cuff				
32692	YTON - one piece cuff				
32704	YTON latex-free - blue cuff				
32703	YTON - with incorporated - stethoscope - black cuff				
32693	YTON KIT - sphygmomanometer + stethoscope				
32701	YTON MANOMETER - spare				







€ 0476 LATEX FREE 32704





### YTON DIGITAL SPHYGMO

### • 32722 YTON DIGITAL SPHYGMO

€ 0476

Semi-automatic digital sphygmomanometer with manual inflation and automatic deflation through manual valve. Light: only 50 g, one third of a normal blood pressure monitor. A large 9 digits LCD display shows systolic/diastolic/pulse rate simultaneously, and store 90 memories. Range: 40-260 mmHg Pulse: 40-160 minute Power supply: 1 x AAA battery Multilanguage box: GB, FR, IT, ES, PT, DE, GR, Arabic Manual: GB, IT





### SPHYGMOMANOMETERS WITH GAUGE ON THE CUFF



- 32724 BERLIN SPHYGMO velcro cuff High quality sphygmomanometer with gauge mounted on cuff:
- high reliable manometer with extra large dial Ø 65 mm
- top quality and resistant linen cuff with simulated leather support and velcro
- extra large PVC bulb, 9x5 cm, latex free Made in Italy - German manometer



### • 32723 NEW EXACTOPHON SPHYGMO pull-on strap cuff

GIMA quality and reliability in a stylish and long-life sphygmomanometer. EXACTOPHON has a reliable manometer fixed on a simulated leather support, on a highly resistant linen pull-on straps cuff. Supplied in a nice carrying case and box. Made in Italy: GIMA.

• 32805 EXACTOPHON BLADDER - spare • 32806 EXACTOPHON CUFF - spare




• 32719 GIMATONO - latex free Economic sphygmo with chrome-plated manometer fixed on the cuff, provided with a rubber protective ring. Nylon cuff with simulated-leather

support. Two tubes adult size latex free TPU bladder, with standard latex free PVC bulb. Supplied in nylon bag and cardboard

box. Made in P.R.C.

### SIRIO SPHYGMO AND 3 MULTICUFF KIT WITH BAG



• 32705 SIRIO PEDIATRIC KIT - sphygmo with 3 pediatric cuffs Sirio with 3 pediatric cuffs: minicuff (32812) 4 months - 3years, minicuff (32813) 3-7 years, minicuff (32814) 7-10 years in a nylon bag. 27177 SIRÍO MULTICUFF PEDIATRIC BAG - empty



• 32706 SIRIO KIT 3 sphygmo with 3 one piece cuffs Sirio with 3 one piece

cuffs: child (32910), adult (32911) and adult large (32912) in a nylon bag. • 27178 SIRIO MULTICUFI

BAG 3 - empty



• 32729 SIRIO SPHYGMO - adult grey/green cuff

Classic sphygmomanometer with fabric cuff with velcro closure (green/grey colour). Reliable large dial manometer for easy readings, fixed on bulb.

Scale 0-300 mmHg, graduated every 2 mmHg. Supplied in carrying case and box, with 4 languages user manual (English, Spanish, French, Italian).



• 32707 SIRIO KIT 5 sphygmo with 5 cuffs Sirio with 5 cuffs: infant cuff (32886). child cuff (32888), adult cuff (32830), adult large cuff (32834) thigh cuff (32837) in a nylon bag. • 27179 SIRIO MULTICUFF BAG 5 - empty

32707





• 32702 SHOCK RESISTANT SPHYGMO - nylon-cuff High quality, shock resistant sphygmomanometer matching the ISO 81060 standard.


One piece design with damped system manometer Creative design with a new structure that fixes all parts together closely to make it more steadier. The damped system absorbs impacts.

### Other features

- large dial Ø 55 mm easy to read
- high precision air-release valve, provides precise rate adjustment and quick deflation
- adult nylon cuff with latex-free bladder - soft bulb for fast inflation.
- Multilanguage box and manual: GB, FR, IT, ES, PT, DE.



- 32713 MINOR 2 SPHYGMO
- High quality sphygmomanometer with traditional design and modern features.
- adjustable by turning a screwdriver, for perfect





• 32714 MINOR 2 SPHYGMO - 2 tubes - black nylon velcro cuff

- 2 tubes - green cotton hook cuff

- high precision manometer, calibration any time

- 2 tubes system for quick inflation



### LONDON: PROFESSIONAL SPHYGMO



• 32725 LONDON SPHYGMO - adult - black cuff 32726 LONDON SPHYGMO - adult - red cuff Professional, stylish, reliable and lightweight sphygmomanometer with ABS manometer, integral PVC bulb, high quality precision mechanism, velcro closure calibrated nylon cuff and one tube TPU bladder. Dial Ø 55 mm, with specially designed eye-catching colour printing and easy to read. Special outer ring protects the manometer from shocks



Supplied in a nice colour co-ordinated carrying bag and box. With multilingual box and user manual: GB. FR. IT. ES. DE. PT. GR. Latex free.

### TOKYO AUTOMATIC

• 32735 TOKYO SPHYGMO - adult - black cuff Professional sphygmomanometer with large Ø 65 mm dial and button type air release valve. ABS light plastic case, and extra shock-proof ring for long durability.

360° rotary handle. Supplied with black nylon calibrated cuff with D-ring, black 1-tube PVC, latex free bladder and black, latex free PVC bulb in a nylon carrying bag and cardboard box.

Multilanguage box and manual: GB, FR, IT, ES, DE, PT, GR, Arab.



# gradual deflation

### **ROMA SPHYGMOMANOMETERS - 4 DIFFERENT MODELS**









protective ring.

Supplied in a nice nylon carrying bag with external velcro pocket and cardboard box. Latex free.


- 32727 ROMA SPHYGMO adult 1 tube
- 32734 ROMA SPHYGMO adult 2 tubes
- Same as 32727 but with pediatric cuff 35x11 cm

- 32856 PVC RIBBED BULB





DIAGNOSTICS



- 32709 ROMA SPHYGMO pediatry 1 tube
- 32728 ROMA SPHYGMO adult

- fluorescent - 1 tube Same as 32727 but with special fluorescent dial plate to allow easy reading even in dark

places. Suitable for emergency.

- 32857 PVC PROTECTIVE RING



### **ROMA MULTICUFFS KIT**



• 32738 ROMA KIT - Sphygmo with 3 cuffs Same as code 32727 but supplied with 3 cuffs: one pediatric (35x11 cm), one adult (49x15 cm) and one adult large (62x17 5 cm) Latex free.

### EMERGENCY MULTICUFF KIT

• 32771 EMERGENCY SPHYGMO KIT - 5 cuffs

Palm type sphygmomanometer with orange silicone shockproof ring and orange cup of air-release valve. PVC tube and 1 tube TPU bladder. Supplied in a plastic carrying case with 5 cuffs: XS infant (13-19 cm), S child (18.4-26.7 cm), M adult (25.4-40.6 cm), L adult large (33.3-51 cm), XL thigh (40.6-66 cm)






### CUFFS ASSORTMENT FROM NEWBORN TO OBESE





tylori cari trial veicio lasternig, El Divi syntede l'abber biadaci, later n'ec						
MINI CUFFS grey/green - nylon						
1 tube	2 tubes	Model	Size cm			
32810	32820	Premature	16xh 5			
32811	32821	Up to 3 months	23xh 5			
32812	32822	4 months to 3 years	29xh 7			
32813	32823	3-7 years	33xh 9			
32814	32824	7-10 years	40xh 11			
32816	32826	32810-14, 32820-24	Set 5 pieces			



CUFFS grey/black - nylon - TPU bladder - velcro fastening							
1 tube	2 tubes	Model	Arm circumference	Size cm			
32886	32887	Infant	13 to 19 cm	7.5x26			
32888	32889	Child	18.4 to 26 cm	11x34			
32830	32832	Adult	25 to 40 cm	52x15			
32834	32835	Adult large	35 to 50 cm	61x17.5			
22027	22020	The Santa	44 4 - 66	02.24			

32837	32838	rnign	41 (0 66 (11)	82X21			
ADULT CUFFS grey/green - cotton - TPU bladder - velcro fastening							
32829	-	Adult		53x14.5			
One tube cuff for Ranger, Sirio, London, Boston, Roma 1T, Tokyo, Ri-san, Precisa, Minimus.							
Two tubes of	uff for Minor	, Diplomat, Ytor	n line, Roma 2T, Dallas, Big	Ben, Empire.			



ilibrateu riyiori c	iibratea nyion cuns with tro biadder and rvc tube							
	CALIBRATED CUFFS - latex free - nylon							
1 tube	2 tubes	Model	Size cm	Colour				
-	32839	Pediatric	35x11					
32846	32847	Pediatric	35x11					
32842	32843	Adult	49x15					
32844	-	Adult	49x15					
32845	32850	Adult	49x15					
32848	32849	Adult large	62x17.5					
-	32841	Adult large	62x17.5					



Bladderless nylon cuffs

- reusable above 10 000 times - washable up to 60°C
- disinfectable with alcohol/ethanol
- ideal to prevent cross-contaminations soft surface for a pleasurable feeling on the skin
- tested according to ISO 105 E01

BLADDERLESS ONE PIECE CUFF - latex free								
1 tube	2 tubes	Model	Size	Arm circumference				
32910	32913	children	10x34 cm	19 to 27 cm				
32911	32914	adult	14.5x54 cm	26 to 41 cm				
32912	32915	adult large	16x63 cm	34.3 to 51 cm				

### SPHYGMOMANOMETERS SPARE PARTS AND ACCESSORIES



Rubber tubing maximum extension. 3 m					
GIMA code	SPHYGMOMANOMETERS SPARE PARTS	Minimum order			
32865	Coiled tubing - black (42-45 spirals) - 48 cm	10 pcs.			
32808	Nylon velcro cuff (no bladder) 54 x15 cm	10 pcs.			
32874	1 tube Bladder	10 pcs.			
32875	2 tubes Bladder	10 pcs.			
32876	1 tube + 1 hole Gimatono Bladder	10 pcs.			
32880	Vertical glass tube	10 pcs.			
32870	Male-Female metal connector	box 10			
32871	Screw Type metal connector	box 10			
32872	Bayonet Type metal connector	box 10			
32873	Plastic connector	box 100			



GIMA code	SPHYGMOMANOMETERS SPARE PARTS	Minimum order
32854	Yota PVC bulb - black - latex free	10 pcs.
32851	Yota PVC bulb - green	10 pcs.
32855	Yota latex bulb - black	10 pcs.
32860	Superior PVC bulb - green - latex free*	10 pcs.
32859	Superior PVC bulb - black*	10 pcs.
32852	Yota chrome-plated air release valve	10 pcs.
32861	Superior chrome plated air valve	10 pcs.
32853	Yota inflation system	10 pcs.
32862	Superior inflation system - latex free*	10 pcs.
32863	Deluxe inflation system	10 pcs.
	*Made in Germany	



# BABYPHON® RIESTER PEDIATRIC SPHYGMO

- 32710 BABYPHON® PEDIATRIC SPHYGMO with 3 cuffs
- Palm pediatric sphygmomanometer with 3 cuffs - fast inflation of the cuff due to ergonomic spoon-shaped stainless steel handle
- easy reading metal manometer with aluminium scale Ø 49 mm (19.29 inch)
- lifelong precision due to almost non-aging precision movement with specially tempered copper-beryllium diaphragm for pressure-loading capacity up to 600 mmHg - linear scale up to 300 mmHg, ±3 mmHg
- bear imprint on the cuffs

Supplied with 3 pediatric cuffs (child, infant and new-born in a padded nylon zipper case).

Newborn: size 15.5x5 cm - circumference 5-8 cm Infant: size 23x7.5 cm - circumference 8-13 cm Baby: size 35.5x10 cm - circumference 13-17 cm

# **PRESS** SAN® HYGIENIC PROTECTION OF SPHYGMOMANOMETER

• 32858 PRESSSAN® HYGIENIC PROTECTION OF SPHYGMO - box of 10 A practical hygienic accessory for the sphygmomanometer to protect patient's skin whilst measuring the blood pressure.

Made of a white non-woven fabric. Ensures patient's comfort and hygiene.

Can fit any kind of sphygmomanometer or pressure holter.



# **RIESTER ORIGINAL CUFFS - LATEX FREE**

GIMA code	RIESTER code	RIESTER CUFFS 1 TUBE	Colour	Size cm	Circumference cm	Compatibility
49811	129	Child velcro cuff	light blue	34.5x10	13-17	Minimus II*, Precisa,
49812	107	Adult velcro cuff	black	54.5x14.5	24-34	Ri-san, R1 Shock proof, E-Mega*,
49813	122	Adult/large velcro cuff	black	70x15	34-44	Baby phon*
		ONE PIÈCE RIESTER CUFF				
		washable at 60°C and disi	nfectable in	n liquid		
		reusable up to 10,000 time	es. ISO 105	E01 tested		
49816	154	Child one-piece cuff	dark green	35.5x10	13-17	Same as cuffs 1 tube
49817	150	Adult one-piece cuff	dark green	54.5x14.5	24-32	Same as curis i tube
		RIESTER CUFFS 2 TUBES				
49821	130	Child velcro cuff	light blue	35.5x10	13-17	Dia Dan
49822	108	Adult velcro cuff	black	54.5x14.5	24-32	Big Ben
Metal valve not included with spare cuff, can use valve from old cuff						



# HEINE ORIGINAL CUFFS - LATEX FREE

GIMA code	HEINE code	HEINE CUFFS 1 TUBE	Colour	Size cm	Circumference cm	Compatibility	Water resistant washable material
49801	M-000-09-702	Child - 2	grey	10x34	13-20		B F
49802	M-000-09-704	Adult small - 3	grey	14x53	20-29	All Heine	
49803	M-000-09-619	Adult - 4	grey	14x58	29-41	1 tube	
49804	M-000-09-706	Adult large - 5	grey	17x70	35-47		11.4



# ERKA ORIGINAL GREEN SUPERB CUFFS - LATEX, PVC, DEHP FREE

made in darable paterited derinari o material, perfect for clearing and als					
GIMA code	ERKA code	ERKA CUFFS 1 TUBE - grey	Size cm	Circumference cm	Compatibility
32895	025-28493	Infant	21.5x6.6	10-15	
32896	025-27493	Baby	30.3x9.1	14-21.5	6 1. 1
32891	025-26493	Child	40x11.6	20.5-28	Switch and
32892	025-20493	Adult	47x14.3	27-35	Kobold
32893	025-24493	Adult large	56x17.5	34-43	Kobolu
32894	025-29493	Thigh	75x21.5	42-54	
		ERKA CUFFS 2 TUBES -	green		
32898	025-26481	Child	40x11.6	20.5-28	
32899	025-20481	Adult	47x14.3	27-35	Vario
32900	025-24481	Adult large	56x17.5	34-43	
		ERKA TWIN TUBE CUI			
32877	025-26482	Child	40x11.6	20.5-28	Perfect
32878	025-20482	Adult	47x14.3	27-35	Aneroid and
32879	025-24482	Adult large	56x17.5	34-43	Profi



# RIESTER ANEROID SPHYGMO - MADE IN GERMANY



integrated stethoscope

A classic palm-style sphygmomanometer for precise selfmeasurement including stethoscope. Sanaphon® quarantees exact measurement values even for patients with heart rhythm disturbances.

- maximum error tollerance +3 mmHa
- supplied in zipper bag

With disinfectable latex free one-piece cuff.

- fast inflation of the cuff due to new ergonomic spoon design
- lifelong precision due to almost non-aging precision movement, with specially tempered copper-beryllium diaphragm for pressure-loading capacity up to 600 mmHg
- comfort air release valve, wearfree, with fine adjustment

# Exact precision that lasts a lifetime.

Made in Germany, 5 years warranty on calibration.

- shock-proof up to a falling height of 120 cm
- scale: Ø 52 mm black with red fluorescent pointer
- valve base and air duct with metal precision valve - two-component ABS casing
- metal threaded tube connection at the top of the casing for fast cuff exchange and
- ergonomical operation. - maximum error tolerance of ±3 mmHq
- weight: 173 g
- supplied in zipper bag
- latex free



32715 Precision air release valve with fine adjustment and wear-free

> Suitable for right or left handed users

### • 32715 RI-SAN® SPHYGMO High quality palm-style

sphygmomanometer with ergonomic design. Air release valve conveniently regulated by finger-tip control.

- calibrated nylon cuff with velcro
- latex-free bulb for pumping up the cuff - tube connection at the top of pressure gauge
- for unhindered blood pressure measurement - microfilter protects air release valve and measuring system
- specially tempered copper-beryllium diaphragm almost non-aging
- the precision movement quarantees reliable measurement
- diaphragm can be pressurized up to 600 mmHg without decalibrating the sphygmo.



### • 32717 PRECISA® N **SPHYGMO**

A typical Riester quality product. In metal with aluminium housing and single tube plua-in connection.

- calibrated nylon cuff with velcro.
- latex-free bulb, and metal valve base
- ergonomic grip of stainless steel - microfilter protects air release valve and measuring system
- specially tempered copper-beryllium diaphragm, with precision movement and almost non-aging - diaphragm pressure-loading capacity up to 600 mmHa
- scale, from 0 to 300 mmHq, ±3 mmHq Supplied with synthetic leather bag.



MINIMUS® is a reliable, durable and elegant palm model aneroid chrome-plated manometer with integral latex-free bulb and air release valve for one hand use, provided with a stainless steel handle, Luer Lock connection. calibrated black nylon velcro closure cuff and 1 tube bladder. Supplied in a nice synthetic leather bag.

# KOBOLD SPHYGMOMANOMETER BY ERKA

- 32691 BLACK KOBOLD with gray cuff 223.20493
- 32695 GREY KOBOLD SET with 3 ped. "Superb" cuffs 227.71.393
- 32696 GREY KOBOLD SET with 6 "Superb" cuffs 227.71.195 Elegant and compact, single tube sphygmomanometer for frequent use in clinic and consu Iting room. Precision manometer, anodised aluminium 0 48 mm. Sensitively adjustable air reduction valve, high quality chrome finish. Scale: 300 mmHg, 2 mm scale division. New technology with air intake via the manometer capsule in the specially tempered copper-beryllium membrane. Codes 32693, 32695, 32696 are latex free. Made in Germany.

### **ERKA "SUPERB" GREEN CUFFS**

All ERKA Green cuff products are PVC, demp and latexfree, every one is individually tested prior to delivery and guaranteed for 50,000 inflation cycles. They are equipped with clearly marked size and positioning features for the most accurate possible measurements. The soft, easy to disinfect, biocompatible materials ensure maximum patient comfort. Conform to ANSI/AAMI SP10 standard

• 32891 PEDIATRIC "SUPERB" CUFF 1 TUBE 20.5 - 28 cm - grey • 32892 ADULT "SUPERB" CUFF 1 TUBE 27-35 cm - grey - spare





# ERKA.







- 32688 ERKA PERFECT 201.204.82 dial Ø 48 mm - 2 tubes green Sphygmomanometer with screw valve for sensitive adjustments, velcro cuff and case. - manometer housing brass chromed plated
- membrane-protection 2-tube technology
- measuring range 0-300 mmHg ±1%
   Made in Germany. 3 year warranty.
   32877 PEDIATRIC "SUPERB" CUFF TWIN
- TUBE 20.5 28 cm grey
   32878 ADULT "SUPERB" CUFF TWIN
  TUBE 27-35 cm grey spare





- It offers oustanding ergonomics and simple adaptation for left and right-handle users. It is manufactured from shock-resistant polycarbonate and has passed the shock test according to AAMI SP9. The sight glass is chemically stable and unbreakable. The brass valve screw works smoothly and is adjustable to exact settings. MR compatibility. Measuring range 0-300 mmHg ±1%. Supplied with pouch. Made in Germany.
- 4 year warranty hand held, 2 year manometer.

   32891 PEDIATRIC "SUPERB" CUFF 1
- TUBE 20.5 28 cm grey
   32892 ADULT "SUPERB" CUFF 1 TUBE
  27-35 cm grey spare

### • 32697 ERKA SWITCH SIMPLEX dial Ø 56 mm - twin tubes grey -294.408.94

ERKA.

It is manufactured from shock-resistant polycarbonate and has passed the shock test according to AAMI SP9. The sight glass is chemically stable and unbreakable.

The brass valve screw works smoothly and is adjustable to exact settings. Measuring range 0-300 mmHg ±1%. Black velcro cuff. Supplied with pouch. Magnetic Resonance (MR) compatibility. Made in Germany. 2 year warranty.

# BOSTON SPHYGMO 🔲 G5® AND G7® HEINE SPHYGMO



• 32731 BOSTON SPHYGMO - adult - black cuff

Strong durable and elegant palm model aneroid metal zinc-alloy manometer with integral PVC bulb and air release valve for one hand use, provided with a special left and right hand adjustable handle, nylon velcro closure calibrated cuff and 1 tube TPU

bladder. Easy to read: large dial Ø 60 mm. Unique push button air release valve offers precise mini-deflation. Special PVC patented ribber bulb. Latex free. Supplied with a nice nylon carrying bag. Multilanguage box and manual: GB, FR, IT, ES, PT, DE, GR, Arab.



32737 GAMMA "G5®" HEINE SPHYGMO - plastic manometer - M-000.09.230
 32741 GAMMA "G5®" HEINE SPHYGMO - plastic manometer
 Same as 32737, but supplied without carrying bag.
 32739 GAMMA "G7®" HEINE SPHYGMO - aluminium manometer -

 32739 GAMMA "G7®" HEINE SPHYGMO - aluminium manometer M-000.09.232

With the new latex free G5° and G7° Heine, GIMA offers an aneroid sphygmomanometer of the highest quality of design and function with unequalled value for money. A modern, functional design combined with exceptional precision of measurement and durability make Heine G5° and

G7® ideal for long-term use in clinic and practice environments.

- latex-free

- exceptionally-strong housing construction with triple-mounted, **shockproof** movement.

 impact-resistant housing crafted in special, shockabsorbing materials incorporate the latest advances in injection-moulding technology.

- a microfilter protects the valve and movement.
 - oversized inflator speeds up cuff inflation.
 Made in Germany. 5 years warranty (G5),
 10 years warranty (G7).

GS\* and G7\* (excluding 32741)

G5® and G7® (excluding 32741) are supplied with high quality HEINE carrying bag.

# WELCH ALLYN® DURA SHOCK™ DS55 SPHYGMOMANOMETER



### • 32700 DURA SHOCK DS55 SILVER LINE - DS-5501-189


Welch Allyn's DS55 sphygmomanometer incorporating shock-resistant DuraShock technology offers practical benefits compared to traditional aneroid sphygmomanometers. This is especially beneficial in busy medical environments where equipment needs to be as robust as possible.

With DuraShock Technology, Welch Allyn B.P. gauges:

- remain in calibration longer than traditional aneroid B.P. gauges, providing you with more accurate readings.

 do not need to be replaced as often as traditional aneroid B.P. gauges, giving you a lower lifetime cost.

- have the only gauge capable of passing AAMI's shock-resistant specification of surviving a 76 cm drop onto a hard surface and remaining in calibration.



### How DuraShock technology works

In traditional aneroid sphygmomanometer design, several delicate gears and springs convert and amplify vertical movement of the pinion to rotational movement to turn the pointer.

The DuraShock gear-free design uses a single helix spring to directly convert the vertical movement of the pinion to rotation of the pointer without the use of a multi-step gear arrangement.

By creating a gear-free design, the Welch Allyn Durashock has fewer moving parts providing a gauge which is shock resistant and lighter than traditional gauges. Until now, a dropped sphygmomanometer required

The DuraShock can fall 76 cm onto a hard surface and still remain accurate. It is the only gauge capable of meeting the AAMI Shock Position transitions.



• 32825 PEDIATRIC CUFF 16-22 cm - optional 32827 ADULT CUFF 22-32 cm - spare • 32828 LARGE ADULT CUFF 32-45 cm - optional

**TECHNICAL SPECIFICATIONS (32800, 32801)** 

• 32801 GREEN MERCURY FREE SPHYGMO - on trolley with basket

Size: 360x96x66 mm (32800)

Face plate with easy-to-read graduated scale.

Basket for convenient accessory storage.

• 32883 GLASS TUBE - spare for EMPIRE

Coiled tubing extensible to 3 m.

Made in Germany

Maximum reading 300 mmHg ±3 mmHg. Mercury lock.

With latex free bulb and chromed-plated air release valve.

Measuring range: 20-280 mmHg


Power supply: battery Accuracy: pressure: ±3 mmHa • 32758 UM-101 MERCURY FREE SPHYGMOMANOMETER - desk • 32775 UM-102A MERCURY FREE SPHYGMOMANOMETER - desk

• 32776 UM-102B MERCURY FREE SPHYGMOMANOMETER - trolley

Measuring range - pressure - pulse:

TECHNICAL SPECIFICATIONS SPECIFICATIONS
360x96x66 mm (32775)
0-300 mmHg ±3 mmHg
40-180 beats/minute ±5% (32775-6)
30-200 beats/minute ±5% (32758)

MERCURIAL SPHYGMOMANOMETERS: DESK, WALL, TROLLEY



ERKA VARIO DESK WALL AND MOBILE - MADE IN GERMANY

• 32671 VARIO - desk - adult cuff - 285.20.481

• 32672 VARIO - wall - adult cuff - 288.20.481+295.00.003

 32673 VARIO - trolley Ø 50 cm - adult cuff+288.20.481+995.00.003 Superior quality product, made in Germany, for use in consulting rooms or hospital. The Vario model consists of a high precision manometer in a high quality ABS housing with an integrated fastening spigot for individual variable swivelling, a big cuff basket in white powder coated sheet steel, a bulb holder and spiral tubing with bulb and air release valve. This high quality chromium-plated valve makes sensitive adjustments easy. The 150 mm scale is equipped with a mirrored exterior ring and non-reflective manometer glass.

• 32898 PEDIATRIC "SUPERB" CUFF 2 TUBES - 20.5-28 cm (arm circumference)


• 32899 ADULT "SUPERB" CUFF 2 TUBES - 27-35 cm (arm circumference) - spare

• 32900 LARGE "SUPERB" CUFF 2 TUBES - 34-43 cm (arm circumference)

**TECHNICAL SPECIFICATIONS** Height with basket: 260 mm (32672-3) Width with basket: 180 mm (32672-3) Depth with basket: 120 mm (32672-3) Graduation: 0-300 mmHg ±3 mmHg

Weight with basket: 1,350 g Height of trolley: 830-1,360 mm (adjustable) Tubing system Ø 18-25 mm up to 60 dea





• 32742 RIESTER BIG BEN® - rail (clamp code 32766 and rail not included)

• 32743 RIESTER BIG BEN® - wall Rotation 130°, 65° right, 65° left

• 32746 RIESTER BIG BEN® - trolley Ø 54 cm

Aneroid sphygmomanometer, made of resistant plastic, with large dial (147 mm) and white pointer on black dial plate for easy-to-read measurements from 0 mmHg to 300 mmHg. Basket on back for cuff storage after use. Velcro-closure black cuff 2 tubes, and long coil tubing Latex free Quality product: made in Germany.

• 32766 RAIL CLAMP

Universal clamp (for code 32742) for any rail.







32939

# **OMRON PROFESSIONAL B.P. MONITOR**

• 32936 OMRON DIGITAL AUTOMA-TIC B.P. MONITOR HEM-907 Professional B.P. monitor designed for clinical use in professional settings. - gold standard accuracy 90 - validated according to international protocols: 1- Associa-

tion for the Advancement of Medical Instrumentation (AAMI)

249

2- European Society of Hypertension

- International Protocol (ESH - IP)

- intellisense technology - irregular pulse indicator

- 3 modes of operation: single mode, average mode, auscultation (manual mode)

Supplied with battery pack, adult cuff (22-32 cm). AC adapter

Made in Japan • 32937 ADULT LARGE CUFF 32-42 cm • 32939 TROLLEY FOR OMRON HEM-907

**TECHNICAL SPECIFICATIONS** Method pressure: 0-299 mmHg ± 3 mmHg or 2% Measurement range: pulse rate: 30-199 beats/min ± 5% of reading automatic inflation with pumping Inflation Deflation: automatic deflation by electromagneti control valve 32936

automatic rapid air release by Air release electromagnetic control valve electrostatic capacity semi-conductor pressure sensor AC adapter (230 VAC, 50 Hz, 20 VA)

Power supply Battery pack (4.8 VDC, 6W) on method: Class II B type Dimension: 139x203x131 mm (5.1/2"x8"x5.1/6")

approx. 910 g EN 1060, EN60601-1-1 - 2007 Weight: Complies with

Range 0-300 mmHg. PVC latex free.

Same as 32769, made in Japan.

• 32760 YTON MERCURIAL SPHYGMO - wall

32764 KENZ MERCURIAL SPHYGMO - trolley

storage compartment. 0-300 mmHg. PVC latex free.

• 32769 YTON MERCURIAL SPHYGMO - trolley - made in China

Mercury sphygmomanometers with velcro cuff (2 tubes) and

# DALLAS SPHYGMO: WALL AND TROLLEY DENVER SPHYGMO



All DALLAS sphygmos are provided with extra large dial plate (Ø 150 mm) for easy reading, black nylon calibrated cuff and latex quality inflation system and bladder. Scale 0-300 mmHg.

# • 32744 DENVER SPHYGMOMANOMETER -

trolley - adult cuff Trolley sphygmomanometer, light but with high stability and 360° swivelling castors. Adjustable height (90 to 135 cm) with metal basket. Square-shaped-dial 145x145 mm.

Nvlon cuff, 2-tube adult TPU bladder. PVC bulb, dual use air-release valve

with spring, spiral PVC tube (1.8 m).
CALIBRATED NYLON CUFFS • 32839 CHILD CUFF - black ( 6 0123

• 32850 ADULT CUFF - black - spare • 32841 ADULT LARGE CUFF - black

All cuffs with 2 tubes TPU bladder.



32745

32804

# DAYTON DESK/WALL SPHYGMO

32747

### • 32745 DAYTON SPHYGMO - desk/wall model

Provided with big dial (Ø 113 mm) for easy reading. Basket with handle easy to move and carry. Nylon cuff with D ring. Wall fixing. Size: 130x130x135 mm - Weight: 180g Measuring range: 0-300 mmHg ± 3 mmHg.

# JOLLY DIGITAL B.P. MONITOR



### • 32777 JOLLY DIGITAL BLOOD PRESSURE MONITOR

- Professional Blood Pressure monitor for medical use.
- large easy-to-read illuminated LCD display 86x74 mm
- WHO classification
- arrhythmia detection (IHB)
- 4-person memory zone 30 memory space each
- average of all saved measured values and morning and evening blood pressure of the last 7 days - time and date
- automatic switch-off
- Multilanguage manual and box: GB, FR, IT, ES, PT, DE, PL, GR. • 32922 CUFF - adult - 22-30 cm (8-11") - black - spare
- 32923 CUFF adult large 30-42 cm (11-16") grev
- 32920 CUFF adult extra large 42-48 cm (16-18.2") grey

# TECHNICAL SPECIFICATIONS

Measurement system: Measurement range:

Oscillometric method Pressure: 0~300 mmHg ±3 mmHg Pulse: 40~180 pulse/min. ±5% 4x1.5 AAA batteries included Outside dimension 150x95xh 65 mm Weight: approx 235 g (without batteries)





### • 32803 DOMINO DIGITAL BLOOD PRESSURE MONITOR

• 32804 DOMINO DIGITAL B.P. MONITOR on trolley with hasket

Professional Blood Pressure monitor for hospital and medical use.

- extra large LCD display with innovative design
- date/time/ambient temperature (°C/°F) display
- IHB Irregular heartbeat detector
- 120 memories (60 sets for 2 users)
- alarm clock reminding function
- WHO blood pressure classification indicator
- 32802 AC ADAPTOR

External dimension

• 32809 ADULT CUFF - spare

### 32865 COILED TUBING EXTENSION 3 m (42/45 spirals)

Measuring range Pressure + 3 mmHa Pulse: + 5% Accuracy: Power supply

TECHNICAL SPECIFICATIONS Pressure - 40 ~ 260 mmHg Pulse: 40 ~ 160 beats/min 4x "AA" batteries or AC adaptor (option 158(L)x120(W)x127(H) mm

# X-LIFE AUTOMATIC DIGITAL B.P. MONITORS - ESH VALIDATED



Size: 74.5x74x30 mm Weight: 95 g LCD size 34 5x42 mm Cuff size for arm circumferences 13.5-19.5 cm

**( €** 0476 32926

European Society



• 32924 X-LIFE B.P. MONITOR - arm

• 32926 X-LIFE B.P. MONITOR - wrist

Accurate and precise automatic digital blood pressure meters for smooth and fast measurements with innovative functions:

- IHB: irregular heartbeat detector
- WHO risk category indicator (classifies your measurements in 6 stages of risk, from optimal to severe hypertension)
- proven clinically to meet European Society of Hypertension **ESH** protocol
- easy to read, wide angle display
- 120 memories for 3 users: 3 zones of 40 memories each start/stop unique button, with blue backlight
- multilanguage manual and box: GB, FR, IT, ES
- memory average: automatically average last 3 memories
- 32925 SPARE CUFF for 32924 adult

### • 32927 AC ADAPTOR for 32924 TECHNICAL SPECIFICATIONS

Measuring method: oscillometric Measuring range: 0-300 mmHa pressure: 40-199 bpm pulse: Accuracy: ±3 mmHg

pressure: pulse: Power supply arm type

4xAA alkaline batteries wrist type:

2xAAA alkaline batteries arm type:

300 measures

# SMART AUTOMATIC DIGITAL B.P. MONITOR - ESH VALIDATION

Battery life:



- 32921 SMART AUTOMATIC B.P. MONITOR with adult cuff Compact, fully logic, multiuser, B.P.M. with innovative features:
- smart inflation technology for automatic pumping to proper pressure - WHO blood pressure indicator
- IHB Irregular Heartbeat Detection
- average value of latest 3 readings
- 2x60 memories, date and time
- displays systolic, diastolic and pulse rate separately
- displays systicinic, diastolic and public rate separately
   multilanguage manual and box: GB, FR, IT, DE, ES, PT, PL, GR, Arabic
   32922 CUFF adult 22-30 cm (8-11") black spare
   32923 CUFF adult large 30-42 cm (11-16") gray

• 32920 CUFF - adult extra large - 42-48 cm (16-18.2") - gray

TECHNICAL SPECIFICATIONS

Measuring method: oscillometric, automatic inflation and measurement cuff pressure: 0-300 mmHg ±3 mmHg Measuring range: pulse rate: systolic: 40~180 beats/min ±5% of reading 60-260 mmHg

diastolic 40-199 mmHa 4x"AA" batteries 1.5 V

Dimensions 138x98x48 mm

130300.49 (iiiii 211 g (excluding batteries) for arm circumferences 22-30 cm, 30-42 cm or 42-48 cm

# SMART AUTOMATIC DIGITAL WRIST B.P. MONITOR




- 32918 SMART AUTOMATIC WRIST B.P. MONITOR
- Compact, fully logic, B.P.M. with innovative features: - smart inflation technology for automatic pumping to proper pressure
- WHO blood pressure indicator
- IHB Irregular Heartbeat Detection
- average value of latest 3 readings
- 2x60 memories, date and time
- displays systolic, diastolic and pulse rate separately
- multilanguage manual and box: GB, FR, IT, DE, ES, PT, PL, GR, Arabic

### **TECHNICAL SPECIFICATIONS**

oscillometric, automatic air inflation and measurement 0-295 mmHg ±3 mmHg 40~180 beats/min ±5% of reading Measuring method: Cuff pressure: Pulse rate range 30-280 mmHg Range of measurer 2x"AAA" batteries 1.5 V

Power supply: Dimensions: 84x64x28 mm 110 g (excluding batteries) Weight:

Wrist cuff: applicable for wrist circumferences 14-19.5 cm



Both units are supplied with multilanguage box and manual (GB, IT, FR, ES, PT, GR, DE, Arabic,

DEFLATION

**C** €0476

• 32787 GIMA AUTOMATIC B.P. MONITOR

• 32788 SPARE CUFF - adult

**(** € 0476

Innovative design digital fully automatic blood pressure meter: Reliable digital blood pressure monitor with following features:

32787

- one-touch measurement

- 30 sec. measurement time for normal blood pressure - 4 persons use / 30 memories each - power saving system

### **TECHNICAL SPECIFICATIONS**

Measuring method: oscillometric Display: Systol, Diastol and Pulse

Measuring range: 20~280 mmHg (cuff pressure) 40~195 beats/min (pulse rate) Pressure: ± 3 mmHg Accuracy Pulse: +5% of reading

Power supply: 4x "AA" batteries Dimensions: 140x120x70 mm Weight: 300 g (ex. batteries) Arm cuff: 22-34 cm



**( 6** 0197

### 32786 GIMA AUTOMATIC WRIST B.P. MONITOR

- one touch automatic inflation and deflation


32786

- large LCD display with date and time
- 2 person use / 60 memories each power saving system

### TECHNICAL SPECIFICATIONS

Measuring method: oscillometric Measuring range: Pressure 20~280 mmHg Pulse 40~195

Pressure: ± 3 mmHg Pulse: ±5% of reading



- large easy to read LCD display, WHO

- 4 groups x 30 times with time and



# ANDON VALUE DIGITAL B.P MONITOR

- 32901 ANDON B.P. MONITOR
- 32922 CUFF adult 22-30 cm • 32923 CUFF - adult large - 30-42 cm
- 32920 CUFF adult extra large 42-48 cm

Measurement system Measurement range

Power Source Dimensions - weight LCD size

TECHNICAL SPECIFICATIONS

Oscillometric method Pressure: 0~300 mmHg ±3 mmHg Pulse: 40~180 pulse/min ±5% 4x1.5 V AAA batteries - not included 107x80xh 52 mm - 170 g (ex. batteries)

evening blood pressure - arrhythmia detection (HB) - automatic switch-off.

for the last 7 days

Voice helps user, explaining

how to measure pressure, and telling obtained

ESH

values and morning and

blood pressure indicator

date stamp

- average of all saved measured ESH Cuff circumfe-

rence: 22-30 cm

• 32940 TALKING BLOOD PRESSURE MONITOR\* - GB, FR, ES, PT, Arabic

32942 TALKING BLOOD PRESSURE MONITOR\*\* - IT, RO, BG, HU, RU

• 32941 TALKING BLOOD PRESSURE MONITOR\*\* - IT, SE, FI, DE, TR

TALKING B.P. MONITOR

WITH VOICE

 large easy-to-read LCD display

- WHO classification

- time and date

- 60 memories automatic switch-off illuminated operation button

arrhythmia detection (IHR)

- for arm circumference 22-30 cm

Features:

# FULLY AUTOMATIC B.P.M.



- 32947 WIDE BLOOD PRESSURE MONITOR
- easy to use and clear LCD display
- 60 memories
- automatic switch-off
- for upper arm circumference 22-30 cm
- 32922 ADULT CUFF 22-30 cm black spare
- 32923 ADULT L CUFF 30-42 cm grev

• 32920 ADULT XL CUFF 42-48 cm - grey TECHNICAL SPECIFICATIONS

Measurement system Oscillometric method

Dimensions - weight LCD size

Measurement range Pressure: 0~300 mmHg ±3 mmHg Pulse: 40~180 pulse/min ±5% 4xAAA batteries 220x66xh 43 mm - 230 g (without batteries)

102.2x27.3 mm

BHS

• 32922 ADULT CUFF 22-30 cm - black - spare

• 32943 AC ADAPTER 230V - 50 Hz • 32923 ADULT L CUFF 30-42 cm - grev • 32920 ADULT XL CUFF 42-48 cm - grey

TECHNICAL SPECIFICATIONS

Measurement range Accuracy Power Source Dimensions - Weight LCD size

Oscillometric method Pressure: 0~300 mmHg Pulse: 40~180 pulse/min Pressure: ±3 mmHa Pulse: ±5% 4xAA batteries, optional AC/DC 6V adapte 153x108xh 60 mm - 290 g (without batteries)

# OMRON DIGITAL BLOOD PRESSURE METERS

The Intellisense™ technology ensures that the right Intelli inflation pressure is automatically detected.
It detects irregular pulses and decides fully automatically

Sense if the measurement result is usable or the measurement

needs to be repeated. Only accurate results are displayed.

OMRON BLOOD PRESSURE MONITOR USER GUIDE						
	M7 INTELLI IT	M6 COMFORT IT	M3	M2	RS3	
Clinically validated*	X	X	X	X	X	
Intellisense technology	Х	Х	X	X	X	
Irregular heartbeats detector	х	Х	х	х	X	
Cuff position detector	Х	Х	Х	Х	Х	
Cuff	Moulded comfort cuff 22-42 cm	Moulded comfort cuff 22-42 cm	Long lasting cuff 22-42 cm	Cuff 22-32 cm	Wrist cuff 13,5-21,5 cm	
Memory measurements	100 for 2 users	100 for 2 users	60 for 2 users	30	60	
Movement detector	X	Х	Х			
Blood pressure light indicator**	х	х	х			
Average 3 last measurements***	х	Х	х			
Morning hypertension	Х	X				
Intelli Wrap technology****	Х	Х				
PC connection	Х					
*To verify validations, please	e see www.dabled	lucational.org				

(85 systolic pressure and/or 135 diastolic pressure)



• 32944 OMRON M2 HEM-7121-E with Easy cuff 22-32 cm. Multilanguage box and manual: GB, FR, IT, ES, DE, NL, RU, TR, Arabic. • 32933 ADULT EASY CUFF 22-32 cm -HEM-CR24 - spare

32929 AC/DC ADAPTOR



• 32932 OMRON RS3 HEM-6130-E Multilanguage manual and box: FR, IT, NL, DE, Arabic

• 32928 OMRON M3 HEM-7131-E With Easy cuff 22-42 cm. Multilanguage box and manual: GB. FR. IT. ES. DE. NL. RU. TR. Arabic. • 32938 ADULT EASY CUFF 22-42 cm -

Pressure

HEM-RML31 - spare 32929 AC/DC ADAPTOR

Memory (with date and time)

Battery life (N° of measurements):

Protection against electric shock

Measuring method

Measuring range:

Inflation:

Deflation:

Power source:

Rating:

• 32948 OMRON M6 COMFORT -HEM-7321-E With Intelli wrap cuff technology.

incorrect positioning

€ 0197

HEM-7322T-E

Cuff 22-42 cm.

• 32949 OMRON M7 INTELLI IT -

With Intelli wrap cuff technology.

The connect OMRON app for smartphone

allows to monitor parameters, create

personalized programs, download data

Cuff 22-42 cm. Multilanguage box and manual: GB, FR, IT, ES, DE, NL, RU, TR, Arabic.

OMRON connect

mobile application

or iPhone/Androi

32929 AC/DC ADAPTOR

TECHNICA	L SPECIFICATIONS				
32944 M2	32928 M3	32948 M6 32949 M7	32932 RS3		
oscillometric-					
	0 mmHq to 299 n	nmHa ± 3 mmHa ——			
		of display reading -			
30	60x2 users	100x2 users	60		
fuzzy logic controlled by electric pump automatic					
automatic pressure release valve———————————————————————————————————					

6VCC 4W 4 "AA" batteries 1.5 V -----4 "AA" batteries 1.5 V --2 "AAA"batteries 1.5 \ 1000 1000 1000 300 mally powered ME equipment -(when using batteries)

280+170 a Weight (console+cuff) whitout batteries 380+163 a 101 a 250+130 a 103x80 xh 129 mm 107x141xh 79 mm 124x161xh 90 mm 78x60 xh 21 mm nylon and polyester

Cuff materials: 13.5-21.5 (wrist) Measurable circumference 22-32 cm 22-42 (arm) 22-42 (arm)

# MICROLIFE AFIB BLOOD PRESSURE MONITOR - STROKE PREVENTION



- 32868 MICROLIFE WatchBP Home A (Professional use) + SOFTWARE - detection of atrial fibrillation (specific heart arrhythmia)
- embedded ESH/AHA measurement guidelines lead to accurate home measurement data physician can trust in - automated data tabulations displays averages for morning, evening and
- overall measurement - clinically tested (BHS protocol)
- MAM technology (automatic analysis of 3 consecutive measurements)
- 250 Data memory in «USUAL» mode - USB port and mains adapter port
- low battery indication
- 4x1.5 V AA batteries
- Supplied with carrying bag, USB cable, soft cuff 22-32 cm software (GB) and manual (GB, IT, FR, ES). Other languages available from web (DE, CZ, DK, GR, FI, HU, NL, NO, PL, RO, RU, SE, SK, SI, YU, UA).
- 32869 ADULT LARGE CUFF 32-42 cm 32864 ADAPTER DC 6V, 600 mA

# microlife

### DETECTION OF ATRIAL FIBRILLATION

### MICROLIFE AFIB technology

An innovative and patented technology for the early detection of Atrial fibrillation (AF) More than 30,000 fatal strokes can be prevented within the European Union by using Microlife AFIB Technology in primary care The new Microlife AFIB technology allows simultaneous blood pressure measurement and AF screening.

Microlife AFIB technology detects AF with high sensitivity (97-100%) and specificity (89%) as demonstrated in several clinical studies. Nice guidelines for "Diagnosis and assessment of hypertension" recommended using AFIB screening for routine blood pressure measurement in primary care.

AF screening by using a Microlife AFIB device is highly recommended in patients that have to monitor their blood pressure while at home

### • 32867 MICROLIFE AFIB EASY (Home use)

- detection of atrial fibrillation (specific heart arrhythmia)
- clinically tested (BHS protocol) MAM technology (automatic analysis of 3 consecutive measurements)
- 1 Data memory
- traffic light indicator
- low battery indicator
- rechargeable battery-friendly
- mains adapter port - equipped with world's latest
- technologies
- Clinically reliable measurements with AFIB & MAM
- 5 vears warrantv
- Supplied with carrying bag, preformed conical cuff 22-42 cm and manual (GB, FR, IT, DE). Other languages available from web: AR, BG, DK, NL, EE, FI, GR, KZ, LV, LT, NO, PT, RO, RU, ES, SE, UA.
- 32866 ADAPTER DC 6V, 600 mA
- 32884 ADULT CUFF M-L 22-42 cm spare
- 32885 ADULT CUFF L-XL 32-52 cm

# GEMINI BLUETOOTH 4.0 SPHYGMOMANOMETER



- 32908 GEMINI BLUETOOTH SPHYGMOMANOMETER Electronic sphygmomanometer with fully automatic measurement of blood pressure.
- wide blue mode backlight LED display 12.8x5 cm. 60x2 groups memory
- average function for the last 3 measured values
- IHB function (irregular beat detection)
- WHO graduation (B.P. classification indicator)
- Bluetooth 4.0 connectivity, free APP (iOS and Android) to manage and track BP measurements

### • 32909 DC 6V POWER ADAPTER

### TECHNICAL SPECIFICATIONS

MWI Technology (Measuring While Inflating) Pressure: 0~300 mmHg ± 3 mmHg Pulse: 40~199 beats/min + 5% of reading

4xAAA batteries (not included) DC 6V power adaptor - optional

Arm cuff: 22-32 cm

# ADULT AND PEDIATRIC B.P. MONITOR WITH SpO<sub>3</sub> OPTION 32902 LEO ELECTRONIC SPHYGMOMANOMETER -



TECHNICAL SPECIFICATIONS SPHYGMO

Inflation - Deflation: automatic inflation - automatic multistep deflation

Measurement method: oscillometric Measurement range: 0-38.67 kPa (0-290 mmHg)

Accuracy: static pressure: ±0.4 kPa (±3 mmHg)

Display: 2.8" colour LCD screen, USB interface

Power: four "AA" batteries or optional power adapter Safety: class II device type BF applied part Dimension - Weight: 130x110x80 mm - 300 g

Resolution: 1 mmHg

**C** € 0476

Electronic sphygmomanometer with fully automatic measurement of blood pressure and large, high definition colour LCD display. Suitable for adult, pediatric and neonatal use.

- data storage (3 users) for up to 100 groups of data
- automatic one-touch operation
- alarm function with possibility to set alarm limits
- dual scales: kPa and mmHg

- selection of five cuff sizes
   automatic power off
   ontional SpO
   ontional Sp optional SpO,
  - PR range: 30-250 bpm, (resolution 1 bpm)

• 80556 POWER ADAPTOR PR accuracy: ± 2 bpm or ± 2% (select larger) SPO, PROBES\*

code 32903 SpO<sub>2</sub> reusable adult probe 33755 SpO<sub>2</sub> disposable adult probe 33756 SpO, disposable child probe (3-20 kg) 33757 SpO<sub>3</sub> disposable pediatric probe (10-50 kg)

80558 Extension cable for SpO, probes

*All SpO <sub>2</sub>	*All SpO <sub>2</sub> probes need extension cable						
GIMA code	CUFFS	Size	Suitable for				
80551	Small	6-11 cm	Child small				
80552	Small/medium	10-19 cm	Child				
80553	Medium	18-26 cm	Adult				
80554	Large	22-32 cm	Adult large				
80555	X-Large	33-47 cm	Adult extra large				

# A&D BLUETOOTH BP MONITOR



### 32907 UA-767 BLUETOOTH BLOOD PRESSURE MONITOR

- B.P.M. clinically proven in accuracy, with Bluetooth® - compatibility with Bluetooth® Android receivers, iOS and Windows
- built-in real time clock
- 200-measurement memory
- irregular Heart Beat Indicator
- extra-large 3-line display for easier reading of results
- one-touch measurement
- comfortable Slim Fit cuff 22-32 cm (8.7"-12.6")
- Supplied with carrying case, batteries and multilanguage manual (GB, FR, ES, IT, DE)

### Method

Display type

Accuracy Pressurization Depressurization Power supply

### TECHNICAL SPECIFICATIONS Oscillometric

Digital, LCD16 mm /10 mm digit height, pressure and pulse displayed simultaneously 20 - 280 mmHg (pressure) I 40 - 200 pulse/minute (pulse)

Dimensions / Weight 64x147x110 mm / Approximately 300 g (0.66 lb) Wireless communication Bluetooth 2.1 Class 1 SSP, SPP Compatible with 2 net QUALCOMM LIFE platfor

± 3 mmHg (pressure) I ± 5% (pulse) Automatic pressurization by micro pump Constant speed exhaust valve Automatic exhaust by electromagnetic valve 4AA alkaline batteries (R6P) for 450 measurements

# 32780

# 24 HOURS BLOOD PRESSURE MONITOR SYSTEM

### • 32780 DAILY ABPM + software A simple, economic and small size unit for 24 hours ambulatory

blood pressure monitoring. Main features:

- 4 memory zones, 99 readings each (total 396 measurements)
- patient-friendly performance at affordable price
- automatic measurement by two predetermined intervals - irregular Heartbeat detector, detect a disturbance in the
- regular rhythm of the heartbeat - big LCD display showing measuring date and time
- 5 mode average function, by hour, day, week, month and overall - transfer to PC via software and USB plug of measured values

- lithium battery, long - time measurement

Supplied with arm cuff (22-34 cm) carrying bag and software.

### • 32783 ADULT CUFF - spare

• 32784 LITHIUM BATTERY - spare

TECHNICAL SPECIFICATIONS

Measuring type: Oscillometric system Measuring range: Pressure: 20~80 mmHg ± 3 mmHg Pulse: 40~195 beats/min ± 5%

Power supply: Lithium Battery, 3.7 V 1050mA Weight: Approx. 260g (including cuff, ex. batteries) External dimension: 184x84x33 mm


# 24 HOURS ABPM, SpO, AND PULSE RATE AMBULATORY MONITOR

- 35110 GIMA ABPM + Pulse rate with software
- 35112 GIMA ABPM + Pulse rate with software and Bluetooth
- 35111 GIMA ABPM + Pulse rate + SpO, with software GIMA ABPM module measures the blood pressure using the oscillometric method with step deflation.

Two modes of measurement: manual and automatic. Each mode displays the diastolic, systolic and mean blood pressure. In the MANUAL mode, only one measurement is conducted for each time.

In the AUTO mode, the measurement is cycled; you can set the interval time to 5/10/15/20/30/45/60/90 min. (35111) or 15/30/60/120/240 min. (35110, 35112)

- compact and portable, easy to use
- suitable for adult, pediatric and neonatal patient
- large colour LCD display of ABPM, SpO, and pulse rate
- adjustable audible and visual alarms
- real-time ambulatory monitoring 24 hours storage and review of date
- clinically proven accuracy
- all data can be transferred to a PC through Windows-based software or to a smartphone through Bluetooth (35112 only).
- 35113 CHILDREN CUFF arm circumference 18-26 cm
- 35114 ADULT CUFF arm circumference 25-35 cm
- 35115 ADULT LARGE CUFF arm circumference 33-47 cm



STANDARD ACCESSORIES

Carrying bag Software 3 nylon cuffs (pediatric, adult, adult large) - latex free SpO, probe (only code 35111) Cuff con Ratteries

Software (GR - IT) Cuff connection tube 1.5 m

### **TECHNICAL SPECIFICATIONS**

0

Display: colour LCD Power: two "AA". 1.5V alkaline batteries Dimension: 120x80x32 mm Weight: <350 g (including batteries)

SpO<sub>2</sub> (35111 only) Measurement range: 0-100% Resolution: 1% Accuracy: 70-100% ±2% Alarm range: 0-100%

Method: oscillometry Mode: manual/automatic/continuous Measurement range: 0-290 mmHg (0 KPa - 38.67 KPa)

Automatic measurement interval: 5, 10, 15, 30, 45, 60, 90, 120 min. (35111) 15, 30, 60, 120, 240 min. (35110, 35112)

Resolution: 1 mmHg Overpressure protection: 290 mmHa systolic 40-270 mmHg diastolic 20-235 mmHg Map 10-270 mmHg (35111 only)

### Pulse rate

Compact size: 12x7x3 cm, and light,

350 g only, including batterie

- creates a monitoring plan tailored to an individual patient

readings, heart rate, mean arterial pressure, blood pressure

PĞ Win reports include full disclosure of blood pressure

load and trend of BP values vs. time. Compatible with

Range: 0-250 bpm (35111) 40-240 bpm (35110, 35112)

Resolution: 1 bpm Accuracy: ±1 bpm Alarm range: 30-250 bpm

35111

Operating system Windows XP/Seven 8, 8.1 (at 32 & 64 bit)

# MT 10 - HANDHELD IMPEDANCE TYMPANOMETER

 33665 MT10 - HANDHELD TYMPANOMETER
 33666 MT10 - HANDHELD TYMPANOMETER WITH IPSI-REFLEX Professional handheld tympanometer for setting fast and reliable testing in an easy and cost effective way. Objective analysis

Fast and easy to operate and provides objective measures that cannot be obtained by otoscopy alone.

### Easy and fast tympanograms

Results can be obtained with little efforts and with no response required from the patient. This is especially beneficial when dealing with difficult-to-test patients or small children. Clinical application

Suitable for diagnostic use as tympanometer and (33666 only) reflex responses are all recorded with great detail. You can detect otitis media (a major cause of temporary or permanent hearing impairment in children), a perforated eardrum, cholesteotomas and certain neurological disorders. You can also check

tympanostomy tubes and follow up on post medical treatments. Ipsilateral Acoustic Reflex (33666 only)

Four different reflex tests at 500, 1,000, 2,000, 4,000 Hz may be performed per ear using either fixed or automatic intensity selection. Actual reflex characteristics are displayed on the screen.

30 patients in memory
Can hold test results of up to 30 patients, allowing to screen a large group of patients and print out the data at a later time. PC-integration with optional infrared USB interface and software. Full data-transfer to PC

33667 INTERFACE USB ADAPTER AND SOFTWARE BY IRDA PORT

equivalent ear canal volume 226 Hz

+200 daPa to -400 daPa

0.2 ml to 5 ml Typically 200-300 daPa/sec;

ipsilateral 500 Hz. 1 kHz. 2 kHz. 4 kHz

depending on ear & cavity volume +600 to -800 daPa

100 dB with 5 dB or 10 dB steps; 95 dB, 90 dB or 85 dB with 5 dB steps

Reflex pass/refer at each level tested; Maximum amplitude of each reflex

(seen on printed report and PC report)

# 33669

Interacoustics

disposable ear-tips (mixed sizes) 4x1.5 battery and manual in GB, DE, FR, IT, ES, SÉ, GR, PT, DK, FI, CZ, PL, LT, EE, HU, NL, NO, IS, RO, MK.

-400 to +200 daPa ipsi-reflex (33666 only) 30 patient memory PC integration

erannomic to hold but also offers the possibility of using the included handle to make it even more stable and lightweight as it can rest on your arm during the measurement.

Size: 19x8x4 cm excluding probe (length with probe 22.5 cm)

Weight 285 g without battery

• 33668 BET55 SET OF DISPOSABLE EAR-TIPS box of 139 mixed sizes

33669 SANIBEL MPTII PORTABLE THERMAL PRINTER

• 33670 THERMAL PAPER ROLLS - box of 3

### TECHNICAL SPECIFICATIONS Peak compliance; peak pressure, gradient;

Data manage Data storage:

Safety standards:

30 records. Any recording can be stored once the tympa-Data held:

nogram is viewed nogram and Reflex graphs and analysis for Left and/or Right Ear, Time and Date of recording, which ears were tested, whether or not the record has been printed and sent to a PC, parameters printed and sent to a PC.

and/or sent to a PC, parameters used for analysis Other data >30 days without main batteries fitted Internal backup: Battery Lifetime: Approx. 400 tests (Alkaline AA batteries) Supported printer

Martel MCP8830 or Sanibel MPTII Infra-red, IrDA hardware, 9600 baud Space for patient and clinician's details, Tympanogram analysis Information printed:

parameters, Tympanogram, Reflex analysis parameters, Reflex graph, S. N. of device, Last and Next Due Calibration dates IEC 60601-1. EMC: IEC 60601-1-2

Impedance standard: IEe 60645-5, Type 2 Tympanometer

# PA5 PEDIATRIC PORTABLE AUDIOMETER

# Interacoustics

Tympanometry Analysis performed:

Measurement mode

Reflex tone levels:

Four reflex levels:

Reflex analysis:

Ear volume measurement range:

Pressure limits (safety shut off):

Reflex measuremets (33666 only)

Probe tone:

Pressure levels:

Sweep speed:

# • 33601 PA5 AUDIOMETER • 33602 TDH39 AUDIOMETRIC HEAD PHONE

Paediatric portable audiometer with air conduction, free-field and visual stimulation capabilities. By means of a headphone it can be also used as a regular screening audiometer for adults. PA5 helps doctors in evaluating the auditory behaviour in neonates and infants till 24 months by means of specific tests: Auropalpebral Reflex (APR) test

APR test is a startle reflex of the eyelid elicited by relatively strong sounds that can be performed on neonates from the day of birth. It is not based on co-operation with the newborn child Conditioned Orientation Response (COR) test

Based on the "Orientation Reflex", a natural reflex movement elicited by sound or visual stimulation. If the visual stimulation elicits a reflex which is conditioned by a tone, the child will look towards the visual stimulation as soon as the tone is heard. If the conditioning is effective the child will look in the direction of the sound source even before the visual stimulation is presented Visual Reinforcement Audiometry (VRA) test

VRA test is an extension and modification of COR, where the cooperation with the child is less important. Not only the sound

localisation orientation reflex are accepted but also four other reactions: reflex reactions (body and face), search reactions, orientation reactions and spontaneous reactions.

Reflex audiometry and maturation of auditory response tests Different stimuli are presented in terms of intensity, frequency, duration, direction of sound in order to elicit proper reactions like waking-up, crying, astonishment, direct sound localization.

Supplied with GB manual and quick guide (GB, US, DE, FR, SE, IT, PT, DK, FI, ES, GR, CZ, PL, NL, NO, EE, HII SI) 33601

**TECHNICAL SPECIFICATIONS** 500, 1,000, 2,000, 3,000, 4,000 Hz

500, 1,000, 2,000, 3,000, 400 to 1.00 Warble tone, NB and WN Distance 50 cm: 2030-80dB HL in 10dB steps, for Warble Tone and WN 10/20-70dB for NB Distance 16 cm: increases intensity by 10 dB LWWH. 25x/x5x cm - 360 g ntensities:

Dimensions - weight: LxWxH
Power supply: 3AA batteries (included)

# BOEL STYLE PEDIATRIC AUDIOLOGY TEST (€

### • 33599 GIMA AUDIOTEST - pediatric audiology test for early detection of childhood deafness

The Boel test is a unique screening tool that tests the hearing abilities and child's response to a sound stimulus. even at an early age (between 6 to 10 months). GIMA audiotest is based on the BOEL test both for the ergonomics (designed to be held in the palm of the hand not visible to the child) and the standard sound of the bells. The two sound stimuli emitted by the audiometer reproduce a dull

low-frequency tone located at about 125-150 Hz and an acute high-frequency tone located at about 5.0-5.1 kHz in exactly the same way as the bells of the Boel test (amplitude 86dBA; 96dBA). Testing the child's response to these highly significant thresholds. Easy to use, with only two buttons for the selection of two frequencies, lightweight and battery-powered. 33599



# UP TO 52 HOURS AMBULATORY BLOOD PRESSURE MONITOR

### 33351 AM100 GIMA ABPM with adult cuff

The AM100 is a compact, lightweight instrument that provides a cost-effective solution for monitoring patient's blood pressure outside the clinical environment. AM100 employs the popular oscillometric technique of blood

pressure measurement. The simplicity of this technique provides for the quickest patient hook-up. AM100 interfaces with Win Pro PC Software for monitor programming as well as report editing and generation.

Oscillometric technology: quick hook-up, making it easy to use, saving your staff time Compact and quiet: silent operation and compact size aid

patient compliance. Low power consumption: requires only two "AA" batteries, making this unit much less expensive than others.

AM100 is supplied complete with software, adult cuff. carrying-bag, English manual and PC connection cable. • 33348 PEDIATRIC CUFF - arm circumference 18-27 cm

• 33349 ADULT CUFF - arm circumference 25-35 cm - spare • 33353 ADULT LARGE CUFF - arm circumference 33-40 cm

TECHNICAL SPECIFICATIONS Tecnique: Oscillometry with step deflation

Sample quantity: Over 250 sample of systolic, diastolic, MAP and heart rate

Blood pressure range: 25-260 mmHg ±3 mmHg Heart rate range: 40-200 bpm Display: Liquid crystal Recording duration: Up to 52 hours

Power source: 3 VDC/Two 1.5 V "AA" Alkaline

Sampling periods: 3 time periods

PG WIN PRO PC INTERFACE

with up to 3 specific time periods

generates concise clinical reports.



# AUDIOMETRIC BOOTHS - CONFORM TO 93/42/CEE - 2007/47/CE - Class I



• 33650 PRO 25 - 96x96x197 cm Portable, lightweight, sound proof booth, easy to install in few minutes. Interior finishing made of acoustic pyramid foam in anthracite grey. External finishing made of highly resistant, fire proof washable panel. Module for cable connection included. Made in Italy.

• 33651 TABLE - 79x50 cm

ACOUSTIC INSULATION							
Hertz		125	250	500	1000	2000	4000
PRO 25 PRO 28 PRO 30	dB	21.7	25.6	32.6	36.2	34.0	41.1

• 33649 PRO 28F - 96x96x197 cm New compact booth with an outstanding level of sound proofing and excellent acoustic thanks to innovative materials. Internal finishing made of fire proof, washable and very resistant fabric. Internal ventilation system. External finishing made of highly resistant, fireproof, washable panel. Module for cable connection included. Made in Italy.

33651

• 33651 TABLE 79x50 cm



- 33654 PRO 30 107x107x242" cm • 33653 PRO 30 - 132x132x242" cm • 33655 PRO 30 - 211x107x242" cm
- 33656 PRO 30 211x211x242" cm
- 33657 PRO 30 size on request

available any size from 1x1 to 3x3 Range with different sizes, with high noise reduction and ventilation system. External finishing made of highly resistant, fireproof, washable panel and aluminium frame. Module for cable connection included. Made in Italy.

- 33651 TABLE 79x50 cm
- 33652 RAMPS for wheelchair access

TECHNICAL SPECIFICATIONS						
	33650	33649	33654	33653	33655	33656
External size (cm):	96x96xh 197	96x96xh 197	107x107xh 242**	132x132xh 242"	211x107xh 242**	211x211xh 242**
Internal size (cm):	81x81xh 180	81x81xh 173.5	92x92xh 201	117x117xh 201	196x92xh 201	196x196xh 201
Door size cm:	55xh 168	55xh 168	75xh 200	75xh 200	75xh 200	75xh 200
opening:	Left/Right	Left/Right		Rig	ht*	
Windows size cm:	56xh 56	56xh 56		56xl	h 88	
material:			2 - crystal insula	ting safety glass		
Wall thickness cm:	7.5	7.5	7.5	7.5	7.5	7.5
Weight (kg):	198	233	255	317	356	552
Ventilation:	no	yes	yes	yes	yes	yes
Tested noise reduction dB at 1,000 Hz:	30.8	36.2	-	34	1.5	
Internal illumination power V-Hz:	230 -	50/60	-	86-265	- 50/60	
Norms:		Class I Me	dical Devices Eur	ropean Directive	93/42 CEE	
*Left opening available on request	"Height inclu	ides air ventilatio	n system (25 cm)	)		



internal illumination ventilation system (PRO 28, PRO 30 only) ISPM-15 wooden box for transport

# SINGLE USE TYMPANOMETER EARTIPS - FOR MOST BRANDS

Interacoustics®

Grason-Stadler®

Maico

MEDRx®



quickly move on to other tasks. Available in different sizes, with different shapes (mushroom and flanged ear tips for infants). The complete range makes it possible to accomodate all ear canal

shapes a	shapes and sizes. All Sanibel™ ear tips are latex free.						
GIMA code	SANIBEL™ AZE MUSHROOM EAR TIPS	Minimum order					
	Ear tip 6 mm - violet	bag of 100 pcs					
	Ear tip 7 mm - yellow	bag of 100 pcs					
53502	Ear tip 9 mm - green	bag of 100 pcs					
	Ear tip 10 mm - light blue	bag of 100 pcs					
	Ear tip 11 mm - white	bag of 100 pcs					
53505	Ear tip 13 mm - yellow	bag of 100 pcs					

VERIFIED COMPATIBILITY FOR SANIBEL™ AZE Tympstar™ AT235™ & AT235h™ with black probe tip AA222™ & AA220™ with black probe tip Grason-Stadler® Interacoustics<sup>1</sup>

MI24™, MI26™, MI34™, MI44™ with black probe tip Maico Kamplex<sup>6</sup>

coae		oraer
	Ear tip 3-5 mm - red	bag of 100 pcs
	Ear tip 4-7 mm - blue	bag of 100 pcs
53517	Ear tip 5-8 mm - yellow	bag of 100 pcs
GIMA code	SANIBEL™ ADI MUSHROOM EAR TIPS	Minimum order
53520	Ear tip 7 mm - blue	bag of 100 pcs
	Ear tip 8 mm - yellow	bag of 100 pcs
53522	Ear tip 9 mm - green	bag of 100 pcs
	Ear tip 10 mm - red	bag of 100 pcs
	Ear tip 11 mm - blue	bag of 100 pcs
	Ear tip 12 mm - yellow	bag of 100 pcs
53526	Ear tip 13 mm - green	bag of 100 pcs
	Ear tip 14 mm - red	bag of 100 pcs
	VERIFIED COMPATIBILITY FOR SANIBEL"	ADI
Ampliyo	v® Otowaye™ with clear (Type 1) probe	

Otowave" with clear (Type 1) probe AT235" & AT235h" with clear probe tip adapter AA222" & AA220" with clear probe tip, Titan" Eclipse" and MT10" with clear probe tip, Titan" MI24", MI26", MI34", MI44" with clear probe tip adapter easyTimp™ - Otowave™ - Ero-scan plus™ - easyScree Otowave'



• 53550 AMPLIVOX 116 SCREENING AUDIOMETER - air conduction Combines style and functionality, the ideal manual screening audiometer for primary care, school and workplace. It offers a comprehensive air conduction threshold facility at very affordable price.

- pure tone, continuous, pulsed and warble tones
- threshold retention function
- talk forward function

STANDARD FREQUENCY MUSICAL FREQUENCY

Air conduction (THD 39 Bone conduction (B 71

Free field

White AC

All option

259

MASKING NOISE Narrow bandwidth AC Narrow bandwidth BC

LOGO-AUDIOMETRY Air conduction Free field

- 125 to 8,000 Hz test frequency
- -10 to 100 dBHL Supplied with audiometric headset, patient response switch, audiogram cards (box of 50) main power adaptor, carrying case and manual (GB, IT, ES, on request FR, SE, PT).
- 53555 PELTOR INSULATION HEADBAND 53556 AUDIOGRAM CARDS - box of 50



# SCREENING AUDIOMETER DIAGNOSTIC AUDIOMETER



- 53551 AMPLIVOX 240 DIAGNOSTIC AUDIOMETER air, bone, masking Cost-effective diagnostic audiometer, ideal for desktop and mobile use.
- USB connectivity
- threshold retention function
- single, pulsed or warble tone preset
- 11 test frequencies: 125 to 8,000 Hz (AC), 250 to 8,000 Hz (BC) - -10 to 120 dBHL range (AC), -10 to 70 dBHL (BC), 90 dBHL max (250 to 4,000 Hz) insert masking output
- automatic AC test functionality Supplied with audiometric headset, bone conductor headset, patient response switch, audiogram cards (box of 50), main power adaptor, carrying case and manual
- (GB, IT, ES, on request FR, SE, RU, PT). 53555 PELTOR INSULATION HEADBAND
- 53556 AUDIOGRAM CARDS box of 50
- 53557 INSERT FOR MASKING

# SCREENING DIAGNOSTIC AND CLINICAL 2 CHANNEL AUDIOMETERS

4,000 4,186 120 70

100

120 70

8,000 HZ 8,372 HZ

110 dB HI

dB HL

dB SPL dB SPL

dB SPL



250 262 100 50 500 523 750

Programme to personalize the audiometer according to the needs of the use FREQUENCIES AND LEVELS

120 70

100 70 100 70 100 70

120

120 60

1,000 | 1,500 | 2,000 | 3,000 | 1,047 | - | 2,093 | -

120 70

120 70

- LCD alphanumeric backlight 33623 SIBELSOUND 400-A SCREENING AUDIOMETER air conduction • 33624 SIBELSOUND 400-AOM DIAGNOSTIC AUDIOMETER - air + bone + masking
  • 33626 SIBELSOUND 400-SUPRA CLINICAL AUDIOMETER -

air + bone + mask + supraliminar tests + W50 software
The SIBELSOUND 400 is a two-channel digital audiometer based on DSP processing. This audiometer is designed for quick and easy audiometric exploration of hearing thresholds and screening tests, such as suprathreshold pure tone tests (FOWLER-ABLB. TONE DECAY, WEBER, LUSCHER, ...).

- Air conduction (TDH 39): 125 8.000 Hz or HF: 8.000 20,000 Hz with optional HDA 200
  - Levels: AC (-10 to 120 dB HL) / BC (-10 to 70 dB HL) /
- speech (-10 to 100 dB HL) free field (-10 to 80 dB HL) Masking levels (manual or synchronized): NBN AC (-10 to 100 dB HL) NBN BC (-10 to 70 dB HL) white & speech (-10 to 100 dB SPL)
- Tone: continous, pulse, anternate, amplitude modulation.
   Level increases: 5 (A-AOM), 1 or 5 (SUPRA)
   Frequency precision: ±1%/ level precision ±2% db SPL
- Automatic calculation of hearing loss and diagnosis (COUNCIL, IMSS MEXICO, ELI, SAL, KLOCKHOFF, MOH, OTHERS ...) Direct USB connection to PC to W50 audiometry software for
- viewing, storage, transmission, analysis and introduction of audiometric tests (Windows® environment).
  - 33628 INTERCOM KIT (headphone + microphone)
  - 33621 INSULATION DEVICE for air conduction phone 33629 ALIDIOMETRY SOFTWARE W50

33023 AUDIOWETKT SOLIWARE WS0							
SIBELSOUN	SIBELSOUND 400 FEATURES						
	Α	AOM	SUPRA				
Audiometry type	4 screening	3diagnostic	2 clinical				
Air conduction TDH 39	•	•	•				
Bone conduction B71		•	•				
Masking by white narrow							
band & speech noise		•	•				
Sisi test			•				
Supraliminar tests			•				
Speechaudiometry +							
Intercom kit	optional	optional	•				
Musical frequencies			•				
Intercom data base	150 tests	1,000 tests	1,000 tests				
USB connectivity	•	•	•				
W50 audiometry software	optional	optional	•				
User manual English, Italian	•	•	•				



# PC OR PC-iPAD CONTROLLED PORTABLE AUDIOMETERS

### PICCOLO PORTABLE AUDIOMETERS

Piccolo is a basic diagnostic audiometer offering air, bone and speech audiometry functions.

Piccolo can be controlled either from a computer running Windows or, for the first time ever, from an iPad®.

Lightweight, compact design, powerful, user-friendly software and Noah connectivity combine to make Piccolo the ideal choice for professionals on the move.

- three different models available:

33615

33616

Basic (AC only) for Pc use Plus (AC/BC) for Pc or Pc-iPad® use (Aero version) Speech (AC/BC/Live Speech) for Pc-iPad® use

- iPad® control (includes Aero option, 33616, 33618 only) through the Maestro App. Wireless Bluetooth connectivity

- computer control through the dedicated Noah or Daisy module. USB connection port



- small and light weight

computer.

Made in Italy

GB, FR, IT, ES, DE, PL, PT, RU.

CD manual and quick quide

GB, FR, IT, ES, DE, PL, PT, NL

Software language

- power supply through the USB

connection, when controlled by

Piccolo Speech

Pc and iPad® control

AC, BC, Live Speech

NBN, WN, SN

Yes

0.5 Hz, 1 Hz, 2 Hz

5 dB

3-diagnostic

	Piccolo Basic	Piccolo Plus			
Type of device	Pc control	PC (33615) or Pc and iPad® control (33616)			
Class EN 60645-1, ANSI S3.6	4-screening	3-diagnostic			
Output	AC	AC, BC			
Masking	NBN	NBN			
Warble tone	Yes	Yes			
Pulsed tone	0.5 Hz, 1 Hz, 2 Hz	0.5 Hz, 1 Hz, 2 Hz			
Frequency range	125 - 8,000 Hz	125 - 8,000 Hz			
Maximum output intensities	AC: -10 to 120 dB HL	AC: -10 to 120 dB HL			
		BC: -10 to 80 dB HL			

Attenuator step 5 dB 5 dB Automatic audiometry HW auto threshold HW auto threshold Speech audiometry No No Speech inputs External microphone External microphone Talk over Connection to PC USB [driverless] USB [driverless] Controlling software aisy or Noah with Maestro module Connection to iPad Bluetooth 4 (only 33616) Controlling app Maestro (App Store) Dimensions 16x16x3cm (16.3x6.3x1.2 in Weight 300 q (10.6 oz) 300 q (10.6 oz) Operating voltage 100-240 V. 50/60 Hz 100-240 V 50/60 Hz



### Management PC (33615/6/8 only) PC Patient response switch Piccolo Plus Aero diagnostic audiometer - air + bone + mask PC + iPad Clip-on microphone for operator to-patient communication PC + iPad

- Jack/jack cable (Ø 3.5 mm) -33618 only - TDH-39 supra-aural headphones - R71 hone vibrator Inventis Daisy Patient Record Manager, with Daisy Maestro module

Noah Maestro module - USB connection cable Medical grande power supply

air + bone + live speech\* + mask \*Speech material IT standard, available on request FR.

33613 Piccolo Basic screening audiometer - air + mask

33618 Piccolo Speech Aero diagnostic audiometer -

# **BELL PLUS DIAGNOSTIC AUDIOMETER**

### • 33635 BELL PLUS DIAGNOSTIC AUDIOMETER - air + bone + mask + software DAISY - MAESTRO

Bell is a basic diagnostic audiometer performing fast and accurate air and bone conduction threshold examinations. Simple operation, fast and reliable automatic examination mode, user-friendly interface and easy portability make Bell the ideal instrument for private clinics, multi-specialist clinics and occupational medicine application.

SCREENING AND DIAGNOSTIC AUDIOMETERS

Piccolo Plus diagnostic audiometer - air + bone + mask

- pure tone audiometry in AC and BC
- hughsone-Westlake auto threshold test
- colour graphic display
- internal memory for 100 patients



- supplied with air conduction phone and vibrator for bone conduction.

### Made in Italy

### Maestro Software interface

The Maestro module is the software interface of Bell Plus audiometer. When it is connected to PC via USB you can see real time progress of the exam on the display and then download the data. It also allows full control of the audiometer from computer.

### STANDARD ACCESSORIES

- TDH-39 supra-aural headphones
- Plastic cover sheet
- B71 bone vibrator - Patient response switch
- Medical grade power supply - User Manual

### TECHNICAL SPECIFICATIONS

Type of device Class (EN 60645-1, ANSI S3.6) Output Masking Insert masking earphone Warble tone Pulsed tone Frequency range

Attenuator step Automatic audiometry Talk over Display type Display size resolution Operating voltage

Dimensions - weight

Hybrid audiometer 3 diagnostic AC. BC NBN, WN Yes 05 Hz 1 Hz 2 Hz 125 - 8.000 Hz -10 to 120 dB HL BC: -10 to 80 dB HL 5 dB HW auto threshold

Internal or external microphone Colour graphic 4.3", 480x272

100 patients 100-240 V. 50/60 Hz 32x32x9 cm (12.6x12.6x3.5 in) - 1.8 kg (4.0 lbs)

- 33471 SPIROTEL with WINSPIROPRO software
- 33472 SPIROTEL with Bluetooth and WINSPIROPRO software
- 33473 SpO, PROBE adult optional

• 33410 MOÚTHPIECES int Ø 2,8 x ext Ø 3, h 6.5 cm touch screen 60x80 nixel **( E** 0476 Manual and internal software languages: GB, FR, IT, DE, ES. Size: 74x88x38 mm - Weight: 151 g FDA ANN MIR (S)

A pocket laboratory which integrates 4 devices in one:

- spirometer with touch screen display

- triaxial accelerometer with motion analysis for therapy monitoring

- intelligent 3D oximeter with on screen results (with 33473) - e-diary for home care symptom control.

Compatible with Qualcomm Life 2 net Hub

### TECHNICAL SPECIFICATION

SpO<sub>2</sub> range: Pulse rate range: Data transmission Memory capacity: Power supply:

Flow sensor: Bi-directional digital turbine
Flow range: ±16Us ±23% or 50 mL Flow accuracy:±5% or 200 mUs
Dynamic resistance: <0.5 cm H,O/Us Temperature sensor. Semiconductor (0-45°C)
Measured parameters: Reading on spirometer: FVC, FEV1, PEF, FEF 25/75 Reading on PC with Winspiro PRO: same parameters as Spirobank G 0-100% ±2% (50-100% SpO<sub>2</sub>) 20-254 BPM ±2BPM or 2%

USB 2.0 or Bluetooth

Up to 10,000 tests - 300 hours oximetry (only with 33473) Lithium-ion 3.7 V, 1100 mAh rechargeable, for 40 hours

# DISPOSABLE AND RE-USABLE TURBINES FOR MIR SPIROMETERS

• 33507 DISPOSABLE TURBINE WITH INTEGRATED MOUTHPIECE - box of 60

Single patient use. Low cost and high accuracy. Individually packed to guarantee maximum hygiene. Easy to replace, no calibration needed.

SPIROTEL SPIROMETERS - BLUETOOTH OPTION

Compatible with GIMA codes: 33509, 33511-14, 33518-22, 33527-29, 33530, 33532, 33534.

• 33526 RE-USABLE TURBINE - bayonet

Easy to replace, no calibration needed. Compatible with GIMA codes: 33511-14, 33518, 33520-22, 33528-32, 33534. 33526



# **MOUTHPIECES** FOR MOST SPIROMETER BRANDS

Paper mouthpieces (disposable) and plastic mouthpieces (re-usable for most brands of spirometers and peak flow. Paper mouthpieces are packed in individual transparent pouch.



•	051 51 11(01)12121( 510 (1155							
			GIMA	PAPER MOUTHPIE	CES			
	GIMA code	Sizes - cm Ø int x ext x h	Suitable for	GIMA codes Other brands		Minimum order		
	33410	2.8x3x6.5	adult	33431, 33433,	Micromedical Vitalograph, Mir Ferraris (Koko legend)	box of 500		
	33897	2.0X3X0.3	aduit	33471-2, 33512-14, 33518-22,	Cardiette (Pneumos 300)	dispenser of 100		
	33411	2.0x2.2x6	paediatric	33528-32, 33534	Micromedical Vitalograph, Mir	box of 250		
ı	33412	Plastic a	dapter	33411	Mir	-		
ı	33506	2.6x2.8x6.5	adult	33480, 33484-7	Sibel	box of 100		
ı	33494	1.9x2.1x7	paediatric	33486, 33487	Sibel*	box of 100		
ı	33890	2.5x2.7x7	adult	-	Fukuda Sangjo, Thor	dispenser of 100		
H	33892	2.8x3.05x7	adult	-	Cosmed (Pony model)	dispenser of 100		
	33898	2.8x3.05x7	adult	-	Cosmed (Pony model)	box of 500		
	33895	3.03x3.3	adult	-	Sensormedics, Microcard	box of 500		
	33899	2.42x2.6	adult	-	Sorin Lifewatch, Fukuda Denshi	box of 500		
			GIMA I	PLASTIC MOUTHPII	ECES			
	33432	1.7x2.1x5 2.7x3x5	adult/ped	33431, 33433	Ferraris	-		
	33691		adult	33682-4, 6, 8	Thor	box of 10		
	*Gimaspir A/B need adapter 33495							

# SPIROMETRY PAPERS

• 33492 MIR SPIROLAB PAPER - roll 112mm x 25m Suitable also for SIBEL DATOSPIR 120 B, C, D, DATOSPIR Touch and GIMASPIR 120 models B, C, D.

- 33893 COSMED PONY PAPER roll 57 mm x 11 m box of 5 rolls 33525 BACTERIAL FILTER box of 50 for MIR, Medisoft spirometers • 33894 COSMED PONY FX PAPER - roll 112 mm x 13m - box of 25 rolls
- Compatible also with Fukuda Spirosift.

• 33250 THERMAL PAPER - roll 58 mm

Suitable for SIBEL DATOSPIR 120 A and GIMASPIR 120-A.

# NOSECLIP

• 33474 NOSE CLIP

# **BACTERIAL FILTER**


• 33557 SPIROGUARD BACTERIAL FILTER - box of 50 Compatibility of Spiroguard

Erich Jaeger Gmbh Ferraris Medical - P.K. Morgan Sensormedics

Masterlah and Masterscreen Autolink-Benchmark Transflo and USA Transfer System 2200 - 2400 - 2450 Wedge-Bellow-Alpha and Escort Spirometers

33474

# **BACTERIAL FILTER - MOUTHPIECE** FOR MOST SPIROMETER BRANDS



**BACTERIAL FILTER - MOUTHPIECE** Disposable filter with anatomical shape to prevent bacterial and viral contamination. Easy to use, direct connection to spirometer one side, patient mouthpiece other side. Suitable for most of spirometers and devices. Class II A. Individually packed in trasparent bag. Made in Italy.

	BACTERIAL FILTERS - MOUTHPIECES - box of 100					
	GIMA	Size - cm	Compatibility with			
	code Ø int x ext GIMA codes		Other brands			
	33884	2.75x3	33341, 33433, 33471-2, 33509-14, 33518-22, 33528-32, 33534	Micromedical, Vitalograph, Mir, Ferraris (koko legend), Cardiette (Pneumos 300)		
	33885	2.75x3.1	-	Cosmed		
	33886	2.95x3.4	-	Customed, Jaeger		
	33887	3.05x3.5	-	Sensormedics, BTL, Thor, Morgan, Chest, Microgard		
	33888	3.4x3.6	-	Medical Graphics		
	33889	2.5x2.7	-	Fukuda Sangjo		

# SMART ONE PEAK FLOW-FEV1 🔲 PEAK FLOW METERS

510 (K)

Health Canada

TIGE

Graphic trends

of Peak Flow

and FEV1 which

can be shared

33681

• 33681 SMART ONE® - Peak Flow and FEV1 Manual in GB, FR, IT, ES, DE, PT, PL, RU, TR, CN Ideal for monitoring respiratory illnesses

and in self management of Asthma, COPD, lung transplant care, cystic fibrosis and for use in clinical trials. Peak flow and FEV1 on your smartphone

Simple handheld wireless device that can be easily connected via Bluetooth to iOS and Android smartphones and tablets.

App (GB, IT) with an exclusive incentive for adult and children based on exhaled flow and volume that gives accurate and helpful results. Graphic trend of Peak Flow and FEV1

Measurements including option to flag any test session. Test results history with Peak Flow, traffic light health indicator, symptoms

scoring and notes. Low battery consumption. New turbine flowmeter with plastic mouthpiece For personal use, easy to remove for cleaning and hygienic. Made in Italy. • 33896 REUSABLE MOUTHPIECE - plastic -

box of 10 • 33897 DISPOSABLE MOUTHPIECE - paper -

### **TECHNICAL SPECIFICATION**

General Power supply: Autonomy Connectivity Size - weight: Mouthpieces:

box of 100

Spirometry Flow sensor: Flow range:

Flow range: ±16 L/s
Volume accuracy: ±3% or 50 ml
Measured parameters: FEV1, PEF

2 batteries AAA 1.5 V included 1,000 tests Low energy Bluetooth® 4.0 49x109x21 mm - 61 g (batteries included) Ø 30 mm (1.18 inch)

bi-directional digital turbine

Flow accuracy: ±5% or 200 mL/s

the application on the smartphone memorizes data



• 33431 POCKET PEAK - standard 60-800 l/min - cream

• 33433 POCKET PEAK - low 50-400 l/min - yellow The Pocketpeak Peak Flow Meter is designed to provide simple and reliable home asthma management.

Lightweight and easy to use, it provides accurate and reliable measurements over time.

It is easy to clean and features a universal mouthpiece.

The EU/ATS Scale Pocket peaks will not only comply with the new European Standards but also with ATS (American Thoracic Society) Standards.

Standards range pocket peak will cover 60-800 litres/min, low range will cover 50/400 litres/min.

Package includes multilingual directions for use and peak flow diary, all packed in a cardboard box. Made in USA. Size 86x81x30 mm.

Weight 45 g. Standards: EN 13826:2003

• 33432 UNIVERSAL MOUTHPIECES - re-usable

# LUNG EXERCISE DEVICE



### • 33442 RESPIPROGRAM

Device to exercise the respiration through inspiration. The respiratory-exerciser Respiprogram helps the patient to recover the normal respiration after a chest or abdominal surgery. The device is composed of: 1 base, 3 small balls different in dimension and colours, 1 transparent central part divided into 3 rooms, 1 tube and mouthpiece. Each unit packed in single box. Made in Italy. User manual: GB, IT.

• 33445 TRI-BALL® - respiratory exerciser

The respiratory-exerciser Tri-Ball® helps the patient to recover the normal respiration after a chest or abdominal surgery. Single patient. User manual in GB, FR, DE, IT, ES.

33445

Size: 108 x 47.5 mm 600/900/1200 Mouthpiece: 22 mm external Ø cc per sec Materials: All Latex Free Silicone User Manual: GB, FR, IT, ES, DE, PT, NL, GR, TR

Volume: 110 m Weight: 33 g

In plastic, sterilizable, suitable both for adults and children.

### • 33410 DISPOSABLE MOUTHPIECES - box of 500

# AEROSOL HOLDING CHAMBER



### • 33438 POCKET CHAMBER

Now you can manage your asthma conveniently and effectively with a truly pocket-sized device, proven as effective as MDI chambers nearly twice its size. The Pocket Chamber delivers a high concentration of respirable aerosol, to help provide relief from asthma symptoms while capturing large particles and reducing unwanted side-effects. - whistle alerts patients if inspiratory rate



- effective, affordable alternative to expensive aerosol delivery flexible port accepts virtually any MDI's mouthpiece

### TECHNICAL SPECIFICATION

Warranty: One year Made in USA

# SPIROBANK II SMART - PORTABLE SPIROMETER WITH SPO, OPTION

• 33512 SPIROBANK II SMART + WINSPIROPRO SOFTWARE Spirometer with 10.000 tests memory capacity, monochromatic LCD display, 6 keys membrane keypad. Battery power supply (3,7 V-1100 mA lithium) with an autonomy of approx. 50 hours of continuous use, rechargeable with USB port.

- cable (USB 2.0) or wireless (Bluetooth 4.0) connection

- internal temperature sensor for automatic BTPS conversion

- high resolution graphic display

- automatic record of a whole spirometry session including best test - USB cable, carrying case, CD manual (GB, FR, IT, ES, DE, PT) re-usable turbine and software included. Selectable internal software (GB, FR, IT, ES, DE, PT)

# 33514 SPIROBANK II SMART + WINSPIROPRO SOFTWARE +

Same as above with more than 300 hours of oximetric test records (SpO, % and pulse frequency tests). Measured parameters: min, max and average SpO, %, min, max

and average pulse frequency, SpO<sub>2</sub> total events, test duration, bradycardia events (<40 BPM), tachycardia events (>120 BPM), T90% (time passed with SpO<sub>2</sub> ≤89%), T89% (time passed with SpO<sub>3</sub> ≤ 88%) • 33525 ANTIBACTERIAL FILTER - box of 50 disposable

• 33507 DISPOSABLE TURBINE with mouthpiece - box of 60 • 33526 REUSABLE TURBINE

33410 MOUTHPIECES int. Ø 2.8 x ext. Ø 3, h 6.5 cm

TECHNICAL SPECIFICATIONS - SPIROMETRY

Measured parameters FVC, FEV1, FEV1/FVC%, DTPEF, FEV 0.5, FEV0.5/FVC%, FEV0.75, FEV0.75/FVC%, FEV2, FEV2/FVC%, FEV3, FEV3/FVC%, FEV6, FEV1/FEV6%, PEF, FEF25%, FEF50%, FEF75%, FEF25-75%, FEF75-85%, FET, Vext, Lung Age, EVOL, FIVC, FIV1, PIF, FIV1/FIVC%, FIF25%, FIF50%, FIF55%, R50, PIF, IRV, VC, IVC, IC, ERV, FEV1/VC%, VT, VE, Rf, ti, te, ti/t-tot, VT/ti, MVV

Pulse rate range: 18-300 BPM ±2 BPM or 2%

Flow accuracy ±5% or 200 mL/s Dynamic resistance <0.5 cm H<sub>2</sub>O/L/s Available tests: FVC, VC, IVC, MVV, PRE - POST Connectivity USB 2.0, Bluetooth® 4.0 Power supply Lithium-Ion 3.7V, 1100 mAh

Volume accuracy ±3% or 50 mL

Flow range ±16L/s

TECHNICAL SPECIFICATIONS - OXIMETRY (33514 only) Measurement method: red and infrared absorption SpO\_range: 0-99% ±2 % between 70-99% SpO\_ Signal quality indicator: 0-8 segments on display Memory capacity: up to 300 hours oximetry

### WinspiroPRO software functions:

- (GB, FR, IT, DE, ES, PT, PL, SE, NL, LV, CZ, TR, RU, CN, JP,
- on-line PC connection with icon interface real time Flow/Volume and Volume/time curves
- bronchial challenge with FEV1 dose-response paediatric incentive animations
- PC system integration with EPR systems

Lung Age Estimation requirements

- data and graphs export also via e-mail

XP, Seven, Vista, 8, 10



PC connection via LISR or Rivetooth® 510 (K)

Supplied with CD manual

(GB, FR, IT, ES, DE, PT, PL)

(GB. FR. IT. ES. DE. PT)

Internal software

100

110

**( €** 0476

# SPIROBANK II BASIC



System requirements: Microsoft Windows Vista, 2000, XP, ME, Seven, 8, 10

• 33510 SPIROBANK II BASIC + WINSPIROPRO software Complete and rapid pocket spirometer for the General Practitioner to carry out spirometry testing anywhere. No calibration required, use disposable turbine FlowMIR with integrated mouthpiece (33507) or reusable turbine (33526).

- measures the most important spirometric parameters including: FVC, VC, IVC, IC, ERV, FEV1, FEV1%, PEF, FEF 25-75, FET, EVOL, TEST POST BD
- traffic lights for immediate test interpretation
- memory up to 10,000 tests
- rechargeable long life battery (40 hours continuous operation) - real time tests via USB
- selectable display language and CD manual (GB, IT, ES, FR, DE, PT) Supplied with Winspiro PRO software, USB cable, 1 disposable turbine in a carriying bag.
- 33507 FLOWMIR DISPOSABLE TURBINE with integrated mouthpiece - box of 60 - spare
- 33526 REUSABLE TURBINE optional

### TECHNICAL SPECIFICATION

Power supply: 3.7 V, 110 mA lithium battery , USB rechargeable Display: LCD monochrome 160x80 pixel Keypad: 6-key membrane keyboard Flow range: + 16 l/s Flow accuracy: ± 5% or 200 ml/s whichever is greater Volume accuracy: ± 3% or 50 ml whichever is greater Max volume: 10 l Data transmission: USB 2.0 Made in Italy

# SPIROBANK G WITH SOFTWARE



- stand alone spirometer with PC online operation

6,000 spirometry in memory

high legibility graphic display
 FVC, VC, IVC, MVV, PRE-POST BD

- advanced spirometry test interpretation

- Lung Age Estimation (ELA) - ready for **Telemedicine** applications

- internal temperature sensor for automatic BTPS

- upgradable internal software via internet

Standard package includes USB cable, pouch, noseclip, battery, re-usable turbine and Winspiro PRO software.

### TECHNICAL SPECIFICATION

Measured parameters: FVC, FEV1, FEV1/FVC%, FEV3, FEV3/FVC%, FEV6, FEV1/FEV6%, PEF, FEF25%, FEF50%, FEF75%, FEF25-75%, FET, Vext, Lung Age, FIVC, FIV1, FIV1/ FIVC%, PIF, VC, IVC, IC, ERV, FEV1/VC%, VT, VE, Rf, ti, te, ti/t-tot, VT/ti, MVV Temperature sensor: semiconductor (0-45 °C)

Flow sensor: bi-directional digital turbine

Max volume: 10 Flow range: ± 16 l/s

Volume accuracy: ± 3% or 50 ml, whichever is greater Flow accuracy: ± 5% or 200 ml/s, whichever is greater Dynamic resistance at 12 l/s: <0.5 cm H.O/l/s

Power supply: 9V DC (PP3 battery)

Weight: 180 g (with battery) Dimensions: 162x49x32 mm Made in Italy

WinspiroPRO PC system requirements
(GB, FR, IT, DE, ES, PT,PL, SE, NL, LV, CZ, TR, RU, CN, JP)
- Microsoft Windows: Vista, 2000, XP, Me, Seven, 8

- Screen resolution: 1024x768 - Hard disk space: 160 MB

263

Internal software and CD manual: GB, FR, IT, ES, DE, + 3D ACCELEROMETER +

FEV1 4.84 FEV1% 84.7

IN ONE UNIT

Nocturnal oximetry repor

with desaturation analysis

# SPIRODOC® - SPIROMETER AND OXIMETER

• 33532 SPIRODOC SPIROMETER + SOFTWARE WINSPIRO PRO - bluetooth • 33533 SPIRODOC OXIMETER + SOFTWARE WINSPIRO PRO

• 33534 SPIRODOC SPIROMETER + OXIMETER + SOFTWARE - bluetooth One touch laboratory for respiratory analysis suitable for professional and personal use.

Complete spirometer ATS/ERS compliant

Specialist-level analysis, screening and Home-care monitoring. It has been developed with various operation modes: "advanced" parameters for the specialist, "reduced" set of

parameters for screening as well as a "simplified" version for Home-care operation. FVC, VC, IVC, MVV, PRE-POST.

Precise spirometry interpretation including post bronchodilator. All tests are automatically memorized. Automatic BTPS conversion. Memory capacity: 10.000 tests. Wide selection of predicted values. Intelligent pulse oximeter with on-screen results

Simple, clear SpO, and Pulse Rate measurements with plethysmographic curve. During the single six-minute walk test (6 MWT), Spirodoce estimates the level of oxygen therapy required by the patient. Spirodoce carries out sleep desaturation studies and memorizes events as well as body position.

3D Accelerometer with motion analysis Spirodoc® is the first 3D Oximeter® incorporating a triaxial motion sensor to correlate the saturation level (%SpO<sub>2</sub>) with physical activity (walk counter, movement analysis and VMU).

Home-care symptoms diary
Fast on-screen symptoms entry. Touch screen with settable questions and automatic answer recording for homecare patient use (eDiary) High performance PC software for spirometry and oximetry All tests memorized in Spirodoc® are automatically downloaded into WinspiroPRO and a patient data card is created with a preview of the spirometry curve. WinspiroPRO can easily be connected to a database, EPR, hospital or occupational health system. This software also gives trend graphs of any parameter. All stored Supplied with reusable turbine.

33534 123 222 

6 minutes walk test: baseline, walk, recovery and the results, including oximetry tests, can be compared. tests and curves of every patient can be reviewed on a single page Multilanguage software: GB, FR, IT, ES, DE, PT, PL, NL SE, CZ, LV, TR, RU, CN, JP.

Spirometry report

### Central unit

Display: LCD backlit touch screen display 128x64 pixels Power supply: Lithium ion 3.7 V, 1100 mA rechargeable battery with 50 hours measurement back up Accelerometer: Triaxial ±2 g, 400 Hz sampling Dimension and weight: central unit 101x48x16 mm, 99 g removable turbine head: 46x47x24 mm, 17 g Spirometry

Flow sensor: Bi-directional digital turbine Flow range: ±16 L/s Volume accuracy: ±3% or 50 mL, whichever is greater

Flow accuracy: ±5% or 200 mL, whichever is greater Dynamic resistance at 12 L/s: <0.5 cm H<sub>2</sub>O/L/s

# **TECHNICAL SPECIFICATIONS**

Three phase report of

Temperature sensor: semiconductor (0-45°C) Spirometer measured parameters FVC, FEV1, FEV1/FVC%, FEV3, FEV3/FVC%, FEV6, FEV1/FEV6%, PEF, FEF25%, FEF50%, FEF75%, FEF25%-75%, FET, Estimated Lung Age, Extr. Vol., FIV, FIV1, FIV1/FIVC%, PIF, VC, IVC, IC, ERV, FEV1/VC%, VT, VE, Rf, ti, te, ti/t-tot, VT/ti, MW measured, MW calculated Oximetry

SpO<sub>2</sub> range: 0 -100%, ±2% (50-100% SpO<sub>2</sub>) Pulse rate range: 20-254 BPM, ±2 BPM or 2% Pulseoximeter measured parameters

SpO, [Baseline, Min, Max, Mean], Pulse rate [Baseline,

Min, Max, Mean], T90% [SpO<sub>3</sub><90%], | T89% | SpO<sub>2</sub><89% | T88% | SpO<sub>2</sub><88% | T5% | [ΔSpO<sub>2</sub>>5% | Δindex [12s], SpO<sub>3</sub> events, Pulse rate events | Bradycardia, Tachycardia|, Step counter, Movement [VMU], Recording time, Analysis time

Sleep analysis
Body position, SpO, events, Desaturation index (ODI). Desaturation [Mean Value, Mean duration, Longest duration, Nadir Peak], ΔSpO<sub>2</sub> [Min Drop, Max Drop], Total Pulse Variations, Pulse Rate Index, NOD89% [SpO,<89%; >5min], NOD4% [SpO, Basale-4%; >5min], NOD90% [SpO,<90%; Nadir<86%; >5min]

# AND MINISPIR®-USB

 33527 MINISPIR with Winspiro Light Minispir Light measures 10 essential parameters for a diagnostic spirometry: FEV6, FVC, FEV1, FEV1%, PEF, FEF25/75%, FIVC, Lung Age, VC, IVC. Pediatric incentives. Flow/Volume loop and Volume/Time curve. Spirometry test interpretation.

MINISPIR® LIGHT

Temperature sensor for BTPS conversion. Minispir Light meets the requirements of integrated healthcare platforms and tablet applications. For use with FlowMir disposable turbine only (33507).

Winspiro Light is an intuitive and efficient software, for complete diagnosis included in Minispir Light.

PC SYSTEM REQUIREMENTS FOR WINSPIRO LIGHT/PRO Microsoft Windows: XP, Vista 32/64 bit, Seven 32/64 bit, 8 Screen resolution: 1024x768 Hard disk: 128 MB (better 256 MB) USB socket Multilanguage: GB, FR, IT, ES, PT, DE, PL, SE, NL, CZ, LV, TR, RU, CN, JP

### TECHNICAL SPECIFICATIONS MINISPIR/MINISPIR LIGHT

Temperature sensor: semiconductor (0-45°C) Flow sensor: bi-directional digital turbine Flow range: ± 16 L/s Volume accuracy: ± 3% or 50 mL

Flow accuracy: ± 5% or 200 mL/s Dynamic resistance at 12 L/s: <0.5 cm H,O/L/s Communication port: USB

Power Supply: line powered from USB port Dimension: 50x142x26 mm Weight: 65 a

TECHNICAL SPECIFICATIONS MINISPIR SpO, SpO, range: 0-99%

33529 PC not included

SpO, accuracy: ± 2% tra 70-99% SpO, Pulse Rate range: 30-300 BPM Pulse Rate accuracy: ± 2 BPM or 2% Measured parameters

SpO, [Baseline, Min, Max, Mean], Fulse Rate [Baseline, Min, Max, Mean], T90 [SpO<sub>2</sub><90%], T89 [SpO<sub>2</sub><89%], T88 [SpO<sub>2</sub><88%], T5 [ΔSpO<sub>2</sub>>5%], Δ Index [12s], SpO, Events, Pulse Rate Events [Bradycardia, Tachvcardial

33528 MINISPIR with Winspiro PRO
 33529 MINISPIR+OXYMETER with Winspiro PRO

Real time Flow/Volume loop and Volume/time curve with PRE/POST comparison. Advanced spirometry test interpretation. Pediatric incentive animations. Lung Age. Bronchial provocation test including new Mannitol protocol with FEV1 response curve. Temperature sensor for BTPS conversion. Supplied with reusable turbine. 32 measured parameters: FVC, FEV1,

FEV1%, FEV3, FEV3%, FEV6, FEV1/ FEV6%, PEF, FEF25%, FEF50%, FEF75%, FEF25-75%, FET, Vext,

Lung Age, FIVC, FIV1, FIV1%, PIF, VC, IVC, IC, ERV, FEV1/ VC%, VT, VE, Rf, ti, te, ti/t-

tot, VT/ti, MVV.
CD manual GB, FR, IT, ES, DE, PT.
Winspiro PRO is a unique
spirometry and oximetry software,

which comes standard with Minispir. All patient records are shown on simple, single-screen patient cards with dynamic management of all data and graphs.

### SPARE PARTS AND ACCESSORIES code 33507 Flowmir disposable turbine with

integrated mouthpiece - box of 60 Adult mouthpieces Ø ext 3 cm - box of 500 pieces (only for 33526) 33526 Reusable turbine (only for 33528-9)



Quality spirometry precise measurement The proven MIR digital turbine flow sensor requires no calibration and complies with ATS 24/26 waveforms. Certified by Dr. Crapo at LDS Hospital, Salt

Lake City - Utah



# STANDARD ACCESSORIES

Software Winspiro PRO Carrying case USB port and cable Battery charger 1 roll thermal paper CD manual: GB, FR, IT, ES, DE, PT

Nose clip Reusable turbine

B B T.

• 33521 SPIROLAB III - diagnostic spirometer with high resolution colour display, built-in printer and PC WINSPIROPRO software

• 33522 SPIROLAB III same as 33521 with SpO A really complete spirometry system:

- FVC, VC with breathing pattern plus MVV tests with real time curves

- over 30 parameters with automatic

interpretation and test quality control - PRE/POST bronchial response protocol with

F/V loop comparison - up to 8 blows curve on one screen

- internal database for about 6,000 complete tests

- predicted values with various authors

rechargeable battery plus mains power 220 V, 50-60 Hz (110V on request)

- user-friendly keyboard with dedicated function keys plus alphanumeric data entry

- internal temperature sensor for automatic BTPS conversion

- free upgradable internal software from web, maintaining previously stored data selectable multilanguage internal software (GB)

FR, IT). Possibility to order also with following internal languages: DE, ES, PL, PT, RU, CN, TR.

Finger Oximeter (33522 only) - short or long term (overnight) SpO, and Pulse Rate measurements

ODI, NOD, T90%, T89%, T88, T87%

- oximetry during exercise test 33410 ADULT MOUTHPIECES - Ø 3 cm ext - box of 500 pcs.

33492 THERMAL PAPER - 112 mm x 25 m

• 33516 SpO, PROBE - paediatric • 33525 ANTIBACTERIAL FILTER - disposable - box of 50 pcs.

33507 DISPOSABLE TURBINE WITH INTEGRATED MOUTH-

• 33524 CONNECTION CABLE MINIFLOWER-SPIROLAB III

33523 CONNECTION CABLE MINIFLOWER-SPIROLAB and

SPIROLAB II (532375) - spare

### **TECHNICAL SPECIFICATIONS 33521-33522**

± 16 l/s Volume accuracy: ±3% or 50 ml Flow accuracy: ±5% or 200 ml/s <0.8 cm H\_O/l/s Dynamic resistance: 310x205x65 mm

FVC, FEV1, FEV1/FVC%, FEV3, FEV3/FVC%, FEV6, FEVI/FEV6%, PEF, FEF25-75%, FEF25%, FEF50%, FEF5%, FET, Vext, \*FVC, \*FEV1, \*PEF, PIF, FIVC, FIV1, FIV1/FIVC%, VC, IVC, ERV, IC, FEV/VC%, VT, VE, Rf, Ti, Te, Ti/T-tot, VT/Ti, MVV \*: Best value

PC System requirements: Windows 2000, ME, XP, Seven, Vista, 8, Made in Italy

# SP-10 POCKET SPIROMETER



### STANDARD ACCESSORIES

Internal lithium battery USB cable

PC software (english language) User manual: GB, IT, ES.



### • 33536 SP-10 POCKET SPIROMETER

### • 33535 SP-10 POCKET SPIROMETER WITH BLUETOOTH

Pocket, portable spirometer with large TFT screen to clearly display both numbers and flow charts. Synchronously measure FVC, PEF, FEV1, FEV1%, FEF25, FÉF2575, FEF75.

Support diagnosis evidence by volume and flow rate chart display. Built-in predicted values.

Built-in lithium rechargeable battery and battery power display. Supplied with USB cable for PC connection, battery charger and software to calculate data and analyse trend.

• 33410 ADULT MOUTHPIECES - Ø 3 cm ext. - box of 500 pcs

### TECHNICAL SPECIFICATIONS

Max volume: 10 l Flow range: 2 l/sec - 16 l/sec

Volume accuracy: ±3% or 50 ml whichever is greater Flow accuracy: ±5% or 200 ml/sec whichever is greater Parameters: FVC, FEV1, PEF, FEV1%, FEV25, FEF2575, FEF75 Made in PRC

CE 92/42 - EMC group I class B - protection type BF

OR COMPLETE

# SPIROLAB SPIROMETER: 7" TOUCHSCREEN AND SPO, OPTION



- 33519 SPIROLAB® SPIROMETER WITH 7" TOUCHSCREEN
- 33520 SPIROLAB® SPIROMETER WITH 7" TOUCHSCREEN AND SpO. Fast, simple, durable diagnostic spirometer, made in Italy. Unbeatable features
- FVC, VC, MVV, PRE/POST Bronchodilator comparison with a wide range of selectable parameters
- long life rechargeable battery
- colour Touchscreen 7" display
- direct connection to external USB Printer PostScript
- 10,000 Spirometry tests or 500 hours of oximetry recording
- wireless Real Time test on PC via Bluetooth® - fast and silent built-in B/W printer with customizable printout
- selectable internal software languages: GB, FR, IT, ES, DE, PT
- Oximetry option

Available adult and pediatric reusable finger probe Fast and user friendly

Each function can be activated by a simple touch.

FlowMIR® disposable turbine complies with ATS/ERS standard Totally disposable (mouthpiece, turbine) quarantees 100% hygiene, no cross contamination.

No calibration required. Suitable also for pediatric use without need of adaptor.



GIMA code	MIR code	ACCESSORIES AND SPARES	Minimum order			
33695	919024	SpO, probe - adult - spare				
33696	939006 + 919200					
33697	910595	Miniflowmeter with cable - spare				
33410	-	Adult mouthpiece - Ø 30 mm ext	box of 500			
33492	-	Thermal paper - 112 mm x 25 m	-			
33525	-	Antibacterial filter - disposable	box of 50			
33507 910004		Disposable turbine with	box of 60			
		integrated mouthpiece				
TECHNICAL SPECIFICATIONS - OXIMETRY (33520 only)						

SpO, range: 0-99% ± 2% between 70-99% SpO. SpO, accuracy: 18-300 BPM Pulse Rate range ± 2BPM or 2% whichever is greater Pulse Rate accuracy:

Memory capacity: up to 500 hours oximetry

### **OXIMETRY PARAMETERS (33520 only)**

%SpO, and Pulse Rate (Min, Max, Average), Test duration, Total SpO Events, T90% (SpO, time ≤89%), T89% (SpO, time ≤88%), T40 (Bradycardia duration with Pulse Rate <40 BPM), T120 (Tachycardia duration with Pulse Rate >120 BPM)

### Suitable for children

Patented pediatric incentive directly on the

### WinspiroPRO®

High perfomances PC software for spirometry and oximetry with free update. Multilanguage software: GB, FR, IT, ES, DE, PT, PL, NL, LV, SE, CZ, RU, TR, JP, CN.





Summary of all tests carried out STANDARD ACCESSORIES

Carrying case
Battery charger
1 roll thermal paper

Nose clip

Power supply

Software WinspiroPRO® USB port and cable SpO, adult sensor (33520 only) manual: GB, FR, IT, ES, DE, PT

### TECHNICAL SPECIFICATIONS - SPIROMETRY

Autonomy:	approx. 10 hours
Temperature sensor:	semiconductor (0-45°C)
Flow sensor:	bi-directional digital turbine
Flow range:	±16L/s
Volume accuracy:	±3% or 50mL
Flow accuracy:	±5% or 200mL/s
Dynamic resistance:	<0.5 cm H,O/L/s
Connectivity:	USB 2.0, Bluetooth® 2.1
Display:	7" colour touch screen LCD, 800x480 resolution
Mouthpieces:	Ø 30 mm (1.18 inch)
Dimensions:	220x210x51 mm (8,66x8,26x2")
Weight:	1450 g (battery pack included) (3,1lb)
Electrical protection:	Class II
Norms:	Electrical safety standard EN 60601-1
	Electromagnetic compatibility EN 60601-1-2

Rechargeable battery

### SPIROMETRY PARAMETERS

FVC, FEV1, FEV1/FVC, FEV1/VC, PEF, FEF25, FEF50, FEF75, FEF25-75, FEF75-85, Lung Age, Extrapolated Volume, FET, Time to PEF, FEV0.5, FEV0.5/FVC, FEV0.75. FEV0.75/FVC, FEV2, FEV2/FVC, FEV3, FEV3/FVC, FEV6, FEV1/ FEV6, FEV1/PEF, FEV1/FEV0.5, FIVC, FIV1, FIV1/FIVC, PIF, FIF25, FIF50, FIF75, FEF50/FIF50, VC, IVC, IC, ERV, IRV, Rf, VE, VT, tl, tE, VT/tl, tE/tTOT, MVV (measured), MVV (calculated).

### WINSPIROPRO® REQUIREMENTS

Windows 2000, Xp, Vista (32/64 bit), 7 (32/64 bit), 8 and 8.1 (32/64 bit), 10 (32/64 bit), RAM 512 MB

# ULTRASONIC, DISINFECTABLE SPIROMETERS

- 33682 OTTHON SPIROMETER US (English) + SOFTWARE
- 33683 OTTHON SPIROMETER IT + SOFTWARE
- 33684 OTTHON SPIROMETER OTHER LANGUAGES + SOFTWARE

Pulmonary function diagnostics and monitoring spirometer for use by general practitioners, respiratory physicians and patients. Compact, mobile, affordable solution for screening COPD (Chronic Obstructive Pulmonary Disease) and asthma.

- automated diagnostic interpretation
- voice and video explain use of device and communicate results
- battery or USB charger
- touchscreen, bright colour high resolution LCD display QVGA (320x240 px), 16 M colours
- external printer connectivity
- automatic internal calibration
- flow tube disinfectable by cold sterilization
- power supply: USB 5 V or built in rechargeable battery Internal software languages: GB, FR, IT, DE, ES, HU, AU, HR. Voice languages available: US (English), AU, FR, IT, DE, ES, AT, HU. Please indicate requested language with order.



- 33688 SPIROTUBE PC SPIROMETER + SOFTWARE • 33689 SPIROTUBE B SHOCK AND WATER PROOF PC
- SPIROMETER + SOFTWARE

PC based pulmonary function diagnostics and monitoring spirometer with ultrasonic Idegen™ respiratory sensor. Suitable for screening COPD and asthma.

- automatic internal calibration
- tele-medical connection via internet
- plug & play USB PC connection detection
- easy upgrade, standard interfaces, XML, HL7 - long-term monitoring for life-long patient support
- pharmaceutical testing subsystem
- flow tube disinfectable by cold sterilization

Spirotube B Edition for harsh conditions

Features an exceptionally robust design for harsh condition and heavy use.

Power supply: USB 5 V. Made in Europe.

STANDARD ACCESSORIES		
33682/3/4	33686	33688
Thorsoft software •		•
Plastic mouthpieces	•	•
Mini USB cable •	•	
Cups for disinfection •	•	•
Battery charger •	•	
Bacterial filter •		•
Carrying bag •		
Paper manual (GB) •	•	•
CD manual (GB, IT, ES, DE, HU)   •	•	•

### TECHNICAL SPECIFICATIONS

Flow measurement principle Idegen™ multiple-path Flow tube diameter 30 mm (OD) Dead space 3 ml/s (33686), 8 mb/s (33682-4, 33688) Flow resolution 2% (33686, 33688), 3% (33682-4) Flow precision ±18 l/s Flow range Connection to PC USB

### **MEASURED PARAMETERS**

FVC, -FEV\*0.5, FEV\*0.5/IVC, FEV\*0.5/FVC, FEV\*1.0/IVC, FEV\*1.0/FVC, PEF, FEF\*25-75%, MEF\*75%, MEF\*50%, MEF\*25%, FET, MTT, FIVC, FIV\*0.5, FEV1/FVC (Tiffeneau index) FIV\*1.0, PIF, FIF\*25-75%, IRV, ERV, TV, Breath rate value Insp./Expi ratio: From 1:10 to 10:1



### • 33686 SPIROTUBE MOBILE EDITION BLUETOOTH SPIROMETER Pulmonary function diagnostics and monitoring spirometer

with Bluetooth communication interface and built in rechargeable battery. Suitable for screening COPD and asthma. - wireless connection to mobile phones, PDAs, android systems. Real-time measurement with FVC curve visible on the mobile

- plug & play USB connection to PC
- automatic internal calibration
- tele-medical connection via Bluetooth
- automated medical interpretation - long-term monitoring for home care use
- pharmaceutical testing subsystem
- flow tube disinfectable by cold sterilization - software can be freely downloaded

from Google Play Store Made in Europe.



Size: 35x120x120 mm



REGISTRATIONS

All spirometers are CE marked and registered in Indonesia, Singapore, Hong Kong, Australia, New Zealand, Korea, Saudi Arabia.

THORSOFT - PULMONARY DIAGNOSTIC PC SOFTWARE Standard medical interfaces (HL7, GDT, BDT, XML). Automatic interpretation module. Diagnostic decision support system (for general

practitioners and physicians) Complete stress testing procedure
Languages: GB, FR, IT, DE, ES, SE, TR, RO, HU,
SL, CZ, HR, NL, KR, CN.

GIMA code	ACCESSORIES	Minimum order
33690	Instrumed disinfectant concentrate 1 I (Bactericidal, fungidal, virucidal, sporocidal, tubercolocidal)	
33691	Plastic mouthpieces	box of 10
33890	Disposable mouthpieces	box of 100
33692	Loki Green single use bacterial filter	box of 50
33505	Calibration syringe 3 I*	

Ultrasonic spirometers do not need calibration. Svringe is only for check if requested by law

# SLEEP APNEA SCREEN METER

### • 33676 SLEEP APNEA SCREEN METER

Suitable for people who have obstructive sleep apneahypopnea syndrome (OSAHS), chronic obstructive pulmonary diseases (COPD), asthma, vascular disease or people over 60 years old. For hospital and home use. Features:

- wrist-design, small in volume and light in weight
- integrate multi-function in one device, convenient to know more physiological information
- displays SpO<sub>2</sub>, PR, pulse sound, bar graph
- display of pulse and nasal airflow waveform
- alarm for low-power, finger-out and over-limit
- adjustable screen brightness
- real-time clock
- auto-power on/off
- multi-care record

Manual (GB, IT)

- record data in continuous 20 hours
- upload data by USB to PC
- PC analysis software
- 33677 RUBBER ADULT SpO, PROBE for day
- 33678 NON-WOVEN SpO, PROBE for night bag of 2
- 34172 NASAL OXYGEN CANNULA

## STANDARD ACCESSORIES

Adult, Neonatal disposable SpO, probe Adult SpO, probe Software

USB cable Nose-oxygen tube

33676



### **TECHNICAL SPECIFICATIONS** 0-40 rpm ±2 rpm

<70 mA

69x50x17.3 mm

Nasal airflow measure range: SpO, measuring range: Pulse Rate measuring range:

0-100 % ±2 % (70-100 %), resolution 1% 30-250 bpm ±2 bpm or ± 2% (select the larger) Resistance to surrounding light: The difference between the value measured in the condition of man-made light and indoor natural light and that of darkroom is less than ±1 % 1.8" colour OLFD

3.7 V rechargeable lithium battery

100 g (lithium battery included)

continuously work for more than 20 hours

Internally powered, Type BF applied part

Display: Power consumption: Power supply: Battery working hour Safety Type:

Dimension of device:

PALM ECG'S are designed for general practitioners or for domestic users who suffer from cardiovascular diseases such as hypertension. coronary disorders, giving the possibility of a daily ECG test. Records can be saved and used as a reference for clinical applications.

33259

D/A Y/D M

measurement. Main features:

- small, portable and easy to use
- 30 second ECG waveform and measurement results
- 600 (CARDIO-A) or 1200 (CARDIO-B) ECG waveform can be saved
- 5 hours (CARDIO-A) or 10 hours (CARDIO-B) ECG continuous measurement data storage

4 measurement modes: palm, leg, chest or lead wire traditional

- analysis and report of 8 types (CARDIO-A) and 17 types (CARDIO-B) of ECG waveform
- USB 2.0 interface with option data cable and ECG viewer software
- traditional measurement with optional ECG cable CARDIO B with Bluetooth module for wireless data

GIMA

transmission. Allows to download data on your smartphone or tablet, compatible with Android.

Supplied with multilanguage manual and box (GB, FR, IT, ES).

GIMA

PALM ECG

33260

33260 CARDIO-A palm ECG

SINGLE CHANNEL PALM ECG: CARDIO-A AND CARDIO-B

GIMA

**( €** 0476

33261 CARDIO-B palm ECG - colour display 33259 CARDIO-B Bluetooth palm ECG+viewer software ACCESSORIES

33265 ECG viewer software+USB 2.0 cable - for 33260, old 33261 33249 ECG viewer software + USB 2.0 cable for new 33261 since SN: XXS02JL01044 - Jan 2014

33248 New ECG 3 pin lead cable - 3 leads - optional - 2012 from SN: XXQ00HJ03925 for 33260

from SN: XXS02HL01709 for 33261 33264 Old ECG banana lead cable - 3 leads - optional

### **TECHNICAL SPECIFICATIONS** CARDIO A CARDIO B 0.5 Hz - 40 Hz 1 Hz - 40 Hz

iHealth<sup>.</sup>

see page 4

Bluetooth ECG

ECG bandwidth: Heart rate measuring ra 30 - 240 bpm ± 2 bpm 128x64 dot matrix 240x160 dot matrix LCD back light display: Display size: 49x25 mm 57.6x40 mm

Power: 2xAAA batteries 115x58x18 mm 125x70x21.5 mm Dimensions Weiaht 65 a 106 g

# BREATHCARE PAP DEVICES: CPAP AND AUTO CPAP



• 53700 BREATHCARE PAP DEVICE - CPAP

### • 53701 BREATHCARE PAP DEVICE - CPAP/AUTO CPAP

The breathcare PAP devices take care of patients every night. PAP (Positive Airway Pressure) device works as an air compressor, it constantly blows pressurized air to patient's airway, to prevent airway collapse.

The PAP devices contain CPAP, Auto CPAP and BiPAP.

CPAP: Continuous Positive Airway Pressure device Auto CPAP: Automatic Continuous Positive Airway Pressure device

BiPAP: Bi level Positive Airway Pressure device

Improve sleep quality immediately No trauma, safe and comfortable

User friendly with little discomfort Quiet, noise ≤ 28 dB

Ultra quiet thanks to 4 methods for reducing noise level. Stable 20.000 hours life time.

Comfortable based on years of clinical data it effectively reduces the average treatment pressure and provides a comfortable therapy experience.







Connection with oxygen concentrator to supply oxygen with mask which can help ease symptoms of hypercapnia Internal software: GB, IT

Supplied with carrying bag, 2 filters, air hose, heated humidifier, breathing hose mask, SD card (only 53701), power adapter, power cable and manual (GB, IT)

• 53704 AIR SOFT TUBE • 53705 BREATHING NOSE MASK

• 53706 AIR COTTON FILTER - box of 10

Advised replacement every 2-3 months • 53707 CONNECTOR to oxygen concentrator

TECHNICAL SPECIFICATIONS Treatment mode Pressure range: Pressure accuracy: Time-lapse boosting: Alarm protection: Operating power: Automatic altimetric compensation USM air circuit system

CPAP, Auto CPAP (53701 only) 4~20 cm H<sub>2</sub>O ±0.5 cm H<sub>2</sub>O 0~45 min 1 face mask fell alarm 100-240 V, 50-60 Hz DC 24 V ultra silence air circuit system noise removal technology

3A self adapting frequency adjustn 27x13.5xh 10 cm - 1.5 kg



# CARDIO-C: 3 CHANNEL POCKET ECG

rue colour 3.5

Porkat siza

13x9.5x3.2 cm

32 MB memory


TFT display

need limb

electrodes 33364 electrodes 33327

or wrist

4 pins lead ECG cable



small size, light-weight and easy to carry

one-key measurement

- clear ECG waveform and interpretation of results on colour dot-matrix TFT 3.5" screen up to 19 types of measurement results

- high capacity built-in memory: 24 hours records storage and review for single channel waveform and 8 hours record storage and review for 3-channel waveforms

- quick measurement: by built-in metal electrodes, on palm, chest or leg or by external lead wires (needs optional limb and chest electrodes)

- data management to review or delete data records locally or to upload to PC

Supplied with ECG viewer software, USB cable, power transformer, ECG 4 pins lead wire, 25 disposable electrodes, manual (GB, FR, IT, ES, DE, PT).

• 33364 SET OF 4 LIMB CLAMP ELECTRODES (4 COLOURS) - adult • 33327 DISPOSABLE TNT ELECTRODES Ø 55 mm

### **TECHNICAL SPECIFICATIONS**

Heart rate measuring range: 30 bpm ~ 240 bpm Heart rate measuring accuracy: ECG bandwidth: ≤ 30µVp-p 5.0 mm/mV ±10% Internal noise level: Display scale: Common-mode rejection ratio (CMRR): > 60 dB Waveform sweeping speed: Input loop current:

Input impedance:

Supply voltage range: Max average working current: Auto power-off Low battery indication

Power

> 5 MO 4 AA alkaline batteries 4.4 ~ 6 VDC

0.5 Hz ~ 40 Hz

20 mm/s ±10%

± 2 bpm or ±2% whichever is greater

≤ 160 mA can be adjustable between 1-5 mins 4.4 VDC ±0.2 VDC

# CARDIOPOCKET ECG - 3 CHANNELS

• 33232 CARDIOPOCKET ECG 3 CHANNELS - with software

12-lead ECG printing ECG waveform with thermal printing system, measuring and diagnosing ECG waveform parameters automatically.

- full-automatic analysis function: auto-analysis and auto diagnosis for routine ECG parameters. It provides measurement results and auto diagnosis conclusion for HR, P-R interval, P Duration, QRS Duration, Q-T interval, Q-tc, P Axis, QRS Axis, T Axis, R(V5), S(V1),

- 2.83" colour LCD screen (resolution 320x240) that operates both with touch screen and keys

 high resolution thermal array output system 8 dots/mm (vertical)
 built-in rechargeable lithium detachable battery can continuously work for 4 hours, print up - store up to 100 cases in a SD card (not included)
- high-accurate digital filter eliminates baseline drift and distorsion to ECG waveform
- ECG-Sync software to form a ECG workstation

• 32963 THERMAL PAPER - box of 20 rolls

• 33328 ECG CABLE spare

Patient cable

4 limb electrodes

6 chest limb electrodes

1 user manual (GB, IT, FR)

• 33233 RECHARGEABLE Li-lon BATTERY

TECHNICAL SPECIFICATIONS AC: 100-240 V, 50/60 Hz - DC 12V rechargeable lithium battery 2,000 mAh

CMRR: >60 dB. > 100 dB (add filter) Noise level: ≤15 uVp-p EMG filter: 25/35 Hz Time constant: Frequency response: 0.05-150 Hz (-3 dB - 0.4 dB)

Patient leakage current: <10 μA

50 mm x 20 m, high speed termal paper Recording paper: 6.25, 12.5, 25, 50 mm/s ±5% Paper speed

Safety standard: IEC class I, type CF defibrillation-proof applied part Input mode floating and defibrillation protection Input circuit current: Input impedance:



software i

GB, IT, FR

# CARDIOPOCKET ECG - 1 CHANNEL

• 33257 CARDIOPOCKET ECG - standard 12 lead ECG - with software

• 33257 CARDIOPOCKET ECG - standard 12 lead ECG - with software
Compact and lightweight pocket device with unbeatable features:

- wide graphic display (it allows "live" view of ECG trace and selection of all parameters)

- rechargeable lithium battery operated (80 ECG with full charge)

- PC software with interpretation included for storing data into PC (GB/IT)
(operating system: Microsoft Windows 2000/XP/2003/Vista/7)

- multilanguage internal software: GB, IT, DE, FR, ES, TR, CN

- real time continuous records of clear and exact single channel ECG waveform and

notes. The notes include mark, sensitivity, chart speed, filter mode, etc - full-touch keyboard control, easy to use. Screen displays, working position, state

of the instrument are clear and easy to be read.

• 32963 THERMAL PAPER - box of 20 rolls

• 33243 RECHARGEABLE Li-lon BATTERY up to S.N. CD 1212100050

33244 RECHARGEABLE Li-Ion BATTERY since S.N. CD 130730000-1

TECHNICAL SPECIFICATIONS

AC: 100-240V, 50/60 Hz - DC: 7.4V / 2,000 mAh DC: 9V rechargeable battery In optimal DC state up to 8 h standby time, up to 4 h continuous print

Noise level: . ≤15µVp-p CMRR: >60 dB, >100 dB (add filter) FMG filter: 35 Hz (-3 dB) Time constant: Sensitivity display: standard sensitivity: 10mm/mV±2%

1/2, 1, 2 (cm/mV), conversion deviation ≤5% Sensitivity setting: Recording system: thermal-array, 8 dots/mm (vertical),

16 dots/mm (horizontal, 50 mm/sec) 32 dots/mm (horizontal, 25 mm/sec) 25 mm/s, 50 mm/s +5% Paper speed:

Recording paper: 50 mm x 20 m, high-speed roll Safety standard: IEC class I, type CF

Input circuit current: <50nA



Size: 207x96x62 mm

Integrated thermal

# STANDARD ACCESSORIES Patient cable

1 roll of paper 1 rechargeable lithium battery 4 limb electrodes

6 chest limb electrodes 1 user manual (GB, IT, FR) 1 CD software and cable for

connection to PC

# ■ PM10 PALM ECG WITH SOFTWARE AND BLUETOOTH

# • 33246 PM10 PALM ECG - with software and Bluetooth

PM10 is a homecare device to check ECG parameters. It can be used as a reference for patient to take further medical treatment and reference for doctor to diagnose. It can help to early prevent from cardiovascular diseases and reduce risks. Intelligent design, it achieves remote health management through mobile application; it can automatically start measurement, store ECG, upload data, download health results. Suitable for patients with chronic diseases, especially coronary heart disease, diabetes, hypertension, myocarditis, obesity, chest pain. palpitations and dyspnea.

4 MEASUREMENT MODES







Features: - 1.77" colour TFT-LCD

- quick ECG test with a simple touch. User friendly

- accurate conclusion can be obtained immediately after measuring

continuously record for up to 500 cases with built-in rechargeable lithium battery in full charge

- Bluetooth transmission

- ECG data can be saved to cloud Platform permanently, easy to check and analyze

- historical data can be printed at any time, easy to diagnose Size: 100x45xh 15 mm Weight: about 60g

> Supplied with a carrying bag, a multilanguage manual (GB, FR, IT, ES, DE, PT) and a CD software to visualize data on PC



DIGITAL SINGLE, 3 OR 3/6 CHANNEL ECG

### • 33220 SINGLE CHANNEL ECG 100G

- large LCD display waveform and data

- high-resolution thermal printing array system - frequency response is as high as 150 Hz

- capable of printing continuously on channel trace and annotations including lead mark and parameter such as sensitivity, paper speed and filter operation status

- high resolution digital filter inhibits baseline drift without affecting ECG waveform

33222 6 CHANNEL ECG 600G - monitor up to 12 channels

- digital isolation technology and signal processing solution,

- patient management, name, age and id, detail analysis report

- thermal printing system provides more than 10 printing modes - can print 90 minutes and print out 150 ECG continually

- ECG-Sync software, USB connection to PC and built-in memory

- auto-measurement, auto-analysis and auto-interpretation

- internal software: GB, FR, IT, ES, DE, TR, PL, PT, SI, RU, KZ, CN

- floating input circuit meets IEC safety standard - rechargeable battery supporting more than

50 patient examinations - internal software: GB, IT, DE, TR, RU, CN

- manual: GB, IT, ES
- 33225 RECHARGEABLE BATTERY - spare • 32968 PAPER ROLL 50 mm x 20 m - box of 20

• 33328 ECG CABLE - 10 leads - spare

- 7" TFT, colour LCD touch screen - 12 leads simultaneous display

can store more than 1000 cases

- PC software: GB. Manual: GB, IT, FR

• 33226 RECHARGEABLE BATTERY - spare

• 32970 PAPER ROLL 110 mm x 20 m - box of 10

- built-in lithium rechargeable battery

digital filter

33220 USB connection allows • 33221 3 CHANNEL ECG 300G - monitor up to 12 channels real-time transmission to PC

remote data analysis and 3.5" TFT colour LCD screen diagnosis, management and printing through the PC

- 12 leads simultaneous display

- thermal printing system

- AC and DC power supply

- high capacity built-in lithium rechargeable battery

- battery power supports up to 150 ECG continuous records built-in Database

built-in memory can store more than 1000 cases

digital signal processor for filter

auto-measurement, auto-analysis, auto-interpretations

ECG-Sync software, USB connection to PC

internal software: GB, FR, IT, ES, DE, TR, PL, PT, SI, YU, RU, KZ, CN

- PC software: GB

- manual: GB, IT, ES, FR

• 33226 RECHARGEABLE BATTERY - spare

• 32969 PAPER ROLL 80 mm x 20 m - box of 10

 33328 ECG CABLE - 10 leads - spare USB connection allows real-time transmission to PC remote data



33222

• 33328 ECG CABLE - 10 leads - spare TECHNICAL SPECIFICATIONS ECG 100G ECG 300G ECG 600G Class I, type CF applied part, which has defibrillation-proof applied par Standard 12 leads Floating and defibrillation protection Safety Type Input way Patient leak current Sampling rate 1,000 Hz A/D conversion 0.05Hz~150Hz (-3dB, + 0.4dB) Frequency response Time constan CMRR ≥ 3.2s >60dB, >100dB(Add filter) Enduring polarization voltage ±500mV Noise level <15µVp-p Dispose EMG interfet
Wave Data AC filter 35Hz (-3dB) 50Hz/60Hz (-20dB) Recording way Thermal printing system Thermal printing system (32spots/mm) 50mm(W)×20m(L) 80mm(W)×20m(L) Recording pape 2.5, 5, 10, 20, 40 mm/mV 5, 10, 20mm/m\ Waveform Auto-record: 25mm/s, 50mm/ output changing Rhythm record: 25 mm/s, 50 mm/s Manual-record: 5, 6.25, 10, 12.5, 25, 50 (only 33221), Manual-record: 25 mm/s. 100 mm/s (only 33222) 50 mm/s 110-220V, 50/60 Hz 7.4V, 3500 mAh Power DC - Lithium battery 7.4V, 2000 mAh supply 2000 mAn 7.4V, 3500 mAn 2.2 pcs φ5x20mm AC time lag; T250mA/250V(Power Supply:220V) 315 x 215 x 77 mm 1.5 kg 1.6 kg 1.7 kg Form

33221



software (only 33221 and 33228 CARRYING BAG 39x29x14 cm

33222)



271

. Neight 800 g

ble battery

ompact.

60x35 mm

only 190 mm

(size: 190x90x40

# 3 AND 6-12 CHANNEL DIGITAL ECG WITH HIGH RESOLUTION MONITOR



Made in Italy

- 33334 CARDIOGIMA 3M 1-3 ch. with interpretation • 33350 CARDIOGIMA 6M - 3-6-12 ch. with interpretation (monitor 3-6 channels, printer 3-6-12 channels)
- LCD monitor in Standard or Cabrera format with base line setting
- High resolution thermal printer (8 dots/mm): hardcopy 1-3 or 3-6-12 channels real time with possibility to print a millimetric grid
- Manual or automatic recording
- Image freeze with memory scrolling for reviewing and hard copy of acquired signals (Memory 10 seconds for each lead)
- Digital filters for elimination of muscle tremors, power line and base line noises
- Pacemaker detection
- Power supply by built-in high capacity Ni-Cd batteries and fast charging time

### **TECHNICAL SPECIFICATIONS CARDIOGIMA 3M AND 6M**

Power supply: internal rechargeable Ni-Cd batteries AC/DC Adapter: 100-240V, 50-60 Hz; 200mA Battery autonomy: 2.5 hours Applied part: CF type Input impedance: > 100 Mohm Frequency response: 0.05: 145 Hz

Cmrr: > 91 dB (33334), Cmrr: > 100 dB (33350) Time constant: > 3.2 s Acquisition: 12 bit 800 samples/sec/channel-isochrome

Leads: 12 standard or Cabrera

STANDARD ACCESSORIES 3M AND 6M 6 chest limb electrodes Patient cable 1 roll of paper 4 limb electrodes Manual (English, Italian) 1 bottle of gel Rapid guide: English, Spanish, Italian Battery

- Very simple operation by pre-defined fast keys and menus

- Based on a risk processor for a full digital signal processing

GIMA code	CARDIOGIMA ACCESSORIES	Minimum order
27139	Transport bag (see at page 60)	-
32996	Thermal paper 58 mm x 25 m (Cardiogima 3M)	box of 20
32953	Thermal paper 112mm x 23m (Cardiogima 6M)	box of 10
33328	ECG cable 10 leads - spare	-

Sensitivity: 5mm/mV; 10mm/mV; 20mm/mV ±5% Scrolling speed: 5mm/s; 10mm/s; 25mm/s; 50mm/s Signal memory: 10s for each lead

Printer: thermal printer 8 dots/mm, paper 58 mm (3M) 110 mm (6M). Filters: muscles tremors 35Hz digital; power line interferences 50-60Hz digital; high pass 0,5Hz digital

Defibrillation protection: internal

Display/Hardcopy: 1/3 channel (3M) 3/6/12 channel (6M) Dimensions: 240x160x65 mm. Weight: 1.5 kg. Made in Italy

# CARDIOGIMA 1M - 1/3 CHANNEL ECG WITH PARAMETERS CALCULATION



• 33329 CARDIOGIMA 1 M - 1-3 channel ECG with monitor A real portable ECG with small dimension and light weight (1 kg), with LCD monitor 128x64 pixel, high resolution thermal printer (8 dots /mm hardcopy, 1 channel real time) and parameters calculation. With manual or automatic recording. memory 10 seconds for each lead. Includes digital filters for elimination of muscles tremors, power line and base line noises. Based on a risk processor for a fully digital signal processing. Made in Italy.

32996 THERMAL PAPER 58 mm x 25 m - box of 20

• 33328 ECG CABLE 10 leads - spare

### STANDARD ACCESSORIES

1 roll of paper Patient cable 4 limb electrodes 1 bottle of ael 6 chest limb electrodes Manual (English, Italian) Rapid guide: English, French, Spanish, Italian

### TECHNICAL SPECIFICATIONS

Power supply: internal rechargeable Ni-Mh batteries AC/DC Adapter: 100-240\/ 50-60 Hz: 200mA Battery autonomy: 3 hours Applied part: CF type Input impedance: > 100 Mohm Frequency response: 0.05: 145 Hz Cmrr: > 100 dR time constant: > 3.2 s

Acquisition: 12 bit 800 samples/sec/channel Leads: 12 standard or Cabrera Sensitivity: 5mm/mV; 10mm/mV; 20mm/mV ±5% Scrolling speed: 5mm/s; 10mm/s; 25mm/s; 50mm/s Signal memory: 10 sec for each lead Printer: thermal printer 8 dots/mm, paper 58 mm. Defibrillation protection: internal

muscles tremors 35Hz digital; nower line interferences 50-60Hz digital: high pass 0.5Hz digital

Dimensions: 190x120x60 mm. Weight: 1 kg. Conformity standards: 93/42/CEE; EN60601-1 EN60601-1-2; IEC601-2-25 Made in Italy

# EDAN SINGLE OR THREE CHANNEL ECG 33330 EDAN III with 12 channel display INTERPRETATION COLOUR DISPLAY

Lead:

Sensitivity:

EDAN PORTABLE ECG - 1 and 3 channe

- foldable LCD screen, vivid waveform display
- built-in high resolution thermal printer
- built-in rechargeable Li-ion battery, AC/DC supply complete digital filter, avoid baseline drift, AC, EMG interfere
- automatic baseline adjustment
- auto/manual operation selectable
- lead-off detection and alarm
- SE-3 Three channel colour ECG also features
- interpretation tested by CSE/AHA/MIT database
- 12 Lead simultaneous acquisition
- automatic ECG parameters measurement and analysis - auto, manual, rhythm off work mode
- support barcode scanner to simplify patient information input
- LAN/RS232/USB connection to PC
- 12 leads grid printing on normal A4 paper by external printer ECG Viewer Software: PC based ECG data management software
- compatible with Windows XP, WIN 7, Vista (32 bit, 64 bit) - multi format reports - XML/SCP/DICOM/PDF/JPG/BMP/TIFF/PNG

· support bi-directional communication with LCG device						
GIMA code	EDAN ECG AND ACCESSORIES					
33330	Edan SE-1 Single Channel ECG					
33333	Edan SE-3 colour Three Channel ECG - interpretative					
33336	ECG-Viewer Software (GB, FR, IT, DE, PL, RU, ES, TÚ) for 33333					
32963	Thermal paper - roll 50mm x 25m for 33330 and 33305					
32964	Thermal paper - roll 80mm x 25m for 33332/3 and 33306					
33328	ECG cable - spare					
33318	Rechargeable Lithium battery 2500 mAh - spare					
27139	Transport bag - see page 60					

### **TECHNICAL SPECIFICATIONS**

Standard 12 leads 12 leads simultaneously Acquisition mode One lead 2.5, 5, 10, 20 mm/mV Input impedance:

> 50 MΩ (10 Hz) EMG Filter 35 Hz (-3 dB) EMG Filter 25/35/45 Hz off AC/DFT Filter 50 Hz/60Hz DFT Filter 0.05/0.15/0.25/0.32/0.5/0.67 Hz Low pass filter 150/100/75 Hz

AC Filter on/off Recording mode: Auto/Manual Auto/Manual/Rhythm/USBPRT Rhythm lead: Any lead selectable IEC I/CF Safety standard

AC: 100-115 V, 220-240 V, 50/60 Hz Rechargeable Li-ion battery: voltage 14.8 V Power supply: More than 6.5 hours continuous operation with battery supply 500 ECG's

Data storage: Thermal paper: 50 mm x 30 m rolled 80 mm x 20 m folded 80x70 mm x 200 pages Paper speed: 25 mm/s, 50 mm/s (± 3%) 5mm/s, 6.25 mms 10 mm/s,

12.5 mm/s, 25 mm/s, 50 mm/s (±3 %) 300x260x75 mm y) 2.5 kg (without battery) 2.3 kg (with battery) Weight: Display: 192x64 pixel LCD Selectable display language GB, IT, FR, ES, 320x240 pixels LCD (colour screen GB, IT, FR, ES, RU, PL, CZ,

PL, RU, TR, UA RO, DE, TR, HR, UA Ethernet, RS232, USB Interface: RS 232 Barcode scanner support yes PDF. Dicom. SCP. XML Report formats:

STANDARD ACCESSORIES Patient cable 1 roll of paper 4 limb electrodes 1 hottle of ge Rechargeable battery 6 chest limb electrodes Manual: GB, IT. On request: FR, ES, PT, TR (SE-1 and SE-3), DE, RU (SE-3 only)

# MINDRAY BENEHEART R3 ELECTROCARDIOGRAPH

• 33301 MINDRAY BENEHEART R3 ELECTROCARDIOGRAPH 3 channels Lightweight portable cardiograph for resting ECG diagnosis. Reliable analysis - Glasgow algorithm Utilizes the University of Glasgow ECG analysis algorithm. one of the world-leading resting ECG interpretations. Great Portability - only 1.2 kg The Glasgow algorithm is the Weighs only 1.2 kg with battery, easy to carry. first to be based on specific variables, including age, gender, race, medication, and class in 5" clear colour display Offers the highest resolution in industry, enabling

clinicians to observe real-time waveforms accurately. Convenient operations ECG recording is automatically unfolded on the writing

pad at the top of the unit for notes or signature. Unique recorder - Z-folded or rolling paper

Compatible with both rolling paper and Z-fold paper. Easily switchable without dismantling the pressure lever.

• 33014 ROLL THERMAL PAPER - 80 mm x 20 m - box of 10

• 33016 Z-FOLD THERMAL PAPER - 80x70 mm x 200 sheet - box of 25

AC power: Battery-type: Input impedance: Patient leakage: 100 to 240 VAC ± 10% 60 VA rechargeable Lithium ion battery 11.1 V typical, 2,500 mAh

- capacity Processing ECG analysis Digital Pacer detection 500 samples/second (sps) 1,000 samples/second/channel 16,000 samples/second/channel

Acquisition mode: Pre-acquisition or post-acquisition provide 10 seconds of instantaneous ECG acquisition

6 hours of continuous operation without recording or 500 ECGs in 2.5 x 4 format at 25 mm/s and 10 mm/mV 3.5 hours with power off

Sensitivity/gain: Colour display Resolution: Display data:

Limb clamp set of 4 Chest bulb set of 6 TECHNICAL SPECIFICATIONS
ECG amplifier: DC-coupled

immediate attention

order to maximize the accuracy of

the ECG interpretation. On the report, a headline may

highlight one or several "critical

value warnings" to alert medical attendants of findings that need

< 10 µA 30 to 300 BPM ± 10% or ± 5 BPM, Heart rate meter: whichever is greater 5, 10, 20 mm/mV, Auto TFT LCD with LED graphics backlit 800x400

Patient ID, gender, age, heart rate, clock, battery power indicator, waveforms, lead labels, speed, gain, filter settings, warning messages, information messages, network status and USB

50 MD at 10 Hz, defib protected

STANDARD ACCESSORIES Cable with banana plugs, IEC 1 roll paper Rechargeable batter

mindrav User manual in: GB, FR, DE, HU, IT, PL, ES, TF Glasgow algorithm (available in 13 languages as internal software)

43

403

Thermal printer: Dot array/Width 80 mm/speed 5.

Resting ECG mode: Records and prints 12-lead resting ECG with 10-second duration
Patient ID, secondary ID, age, date
of birth, gender, race, medication
class and V3 electrode placement Patient information:

Internal storage: 800 ECGs in internal memory ECG Storage format: PDF and Mindray storage format internal software: GB, FR, IT, ES, DE, PL, PT, TR, RU, HU, RO, CZ, CN

Report formats Thermal printer/PDF/A4/letter 250x194xh 55 mm/1.2 kg

Power

# MULTI CHANNEL ECG WITH INTERPRETATION ON PAPER

Recorder:

1 LAN cable

suction for adult

Patient leak current

EMG interference filter

Sensitivity selections

Input impedance Frequency response Time constant CMRR

Thermal pape

Paper speed

Auto record

Rhythm record

Product safety type

Size Power

1 Power cable



### 33354 CARDIOGIMA 12 ECG - 3-6-12 channel

Cost effective 12 channel resting ECG recorder without performance compromise. The simultaneous record of 12 channels has a high diagnostic value - all the 12 channels are shown at the same time. A4 size paper, one body type. Main Features:

- 12 leads simultaneous 10-second resting ECG with interpretation in only 60 seconds multilanguage. Internal software+print in GB, FR, IT, DE, RU, TR, CN,

- wide paper printing (A4 size thermal paper, fax paper is OK) - combined output of all relevant curves, patient data, date, time and instrument settings

### - PC Connections

Connection to PC with RS 232 port or LAN to submit recorded ECG signal to other specialist for evaluation (only a modem is needed)

change the settings of ECG's and save them in JPG format, which ensure compatibility with most EMR package. - rechargeable batteries (optional) with 1 hour capacity in

A fully configured PC-based software enables to record, print.

normal use (about 100 ECG printouts)

TECHNICAL SPECIFICATIONS

3-6-12 channel illustration of ECG signals in continuous ECG Leads: recording or 10 sec. recording with interpretation. 296x305.5x92.5 mm Approx 3 kg 3, 6, 12 channel and 1 channel (60 sec.) Recording channel

2.5. 5. 10. 20. auto (I~aVF: 10. W1~V6: 5) mm/mV Sensitivity: Printing speed: 12,5; 25; 50 mm/s

AC (50/60 Hz, -20 dB or better), Muscle (25~35 Hz, -3 dB or better) Low pass filter (off, 40 Hz, 100 Hz, 150 Hz) 2x16 character LCD display Display:

Sensitivity, speed filter status, HR, Printing form, rhythm lead LCD display: LED indicator: Signal quality, power source, battery

Membrane keyboard, alphanumeric and symbol available Keyboard: Patient data: ID, name, age, sex, height, weight Heart rate, PR, QRS, QT/QTc, P-R-T axis

Thermal print head, thermal paper roll Report papers: A4: 215X297 mm (8.5"x11.7") Letter: 215x280 mm (8.5"x11")

vertical: 8 dots/mm, horizontal: 16 dots/mm Resolution Electrical: Internal noise: 20 µV (p-p) max

Input circuit: floating input Isolated and defibrillation protected DC offset voltage: ≥ ± 300 mV Patient leakage current: < 10uA Frequency response 0,05~150 Hz

Power supply: AC or built-in battery (options) Power requirement: 100-240 Vac, 50/60 Hz, 1.0-0.5 A Power consumption: 60 W max

Battery capacity: 1 hour of normal use (approx. 100 automatic ECG printouts) Communication: PC Connection with RS-232 interface and Ian

STANDARD ACCESSORIES

Class I, Type BF CE, FDA, KFDA, CFDA, NCC Made in Korea

### 1 ECG gel tube (250 ml) 1 PC software (GB/IT) 1 Recording paper roll Patient cable - 10 leads 4 ECG clip-on electrodes 6 Chest electrodes.

< 10 IIA

1 Operation manual (GB/IT)



code	CARDIOGIMA 12 ACCESSORIES	3335
29534	Rechargeable battery - for 33354/33355/33357	+
32950	Thermal paper A4 - for 33354-5-7 - box of 5	2951
	ECG cable for 33354-5-7	leff .
29519	Trolley for 33354-5-7	No.

Floating and defibrillation protection Standard 12 leads

Auto and rhythm record: 25, 50 mm/s, ±5% Manual record: 5, 6.25, 10, 12.5, 25, 50 mm/s, ±5%

2.5, 5, 10, 20, 40 mm/mV, ±5%. Standard sensitivity is 10 mm/mV ±0.2 mm/mV.

Record setup according to auto record format and mode, automatically changing leads, measuring and analyzing.

Record setup according to rhythm record format and mode, automatically measuring and analyzing.

Class I CF defibrillation and pacing protection

DC:14.8 V, 3700mAh rechargeable lithium battery

0.05 - 150 Hz (-3 - + 0,4 dB)

25/35 Hz (-3 dB) 210 mm x 30 m high-speed

Manual record Record setup according to manual record format, manually changing leads.

Measurement parameters HR, P-R interval, P Duration, QRS Duration, T Duration, QT Interval, Q-Tc, P Axis, QRS Axis, T Axis, R(VS),

S(V1), R(V5)+S(V1)

334x320x85 mm AC: 100-240 V, 50/60 Hz

1 paper roll

≥ 3.2 s >60 dB, > 100 dB (adding filter)

# CARDIO 7: 12 CHANNEL RESTING ECG WITH TOUCH SCREEN

SOFTWARE EKG VIEW PLUS Long term ECG recording Touch screen operation full Optional alphanumeric keyboard support spirometer and automatic arrhythmia detection 0 0 0 0 33357 One touch operation for analyzing, rious stanstoring and printing within 3 seconds dard formats: Rotary key / JPG, PDF, XML, 1 power cable access to all menus

• 33357 ECG CARDIO 7: 12 CHANNEL ECG WITH TOUCH SCREEN

- 12 channel interpretive ECG for adult, pediatric and neonatal use - over 130 kinds of interpretation results based on advanced Minnesota code, HRV (Hearth Rate Variability analysis)

- memory for up to 200 patients - real-time preview monitor

USB - PC compatible through LAN or Wi-Fi

function - multi-language selectable software (GB, RU, FR, DE, IT, CN, ES, TU, PL, RU, PT)

lead fault message

pace maker detection

automatic arrhythmia detection

- 3, 5, 10 minutes long term recording

grid function allows you to use low cost plain fax paper

wide and clear colour 7" TFT LCD (800x480) touch screen for easy operation

full disclosure function

32950 THERMAL PAPER A4 - box of 5 rolls

 29534 RECHARGEABLE Ni-MH 12 V BATTERY up to S.N. T7xxxxxxxx - optional

29536 RECHARGEABLE Li-Ion BATTERY since S.N. T8xxxxxxx - optional

STANDARD ACCESSORIES

 29519 TROLLEY 33328 ECG CABLE

Patient cable - 10 leads LAN cable

1 paper roll 4 limb electrodes 1 bottle of ECG cream (70 g) 6 chest limb electrodes EKG View Plus (GB, IT) manual (GB, IT)

Vertical: 8 dot/mm

Horizontal: 16 dot/mm

Time constant: 3.2 sec Patient leakage current: < 10 µA

Internal noise: 20 µV (p-p) max

Input circuit: floating input

Input voltage range: ≥ ±5 mV

DC offset voltage; ≥ ±400 mV

Pacemaker pulse detection

Common mode rejection: > 105 dB

Frequency response: 0.05 ~150 Hz

Isolated and defibrillation protected

Input impedance: ≥50 MΩ

**TECHNICAL SPECIFICATIONS** 

MFER. DICOM

10 lead, 12 channel simultaneous ECG and acquisiti ECG leads 300(W) x 299(H) x 123(D)mm, approx. 3.5 kg Dimension Recording channel: 3 channels + 1 rhythm, 3 channels + 3 rhythm 6 channels + 1 rhythm, 12 channels, 60 seconds

1 channel, 3, 5, 10 minutes 1 channel and beat report 2.5, 5, 10, 20, auto (I~aVF: 10, V1~V6: 5) mm/mV Sensitivity: Printing speed: 5, 12.5, 25, 50, 100 mm/s Sampling rate:

2.000 samples/sec AC (50/60 Hz, -20 dB or better) Muscle (25~35 Hz, -3dB or better) Base line drift (0.05, 0.1, 0.2 Hz, -3dB or better)

Low pass filter: off, 40 Hz, 100 Hz, 150 Hz Display: 7" color TFT LCD display (800x480), 12 channels

preview FCG wave Monitor display:

Filters:

ID, date, sensitivity, speed, filter, form, rhythm lead Touch screen (alphanumeric and symbol available), User interface: Keyboard, rotary push-knob (pop-up menu) Patient data ID, name, age, sex, height, weight, smoke, race Basic measurement: Heart rate, PR int, QRS dur, QT/QTc, P-R-T axis

Thermal print head, roll paper A4 report paper: 210x300 mm (8.5"x11") Signal quality control: Disconnected lead detection

Electrical:

ECG data storage:

Safety conformity:

storage for 200 ECGs (Internal on flash memory) Battery (Li-Ion): Communication

AC 100~240 VAC, 50/60 Hz or battery (option) 2.0~1.0 A, 60 VA max 4 hours of normal use (approx.200 ECG printouts)

PC connection with LAN D2 Wi-Fi

Class I, Type CF, CE, CSA, FDA, KFDA, CFDA, CCC

33356

## DIGITAL 12 CHANNEL COLOUR ECG WITH WI-FI TECHNICAL SPECIFICATIONS



### • 33223 12 CHANNEL ECG 1200G with WI-FI

- 8" TFT display, 800x600 dots high resolution colour LED backlight
- simultaneous 12 leads acquisition and display - digital signal technique, AC filter, baseline filter, EMG filter
- auto-analysis and auto-interpretation
- Multi-mode display and printing, such as 12, 6+1 (rhythm), 6, rhythm 12, rhythm 10, rhythm 8, rhythm 6. Manual, Freeze etc
- 0.5 built-in lithium rechargeable battery
- 2 USB and LAN Socket for uploading data to PC - built-in flash memory. Stores more than 1,000 files Multi-language internal software: GB, FR, IT, ES, PT, PL, SI, TR, RU, KZ, CN.
- 33227 RECHARGEABLE BATTERY spare
- 32967 PAPER ROLL 210 mm x 30 m • 33328 ECG CABLE - 10 leads - spare

- STANDARD ACCESSORIES 1 ECG cable 1 set limb electrode clamp 1 set chest electrodes USB connection Rechargeable battery Software (same languages as internal software) Manual: GB, FR, IT



# SPIROMETER MODULE FOR CARDIO 7

 33356 SPIROMETER MODULE - for code 33357 It transforms CARDIOGIMA 7 in a 2 in 1 system: FCG-SPIROMETER

Spirometry measuring values:

FVC: FEV 1.0, FEV 1/FVC, FEV 0.2-1.2L, FIVC, FEV 25-75, FEV 75-85%, PEF, FEF 200-1200 ml, FEF 25%, FEF 50%, FEF 75%, PIF, FET 100%, FIVC.

SVC: SVC. ERV. IRV. TV.EC. IC. MVV: TV, MVV, FB

Pre and post bronchodilator comparison. Presentation: flow volume loop, flow time plot, measurement values table. Complies with ATS standard

• 33362 DISPOSABLE MOUTHPIECES - box of 100 pcs.

# ECG CABLE COMPATIBLE WITH MOST ECG BRANDS

• 33328 ECG cable - 10 leads

Long lasting, individually tested cable compatible with the following ECG machines: BIONET: Cardiocare, Cardiotouch CARDIOLINE: E1, E1R, E3, Delta 300, Delta 360, C3.

**CARDIETTE (Elettronica Trentina):** 

Autoruler 12/1, Autoruler 12/3, Excel 103, Excel 106, Astron Comp 1, Astron Comp 3, Astron Comp 6, Start 100 P, Start 100 H, Start 200, Start 200HV, AR600, AR 600 ADV, AR1200, AR1200ADV.

CARDIORAPID CAMINA: K111, K112, K33, K36, K300 M, K300 P, K600 P, K600 D, K130 B, K 130 D. AT/10, CS6, CS12, CS100, CV6, P80.

CONTEC: 100G, 300G, 600G, 1,200G EDAN: Smart SE-1, SE-3

**ESAOTE:** P80, P8000 GIMA: CARDIOGIMA 1M. 3M. 6M. 12. 12M HP: Pagewriter 1513, 154B/C, 1514D, 1515A/B, 1517A.

**KONTRON** EKG P80 MACOUAIRE CT100, CT200. M4 MEDICAL: M traces

NIHON - KOHDEN Cardiofax 651, 6581, 8110. PROGETTI all models: EPG junior, EPG view,

EPG6 view, EPG6 view plus SCHILLER AT/1, AT/2, AT/3, AT/4, AT/5, AT/6,





# ■ HOLTER ECG SYSTEM - 24 HOURS MONITORING




### • 35130 ECG HOLTER + SOFTWARE

ECG Holter system includes ECG recorder and software connectable to a computer system or laser printer. The recorder has built-in flash storage media to increase memory capacity. The sampling rate of 1,000 sampling/sec has improved the quality of waveform.

Accuracy of the system is ensured by AHA and MIT data. Features:

- windows software interface (GB, IT, PL)
- quick and accurate analyzing system
- special editing system of R point
- perfect analysis function of ST segment
- analysis function of T wave of all channels and T wave trend graph - review of ECG trend graph
- analysis system of HR variability, providing regular SDNN,
- SDANN, RMSSD, LF, HF, time domain and frequency domain - QT analysis and QT trend graph
- acquire pacing ECG directly without separate channel; Also have the functions of VCG, VLP, TVCG, HRT, TWA





### Recorder:

- 12 channel Synchronized ECG Acquisition
- small ECG recorder with OLED colour screen to display real time ECG waveform and review storage data.
- capacity up to 2G
- selectable sampling rate, 200, 500, 1,000 sampling/sec
- sampling accuracy: 12 bit
- built-in FLASH storage media, to prevent the flash card from damage due to repeated insertion and pull out
- USB interface
- operating system: Win 98, 2000, XP, 7, 8, 10
- 35131 ECG CABLE spare

### TECHNICAL SPECIFICATIONS

Scale voltage: 1mV±5% Standard sensitivity:10mm/mV ±5% Noise level: CMRR. >60dR Frequency response: 10Hz as benchmark, 0.5Hz~55Hz; -3dB Time constant: >3.2s Scan speed: 25mm/s ±5% Enduring polarization voltage: ±300mV



### STANDARD ACCESSORIES

Holter recorder 1 CD with software

10 leads natient cable

10 disposable ECG sensor

1 pouch for hanging recorder 1 USB cable for data downloads

# Instruction Manual (GB, IT)

# PC-ECG WITH INTERPRETATION SOFTWARE AND USB PORT

### • 33320 PC-ECG + ECG LAB SOFTWARE

Innovative PC-ECG device that can be connected to your PC via USB port. No power cable is required as it is powered through the USB PC cable. The unit is supplied with a 10 banana plug ECG cable (length 295 cm) and a powerful interpretation software (GB, FR, IT, DE, ES, PT, CN). Main software features:

### - 12 lead resting ECG with auto interpretation (ECG)

- vector ECG (VCG)
- sampling screen colour customization multi ECG report formats
- standard or thermal paper print, B&W or colour - auto interpretation On or Off
  - measurement table
- tests comparison - 90s resting ECG full disclosure
- multi hour ECG monitoring with holter analysis
- simple exercise stress test with report - e-mail, PDF, ASCII, HL7, Dicom, GDT Interfaces
- 33328 ECG CABLE SPARE

### 33321 PC-ECG+CARDIOLOGY SOFTWARE

- Same as code 33320 but with the following specialist functions: - timed vector ECG (TVCG)
- SAECG (Signal Averaged ECG) ventricular late potentials analysis - QTd analysis
- High Frequency ECG (HFECG)
- Frequency Cardiogram (FCECG) - simple exercise ECG

### 33322 CARDIOLOGY SOFTWARE to upgrade 33320 into 33321 TECHNICAL SPECIFICATIONS

Size:

Power source: Patient insulation: Defibrillation protection:

Sample rate: 10240Hz - Sample accuracy: 16 bit PC minimum requirements: Windows 2000, XP Vista and Windows 7

USB - Support HL7, Dicom interface 120x85x28 mm - 190 a 5V DC (from PC USB port) 4000 V AC built-in patient cable

CPU ≥ 1 GHz - HD ≥ 40 G - RAM ≥ 256 M

STANDARD ACCESSORIES 4 limb electrodes

Banana plug

6 chest electrodes Patient cable 10 leads 10 electrodes USB pen driver

QT Dispersion

chroma map

to code 33321

OTD analysis with

Ahove 3 nictures refers


RESERVEN ECGLAB 4.0 to locate coronary artery disease and ischemia 3-VCG analysis



# FIAB ECG UNIVERSAL ELECTRODES









33373 4 mm

10 pcs

10 pcs

GIMA code	FIAB code	Material	Size	JNIVERS Gel	SAL DISPOSA Shape	Connection	CTRODES - latex free Application	Minimum order
33313	F9089P-100	Foam	Ø 32x36 mm	Solid	Oval	Snap	Pediatric - rest, long term, stress and ECG holter	box of 2,000 pcs (20 bags of 100)
33370	F9060P	PE-Foam	Ø 40 mm	Solid	Round	Snap	Pediatric - rest, long term, stress and ECG holter	bag of 50 pcs
33314	F9089-100	Foam	Ø 36x40 mm	Solid	Oval	Snap	Adult - rest, long term, stress and ECG holte	box of 2,000 pcs (20 bags of 100)
33371	F9060	PE-Foam	Ø 48x50 mm	Solid	Oval	Snap	Adult - rest, long term, stress and ECG holter	bag of 50 pcs
33344	F9067	PE-Foam	Ø 48x50 mm	Liquid	Oval	Snap	Adult - rest, stress and ECG holter	box of 1,200 pcs (24 bags of 50)
33327	F2080	Non woven	Ø 55 mm	Solid	Round	Snap	Adult - rest ECG	box of 1,200 pcs (24 bags of 50)
33341	F3001ECG	Gelled	34x23 mm	Solid	TAB	Alligator	Adult - rest ECG	bag of 100 pcs
33372	F9047/4FL	PE-Foam	28x44 mm	Liquid	Rectangular	Plug 4 mm	Adult - rest ECG	box of 1,000 pcs (20 bags of 50)
33373	F9053N	Foam	Ø 23x30 mm	Solid	Oval	35 cm wire with 4 mm socket	Pediatric and neonatal	box of 150 pcs (5 bags of 30)





33374 Grabber adaptor - fit snap electrodes - size 22.5x33 mm

33342 Multifunction adaptor - can fit both snap electrodes and TAB electrodes - size 14x54x17 mm

ADAPTORS FOR ECG ELECTRODES



33368

Ø 15 mm

code	LATEX FREE - NICKEL FREE	order
	Set of 4 limb clamp electrodes (4 colours) pediatric Set of 4 limb clamp electrodes (4 colours) adult	1 set 1 set
33365 33369 33323	Set of 6 chest electrodes Ø 15 mm - silver coated Set of 6 chest electrodes Ø 24 mm - silver coated Set of 6 chest electrodes Ø 30 mm - silver coated Set of 6 chest electr. Ultra Ø 24 mm - silver coated Set of 6 chest electr. Ultra Ø 30 mm - silver coated	1 set 1 set 1 set 1 set 1 set

277

Ø 30 mm Ø 14 mm

4 mm elastic

33369

Ø 30 mm

33365

Ø 24 mm

metal connecto

GIMA ECG THERMAL PAPERS FOR DIFFERENT ECG BRANDS

# ■ 3M™ RED DOT™ ELECTRODES



bag of 100

bag of 50



33300





3M 2570 electrode with foam tape and sticky gel -

3M 2237 fluid resistant foam polyethylene backing. 3-days wearing time

radiolucent. 5-davs wearing time





Ambu<sup>\*</sup>

box of 1,000 20 pouches of 50

3M 2239 monitoring electrode with micropore tane backing

33294 2237 3M™ Red Dot™ - Ø 6 cm bag of 50 Non woven monitoring electrodes **33299 2248-50** 3M<sup>™</sup> Red Dot<sup>™</sup> - Pediatric - Ø 4.5 cm box of 50 **33300 2271** 3M<sup>™</sup> Red Dot<sup>™</sup> - 5.6 x 5.1 cm box of 50 **33297 2239** 3M<sup>™</sup> Red Dot<sup>™</sup> - Ø 6 cm box of 1,000\*

Gel electrodes - short term diagnostics

Foam monitoring electrodes

**33378 2330** 3M<sup>™</sup> Red Dot<sup>™</sup> - 3.2 x 2.2 cm

33293 2570 3M™ Red Dot™ - 4 x 3.5 cm

3M 2271 diaphoretic soft cloth monitoring electrode with blue abrader 3-days wearing time

3M 2330 resting ECG

electrode with adhesive gel

3M 2248-50 pediatric monitoring electrode with micropore tape backing

\*20 bags of 50 pieces

GIMA

# AMBU BLUE SENSOR ECG ELECTRODES



Shelf life means maximum life from production date. Average Gima shelf life is 50 to 90% of maximum life

### BLUE SENSOR

BlueSensor is the world's most time and cost efficient range of electrodes that delivers unmatched readings, user convenience and patient comfort.

BlueSensor ensures that you don't get your workflow disrupted by false alarms or have to waste time resolving problems with electrode adhesion.

### Exact monitoring - clear picture

Blue Sensor electrodes give a fast and reliable trace without the need for skin preparation, maximizing comfort for the patient. We know that fast, exact monitoring that ensures a clear picture of the patients' heartbeat is essential to accurate diagnoses.

### AMBU BLUE SENSOR SU

- highly conductive wet gel
- superior quick adhesion
- unique offset connector fitting or tab

- occlusive backing material - high quality Ag/AgCl sensor AMBU BLUE SENSOR L
- highly conductive wet gel
- combination of instant and long-term adhesives
- breathable microporous material
- unique offset connector
- · high quality Ag/AgCl sensor
- AMBU BLUE SENSOR VL
- highly conductive wet gel - combination of instant and long-term
- breathable microporous material
- unique offset connector
- high quality Ag/AgCl sensor AMBU BLUE SENSOR R
- highly conductive wet gel
- superior adhesion
- comfortable foam backing
- large measuring area



Snap

33263

# ECG GEL AND SPRAY

- 33266 ECG GEL 250 ml box of 40 tubes
- 33263 ECG GEL 5 I box of 4 bags\*
- 33268 ECG SPRAY GEL 250 ml box of 20 tubes

Suitable for non pre-gelled electrodes, ECG latches and pendant switches in any ECG and exertional applications. Allows ECG waves clear transfer to equipment.

It is hypoallergenic, does not irritate skin, does not contain oil and oily substances, does not contain formaldheyde and salt, has no toxic effects and is odourless.

• 33283 PUMP FOR BAG 5 I

"Includes 4 empty bottles 250 ml and 1 nozzle for easy refill



33266

		D.			1			
GIMA code	ECG MANUFACTURER AND MODEL ASPEL	Туре	Width mm	Length m	Sheet	Marker	Grid*	Min. orde
32951	Ascard A4, B56, Mr. Blue, Mr. Silver 3 Topaz, grey, v.07.204, orange, red, v.07.303	roll	112	25	-	no	or/red	10
32996 32952	Ascard B5 eco, Mr. Green, mint Ascard, Mr. Gold, Gold/3	roll roll	58 210	25 25	-	no no	or/red or/red	20 5
	BIOCARE 101G	roll	50 63	20 30	-	no	or/red	20 20
32969 32969	300G, 3010 iE3	roll	80	20	-	no no	or/red	10
33002 32992	3030, 6010 1200	roll	112 210	27 30	-	no no	or/red	10 5
32962 33004	1210, 1215	pack pack	210 210	140 150	215 200	yes yes	or/red or/red	10 10
32969 32966	BLT, 1203A, E 30 E70, E80 BIONET	roll pack	80 210	20 295	150	no yes	or/red or/red	10 1
32950	Cardiocare/Cardiotouch BIOSET-HORMAN	roll	215	25	-	no	or/red	5
	3800 Bioset 3600/3601/3700	roll pack	80 110	20 100	200	no ves	or/red or/red	10 10
33051	Bioset 8000 - 8100 - 9000 - 9100 BTL	pack	210	150	400	yes	or/red	5
32953	BTL 08/MT, 08/MD, 08/MD3 08 MT, MD BTL 08/LC, 08/LT	roll roll	58 112 210	25 23 25	-	no no no	or/red or/red or/red	20 10 5
32952 32954	BURDICK Atria 3100/6100, quest	pack	210	300	200	yes	or/red	1
32955	CARDIOLINE Elan 100	pack	112	100	300	ves	or/red	25
32956	Delta 1 plus	pack	60	100	300	yes	or/red	25
32957 32958	Delta 1 plus Delta 3 plus	roll pack	112	30 100	300	no yes	or/red	20 25
32959	Delta 30	roll	183	30	-	no	or/red	5
	Delta 60 plus	roll	210	30	-	no	or/red	5
32961 33053	Elan 2100, Delta 612 ECG 100+	pack pack	210 100	280 150	200 200	yes yes	or/red or/red	1 10
	AR/2100 (VIEW/ADV) - 66010042	pack	210	140	200	yes	or/red	8
	ECG 200+ CAREWELL	pack	210	295	180	yes	or/red	1
32963	ECG-1101B, 1101C, 1101G	roll	50 63	25 30	-	no no	or/red or/red	20
33058	ECG-1103B, 1103G, 1103L ECG-1103GW, 1103LW	roll	80	30	-	no	or/red	10
33059	ECG-1106G, 1106L ECG-1112L, 112M, T/12	roll	112 215	25 25	-	no no	or/red or/red	10
	COMEN							
	CM300 CM600	roll	80 110	20 20	-	no no	or/red or/red	10 20
32992	CM 1200 A/B	roll	210	30	-	no	or/red	5
32966	CM 1200 A/B CONTEC	pack	210	295	150	yes	or/red	1
	90A, 100G 300G, 300GT	roll	50 80	20 20	-	no no	or/red or/red	20 10
32970	600G	roll	110	20	-	no	or/red	10
32967	1200, 1201 DIMED LTD400	roll	210 50	30 25	-	no no	or/red or/red	5 20
32996	LTD410, Heartscreen 60G	roll	58	25	-	no	or/red	20
32964	LTD405S, LTD405W, LTD415 Heartscr. 80G	roll	80	25	-	no	or/red	10
32951 32965	LTD418, Heartscreen 112 LTD440, LTD445/S	roll pack	112 110	25 140	143	no yes	or/red	10 20
32960	LTD450, LTD455/S, LTD455/W	roll	210	30	-	no	or/red	5
32966	LTD450, LTD455/S, LTD455/W EDAN	pack	210	295	150	yes	or/red	1
32963 32964		roll	50 80	25 25	-	no no	or/red or/red	20 10
32965	SE-601	pack	110	140	143	yes	or/red	20
32966	SE-6, 12, 1200 EXP SE-6, 12, 1200 EXP	pack	210	295	150	yes	or/red	1
32960 32962	SE-6, 12, 1200 EXP SE/1201	roll pack	210 210	30 140	215	no yes	or/red or/red	5 10
J2302	ELETTRONICA TRENTINA/C					yes		
32971	Autoruler 12/1, comp. 1x12	roll	50	30	-	yes	blue	20 10
2/9/2	Start 100	roll	130	27	-	yes	blue	
	AR 600	roll	60	15	-	yes	blue	25

code	ECG MANUFACTURER AND MODEL	Туре	Width mm	Length m	Sheet	Marker	Grid*	Mi
32977	AR 600 Adv	pack	60	75	250		blue	2!
32974	AR 1200	roll	120	18	300	yes	blue	10
32978	AR 1200 (View/Adv)	pack roll	120 210	100 20	300	yes yes	blue blue	10
32976	Daedalus, Start 200, AR2100	pack	210	150	200	yes	blue	8
	Daedalus, AR2100 Daedalus, Start 200, AR2100 ESAOTE BIOMEDICA							
32980 32981	P 80 base P 80 base P 80 Power, P 80 SIX	roll pack	90 90	28 70	400	no	or/red or/red	10
32982	P 80 Power P 80 SIX	pack	210	280	215	yes yes	or/red	2!
32983	P8000 base P8000 Power	pack	80	70	300	yes	or/red	20
32984	P8000 Power	pack	210	280	200	yes	or/red	
32985 32986	Archimed 4240, Archiwin	pack	210	300 150	200 170	yes	or/red	1
32986	Personal 120	pack	126 114	90	200	yes yes	white or/red	20
3040	Esaote my Cardiopad 2157036	pack	210	140	180	yes	or/red	5
	My Cardiopad base Esaote my Cardiopad 2157036 FUKUDA ME - FUKUDA DE	NSHI						
32988 32989	501A, FX121, FCP-500, OP18TE FCP15, FCP11, OP110TE, OP119TE	roll	50 63	30 30	-	no no	or/red or/red	20
2303	FCP2101, 2155, FX 2111, CASE10,	TOIL	65	30	-	no	or/rea	21
	FCP 7101. FX 7102							
32994	OP/358TE, FCP/131, FX3010,	roll	145	30	-	no	or/red	10
	FX3101, FX-8822	٠.						
32990 32991	FX3101, FX-8822 OP 111 TE, OP 115 TE, FX102 OP 112 TE, FX 2111, FX 7101,	pack	50 63	75 75	400 400	yes yes	or/red or/red	21
,2331	EX 7102 ECP 2201 G	pack	0.5	/ / /	400	yes	Oinca	-
32992	FX 7102, FCP 2201 G FCP231, OP69TE, FX7402, FX7542, FX 8322 OP/382TE, FX-3010, FX-8222 OP22TE, FX7202	roll	210	30	-	no	or/red	5
	FX7542, FX 8322	١.					l	
32993 32965	OP/382TE, FX-3010, FX-8222 OP222TE, FX7202	pack pack	145 110	75 140	400 143	yes yes	or/red or/red	10
2905	GIMA	pack	110	140	143	yes	or/rea	20
32996	Cardingima 1M 3M	roll	58	25	-	no	or/red	20
32953	Cardiogima 6M colour	roll	112 215	23 25	-	no	or/red	10
32950	Cardiogima 12, 12M HEWLETT PACKARD	roll	215	25	-	no	or/red	5
32999	Page Writer 100/200,	pack	210	300	200	hole	or/red	1
	M1709A, M2483A	ľ						
32988	M1709A, M2483A 40453 A, 43120 INNOMED	roll	50	30	-	no	or/red	20
2996	HearthMirror IKO 3,	roll	58	25		no	or/red	20
	HeartScreen 60 IKO, 60 G							-
32964	HeartScreen IKO 80G-L, 80C-L	roll	80	25	-	no	or/red	10
32953	HeartScreen 112 C-D KENZ - SUZUKEN	roll	112	23	-	no	or/red	10
3002	Cardico 302/601	roll	112	27	_	no	or/red	10
33003	Cardico 302/601 Cardico 302/601	pack	112	90	200	yes	or/red	20
32960	Kenz-Cardico 1210, 1211 103, R50-30R, TEC 8300	roll	210	30	-	no	or/red	5
32988	MARQUETTE - HELLIGE - G	roll	50	30	-	no	or/red	20
33010	MAC PC	roll	108	23	-	no	or/red	10
33011	Case 10-12-15, MAC 3000-5000	pack	215	280	300	hole	or/red	1
32966 33012	Cardiosmart, MAC 1200/1600	pack	210 80	295 90	150 280	yes	or/red or/red	1
33012	MAC 800	pack	110	140	200	yes	or/red	2!
	Case 10-12-15, MAC 3000-5000 Cardiosmart, MAC 1200/1600 MAC 400, MAC 600 MAC 800 MINDRAY					1		
33014	Beneheart R3 Beneheart R3	roll	80 80	20 70	200	no	or/red or/red	10 2!
32966	BeneHeart R12	pack	210	295	150	yes	or/red	1
	MORTARA					1		
33017 33010	Eli 50 Eli 100	pack roll	50 108	70 23	200	yes	or/red	2!
33019	Eli 210, 250, 280, 350, 380	pack	210	300	250	yes	or/red	"
33020	Eli 150 Eli 230	pack	108	140	200	yes	or/red	25
33021	Eli 230	roll	210	20	-	no	or/red	5
33025	NIHON KOHDEN CARDIOFAX 8110, 9620, 1150K	roll	63	30		no	or/red	20
33026	Cardio-fax GEM/1250/1950.	pack	210	140	215	yes	white	10
	ECG-9010/9020/9022	١.						
32962	Cardio-fax GEM/1250/1950, ECG-9010/9020/9022	pack	210	140	215	yes	or/red	10
33027	GEM 9010, 9020, 9022, 1250, 1950 1500, 1550, 9110, 9130, 9132, 9320, 2250	pack	110	140	143	yes	white	20
33028	1500, 1550, 9110, 9130,	nack	210	295	170	ves	white	1
		puck	2.0	233	.,,	,	***************************************	
32998	Page Writer TC/10	roll	110	25	_	no	or/red	10
32999	Page Writer TC/50 - TC/70	pack	210	300	200	hole	or/red	1
32997	Page Writer TC/10 Page Writer TC/50 - TC/70 Touch, TRIM I / II / III, Page Writer TC/20, TC/30	pack	210	300	100	hole	or/red	1
	PROGETTI							
32953	EPG 612 EPG Basik-pocket	roll	112	23	-	no	or/red	10
32996	EPG Basik-pocket	roll	58	25	-	no	or/red	20
3037	SCHILLER AT 1 AT 4	pack	90	90	390	yes	green	2!
32982	AT 1, AT 4 AT 2, CS 200 AT 10	pack	210	280	215	yes	or/red	1
33038	AT 10	pack	210	140	250	yes	green	10
32983	AT 101 AT 102	pack	80 210	70	300	yes	or/red	20
32984 33039	AT 102 AT110, AT 10 Plus, AT 2 Plus	pack pack	210	280 140	200 150	yes yes	or/red green	1 5
22027	Cardionad MS 2010	nack	114	90	200	yes	green	20
3040	Esaote my Cardiopad 2157036 SIEMENS	pack	210	140	180	yes	or/red	5
32990	Cardiostat 1	pack	50	75	400	yes	or/red	20
32991	Cardiostat 11	pack	63	75	400	yes	or/red	2!
	TRISMED	ľ				1		
32989 33046	Cardipia 201N Cardipia 400, 406RS	roll roll	63 110	30 30	-	no no	or/red or/red	21
33047	Cardipia 800, 812RS	roll	215	30		no	or/red	5

GIMA ECG MANUFACTURER Type Width Length Sheet Marker Grid' Min.

# ■ SONY MEDICAL PRINTERS ■ SONY ORIGINAL PAPER



154x240xh 88 mm, for flexible integration into medical carts

33968

# SONY

33993

### • 33968 SONY HYBRID GRAPHIC PRINTER UP-X898 MD black/white

Produces A6 size printings in about 2 seconds, with superb print quality with 325 dpi and grey level of 256 steps. Can take both analogue video and digital signal inputs. 110-240 V AC, 50/60 Hz.

• 33993 SONY COLOUR PRINTER UP-25 MD

High quality analogue A6 Dye. Sublimation Printer for use in medical applications. An ideal technology for making high quality,

accurate photographic prints. See more info on

www.gimaitaly.com



### SONY VIDEOPRINTER PAPERS

- 72726 SONY PAPER UPP-110 HD box of 10 rolls High density printing paper - 110 mm x 20 m
- 72727 SONY PAPER UPP-110 HG box of 10 rolls High glossy printing paper - 110 mm x 18 m
- 72728 SONY PAPER UPP-110S box of 10 rolls
- 72729 SONY PAPER UPP-110HA box of 10 rolls
- 72735 SONY COLOUR PAPER UPC-21L

# (4 ink rolls + 200 supports 144x100 mm)

# MITSUBISHI ORIGINAL PAPER

• 72740 MITSUBISHI PAPER K65HM-CE - box of 4



# COMPATIBLE PAPERS FOR SONY AND MITSUBISHI PRINTERS



Compatibility SONY MITSUBISHI grade mm x m order 72745 UPP-110HG K91HG/KP91HG 110x18 box of 5 high glossy 72746 UPP-84HG 84x12.5 box of 10 72747 UPP-110HD 110x20 box of 5 72748 K65HM/KP65HM 110x20 box of 5 high density 72749 UPP-210HD 210x25 box of 5 72750 UPP110S 110x20 box of 5 standard K61S/KP61S/KP61B

ULTRASOUND COMPATIBLE PAPER FOR VIDEOPRINTERS Top quality thermal print media perfectly fitting Sony and Mitsubishi thermal printers.

Long lasting image durability for high storage durability

- high humidity and heat resistance for long storage - strong resistance to water, finger prints and ultrasound gel drops.

Precise, high resolution image reproduction - first class colour intensity for highest black

- colour density
   outstanding, bright, sharp and detailed medical image - high glossy, brilliant, photorealistic reproduction Trouble-free printing and long-term use of printer
- easy tearing along the cross direction minimum curling for flat photo media and easy
- built-in anti-electrostatic layer preventing
- thermal head damage.



# ■ COMPATIBLE DEFIBRILLATOR ECG THERMAL PAPER - DIFFERENT BRANDS

GIMA	MANUFACTURER	Туре		Length	Sheet	Marker		Min.	GIMA	MANUFACTURER	Туре			Sheet	Marker		Min.
code	AND MODEL		mm	m				order	code	AND MODEL		mm	m				order
	CORPLUS									PHILIPS							
33100	Corplus 3	roll	106	20	-	no	or/red	10	33102	Defibrillator MRX	roll	75	25	-	no	or/red	10
	MINDRAY								33103	Heartstart XL	roll	50	30	-	no	or/red	20
32968	Beneheart D3, D6	roll	50	20	-	no	or/red	20		PHYSIO CONTROL							
	HEWLETT PACKARD								33032	Life Pack 8-9-10	roll	50	23	-	no	or/red	20
33103	40457C/D, Codemaster 100, XL	roll	50	30	-	no	or/red	20	33033	Life pack 11-12-15	roll	107	25	-	no	or/red	10
	NIHON KOHDEN									SCHILLER							
33029	Def. TEC 5521, 5531,	a a ata		100	200			25	32983	Defigard 6002	pack	80	70	300	yes	or/red	20
	BSM 2300, 3000	pack	50	100	200	no	or/red	25		ZOLL							
32988	Tech-8300	roll	50	30	-	no	or/red	20	33106	Defi/1400 (P/N 8000-0300)	pack	90	90	200	yes	or/red	20
'or/red:	izasa rectrission in the state of the state																

# GIMA ULTRASOUND GEL



GIMA code	ULTRASOUND GEL	Minimum order	GIMA ULTRASOUND GEL Hypoallergenic, water soluble gel suitable for ultrasonography.
33269	Sterile ultrasound gel - sachet - 20ml - transp	box of 48	Hypoallergenic, water soluble gel suitable for ultrasonography, doppler and defibrillator applications. It ensures the
33271	Ultrasound gel - sachet - 20ml - transparent	box of 200	ultrasound waves come to the equipment display in a clear and uninterrupted way. Salt, formaldehyde, fragrance free.
33270	Ultrasound gel - tube 60 ml - transparent	box of 12	and uninterrupted way. Salt, formaldehyde, fragrance free.
33272	Ultrasound gel - tube 250 ml - blue	box of 40	
33273	Ultrasound gel - tube 250 ml - transparent	box of 40	GIMA
33274	Ultrasound gel - bottle 1 l - blue	box of 12	Ultrasound
33275	Ultrasound gel - bottle 1 I - transparent	box of 12	ce lead to the lead of the lea
33276	Ultrasound gel - tank 5 l - blue	box of 2*	Name and the Control of the Control
33277	Ultrasound gel - tank 5 l - transparent	box of 2*	Throughout the same of the sam
33278	Ultrasound gel - bag 5 I - blue	box of 4**	
33279	Ultrasound gel - bag 5 I - transparent	box of 4**	COMPLEX SIZE
33283	Pump for tank 5 I and bag 5 I		MORTHWAY
*includes	2 empty bottles 250 ml ** includes 4 empty bottles 250 ml	and 1 nozzle	33270 33271

# GEL CLEANER

• 33281 GEL PROBE CLEANER 250 ml It removes the gel left over the probe, makes the

image clearer and extends the probe life. Thanks to the active agents contained, it prevents

the bacteria to pass from patient to patient, and it ensures hygiene. Alcohol-free.



33281

# COSMETIC GEL



 $\epsilon$ 

# TECARTHERAPY CREAM

### • 33251 TECARTHERAPY CREAM 1 I

It allows to reduce the contact impedance between the probe and the skin. The high conductivity ensures the best results both in the capacitive phase and in the resistive phase of the treatment. Preservatives and dyes used are non-toxic. 33251

# EEG PASTE

# • 33262 EEG PASTE - 400 g

Used with EEG electrodes in EEG application for brain mapping. Thanks to the active substances in its content, it allows the electrode to cling to the strand of hair easily and provides conductivity. It is hypoallergenic, does not irritate skin, soluble in water and can be cleaned easily Does not contain oil and oily substances. It has no toxic effects and odour.



### KONIX COSMETIC LASER & CAVITATION GEL

Laser & Cavitation gel reduces the pain that patients experience during depilation and makes the device last longer by cooling the device head and window.

Thanks to the vacuum technology, its active substances and its high viscosity it preserves probe from damages.

It is not affected by the body salt during the use, ensures an easy application.

Technical properties: it is hypoallergenic, does not irritate skin, is water soluble and easily cleanable.

Oily substances, formaldehyde and salt free. No toxic effects and odourless.

GIMA code	COSMETIC LASER & CAVITATION GEL	Minimum order
33253	Cosmetic gel - tube 250 ml	box of 40
33254	Cosmetic gel - bottle 1 l	box of 12
33255	Cosmetic gel - bag 5 l	box of 4**
33283	Pump for bag 5 l	

<sup>\*\*</sup> includes 4 empty bottles 250 ml and 1 nozzle for easy refil

280

# GIMA PORTABLE, BIDIRECTIONAL, VASCULAR DOPPLER

### 33230 GIMA BIDIRECTIONAL DOPPLER NON STEREO with two probes: 4 and 8 MHz

Continuous wave (CW) bidirectional doppler equipped with electronic probes for high sensitivity and low background noise. - bidirectional graphic separation of flow (forward and reverse)

- LCD graphic display for real time display of forward and reverse flow in bidirectional or separate mode

- selectable amplitude scale: 1, 2, 4, 8 kHz during the test and before printing. Preset zero line

- 5 minutes (300 sec.) continuous and reviewable memorized test. Operator can select the most meaningful exam and print it.
- calculation of: heart rate, peak flow and mean flow
- simultaneous connection of high sensitivity probes
- internal rechargeable large capacity battery (Ni-Cd 1.8 Ah); the system can be operated during charging. Autonomy 8 hours
- footswitch for freezing or memorizing the graphs
- hardcopy may or may not include the parameter calculation - printing time scale: 25 mm/s
- Hi-fi audio output for correct acoustic diagnosis



- 33240 GIMA BIDIRECTIONAL PROBE 4 MHz spare for 33230
- 33241 GIMA BIDIRECTIONAL PROBE 8 MHz spare for 33230
- 33250 THERMAL PAPER 58 mm x25m (pack of 5 rolls)

# POCKET DOPPLER WITH INTERCHANGEABLE OR FIXED PROBES



### **TECHNICAL SPECIFICATIONS**

Ultrasound Frequency: 2, 5 or 8 MHz continuous wave Transducer: 2 crystal narrow beam Output power: <15mW/cm² SATA Audio Response: 300Hz - 4 KHz

Unit Controls Keys: 1 Key (for unit on/off) Indicators: Yellow battery low LED Power supply Battery 9V Alkaline (not included) Expected battery life: >9 hours

Output Headset: Audio output to optional headset (not included) Material: ABS / Noryl

Large backlight

Size - weight: 150 mm by 75 mm - 299 g Classification: Class I Type B - IEC 60601-I

### GIMA POCKET DOPPLERS

Small, lightweight, high sensitivity pocket Doppler. Its probes are ideal for use by a General Practitioner, vascular specialist for routine vascular examination in ER for vessel location, or by specialists in diabetes, urology and gynaecology. Vascular flow signals and FHR are easily located using the transducer while internal signal processing minimizes noise artefacts. The flow signal is also available to the user via the built-in loudspeaker with output level controlled by rotary volume control. 2 years warranty.

Supplied in a nice bag with probe, cable, gel tube and 7 languages user manual: GB, FR, DE, IT, ES, GR, PT.

### **GIMA POCKET DOPPLERS**

33120 DOPPLER V2005 with 5 MHz fixed vascular probe

33121 DOPPLER V2008 with 8 MHz fixed vascular probe 33123 DOPPLER V2000 (without probe)

33126 2 MHz interchangeable probe - foetal for V2000

33127 5 MHz interchangeable probe - vascular for V2000

33128 8 MHz interchangeable probe - vascular for V2000

29511 ON/OFF membrane switch spare for 33120/3

# SONOTRAX DOPPLERS



built-in audio recorder and rechargeable batteries,

battery charger, carrying bag, without probe

29496 2MHz waterproof probe - gynaecology

29497 3MHz waterproof probe - gynaecology

29498 4MHz waterproof probe - vascular

29499 8MHz waterproof probe - vascular

hours with two "AA" batteries LR6

29499

Dimension - weight:

• 29481 2 MHz WATERPROOF PROBE - gvn

• 29482 3 MHz WATERPROOF PROBE - gyn

29484 8 MHz WATERPROOF PROBE - vascular

Ultrasound working frequency: 2 MHz ± 10% Fetal heart rate: range: 50-240 bpm accuracy: ± 2 bpm resolution 1 bpm low limit: 120 bpm high limit: 160 bpm Ultrasound intensity: < 5 mm/cm Auto power off after 1 minute no signal

135x92x29 mm - 245 g

# SONOLINE COLOUR DOPPLER

0

0

### 29480 COLOUR SCREEN POCKET DOPPLER

portable and lightweight

- built-in speaker

- TFT-LCD, real-time display of FHR - three working modes: real-time FHR, average FHR and manual

- display of FHR, bar graph and heartbeat waveform, red alarm for

abnormal FHR - low power consumption, continuously work for more than 8

- 1.5 VDC - indication for probe-off and low

29483 4 MHz WATERPROOF PROBE - vascular

# TECHNICAL SPECIFICATIONS

### width 35C50EB Convex 2.0 - 5.0 • • • 33976 33977 75I 38FR | Linear 7 5 33978 65C15EA Micro-convex 6.5 5.0 - 8.5 65EC10EBMicro-convex 6.5

Mindray Scanning

band method freq. code 5.0 - 10.0 • • • • • • 5.0 - 8.5 35C20FA Micro-convex 3.5 20-50 • • • 33980 75L53EA Linear 5.0 - 10.0 • • • • •

# MINDRAY DP-10 AND DP-20 DIGITAL ULTRASOUND SYSTEM

Good image quality, easy to use and lightweight to take it anywhere. It combines fashionable design, diagnostic confidence and economy.

### DP-20 exceeds your expectations

Smart portable B/W ultrasound system with advanced features

### Display modes and imaging processing:

Broadband, multi-frequency imaging: B, B/B, 4B, B/M,

### Imaging processing:

- multi-frequency probes for 2D imaging modes -
- iClear: speckle reduction image
- THI (Tissue Harmonic Imaging) with convex probe 33976 only
- TSI (Tissue Specific Imaging)
- zoom function; spot zoom, pan zoom
- ExFOV (Extended field of view)

Extended view of the anatomical structure on all convex and linear probes allow to discover better diagnostic information.

- iTouch (Auto image optimization)

### User interface

- alphanumeric OWERTY keyboard with backlight
- trackball: speed presettable
- 8-segment TGC
- user defined blank keys: shortcut for easy access to menus

### iStation™ intelligent workflow

- Intelligent patient data management system
- integrated search engine for patient data - detailed patient information review
- intelligent data backup/restore
- patient data/image sending, data deleting (USB, DVD, DICOM)
- exam managing: activate exam

### Storage/review mode:

- image archive on hard disk and USB mobile storage medium. temporary saving in cine memory, directly transfer report to PC - 2 USB ports
- multiple image formats: BMP, JPG, DCM, FRM, AVI, DCM, CIN
- iVision: demo player
- Cine review: auto, manual (auto review segment can be set), supports linked cine review for 2D, M images
- Cine memory capacity (max.)
- clip length presettable: 1-60 s

B mode: 11959 frames M mode: 110.0 s

Supplied with GB, IT manual and CD manual (GB, FR, IT, ES, PT, DE, RU, BR).

### DIGITAL ULTRASONIC DIAGNOSTIC IMAGING SYSTEM code 33970 MINDRAY DP-10 B/W system with 1-probe connector, 12.1" high resolution LED monitor, 2 USB port, 1 VGA OUT port,

1 video OUT, 1 S-Video OUT, software, without probe 33971 MINDRAY DP-20 portable B/W system with 1-probe connector, 12.1" high resolution LED monitor, 2 USB port, THI, iStation™, software package, without probe

### PW DOPPLER

PW (Pulse Wave) doppler for probes 33976, 33977

# ACCESSORIES

Needle guided brackets for Linear probe (33977, 33983) Needle guided brackets for Micro-Convex probe (33979, 33984) 33876 Lithium-ion rechargeable battery for DP-20 Carrying bag for DP-10, DP-20, DP-30 33974 33986

UMT-110 mobile trolley for DP-10, DP-20, DP-30 SONY HYBRID GRAPHIC PRINTER X898 MD 33968 PROBES DP-10 - DP-20 FREQUENCY (MHz)



### iScanHelper function

Dedicated inbuilt tutorial function to enhance ultrasound experience.

- wide selection of application specific exam planes
- anatomical illustrations
- standard ultrasound images
- scanning reference pictures tips on scanning and diagnosing

Optional PW doppler for probes 33976 (Convex), 33977 (Linear)

DP-10/20 support superb PW Doppler imaging to access blood flow in different clinical conditions.

With PW, doctors will be able to:

- differentiate non echoarea and blood vessels
- distinguish arteries and veins
- evaluate blood flow velocity for more comprehensive diagnosis
- Check the health of a fetus by blood flow evaluation of the umbilical cord

### Features

Parameter adjustment: Gain, Sample volume size, Scale, Steer, Dynamic range, Wall filter, etc.

Measurement: Trace, HR, Velocity, PS/ED, PI, RI, etc.

TECHNICAL SPECIFICATIONS 16x29xh 35.4 cm (6.3"x11.4"xh 13.9" Dimension: Weight: 12.1" LED, high-resolution 1024x768 Display: DP-10, DP-20: GB, FR, DE, IT, ES, PT, RU, CZ, PL Display language AC100-240 V, 50-60 Hz Power: Rechargeable lithium-ion battery (DP-20 only)











• 33973 MINDRAY DP-50 PORTABLE ULTRASOUND with 15" high resolution LCD monitor, 2 probe connectors, 320GB hard disk, 4 USB ports, multiple software package, without probes. Imaging mode: B. B/B. 4B. B/M. M

Image processing technology:

Phase Shift Harmonic Imaging - Tissue Harmonic Imaging · iBeam™ Spatial Compound Imaging

iClear™ Adaptive Speckle Suppression Imaging

- Trapezoid imaging · iTouch™ Auto Optimization iZoom™ Automatically expand the image to full screen

- Slant scanning for linear probes (2D Steer)

Wideband multifrequency probes: continuously adjustable 2-14 MHz Intelligent Workflow/Storage/Review:

· iStation™ Intelligent patient data management system

· 320 GB integrated hard disk for storage - 4 USB ports Cine memory capacity (Max.) B mode: 10566 frames

M mode: 66.3 s

• 33972 MINDRAY DP-50 PT PORTABLE ULTRASOUND PHYSIOTHERAPY PRESET with 15" high resolution LCD monitor, 2 probe connectors, 320GB hard disk, 4 USB ports, multiple software package, without probes.

Same as 33973 but with real time ultrasound imaging (RTUI)

for physiotherapy.
Dedicated Physiotherapy presets: pelvic/hip/lumbar spine/
shoulder/elbow/wrist/knee/ankle/Achilles tendon/cervical spine. Dynamic tracking therapeutic effects with image comparison function. Optimal musculoskeletal image quality

# MINDRAY Z5 COLOUR DIAGNOSTIC ULTRASOUND SYSTEM

• 33880 MINDRAY Z5 COLOUR PORTABLE ULTRASOUND with 15" high resolution LCD monitor, 2 probe connectors, 320GB hard disk, 4 USB ports, multiple software package, without probes.

AC 100-240 V - 50/60 Hz

rechargeable lithium-ion battery - on request

19x41.5xh 37.8 cm (7.5"x16.3"xh 14.9"); 7.7 kg (17 lb)

A colour doppler system that offers a rare combination of high performance and low cost. Superior image quality, affordability, versatility and mobility in a unique portable Doppler system: Versatility

- scanning modes: B, Colour, PW, Power, M, FreeXros M
- image display modes: B, 2B, 4B, B/C, B/M, B/PW, Triplex PW
- applications: ABD/OB/GYN/CAR/SML/URO/VAS/ORTH/EM/NERVE - transducer variety: Convex, Linear, Micro-convex, Endocavity
- extended scanning angle with ExFov function
- high frequency linear probe for superficial scanning
- Productivity
- iTouch: quick image optimization with one-click
- iZoom: instant full screen zoom with one-click
- iStation: patient database review and analysis platform
- iStorage: direct data transfer to PC

Size and weight


- Clipboard: easy play, preview and sharing of cineloop
- Multiple image formats : BMP, JPG, DCM, AVI, DCM, CIN Mobility
- compact and streamlined design weighing 7.7kg
- 15" LCD monitor with 30 degree tilt function

33984\* 65EC10EA Micro-convex 6.5 5.0 - 8.5

33990\* 10L24EA Linear array 10.0 8.0 - 14

- dual universal transducer connectors

33875



TR. FI. DK. NO. SE

AC 100-240 V - 50/60 Hz

rechargeable lithium-ion battery - on request 19x41.5xh 37.8 cm (7.5"x16.3"xh 14.9"); 8.8 kg (19.4 lb)

# PROBES AND ACCESSORIES FOR DP-50 AND Z5

+ keyboard input

Keyboard input:

Size and weight:

	33876 33975 33987 33988 33968 33993	Needle guided brackets for Micro-Convex probe (33984) Lithium-ion rechargeable battery for DP-50 and Z5 Carrying bag for DP-50 and Z5 UMT-150 mobile trolley for DP-50 and Z5 SONY PRINTER UP-X98 MD FOR DP-50 SONY COLOUR PRINTER UP-25 MD FOR Z5														
PROBES DP-50 and Z5					QUENCY MHz)	Main application										
	GIMA code	Mindray code	Scanning method	Main freq.	Probe band width	ABDOMINAL	OB / GYN	UROLOGY	SMALL PARTS	CARDIOLOGY	MSK	VASCULAR	PEDIATRIC	DBOCTATE		
	33982	35C50EA	Convex	3.5	2.0 - 5.0	٠	٠	٠								
	33983	75L53EA	Linear	7.5	5.0 - 10.0	۰			٠		٠	٠	٠			
	33978*	65C15EA	Micro-convex	6.5	50-85					٠			•			

ACCESSORIES for DP-50 and Z5

Needle guided brackets for Linear probe (33983)



34004 75L38EA 7.5 5.0 - 10.0 Linear \*not for DP-50P1

# CHISON ECO1 AND ECO3EXP. DIGITAL ULTRASOUND SYSTEMS



HISON ECO1 DIGITAL ULTRASOUND B&W DIAGNOSTIC IMAGING SYSTEM

33863 CHISON ECO1 with 1 probe connector without probe 33864 CHISON ECO3EXP. with 2 probe connectors without probe

STANDARD PACKA	GE			
	ECO1	ECO3EXP.	ECO5	
12" high resolution LED monitor - B&W	•	•		
12" high resolution LED monitor - colour			•	
8G memory card	•	•	•	
Hot Key	•	•	•	
PC printer connection	•	•	•	
3 USB port	•	•	•	
1 ethernet port	•	•	•	
1 video out port, 1 VGA out port	•	•	•	
1 footswitch port	•	•	•	
Full screen display	•	•	•	
2.5 hours rechargeable lithium-ion battery	optional	•	•	
Power adaptor	•	•	•	
Standard software package	•	•	•	
Easy View image archive system	•	•	•	
THÍ	•	•	•	
PW (doppler function to detect blood flow speed)		•	•	

TECHNICAL SPECIFICATIONS Dimension and weight: 33.5x15.5xh 35 cm (13.2"x6.1"xh 13.8"); 6 kg

12" LED, high resolution 1024x768 Display: AC 100-240 V - 50/60 Hz

rechargeable lithium-ion battery (ECO1 option, ECO3EXP. standard)

LANGUAGE - switchable by user

GB IT FR ES DE CZ TR CN RU

• • • • • • • • • Software

**ECO1 Premium Design, Surprising Price** 

6197 ECO3EXP. Premium Black&White Model with Doppler,

- ultra-compact and ultra-light weight, easy to carry - latest LED screen technology, super bright images allow to easily view scan even outdoor.

ergonomic monitor design, 30 degree rotation, adjustable.

- ultra-long battery life up to 2.5 hours, for outdoor scanning one-key to enlarge image to full screen, easy to view from distance

- streamlined workflow, easy to operate, 6-one-key to finish the cycle of diagnosis.

Display modes and imaging processing

B, B/B, 4B, M, B/M, PW (ECO3EXP. only) multi-frequency imaging Imaging processing

- compound Imaging

- trapezoidal i-image intelligent image optimization - automatic PW trace THI (Tissue Harmonic Imaging) (ECO3EXP. only)

SRA (Speckle Reduction Algorithm)

full digital beam-former - AIO (Automatic full screen display Image Optimization)

- Chroma

### User interface

- fold-up control panel and alphanumeric keyboard - back-lit keyboard for good visibility in dark room

- interactive back-lighting

- indicator lights identify activated keys

- 8 TGC slides for easy adjustment

- short cut knob for quick adjustment (hot key user- defined)

- neat and clear keyboard layout, doctor can remember easily

- user defined preset

Streamlined workflow, one key to: - select desired application with automatic preset

- optimize the image automatically (AIO) - Make report

- save still image and CINE loop - Measure

print to PC printer\* (laser or inkject) or video printer

See list of compatible printers on our website

### EASYVIEW™ Archive system

- image archive on hard disk and USB mobile storage

- 3 USB ports

multiple image formats: BMP, JPG, DCM, CIN, AVI

cine review: auto, manual (auto review segment can be set) for 2D, M, PW (ECO3EXP. only) images

- cine memory capacity (256 frames/10s)

# CHISON ECO5 COLOUR DOPPLER DIGITAL ULTRASOUND SYSTEM



• 33865 CHISON ECO5 Colour Doppler 12" high resolution color LED monitor, 8G high speed memory, 3 USB ports, 2 probe connectors, EASYVIEW™ archive system, without probe Imaging model: B, B/B, 4B, B/M, M, CFM, PW Imaging processing:

MCI (Multiple Compound Imaging) - trapezoidal

i-image intelligent image optimization - automatic PW trace - THI (Tissue Harmonic Imaging) - Chroma

- SRA (Speckle Reduction Algorithm) - full screen display model

- full digital beam-former - AIO (Automatic Image Optimization) Other specifications as ECO3EXP.


**TECHNICAL SPECIFICATIONS** 

Dimension and weight: 33.5x15.5xh 35 cm(13.2"x6.1"xh 13.8"); 6.5kg 12" LED, high-resolution colour 1024x768 AC 100-240 V, 50-60 Hz Display: Rechargeable lithium-ion battery

# PROBES AND ACCESSORIES FOR CHISON ECO SERIES

PR	OBES EC	01 - 3 - 5	FREQUENCY(MHz) • Main applica								itio	n	
GIMA code	CHISON code	Scanning method	Main freq.	Probe band width	ABDOMINAL	OB&GYN	UROLOGY	SMALL PARTS	BASICCARDIOL	MSK	VASCULAR	PEDIATRIC	ORTHOPAED.
33998	C3-A	Convex	3.5	2.5 - 5.0	•	•	•					•	
33999	L7M-A	Linear**	7.5	5.3 - 10.0				•		•	•	•	•
33871	L7S-A	Linear***	9.0	5.3 - 11.0				•		•	•	•	•
33872	V6-A	Trans-vaginal	6.0	4.5 - 8.0		•	•						
33997	MC6-A	Micro-convex	6.0	4.5 - 8.0	•							•	
33873*	R7-A	Trans-rectal	7.5	5.0 - 10.0			•						
33874	MC3-A	Micro-convex	3.0	2.5 - 5.0	•			•	•				
*For ECO3		CO5 only "Wi											
285	***Wit	h 30 mm footprint	for supe	erficial tissue e	exa	ms	wit	h h	igh	er r	esc	lut	ion

**ECO SERIES ACCESSORIES** 33869 Rechargeable lithium-ion battery BT-2500 (2.5 hours) 33867 ECO trolley TR-9000 33868 Carrying bag
33866 Needle guided brackets - specify for which
probe (for 33998-9, 33872-4 only)
PRINTERS 33968 SONY UP-X898 MD B&W printer (for ECO1 and ECO3EXP.)



33965

4 probe

Fetal face, virtual HD

- B/BC mode

- panoramic

chroma B/M/PW/CW

33956

33959

# CHISON OBit5 AND i8 ECOCOLOURDOPPLERS



• 33877 QBit5 ECOCOLOURDOPPLER - 15" flat high resolution LED monitor. Supplied with 2 probe connectors and 1 parking probe connector, trolley, keyboard, large image storage: 32 GB HardDisk, 6 USB ports, VGA format, without probes. Affordable and reliable colour doppler with advanced technologies: compound imaging, quad beam former imaging Q-image, Q-flow, X-contrast providing superb images. The Streamlined workflow and ergonomic outlook design improve work efficiency. Imaging modes:

Imaging modes: - Power Doppler / Directional PD - B/BC
- CFM - PW mode - CW mode - full screen - duplex, triplex
- chroma B/M/PW/CW - B, 2B, 4B, B/M, M Four chambers view, B/BC mode

- trapezoidal on linear probe

Spare for 33966

Image processing technology:
- Speckle Reduction Algorithm (SRA)

- direct print to PC or video printer automatic image optimizaton (AIO) - fusion harmonic imaging (FHI)

Special radiology function: 2D steer and super needle (optional) Phased array probe and package

Phased array probe functions include CW, TDI, ECG, Colour M and complete calculation packages including PISA/Dp/Dt

		PROBES	FREC	UENCY	(MHz)		•	Ma	in	app	olic	atio	on	
GIMA code for QBit5	GIMA code for i8	Scanning Method	Main freq.	Probe band width QBit5	Probe band width i8	ABDOMINAL	OB/GYN	UROLOGY	SMALL PARTS	CARDIOLOGY	70	<b>PROCTOLOGY</b>	PEDIATRICS	VESSELS
33953	33953	CONVEX	3.5	2-6.8	2.5-5.3	•	•	•						
33955	33955	LINEAR	7.5	4-15	5-10				•					•
33956	33956	MICRO-CONVEX (TRANSVAGINAL)	6.0	4-12	4-10.7		•							
33964	33964	MICRO CONVEX (BASIC CARDIAC)	3.0	2-6.8	2.5-6.4					•			•	
-	33963	CARDIAC (PHASED ARRAY)	3.0	-	2.5-4					•				
33879	-	CARDIAC (PHASED ARRAY)	3.0	1.5-5.3	-					•	•			
33958	33958	PEDIATRIC	5.0	4-10.7	3.5-8								•	
-	33959*	4D CONVEX	4.5	-	2.2-6.4	•	•							П

CHISON 600M PORTABLE ULTRASOUND - various measurements: distance, circumference, area, volume

Supplied with 4 probe connector, trolley, keyboard, large image storage: 500 GB HardDisk, 6 USB port, DVD-RW, VGA

Digital colour Doppler System with professional features:

I-IMAGE improves image quality and offers ECG Intelligent

Operating voltage: 100-240 V, 50-60 Hz
Cardiac Package (colour M, CW, steering M, ECG, TDI, IMT)

• 33966 i8 ECOCOLOURDOPPLER+4D PROBE AND PACKAGE

Same as 33965 but with 4D real time imaging composed of 3D

33968 SONY UP-X898 B/W PRINTER for i3, i8, QBit5

33958

pictures with addition of live motion and probe 4D convex (33959)

• 33993 SONY UP - 25 MD COLOUR PRINTER A6 for i3, i8, QBit5

format, I-image, Cardiac Package, without probes.

CFM, Power doppler, Directional PD

instant triplex, duplex, quadplex

- Multiple Compound Imaging (MCI)

Wideband multifrequency probes Continuously adjustable, 2.5-12 MHz

trapezoidal on linear probe

PW mode, CW mode (with cardiac probe)

Image processing technology:
- Tissue Harmonic Imaging (THI) on all probes
- Speckle Reduction Algorithm (SRA)

I-image optimization.

Imaging mode: - B, 2B, 4B, B/M, M

10" SVGA monitor with two probe confull Ob/Gyn software included: 7 EDD tables (BPD, GS, FL, AD, nectors, 256 frames cine memory, USB HC, AC, CRL), G.A. (fetal age) from 4-43 weeks port, VGA port, without probes - fetal weight, fetal heart rate measurement zooming and measurement functions - imaging reversing: up/down, left/right, positive/negative

(max scanning depth: 252 mm) power supply: 110-230 V, 50-60 Hz wide applications: GYN, urology, 33968 SONY PRINTER UP-X898 MD • 33901 TROLLEY FOR 33930 abdominal, small parts

33953

33964

4-steps sweep speeds for cardiac study: 4-steps zoom with depth control: x0.8, x1.0, x1.5, x2.0

• 33930 CHISON 600M PORTABLE ULTRASOUND

Liahtweiaht: only 7 kg (size: 42x27x25 cm)

FREOUENCY (MHZ) PROBES Multi-33932 CONVEX 3.5 2.5/3.5/4.0/5.0 33933 LINEAR 7.5 5.0/6.0/7.5/9.0

# SONOTOUCH™ 10.4" TOUCH ULTRASOUND COLOUR DOPPLER

• 33919 SONOTOUCH™ 30 - colour doppler with built-in probe connector, 10" high contrast LED monitor, 16 G memory, 3 USB port, video, LAN port, without probe. Lightweight, portable, small size, touchscreen ultrasound devices.

Main features: - display mode: B, B/B, 4B, B/M, M, Colour and PW mode. In the M or B/M mode, 4 steps sweep speeds.

- multi-step display magnification, depth enhancement - setting adjustment of total gain, and 8 segments of TGC slides for selection and adjustment

- multifocal firing focus, edge enhancement, frame averaging, compound

- image freezing and storage function, built-in 16 GB high-speed memory and external USB memory disk can be connected to the system for mass storage through USB port. Stored images can be retrieved for analysis.

- 256 frames of real-time images can be stored in Cine-memory - probe scanning direction can be changed and the image can be reversed in left/right, up/down direction

- measurements of distance, area, circumference, volume, OB etc. Automatic calculation of OB and cardiology. Direct display of gestation age, expected date of child delivery and direct measure of heart rate

- real-time clock displays date and time automatically

- display of body marks with corresponding probe position indication

- annotation function in image area of the screen. Special annotation terms for different exam-mode can be added according to user's requirement

- built-in rechargeable lithium Ion battery. Life up to 2.5 hours

- full touch screen display



GIMA Probe	MAR N N N N N N N N N N N N N N N N N N N
Method freq. width	ABDOMIN OB/GYI UROLOG CARDIOLC VASCULL SMALL PA
33922 CONVEX 3.5 2.5 - 5.0	
33923 LINEAR 7.5 5.0 - 10.0	
33924 MICRO-CONVEX 3.0 2.5 - 5.0	
33926 TRANSVAGINAL 6.0 4.0 - 7.5	
33927 MICRO-CONVEX 6.0 4.0 - 8.0	

# CHISON Q5, Q9 AND Q9 4D PORTABLE COLOURDOPPLER

• 33950 CHISON Q5 COLOURDOPPLER with 2 probe connector, 15" high resolution monitor, 500 GB hardisk, 2 USB port, LAN port, Video, TV, VGA out, I-Image, without probe.

Portable digital colourdoppler with high professional features: Imaging mode: - Instant Triplex, Duplex

- B, 2B, 4B, B/M, M - Power Doppler / Directional PD

- CFM - Trapezoidal - PW mode - Chroma B/PW Image processing technology:

- Multi-beam former technology

- I-image™: image optimization technology

- Speckle reduction algorithm (SRA)

- Multiple compound imaging (MCI)

Operating voltage: 110-240 V, 50-60 Hz. Manual: GB, IT, on reguest FR.

• 33952 CHISON O9 COLOURDOPPLER

Same as Q5 but with TDI quantitative cardiac dialysis, THI on all probes, double phase digital beam, DPDBF, IMT calculation, needle enhancement, 500 GB hard disk, quadplex, Cardiac Package. Suitable for cardiac use.

Cardiac Package (ECG software, CW, Free Steering M, colour M, TDI) included.

• 33951 CHISON O9+4D COLOURDOPPLER Same as O9 but with 4D real time imaging

• 33901 TROLLEY FOR Q5, Q8, Q9

		PROBES	FREQU	JENCY (MHz)		M	lair	ı a	ppl	icat	ior	ı
GIMA code for Q5	GIMA code for Q9	Scanning Method	Main freq.	Probe band width	ABDOMINAL	OB/GYN	UROLOGY	SMALL PARTS	ENDOCAVITY	CARDIOLOGY	PEDIATRICS	VESSELS
33954	33954	CONVEX	3.5	2.5 - 5.3	•	•	•					
33955	33955	LINEAR	7.5	5.0 - 12.0				•				•
33956	33956	TRANSVAGINAL (MICRO-CONVEX)	6.0	4.0 - 12.0		•	•		•			
-	33957	CARDIAC (PHASED ARRAY)	3.0	2.5 - 5.0						•		
33958	33958	PEDIATRIC	5.0	3.5 - 9.6							•	
33959	33959	4D CONVEX	4.0	2 - 6.8	•	•						

CHISON **( €** 0197 33952



# GIMA VITAL SIGNS MONITORS

"Vital Signs" is a line of small multi-parameter patient monitors, which can monitor the vital physiological parameters: non-invasive blood pressure (NIBP), pulse oxygen saturation (SpO<sub>2</sub>), electrocardiogram (ECG) and temperature (TEMP)

- small size, clear and bright display (14x17 cm) for remote view - up to 12,000 groups of NIBP measurements can be stored and listed
- up to 96 hours of SpO, and HR trend curve can be displayed
- built-in rechargeable battery, 2 hours use (35120-2) or 3 hours (35124)
- USB port (35124 only)

Manual (English)

- optional built-in thermal printer

GIMA code	MONITOR	SpO <sub>2</sub>	NIBP	ECG	TEMP	
35120	VITAL-S	•				
35121	VITAL-SNT	•	•		•	
35122	VITAL-SNET	•	•	•	•	
35124	VITAL PRO-SNET	•	•	•	•	
35125 35141	Printer*- optional * Inst Paper 5.1 cm x 12 m -	tallation don	e by Gima i Need :	f ordered w service if on	ith monitor. dered later.	
35126	Lead acid re-chargeabl	le batter	y - spare	for 3512	20-2	
35129	Lithium re-chargeable	battery	spare f	or 35124	.	
35135	Adult SpO, probe - spa		//		35120	
35136	Pediatric SpO, probe		- //		+ 35128	
35137	ECG cable - spare		- 10			
35140	NIBP cuff - 10-19 cm -	pediatri	c 🔝		Rail /clam	N an
35142	NIBP cuff - 18-26 cm -	, pediatri	c XL	1643	Clair	T
35139	NIBP cuff - 21-35 cm -			1	4	S
35143	NIBP cuff - 27-42 cm -	adult XL		CHIEF		
35127	Trolley - adjustable 73	to 113 d	m			
35128	Rail clamp			_		N
STANDAR	D ACCESSORIES 35120	35121	35122	35124		S
- Adult Spi - NIBP adu		•	•	•		SI
		•	•	•	· P	S
- Iempera	ture probe - skin type e + 10 ECG electrodes	•		• 254	27	
- Lead acid	battery •	•	•	• 351	21	Lo
- Lithium b	oattery			•	00	P



### TECHNICAL SPECIFICATIONS

Technology: Oscillometric method tandard measurement range: Systolic: Adult: 50 - 240 mmHg Diastolic: Adult: 15 - 180 mmHg MAP: Adult: 25 - 200 mmHg

pO. measurement range: 0 - 99% pO, measurement accuracy: 75 - 99% +2%

50 - 74% +3% ow perfusion performance: 0.4% Pulse rate measurement range:

Measurement accuracy

Measurement mode:

requency response:

**RESP Monitoring** 

Automatic measuring: TEMP Monitoring

+ 2 bpm or 2% whichever is greater Size: 18.5 x 18 x h 29 cm Weight: 2.4 kg ECG and TEMP

SpO.+NIBP+

ECG+TEMP

Heart rate range: 20 - 300 bpm TEMP measurement range: 25 - 45 °C Measurement mode: Manual, Auto, STAT Accuracy: ±2 bpm or 1% whichever is greater (ECG) ±0.2 °C (TEMP)

> AC power supply: 100 - 250V, 50/60 Hz Internal power supply: 12 VDC (rechargeable)

12V 2,3AH (lead-acid battery) (35120-2) 11.1 V, 4,400 mAh liuthium battery (35124)

# PC-3000 MULTI-PARAMETER PATIENT MONITOR



# • 35134 PC 3000 MULTI-PARAMETER PATIENT MONITOR

- 7" high resolution colour TFT display, 5-channel waveform display standard parameters: ECG, RESP, SpO., NIBP, 2-TEMP, PR; Arrhythmia analysis and ST segment analysis
- up to 12,000 groups parameter data & 60-hour ECG waveform storage and recall
- 1,000-hour graphic and tabular trends for all parameters
- 7-channel ECG simultaneous waveforms display
- protection against interference from defibrillator, electrosurgical knife - adult / pediatric measurement modes
- visual and audible alarms; networking capability
- carrying handle with bed-hooks

Internal software: GB, IT, On request: FR, ES, PT, PL, CZ, TR, CN,

STANDARD ACCESSORIES NIBP cuff 10 Disposable electrodes 1 ECG cable Li-ion battery 1 Body surface temperature transducer

ı	GIMA code	ACCESSORIES - SPARES								
ı	35135	Adult SpO <sub>3</sub> probe - spare								
ı	35136	Pediatric SpO. probe								
	35137	Pediatric ŚpO <sub>2</sub> probe ECG cable - spare								
	35138	Li-ion battery - spare								
	35140	NIBP cuff - arm circumf. 10-19 cm - pediatric								
	35142	NIBP cuff - arm circumf. 18-26 cm - pediatric XL								
	35139	NIBP cuff - arm circumf. 21-35 cm - adult - spare								
	35143	NIBP cuff - arm circumf. 27-42 cm - adult XL								
		TECHNICAL SPECIFICATIONS								
NIBP Monitoring										

Measuring method: Automatic measurement by oscillating method Initial cuff inflation pressure: Overpressure protection limit Adult mode: <180mmHg Adult mode: 300mmHg infant mode: <120mmHc Measuring range Systolic pressure: Diastolic pressure: Mean arterial pressure: Adult: 40-225 mmHa Infant: 40-200 mmHg

Adult: 20-215 mmHg Adult: 10-195 mmHg Infant: 20-165 mmH Infant: 10-150 mmHg Diastolic ±10% MAP ±10% Manual, Auto, STAT

Measuring range, accuracy: 25.0 - 45.0 °C, ±0.2°C SpO, & Pulse Rate Monitoring ng dual-wave length LED 35%-100% Transducer: SpO, measuring range: Low perfusion capability: SpO<sub>2</sub> display accuracy: PR measuring range: 0.4%-5% 70%-100% +3%

30bpm-250bpm PR measuring accuracy: ECG Monitoring Heart rate measurement: Heart rate display range:

±0.4 mVp - ±5 mVp 20 - 250bpm Display accuracy\*: Heart rate alarm delay time: Sensitivity selection: ±1% or ± 2 bpm, whichever is greater ≤10s Auto, ×1/2, ×1, ×2, ×4 12.5 mm/s, 25 mm/s, 50 mm/s

Sweeping speed: Common-mode rejection ratio:

Monitoring range, accuracy: RESP alarm range: 0 - 120 rpm,  $\pm 5\%$  or 2 rpm, whichever is greater 0 - 100 bpm  $\pm 10\%$ 

Other Technical Specifications 100 - 250 Vac, 50/60 Hz <80 VA

# UP 7000 MULTI-PARAMETER PATIENT MONITOR



### 35145 MULTI-PARAMETER PATIENT MONITOR ECG, RESP, SpO<sub>2</sub>, 2 TEMP, PR

- 12.1" high resolution colour TFT display
- 3 channel ECG amplification - arrhythmia analysis and ST segment analysis
- up to 800 groups parameter data & 24-hour ECG waveform
- storage and recall
- 480-hour graphic and tabular trends for all parameters
- 7 trace ECG waveforms simultaneous display protection against interference from defibrillator
- adult/pediatric measurement modes
- visual and audible alarms
- built-in rechargeable battery
- built-in thermal printer
- multilanguage internal software: GB, FR, IT, ES, PT, PL, CZ, TR, RU, CN

### ACCESSORIES AND SPARES Adult SpO, probe 35135 Pediatric SpO, probe 35136 35137 ECG cable NIBP cuff - arm circumf. 10-19 cm - pediatric NIBP cuff - arm circumf. 18-26 cm - pediatric XI 35140 35142 NIBP cuff - arm circumf. 21-35 cm - adult 35143 NIBP cuff - arm circumf. 27-42 cm - adult XL Lead acid rechargeable battery - spare Paper 5.1 cm x 12 m - box of 5 35141 Trolley - adjustable 73 to 113 cm 35150 STANDARD ACCESSORIES Adult SpO, probe Re-chargeable battery - Disposable electrode NIBP adult cuff - Printer - Dust-protective mantle Temperature probe - skin - Power supply cable - Manual (GR IT) Temperature probe - rectal - ECG cable 5 leads (RA - LA - LL - PL - C) TECHNICAL SPECIFICATIONS **NIBP Monitoring** Measuring method Measuring range: Systolic pressure: Diastolic pressure: Mean arterial pressure 40~255mmHg 10~220mmHg 20~215mmHg

pediatric: 40~200mmHa 10~110mmHg 20~165mmHg TEMP Monitoring 25.0°C~45.0°C ±0.2°C Measuring range: Response time: ≤ 15 SpO, & Pulse Rate Monitoring 35%~100% pO, measuring range: PR measuring range: ECG Monitoring 30bpm~240bpm ±2bpm +0.4m\/n~+5m\/n Heart rate measurement Heart rate display range: RESP Monitoring 20bpm~250bpm

Measuring method Thoracic impedance 0rpm~120rpm, ±5% or ±2rpm whichever is greater Monitoring range: Monitoring accuracy: Other Technical Specifications

100~250Vac, 50/60Hz Power supply: Power consumption <80 VA Display mode: 12.1 inches TFT color LCD Audible-visual alarm

Ethernet port 29x31.5x15 cm - 3.9 kg

# CMS 8000 CONTEC PATIENT MONITOR



### 35151 CMS 8000 PATIENT MONITOR ECG, RESP, SpO., PR, NIBP, DUAL CHANNEL TEMP

- 12.1" TFT colour LCD display
- multilanguage interface (GB, IT, FR, DE, ES, PT, NL, PL, CZ, TR,
- adult/pediatric/neonate measurement modes
- 8 channel waveform synchronous display
- 7 lead FCG waveform on one screen
- anti-motion, anti-ambient light interference digital SpO, technology
- AC/DC rechargeable lithium battery
- manual/AUTO/continuous NIBP measurement mode
- standard/OXY- graph/Trend-graph/big characters and view bed interfaces

### GIMΔ ACCESSORIES AND SPARES 35149 Adult SpO, probe - 3 m cable - spare 35107 Neonate SpO, probe <3 kg - reusable 35108 SpO, extension cable 35113 Pediatric NIBP cuff 18-26 cm 35114 Adult NIBP cuff 25-35 cm 35115 Adult large NIBP cuff 33-47 cm **35116** Thigh NIBP cuff 46-66 cm **35154** Rectal temp probe - optional 35158 Adjustable beigh 35155 Skin temp probe - spare 104-130 cm 35156 ECG cable - spare 35157 Printer - optional 35158 Trolley 35159 Rechargeable lithium battery - spare 32968 Printer paper roll 50 mm x 20 m

# STANDARD ACCESSORIES

Adult SpO, probe - FCG cable NIBP adult cuff power supply cable

NIBP extension tube Temperature probe - skin

manual (GB, IT, ES) on request (PT, TR) - ECG electrodes

35150

# - Rechargeable lithium battery

TECHNICAL SPECIFICATIONS Measurement period in CONT mode: 5 min 5-lead, dual channel, 3-lead, single channel Measurement alarm: 10-270 mmHg Scan speed: 12.5 mm/s, 50 mm/s ST segment monitoring Measurement and alarm range: 0-100%

Measurement and alarm range: -2.0 mV ±2.0 mV Measurement accuracy: 70-100% ±2% Method: R-F (RA-LL) impedance Measurement and alarm range: 30-250 bpn Measurement and alarm range: 0-150 rpm TEMP Apnea alarm: 10-40 sec

NIRP Method: oscillometry Mode: manual/AUTÓ/continuous Measurement interval in AUTO mode: 1/2/3/4/5/10/15/30/60/90/120/240/480/960 min

Channel: dual channel Measurement and alarm range: 0-50 °C Power supply: 110-240 V - 50/60 Hz Safety classification: Classe I type CF Defibrillation-proof applied part

tolerance: <10%

• 33774 BM7 MONITOR 12.1" touch screen LCD display - 7 channels

# BM7 PREMIUM PATIENT MONITOR FOR INTENSIVE CARE

Premium patient monitor for intensive care.

Superior features: - touch screen operation display

- individual sweep speed setting for each parameter
- 168 full hours of trend data storage
- 4-split large multiple display modes
- oxy/CRG
- drug calculation - screen freeze ON-OFF
- ST level analysis histogram

### High performances:

- ECG, SpO<sub>2</sub>, NIBP, Respiration, 2 Temp, 2 IBP
- Sidestream EtCO<sub>2</sub> optional
   13 Arrhythmia analysis modes
- high performance Suntech NIBP
- Li-ion battery with longer life time (1.5 hrs continuous operation) possibility to connect to BM central monitoring system see page 291
- 33725 CART adjustable height, basket included
- 33709 Li-ion BATTERY 11.1 V spare Same accessories and probes as BM5 monitors, see page 292, 293.

### STANDARD ACCESSORIES

3-lead, 5-lead

3-lead: LILIII

3-lead: 1 channel

5-lead: 2/7 channel

Adult: 15-300 bpm

5 lead: I, II, III, aVR, aVL, aVF, V

Neonate/pediatric: 15-350 bpm

Reusable Pediatric Cuf 5-lead patient Cable (MECA5 (AHA), MACE5 (IEC)) SpO<sub>-</sub> extension cable (2m) Electrodes - box of 10 Reusable Adult SpO, probe DC adapter (18 VDC, 2.5A) Reusable Adult Cuff (25-35 cm)

### TECHNICAL SPECIFICATIONS

Sweep speed

12.1" color TFT. 800x600 pixels Leads type Lead selection 322x250x224.8 mm Approx. 4.5 kg 6 waveforms: 2xECG, SpO<sub>3</sub>, RR or ECG waveform FtCO . 2xIBP Heart rate range theorate/pediatric. 15-350 bpm accuracy ±1 bpm or ±1% wichever is greater ed 6.25, 12.5, 25, 50 mm/sec Diagnosis: 0.05~120 Hz Heart rate accuracy

Indicators Visual alarm lamp handle and heart beat tone QRS beep & SpO, pulse beep SpO, pitch tone Battery status, external Power LED Interfaces

MONITOR Display, Resolution

Touch screen, rotary knob DC input connector: 18 VDC, 2.5 A Defibrillator Sync. Output: Signal level: 0 to 5 V pulse
 Pulse width: 100 ± 10 ms

LAN digital output for transferring data
External VGA monitor connection DC output 5VDC 14 Max

Rechargeable Li-ion battery, 1.5 hours continuous operation Thermal Printer Speed: 25, 50 mm/sec. paper width: 58 mm 168 hours trends, 20 cases of Data Storage

10 sec alarm waveform USB memory storage
Internal language (selectable) GB, FR, IT, ES, DE,
CZ, PL, PT, RO, BG, HU, TR, RU, CN, KR

Sweep speed: 6.25, 12.5, 25, 50 mm/sec Categorized alarms (3 priority levels)

Monitoring: 0.5~40 Hz Moderate: 0.5~25 Hz Moderate: 0.5~25 Hz Maximur: 5~25 Hz S-T segment detection range -2.0 to 2.0 mV Arrhythmia analysis ASYSTOLE, VTACH, VFIB, BIGEMINY, ACCVENT, COUPLET, IRREGULAR, PAUSE, PVC, RONT

TRIGMINY, VBRADY, SHORTRUN Pacemaker detection mode
Indicator on waveform display (user selectable)

Protection Against electrosurgical interference and defibrillation

RESPIRATION Thoracic impedance RA-LA or RA-LL Channel selection 5-120 breath per minute ±1 breath per minute Measurement range Accuracy

Apnea alarm 0 to 100%; (70 to 100% ±2% digits) Li-ion 11.1 V battery Thermal printer 2 paper roll User manual: GB, IT

Pulse rate range 0 to 254 bpm ±2 bpm NIBP SUNTECH Oscillometry Method

Operation Mode manual / Automatic / Continuous
Pressure measurement range 0-300 mmHg
Safety pressure: Adult: 300 mmHg
Neonate: 150 mmHg Blood pressure Adult pressure: 20 to 220 mmHc

Measurement range: Pulse rate: 30-220 bpm
Pediatric pressure: 20-160 mmHg Pulse rate: 30-220 hpm Neonate pressure: 20-130 mmHg Pulse rate: 30-220 bpm

Accuracy: The static pressure measurement is Meets ANSI/AAMI SP 10 2002

TEMPERATURE Measurement range: 10 to 45°C (59 to 113°F) ±0.1°C Compatibility YSI SERIES 400 temperature probes

Channels Accuracy

: -50 to 300 mmHg <100 mmHg ±1 mmHg >-100 mmHg ±1% of reading nent range 0 to 300 bpm Range: ±200 mmHg Zero balancing Accuracy: ±1 mmHg Drift: ±1 mmHg of over 24 hours

Transducer sensitivity: Pulse rate measurement range: 0 to 300 bpm

# BM1, BM3, BM5, BM7 MONITOR ACCESSORIES

33738 NIBP Extension cable, 3 m (necessary for all cuffs) 33735 Adult cuff - 49x15 cm - need ext. cable 33738 32848 Obese cuff 62x75.5 - need ext. cable 33738 32848 Obese cuff 62x75.5 - need ext. cable 33738 32810 Mini cuff 16x5 cm - needs 33738+33739 32811 Mini cuff 123x5 cm - needs 33738+33739 Metal connector (necessary for mini cuff) 33771 Temp Temperature sensor 3.0 m, skin type Compatible with Drager MM15114, MM15822, GE 21733601, Philips HP21059B, Nihon Kohden P242A, Datascope 0206-02-0003 Temperature sensor 3.0 m, rectal type 33743 Paper Thermal paper 57.5 mm, 38 Ø 33715 Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus 33715 Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus 33711 Li-ion battery 11.1 V for BM1 33798 Li-ion battery 11.1 V for BM1 Li-ion bat terry 11.1 V for BM7 33747 Adapter AC adapter for BM3, BM5, BM7	code		ACCESSORIES FOR BM1, BM3, BM5, BM7			33736
33737 Kit of 3 neonatal cuffs* - needs cable 33738 Mini cuff 16x5 cm - needs 33738+33739 Mini cuff 23x5 cm - needs 33738+33739 Metal connector (necessary for mini cuff)  33771 Temp Temperature sensor 3.0 m, skin type Compatible with Drager MM15114, MM15822, GE 21733601, Philips HP21059B, Nihon Kohden P242A, Datascope 0206-02-0003 Temperature sensor 3.0 m, rectal type  33742 Paper Thermal paper 57.5 mm, 38 Ø 33742 Battery Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus Li-ion battery 11.1 V - 6 cell for EtCO <sub>2</sub> - for 33782 only Li-ion battery 11.1 V - for BM1 Li-ion battery 11.1 V for BM1 Sa719 Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM1 Sa719 Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM1 Sa719 Li-ion BM1 Sa719 Li-io	33735 33736		Adult cuff - 49x15 cm - need ext. cable 33738 Child cuff - 35x11 cm - need ext. cable 33738		33735	
32811 Mini cuff 23x5 cm - needs 33738+33739 Metal connector (necessary for mini cuff) 33771 Temp Temperature sensor 3.0 m, skin type Compatible with Drager MM15114, MM15822, Datascope 2006-02-0003 Temperature sensor 3.0 m, rectal type 33742 Battery Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus 33715 Li-ion battery - Since Sept. 2007" - new BM3, Plus, BM5 Li-ion battery 11.1 V - 6 cell for EtCD, for 33782 only Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM7 33709 Li-ion battery 11.1 V for BM7					(GIMA)	(GINA)
33739 Metal connector (necessary for mini cuff)  33771 Temp Temperature sensor 3.0 m, skin type						
Compatible with Drager MM15114, MM15822, GE 21733601, Philips HP2 1059B, Nihon Kohden P242A, Datascope 2006-02-0003 Temperature sensor 3.0 m, rectal type 33742 Battery Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus Ni-MH 12V battery - Since january 2006" - BM3, BM3 Plus Ni-MH 12V battery - Since Sept. 2007" - new BM3, Plus, BM5 Li-ion battery 11.1 V - 6 cell for EtCO <sub>2</sub> - for 33782 only Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM7					32810	32811
33743 Paper Thermal paper 57.5 mm, 38 Ø 33771 33772 33772 Battery Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus 33715 Li-ion battery - Since january 2006" - BM3, BM5 Plus BM3, BM5 Plus Li-ion battery 11.1 V - 6 cell for EtCO₂ - for 33782 only Li-ion battery 11.1 V + 0 cell for BM1 Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM7 33709 Li-ion battery 11.1 V for BM7 33710	33771	Temp	Compatible with Drager MM15114, MM15822, GE 21733601, Philips HP21059B, Nihon Kohden P242A,	33738		
33742 33715 33717 33717 33717 Li-ion battery - 11.1 V for BM1 33709  Battery Ni-MH 12V battery - up to january 2006" - BM3, BM3 Plus Ni-MH 12V battery - Since january 2006" - BM3, BM3 Plus Since january 2006" - BM3, BM3 Plus Since january 2006" - BM3, BM5 Plus Since january 2006" - BM3, BM5 Since january 2006" - BM3, BM3 Plus Since january 2006" - BM3, BM3, BM3, BM3, BM3 Since january 2006" - BM3, BM3, BM3, BM3, BM3, BM3, BM3, BM3,	33772		Temperature sensor 3.0 m, rectal type			
33715 Ni-MH 12V battery - Since january 2006" - BM3, BM3 Plus 33717 Li-ion battery - Since Sept. 2007" - new BM3, Plus, BM5 33798 Li-ion battery 11.1 V - 6 cell for EtCO <sub>2</sub> - for 33782 only Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM7 33717	33743	Paper	Thermal paper 57.5 mm, 38 Ø		33771	33772
33717 Li-ion battery - Since Sept. 2007" - new BM3, Plus, BM5 33798 Li-ion battery 11.1 V - 6 cell for EtCO <sub>2</sub> - for 33782 only 33710 Li-ion battery 11.1 V for BM1 33709 Li-ion battery 11.1 V for BM7 33717	33742	Battery		22742		
33798 Li-ion battery 11.1 V - 6 cell for EtCO <sub>2</sub> - for 33782 only Li-ion battery 11.1 V for BM1 Li-ion battery 11.1 V for BM7  33715  33715	33715		Ni-MH 12V battery - Since january 2006** - BM3, BM3 Plus	33742	_	
33710 Li-ion battery 11.1 V for BM1 2 33709 Li-ion battery 11.1 V for BM7 33715						Cream III
33709 Li-ion ba ttery 11.1 V for BM7 33715	33798			1)		ative.
33703 El-1011 ba ttery 11.1 V 101 BW17	33710		Li-ion battery 11.1 V for BM1			
33747 Adapter AC adapter for BM3, BM5, BM7	33709		Li-ion ba ttery 11.1 V for BM7		33715	33717
	33747	Adapter	AC adapter for BM3, BM5, BM7			

\*\*Date is approximative. Please select battery according to picture and specifications \* Cuff 3.3-5.6 cm, 4.2-7.1 cm, 5-10.5 cm

# handle indicated on FCG display BM3 faten m ( GIMA

Battery status indicator 58 mm built-in printer for - continuous operating both real time and trend date (Speeds: 25-50 mm/sec)

Printing sample



vith bed-rail hook

Direct connection of external monitor through optional card

# **COLOUR MULTIPARAMETER MONITORS**

33718 GIMA BM3 MONITOR (7" - 800x480 - TFT display)

### • 33719 GIMA BM3 VET MONITOR - VETERINARY ECG+SpO<sub>2</sub>+NIBP+RESP+TEMPERATURE

GIMA monitors are configured with Angle of plate - 7" colour TFT LCD for a clear view adiustable

- Individual sweep speed setting for each parameter

- 128 full hours trend data stored SpO, measurement with very low perfusion Height of cart

detection and pulse beep is adiustable

- 2 traces ECG - screen freeze on/off

- connection to Central monitoring system using LAN or W-LAN - Li-ion Battery (for 1.5 hours continuous operation)

- High-performance ECG detection and analysis

• input impedance for dry skin or electrode patch

• ST level, PVC count real-time display

 3 kinds of Arrhythmia analysis pacemaker detection function

flexibility around the - Enhanced data management ward or department. graphical and tabular trends

• 20 cases per 10 sec alarm waveform stored, reviewed and printed - Internal software selectable in GB, DE, FR, IT, PT, PL, RO, HU, ES, C7 BG RU TR CN

- User manual: GB, IT (on request: ES, FR, DE).

• 33725 CART Adjustable height, basket included

See temperature sensors, cuffs, batteries and accessories at page 290, 293

STANDARD ACCESSORIES 33718 33719 3 lead patient cable (ECG) vet Disposable electrodes: 10 pcs NIBP tubing - 3m Reusable adult cuff 25-35 cm Reusable child cuff Set of 3 veterinary cuffs SpO, sensor - reusable • vet SpO, sensor extension cable 2 m Thermal printer 58 mm DC adaptor (18 VDC, 2.5A) Battery

33725

Moving cart increase

User manual: GB. IT PATIENT CENTRAL SYSTEM (up to 31 monitors) It allows the user to monitor and extract the exact

status of several patients simultaneously at a place. Convenient bidirectional communication allows you to admit new patient information, set alarms at

either central station or patient monitor.
• 33745 WIRE CENTRAL SYSTEM (PC, monitor, 16 port switch and software)
• 33746 LAN CABLE - 3 m

• 33767 LAN CABLE - 30 m

One for any monitor to be connected. Customized cable length on request.

• 33758 WIRELESS CENTRAL SYSTEM

(PC, monitor, wireless router and software) 33759 WIRELESS CONNECTION KIT

Ethernet converter and power cable

One for any monitor to be connected 33745

### TECHNICAL SPECIFICATIONS Arrhythmia analysis:

Protection:

GENERAL Display: Dimensions - Weight Trace

Indicators

Thermal printer: Battery:

Interfaces:

Operating voltage Data storage ECG Lead type: Lead selection

Heart rate range Heart rate accuracy: Sweep speed:

S-T segment detection range: -2.0 to 2.0 mV

7" colour TFT 800x480 pixels 238x250xh 163 mm - 3.1 kg 4 waveforms: 2\*ECG, SpO., Respiration Sweep speed: 6.25, 12.5, 25, 50 mm/sec Categorized alarms (3 priority levels) Visual alarm, QRS beep & SpO<sub>2</sub> Pulse beep Percent (%) SpO<sub>2</sub> pitch tone. Battery status, Enternal Power LED 25, 50 mm/sec (paper width 58 mm) Rechargeable Li-ion battery Operating time: 1.5 hours (fully charged) LAN digital output for transferring data DC input connector: 18 VDC, 2.5 A max 100-240 V 50-60 Hz 128 hours trends, 20 cases of 10 sec alarm waveform

3-lead, 5-lead (option) 3-lead I, II, III 5-lead I, II, III, aVR, aVL, aVF, V (option) Adult: 30 to 300 bpm, Neonate/Pediatric: 30 to 350 bpm ± 1bpm or ± 1%, whichever is greater 6.25, 12.5, 25, 50 mm/sec Diagnosis: 0.05 to 150 Hz - Monitoring: 0.5 to 40 Hz

Moderate: 0.5 to 25 Hz - Maximum: 5 to 25 Hz

Pressure range: Measurement range Respirations Method: Range: Accuracy: Temperature Unit

Accuracy:

SpO<sub>2</sub> % Saturation Range:

Pulse rate range

Technique: Measurement Modes

Pacemaker detection mode:

ASYSTOLE, VTACH, VEIB Indicator on waveform display (user selectable) Against electrosurgical interference and defibrillation

0% to 100% ± 2 digits (70% to 100%)

30 to 254 bpm ± 2 bpm

Manual/automatic/continuous 0 to 300 mmHg ±3 mmHg Adult pressure: 20 to 260 mmHg Pediatric pressure: 20 to 230 mmHg Neonatal pressure: 20 to 120 mmHg

Thoracic impedance 5 to 120 breath/min ± 1 breath/min

0° to 50°C (32°F to 122°F) ± 0.1°C (25°C to 50°C), ± 0.2°C (0°C to 24°C)
YSI Series 400 Temperature Probes

# ■ BM5 MULTIPARAMETER MONITOR WITH EXTENDIBLE PARAMETERS

ECG+SPO<sub>3</sub>+NIBP+RESP+ 2 TEMI

optional 2 IBP + ETCO, MODULE

12 Channel display

€ 0123

TÜV

• 33777 GIMA BM5 MONITOR - 10.4" TFT display - 7 ch ECG • 33779 GIMA BM5 VET MONITOR - 10.4" TFT display

high-performance ECG analysis

ST level PVC count display
13 kinds of Arrhythmia analysis 7 channels

- 10.4" colour TFT screen with 6 waveforms

- visible alarm lamp handle

SpO, technology with very low-perfusion detection

- SpO pitch tone

- 58 mm built-in chart recorder

- graphical and tabular trends of printing

LAN or wireless LAN

33789

- 128 full hours trend data stored

- direct DC input for vehicle transport

- Li-ion battery with long life time connection to central monitoring system

- selectable software language (GB, DE, FR, IT, PT, PL, RO, HU, ES, CZ, BG, RU, TR, CN) Standard accessories as BM3 monitor, page 291. Other accessories page 290-293.

GIMA code	TEMPERATURE, EtCO <sub>2</sub> AND IBP KIT	
33771	Temperature sensor 2.75 m - skin type	
33772	Temperature sensor 2.75 m - rectal	
33741	Exacon temperature sensor 2.75 m - rectal	
33796	EtCO, Sidestream module for 33714, 33777/8/9	
33790	Intubated Filter Line H - adult - box of 10 for 33796	
33791	Intubated Filter Line H - infant - box of 10 for 33796	
33792	Non intubated CO, nasal cannula - adult - box of 10 for 33796	
33793	Non intubated CO <sub>3</sub> rasal cannula - pediatric - box of 10 for 33796	
33794	Non intubated CO <sub>2</sub> +O <sub>3</sub> nasal cannula - adult - box of 10 for 33796	
33795	Non intubated CO, +O, nasal cannula - pediatric - box of 10 for 33796	
33786	Single line monitoring kit (catheter)	
33787	IBP Kit - disposable - single	
33788	IBP Kit - reusable (not autoclavable) - single	

IBP Kit - reusable (not autoclavable) - double

rrhytmia analysis: VTAG, VFIB, ASYSTOLIC Pacemaker detection 33777 indicated on the ECG waveform display 33790 33792 cation tubing for







### GENERAL Dimensions/Weight: 270x185xh 250 mm/4 kg Trace: 6 waveform (ECGx2, SpO<sub>2</sub>, RR 6 waveform (ECGx2, SpO<sub>2</sub>, RR or EtCO<sub>2</sub> IBPx2) categorized alarms (3 priority levels), Indicators:

visual alarm lamp handle. heart rate, SpO<sub>2</sub> pulse pitch tone battery status, external power LED Thermal printer: 25, 50 mm/sec (paper width 58 mm) Li-ion (2 hours operating time)

LAN digital output for transferring data

Nurse call system connection defibrillator sync, output DC input connector: 12 to 18 VDC, 2.5A max Operating voltage: 100-240 V, 50-60 Hz

% Saturation Range 0% to 100% Pulse Rate Range: 0 to 254 bpm 70% to 100% ±2 digits

SpO<sub>2</sub> Accuracy: Pulse Rate Accuracy: ± 2 bpm 3-lead, 5-lead (33777), 10-lead(33779) Lead selection: 3-lead; I. II. III (33777/79)

10-lead: I, II, III aVR, aVL, aVF, V1, V2, V3, V4, V5, V6 (33779 only)

3-lead 1 channel (33777/79) 5-lead: 3/7 channels (33777/79) 10-lead: 3/12 channels (33779 only

# **TECHNICAL SPECIFICATIONS FOR MONITOR 33777 - 33779**

NS FOR MONITOR 337// Adult: 30-300 bpm
Neonate/pediatric: 30-350 bpm
± 1 bpm or ± 1%, wichever is greater
6.25, 12.5, 25, 50 mm/sec.
Diagnostic mode: 0,67-150 Hz Heart rate accuracy: Sweep speed:

Monitoring mode 0,67-40 Hz Surgical mode: 5-25 Hz S-T Segment detection range: - 2.0 to 2.0 mV Asystole, Vtach, Vfib, Bigeminy, Accvent Couplet, Irregular, Pause, Pvc, Arrhythmia analysis: Ront, Trigeminy, Vbrady, Shortrun

Diagnostic analysis: 120 kinds (33779 only) Pacemaker detection mode: Indicator on waveform display (user selectable)

Protecion: against electrosurgical interference and defibrillation Oscillometric with linear deflation

Measurement Modes Manual-Automatic-Continuous Measurement range: Adult pressure: 20 to 260 mmHa Pediatric pressure: 20 to 230 mmHg Neonate pressure: 20 to 120 mmHg

Cuff pressure display 0 to 300 mmHa B.P. measurement range: Systolic: 40 to 270 mmHa

Diastolic: 10 to 210 mmHa Adjustable Cuff Inflation Pressure

Respirations Apnea alarm Temperature Unit Range: Accuracy:

Compatible with: IBP - option Channels: Measuring range Measuring accuracy:

Pulse rate counting range: Zero balancing:

Transducer sensitivity: EtCO<sub>2</sub> - option Measurement mode: Measurement range: Respiration range

Accuracy:

5 to 120 breaths/min yes 15° to 45°C (59°F to 113°F)

YSI Series 400 Temperature Probes

-50 to 300 mmHa ± 1 mmHa (<100 mmHa) ± 1 % of reading(>100 mmHg) 0 to 300 beats/min range ± 200 mmHg accuracy ± 1 mmHg drift ± 1 mmHg over 24 hours

5µV/V mmHq Sidestream 0~150 mmHg, 0 to 19% 2~150 bpm ± 2 mmHg, 0~40 mmHg ± 5%, 41~70 mmHg

± 8%, 71~100 mmHa ± 10%, 101~150 mmHc

Respiration accuracy

# ECG CABLES FOR BM GIMA AND BIONET MONITORS

GIMA code	ECG CABLES FOR BM3 (33718, 33719, 33720,		ACCESSORIES FOR MONITOR BM3, BM5, BM7							
	33721, 33722, 33723, 33724, 33780, 33781)		NEW (aft	er 6/2006)		OLD (before	re 6/2006)			
33711	3-lead patient cable kit (cable+snap connectors 33748)									
33712	5-lead patient cable kit (cable+snap connectors 33749)		337		ble kit		Vet cable kit			
33726	3-lead patient cable kit (cable+snap connectors 33750)		33/	13	- III 410	33727	/			
33728	5-lead patient cable kit (cable+snap connectors 33751)	3								
33727	3-lead veterinary cable kit (cable+3 clips connectors)	L	2 - 1	1998						
33713	3-lead veterinary cable kit (cable+3 clips connectors)	е	Br.	Ser 1	1					
33748		a			3711——		33726			
33749	5-lead snap connectors for 33712 - spare - new	а			le kit	22752	cable kit			
33750	3-lead snap type connectors for 33726 - spare - old		33760 Vet clip connect	33762	33748 Snap connect	33752 Vet clip connect	33750			
33751	5-lead snap type connectors for 33728 - spare - old		vet clip connect	Cable	зпар соппесі	vet clip connect	Snap connect.			
33752	Vet 3-lead clip type connectors for 33726-7 - spare - old									
33753	Vet 5-lead clip type connectors for 33728 - spare - old		WA 201111		10 mg / 100					
33760		-			1					
33761	Vet 5-lead clip type connectors for 33712 - spare - new	3	A Strini	12	1					
33762	3-lead patient cable	L	Marini	1000	- In	A. N. S.	160 160			
33763		е	F	33	3 <b>712</b>	<b>⊢</b>				
E	ECG CABLES FOR BM5-BM7 (33777, 33778, 33779)	a	22764		33749	33753	33751			
33764		a	33761 Vet clip connect	<b>33763</b> <i>Cable</i>	Snap connect	Vet clip connect	Snap connector			
33765	10-lead patient cable kit (cable + snap connector) only 33778			Cable	snap connect	ver ciip connect	Shap connector			
33766	3-lead veterinary cable kit (cable + clip connector)									

# ■ BM1, BM3, BM5, BM7 SpO, SENSORS - NELLCOR COMPATIBLE

		)
GIMA code	SpO <sub>2</sub> SENSORS FOR ALL BM MONITORS	SpO, REUSABLE PROBES —
33730" 33731 33732	Adult reusable finger sensor (> 45 kg) Nellcor comp 7 pin Pediatric reusable finger sensor (15-45 kg) - Nellcor comp. Vet reusable sensor - clip "Not compatible with Nellcor NP840 and N65	33730 33731 33732
	ABLE OTHER NELLCOR AND NELLCOR OXITECH BLE COMPATIBLE SpO <sub>2</sub> SENSORS - see page 295	7 pin' 33/30 33/31 33/32
GIMA code	EXTENSION CABLES FOR BM SpO <sub>2</sub> SENSORS	33716 33734
33733 33734	Extension cable*, 2 m (7 pin small SpO <sub>2</sub> connector) up to 2005 Extension cable* 2 m (6 pin SpO <sub>2</sub> connector) sold in 2005/6/7	

for units sold before Oct. 2005


# ■ NELLCOR COMPATIBLE DISPOSABLE SpO<sub>3</sub> SENSOR











### NELLCOR COMPATIBLE DISPOSABLE SpO. PROBES (not compatible with Nellcor Oximax)

33716 Extension cable\*, 2 m (7 pin big SpO, connector) since 2007

"Necessary for all probes. Please select correct one

33755 Disposable neonate/adult probe - under 3 kg (neonate foot) - over 40 kg (adult finger)

33756 Disposable infant probe - 3-20 kg

33757 Disposable pediatric probe - 10-50 kg 33754 Disposable adult probe - over 30 kg

TECHNICAL SPECIFICATION SpO, SENSORS Range of SpO<sub>2</sub> measurement: 70%~100% Accuracy: 70%~100% ±2%; below 70%: unspecified Range of pulse measurement: 30~250 bpm Accuracy: ±2 bpm of 2% (select larger)
Optical Sensor: red light (wavelength is 650~670 nm, 6.65 mW) infrared (wavelength is 880~910 nm, 6.75 mW)

# WRIST OXIMETER

# • 34340 WRIST PULSE OXIMETER - with software

Small and lightweight wrist Oximeter available for home and clinical long-term and comfortable monitoring. It can be simply worn on the patient's wrist as a watch to start the monitoring and can be used during sports to measure SpO<sub>2</sub> and pulse rate (PR) - audible and visual alarm with adjustable alarm limits

- trend review function of SpO<sub>2</sub> and PR

- selectable storage modes: 1 group/1s, 1 group/4s, and 1 group/8s - up to 500 hours storage for SpO, and PR data in default mode (1 group/8s)

- clock setting and date display function

- software to download and store all measurements on PC integrated

- removable finger probe

293

- not suitable for pediatric use



# BM1: SLIM AND LIGHT MONITOR WITH STRONG MOBILITY

### • 33714 GIMA BM1 MONITOR SpO,+NIBP optional Temp. and EtCO.

Professional multiparameter monitor in compact size: - only 60 mm (2.36 inch) thick and 1.0 kg (2.2 lb)

- easy mounting to an IV pole - 4.5 hours battery operation (rechargeable Li-ion)
- top handle and rear grip - monitoring mode and spot check mode
- 4.3" color TFT monitor for clear view 480x272 pixels - touch key and wheel navigation
- external VGA output for large LCD monitor (option) - saves 128 hours trend and 400 cases - multilanguage selectable software (GB, FR, IT, ES, DE,
- PL. PT. RO. BG. HU. CZ. RU. TR. CN. KR)
- highly advanced CO, monitoring technology
- plug and play EtCO, module
- Same accessories of BM line. SpO<sub>2</sub>, TEMP, EtCO<sub>2</sub>, NIBP technical specifications same as BM5.
- 33710 Li-lon RECHARGEABLE BATTERY spare



# PC-300 SPOT CHECK BLUETOOTH MONITOR



	Memory of	
GIMA code	PC-300 ACCESSOR	
35164 35165	SpO <sub>2</sub> pediatric probe - optional SpO <sub>2</sub> adult probe - spare	35165
35166 35167	NIBP pediatric cuff 10-19 cm - with extension cable - optional NIBP adult cuff 22-30 cm - spare	35167
35170 35171	Ear infrared thermometer Ear probe cover - box of 500	35170
35172	Lithium battery - spare C-300 ACCESSORIES: glucose and EC	
PC		
23890	Glucose monitor On Call Plus II* -	
23891	Glucose monitor On Call Plus II* -	
23892	Glucose monitor On Call Plus II* -	
23895	Glucose monitor Kit On Call Plus	
23896	Glucose monitor Kit On Call Plus	
23897	Glucose monitor Kit On Call Plus	II" - ES, PT
23910	Glucose strips - box of 25	CALLS !
23912	Glucose strips - box of 50	
23913	Glucose strips - box of 100	
35176	Glucose monitor USB cable	
35178	ECG module** needs 33248	33248
33248	ECG pin lead cable 3 leads	33240

• 35162 PC-300 SPOT CHECK MONITOR PC-300 handheld Spot-check monitor measures SpO<sub>3</sub>, Pulse Rate, NIBP and TEMP. Widely used in hospitals, clinics and family daily measurement. Equipped with Bluetooth and USB interface, allows to transfer data to PC, tablets and smartphone (Android and iOS).

- up to 6000 groups NIBP data storage, up to 100 different patients (each user can store 999 measurement records) quick ear probe TEMP measurement result in 5 seconds

data transfer to PC/Smartphone by USB or Bluetooth - optional NIBP pediatric cuff and SpO, pediatric probe optional ECG and Glucometer

built-in rechargeable lithium battery communication protocols available on request STANDARD ACCESSORIES SpO, adult probe

NIBP adult cuff Ear thermometer (probe covers not included) Lithium battery with charger Carrying bag User manual: GR FR IT FS TECHNICAL SPECIFICATIONS

SpO<sub>2</sub> Measuring range Accuracy: Pluse Rate Measuring range

30-240 bpm ±2% or ±2 bpm (whichever is greater) Accuracy\*: \*Root-mean-square value of deviation according to ISO 1919 NIRP

35%-100%

±3% (70-100%)

Pressure range: 0-300 mmHg (0-39.9kpa) Accuracy: ±3 mmHa Measuring range

Systolic pressure: 60-240 mmHa Diastolic pressure: 30-180 mmHg 32-43.0°C

Measuring range Accuracy: ±0.2°C (35-42°C) - ±0.3°C (other) Measuring time <5 s

ECG (Optional) Heart Rate measuring range: 30-240 bpm Heart Rate accuracy:

±2 bpm or ±2% whichever is greater Display scale: 5.0 mm/mV +10% Common-mode rejection ratio (CMRR): ≥60 dB

Blood Glucose (Optional) 20 to 600 mg/DL Measuring range:

SEE other specification at page 5 Power Supply

Battery: 3.7 V built-in Li-ion battery Operating voltage: 3.6-4.2 VDC Operating current:

100 - 240 VAC, 50/60 Hz, 5 VDC or USB

See electrodes at page 277-278
"ECG module can be used without 3 leads cable in palm mode

# ■ PALM SAT® 2500A NONIN PULSE OXIMETER

### • 35086 PALM SAT® 2500A PULSE OXIMETER with rubber reusable adult probe and alarm.

A compact versatile and reliable pulse oximeter designed and tested to exceed all durability requirements. Main features:

- Pure Sat® technology offers accuracy & speed in getting a reading, even with varying skin pigmentations or polish and is able to monitor, with declared accuracy in challenging conditions, such as motion & low perfusion, for all patients

- it is tested to assure performance in challenging conditions, such as drop and liquid ingress (IPX 2). Granted by US Army/Air Force Aeromedical certification

It also features: audible and visual alarms, 72 hour memory, long battery life (60 hours) or rechargeable battery for 40 hours Supplied with multilanguage cd-rom manual: GB, FR, IT, DE, ES, PT, GR, NL, PL, NO, FI, DK, SE.

### TECHNICAL SPECIFICATIONS

SnO2 range 0% to 100% ±2 (70-100% without movement) 18 to 321 bpm ±3 (18-300% without movement) Power: 4AA alkaline batteries 1.5 V (for 60 hours use) optional NiMH rechargeable battery (for 40 hours use) Size: 7x13.8x3.2 cm Weight: 213 g

GIMA

**ACCESSORIES SAT 2500** 35087 Adult reusable rubber probe (12.5-25.5 mm) - 1 m cable Rugged rubberized 35088 Pediatric reusable rubber probe (10-19 mm) - 1 m cable 35089 Charger stand with NiMH battery pack, plug kit

35082 NVISION software for data management (GB) 35083 Adaptor for USB - PC connection



REUSABLE COMPATIBLE SpO<sub>3</sub> SENSORS FOR ALL BRANDS (€0123)

1- Adult 1	finger sensor OEM -	2- N	Adult soft-finger sensor Sensor	- Adult \	/-type ear sensor 4- Adu Connector	t-neonatal wrap sensor 5- Pediatric sensor 6- Neonatal Y	-type se
code	Brand		type	length	type	Compatibility	cable - 2
35220° 35221 35222	BCI	5 1 1	Pediatric finger Adult finger Adult finger	0.9 m 0.9 m 3.0 m		BCI: 3401, 3304, 3303, 3302, 3301, 3300; Spacelabs Burdick: PRO <sub>2</sub> ; Draeger: Oxipac 2000/2500	353 - -
35225 35226 35227	CSI (Criticare)	6 1 1	Neonatal Y-type Adult finger Adult finger	3.0 m 0.9 m 3.0 m		Alaris (IVAC): VitalCheck 4400; Criticare: 503DX. 503 Spot, 504DX/P. 504DX, 506 series (except 506LN3), 507ELC2, 8100 Poet Plus, Poet (602-3A), Scholar, Scholar III	-
35230°	Datascope	1	Adult finger	0.9 m		Accusat, Accutorr 3/4 SAT, Accutorr Plus,	353
35231	Datascope	1	Adult finger	3.0 m	<b>*************************************</b>	Passport (Database SpO <sub>2</sub> )	-
35232°	Datex-	1	Adult finger	0.9 m		Datex-Ohmeda: AS/3 ,CS/3, CH/S, CH/2S, CH-RS, SAF-F, CG/2S, Cardiocap I, Cardiocap II, Cardiocap 5, Capnomac Ultima, Light	353
35233 35234 35235	Ohmeda	5 1 3	Pediatric finger Adult finger Adult Y-type ear sensor	3.0 m 3.0 m 3.0 m		Cardiocap I, Cardiocap II, Cardiocap 5, Capnomac Ultima, Light Monitor, M-Estpr, Oscar II, OSP-200, Satilte Trans, Satlile, Trans Plus, System 5, ULTS00	-
35238 35239 35240	GE Datex-	1 2 3	Adult finger Adult finger Adult soft-finger	3.0 m 4.0 m 3.0 m		GE (Datex-Ohmeda): S/5, i4 Modular Monitors with Eseries modules, Corometrics® 259 with TruSignal Ohmeda Technology	-
35241 35243	Ohmeda	1	Adult Y-type ear  Adult finger	3.0 m	(bid)	Ohmeda TruSat	-
35245	GE	GE: Dash 2000/3000/4000 with Nellcor option, Dash 3000/40  1 Adult finger 3.0 m  GE: Dash 2000/3000/4000 with Nellcor option, Dash 3000/40 Ohmeda option, Solar 8000/8000M, 19500 with Tram Module 4/ Correttier's 1202/120 series Eagle 1000/3000/4000 Resoon		GE: Dash 2000/3000/4000 with Nellcor option, Dash 3000/4000/5000 with Ohmeda option, Solar 8000/8000M, 19500 with Tram Module 451/451N 851/851N, CardioLab*Mac-Lab* with Tram Module 451/451N Corometrics* 120/2120 series, Eagle 1000/3000/4000 Responder 3000 with Nellcor option	-		
35247°	GE TruSignal	1 Adult finger 0.9 m TruSignal sensors and interconnect cables are back compatible with Datex, ohmeda and GE SpO <sub>2</sub> techn					
35250	Goldway	1	Adult finger	3.0 m	<b>(8)</b>	Goldway: UT4000 A / 4000 A pro / 4000B, UT6000 C	-
35252	Mindray	1	Adult finger	3.0 m	<b>(</b> (a)	PM-600, PM-5000, PM-6000, PM-7000, PM-8000, PM-9000, MEC- 1000 (Nellcor based) PM-50	-
35255** 35256** 35257** 35258** 35259** 35260** 35261**	Nellcor	6 5 4 1 1 2 3	Neonatal Y-type Pediatric finger Adult/neonatal wrap Adult finger Adult soft-finger Adult y-type ear	0.9 m 3.0 m 0.9 m 3.0 m		Artema: Diascope, Datascope: (Mindray): Accutorr Plus, Expert, Passport, PM-50, Drager Cicero, Narkomed, Vitalert 1000, GE Meditad: Corometrics 118, 120, 129, 188, 510, 556, Critikon 9710, 9720, Plus, Compact, Dinamap Select, MFS, Oxyphuttle, Pro 300/400. Eagle series, Dash Series, Hellige Eagle, 1000, 3000, Eagle SMK, SMU, SWM, SOLAR Series, TRAM Modular StÖLS Series, invivo Research: MIZ (Nellors Spot), Milleninal St00 Plus 2, Milleninal St00 Plus 2, Milleninal St00 Plus 2, Milleninal St00 Plus 2, Milleninal St00, Milleninal St00 Plus 100, Milleninal St00, Milleninal St00 Plus 100, Milleninal St00, Milleninal St00 Plus 2, Milleninal St00, Milleninal St00 Plus 2, Milleninal St00, Milleninal St	353 353 353 353 353 353 353
35262** 35263** 35265**	Nellcor Oxitech	1 2 4	Adult finger Adult soft finger Adult/neonatal wrap	0.9 m 0.9 m 0.9 m	man ?	Nellcor Oximax: N-550, N-560, N-595, N-600 and Patient monitors with Oximax module	353
35264	Nihon- Kohden	1	Adult finger	3.0 m		Nihon Kohden: BSM-4101,4103 4111,4113 Life scope P BSM-5105, 5135 Life scope A BSM-2351, 2353 Life scope L BSM-2301, 2303 Life scope I, Life scope S	-
35266**	Nonin	1	Adult finger	0.9 m		NONIN: 8500, 8600, 8700, 8800/9840 NONIN: 2500, 9600, 9700	-
35268 35269	Novametrix	6 1	Neonatal Y-type Adult finger	3.0 m 3.0 m	<b>*****</b>	Novametrix: 505, 510, 511, 515B/C, 520, 7000, 7100; Oxypleth	-
35272	Ohmeda	1	Adult finger	3.0 m	<b>A</b>	Datex-Ohmeda: 3740, 3710, 4700 OxiCap, 520RGM, Biox 3760, Ohmeda 3700, 3775, Rascal II, GE Medical System: 7000 series, Corometrics 511, TRAM A.R., Tram Modular x00SL Series, Mennen:Horizon XL800 (Ohmeda SpO <sub>2</sub> )	-
35275 35276 35277 35278 35279 35280 35281	Philips	6 4 1 1 2 2 3	Neonatal Y-type Adult/neonatal wrap Adult finger Adult soft-finger Adult soft-finger Adult y-type ear	1.6 m 1.6 m 1.6 m 3.0 m 1.6 m 3.0 m 3.0 m	<b>6</b>	Philips: M3, M4, MP20, MP30, MP40, MP50, MP70, MP80, VM4, VM6, VM8	
35283		2	Adult soft-finger	3.0 m		Philips: 1205, M1205A, 78352C, 78834C, 78354C, M1020A, M1025A, M1025B, M1350B, M1772A/B, M1732A/B, M2475B	-
35285 35286	Siemens/ Drager	1 2 3	Adult finger Adult soft-finger	1.6 m 1.6 m		Siemens/Drager: SC6002XL, 7000, SC8000, SC9000XL	-

### CAPNOGRAPH AND OXIMETER **(** € 0123 • 33698 CAPNOGRAPH AND OXIMETER PC-900B 510(K) This innovative and handheld capnograph and oximeter is ideal for monitoring the most severe conditions of patients. It provides reliable SpO, and pulse rate measurements thanks to its unique MoveOxy<sup>™</sup> technology specially conceived for PC software for data review and analysis SpO<sub>2</sub>. It offers an accurate monitoring even in weak pulse Software (GB only) can be freely signals condition and reliable monitoring in movement. Display of graphical trends and plethysmographic waveform. - 3.5" TFT display showing EtCO,, RR and SpO, PR - lung pressure and temperature compensation (BTPS compensation) - for intubated or non-intubated patients Wireless connection - graphic trend storage up to 24 hours Bluetooth printer - USB cable to transfer data on PC - wireless module to connect to Bluetooth printer Silicone Internal languages: GB, IT, ES, NL Water filter, sampling line and airway adapter STANDARD ACCESSORIES must be changed anytime you use it. USB data cable 2 water filters • 34351 ADULT SpO, RUBBER PROBE - reusable Nasal CO sampling cannula 2 sampling lines • 34345 ADULT SpO<sub>2</sub> CLIP PROBE - reusable - spare Silicone protective case Carrying bag • 34347 PEDIATRIC SpO. PROBE - reusable • 34349 NEONATAL SpÓ, Y PROBE - reusable • 33699 WATER FILTER • 33700 SAMPLING LINE 34345 34351 34347 33701 AIRWAY ADAPTER Support base Reusable SpO. adul 34172 NASAL CANNULAS

rubber probe probe **TECHNICAL SPECIFICATIONS** SpO<sub>3</sub> Oximetry saturation range: 0-100% Oximetry saturation range: 0-100% Accuracy: ±2% when 70-100%, ±3% when 50-69% Trand length: 24 hours 0-150 mmHg (0-20 kPa, or 0-20% (V/V)) ±2 mmHg when 0-40 mmHg ±5% (reading) when > 41-70 mmHg ±8% (reading) when > 71-100 mmHg ±10% (reading) when > 101-150 mmHg Every breath, 10, 20 or 30 sec selectable EtCO,/CO, range: Accuracy: Range: Update: ±2 bpm or ±2% (reading) when 30-250 bpm 24 hours Trend length Respiration rate Power supply 3-150 breaths/min ±1% (reading) or ±1 times/min whichever is greater 24 hours AC input consumption: 100-250 V, 50-60 Hz, 5 W
Battery: Built-in rechargeable lithium battery - 3.6 V, 3000 mAh Accuracy Trend length

OXY-200 DESKTOP PULSE OXIMETER Audible and visible alarm for over-limit and low battery Continuous working time: more than 1 hour

50-250 cc/min selectable

Screen brightness, volume and 320x240 TFT screer display mode can be adjusted and LCD

35101

• 35101 OXY-200 DESKTOP PULSE OXIMETER with monitor and battery

Portable oximeter displays SpO<sub>2</sub>, PR, bar graph, PI, pulse waveform and battery power. Multiuser data storage and review. Stored data can be uploaded to PC in real time. Finger adult probe, battery and software for PC download are

- 35102 LITHIUM RECHARGEABLE BATTERY spare
- 35105 SpO, FINGER-PROBE adult or child over 15 kg spare
- 35106 PEDÍATRIC PROBE 3-15 kg reusable
- 35107 NEONATAL PROBE <3 kg reusable needs 35108
- 35109 ADULT NEONATAL PROBE\* disposable needs 35108

### • 35108 EXTENSION CABLE necessary for 35107, 35109

TECHNICAL SPECIFICATIONS Power supply: 100-240 V, 50/60 Hz

rechargeable lithium battery SpO<sub>2</sub> measuring range: 0-100% ±2% (between 70-100%)
Pulse rate: 30-250 bpm ±2 bpm or ±2% (select larger) Resolution: 1% PI measuring range: 0-20% ±1% (between 1%-20%)

Resolution: 1 bpm Resolution: 0.1% User manual (GB, IT)

Menu operation

easy to use

Size: 269x222x79 mm - Weight: 1 kg \*Suitable for adult over 40 kg (finger) or neonate less than 3 kg (foot)

# ETCO<sub>2</sub> +SPO<sub>2</sub>

PORTABLE OXI-CAPNOGRAPHY MONITOR • 33702 OXY CAPNOGR, HUMAN • 33703 OXY CAPNOGR, VET

10 hours 70x160xh 40 mm - 600 a

Portable multifunctional Capnography monitor providing SpO,, Pulse, EtCO,, Respiration with accuracy 72 hours and reliable performance. Light and large LCD display with trend providing graphical SpO, function EtCO, and Trend function all in one design. Through optional software link to PC via USB. Filter replacement after 8 hours of use. Supplied with adult sensor, AC adapter, sampling tube, airway adapter, filter cartridge, carrying bag, 4 AA rechargeable batteries

• 33705 FILTER - box of 10

SnO Saturation

• 33706 SAMPLING TUBE 1.2 m - box of • 33708 VET PROBE - spare

### TECHNICAL SPECIFICATIONS

Range Accuracy 0% to 100% +2% between 80% to 100% 30 bpm to 250 bpm ±1% of full scale Range Average

4 breaths of EtCO<sub>2</sub> 8 breaths of respiration rate 0 mmHg to 100 mmHg 0 l/min to 99 l/min Respiration rate Memory: 72 hours Output interface: USB Default Alarm Settings:

SpO<sub>2</sub> upper limit: 100% Pulse rate upper limit: 250 bpm EtCO<sub>2</sub> upper limit: 100 mmHg SpO<sub>2</sub> lower limit: 50% Pulse rate lower limit: 30 bpm EtCO, lower limit: 0 mmHq Resp upper limit: 99 l/min Resp lower limit: 0 l/min Power 4 AA rechargeable batteries 6 volts or AC/DC adapter

# 296


Size: 170x88x44 mm

98. 72

THE EXAMPLED OF

0

# OXY-50 HANDHELD PULSE OXIMETER



for both routine check and continuous monitoring Main features: - display: 1.8" colour OLED

- resolution: 160x128 - alarm sound, pulse tone
- power supply: DC3V, <100MA
- record: data can be recorded up to 24 hours
- alarm: adjustable high and low limits
- PC software for transfering real time data

Te software for transferring real time data							
GIMA code	ACCESSORIES OXY-50						
35105	Adult probe >15 kg - reusable - spare						
35106	Pediatric probe 3-15 kg - reusable						
35107	Neonatal probe < 3 kg - reusable						
35109	Adult neonatal probe* - disposable - 70 cm						
	cable						
35108	Extension cable necessary for 35107, 35109						
	- 2 m						
Suitable for adult over 40 kg (finger) or neonate less than 3 kg (foot)							

Extension cable (necessary for 35107, 35109) Adult, neonatal probe - disposable

Pediatric probe - reusable

Neonatal probe - reusable

35106

35107

35108

### TECHNICAL SPECIFICATIONS Average pulse rate: Moving calculate the average

Display mode (OLED display) Pulse oxygen saturation (SpO<sub>2</sub>): 2 digits Pulse rate (PR): 3 digits

automatic power-off

• 34344 SOFTWARE

Manual: GB, FR, IT, ES, PT.

Pulse rate Measuring range: Resolution Accuracy:

Measuring range: Accuracy: Average value

±2bpm or ±2% 0 ~ 100%, (resolution 1%) 70 ~ 100%; ±2% Calculate the average value every 4 measure value Deviation between average

This software allows to download and store all

• 34345 ADULT SpO, CLIP PROBE - reusable - spare

• 34351 ADULT SpO, RUBBER PROBE - reusable

measurements on a PC through USB port.

• 34347 PEDIATRIC SpO, PROBE - reusable

• 34348 EXTENSION CABLE - spare for

34345-34347-34349-34351 - 1 m

25 ~ 250bpm

Battery: Oxymeter probe Dimension: value and true value does not

pulse rate every 4 cardio-beat's cycle. Deviation between average value and true value does not exceed 1%

> Continuous bar-graph display, the higher display indicates the

stronger pulse dry battery (2AA) wavelength: 660 - 880nm 110(L)x60(W)x23(H) mm about 180g (with dry battery 2AA)

Rattery status

displat

BF Type

Pulse intensity

Range:

3 ways switchahle

numbers, number and

display to show:

waveform, wav

# OXY-100 HAND-HELD PULSE OXIMETER

### • 34342 OXY-100 PULSE OXIMETER

35100

Compact pulse oximeter for hospital and rescue applications to monitor SpO<sub>2</sub> pulse rate, and perfusion index (PI). SpO<sub>3</sub> can be displayed in numbers with bar-graph of pulse as well as full display of plethysmogram.

Includes adult SpO, sensor and extension cable. Features:

- high accuracy and repeatability
- visual and audible alarm, with adjustable limits - 384-hours data storage and review (with 1/2/4/8 sec.)

### **TECHNICAL SPECIFICATIONS**

Oxygen saturation range: 35% to 100% Pulse rate range: 30 bpm to 240 bpm Perfusion index (PI) range: 0.2% to 20% Display: oxygen saturation, pulse rate, pulse strength

low battery indicator, perfusion index SpO<sub>2</sub> accuracy: not greater than 3% for SpO<sub>2</sub> range from 70% to 100% Accuracy defined as root-mean-square value of

34351

Reusable SpO\_adult rubber probe

derivation according to ISO 9919 Pulse accuracy: ± 2% of full scale Range alarm setting: SpO\_upper limit: 95%

SpO<sub>2</sub> lower limit: 85% pulse rate upper limit 100 - 240 bpm pulse rate lower limit 30 - 60 hpm Power requirements: 3 alkaline AA size batteries 4.5 V continuous working time >30 hour

Dimensions: 145x74x29 mm - Weight: 210 g Warranty: 1 year

34345

297

34342

34347

• 34349 NEONATAL SpO, Y-TYPE PROBE - reusable

All probes with cable 0.9 m Hiah resolution LCD display backlight to display SpO., PR, Pulse Bar, Pi, and



Portable and





Reusable pediatric SpO, probe Veterinary oximeter see page 369

# MINDRAY PM-60 PULSE OXIMETER

### • 35060 MINDRAY PM-60 PULSE OXIMETER PM-60 is a miniature, lightweight device capable of spotcheck and continuous monitoring of SpO<sub>2</sub> and pulse rate.

- Spot Check Mode auto-standby and power off during the idle status
- auto-increase the patients IDs
- non-alarm setting for "sensor off" occasion
- 1-99 IDs for maximum 4,000 sets of measurements

Continuous monitoring mode regular alarm handing

- enable to input patient ID manually
- view SpO<sub>2</sub> waveform for maximum 96 hours trend Other features
- suitable for adult and pediatric patients
- high resolution 2.4" colour LCD display
- adjustable visual and audible alarms
- real-time data transfer by infrared technology choose between Lithium-ion or AA alkaline batteries
- (for up to 36 hours continuous working) depending on vour run-time needs
- protective cover perfect for portable monitoring needs
- Supplied with adult reusable sensor

   35062 PROTECTIVE COVER light blue
- 35063 DATA MANAGEMENT KIT
- 35064 BATTERY CHARGING KIT (EU)
- Li-ion battery + charge stand + power cable 35062
- 35065 PEDIATRIC REUSABLE SENSOR



for PC data

Resolution: 1 bpm Refreshing rate: 1 s

Averaging time: same as SpO.

# TECHNICAL SPECIFICATIONS

Performance specifications
Display: 2.4" colour TFT Resolution: 320x240

Performance specific process of the control of the

infrared link allows downloading realtime patient data to compute

DC power interface: Charger stand for Li-ion battery
DC power requirements: input voltage 5V DC Power 1.2A
Battery: Li-ion battery 24 hours continuous working 3xAA batteries 36 hours continuous working Trend memory: Monitoring mode: Resolution: 2s

Maximum time: 96 h
Spot-check mode Review of up to 4,000 data

Measure up to 99 patients user adjustable high and low limits 3-level audible and visual alarm

**SpO**<sub>2</sub>
Measurement range: 0~100% ±2% (70~100%)
Resolution: 1%
Alarm range: 50~ Alarm range: 50~100% Refreshing rate: 1 s Averaging time: 7 s (sensitivity set HIGH) 9 s (sensitivity set MED) 11 s (sensitivity set LOW)

Pulse rate

18~300 bpm (±3 bpm non-motion) (±5 bpm motion) Alarm range: 18~300 bpm

With

Type of protection: Class II with internal electric power supply Degree of protection: BF (defibrillation proof)
Protection against ingress of liquid: IPX 2

# COMDEK HOSPITAL PULSE OXIMETERS USB Output port

- 34290 MD-600 PULSE OXIMETER with alarms
- 34291 MD-630 PLUS PULSE OXIMETER with alarms, printer and USB Light-weight pulse oximeters with high accuracy and reliable performances:
- adjustable SpO, and pulse alarm settings
- quick assessment of oxygen saturation and pulse rate

- with SpO, and pulse rate display

mindray

Spot-Check

Size: 55x120x30 mm

Weight 300 g with battery

Pulse oximeter with printer and USB (34291 only)

Built-in thermal printer allows immediate data printing. 36 hours memory (with interval of 6 seconds) or 24 hours (with interval

of 4 seconds) with possibility to recall up to 100 records (print out the last records up to 240 seconds).

Tone function and adjustable volume.

- 34295 THERMAL PAPER for code 34291
- 33704 PC-SMART LINK SOFTWARE for code 34291
- 34292 ADULT FINGER SENSOR over 40 kg reusable
- 34294 CHILD TOE SENSOR 3-15 kg reusable need 34299
   34299 EXTENSION CABLE for 34294

Oxygen saturation range: Pulse rate range

Display:

Range alarm setting: Power requirements: Dimensions - weight:

TECHNICAL SPECIFICATIONS (codes 34290-34291) 0% to 100% ± 2% between 80% to 100%; ± 3% between 65% to 79%

30 bpm to 250 bpm ± 1% of full scale

oxygen saturation, pulse rate, pulse search indicator, low battery indicator

SpO<sub>2</sub> upper limit: 100%, lower limit: 50%; pulse rate upper limit 250 bpm, lower limit 30 bpm DC 6 volts by 4 alkaline AA size batteries AC adapter output DC 6 Volts, 600 mA

172x90x36 mm (34290) - 170x88x44 mm (34291) - 240 g - 300 g (34291) - without battery



### OXY 110 PULSE-OXIMETER FOR NEONATES, CHILDREN AND ADULTS TECHNICAL SPECIFICATIONS

### • 34341 OXY 110 PULSE OXIMETER

- large 3.5 inch auto rotation TFT display for SpO,, PI, Plethysmogram, PR and temperature
- patented MoveOxy™ SpO, technology with artifact removal and anti-motion performance - various choice of SpO, probes for adult, pediatric and neonate
- in-built lithium battery up to 20 hours continuous monitoring
- adjustable alarm limit, pitch tone level, key tone and brightness
- up to 1,000 hours SpO data storage
- upgradeable to infrared ear temperature
- Supplied with adult probe, charging base, USB cable.
- 34345 ADULT SpO. CLIP PROBE reusable cable 0.9 m spare
- 34351 ADULT SpO, RUBBER PROBE reusable cable 0.9 m
- 34347 PEDIATRIC SpO, PROBE reusable cable 0.9 m
- 34349 NEONATAL Spo, Y-TYPE PROBE reusable cable 0.9 m
- 35170 EAR INFRARED THERMOMETER • 35171 EAR PROBE COVER for 35170 - box of 500
- 34344 SOFTWARE for download and store

34290

1 AC/DC Adaptor

1 Carrying bag

4 AA Batteries - alkaline

(codes 34290-34291)

Technique: dual wavelength LED Oxygen saturation range: 35 to 100% ±3% Pulse rate range: 30 to 250 bpm ±2% Perfusion index (PI) range: 0.2 to 20% Display: 3.5" TFT display
Data storage: up to 1,000 hours

easuring mode: continuous or spot check Power supply: lithium battery Charging: charging stand or USB cable Dimension: 158x73x25 mm

Weight: 240 g Data upload: USB cable or wireless







34341







- 34282 OXY-5 FINGERTIP OXIMETER
- 34265 OXY-5 PEDIATRIC FINGERTIP OXIMETER
- 34285 OXY-6 COLOUR FINGERTIP OXIMETER

To monitor pulse oxygen saturation and pulse rate through patient's finger (10-22 mm finger thickness for 34282, 34285 - 8-16 mm finger thickness for 34265) in medical and hospital

- Main features:
- SpO, and pulse rate measurement
- bargraph of pulse rate

- perfusion index display. P.I. is a numerical value that indicates the blood perfusion condition at the sensor site. It is a relative value that varies from patient to patient and from measuring site - high accuracy and repeatability: products are manufactured by GIMA (in P.R.C. facilities) under strong quality controls guaranteed by Italian notified body (CE 0476 CERMET)
- accuracy from the first reading in few seconds thanks to a unique noise rejecton capability feature

- extra stability against motion during measurement (finger bending, Parkinson's disease, hand movement, button pressing)

- audible and visible alarms
- automatic power on and power off when finger is out
- low voltage alarm display
- 8 or 9 language manual (GB, FR, IT, ES, DE GR, PT, PL\*, Arabic)
- 50 hours working time with full batteries (30 hours for oxy-6)
- supplied in plastic case with batteries and pouch
- 4 direction adjustable display (Oxv-6 only)

• 35076 CORDURA BAG with belt loop - blue

\*34265 34282 only RANGE ACCURACY RESOLUTION Pulse rate: 30-240 bpm ± 2 bpm (2%) 1bpm SpO,: 35%-99% ± 2% (75-99%) ± 3% (50-75%) Perfusion: 0.1% 0-20% ± 0.1% (0,2-2%) ± 0.2% (2-10%) Index: SpO<sub>3</sub>: low limit 90% Alarm Pulse rate: low: < 50 bpm - high > 120 bpm

1.5V (AAA size) alkaline battery x 2 Power IEC 60601-1-2 Class II (€0476 Norms: oxygen saturation, pulse rate, low battery indicator

6.6x3.6x3.3 cm - 60 g including batteries

Italian manufacturer (made in P.R.C.)

# **OXY-3 OXIMETER**



- simple operation, small & lightweight design, portable - display SpO<sub>2</sub>, SpO<sub>2</sub> waveform, PR, Pulse bar

35076

- low power consumption
- 2 AAA alkaline batteries included
- low battery indication, auto power off - accommodates widest range of finger sizes from pediatric to adult
- soft silicone padding, strong slip - resistant clip, non-invasive, no pricking
- 4 direction display - user manual in GB, IT, ES, FR
- 35075 SILICONE COVER light blue • 35076 CORDURA BAG with belt

299

loop - blue

# OXY-4 COLOUR OXIMETER



• 35091 OXY-4 OXIMETER - blue

• 35092 OXY-4 OXIMETER - orange

• 35093 OXY-4 OXIMETER - other colour (minimum 100 pieces) Select colour with order

Select colour with order

1 2 3 4 5 6
Fingertip pulse oxymeter to monitor pulse oxygen saturation, pulse rate, and perfusion index.

- it is light, small in size and easy to take

- accurately measures SpO, value and pulse rate value
- · dual-color display of SpO, PR, PI, Plethysmogram and pulse bar
- measuring range, SpO, 35 99%, Pulse rate 30 240 bpm - innovative 4 directions display
- automatic power On/Off
- more than 30 hours continuous working with 2AAA alkaline batteries audible and visible alarm function
- battery voltage indication, low battery voltage alarm
- prevention against water ingress, drop resistant
- manual in 8 languages: GB, FR, IT, DE, ES, PT, GR, PL • 35076 CORDURA BAG with belt loop - blue



Back light display 2400 tests performed with one AAA battery (21 hours continued use)

( € 0123

Lead (PR) free and latex free

• 35079 NONIN GO2 -9570 - IT, FR, DE, NL 35080 NONIN GO2 -9570 - GB, FR, ES, PT GO2 are manufactured to

the same technical specifications and technology used in NONIN professional oximeters, but are dedicated to consumers

for people suffering from shortness of breath, fatique or limited activities. - highly resistant: it is tested to resist 25 times

- to fall down from 1 meter, to liquids and to continuative use
- patient oriented display
- finger size range from pediatrics to adult
- easy to read perfusion indicator

- suitable for low perfusion patient Other manuals for download: GR, PL, DK, NO, SE, FI.

### TECHNICAL SPECIFICATIONS

Saturation range: 0-100% ±2 digit (70-100%) Pulse rate range:18-321 bpm ±3 digit (20-250 bpm)

# **OXY-PED**



### • 34266 OXY-PED PEDIATRIC OXIMETER

Similar to OXY-6 but suitable for pediatric use. Input shaped to fit children's fingers thickness 8-16 mm. It is supplied with two rechargeable batteries and USB battery recharger. All other specifications are like OXY-6 model.

• 34270 RECHARGEABLE BATTERY - spare



ACCURACY 30-240 hr + 2 hnm (2%) 1bpm 1% ± 2% (75-99%) 35%-99% SpO,: ± 3% (50-75%) Perfusion index: 0-20% ± 0.1% (0.2-2%) 0.1% ± 0.2% (2-10%) Alarm: SpO2: low limit 90%

Pulse rate: low: < 50 bpm - high > 120 bpm

Power: 3.6V rechargeable batteries Norms: IEC 60601-1-2 Class II

# NONIN GO2 OXIMETER NONIN ONYX® VANTAGE 9590

Large Bright LED Display SpO<sub>2</sub> and pulse rate can be read from any angle, day or night

The original all-in one digital fingertip pulse oximeter" Lead (PB) free and latex free

### 35085 NONIN ONYX® VANTAGE 9590 PULSE OXIMETER

The Onyx is the only finger pulse oximeter with scientifically proven accuracy in motion and low perfusion, and it is tested for use on fingers, thumbs, or toes.

- Accurate - Scientifically proven performance in the widest range of patient populations and settings Durable - Protects against dropping and water spills; allows for thousands of uses in the most demanding environments and exceed IP32 water ingress testing

- Efficient Up to 6000 spot checks or 36 hours of continual operation on two AAA batteries
- Safe Built in the USA with lead-free and latex-free construction
- Versatile One unit works on the widest range of patients from pediatric to larger adult patients. Accomodates a wide range of digit thicknesses from 8 mm to 25.4 mm
- Warranted Industry-leading 4-year warranty

- Cost Effective - Proven accuracy, quality and durability make the Onyx Vantage a smart purchase for the long term

Supplied with multilanguage CD-rom manual: GB, FR, IT, DE, ES, PT, GR, NL, PL, NO, FI, DK, SE.

	TECHNICAL SPECIFICATIONS							
Pulse rate range:	18-321 bpm	±3 digit (20-250 bpm						
SpO, range:	0-100%	±2 digit (70-100%)						
Low perfusion SpO <sub>3</sub> :	70-100%	±2 digit						
Low perfusion pulse rate:	40-240 bpm	±3 digit						

# OXY-10 OXIMETER - WIRELESS



• 35095 OXY-10 FINGERTIP MULTIFUNCTION OXIMETER

Professional oximeter to monitor pulse oxygen saturation and pulse rate through patient's finger (adult, child, neonate).

wireless Bluetooth technology for transmission to PC Windows (XP and Seven) and Android (need APP). Software for data management

- external pediatric SpO<sub>2</sub> probes

available in 4 sizes for pediatric and neonatal use - large true colour OLED display

- SpO<sub>2</sub>, PR, Pulse bar, P.I. and plethysmogram
- accuracy from the first reading in a few seconds - extra stability against motion during measurement - audible and visible alarms with high and low alarm limits adjustable by user

NEONATAL PROBES

Neonatal reusable probe

with disposable wrap

- patient oriented display with automatic EXTERNAL PEDIATRIC change of 4 directions - 9 languages manual (GB, FR, IT, DE, ES, GR, PT, PL, Arabic) Communication protocols on request Supplied in nylon bag with batteries • 35096 PEDIATRIC CLIP PROBE - reusable

- 35097 PEDIATRIC RUBBER PROBE reusable • 35094 NEONATAL PROBE KIT - reusable
- probe + 20 disposable wraps • 35099 NEONATAL Y-PROBE - reusable

TECHNICAL SPECIFICATIONS RANGE ACCURACY Pulse rate 30-240 bpm ± 2 bpm or 2% 70%-100% + 3% Perfusion index (PI): 0.2-20% Alarm: SpO.: 85-99% Pulse rate: high 100-240 bpm low 30-60 bpm

Power: 2xLR03 (AAA) Alkaline batteries 3.0 VDC

Weiath: 35 a

60x33x30 mm



35094

300

# ■ iPAD CU-SP1 INTELLIGENT PUBLIC ACCESS DEFIBRILLATOR

CU-SP1 is the last generation of intelligent public access defibrillators with innovative features:

- Auto volume adjustment

It detects the ambient noise and automatically adjusts the volume of its prompts to make them audible over the background noise.

- Smart pads - intelligent storage

The pre-connected "Smart" electrode pads are stored in an easy access compartment on the underside of the unit. This ensures that the iPAD SP1 is always ready to be used in the shortest time possible. In addition, the visual frontal indicator shows if the connected pads are within their life expectancy. The indicator will change when the pads have only 3 months life left before their expiry date giving you time to arrange for replacements. It will change again when the expiry date is reached. - CPR detection

CPR ensures that the casualty has the best chances of survival. The CU-SP1 detects if CPR is being performed with appropriate prompts, if not it encourages the responder to perform it.

- Easy communication with CU-EX1 software

Installing CU-EX1 software onto a computer allows you to see and analyze the usage history of the unit. Information such as

time of "power on", the casualty's heart rhythm and shocks delivered are all clearly presented.

The iPAD CU-SP1 can store up to 5 events with up to 3 hours of ECG analysis on an SD memory card.

- 16 languages available (to be indicated with order)

Selectable software languages: US, GB, FR, IT, ES, DE, PT, NL, PL, SE, DK, NO, CZ, GR, AE, KR, IL. On request LT. Supplied with adult SAVE PADS, carrying

bag CD

g, disposable lithium battery pack, paper manual (GB, IT) and manual in above languages excluding PL and GR.							
AMIE	iPAD CU-SP1 AED DEFIBRILLATOR						

GIMA code	iPAD CU-SP1 AED DEFIBRILLATOR
	iPad CU-SP1 defibrillator - semiautomatic

### ACCESSORIES FOR CU-SP1

- 35342 Trainer Defi Pads kit of 2 35343 Trainer - 16 selectable software languages
- 35344 Adult PADS kit of 2 pcs disposable 35345 Pediatric PADS - kit of 2 pcs - disposable
- 35346 Disposable lithium battery LiMnO high capacity 4.2 Ah
- 33423 Wall cabinet with sound alarm
- 35349 SD card+ software for event recording download

# METAL CABINETS FOR DEFIBRILLATORS - INDOOR OR OUTDOOR

# METAL CABINETS FOR DEFIBRILLATORS - INDOOR USE

- 35330 METAL CABINET INDOOR USE white
- 35331 METAL CABINET WITH ALARM INDOOR USE white Door with opening at 180° with transparent acrylic window. Suitable for wall mounting or use with pole.
- 35333 POLE for cabinet white

### METAL CABINETS FOR DEFIBRILLATORS - OUTDOOR USE

• 35334 METAL CABINET - OUTDOOR USE - vellow Water tight welding on the sides, water and dust proof gaskets. Made in carbon steel, thickness 15/10. Adjustable internal shelf. Door with transparent acrylic window.

• 35335 METAL CABINET WITH THERMO REGULATION SYSTEM AND ALARM - OUTDOOR USE - yellow

Same as 35334, with antitheft magnetic sensor that activates a 100 dB siren in case of non authorized withdrawal. 9V alkaline battery for alarm. Low charger indicator. Power 230V for thermoregulation.

Suitable for wall mounting or use with pole. • 35337 POLE for cabinet - yellow

# AHA/ERC 2010 GUIDELINES **TECHNICAL SPECIFICATIONS**

Defibrillator Operating mode: Waveform: Energy:

Sealing:

Automatic defibrillator

35340

Semi-automatic e-cube biphasic (Truncated exponential type) 150J fixed Adult: nominal 150J at 50 ohm load

Infant/child: nominal 50 joules at 50 ohm Charge control controlled by automated natient analysis system Charging time: within 10 seconds since voice instruction "an electric

shock is needed"
wateriet proof IPX5 per IEC60529 (IP55) dust protected IP5X per IEC60529

detailed voice prompts and flashing indicators

voice prompts for how to perform CPR for adult and child

on/off button, "i" button, shock button (only 35340)

LCD display (Device status, Battery status, Pads status)

### User interface User support: CPR guidance: Controls: Indicator:

Sensina: pads expiry date. Pads connection status CPR Monitoring Automatic Volume adjustment

Data recording and transmission wireless transmission of event data to PC, SD Card IrDA port:

Internal Memory (Nand-flash): ECG, Event Storage capacity: multi recording 5 events / Max 3 hours
Data review PC Programme: CU-EX1

Patient analysis system

Shockable Rhythms - Ventricular Fibrillation, Tachycardia Patient Analysis: Sensitivity/Specificity Meets AAMI DF80 Guideline

Disposable high capacity battery
Standard Type: DC 12 Volt 4.2 Ah, Lithium manganese dioxide Capacity: Minimum 200 shocks (1501)

# INDOOR USE

- Horn alarm at 100 dB (only 35331)



External size: 42.5x16xh 42.5 cm Internal size: 40x13xh 40 cm

**OUTDOOR USE** DEFIBRILLATOR

PROTECTION External size: 43x21xh 48 cm Internal size: 42x20xh 45 cm

State LFC

DA port used

for data communication

# iPAD CU-SP2 AED MODE DEFIBRILLATOR



### 35341 IPAD CU-SP2 DEFIBRILLATOR - AED MODE

CU-SP2 is the last generation of intelligent public access defibrillators with innovative features:

### - Auto volume adjustment

It detects the ambient noise and automatically adjusts the volume of its prompts to make them audible over the background noise.

- Smart pads - intelligent storage The pre-connected "Smart" electrode pads are stored in an easy access compartment on the underside of the unit ensuring use in

the shortest possible time. In addition, the visual frontal indicator shows if the connected pads are within their life expectancy. The indicator will change when the pads have only 3 months life left before their expiry date giving you time to arrange for replacements. It will change again when the expiry date is reached.

### - CPR detection

CPR is vital to ensure that the casualty has the best chances of survival. iPAD CU-SP2 detects if CPR is being performed with appropriate prompts, if not it encourages the responder to perform it.

### - Easy communication with CU-EX1 software

It allows to see and analyze information such as time of "power on", the casualty's heart rhythm and shocks delivered. It saves 3 events on the internal memory (up to 17 hours per event).

- Wireless ECG transmission device (CU-EM1) - optional In monitor mode, iPAD CU-SP2 uses Bluetooth to receive ECG data from CU-EM1 and displays it on the LCD screen.

### - Printer - ontional

iPAD CU-SP2 supports connection to an external Bluetooth printer.

### - 16 languages available

Selectable software languages: GB, FR, IT, ES, DE, PT, NL, SE, PL, FI, DK. NO. CZ. GR. UA. KR.

Supplied with adult SAVE PADS, carrying bag, disposable Li-ion battery pack, paper manual (GB, IT) and CD manual in above languages excluding PL and GR. Warranty 5 years.

### **TECHNICAL SPECIFICATIONS**

Operating mode: Semi-automatic Waveform:

Defibrillator

e-cube biphasic (Truncated exponential type) AED mode: 150/200J fixed or 150-150-200J energy escalating Energy:

Manual mode: 2-2001, R-Sync Charging time: within 10 seconds

Charging time after CPR finished: at least 6 seconds Sealing: waterjet proof IPX5 per IEC60529 (IP55) dust protected IP5X per IEC60529

### User interface User support: detailed voice and text prompts

voice prompts for how to perform CPR for adult and child on/off button, "i" button, shock button, soft keys CPR guidance: Controls: Indicator: graphic LCD display (status, user's guide, ECG, heart rate, ....

Sensing: pads expiry date, pads connection status CPR Monitoring, ECG Monitoring, Automatic Volume adjustment

### Data recording and transmission

wireless transmission of event data to PC, SD Card

Internal Memory (Nand-flash): ECG, Event

multi recording 3 events / Max 17 hours for each event Storage capacity: communication with the printer

### Data review PC Programme: CU-EX1 Patient analysis system

Shockable Rhythms (Ventricular Fibrillation, Tachycardia) Patient Analysis:

Sensitivity/Specificity meets AAMI DF80 Guideline Battery

Rechargeable battery Type: DC 11.1 Volt 1.9 Ah, Li-ion rechargeable

Capacity: Minimum 60 shocks or 3 hours of operation Type: DC 12 Volt 4.2 Ah, Lithium manganese dioxide Standard

Capacity: Minimum 200 shocks (150J) GIMA

### **ACCESSORIES FOR CU-SP2** Adult PADS - kit of 2 pcs - disposable 35344

35345 Pediatric PADS - kit of 2 pcs - disposable 35346 Disposable Lithium battery LiMnO, high capacity 4.2 Ah - spare

35347 Rechargeable 12 V, 1.9 Ah Li-ion battery - optional

35348 Battery charge dock + battery charger for 35347 35349 SD card+ software for event recording download

35350 Wireless ECG for CU-SP2

Wireless printer for CU-SP2

# COMPATIBLE DEFIBRILLATOR ECG THERMAL PAPER - DIFFERENT BRANDS

GIMA code	MANUFACTURER AND MODEL	Туре	Width mm	Length m	Sheet	Marker	Grid*	Min. order	GIMA code	MANUFACTURER AND MODEL	Туре	Width mm	Length m	Sheet	Marker	Grid*	Min. order
	CORPLUS									PHILIPS							
33100	Corplus 3	roll	106	20	-	no	or/red	10	33102	Defibrillator MRX	roll	75	25	-	no	or/red	10
	MINDRAY								33103	Heartstart XL	roll	50	30	-	no	or/red	20
32968	Beneheart D3, D6	roll	50	20	-	no	or/red	20		PHYSIO CONTROL							
	HEWLETT PACKARD								33032	Life Pack 8-9-10	roll	50	23	-	no	or/red	20
33103	40457C/D, Codemaster 100, XL	roll	50	30	-	no	or/red	20	33033	Life Pack 11-12-15	roll	107	25	-	no	or/red	10
	NIHON KOHDEN									SCHILLER							
33029	Def. TEC 5521, 5531,	١.		400				25	32983	Defigard 6002	pack	80	70	300	yes	or/red	20
	BSM 2300, 3000	pack	50	100	200	no	or/red	25		ZOLL	Ι'				,		
32988	Tech-8300	roll	50	30	-	no	or/red	20	33106	Defi/1400 (P/N 8000-0300)	pack	90	90	200	yes	or/red	20
*or/red:	grid could be orange or red o	olour													-		

i-PAD NF 1200 PUBLIC ACCESS DEFIBRILLATOR

Semi-automatic external defibrillator designed for minimally trained individuals It provides simple and direct voice prompts and indications for a straightforward rescue operation. Lightweight and battery powered for maximum portability. Designed to treat Ventricular Fibrillation (VF) and Fast Ventricular Tachycardia: the most common causes of sudden cardiac arrest (SCA). In SCA, the heart of the victim suddenly stops pumping. The only effective treatment for VF is the application of a defibrillating shock. It may be used on children 1-8 years old (less than 25 kg) with pediatric reduced energy pads, over with adult pads. Supplied with a set of adult pads, lithium battery (200 Shocks or 10 hours operating time), manual. According to ERC Guidelines 2010.

TRAINER: simulates all the functions of i-PAD, with 8 rescue scenarios.

Voice version		i-PAD DE	FIBRILLAT	OR AND	TRAINER			
and manual	Spanish	French	Portuguese	Italian	English	Other languages*		
DEFIBRILLATOR	33408	33409	33413	33414	33416	33417		
TRAINER	-	-	-	33424	33405	33406		
GIMA code	, 11, 11, 11							
Voice Introduces: C2 (R. H.U. L. R. No. ) R. with English manual, updated to ERC quidelines 2005 GIMA code  33418 Lithium battery pack for i-PAD and i-PAD trainer (for 200 Shocks) Disposable pads - kit of 2 pcs Disposable pediatric pads - kit of 2 pcs Carrying bag Wall cabinet with alarm sound								
33403			data comi g downloa			are		

33405 TECHNICAL SPECIFICATIONS

Semi-automatic e-cube biphasic (Truncated exponential type) impedance compensated 200J fixed Adult: nominal 200J into a 50 ohm load

Infant/child: nominal 50 joules into a 50 ohm load Shock energy accuracy: Within +3% (2001 into 50 0) Shock to shock cycle time: Typically less than 20 seconds

Voice prompts and indicators guide through protocol Protocol: Charge control Automatic by Software (Arrhythmia Detection System and Charging Control)

Operating mode

Waveform

Energy:

Voice instruction: Controls: Indicators: Patient isolation:

**C** € 0470

**JFDA** 

Battery capacity Data recording Size - Weight

FOR PUBLIC USAGE





SPECIALLY DESIGNED

Other

languages\*

Charge time from "Shock advised": < 10 seconds, typical Voice messages guide through use of defibrillator

hutton


Shock Button, i-Button, On/Off Button 7 LEDs (different colours), i-Button Type BF, defibrillation protected

12 Volt DC, 4.2 Ah, lithium manganese dioxide disposable long-life primary cell Min. 200 Shocks or 4 hours of operating time

Data Stored: First 40 minutes of ECG and the entire incident's events and analysis decision

220x260x70 mm - 2.2 kg (4.84 lbs) with battery pack

# RESCUE SAM AED DEFIBRILLATORS - SEMI OR FULL AUTOMATIC





English French Spanish 33425 33427 33430 R. KR. TH (voice with English manual)
RESCUE SAM DEFIBRILLATOR - Full automatic 33165

TRAINER FOR SEMI-AUTOMATIC RESCUE SAM 33170 20 days: FS FR PI (voice only)

GIMA ACCESSORIES FOR RESCUE SAM DEFIBRILLATORS code 33558 USB PC interface

RESCUE SAM DEFIBRILLATOR - Semi automatic

Lithium battery pack
Disposable pediatric pads (kit of 2) 33419 Disposable adult pads (kit of 2) Disposable adult pads (kit of 2) and cable 33/120 33421

Carrying bag

Energy: Charge control Charge time: Shock delivery vector

spoken and visual instructions. Voice instructions: 5 pre-programmed scenarios selected directly by the remote control. Totally safe real shock simulation

Automatic manual tests: Long life lithium battery: Battery capacity: Data recording, stored: Size-weight

33420 Disposable adult pads with cable

TECHNICAL SPECIFICATIONS Semi-automatic or Full-automatic BTE (Biphasic Exponential Truncated)

impedance compensated 200 J fixed Automatic by software (Arrhythmia Detection

Automatic by software (Arrnythmia Detection System and charging control) 
< 8 seconds, typical with new battery adult pads in the anterior (Lead II) position or reduced energy paediatric pads in anterior-posterior position Vocal and optical message guide

Battery insertion test and daily self tests 12 Volt DC, 4.2 Ah, LiMnO, disposable 200 shocks or 4 hours of continuous operating time

first 60 minutes of ECG and the entire incident's event 30x28xh 9 cm - 2.3 kg with battery

# COMPATIBLE PADS FOR OVER 90% OF DEFIBRILLATORS ON THE MARKET ADULT COMPATIBLE PADS - disposable



33609 Metrax Primedic - Heartsave AED - AED-M - 6 - 6S

since S.N. 739xxxxxxx

- Defimonitor XD

A range of compatible pads BSI certified for patients >8 years (25 kg) for most defibrillators on the market. Excellent adherence and adequate gel thickness. Includes a couple of pads, cable and connector. Maximum shelf life 30 months from production date. Latex free.

Compliance to regulations: Directive 93/42/EEC and amendments. Class IIb medical device. ANSI/AAMI: DF-80; IEC/ EN: 60601-1, 60601-2-4; ISO: 10993-1, Made in Italy.

MODEL

ı	code	BRAND		MODEL	code	BRAND	MODEL
	33576	Agilent-Philips		HeartStart XL M4735A	33587	Mindray	- Beneheart D3 - Beneheart D6
			- Heartstream/I	HeartStart XLT M3500B	33579	MRL	Life - Lifequest
			<ul> <li>HeartStart XL</li> </ul>	. 861290	33579	Nihon Kohden	Cardiolife TEC 2202 - 2203 - 5500 -
			- HeartStart 40	00 M5500B			7531 - 7600 - 7700 - 8251 all with cable
			(all with Philip	ps cable M3508A)			JC-755V, TEC 8300 with cable JC855V
	33577	Agilent Hewlett-	Packard - Code	master 100-XE-XL-XL+	33587	Osatu Bexen	- Reanibex 200 - 300 - 500 - 700 - 800
		_	- Heartstream 2	XL, XLT, XL+	33576	Philips Laerdal I	Vledical
			with cable M35	507A		- Heartstream Fo	ore Runner I AED models E, S, EM
				· 200 - 200B - 360B - XL - XL+			AED 940010XX - 940020XX - 940030XX
	33579	Artema S&W	- Cardio Aid LS -	MC - MC+		- Heartstart FR2	AED M3841A - M3861A
	33587	Cardioline	- Elife 700			- Heartstart FR2+	AED, with ECG module M3840A, M3860A
	33448	Cmos Drake	- Futura			- Codemaster M	1722A/B, M1723A/B, M1724A, M2475B
		<b>CU Medical System</b>	- i-PAD NF1200	)		(with Philips cal	ole M3507A and pad adapter 05-200)
	33578	Defibtech	- DDU 100 Lifeline A	ED - DDU 120 Lifeline Auto AED		- Heartstart MR	x M3535A (with Philips cable M3508A)
	33579	Drager	- Cardiolog 200		33588	Schiller	- Fred Easy - Fred Easy 2G
		Esaote	- MDF SAED - N				- Defigard DG4000 - DG5000 - DG6002
		Innomed		- 200 - 100 - 360B - XL+ - XL	33586	Schiller	- Defigard DG1002 - DG3002 - DG2000 EDOS
		Laerdal Medical		00	33592	Schiller	- Fred easy port - Argus PRO Lifecare
	33589		- AED 7000				- Argus PRO Lifecare 2
	33587	Medtronic-		nector Quick-Combo			- Cardiovit AT 101 Easy
		Physiocontrol		2 - 15 - 20 - 500 AED	33579	S&W	- Cardio Aid LS - MC - MC+
				ocket - 1000 AED	33579	Welch-Allyn	- AED 10 - AED20
	33600	Metray Primedic	- Heartsave AF	D - AFD-M - 6 - 69		,	DICCO DICAG DICEG

Connectors to defibrillator of compatible pade

Multilanguage envelone: English Italian French German Spanish Portuguese Greek Dutch Russian Su

connectors to denominator or compatible pads		iviaididigae	ige criverope. Eri	giisii, italiaii, i ici	nen, dennan, spe	iriisii, i ortuguese	, dices, buter, ne	assidir, Svvcdisiri
	33577	33578	33579	33586				
33448 33609 33576	1.00			9	33587	33588	33589	33592

# PEDIATRIC COMPATIBLE PADS WITH ENERGY REDUCTION SYSTEM

### PEDIATRIC COMPATIBLE PADS - disposable

These pads have an energy reduction system: defibrillator output of 150J (33606) or 200J (33603) is reduced to 50J. International RCP guidelines state 8 years as limit age for

**BRAND - MODEL** 33603 Medtronic-Physiocontrol 33603 - Lifepak 500 AED pink socket - Lifepak 1000 AED - Lifepak CR plus AED - Lifepak Express AED

pediatric treatment, corresponding to about 25 kg according to standard growth curves. Compliance to regulation as above adult compatible pads. Latex free. Made in Italy.

GIMA **BRAND - MODEL** Philips Laerdal Medical 33606

 Heartstart FR2 AED M3841A & M3861A Heartstart FR2 AED, with ECG module 3840A, M386

- PIC30 - PIC40 - PIC50

2000 - M series - E series - R series

33606

33589 Zoll Medical Corp - Zoll PD 1200 - 1400 - 1600 - 1700 -

# ORIGINAL CU, PRIMEDIC AND PROGETTI PADS

GIMA code	BRAND - MODEL	4	GIMA code	BRAND - MODEL	
	PEDIATRIC PADS			ADULT PADS	To EU Martine Toyotana, Inc.
33443 35345 35390	CU Medical System CU-ER1, CU-ER2, CU-ER3 iPad NF 1200 CU-SP1, CU-SP2 Metrax-Primedic HeartSave Pad, AED, AED-M, 6, 6S since S.N. 739xxxxxxx Progetti Rescue Sam, Rescue 230,	35345	33441 35344 35392	CU Medical System CU-ER1, CU-ER2, CU-ER3 iPad NF 1200 CU-SP1, CU-SP2 Metrax-Primedic HeartSave Pad, AED, AED-M, 6, 6S since S.N. 739xxxxxxx HeartSave Pad, AED, AED-M, 6, 6S up to S.N. 738xxxxxxx	
33430	Rescue Life 5.7" and 7"				<u> </u>

# PRIMEDIC™ EXTERNAL DEFIBRILLATORS - AED

PRIMEDIC HeartSave product range is easy to operate and offers fast operation Clear voice prompts guide first aiders through the rescue procedure. Current controlled defibrillation - CCD

CCD Biphasic technology delivers peak-free current defibrillation on the patient's heart muscle through its individualized, gentle, effective and current-controlled defibrillation pulse. Featuring an escalating defibrillation strategy, HeartSave is impedance compensated and capable of a maximum energy of 360J. Effective workflow

HeartSave is designed to help first aiders delivering the most effective life Connection support. Through its advanced workflow, HeartSave supports the rescuer socket for save in minimizing the perishock pause as well as no-flow fraction. Pediatric mode

At a touch of a button the Paediatric Mode can be promptly selected. No need of dedicated paediatric electrodes and extreme ease of use result in optimized costs of maintenance and prompt operation.

It turns on automatically as soon as the cover has been opened and rhythm analysis starts immediately as the pre-connected electrodes are attached to the patient. All accessories (razor, breathing mask, scissors and gloves) are included.

Active status display provides comprehensive information on the device's operating status and battery status (daily and monthly self-tests).

### HEARTSAVE PAD and HEARTSAVE AED

Automatic external defibrillator with 3 years life (PAD) or 6 years life (AED) in standby mode with non rechargeable lithium battery.

### The HeartSave AED has 4 selectable languages.

### HEARTSAVE AED-M

Same features as HeartSave AED, plus large LCD display for ECG waveform, HR, shockable rhythm counts and other relevant information. AED-M is supplied with non rechargeable lithium battery

For professional and non professional users. In addition to the AED-M features, HeartSave 6 offers both AED and MANUAL mode, 6 leads ECG, alarms and SYNC for Cardioversion

HEART SAVE EXTERNAL DEFIBRILLATORS Voice version and manual WITH LITHIUM BATTERY 140 DISCHARGES AT 360J languages **3 YEARS STANDBY** HeartSave PAD 33393 33395 33398 33402

\*\* We can provide following languages (voice + manual): ES, PT, GR, DK, FI, CZ, PL, DE, SE BG, RU, TR, AE, IR, BR,

HU, TH, JP, KU, SI, IL. UNI	/ VOICE: IVIK, HK, FI, INL, LI, IS, IL, K I, IK,	IK, BK, JP. UI	niy manuai ivo		
AED	WITH LITHIUM BATTERY 200 DISCHARGES AT 360J 6 YEARS STANDBY	Spa Gr	glish Inish eek Iguese	Italian French German Polish	Other languages"
	HeartSave AED HeartSave AED-M		391 396	33392 33397	33394 33399
1	WITH AKUPAK LITE RECHARGEABLE BATTERY AND CLIP CHARGER	English Italian Spanish French	English Spanish Greek Portuguese	Italian French German Polish	Other languages"
	HeartSave AED-M HeartSave 6	33440 -	- 33452	- 33453	33446 33456

\*\*\*We can provide following languages (voice + manual): BG, CZ, DK, FI, HR, HU, MK, NL, NO, RO, RU, SE, SI, TR, AE, CN, IR, TH. Please specify with order. Available in 40/60 days.

TECHNICAL SPECIFICATIONS

SAVEPADS Self-adhesive electrode, cable, razor and gloves - shelf life 3 years	GB, IT, FR, ES	Other languag
SavePads mini for 1-8 years max 25 kg	35390	3539°
SavePads preconnect for over 8 years,	35392	35393
25 kg Since S. N. 739xxxxxxxx		
SavePads for over 8 years 25 kg Only for 33384/5 and AED sold before April 2014 up to S.N. 738xxxxxxx	33388	33386
ACCESSORIES - SPARES		

PRIMEDIC" High resolution LCD

PRIMEDIC\* HeartSave AEC

33396

Status display

Trigger button for real

single-button operation.

You can save a life with

only one button.

monitor aives

for resuscitation

important information

Size approx 6x26x8.5 cm

EN 1789

**AHA/ERC GUIDELINES** 

2015 CONFORMITY

**IP55 WATER-**

LASS-PROTECTED

MADE IN GERMANY

Menu

button

nd AED sold before April 2014 up to S.N. 738xxxxxxx		
ACCESSORIES - SPARES		
ithium BATTERY - not rechargeable ife 6 years for AED and AED-M	33387	33387
AkuPak Lite Rechargeable battery*****	33400	33400
PowerPak Battery charger for code 33400	33407	33407
lashcard ERC guidelines update (2010 to 2015)****	33401	33401
For defibrillators sold up to December 2010 -:	Specify sei	rial

number with order

STANDARD ACCESSORIES
Lithium battery, 3 years stand-by (140 shocks @360J), (PAD only) Lithium battery, 6 years stand-by (200 shocks @360J), (AED, AED-M\*) AkuPak Lite, rechargeable battery with clip charger, (AED-M\*, HS6) ECG cable 3 leads (HeartSave 6 only) SavePads Data and voice recording Manual

\*AED-M is available with lithium battery or with Akupak Lite rechargeable battery. Select code for requested model

	PAD	AED	AED-M	HS6		PAD	AED	AED-M	HS6	
Defibrillation					LCD Monitor					
Semi-automatic mode	•	•	•	•	95x72 mm (diagonal 4.7"/120 mm)			•	•	
Manual mode				•	320x240 (pixel size 0.36x0.36 mm)			•	•	
Wave: biphasic, current controlled pulse	•	•	•	•	Storage battery status display			•	•	
Energy 50-360J	•	•	•	•*	Speed 25 mm/s			•	•	
Charging time: < 12 sec @ 360J	•	•	•	•	Heart rate, number of defibrillation,					
Operating modes: asynchronous	•	•	•	•"	number of VF/VT, total resuscitation time					
Paediatric mode	•	•	•	•	Data backup					
ECG					Removable memory	•	•	•	•	
Lead: II			•		Voice recording	•	•	•	•	
I, II, III, aVR, aVF, aVL				•	Power supply					
Patient's impedance range: 23-200 Ohm	•	•	•	•	Lithium battery 3 years life or 140 dischar-					
Heart rate: 30-300 per min			•	•	ges at 360J	•				
VF:VT Detection					Lithium battery 6 years life or 200 dischar-			•		
VF/VT Detection	•	•	•	•	ges at 200J - 15 hours monitoring		•	'		
Analysis time 7-12 sec	•	•	•	•	AkuPak Lite with rechargeable battery					
Asystole threshold <0.2mV	•	•	•	•	100-240 V, 50/60 Hz - 150 discharges at 200J			•****	•	
Artefact-Pacemaker detection	•	•	•	•	- 5 hours monitoring					
Flectrodes					Status display					

305 <sup>'20-360</sup>

"With sincronism for cardioversion in manual mode

...33396/7/9

\*\*\*\*33440, 33446

Defibrillator and battery status visualization • • • •

Size: 33x29x16 cm

EN 1789

# PRIMEDIC™ DefiMonitor XD - PROFESSIONAL DEFIBRILLATORS

The sophisticated high performance instrument with multifunctional features.

It combines a compact product design, proved and tested in practice with the highest possible degree of safety and user friendly handling.

Range of 8 manual (XD1, XD3, XD10, XD30) or manual + AED (XD100, XD300, XD110, XD330) defibrillators with or without SpO and external pacer.

Supplied with adult/pediatric paddles, disposable adult Save Pads, connect cable, ECG cable, power cable, 1 tube gel, 1 paper roll.

Standard software: GB. FR. DE. IT. ES. KT. PT. RO. TR. CN. Manual: GB, IT (on request DE, ES, PT, RU, UA).

Other softwares available on request: CZ, FI, HU, NL, NO, PL, RU, SE, DK, GR, LT, JU, AE, BR, CN, IR, JP, TH, US.

DefiMonitors XD

										GIMA	Accessories for DefiMonitors XD	
35370 DefiMonitor XD1 manual 35371 DefiMonitor XD3 manual + SpO, 35372 DefiMonitor XD30 manual + pacer 35373 DefiMonitor XD30 manual + SpO, + pacer 35374 DefiMonitor XD100 manual + AED 53375 DefiMonitor XD300 manual + AED + SpO, 25376 DefiMonitor XD300 manual + AED + spO, + pacer 35377 DefiMonitor XD300 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35370 DefiMonitor XD330 manual + AED + SpO, + pacer 35370 DefiMonitor XD330 manual + AED + SpO, + pacer 35370 DefiMonitor XD330 manual + AED + SpO, + pacer 35370 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35377 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD330 manual + AED + SpO, + pacer 35376 DefiMonitor XD300 manual + AED + SpO, + pacer 35376 DefiMonitor XD300 manual + AED + SpO, + pacer 35376 DefiMonitor XD300 manual + AED + SpO, + pacer 35376 DefiMonitor XD300 manual + AED + SpO, + pacer 35376 DefiMonitor XD300 manual + AED + SpO, + pacer 35376 DefiMonitor XD300 manual + AED + pacer 35376 DefiMonitor XD300 manual +								35380 35383 35384 33400 35386 35387 35388	SAVE PADS Connect GB, FR, IT, ES (require cable 3538 SAVE PADS Connect other languages (require cable 3538- Connect cable for SAVE PADS Connect 35380/3 - spar AKuPak LITE rechargeable battery Charge base for 33400 for DefiMonitor XD Paper roll 58 mm x25 m - box of 10	4)		
		VD4	vna	VD40	vose	VD400		CHNIC XD110		PECIFICATIO	ONS XD1 XD3 XD10 XD30 XD100 XD300 XD110 XD3	20
Defibrillati		ΧVΙ	XD3	XD IU	XD3U	XD 100	XD300	טווטאנ	XD330	TET LCD MI	ue-mode monitor	30
	nasic, current controlled impulse											
	tomatic mode) 140-360 J									320x240 pi		
	ergy stages:									Electrodes		
	, 301, 501, 1001, 2001, 3001, 3601	•	•	•	•	•	•	•	٠	Adhesive e	electrodes, 3 years shelf life	
	ime: < 6 sec at 200 J	٠	•	•	٠	•	•	•	•	Cable lengt	th 3.5 m Save pads connect	
	on: manual activation, QRS marker	٠	•	•	٠	•	٠	•	•	Data backu		
ECG											e memory 2 GB • • • • • • •	
	: Eindhoven I, II, III	٠	•	•	•	•	•	•	•		recording up to 35 h	
	Goldberger, aVR, aVF, aVL	•	٠	•	•	•	:	•	٠	Power supp		
Patient's re		•	:	•	•	:	•	•	:		0-264 V, 50/60 Hz	
Heart rate:		•	•	•	•		•	•	•		ble Lithium-ion battery (LiFePO <sub>4</sub> ): 2.5 Ah Voltage: 13.2 Vdc	
VF: recogni								١.		Capacity Discharges		
Analysis tir										Monitoring		
VF thresho											ion quidelines	
Asystole th										AHA/ERC	on guidennes	
Artefact, P.	acemaker detection									Standards		
Pulse Oxim											1:1988+A1:1991+A2:1995	
Nellcor Oxi	imax		•		•				•	(Electrical S	Safety of Med. Electrical Devices)	
Pacer											1-2:2001 (Electromagnetic compatibility) • • • • • • • •	
	cic heart pacemaker			•	٠			•	٠		1-4:1996+A1:1999	
	ix, demand, overdrive			•	•			•	٠		nable electrical medical systems)	
Thermal pr											2-4:2002 (Defibrillators) • • • • • • • •	
Resolution	: 200 dpi	٠	•	•	•	•	•	•	•	EN1789:200	03 (Ambulance standard) • • • • • • • •	

# **DEFI-B BATTERY DEFIBRILLATOR** - MADE IN GERMANY



The mobile security: PRIMEDIC DEFI-B is a state-of-the-art accumulator-driven defibrillator. It was designed in accordance with strict requirements of emergency medical science. Fully developed and reliable technique, world-wide in use since years, PRIMEDIC DEFI-B is a battery supplied version and has proved successful in daily use in ambulances, with cardio sport groups and in hospitals. The convincing advantages: PRIMEDIC DEFI-B is immediately ready for application and is not depending on the main power supply due to large accumulator capacity. After switching on, the defibrillator carry out an internal self-test. In order to ensure a functional optimal handling, the user is supported by clear instructions and pictograms. A shock-resistant plastic casing protects the device, especially under rough conditions.

• 33381 SPARE BATTERY

### TECHNICAL SPECIFICATIONS

Mode: Asynchronous, external defibrillator Energy step: 20, 50, 100, 160, 250, 360 Joule Discharges: 45 shocks at 360 Joule. (10 reserve after signal "battery low") Charging time: 2 sec up to 100 Joule

4.5 sec up to 360 Joule Paddles for children integrated Accumulator: 14.4 V / 1.4 Ah

Dimensions: 40x48x12 cm (W x D x H)

Charging time: 3.5 hours Internal discharge of energy after 15 sec. Internal self-testing and fault recognition Protection class II, type BF Mains voltage: 200-240 V 50/60 Hz

Weight: 8.5 kg

# RESCUE 230 BIPHASIC MANUAL DEFIBRILLATOR

### RESCUE 230 BIPHASIC MANUAL DEFIBRILLATOR

A range of 2 professional models with advanced features:

- BTE (Biphasic Truncated Exponential) discharge type

- impedance compensated energy delivery

- energy selection from 2 to 230 joule directly from the front panel

- charge time 5 sec for 230 joule with fully charged battery

- 100 shocks of 230 j with fully charged batteries

- charge/discharge control from the paddles

- ECG 'R' wave synchro mode or async mode

- large (5.7") high resolution backlight LCD display (320x240 dots)

- ECG through the paddles or through patient cable - adjustable HR and SpO, alarms limits

• 33447 RESCUE 230 BIPHASIC DEFIBRILLATOR

 33457 RESCUE 230 BIPHASIC DEFIBRILLATOR WITH PACEMAKER (rectangular pulse, pulse duration 22 msec, pulse max

amplitude 150 V, stimulation frequency 30 to 150 BPM) • 33458 DISPOSABLE PADDLES - box of 2 - pediatric

• 33451 DISPOSABLE PADDLES - box of 2 - adult

33449 CABLE/ADAPTOR FOR DISPOSABLE PADDLES

• 33439 SpO, PROBE

33250 THERMAL PAPER

### TECHNICAL SPECIFICATIONS

- Jarge (5.7") high resolution backlight LCD display (320x240 dots) - ECG through the discharge paddles (1 trace) or through 4 leads

patient cable (6 traces): I, II, III, aVR, aVL, aVF Automatic change over when plugging the patient cable

Filters: 50/60 Hz, base line, low pass

heart rate indicator

Printer:

auto printing mode
integrated thermal printer for ECG traces and events documentation hardcopy

paper speed 5, 10, 25 mm/sec (paper width 58 mm)

Safety: - two hands safety shock release - ECG input insulation CF class

internal discharge after 30 sec of standby after charge

Power supply: internal Ni-Cd high capacity batteries (charging time 95%: 2 hours) universal mains adaptor charger 110/220 VAC, 50/60 Hz 26x13 cm Weight: 5.5 kg Made in Italy

Dimensions: 34x26x13 cm

33447 33451

Adult and pediatric standard pads

Optional paddles for monitoring

Battery charging

car plug on request

STANDARD ACCESSORIES Internal Ni-Cd high capacity battery

Carrying case Patient cable 4 leads Manual GB, IT, on request ES, TR

1 paper roll 2 reusable paddles Mains adaptor charger

34042

Weight: 13 kg

# AMBU® TRAINING MANIKINS

# • 34044 AMBU® MAN COMPRESSION

A basic instruction and training manikin for the practice of external chest compression that meets recommendations of AHA (American Heart Association) and ERC

34044 (Furopean Resuscitation Council). With the size of a normal adult torso, provides a lifelike representation of human anatomy. Indicator for correct compression

The manikin includes an indicator bar that shows the correct compression depth, changing colour from red to

green. Compact and portable

Easy AED training

Due to the closed shaped torso, defibrillation pads can be placed and AED training can be performed realistically. Weight: 2 0 kg Size: 45x37x25 cm

Max compression depth: 7.5 cm Manual in: GB, FR, IT, ES, DE, PT, GR, HU, DK, PL, NO, SE, SI, CZ, TR, JP, CN.

• 34047 AMBU® MAN BASIC Cost efficient and reliable training manikin designed to fulfill all requirements for the BLS algorithm training. The closed shaped torso with its anatomical correct landmarks allows trainees to learn and train the use of Automatic External Defibrillators (AED) and the placement 34047 of pads. It allows an optimal training of chest compression in combination with realistic ventilation. The unique hygienic system prevents cross contamination. It allows a realistic ventilation resistance and expiration through mouth and nose. The correct compression depth and required ventilation volume can be monitored by the feedback indicator on the manikin.

Ventilation as in real life The trainees will feel the realistic airway resistance and the chest will start rising when the head is correctly tilted and air blown into the manikin. Weight: 6.0 kg. Size: 70x37 cm

Max ventilation: 1,200 ml Max compression depth: 7.5 cm Manual in: GB, FR, IT, ES, DE, PT, HU, DK, NL. PL. CZ. TR.

34039 HEAD BAG - box of 100 pcs

• 34042 AMBU® AIRWAY MAN LAG

• 34049 AMBU® AIRWAY MAN W with CPR Adult-sized training manikins that provide an optimal lifelike representation of the human

anatomy. Mechanical instrument gives you instant feedback

on ventilation volume, stomach inflation, chest compression depth in mm and wrong Size: 80x35 cm

hand position. PC connection (34049 only) of Ambu CPR Software Kit,

Ambu CPR Printer or USB Interface. Make intubation possible

with ET tube, Guedel, Laryngeal Mask and combi-tube Ambu Airway man includes torso with hooks for arms, computer interface with CPR software kit (34049 only), supplied in track suit jacket and training mat. CPR software kit selectable languages: GB, FR, IT. ES. DE. PT. PL. DK. HU. NL. RU. JP.

 34043 COMPLETE SET: ARMS, LEGS, TROUSERS AND BAG

306

# RESCUE LIFE MANUAL AND SEMIAUTOMATIC DEFIBRILLATORS

Ergonomic design. Impact proof, compact and lightweight. Bright, high contrast, wide-angle TFT LCD colour display Comfortable and washable carrying bag keeps all accessories at hand and protects Rescue 5.7" to view simultaneously up to 3 ECG channels Memory and data management. Simple € 0068 commands, extremely intuitive and easy to use **RESCUE LIFE 5.7** Immediate access to main setup parameters MADE IN ITALY using only trim knob and function keys **AVAILABLE WITH** SpO. - NIBP PACEMAKER OU MAY ORDER UNIT WITH 1 TO 3 OF ABOVE PARAMETERS Fast connection. User can choose between Large TFT LCD colour display 7 ergonomic reusable naddle for manual defibrillator or Adult and pediat disposable pads for AED eusable paddles defibrillation. Both types are equipped with a single fast lock connection for reliable rescue operations

### RESCUE LIFE BIPHASIC DEFIBRILLATORS 5.7" and 7"

Rescue Life is an external defibrillator with monitor. It is designed to be used by out-of-hospital and hospital users. Lightweight, transport facility, attractive line, ergonomic shape, studied in every details. It is a complete acute cardiac care response system designed for Basic Life Support (BLS) and Advanced Life Support (ALS) patient management protocols. The IPX4 standard permits the operation under adverse climatic situations. Rescue Life is totally MADE IN ITALY. SpO<sub>a</sub> and pacemaker

Range includes models with pacemaker and SpO<sub>3</sub>. ECG module for monitoring (not for diagnosis) includes up to 12 derivations standard 5 leads patient cable (for I. II. III. aVL. aVR. aVF) or optional 10 leads patient cable (for 12 derivations).

The NIBP option is focused on advantage A+ module of SunTech Medical that provides the highest NIBP performance during movements. Suitable for adult, pediatric and neonatal. High contrast TFT LCD colour display 5.7" or 7" (Rescue Life 7) Bright, high contrast, wide-angle colour display for simultaneous view of up to 3 ECG channels

Data management The memory is based on a flash disk of 4 GB for 300 recorded hours for all AED models

### Asynchronous and synchronous

- in asynchronous defibrillation. Rescue is advised on patients with the following symptoms: unconsciousness, absence of

normal breathing and lack of detectable pulse. - in synchronous defibrillation, Rescue Life is advised on patients with ECG's reporting Atrial Fibrillation

### 3 operation modes: manual, AED, Advisory

- in manual mode RESCUE LIFE is intended for use by doctors and trained individuals. Only 3 steps: energy selection from 1 to 230J, energy charge and shock.
- in AED mode, RESCUE LIFE is intended for use by personnel authorized by a physician or medical director. The voice prompts and display messages are assisting the operator during CPR operations, charging automatically to 150J when a shock-able ECG rhythm is detected.
- in advisory Mode, the system alerts when the shock is necessary leaving the energy level and charging choice to the operator.

### Initialising and system test at switching on of the device (Rescue Life 7 only)

Auto test and fault recognition (Rescue Life 7 only). Clinical test

Available on our web site.

STANDARD ACCESSORIES Internal Ni-Mh battery (Rescue 5,7") Internal Li-Ion battery (Rescue 7") 2 adult and pediatric reusable paddles Manual: GB, IT

Printer
1 paper roll Patient cables 5 leads
2 disposable pads (AED only) Main adaptor charger

RESCUE LIFE 7" DEFIBRILLATORS

English	Italian	languages	
33590	33537	33538*	Rescue life defibrillator
33597	33540	33541*	Rescue life defibrillator with SpO,
33591	33543	33544*	Rescue life AED defibrillator with pacemaker
33598	33545	33546*	Rescue life AED defibrillator with SpO
33547	33548	33549*	Rescue life AED defib. SpO <sub>3</sub> +NIBP+Pacemaker
		33539**	

\*On request we can offer Rescue Life and Rescue Life AED in Spanish and French "On request we can offer Rescue Life and Rescue Life AED with SpO<sub>2</sub>+NIBP, SpO<sub>2</sub>+Pacemaker (available in GB, FR, IT, ES)

33182	33183	Rescue Life 7 defibrillator
33185	33186	Rescue Life 7 AED
33188	33189	Rescue Life 7 AED defib. other configurations
La cara accordant com		: 4- 7 : th C-O NUDD D

You can choose 1 to 3 of above parameters. "Available on request manual in FR and ES. ES

AMIC	RESCUE LIFE	ACCECCOD!
rode	KESCUE LIFE	ACCESSORI

code	
33448	Disposable paddles - box of 2 - adult - compatible
33451	Disposable paddles - box of 2 - adult - original
33458	Disposable paddles - box of 2 - pediatric - original
22502	Cable for disconnible modules

Cable for disposable paddles 33594 ECG cable 10 leads

Italian

33595 Rescue Life bag 33250 Thermal paper

33596 12V car light adapter - inverter

### TECHNICAL SPECIFICATIONS

Display:
- high contrast TFT colour LCD 5.7" (320x240 pixel) or LCD 7" (800x480 dots)

-ECG through the discharge paddles (1 trace) or through 5, 10 leads patient cable for 3, 6, or 12 traces and SpO<sub>2</sub> value Automatic change over when plugging the patient cable
- filters: 50/60 Hz, base line, EMG

heart rate indicator

- heart rate indicator
ECG monitoring
- bandwidth: 0.5 to 120 Hz (-3db) with filters off
- speed: 5, 10, 25, 50 mm/sec.
- gain: 2.5, 5, 10, 20, 40 mm/mV with patient cable;
auto with paddles
- HR digital readout on the display 20 to 300 bpm (± 2%)
- alarm: set4able HB min - 10 ppm may 250 bpm.

- nk algiar feadout on the display 20 to 300 ppt (±2 of 20 ppt), max 250 ppm Pulse oxymetry (\$pQ) 33540-15-67-89, 33597-8 only oxygen saturation range: 0 to 100% pulse rate range: 30 - 250 pulses per minute - accuracy \$pO: 70-100% ± 2 digits for adults using the finiger (10) sensor (50%) = 500, Alarms adjustable (min. 50%) = 500, Alarms adjustable (min. 50%)

Non-invasive pacemaker (33543-4, 33591, 33547-8-9)

rectangular wave operating mode: fixed on demand pulse rate: 0 to 180 ppm adjustable in steps of 5 ppm impulse duration: 22 ms

pulse Current: 0 to 180 mA adjustable in steps of 5 mA

- amplitude: MAX 150 V NIBP (33547-8-9 only) - technique: oscillometric

- technique: oscillometric
- accuracy: meets ANSI/AAMI SP10-2002, EN 1060-4
- patient application: adult/pediatric/neonatal
- range mmHg adult pediatric neonatal
systolic
- 40-260 40-160 40-130
- MAP 26-220 26-133 26-110
- diastolic 20-200 20-120 20-100 Printer:

 manual, automatic (10"pre and post recording)
 integrated thermal printer for ECG traces and events documentation including HR/SpO<sub>2</sub> values - paper speed: 5, 10, 25, 50 mm/sec. - paper width: 58 mm

Sarety: - two hand safety shock release - ECG input insulation CF class - internal discharge after 30 sec. of standby after charge Power supply: internal Ni-Mh battery (Rescue Life 5.7")

internal In-IMI battery (Rescue Life 5.7-)
internal Li-Ion battery (Rescue Life 7")
(charging time 95%: 2 hours)
AC 100-240 VAC, 50/60 Hz
Memory: internal flash 4 GB up to 300 hours of
ECG data, events and usage review

General: Dimensions: 36x24x34 cm Weight: 5.5 kg with battery

308

# DTS-3000 SMART PNEUMATIC TOURNIQUET SYSTEM



- 33138 DTS-3000 PNEUMATIC TOURNIQUET 2 channels for 2 double cuffs or 2 single cuffs with 5 no pinch cuffs DTS-3000 provides stable operation, easy setup and effective alarm system for safe surgery in an operation room. System features
- 2 channels (4 ports for 2 double cuffs or single cuffs)
- easy settings by touch key operation
- graphic LCD screen: easy checking and cleaning
- graphic Education recording (date, time, pressure)
   LOP (Limb Occlusion Pressure) sensor to check limb occlusion
- pressure and set automatically the optimized pressure
- self test of pressure and system check - self air pressure sensor calibration
- safety alarm system (cuff, pressure, battery, time)
- built-in battery (max life time: 12-72 hours)
- Full autoclavable no pinch cuffs included
- no pinching, no damage to the skin
- lower pressure compared to normal cuff (about 50 mmHg lower)
- no leaking (main reason for lower pressure)

 33139 TROLLEY CUFFS for DTS-2000 and Standard pinch DTS-3000 Thigh 33141 Single cuff 61x9 cm - red S 33142 Single cuff 80x9 cm - blue M 33160 Single cone cuff 70x10 cm 33161 33144 Single cone cuff 90x12 cm - blue 1 33145 Double cuff 57x10 cm - blue 33146 Double cuff 80x15 cm - red M





INTENDED USE OF TOURNIQUET SYSTEM

To be used by qualified medical professionals to temporally occlude blood flow in patient's extremities during surgical procedures. Tourniquet has been found useful in producing bloodless operation field in surgical procedures involving

- the extremities including: - bone grafts
- reduction of certain fractures total wrist joint replacements replacement of joints in the fingers Kirschner wire removal
- tumor and cyst excision
- knee joint replacements - subcutaneous fasciotomy
  - - amputations

# RIESTER INFUSION CUFFS

• 32684 RIESTER METPAK® INFUSION CUFF - 500 cc - latex free • 32685 RIESTER METPAK®

INFUSION CUFF - 1.000 cc - latex free • 32683 RIESTER METPAK® INFUSION CUFF - 3.000 cc -

latex free Pressure cuff for infusion with high quality chromeplated gauge Ø 49 mm up

to 300 mmHq. Made in Germany













# **ECONOMIC INFUSION CUFF**



• 32680 INFUSION CUFF 500 cc

Infusion cuff similar to above. Latex bladder and bulb. Made in Asia.

# PNEUMATIC TOURNIQUET • 33150 RIESTER PNEUMATIC TOURNIOUET with adult arm and

- thigh cuff latex free bladder • 33151 CHILD CUFF 38x8 cm - latex free bladder

• 33148 ADULT CUFF 57x9 cm - latex free bladder - spare

• 33149 THIGH CUFF 96x13 cm - latex free bladder - spare Riester Reliable pneumatic tourniquet used during amputations to restrict blood circulation in the limbs. A robust and accurate manometer provide exact measurements and a long service life. - sturdy metal pump to produce pressure - air in the cuff can escape by opening the release valve - chromium-plated metal manometer with easy-to read aluminium scale up to 700 mmHg. Supplied with 2 cuffs (upper arm 57x9 cm and thigh 96x13

cm) with latex-

free bladders.

33150

# VOLUMETRIC INFUSION PUMP

• 35200 INFUSION PUMP IP-7700

This pump using peristaltic method is a cutting-edge pump realizing high flow precision with compatibility with I.V. set of various brands through ultrasonic bubble detection.

IP-7700 provides simple and easy setup process with its numerical silicon keypad. FND and color LCD provides complete information and user gets the information at one gland Most infusion condition such as K.V.O. rate, purge rate and bolus can be setup as operating application. Supplied with battery. IV clamp Main features

Light and compact design: light as 3.5 kg, compact design, and easy to use.

- Standard compatibility with 4 brands of IV SET: TERUMO (TS PA 200L), BD (A122), KOREAN VACCINE (1 and 2), ARIES. Each pump can be calibrated for up

- Flexible flow setting and easy operation method: Flow-setting range of 1~1000 ml/h, 0,1~999,9 ml/h is available for wide range settings and numerical keypad is easy to use for setting flow-volume.

- Full program dosage feature (option): it can calculate the right flow rate for a patient and inject promptly.

- Easy recognition of alarm: it notifies errors and emergencies with LED light and buzzer,

simultaneous visual and audio alarm system.

Notifying remaining battery: battery LED is attached to notify charged battery showing remaining battery and when to recharge.

Keep Vein Open feature: when reached preset value, it converts to low flow speed of 3ml/h

(when IV set is 15, 19, 20 drops/ml) or 1ml/h (when IV set is 60 drops/ml) automatically to prevent flow route clog due to blood coagulation. Automatic setup system (flow Ultrasonic air bubble detector rate, time, delivery volume)

- Suitable also for VET use
• 35202 DROP SENSOR - for more accurate dropping control (suggested for ICU and new born)

• 35210 DROP SENSOR - for more accurate dropping control (suggested for Ico and live worth)

- 35211 DOSAGE AND PROFILE PROGRAM need Serial Number • 35203 Ni-Cd BATTERY - spare

• 26073 I.V. SET ARIES - box of 150 (6 bags of 25) • 35204 ADAPTER 110 V - 60 Hz - for 35200 (20) TECHNICAL SPECIFICATIONS
Rapid flow volume (Purge)

Flow volume setting range 1~1000 ml/h (1 ml infusion interval) 0.1~999 9 ml/h (0.1 ml infusion interval) Flow volume error margin +5% Infusion limit volume range

1~9999 ml Total estimated volume range 1~9999 ml

K.V.O rate (Keep Vein Open) 1 ml/h ~ 10 ml/h adjustable Pump method Peristaltic method Size (WxDxH) 100x190x250 mm Weight 3.5 kg (battery included)

-1000 ml/h adjustable Bolus 1~1000 ml/h adjustable Alarm features Air in line, occlusion, flow error (free flow), door open, K.V.O. (Infusion completion), standby, low battery, alarm, device malfunction (CPU error), empty container (with optional drop sensor

Keypad lock, retain memory, remaining time, alarm repeat, open system, K.V.O., purge, bolus, occ. level,

Numerical silicone key pads AC 230V, 50/60Hz and DC9.6V inner source adapter DC 12 / 24V - 2A Switchable at 110V / 60Hz - with

1 2 3

4 5 6

7 8 9

adapter 35204 Maximum power consumption 40VA Electric protection levels

Class II B. inner source device. CF type Waterproof level IPX2 Battery type Ni-Mh rechargeable

Battery using time 4 hrs (when infusing 125 ml/h)

ALIBRATION TO ANY SYRINGE BRAND

Automatic set-up system (flow

rate, time, delivery volume)

Battery recharging time Minimum 6 hours. Battery life approx 6 months

samples of your syringe very in 60 days

**( €** 0120

sv and quick in

iust in five seconds

310

alish and

# AUTO SYRINGE PUMP

### • 35205 SYRINGE PUMP SP-8800

SP-8800 provides easy syringe installing through one-touch method by slider hook, simple and easy setup process with its numerical silicon keypad. Color LCD displays infusion information dramatically shortcut key manages easy approach for frequent functions. K.V.O. rate, purge rate, bolus and anti bolus can be setup as operating application. Supplied with battery.

Flexible flow volume setting.

Full program dosage feature (optional): it automatically calculates flow rate by patient's weight, injection's mass and melting. Keep Vein Open (K. V. O.) feature: When reached to the preset value, it converts to low flow speed of 0.1 ml/h automatically to prevent flow route clog due to blood coagulation.

Standard compatibility with 5 major brands of syringes\*: Setting feature enables you to choose from following syringe brands: BD (Precise), TERUMO, RAYS,

PENTAFÉRTE, KOVA. Each pump can be calibrated for up to 9 different syringes. Alarm and notification feature: It notifies errors and emergencies with LED light and buzzer. Simultaneous visual and audio alarm. Occlusion error range setting: You can set the pressure level of occlusion stage to High, Medium and Low by patient's age condition. Suitable also for VET use

• 35210 Ni-MH BATTERY- spare • 35204 ADAPTER 110 V - 60 Hz - for 35205

35211 DOSAGE AND PROFILE PROGRAM need Serial Number

# 23857 BD SYRINGES 50 ml LL - box of 60 - BD 300865

Flow volume setting range Syringe 10ml: 0.1-300 ml/h Syringe 20ml: 0.1-400 ml/h Syringe 30ml: 0.1-500 ml/h

Syringe 50ml: 0.1-1,200 ml/h Flow volume error margin ±3% Infusion limit volume range

0.1~999.9ml (0.1 ml infusion interval) Total estimated volume range 0.1~999.9ml (0.1ml infusion interval) K.V.O rate(Vein maintaing function)

1-10 ml/h adjustable Size (WxDxH) 220x130x108 mm Weight 2 kg (battery included)

### **TECHNICAL SPECIFICATIONS** 0.1~1200 ml/h adjustable

Bolus: adjustable 0.1~1200 ml/h 0.1~1000 ml

Alarm features Occlusion, K.V.O. (infusion completion). standby, near empty, low battery, device malfunction (CPU error), clamp/handle le

ver/slider disengaged, syringe disengaged. Special features Keypad lock, shortcut key, retain me mory, remaining time, alarm repeat, open system, K.V.O., purge, bolus, anti bolus, occ. level, history call-back.

AC 230V. 50/60Hz and DC9.6V inner source adapter DC 12 / 24V - 2A Switchable at 110V / 60Hz - with adapter 35204

IV clami

included

Maximum power consumption 45VA Electric protection levels Class II B, inner source device, CF type Waterproof level IPX2
Battery type Ni-MH rechargeable

Battery using time 2 hours Battery recharging time Minimum 6 hrs Battery life about 6 months.



### \* We can calibrate our pumps for other syringe brands, please provide minimum 5 samples. Availability in 60 days

# PLASTER COVER FOOTWEAR ORTHOPEDIC SUPPORTS



Cover plaster footwear to be worn over plaster or similar rigid bandage.

It can be worn immediately after application of the plaster because breathable.

The sizes are the same as for standard shoes, with appropriately increased fit.

The shape is symmetrical, then the same cover can be used indifferently on the right or left foot. Washable at 30°.

# **ARM SLINGS**



Suitable for supporting a sprained or broken arm during recuperation.

The shoulder strap is adjustable to allow a correct positioning of the arm. Stitched from cotton fabric requiring normal laundry care. Fits any arm.

Available in 3 sizes.

GIMA code	POUCH ARM SLINGS
28624	Arm sling - small
28625	Arm sling - medium
28626	Arm sling - large



Knee support Wrist support Elbow support Elastic knitting supports to fit body contour. Gel pad inside to release pressure for nerves, muscle, joints and improve stabilization. Hand washable.

Size	WRIST Left Right	ELBOW	KNEE	ANKLE Left Right
S	28731 2874	28751	28761	28771 28781
rcumference	15-16 cm	21-23 cm	28-31 cm	19-21 cm
M	28732 28742	28752	28762	28772 28782
rcumference	16-17 cm	23-25 cm	31-34 cm	21-23 cm
L	28733 28743	28753	28763	28773 28783
rcumference	17-18 cm	25-27 cm	34-37 cm	23-25 cm
XL	28734 2874	28754	28764	28774 28784
rcumference	18-19 cm	27-29 cm	37-40 cm	25-27 cm

# UNIVERSAL ARM SLINGS



# • 28623 UNIVERSAL ARM

Universal arm sling with adjustable strap and loop contact closure. Fits left and right. Made in comfortable polypropylene material in navy

Machine washable.

# SOFT AND RIGID COLLARS UNIVERSAL COLLARS

### SOFT CERVICAL COLLARS

This collar is made of soft expanded polyurethane lined with an anti - allergic 100% cotton fabric. Velcro fixing on the back. Available in 3 sizes.

### RIGID CERVICAL COLLARS

Made of polyethylene, with comfortable resting support in vinyl leather and height adjustable. Velcro straps on the back. Available in 3 sizes.





GIMA code	SOFT AND RIGID NECK COLLARS X-Ray Translucent
34600 34601	Rigid cervical collar 32-40 cm (neck circumference) Rigid cervical collar 41-46 cm (neck circumference)
34602	Rigid cervical collar 47-52 cm (neck circumference)
34610	Soft cervical collar 43x8 cm - small (h 7 cm)
34612	Soft cervical collar 46x8 cm - medium (h 8.5 cm)
34614	Soft cervical collar 49x10 cm - large (h 10.5 cm)



UNIVERSAL CERVICAL COLLARS Collars made of foam coated PVC. Washable, non toxic, with velcro straps. X-Ray translucent. Available in 3 sizes or in a set of 3 in a bag.

code	NECK COLLARS	Α	В	С
34051 34052 34053	Set of 3 collars in a bag Cervical collar - small Cervical collar - medium Cervical collar - large Bag for 3 collars - blue	513 mm 560 mm 623 mm	95 mm	123 mm

Ambu<sup>⊁</sup>

34638

# AMBU® REDI-ACE™ AMBU® PERFIT™ PERFIT™ MILITARY







### AMBU® REDI-ACE™ COLLARS

Ambu® Redi-ACF™ Min is adiustable in 6 sizes

Unique adjustable disposable collar available in 2 versions adult and pediatric collar is a one-piece rigid cervical spine for immobilizing of cervical column. With 8 sizes of Ambu® Redi-ACE™ and 6 sizes of Ambu® Redi-ACE™ Mini the majority of patients can be treated. Easy to use, it has an automatic flip up chin and two locking buttons. It can be placed on the patient using only 3 steps; sizing - locking - placement. Made from radiotranslucent material. Packaged completely flat. Latex free.

GIMA code	ADJUSTABLE NECK COLLARS
	Ambu® Redi-ACE™ paedyellow Ambu® Redi-ACE™ adult-blue

### AMBU® PERFIT™ ACE® COLLARS

The Ambu® Perfit™ ACE® extrication immobilization device, available in 2 versions, adult and pediatric, both adjustable in different sizes/positions. Adult has 16 adjustments, covering neckless, short, regular and tall. Paediatric has 12 adjustments, covering infant, child, small adult. Radiotranslucent CT and MRI compatible it comes with a ventilated, posterior shell for fluid drainage. Made in polyethylene. Flat storage. Latex free

polyculyi	olyethylene. Hat storage. Latex free.				
GIMA code	ADJUSTABLE NECK COLLARS				
	Ambu <sup>®</sup> Perfit <sup>™</sup> paediatric-yellow Ambu <sup>®</sup> Perfit <sup>™</sup> adult-white				

Designed to assist with the maintenance of neutral alignment, prevention of lateral sway and anterior-posterior flexion and extension of the cervical spine during





### AMBU® PERFIT™ ACE® MILITARY

Ambu® Perfit™ ACE® is also available in a military version that incorporates a camouflage colour scheme of olive drab body and charcoal black foam and label. The features and specifiactions are identical to Ambu® Perfit™ ACE®:

- 16 sizes in one collar
- flat storage
- radiotranslucent CT and MRI compatible Latex free.

GIMA code	ADJUSTABLE NECK COLLARS
34642	Ambu® Perfit™ Military

# FIRST AID CERVICAL COLLARS





### ONE PIECE AND TWO PIECES FIRST AID COLLAR

Made in polyethylene with washable internal part made in EVA (kind of rubber) fixed to structure by plastic rivets. With a tracheal hole, removable chin support and velcro fastener. X-ray translucent. Available in 6 sizes differentiated by safety closure colour or in a set of 6 in a bag.

### GIMA ONE PIECE FIRST AID code **NECK COLLARS** 34620 Infant 44-48 cm - pink 34621 Pediatric 45-48 cm - light blue 34622 Stout (bull-neck) 56-60 cm - yellow 34623 Adult small 56-62 cm - blue 34624 Adult medium 56-64 cm - orange 34625 Adult large - tall 56-66 cm - green 34626 Set of 6 collars in a bag 34627 Bag for 6 collars - green

### GIMA TWO PIECES FIRST AID NECK COLLARS 34630 Infant 2-6 years 35-99 cm - pink 34631 Pediatric 6-12 years 40- 46 cm - light blue **34632** Stout (bull neck) 48-52 cm - yellow 34633 Adult small 50-54 cm- blue 34634 Adult medium 54-58 cm - orange 34635 Adult large - tall 56-60 cm - green 34636 Set of 6 collars in a bag

34627 Bag for 6 collars - green

# AIR CUSHION SPLINTS



• 34106 FIRST AID AIR CUSHION SPLINTS - set of 4 pieces Indispensable instrument for first aid in case of accidents, cutting and crushing injuries. Prevent surface bleeding without stopping the circulation and secure painless transportation of the injured part. The bandage is a transparent cover of PVC easy to clean and reusable, resistant against water and shifting weather conditions. X-rays can penetrate and medical diagnosis can be made without removing the bandage. The long tube (14.5 cm) with the valve make the inflation of the bandage easy, even by the injured part himself.

Set of 4 different pieces: full leg, foot/ ankle, full arm, hand/wrist splints in a 4 compartment bag, with inflating pump.

### ALUMINIUM SPLINTS soft lining With curved edges to avoid harming yourselves. Aluminium thickness 1.2 mm. Made in Italy.

• 34120 SPLINTS - size 13x500 mm • 34121 SPLINTS - size 19x500 mm • 34122 SPLINTS - size 24x500 mm



# **BOSTON SPLINTS** (€

### • 34123 BOSTON SPLINTS

Adaptable light-weight splints, x-ray translucent, coated with a non-toxic material which can be easily washed and disinfected. Size cm 92x11. Made in Italy.

# FINGER SPLINTS

FINGER Set of 8 finger splints in different size (from 5 to 6.5 cm length, from 4.5 to 7.8 cm width circumference). Available in clear and skin tone colours. Made in polypropylene. With holes for air circulation and cooling. 34113 FINGER SPLINT KIT - clear - kit of 8 • 34115 FINGER SPLINT KIT - skin - kit of 8



# GIMASPLINTS IN 5 SIZES: LEG. ARM, FOREARM, WRIST AND ELBOW



GIMASPLINTS these supports immobilize your limbs in an efficient and practical way. Each splint can be shaped to fit the patient's personal need. It ensures a high degree of rigid support: thanks to inner part made of neoprene lined with 100% laminated, absorbent-proof nylon assembled to a rigid

	in 5 sizes or in a bag set of 5 piece	
GIMA code	GIMASPLINTS	
34680 34681 34682 34683 34684 34685 34054	Splint for leg - 57 cm Splint for arm - 60 cm Splint for forearm - 39 cm Splint for wrist - 33 cm Splint for elbow/ankle - 54 cm Set of 5 splints in a blue bag Bag for 5 splints - blue	<b>(€</b>

# **VACUUM SPLINT KIT**

### • 34689 VACUUM SPLINT KIT

The set includes vacuum splints for arm (70x50 cm), leg (100x70 cm) forearm (50x30 cm) and a nylon bag. Produced with high quality

materials these splints allow perfect immobilization of the lower and upper limbs by removing the air inside.

Equipped with an outside valve, to avoid troubles to the patient, and three velcro straps.

Made in vinvl covered nylon, x-ray translucent.

• 34093 ALUMINIUM PUMP -

for vacuum splints and mattress • 34084 ALUMINIUM MINI PUMP







34088

Sturdy material and careful manufacture make it suitable

Size: 200x75 cm. Weight: 8.8 kg. Loading capacity: 150 kg.

for Civil Defence, Fire Brigades, Industry and First-aid on the

Supplied with nylon bag size 70x43x15 cm, pump not included.

• 34088 MAT VACUUM MATTRESS

PVC. X-ray translucent mattress with 6 transport handles, perfectly fits the patient body.

• 34091 MAT ORANGE VACUUM MATTRESS

transport handles and 4 immobilization straps.

X-ray translucent, comfortable vacuum mattress with 8

# VACUUM MATTRESS

### • 34089 MAT PLUS VACUUM MATTRESS

PVC, X-ray translucent mattress provided with 4 immobilization straps and 12 transport holes. Suitable for any kind of emergency situation. Size: 210x90 cm. Weight: 11.2 kg. Loading capacity: 150 kg. Supplied with nylon bag size 86x43x17 cm, pump not included.



34089 Vylon carrying with all vacuum




# SEMIRIGID SPLINT KIT

### • 34119 SEMIRIGID SPLINT KIT

Kit of 3 splints (arm, wrist, leg) in nylon carrying bag. All splints are made of polyester + PVC. with lightweight stays providing high strength support. Adjustable velcro for easy use.





• 34027 SPINAL IMMOBILIZER TYPE A

• 34028 SPINAL IMMOBILIZER TYPE B GIMA presents 2 different shape of spinal immobilizers, both are ideal for

the immobilization and setting free of

horizontally the head and spine of the

patient to limit any injuries caused by

Supplied with different colour buckles

and belt for easy use, padded cushion

patients from emergency situations.

They allow to fix vertically and

wrong transport.

34091

EXTRICATION KITS



velcro straps and waterproof bag.



• 34116 BODY BAG - PVC Made of PVC (Inner transparent PVC, over black), provided with two long slide fasteners. Colour: black. Size: 210x90 cm Loading capacity: 150 kg

• 34117 BODY BAG - vinyl - blue Made of vinyl covered nylon conform to standard EN 1865. Provided with a long slide fastener. Size: 210x90 cm. Loading capacity: 150 kg.

# CARRYING COT



• 34090 CARRYING COT

Made in polyester, PVC coated. Anti-putridity, bacterial and fungus proof, waterproof, easy to wash and disinfect, X-ray translucent material. Size 185x57 cm. Loading capacity: 150 kg. Certified EN1865-2010 + A1 2015

# GIMA STRETCHERS AND SPINAL BOARDS



• 34101 GIMA STRETCHER 2 - foldable in 2 Emergency stretcher is sturdy, but lightweight in construction, with aluminium frame and three solid iron cross-bars for heavy use. Reinforced nylon canvas, fluid repellent and

• 34107 GIMA STRETCHER 4 - foldable in 4 Made of strong alloy and watertight material.

Light weight, easy to carry, foldable in 4. Length foldable in 2 parts, width foldable in 2 parts.



### • 34105 STACKABLE STRETCHER

Used in small rooms where it is necessary to store a large number of stretchers. PVC does not absorb blood or body fluids. Strong lightweight aluminium construction with vinyl coated poliester

### • 34076 BLUE STRETCHER foldable in 2

Light-weight, small sized, easy to carry. High-strength aluminium poles and vinyl coated waterproof nylon canvas.

### • 34077 WHEEL STRETCHER foldable in 2

Wheels, outriggers and adjustable backrest. High strength aluminium poles and vinyl coated, waterproof nylon canvas. Light weight, small sized, easy to carry.

### • 34083 SPINAL BOARD

34077

X-ray translucent, washable, buoyant and impervious to all fluids. Made in linear high density polyethylene with plastic pins. Compatible with all head-immobilization devices and strapping system. CT and MRI transparent. Colour orange.

### • 34022 B-BAK PIN SPINAL BOARD - yellow

PE spinal board with Pin with robust and light structure to ensure high resistance. The 14 handles and their shape offer an easy grip, the low thickness make the application easier. Equipped with 8 plastic pins to allow easy fixing of belts with

### • 34097 SPINAL BOARD WITH SAFETY GLASS FIBRE PINS - orange

Strong and lightweight high density PE spinal board, with two fibre reinforced plastic stays. Provided with glass fibre pins for better fixation of immobilisation belts. Excellent in water rescues. X-ray translucent, except 2 plastic stays.





• 34023 BABY GO PEDIATRIC SPINAL BOARD Baby go is a professional board, designed for children, which maintains the spine in neutral 34097+ position with the ideal alignment for air flow. Board has four different profiles which guarantee the correct position of the child according to his

• 34024 PEDIATRIC HEAD IMMOBILIZER Ensure optimal immobilization of the head of children perfectly fitting their pronounced occipital prominence.

• 34025 PEDIATRIC SPIDER STRAP SYSTEM



	34024						ape measure			
TECHNICAL SPECIFICATIONS 34101 34107 34105 34076 34077 34083 34022 34097						34097	34023			
		GIMA 2	GIMA 4	STACKABLE	BLUE	WHEEL	SPINAL	SPINAL WITH PINS	SPINAL WITH PINS	PAED SPINAL
	Open size cm:	203x50x14	221x53x16	188x48x18	188x45x7	188x53x21	184x44.5x6.5	184x40.5x4.5	183x46x5	119.5x32x4.5
	Folded size cm:	96x50x17	104x19x12	-	94x48x10	92x53x12	-	-	-	-
	Weight:	6 kg	5 kg	6 kg	4 kg	8 kg	7.6 kg	6 kg	7 kg	2.2 kg
	Load:	120 kg	150 kg	170 kg	150 kg	150 kg	150 kg	180 kg	200 kg	30 kg

3x34011



### **SCOOPING STRETCHER**

# 34103 Supplied with multilanguage manual:

### • 34103 SCOOPING STRETCHER

A wonderfully practical scooping stretcher allows to put the stretcher under the patient without moving him/her much. The shape of the stretcher has been designed to immobilize the patient properly during transport.

- effective hooking and unhooking device for stretcher uncoupling
- adjustable stretcher length with automatic locking device
- bag with 3 guick unhooking safety belts for patient immobilization - once folded can be easily stored inside the ambulance
- completely built in light and sturdy aluminium

Open size cm Folded size cm Weight: Load:

TECHNICAL SPECIFICATIONS
min 171x43 max 212x43 120x43 8 kg 150 kg

spinal boards

contains up to 3 belts

### **HEAD IMMOBILIZERS**

of two head blocks and

injured person during

transport. We can offer

"STOP" head immobilizer in yellow, bluette, red, green, military green for minimum 50 pieces.

Adjustable spider mix

red

Nylon bag

32794

5x51x203

two straps to prevent any head movement of the

GB. FR. IT. ES. PT. DE



•	3407	79	
GIMA code	Туре	Colour	Material
34021 34080 34078		yellow red orange black yellow	PE foam covered with PVC NBR foam dipped with PVC High density foam+water repellent coating High density foam+water repellent coating Moulded polyurethane and PVC

### **IMMOBILISATION BELTS** FOR STRETCHERS AND SPINAL BOARDS



velcro strapping system - adjustable

### AUTOMATIC LOADING STRETCHER MULTIPOSITION STRETCHER



### • 34055 AUTOMATIC LOADING STRETCHER

Automatic stretcher to load and unload patients from emergency vehicles, can be moved by only one person. Specially designed with roll-in system to easily load and unload patients from emergency vehicle without lifting them. Legs fold under cot automatically as stretcher is rolled into the vehicle. Lock-in operating position as cot is removed from vehicle, left-hand and right-hand control levers unlock front and back legs respectively so as to be folded when cot is loaded. Polyethylene covered legs allow cot to roll smoothly in and out of vehicle. Mattress, belts, side rails, IV stand and fixing devices are included.

### TECHNICAL SPECIFICATIONS

Maximum size (LxWxH): Minimum size (LxWxH): Packing size: Weight Load

193x60x88 cm 193x60x21 cm 195x61x26 cm







Multifunctional automatic stretcher for ambulance with easily adjustable positioning system, for any emergency situation. The stretcher can bend through 6 different grades, forwards or backwards. The back of the stretcher is fixed by pneumatic springs moving in the range of 0 to 60 degrees, also equipped by front and back fixed supports. It can be locked into place inside ambulance at proper position. Mattress, belts, side rails, I.V. stand and fixing devices are included.

### TECHNICAL SPECIFICATIONS

198x53x93 cm Maximum size (LxWxH) Minimum size (LxWxH) 198x53x34 cm Packing size: 200x60x35 cm Load: 159 kg Net weight, Gross weight: Maximum angle of leaning forwards: 11 degrees Maximum angle of leaning backwards:

35 kg, 40 kg 25 degrees

The height scope of touching down (6 grades): 98 cm- 94 cm - 87 cm

### AUTOMATIC MULTIPOSITION STRETCHER WHEELCHAIR STRETCHER



### 34072 FULL AUTOMATIC MULTIPOSITION STRETCHER

198x54x93 cm

198x54x30 cm

218x67x35 cm

159 kg

Full automatic multiposition stretcher. Easily adjustable to 6 levels for any emergency situation. Back wards and forwards reclining, back and foot rest adjustable to different positions. Can be loaded into ambulance by one operator only and locked at desired position. Structure in high-stength aluminium alloy. Soft foam surface mattress, covered by special seamless welded PVC. Protective block side rust proof and easy to clean. Mattress, belt, side rails, IV stand and fixing device are included. TECHNICAL SPECIFICATIONS

Maximum size (LxWxH): Minimum size (LxWxH): Packing size:

317

Load: Net weight, Gross weight



### • 34070 WHEELCHAIR STRETCHER

Wheelchair stretcher with varied positions. Lightweight emergency cot quickly convert to any of four chair positions for maneuvering in narrow hallways, elevators and other confined spaces. Stretcher is made in high quality

aluminium alloy.

Soft foam mattress and protective block side, rust proof and easy to clean. Mattress, belts, side rails, IV stand and fixing device are included.

### **TECHNICAL SPECIFICATIONS**

Size (LxWxH): 190x57x85 cm 198x60x25 cm Packing size: 159 ka Net weight, Gross weight: 32 kg, 40 kg



• 34094 TWIN SHELL BASKET STRETCHER - orange

• 34098 BASKET STRETCHER - orange

Robust, resistant and flexible, it is ideal for a wide range of rescue operations in mines, at altitude and in water. A revolutionary production technique ensures uniform thickness of the entire length of the stretcher. The shell is in high-density polyethylene and is joined to an aluminium framework for better

strength. The handles for transport, integrated in the structure, are placed along the entire perimeter. The grommets for the fixing of the spring catches of the harnessing are in stainless steel. Inside the shell there is a removable mattress, applied with Velcro®, made in closedcell EPDM, which makes it impermeable to both blood and water. High density polyethylene quarantees shatterproofness and sanitization. It can contain a spine board. Comes with nylon rope along entire perimeter, three 50 mm nylon belts with quick-release buckles, water resistant and closed-cell mattress, footrest in pre-formed polyethylene with position regulator. Twin shell basket stretcher

It can be transversally divided in half to improve the storage and transport. To ensure a perfect hold between the two shells, have been inserted four nylon cones and a security system protected by a protuberance placed in the mould itself.

• 34099 LIFTING BRIDLES

Adjustable, can be used for horizontal and vertical patient lifting. Manufactured in durable woven nylon with sound steel attachment hardware and brass locking mechanism.

34100 FLOTATION SYSTEM

• 34096 CARRYING BAG for 34094

### WHEELCHAIR STRETCHERS

• 34060 WHEELCHAIR STRETCHER - 2 wheels

• 34074 WHEELCHAIR STRETCHER - 4 wheels

Specially designed for confined areas such as narrow hallways or multiple landing stairways; anywhere access is seriously limited. Made in light aluminium with waterproof orange sheet. Two rearstationary wheels Ø 12 cm (34060) or 4 wheels, 2 with brake (34074) two back handles and four front handles. 2 adjustable 30 cm, facilitate transport on most floor types. 2 quick lock safety belts immobilize patient during transport. Locking safety latch maintains chair position during use.

### TECHNICAL SPECIFICATIONS

Folded size: 91x52x19.5 cm Open size: 91x52x71 cm Wheelchair size: - back height: 91 cm - width: 52 cm seat height: 48 cm - width: 52 cm Loading Weight: 8.5 kg



Height

open/close

154/104 cm

### 🛮 FOLDING STAIR CHAIR AND EVACUATION CHAIR 🚄

Foldable

• 34058 EVACUATION CHAIR - orange/chrome

Designed and built for emergency patient removal from confined spaces. Folded it can be stored in most ambulances. Manufactured from chromed steel with brakes on the front wheels. Seat cover made of vinyl coated nylon, easily washable. Folds in one C€ movement, equipped with two quick-release patient restraints.

• 34059 FOLDING CHAIR - black/yellow (orange/chrome on request)

A cost effective choice for moving patients through difficult situations. Four non-slip grip handles make lifting the patient safer and easier. Two large rear wheels provide easy manoeuvering. Tough, black, vinyl coated seat cover easy to clean, resists stain and provides bacteriostatic protection.

Supplied with a set of 3 plastic buckle belts. Made in Italy • 34061 SKID EVACUATION CHAIR - with braking slide

Skid-Ok a new ultra compact evacuation chair with innovative aluminium frame and tubular trellis swing fork.

New concept materials and components make the chair lightweight and easy to manoeuvre to offer top performance in any scenario. Reclining armrests to increase patient comfort. The innovative self braking

slide system offers the operator total control during the stair descent. Manufactured in welded aluminium with polished finish.

Adjustable seat strengthened with Spentex®.

Skid-OK is supplied with 2x50 mm polypropylene belts. Made in Italy

TECHNIC	CAL SPECIFI	CATIONS	
	34059	34058	34061
	FOLDING	EVACUATION	SKID
Height (open/closed):	92 cm	98/78 cm	154/104 cm
Width:	48 cm	41 cm	52 cm
Depth with retracted handles:	59 cm	-	
Depth with extended handles:	125 cm	open 80 cm	
Depth when folded handles:	19 cm	closed 31 cm	
Weight:	10 kg	12 kg	11 kg
Load:	165 kg	116 kg	150 kg

34098

TECHNICAL SPECIFICATIONS

34098

13.5 kg

34098+34099

34098+34100

Size (LxWxH): 215x65x19 cm 118/215x64x19 cm

 34598 SMART OXYGEN CONCENTRATOR 5 I Medical grade, ultra quiet, small oxygen concen-

trator for home use. Provide high concentration of oxygen through nasal canula. Work continuously. Flow range:

• 34599 PAPER FILTER - box of 10

• 34608 HUMIDIFIER BOTTLE

• 34167 OXYGEN MASK with tube - pediatric • 34166 OXYGEN MASK with tube - adult

• 34172 OXY GLASSES - nasal cannulas

**OXYGEN CONCENTRATORS 3 AND 5 LITRES** 

Oxygen concentration

Output pressure:

Operating voltage:

Input power:

Size - weight:

• 34604 OXYGEN CONCENTRATOR 3 I

• 34605 OXYGEN CONCENTRATOR 5 I - with nebulizing function

FIRST AID - PARAMEDICAL - EMERGENCY

SMART OXYGEN CONCENTRATOR

Bionic and streamlined fashion design, which won the national outlook top award-Red Star Award. Low noise achieved by using advanced round airway and multi-level noise decreasing design. Large LCD screen for clearer figures. Cumulative time metering and timing off function. Fault self-detection system. Four alarm functions:

Flow range:

Input power:

Packing size:

Net/gross weight:

Oxygen concentration: Output pressure:

Operation noise level

- power failure alarm - low oxygen concentration alarm

- pressure cycle failure alarm - compressor failure alarm

Nebulizing function (only 34605)

Oxygen concentrator (with nebulizer function) uses the combination of oxygen uptake and atomization function to offer clean and safe air. It assists in atomized treatment while maintaining the same oxygen concentration.

-62x37xh 71 cm

-230 V - 50 Hz (on request 110 V - 60 Hz)-

• 34607 PAPER FILTER - box of 10 (5 internal + 5 external)

• 34608 HUMIDIFIER BOTTLE

34604

0.5 ~ 3 l/min

93% + 3%

≤ 50 dB (A)

TECHNICAL SPECIFICATIONS

• 34166 OXYGEN MASK with tube - adult

• 34172 OXY GLASSES - nasal cannulas • 34167 OXYGEN MASK with tube - pediatric

uwe

Top manufacturer over 200,000 pcs/years

and nebulizer set

(3)

knob

TECHNICAL SPECIFICATIONS

230 V - 50 Hz (110 V - 60 Hz on request)

**(** € 0123

0.5 ~ 5 l/min

40 ~ 70 kPa

Operation noise level: 

48 dB (front) - 

52 dB (whole unit)

39x24xh 50 cm - 16 kg

400 W

Supplied with filter, nasal oxygen canula, nebulizer set (34605 only)

### OXYGEN CONCENTRATOR 3 AND 5 L DELUXE

34605

0.5 - 5 l/mir

95.5% ~ 87%

< 53 dB (A)

400VA

• 34616 OXYGEN CONCENTRATOR 3 | DELUXE

• 34617 OXYGEN CONCENTRATOR 5 I DELUXE

Top of the range oxygen concentrator with innovative design and superior features:

- backlit LCD screen with adjustable brightness

- built-in oximeter for monitoring SpO, in real time

- oil free pump: the heart of concentrator adopt compressor with German technology for 30,000 hours service life and 5 years warranty

- high intake position, cleaner air

- remote control function

- 4 alarm system (low oxygen concentrator alarm, power outage alarm, pressure cycle failure alarm, compressor failure alarm), self detection of fault

- 4 safety protections

• 34618 PAPER FILTER - box of 10 • 34619 HUMIDIFIER BOTTLE

• 34166 OXYGEN MASK with tube - adult

• 34167 OXYGEN MASK with tube - pediatric

• 34172 OXY GLASSES - nasal cannulas





TECHNICAL SPECIFICATIONS 34616

Flow range: Oxygen concentration Operation noise level: Output pressure Input power: Size - Packing size

93% + 3 % ≤ 46 dB(A) 20 ~ 50 kPa 320VA

40 ~ 70 kPa 400VA 50x21xh 64 cm - 56x32xh 71.5 cm 230 V - 50 Hz (110 V - 60 Hz on request)

34617

87-95 5 % ≤ 49.5-52 dB(A)

319

### OXYGEN CYLINDERS: 0.5, 2, 3, 5 AND 7 LITRES





Oxygen therapy masks are produced with non toxic material, complete with adjustable elastic clip for nose and



CYLINDERS FOR OXYGEN THERAPY (empty)

Steel cylinders for therapeutic oxygen at 200 bar pressure, with valve and safety lock. These cylinders are ideal for home and hospital therapeutic use, particularly in case of desultory oxygen supply. Supplied in a sturdy plastic bag (5 and 7 l) or soft bag (2 and 3 I) with cover. Oxygen cylinders are provided with a pressure reducer with two-stage release valve (0-15 l/min) and high pressure manometer to indicate oxygen quantity in the cylinder (Code 34510/34511) and face mask (excluding 34500/34520).

GII		OXYGEN CYLINDERS WITH INTEGRATED PRESSURE REDUCER				
UNI	NF	Litres	Flow	Size	Weight kg	
34500	34520*	0.5	fixed 6 I	Ø 60x400mm	2.75	-
34502	34522*	2	0/15 l	Ø110x410mm	4.5	with soft bag + cover
34503	34523°	3	0/15 I	Ø110x530mm	5.5	with soft bag + cover
34505	34525*	5	0/15 l	Ø140x550mm	9	with plastic bag + cover
34507	507 34527* 7 0/15 I Ø140x680mm 11			11	with plastic bag + cover	
RESSURE REDUCER with valve 9 steps for flow adjustment						

PRESSURE REDUCER with valve

Pressure reducer with valve and index flowmeter adjustable 0-12 l/min, suitable for cylinders 1 to 3 litres (code 34510/34530) and 5 to

7 litres (34511/34531). It includes two stages, ( release valve and high pressure manometer. Thread cylinder connection: E25/E17 conical refill thread connection

UNI 21.7 x 1/14" or NF Ø 22.91 x 1.514

Apparatus to be connected to a cylinder without valve.					
	UNI	NF	PRESSURE REDUCERS WITH VALVE - spare		
	34510	34530*	Integrated pressure reducer with valve for 2/3 litres		
	34511	34531*	Integrated pressure reducer with valve for 5/7 litres		
	34539		Cover protection for cylinders 2/3/5/7 litres		
	GIMA code		OXYGEN THERAPY MASKS		
	34166		Oxygen therapy mask - adult - with tube		
	34167		Oxygen therapy mask - paediatric - with tube		
	34168		HI-Oxygen therapy mask - adult - with tube		
	34169		HI-Oxygen therapy mask - paediatric - with tube		
	34276		Disposable oxy tube - 2m - female - female		
24472		172	Over alasses inasal cannulas		

34510

### 34172 Oxy glasses - nasal cannulas

Products not in stock, available in 15 days

### GENERAL PURPOSE CYLINDERS 5 AND 10 I AND PRESSURE REDUCERS













DETAILS OF PRESSURE REDUCER WITH FLOWMETER

19	-	= 8	-8	-
UNI	NF	DIN	BS	PIN INDEX
34541	34551	34561	34571	34581

PRESSURE REDUCER - WITH FLOWMETER AND HUMIDIFIER (34541, 34551, 34561, 34571, 34581) Pressure reducer with release valve and H.P. manometer with adjustable ball flowmeter 0-15 l/min and autoclavable humidifier apparatus to be connected with cylinder valve.



### GENERAL PURPOSE CYLINDERS (empty)

Supplied with valve. Ideal for anaesthesia apparatus, can be used with pressure reducer code 34540-34541 or other standards (NF, DIN, BRITISH STD or PIN INDEX).

		GIMA cod		OXYGEN CYLINDER WITH	
UNI	NF	DIN	BULL NOSE BRITISH STD		VALVE AND ACCESSORIES
34545	34555*	34565*	34575*	34585*	Oxygen Cylinder 5 I with valve
					Oxygen Cylinder 10 I with valve
					Pressure reducer
34541	34551*	34561	34571*	34581*	Pressure reducer with
					flowmeter and humidifier
34590	34590	34590	34590	34590	Humidifier autoclavable at 121°C

PRESSURE REDUCER (34540, 34550, 34560, 34570, 34580) Same as code 34541, with adjustable flow 0-15 l/m in 9 steps (1/1.5/2/3/4/6/9/12/15), LP\* port, without flowmeter and

34590





34590 AUTOCLAVABLE HUMIDIFIER

• 34177 TROLLEY FOR OXYGEN CYLINDER - 5 | -7 | • 34178 TROLLEY FOR OXYGEN CYLINDER - 10 I

\*Low pressure port (for ventilators,...)



34200 34204

34200 AMBU® MARK IV RESUSCITATOR - adult

Designed in accordance with the original double wall principle, the new 100% latex-free Ambu bags are more robust and provide users with exceptional visual and tactile lung condition feedback during manual resuscitation, making operation safer and more secure.

Built-in pressure limitation prevents compression if there is any resistance in the patient's airways.

Suitable for adults and children over 15 kg (3 years). Supplied with face mask N°5 and single shutter valve. Autoclavable at 134°C.

Maximum volume 1300 ml

### • 34204 AMBU® MARK IV RESUSCITATOR - babv

Same as 34200, but suitable for neonates, infants and children up to 20 kg (approx 4-5 years).

Supplied with face mask N°OA, oxygen reservoir tube 250 mm and pressure limiting valve 4.0 kPa (40 cm H<sub>2</sub>O). Maximum volume 300 ml.

• 34217 AMBU MARK® IV RESUSCITATOR - adult with kit bag Same as code 34200, supplied with helicoidal mouth-wedge, tongue holding forceps, 3 Guedel airways (small, medium and large) and oxygen tube, all fitted in a resistant nylon bag.



The silicone face masks are self-inflating and the cuff pressure can be regulated for an easy and efficient seal. They are comfortable to grip and feature a thumb rest so rescuers can achieve a tight seal. Visual checks of bleeding, vomitus and spontaneous breathing can be made through the transparent dome. Autoclavable at 134°C





### GIMA RESUSCITATORS - DOUBLE CHAMBER, WITH QUALITY MASK

### GIMA RESUSCITATOR BAG - with double chamber

Highly professional resuscitator bag with an antistatic autoclavable and self expanding rubber internal bag and with extra soft external bag.

Available in 2 models: adult and infant.

All models are equipped with connections in accordance with EN 1281-1 directives for peep valve, intubation fitting, oxygen reservoir, oxygen intake and face masks.

Radiotransparent and latex free All equipped with removable and autoclavable valve. Made in Italy.

• 34240 RESUSCITATOR BAG - adult

Supplied with facemask N° 4 - volume 1900 cc

• 34241 RESUSCITATOR BAG - with kit bag

Same as 34240 supplied with helicoidal mouth-wedge, tongue holding forceps, 3 Guedel airways (small, medium and large) and oxygen tube, all fitted in a resistant nylon bag.



• 34242 RESUSCITATOR BAG - infant Supplied with facemask N° 2 - volume 400 cc 321





### GIMA RESUSCITATORS WITH DOUBLE STAGE VALVE



### GIMA RESUSCITATOR BAGS

The line offers 3 models of different size: adults, children, infants and an adult kit. All models are supplied with pressure relief valve and equipped with connector under EN 1281-1 directive for: peep valve, intubation fitting, reservoir, oxygen intake, face mask. Each resuscitator can be completely disassembled for cleaning and sterilization. Made in Italy. Autoclavable at 121°C max 20 times.

- 34230 RESUSCITATOR BAG with mask N°4 adult With a special double stage valve at 54 m/bar. Volume 1800 cc.
- 34233 RESUSCITATOR BAG with mask N°3 child With a special double stage valve at 54 m/bar. Volume 800 cc. • 34232 RESUSCITATOR BAG - with mask N°2 - infant/newborn
- 34231 RESUSCITATOR BAG adult with kit bag Same characteristic as code 34230. It is supplied with helicoidal mouth-wedge, tongue holding forceps, 3 Guedel airways (small, medium and large) oxygen tube, in a nylon bag.
- 34271 NYLON BAG 18.5x15xh 30 cm spare



### SILICONE TRANSPARENT AUTOCLAVABLE RESUSCITATORS

Size 235xØ 78 mm

Capacity=400 cc

SILICONE RESUSCITATORS - latex free

Transparent resuscitators made of silicone and polysulfone fully autoclavable at 134°C.

• 34244 SILICONE RESUSCITATOR KIT - adult

Supplied with silicone face mask N° 4, 60 cm H<sub>2</sub>O pop-off valve, oxygen tube 2 metres, autoclavable reservoir valve and 2500 ml reservoir bag. Volume: 1,600 ml.

• 34245 SILICONE RESUSCITATOR - adult

Supplied with silicone face mask N° 4. Volume: 1600 ml.


• 34246 SILICONE RESUSCITATOR - child


Supplied with silicone face mask N° 3 and 40 cm H<sub>2</sub>O pop-off valve. Volume: 500 ml.

• 34247 SILICONE RESUSCITATOR - infant

Supplied with silicone face mask N° 1 and 40 cm H<sub>2</sub>O pop-off valve. Volume: 280 ml. All silicone resuscitator have multilanguage manual:











€ 0476

All resuscitators

are LATEX FREE

34245



### AMBU® SPUR II RESUSCITATOR - THE NEXT GENERATION

Thin-walled compression

AMBU SPUR II RESUSCITATOR - single patient Ambu SPUR II provides users with exceptional tactile and visual feedback during resuscitation. The bag is highly responsive, with minimal mechanical resistance. Furthermore the characteristic design provides optimum stroke volume with perfect recoil. Range includes infant, pediatric, and adult sizes. All Ambu SPUR II resuscitators come in individual, resealable plastic carrying bags, complete with mask, reservoir bag (34235, 34236 only) oxygen tube and pressure limiting valve 4.0 kPa H<sub>2</sub>O (34236/7 only). The bags are color-coded for fast identification of infant, pediatric, and adult sizes.

- 34235 AMBU SPUR II ADULT with face mask n° 5 and reservoir bag
- 34236 AMBU SPUR II PEDIATRIC with face mask n°1 and reservoir bag
- 34237 AMBU SPUR II INFANT with face mask no 0

	TECHN	VICAL SPECIFI	CATIONS	
	i L Ci ii	34235	34236	34237
Suitable for		adult > 30 kg	baby 10 to 30 kg	infant < 10 kg
Stroke volume	1 hand	800 ml	450 ml	150 ml
	2 hand	1,000 ml		
Resuscitator volume		1,475 ml	635 ml	220 ml
Size (Length x diameter	)	295x127 mm	234x99 mm	168x71 mm
Bag reservoir volume		2600 ml	1500 ml	-
-				



Integrated handle

### **RESUSCITATOR BAGS SINGLE-USE, SINGLE PATIENT - LATEX FREE**

**PVC RESUSCITATORS - SINGLE PATIENT USE** 

Disposable resuscitator bags with disposable mask, no return membrane valve and connection for PEEP valve. PVC disposable, transparent mask shaped to allow a perfect

adhesion to the patient's face. Latex free. • 34277 PVC RESUSCITATOR - adult

Supplied with single use mask N° 5. Volume: 1,600 ml



- 34248 PVC RESUSCITATOR child Supplied with single use mask N° 3 and 40 cm H<sub>2</sub>O pop-off valve. Volume: 500 ml
- 34249 PVC RESUSCITATOR infant
- Supplied with single use mask N° 1 and 40 cm H<sub>2</sub>O Pop-off valve - Volume: 280 ml
- 34239 PVC RESUSCITATOR KIT adult

Same as code 34277. Supplied with oxygen reservoir 2,500 ml, tongue holding forceps and oxygen tube in a nylon bag.



### **GUEDEL AIRWAYS**

STERILE AND NON STERILE GUEDEL AIRWAYS

Guedel airways in 9 sizes with smooth surface and round tip for improved patient comfort. Made in polyethylene (PE). Latex free.

GIMA	GUEDEL AIRWAYS - STERILE	Minimum
code	FLEXIBLE, TRANSPARENT, INDIVIDUALLY PACKED GUEDEL AIRWAYS	order
34431	Guedel airway 40 mm - pink - newborn - 000	box of 10
34432●	Guedel airway 50 mm - blue - newborn - 00	box of 10
34433●	Guedel airway 60 mm - black - child - 0	box of 10
34434▲	Guedel airway 70 mm - white - boy - 1	box of 10
34435▲	Guedel airway 80 mm - green - adult/small - 2	box of 10
34436●	Guedel airway 90 mm - yellow - adult/small - 3	box of 10
34437●	Guedel airway 100 mm - red - adult/medium - 4	box of 10
34438●	Guedel airway 110 mm - orange - adult/large -5	box of 10
34383	Guedel airway 120 mm - purple - adult/x-large	box of 10
34439	Mixed Guedel airways pack of 1 pcs. of ● m	
	and 2 pcs of $\blacktriangle$ marked airways for a total of	of 10 pcs.



GIMA code	GUEDEL AIRWAYS - NON STERILE FLEXIBLE, TRANSPARENT,	Minimum order
57751	Guedel airway 40 mm - pink - newborn - 000	box of 50
57752	Guedel airway 50 mm - blue - newborn - 00	box of 50
57753	Guedel airway 60 mm - black - child - 0	box of 50
57754	Guedel airway 70 mm - white - boy - 1	box of 50
57755	Guedel airway 80 mm - green - adult/small - 2	box of 50
57756	Guedel airway 90 mm - yellow - adult/small - 3	box of 50
57757	Guedel airway 100 mm - red - adult/medium - 4	box of 50
57758	Guedel airway 110 mm - orange - adult/large - 5	box of 50

### SILICONE AUTOCLAVABLE AND SINGLE USE FACEMASKS

### GIMA AUTOCLAVABLE FACE MASKS Made in silicone and polycarbonate (sizes FACE MASKS - ANAESTHESIA MASKS 3. 4. and 5) or all in silicone (sizes 0. 1 and 2). Completely transparent, allowing a total visibility. They can be used with

any resuscitator and lung ventilator. AUTOCLAVABLE UP TO 40 TIME 34221

	34222
GIMA	SILICONE FACE MASKS
code	LATEX FREE
34220	Facemask N° 0 - infant small
	Facemask N° 1 - infant large
34222	Facemask N° 2 - child small
34223	Facemask N° 3 - child large
34224	Facemask N° 4 - adults small
34225	Facemask N° 5 - adults large

### GIMA PLUS AUTOCLAVABLE

Blue silicone inflating cuff and unbreakable transparent polysulfone hood. They can be used with any resuscitator or lung ventilator. Available in 5 sizes. Latex free.

UTOCLAVABLE UP TO 120 TIME

GIMA code	GIMA PLUS FACE MASKS LATEX FREE
34253 34254 34255	Face mask N°2 - child small Face mask N°3 - child large Face mask N°4 - adult small Face mask N°5 - adult large Face mask N°6 - adult extra large

### INFLATABLE AIR CUSHION

**FACE MASKS - ANAESTHESIA MASKS** 

Quality disposable single patient face masks provided of connector for air inflation and hook. Available in 7 sizes.



GIMA	GIMA SINGLE PATIENT FACE MASKS
code	LATEX FREE
7700	Facement NO Consultant white

5//00	racemask in 0 - newborn - white
	Facemask N° 1 - infant - pink
57702	Facemask N° 2 - child - yellow
57703	Facemask N° 3 - child large - red
57704	Facemask N° 4 - adult - green
57705	Facemask N° 5 - adult large - blue
57706	Facemask N° 6 - adult extra large

### OXYGEN RESERVOIRS, VALVES AND ACCESSORIES



•	(A)		-	34275	Sac.	<b>C</b>	Į.
342	257	34258	-	34279		34259	
GIMA code	OXYG	EN RESERV	OIR - OXYG	EN TUBE	To b	e used with GIM	A codes
34275	SINGLE USE OXY	GEN RESER	RVOIR - 2,500	ml - without valve		- 34245 - 3427 alve 34279), AMBU	
34279	RESERVOIR VAL	VE - autocl	avable		34275		
	SINGLE USE OX				34246	- 34247 - 3424	8 - 34249
34258	SINGLE USE OX	YGEN RESE	RVOIR - 2,500	ml - with valve	34244	- 34245 - 3427	7
24276	OVVICENTIBE	2			A 11		

34276 OXYGEN TUBE - 2 m All resuscitators 34259 NON-REBREATHING VALVE with 60 cm H,O Pop-off - autoclav. 34244 - 34245 - 34277 34227 PEEP VALVE - 30 mm (5-20 cm H,O) 34244-5 - 34277 (need 34228) 34227 autoclavable at 121°C/248°F 34230 - 34240 - 34200 34228 PEEP VALVE ADAPTOR - int, Ø 22 mm, ext, Ø 30 mm 34227 - 34248 - 34249 34256 REAR VALVE (intake valve) 34244 - 34245 - 34246 - 34247

### ULTRA FACE MASKS

### ULTRA ANAESTHESIA - FACE MASKS

Disposable single patient face masks. Anti-slip design and anatomical shape for a precise fit. Excellent visibility, soft and comfortable seal. Provided with hook. Medical grade non-PVC, phthalate free.



GIMA		Suitable	
code	MASKS LATEX FREE - box of 50	for kg	
57711	Facemask N° 1 - infant - pink	2-10	
	Facemask N° 2 - child - yellow	10-25	
57713	Facemask N° 3 - adult S - green	25-60	
	Facemask N° 4 - adult M - red		
E774E	Facamanda NIO F and old I labora	. 110	

### MOUTH OPENERS AND TONGUE HOLDING



34274 • 34274 TONGUE HOLDING **FORCEPS** 

### NYLON BAG

Suitable for all

# • 34271 NYLON BAG

### STERILE CUFFED AND UNCUFFED ENDOTRACHEAL TUBES

code	STERILE	order
	box of 10	
(€0	Uncuffed Endotracheal tube Ø 4 mm - 21 cm 123	BOX 01 10
9	The second of th	1

LINCHEEED ENDOTRACHEAL THREE


	GIMA code	CUFFED ENDOTRACHEAL TUBES - STERILE	Minimum order
1	34387	Cuffed Endotracheal tube Ø 3.5 mm - 18.5 cm	box of 10
	34388	Cuffed Endotracheal tube Ø 5 mm - 24.5 cm	box of 10
	34389	Cuffed Endotracheal tube Ø 6 mm - 28.5 cm	box of 10
	34390	Cuffed Endotracheal tube Ø 6.5 mm - 29.5 cm	box of 10
	34391	Cuffed Endotracheal tube Ø 7 mm - 31 cm	box of 10
	34392	Cuffed Endotracheal tube Ø 7.5 mm - 31.5 cm	box of 10
	34393	Cuffed Endotracheal tube Ø 8 mm - 33 cm	box of 10
	34394	Cuffed Endotracheal tube Ø 8.5 mm - 33 cm	box of 10
	34395	Cuffed Endotracheal tube Ø 9 mm - 33 cm	box of 10
	34396	Cuffed Endotracheal tube Ø 10 mm - 33 cm	box of 10
	Ø: Internal	diameter	324

### LARYNGEAL MASKS FOR SAFE AND EASY INTUBATION

### SILICONE REUSABLE LARYNGEAL AIRWAY MASK

- 1. Optimal anatomical design ensure convenient and safe insertion. Universal 15 mm connector (ISO).
- 2. See-through flexible airway tube, clear guideline for easy insertion
- 3. Tiny protruding bumps minimize the vomiting substance flowing from exophagus and into the lung.
- 4. Seamless cuff formation offers maximum comfort.
- 5. Strengthened oval tip prevents possible bending during insertion 6. Thin walled pilot balloon facilitates the sensing of the inflation

GIMA code	Size	Patient range	Weight range	Cuff volume (ml. of air)
34424	1.5	infant	5-10 kg	7 ml
34425	2	infant	10-20 kg	10 ml
34426	2.5	child	20-30 kg	14 ml
34427	3	boy	30-50 kg	20 ml
34428	4	adult	50-70 kg	30 ml
34429	5	adult	>70 kg	40 ml



The airway tube is flexible at the cuff and rigid at the connector for easy,

matic insertion and removal

Practical clea

'window"

to view

### AMBU® AURAONCE™ DISPOSABLE LARYNGEAL MASK AMBU® AURAONCE™ DISPOSABLE LARYNGEAL MASKS

Cuff and airway tube moulded

as single unit with built-in

AuraOnce has a special curve that carefully replicates natural human anatomy. Molded directly into the tube, the unique shape makes correct insertion easy without abrading the upper airway. AuraOnce's curve also ensures that the patient's head remains in a natural supine position when the mask is in use without extra stress on the upper jaw. Moreover, Auraonce is specially designed to give the airway tube the flexibility needed to adapt to individual anatomical variances and wide range of head positions. AuraOnce has a D-shaped airway tube

to give a firm and ergonomical grip during insertion. In short, positioning is fast and accurate, with least possible internal pressure.

- Packaged sterile and ready for use
- Colour coded pouch with directions for use - Available in 5 sizes fitting a wide range of
- patients.

flexible scope

### **TECHNICAL SPECIFICATIONS**

Maximum intra-cuff pressure: 60 cm H<sub>3</sub>O Airway connector: 15 mm male (ISO 5356-I) Tube/cuff material PVC

	with un	in pilot balloon iversal check val s precise tactile on of degree ion	Universal 15 is connector (ISI
GIMA code	AMBU® AURAONCE™	Patient weight	Maximum cuff inflation volume
34406	Laryngeal Mask N 2 - pink	10-20 kg	10 ml
34407	Laryngeal Mask N 2.5 - pink	20-30 kg	14 ml
34408	Laryngeal Mask N 3 - green	30-50 kg	20 ml
34409	Laryngeal Mask N 4 - yellow	50-70kg	30 ml
34410	Laryngeal Mask N 5 - blue	70-100 kg	40 ml

month side

without ridges

### LARYNGEAL MASK VENTILATION & INTUBATION

### AMBU® AURA-i™ DISPOSABLE LARYNGEAL MASKS

Ambu® Aura-i™ is a disposable laryngeal mask designed for everyday use. Pre-formed to follow the anatomy of the human airway, the soft rounded curve of the Aura-i ensures fast and easy placement and guarantees long-term performance. Aura-i is the preferred everyday routine device for establishing an airway where an ET-tube is deemed unnecessary. At the same time it holds a place on the difficult airway cart. In case of a "Cannot Intubate - Cannot mask Ventilate" (CI-CV) situation, where the purpose is to intubate the patient, Aura-i can be used as conduit for direct endotracheal intubation assisted by a

The airway tube is designed to allow easy passage of an appropriately sized ET-tube. The recommended ET-tube size is indicated on the connector block of the mask Aura-i comes in a complete range of 5 sizes, suitable for pediatrics and adults.

- packaged sterile and ready for use
- colour coded pouch with directions for use - available in 5 sizes fitting a wide range of
- natients Direct endotracheal intubation using

a flexible scope and standard ET-tubes

### **TECHNICAL SPECIFICATIONS**

Maximum intra-cuff pressure: 60 cm H<sub>2</sub>O Airway connector: 15 mm ISO 5356-1 Tube/cuff material PVC



GIMA code	AMBU® AURA-i™	Patient weight	Maximum cuff inflation volume	Mask ET-Tubes
34593	Laryngeal Mask N 2 - pink	10-20 kg	10 ml	5.0
34594	Laryngeal Mask N 2.5 - violet	20-30 kg	14 ml	5.5
34595	Laryngeal Mask N 3 - green	30-50 kg	20 ml	6.5
34596	Laryngeal Mask N 4 - orange	50-70kg	30 ml	7.5
34597	Laryngeal Mask N 5 - blue	70-100 kg	40 ml	8.0

### STANDARD LARYNGOSCOPE BLADES AND SETS - 2.5 V



code

- standard 2.5 V vacuum bulb
- light ergonomic, satin finish handle to reduce glare
- Stainless Steel contacts guarantee long working life
- easy sterilization ETO or steam
- full range of Mc Intosh & Miller blades, latex free
- ISO 7376 fittings allow use of blades with existing handles
- set is packaged in an anti-shock case and in cardboard box
- 2.5 V handles work with both alkaline batteries or rechargeable batteries
- good light transmission of 3,500 LUX with 2.5 V handles
- autoclavable up to 134° for 5 minutes (approx. 2,000 times)
- non magnetic blades and handles

GIMA code	STANDARD BLADES	Overall Length mm	Distal Width mm
34310	Blade N° 00 MILLER OXY - premature	65	12.5
34311	Blade N° 0 MILLER - premature/newborn	78	11.5
34312	Blade N° 1 MILLER - babies	102	11.5
34313	Blade N° 2 MILLER - adults	155	16.5
34314	Blade N° 3 MILLER - adults/large	195	16.5
34317	Blade N° 0 Mc INTOSH - newborn	80	13
34318	Blade N° 1 Mc INTOSH - babies	92	14
34319	Blade N° 2 Mc INTOSH - infants	100	14
34320	Blade N° 3 Mc INTOSH - adults	130	18
34321	Blade N° 4 Mc INTOSH - adults/large	155	18

### 34301 Pediatric set 2 blades MILLER 0-1 3 blades MILLER 00-0-1 34307 Pediatric set 3 blades MILLER 0-1, Mc INTOSH 0 3 blades MILLER 1, 2, 3 34305 Pediatric set 34306 Doctor set 3 blades Mc INTOSH 2-3-4 34302 Adult set 34303 Adult set 4 blades Mc INTOSH 1-2-3-4 **BULBS, BATTERIES AND RECHARGEABLE HANDLES** code 34352 Small rechargeable handle - pediatric (2xAA) - 2.5 V 34354 Large rechargeable handle - adult (2XC) - 2.5 V Pediatric rechargeable Li-ion battery 2.5 V AA 34467 Adult rechargeable Li-ion battery 25 V "C" 2.5 V "Charging time 2.5 hours (34466), 5 hours (34467) 31542 Charging station (including pediatric adaptor, wall support, UK, US and EU plug) 100-240 V 34324 Small Bulbs for MAC N°0 and MILLER N°0,0,1 Large Bulbs for MAC N°1,2,3,4 and MILI FR N°2 3 compatible with Kawe and Rieste

### DISPOSABLE F.O. LARYNGOSCOPE BLADES MILLER AND MC INTOSH

SINGLE-PATIENT USE LARYNGOSCOPE F.O. BLADES Choice of 5 different blades: Mc Intosh N° 2, 3, 4 and Miller N° 0,1. All blades are tested for tensile strength. Individually packed, non sterile.

### COMPATIBILITY WITH ALL "GREEN" F.O. SYSTEMS

			_
GIMA code	DISPOSABLE BLADES NON STERILE	Overall Length mm	Distal Width mm
34481	Metal handle		
34364	Plastic handle		
34365	N° 0 Miller - infant	90	22
34366	N° 1 Miller - child	100	23.3
34375	N° 2 Mc Intosh - adult small	115	34.4
34376	N° 3 Mc Intosh - adult	132	40.6
34377	N° 4 Mc Intosh - adult large	155	58.7
34359	Bulb for old plastic handle sold	up to ma	ay 2016
34358	Bulb for new plastic handle sol		



### GIMA GREEN F.O. XENON/HALOGEN AND LED LARYNGOSCOPES

- maximum light transmission thanks to durable and high quality fibres
- specially designed blades for easy intubation
- matt finished to reduce glare

- autoclavable up to 134°C for 5 minutes. Blades autoclavable up to 2,000 times

- compatible to plasma sterilization
- all blades are compatible to BS EN ISO 7376 Green standard handles
- all blades are made from Austenitic Stainless steel thereby making them rust proof
- long life blades. GIMA offers 3 years Warranty
- a large selection of power sources to use: 'AA' and 'C' type batteries
  - or 2.5 V and 3.5 V rechargeable batteries
  - 2.5 V handles can be used with standard or rechargeable batteries
  - handles are available with 2.5 V and 3.5 V Xenon/Halogen and LED bulbs
  - all blades and handles are non magnetic



### Gima Green and Maxlite: Miller and Mc-Intosh blades

McIntosh Maxlite: 8,000/14,000/20,000/40,000 lux

- Gima Green 4.0 mm Ø EO, bundle with more than 5.500 individual fibre strands
- Miller Maxlite 3.0 mm Ø bundle with more than 5,000 individual fibre strands
- McIntosh Maxlite 4.5 mm Ø bundle with more than 6,500 individual fibre strands High quality fibres ensuring excellent light transmission Gima Green and Miller Maxlite: 7,000 lux with 2.5 V Xenon/Halogen lamp, 12,500 lux with 3.5 V Xenon/Halogen lamp, 18,000 lux with 2.5 LED lamp, 30,000 lux with 3.5 V LED lamp

GIMA code	"GIMA MAXLITE" FIBRE OPTIC BLADES	Α	В
58051 58052 58056 58057 58058 58059 58060 58061	MILLER N° 0 blade - Newborn MILLER N° 1 blade - Infant MC INTOSH N° 0 blade - Newborn MC INTOSH N° 1 blade - Infant MC INTOSH N° 2 blade - Child MC INTOSH N° 2 blade - Child MC INTOSH N° 3 blade - Adult MC INTOSH N° 4 blade - Adult large MC INTOSH N° 5 blade - Adult x-large	80 100 82 93 115 135 155 176	55 75 57 68 90 110 130 151
GIMA code	"GIMA GREEN" FIBRE OPTIC BLADES*	Α	В
34460 34461 34462 34463 34464 34469 34470 34471 34472 34473	MILLER N° 00 OXY blade - Premature MILLER N° 0 blade - Newborn MILLER N° 1 blade - Infant MILLER N° 2 blade - Child MILLER N° 3 blade - Adult MC INTOSH N° 0 blade - Newborn MC INTOSH N° 1 blade - Infant MC INTOSH N° 2 blade - Child MC INTOSH N° 3 blade - Adult MC INTOSH N° 3 blade - Adult MC INTOSH N° 4 blade - Adult MC INTOSH N° 5 blade - Adult x-large MC INTOSH N° 5 blade - Adult x-large	65 78 102 155 195 80 92 100 130 155 175	40 53 77 130 170 55 67 75 105 130 150
*equipped	with detachable fibre ontic light guide		

'equipped with detachable fibre optic light guide

F.O. Light GUIDE FOR GIMA GREEN BLADES

34843 F.O. Light guide for "GIMA Green" N°3

34848 F.O. Light guide for "GIMA Green" N°4

34486 F.O. Light defor "GIMA Green" other - specify code

• 31542 GIMA GREEN CHARGING STATION - 100/200 V - 50/60 Hz It can charge either 2.5 V / 3.5 V NiCa, NimH or Li-ion rechargeable batteries independently of their status of charge. Unit is designed to prevent over charging of batteries.





- closed battery compartment prevent liquid penetrating inside the battery

handles are supplied with lamp. Battery not included

solid metal handle of chromium plated metal

	GIMA GREEN RECHARGEABLE BATTERY HANDLES
GIMA code	F.O. XENON/HALOGEN BATTERY HANDLES - 2.5 V
34480 34481 34466 34467 34485	Pediatric rechargeable metal handle (2xA) - 2.5 V Adult rechargeable metal handle (2xC) - 2.5 V Pediatric rechargeable Li-lon battery 2.5 V 1,000 mAh Adult rechargeable Li-lon battery 2.5 V 2,200 mAh Halogen bulb 2.5 V (minimum order 6 pcs)
	REEN" RECHARGEABLE HANDLES AND BATTERIES 3.5 V - OL up to lot 8 (ped handle) up to lot 7 (adult handle)

Pediatric rechargeable metal handle (3.5 V) - old 34487 Adult rechargeable metal handle (3.5 V) - old Pediatric rechargeable NiCa battery 3.5 V/700 mAh for 34487 Adult rechargeable NiCa battery 3.5 V/1.300 mAh for 34488 Halogen Bulb 3.5 V

F.O. XENON/HALOGEN BATTERY HANDLE 3.5 V Pediatric rechargeable metal handle (3.5 V) Adult rechargeable metal handle (3.5 V) Pediatric rechargeable Li-ion battery\*\* 3.5 V for 34456 Adult rechargeable Li-ion battery\*\* 3.5 V for 34457, 34482 for handles sold after may 2013 Halogen Bulb 3.5 V

F.O. LED BATTERY HANDLES 2.5 V AND 3.5 V

34476 Pediatric LED rechargeable handle 2.5 V Adult LED rechargeable handle 2.5 V Adult rechargeable metal handle - LED light 3.5 V

**COMPATIBILITY HANDLE - BATTERY - BULB** 

	code	Xenon	LED	V	Stan 2xAA	dard 2xC	Rechargeable Li-ion*	Bulb
	34480	Ped.	-	2.5	yes	no	34466	34485
	34481	Adult	-	2.5	no	yes	34467	34485
	34456	Ped.	-	3.5	no	no	31540	34491
	34457	Adult	-	3.5	no	no	31541	34491
	34476	-	Ped.	2.5	yes	no	34466	-
	34477	-	Adult	2.5	no	yes	34467	-
	34482	-	Adult	3.5	no	no	31541	-

\*Li-ion batteries have twice the capacity of an equivalent size NimH batteries

### GIMA GREEN F.O. XENON/HALOGEN, LED LARYNGOSCOPE SETS



LED SETS - Mc Intosh or Miller blades

- F.O. laryngoscopes provide cool bright illumination - Gima Green F.O. blades with detachable fibre or Maxlite F.O. blades with integrated fibre

- Xenon/Halogen or LED F.O. rechargeable battery handle - 2.5 V or 3.5 V rechargeable battery handle (battery not included). 2.5 V rechargeable battery handle can be used with standard or rechargeable batteries. Rechargeable battery handles should be used with charging station 31542 (not included). - non magnetic blades and handles

LARYNGOSCOPE SET WITH F.O. BLADES						
GIMA code	GIMA GREEN	F.O. XENON/HALOGEN SET - 2.5 V				
34451	Pediatric set	2 blades Miller 0-1				
34454	Pediatric set	3 blades Miller 0-1, Mc Intosh 0				
34452	Adult set	3 blades Mc Intosh 2-3-4				
34453	Adult set	4 blades Mc Intosh 1-2-3-4				
34455	Doctor set	3 blades Miller 1-2-3				
34485	Halogen bulb 2.5	5 V (minimum order 6 pcs)				
34450	Empty box without sponge					
GIMA	GIMA GRE	EN F.O. LED SET - 2.5 V OR 3.5 V				

**34327** Adult set 3 blades Mc Intosh 2-3-4 - 2.5 V 34328 Adult set 4 blades Mc Intosh 1-2-3-4 - 2.5 V **34329** Adult set 3 blades Mc Intosh 2-3-4 - 3.5 V 34330 Adult set 4 blades Mc Intosh 1-2-3-4 - 3.5 V

### MAXLITE F.O. BLADE WITH INTEGRATED FIBRE



TECHNICAL SPECIFICATIONS - BLADES AND BULBS							
Gim	na Green F.O. blade	Maxlite F.O.					
		Mc Intosh blade					
Fibre light carrier:	detachable	integrated					
F.O. bundle Ø:	4.0 mm	4.5 mm					
Individual fibre strands:	> 5,500	> 6,500					
Light transmission with 2.5 V (Xenon):	7,000 lux	8,000 lux					
Light transmission with 2.5 V (LED):	18,000 lux	20,000 lux					
Light transmission with 3.5 V (Xenon):	12,500 lux	14,000 lux					
Light transmission with 3.5 V (LED):	30,000 lux	40,000 lux					
Autoclavable at 134 °C:	2,000 times	2,000 times					
LED bulb life:	50,000 hours	50,000 hours					

### LARYNGO SET WITH E.O. BLADES - INTEGRATED FIBRE

	INGO SEI WIIII	I.O. DEADES HATEGINATED HIDI
GIMA code	MAXLITE F.	O. XENON/HALOGEN SET - 2.5 V
34332	Pediatric set	3 blades Miller 00-0-1
34333	Adult set	3 blades Mc Intosh 1-2-3
34334	Adult set	4 blades Mc Intosh 1-2-3-4
34485	Halogen bulb 2.5	V (minimum order 6 pcs)
GIMA code	MAXLIT	E F.O. LED SET - 2.5 V or 3.5 V
		3 blades Miller 00-0-1 - 2.5 V 3 blades Mc Intosh 2-3-4 - 2.5 V

34337 Adult set 4 blades Mc Intosh 1-2-3-4 - 2.5 V 34338 Adult set 4 blades Mc Intosh 1-2-3-4 - 3.5 V **BATTERIES for GIMA GREEN and MAXLITE** 

34466 | Pediatric rechargeable Li-ion battery 2.5 V 1,000 mAh 34467 Adult rechargeable Li-ion battery 2.5 V 2,200 mAh 31541 Adult rechargeable Li-ion battery 3.5 V\*

### FLEXTIP F.O. XENON/HALOGEN AND LED SETS FOR DIFFICULT INTUBATIONS

### F.O. SET FOR DIFFICULT INTUBATION

Deluxe boxed set including one F.O. rechargeable handle, one or two F.O. Mc Intosh blades N° 3 or N° 3 and 4, \_ \_ \_ for difficult intubations and bulb. The movable blade tip facilitates lifting of the epiglottis and enables a perfect visibility of the intubation process even in case of difficult anatomical conditions. A better visibility and a lower lever force reduce the risk of injury of the larynx and the teeth. Autoclavable at 134° C.

- stainless steel construction, matt finish
- can be used with all Green Spec Handles
- compatible with ISO 7376 Green Standards - channel provides improved viewing area
- 4.0 mm fibre bundles (GimaGreen) or 4.5 mm fibre bundle (Maxlite) for maximum light output

- 21 (	batteries of rechargeable batteries
GIMA code	FLEXTIP F.O. SET - 2.5 V
	GIMA GREEN FLEXI F.O. SET 1 blade Mc Intosh 3 GIMA GREEN FLEXI F.O. SET 2 blades Mc Intosh 3-4
34498	MAXLITE F.O. LED FLEXI SET 2 blades Mc Intosh 3-4 with integrated fibre



GIMA code	ACCESSORIES AND SPARES
	FLEXI F.O. BLADE N° 3 Mc Intosh (130x105 mm)
34494	FLEXI F.O. BLADE N° 4 Mc Intosh (155x130 mm)
34485	Bulb 2.5 V - spare
34467	Adult rechargeable Li-ion battery 2.5 V
31542	Charging station 100-240 V - see page 327

# HEINE CLASSIC+® F.O. XHL OR LED<sup>HQ</sup> LARYNGOSCOPES HEINE CLASSIC+® F.O. XHL OR LED<sup>HQ</sup> LARYNGOSCOPES

The "Classic+" range of F.O. blades with HEINE HiLite® Fibre bundle with over 6,500 individual micro-fibres offer improved light transmission and longer life. Together with the innovative HEINE LED™ light in the handle or the traditional XHL Xenon Halogen Bulb, the exclusive HEINE HiLite® Fibre Optic bundle with up to 4.3 mm of Ø offers 3X or 40% brighter light as with other conventional halogen bulbs. 5 years warranty 5-years guarantee or 4,000 standard autoclave cycles of 134°C/5 min. with more than 1,000 lux on all blades with HEINE HiLite® fibre bundle.

Long lasting bulbs HEINE XHL® Xenon Halogen bulbs incorporate the latest Xenon Halogen Technology to give you up to 40% more light! HEINE XHL Xenon Halogen 3.5 V bulbs last up to twice as long as 2.5 V bulbs and give up to three times the light of conventional 2.5 V Halogen laryngoscope bulbs. HEINE LED™ handles offer even three times the light intensity of the 3.5V Xenon Halogen bulbs for an outstanding and constant bright illumination.

Long lasting 3.5 V rechargeable batteries HEINE 3.5 V systems (LED<sup>oo</sup> or XHL) use a long-lasting 3.5 V lithium rechargeable battery which avoids the need to replace non-rechargeable batteries at frequent intervals. HEINE F.O. laryngoscope blades and handles are compatible with the ISO 7376 (green standard).

For fast charge



• 34374 NT 4 CHARGER UNIT FOR 2 HANDLES - X-002.99.494 Two indipendent charging


compartments: fast charge capability:

2 hours for Li-ion handle automatic charging charger indicator



code	code	HEINE FIBRE OPTIC BLADES	length	length	-				
34411	F-000.22.119	MILLER 00	76 mm	9.5 mm					
34412	F-000.22.120	MILLER 0	80 mm	10.5 mm					
34413	F-000.22.121	MILLER 1 100 mm 11.5 mm							
34414	F-000.22.122	MILLER 2 152 mm 13 mm							
34415	F-000.22.110	PAED 0 82 mm 12 mm							
34416	F-000.22.111	PAED 1 95 mm 13 mr							
34417	F-000.22.100	MAC 0	82 mm	9 mm					
34418	F-000.22.101	MAC 1	93 mm	11 mm					
34419	F-000.22.102	MAC 2	115 mm	13 mm					
34420	F-000.22.103	MAC 3	135 mm	15 mm					
34421	F-000.22.104	MAC 4	155 mm	15 mm					
34422	F-000.22.105	MAC 5	176 mm	15 mm					
34423	F-000.22.313	MAC 3 - Flex Tip+	115 mm	13.2 mm	er				
34368	F-000.22.314	MAC 4 - Flex Tip+	137 mm	13.2 mm					
		LARYNGOSCOPE HANDLES AN		RIES	ST				
34430	F-001.22.800	Slim F.O. handle 2.5 V - pedia			Li				
34400	F-001.22.812	Short F.O. handle 2.5 V - pedia	atric and ob	oese	Re				
34401	F-001.22.860	Standard F.O. handle 2.5 V			ha				
34405	F-008.22.860	Standard F.O. handle 2.5 V LE	_		di				
31769	X-001.88.035	Spare bulb 2.5 V for 34400, 34	1401, 34430	)					
31768	X-002.88.044	Spare bulb 3.5 V for 34369			St				
		BLE LARYNGOSCOPE HANDLES			or				
34371	F-008.22.804	Pediatric LED handle 2.5 V Li-			ch				
34372	F-007.22.894	Standard F.O. handle 3.5 V Li-							
34373	F-008.22.894	Standard LED handle 3.5 V Li-			tin				
34378	X-007.99.104	Re-chargeable 2.5 V battery p			13				
34448	X-007.99.383	Re-chargeable 3.5 V battery for Need NT4 charger unit code 34374	r 34372-3, 34	1402, 34367					
	HEINE CLAS	SIC+® FIBRE OPTIC LARYNGOSCO	DE CETC"						
	HEINE CLASSIC+ FIBRE OF IIC LARTINGOSCOFE SETS								

34401	F-001.22.860	Standard F.O. handle 2.5 V
34405	F-008.22.860	Standard F.O. handle 2.5 V LED
31769	X-001.88.035	Spare bulb 2.5 V for 34400, 34401, 34430
31768	X-002.88.044	Spare bulb 3.5 V for 34369
HE	INE RECHARGE	ABLE LARYNGOSCOPE HANDLES AND BATTERIES
34371	F-008.22.804	Pediatric LED handle 2.5 V Li-ion rechargeable*
34372	F-007.22.894	Standard F.O. handle 3.5 V Li-ion - rechargeable*
34373	F-008.22.894	Standard LED handle 3.5 V Li-ion - rechargeable*
34378	X-007.99.104	Re-chargeable 2.5 V battery pediatric for 34371
34448	X-007.99.383	Re-chargeable 3.5 V battery for 34372-3, 34402, 34367
		'Need NT4 charger unit code 34374
	HEINE CLAS	SIC+® FIBRE OPTIC LARYNGOSCOPE SETS**
		SIC+® FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle
34403	HEINE CLAS F-119.10.860	SIC+® FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL
	F-119.10.860	SIC+® FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL handle
34403 34404		SIC+® FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL
	F-119.10.860	SIC+® FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL handle
	F-119.10.860	SIC+° FIBRE OPTIC LARYNGOSCOPE SETS'' with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, XHL
34404	F-119.10.860 F-120.10.860 F-120.18.860	SIC+® FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, LED HQ handle
34404	F-119.10.860 F-120.10.860 F-120.18.860	SIC+* FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, LED
34404	F-119.10.860 F-120.10.860 F-120.18.860	SIG.* FIBRE OPTIC LARYNGOSCOPE SETS:" with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, LED HQ handle with 3.5V rechargeable handle 3 blades set with paed 1, mac 2, mac 3, LED HQ
34404 34446	F-119.10.860 F-120.10.860 F-120.18.860	SIC+* FIBRE OPTIC LARYNGOSCOPE SETS** with 2.5V handle 3 blades set with paed 1, mac 2, mac 3, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, XHL handle 4 blades set with paed 1, mac 2, mac 3, mac 4, LED HQ handle with 3.5V rechargeable handle



STANDARD HANDLE 3.5V LED Rechargeable 3.5V F.O. LED andle with charge status lisplay in bottom cap. State of charge is indicated for 10 seconds after switching on or after removing from the harger. Two hours charging ime with NT4 charger, up to 13 hours ON time.

LEDHQ

ED HANDLE: 5.000 Kelvin 12,000 LUX at 40 mm 50,000 hours bulb life

Handle with charge status display



329

3 channeled vision blades - size 3

1 standard vision blade - size 3

standard

blade

58104

USB port

Vision display

AAA batteries

channeled

blade

58105

### AMBU® KING VISION® VIDEO LARYNGOSCOPE STANDARD ACCESSORIES

### • 58101 KING VISION® VIDEO LARYNGOSCOPE SET

The King Vision® video laryngoscope is especially designed to visualize, in the most reliable way, the airways for routine and difficult intubations.

The reusable display is lightweight, water resistant, non-glare, smudge-proof, packaged in a protective foam case and is battery operated.

The blades are disposable and are individually packaged, eliminating cross contamination risks. It can be used continuously about 80 minutes, making it highly portable.

Video output compatible with external monitor and recording devices.

Two blade types: a standard blade that requires the use of a stylet to direct the ET tube and a channeled blade where you can guide the ET tube with the

Made in the USA

- 58104 STANDARD VISION BLADE size 3 spare
- 58105 CHANNELED VISION BLADE size 3 spare

### Full colour TFT LCD display anti-reflective

NCY

### Protective gasket

Ergonomic design Integrated blade handle design for complete control

Channeled and standard disposable blades for guided or standard insertions

Guiding channel for easy ETT placement and removal

New optics and light in every blade

58101

New anti-fog lens in every blade

### USB F.O. LARYNGOSCOPE HANDLE

### • 34468 USB F.O. LARYNGOSCOPE HANDLE

Universal USB handle for green fibre optic blades. This handle is a charging unit including lithium-ion rechargeable battery and USB port for easy recharging without charging station.

Features:

- glass bead blasted, matt chromium plated surface for a high quality optic
- no surface structure, lateral grooves for hygienic use and secure grip in the hand
- metallic lamp case
- quick and easy removal of bulb
- autoclavable up to 134° (without batteries)
- handle in accordance with ISO 7376 (green standard)

# 34468


Handle supplied in a rigid case with 3

### FO. LARYNGOSCOPE BLADES AND BATTERY HANDLES SINGLE PATIENT STERILE

### SINGLE PATIENT USE F.O. LARYNGOSCOPE BLADES

Choice of 6 blades Miller 0.1 and McIntosh 1, 2, 3, 4 for everyday hospital use. Compatible to ISO 7376 Green System. Light conductor made from material with excellent light transmission: 4,000 lux with 2.5 V Xenon handle and 10,000 lux with LED handle. Need F.O. handle.

A high impact resistant plastic block coupled with metal spatula provides great streng-



### SINGLE PATIENT USE BATTERY HANDLES

- lightweight, suitable for everyday hospital use - single patient use, prevent cross infection
- compatible to ISO
- 7376 Green System - perfect solution to
- cleaning problems confronting EMS field - Ready To Use (RTU) handles are supplied with preloaded batteries, thus eliminating the hessel of loading batteries
- the 'C' type handles are identified with yellow colour bottom cap, supplied without batteries
- suitable also for reusable blades - made in ABS



GIMA code	SINGLE PATIENT USE F.O. LED BATTERY HANDLES 2.5 V
58012	Battery handle "C" type - adult
E0014	Rattery handle "PTII" (ready to use) - pediatric

58015 Battery handle "RTU" (ready to use) - adult





### SMART BAGS - medium - blue

- 27152 SMART BAG medium empty 55x35xh 32 cm
- 34173 "GIMA 3" EMERGENCY BAG filled without cylinder



### LOGIC 2 RUCKSACKS - red

- 27171 LOGIC 2 RUCKSACK empty 40x25xh 47 cm
- 34162 "GIMA 8" EMERGENCY RUCKSACK filled
- 34163 "GIMA 9" EMERGENCY RUCKSACK filled
- 34164 "GIMA 10" EMERGENCY RUCKSACK filled without cylinder
- 34175 "GIMA 11" EMERGENCY RUCKSACK filled

### LOGIC 2 RUCKSACKS PVC COATED - red

 27172 LOGIC 2 RUCKSACK PVC COATED empty - 40x25xh 47 cm

• 34165 "GIMA 12" EMERGENCY **RUCKSACK PVC COATED - filled** same as "GIMA 9", without cylinder

### **EMERGENCY ALUMINIUM CASE** • 34159 ALUMINIUM CASE -

empty - 40x35x10 cm • 34161 "GIMA 2" EMERGENCY CASE - filled

> 34161 Aluminium emergency case



### SMART BAGS - large - red

**EMERGENCY KITS** COMPLETE WITH STANDARD EMERGENCY DEVICES

- 27153 SMART BAG large empty 65x35xh 35 cm • 34174 "GIMA 7" EMERGENCY BAG - filled
- Capacious bag, made in water resistant, anti-scratch 600D polyester, with yellow reflective strips. With 1 large central compartment front and 3 lateral pockets. Can be carried on shoulders (braces)

### **EMERGENCY BAGS - red**

34156

- 27165 EMERGENCY BAG empty 35x45x21 cm
- 34155 "GIMA 6" EMERGENCY BAG filled without cylinder
- 34156 "GIMA 4" EMERGENCY BAG filled
- 34157 "GIMA 5" EMERGENCY BAG filled

### **EMERGENCY BAGS PVC COATED - blue**

- 27167 EMERGENCY BAG PVC COATED
- empty 35x45xh 21 cm
- 34154 "GIMA 13" EMERGENCY BAG

PVC COATED - filled - same as

"GIMA 4", without cylinder 27167



IP67 CERTIFIED DURABLE CASE - waterproof and dustproof • 27222 LARGE DURABLE CASE - empty - 55x43xh 21 cm

• 34176 "GIMA 1" EMERGENCY DURABLE CASE - filled

### EMERGENCY KITS - BAGS, RUCKSACKS, CASES

KIT CONTENTS	Size cm	34155 GIMA 6	34156 GIMA 4	34157 GIMA 5					34176 GIMA 1			34164 GIMA 10		
KII CONTENTS	Size ciii	baq	baq	baq	bag	bag	bag					rucksack		
Container (bag, rucksack or case)		Dug	bug	bug	bug	bug	bug	ui cusc	pi cusc	ruciouci	racksack	ruciouci	rucioucio	ruciouc
Smart bag - medium - blue 600D polyester (27152)	55x35xh 32					•								
Smart bag - large - red 600D polyester (27153)	65x35xh35						•							
Emergency bag - red 600D polyester (27165)	35x45xh 21	•	•	•										
Emergency bag - blue 600D polyester PVC coated (27167)	35x45xh 21				•									
Logic 2 rucksack - red 600D polyester (27171)	40x25xh 47									•	•	•	•	
Logic 2 rucksack - red 600D polyester PVC coated (27172)	40x25xh 47													•
Durable case - orange (27222)	55x43xh 21								•					
Aluminium case (34159)	40x35xh 10							•						
Products included in kits														
Emergency cover (34085)		•	•	•	•	•	•	•	•	•	•	•	•	•
Universal scissors - 15 cm (34128)		•	•	•	•	•	•	•	•	•	•	•	•	•
Facemask n. 2 - child/small (34222)		•	•	•	•	•	•	•	•	•	•	•	•	•
Silicone resuscitator bag with mask n 4 - adult (34245)		•	•	•	•	•	•	•	•	•	•	•	•	•
Teeth screw driver (34273)		•	•	•	•	•	•	•	•	•	•	•	•	•
Tongue holding forceps (34274)		•	•	•	•	•	•	•	•	•	•	•	•	•
Oxygen tube - 120 cm (34276)		•	•	•	•	•	•	•	•	•	•	•	•	•
Mixed Guedel airways - box of 10 (34439)		•	•	•	•	•	•		•	•	•	•	•	
Oxygen therapy mask - adult (34166)				•			•			•			•	
0.5 I oxygen cylinder (empty) with reducer UNI std (34500)			•	•			•	•	•	•	•		•	
Yton nurse stethoscope (32514)		•	•	•	•									
Jotarap dual head stethoscope - black (32580)						•	•	•	•	•	•	•	•	•
Yton sphygmomanometer (32720)		•	•		•									
London sphygmomanometer (32725)				•		•	•	•	•	•	•	•		•
Welch Allyn DURASHOCK sphygmomanometer (32700)													•	
Emergency pack - 3 F.O. single-use blades+plastic handle (34381)		•	•		•					•				
Laryngoscope set 3 Mc-Intosh blades 2-3-4 (34302)				•		•	•		•		•	•		•
"Gima green" F.O. laryngoscope set 4 Mc Intosh blades 1-2-3-4 (34453)													•	
Hand suction unit (28180)		•				•	•					•		
Res-g-vac hand suction unit (28124)				•					•		•		•	•
Delta pen light (25629)				•		•	•		•		•	•	•	•
Fast tourniquet - green (25728)				•		•	•		•		•	•	•	•
Magill forceps - 20 cm (34002)				•		•	•		•		•	•	•	•
Gima digital thermometer °C (25560)				•		•	•		•		•		•	•
Disinfectant wipes - tube 100 wipes (36625)				•		•	•		•		•		•	•
Emocontrol elastic bandage (34782)				•		•	•		•				•	
Gauze bandage 3.5 m x 7 cm - box of 10 (34841)				•		•	•		•				•	
Sterile adhesive dressing 10 x 10 cm - box of 6 (34851)				•		•	•		•				•	
Oxy-4 fingertip oximeter (35092)						•	•						•	
Instant ice - bag 3 pcs. (34111)						•	•		•				•	
Burn dressing - 10x10 cm (34871)											•	•		
3 E3 padded pouches with window red (27188), blue (27189), green (27191)														
2 E4 pouches with window red (27192), yellow (27194)									•					

### INTUBATION BAG WITH EMERGENCY ACCESSORIES

- 27133 INTUBATION BAG empty
- 34152 INTUBATION KIT complete
- 34153 INTUBATION KIT F.O. complete

Compact nylon bag suitable for various uses: 2 internal zip pockets, 9 elastic retainers for instruments, made in water-resistant

Magill forceps Guedel cannula anti-scratch 600D polyester, blue colour. Mouth opener Size: 32x22.5xh 7.5 cm. Scissors cm 14.5 Endotracheal tubes





2 zip pockets

### MEDICATION FIRST AID BAG

• 27132 MEDICATION FIRST AID BAG - empty - 31x22x11 cm

• 34149 MEDICATION FIRST AID BAG - filled

First aid bag provided with 2 internal transparent pockets. one external pocket, internal division with 2 zip on both sides, handle and carrying belt.

### STANDARD ACCESSORIES

London palm sphygmomanometer (32725) Yton single head sthetoscope (32514)

Delta Led pen light (25629) Fast tourniquet (25728)

Digital thermometer (25560) Sterile adhesive dressing 10x10 cm - box of 6 (34851) Liester bandage scissors - 15 cm (34129)

CPR mask (34218) Disinfectant wines

3M Steri strips (34915 - 34916 - 34917 - 34918) Emergency cover (34085)



### GIMA RESUSCITATION KITS • 34181 SPEED 1 RESUSCITATION KIT - UNI cylinder

- 34182 SPEED 2 RESUSCITATION KIT NF cylinder
- 34183 SPEED 3 RESUSCITATION KIT without cylinder
- 34180 SPEED EMPTY CASE with sponge

• 34222 FACEMASK N° 2 - child small

First aid kits for reanimation, very useful for medical and dental rooms, sport clubs, factories, ambulances... Case made of antishock plastic. Size: 43 x 37 x 11 cm.

STANDARD ACCESSORIES SPEED 1 SPEED 2 SPEED 3 Silicone resuscitation bag - autoclavable Silicone Face mask n° 4 Oxygen cylinder 0.5 l (empty). UNI standard

Oxygen cylinder 0.5 I (empty). NF standard High pressure manometer Guedel airways (small + medium + large) Helicoidal mouthwedge + Tongue holding forceps Atoxing tubing for connection to oxygen cylinder

**AVAILABLE WITH** OR WITHOUT CYLINDER CE 34181

### SPLINTER REMOVAL KIT



### • 34190 SPLINTER REMOVAL KIT

Includes everything to remove splinters and for first aid medications. In a polypropylene box size 235x190x43 mm:

- 1 Eye wash solution 100 ml with an eye glass
- 1 magnifying glass, 2 sterile gauze pads 18x40 cm
- 1 Professional removal pencil, 1 mirror.
- 1 stainless steel tweezers 11.5 cm

### • 34192 PROFESSIONAL REMOVAL PENCIL

Small metallic splinters eye tool remover. On one side a magnetic point to remove any metallic splinter avoiding any risk for the eye. On the other side an antiabrasive nylon loop for non metallic splinters.

### **EYE WASH SYSTEMS**

 34889 DROP - eye wash station
Thermo-formed wall kit with all necessary items for an efficent first emergency eye wash - 2 sterile saline solutions of 500 ml

- 2 integrated eye cups and one mirror.
- 34888 EYE WASH SOLUTION 500 ml



**MEDICAL SPORT BAG** 

1 isothermic blanket Gold/Silver

- 160x210 cm 1 Disinfectant liquid 250 ml
- 2 adhesive plasters 5 m x 2,5 cm 2 pairs of sterile gloves
- 2 VENTO mouth to mouth resuscitators 5 instant ice packs 6 sterile gauze pads 18x40 cm
- 2 instant ice sprays 150 ml
- 3 triangular TNT bandages 96x96x136 cm 1 haemostatic lacet
- 3 Elastic bandages 6 cm
- 3 Elastic bandages 8 cm
- cotton wool pack
- 1 pair of LISTER scissors 14,5 cm
- 2 compressive pad bandages 80x100 mm guidance leaflet 5 languages 2 compressive pad bandages 100x120 mm

STANDARD ACCESSORIES 1 pack of 20 adhesive plasters 2x7 cm

• 34135 MEDICAL SPORT BAG Special kit designed for first

aid in sporting clubs (tennis

Soft nylon bag has 2 side pockets and zip

Size: 470x240x190 mm

clubs, swimming pools,

closure.

gymnasium,....).

- 8 adhesive plasters 10x6 cm
- 1 sterile TNT bandage 60x40 cm
- 1 sterile TNT bandage 60x80 cm 6 sterile TNT pads 10x10 cm
- 1 hydrogen peroxide solution
- 1 elastic net bandage
- 1 sterile tweezers
- 5 ammonia towelettes
- 1 sterile saline solution bottle 250 ml 1 gel hands disinfectant 100 ml

### AID FAMILY CASE FIRST AID CASE AND BAG



propylene Guidance in GB, FR, IT, ES,

DE, TR

• 34136 FAMILY FIRST AID CASE • 34450 EMPTY CASE Small first aid case suitable for use anywhere and anytime:

### (at home or office, in the car or boat...). Made in Italy STANDARD ACCESSORIES

- 2 sterile gauze pads 18x40 cm
- 1 pair of scissors. 1 plastic tweezers
- 1 sterile bandage 60x40 cm

333

- 1 cotton wool pack 5 g 1 nack of 10 adhesive plasters 1 tissue pack 10 pcs
- 3 antiseptic wipes
- 1 adhesive dressing 10 x 6 cm 1 gauze bandage 5 cm
- 1 adhesive plaster roll 2 cm x 1m 1 pair of protection gloves Guidance Leaflet 6 language
- 34184 Advised for offices or workshops of 2 people Meets Italian law 388-Art 2





### FIRST AID PLASTIC CASES AND METAL CABINETS



- 34196 MEDIUM KIT plastic case Size: 275x240x123 mm 2 kg
- 34197 MEDIUM KIT metal cabinet Size: 370x300x140 mm 3.8 kg
- 34187 REFILL PACK for code 34196-97
- 34141 EMPTY METAL CABINET 370x300x140 mm



- 34195 LARGE KIT plastic case 1 Size: 460x345x135 mm 6.2 kg
- 34198 LARGE KIT plastic case 2 Size: 395x270x135 mm 6.2 kg
- 34199 LARGE KIT metal cabinet Size: 460x300x140 mm 7.5 kg
- 34189 REFILL PACK for code 34195-34198-34199 without sphygmomanometer
- 34191 EMPTY PLASTIC CASE 1 460x345x135 mm
- 34138 EMPTY PLASTIC CASE 2 395x270x135 mm



34143 METAL CABINET

Supplied with 3 internal metal shelves, removable bottle floor support, 2 small shelves on the door, lock and key. Size 402x582x202 mm - 12.9 kg

• 34145 EMPTY METAL CABINET 402x582x202 mm

- 34194 34196 34195 34143 34151 SPARES STANDARD CASES / 34184-5 34197 34198-9 CABINETS CONTENT ee page Bags liquid soap Bags antiseptic wipes 349 Bottle antiseptic solution 125 ml Bottle antiseptic solution 250 ml 349 Bottle antiseptic solution 500 ml Oxygenated water bottle 349 Ammonia baq 2 Pair protective gloves, sterile 5 2 19 Box of 10 assorted plasters 2 345 Box of 100 assorted plasters Plastosan 345 Box of 100 assorted 7x2 cm Plastosan 345 Adhesive plaster roll 2,5 cm x 5 m 2 2 343 2 Elastic bandage with clip 4,5 cm x 7 m 339 Pack of 8 assorted gauze bandages 339 Gauze bandage 10 cm x 3,5 m 339 Tubular net gauze 336 Pack of sterile compress 10 x 10 cm 3 10 341 Pack of sterile compress 18 x 40 cm 341 Pack of cotton wool 342 Mask with fare shield 16 Pair of scissors cm 14,5 335 Sterile forceps 38 56 Haemostatic lacet Sphyamomanometer + Stethoscope 229-250 Sterile blanket 40x60 cm 2 Pack of instant ice, single use 347 Digital thermometer 78 Trash bag First aid multilanguage booklet Guidance leaflet Irrigating solution 250 ml 349 Irrigating solution 500 ml Triangular blanket 96x96x136 cm Isothermic blanket gold/silver 160x210 cm 347 Sterile burn gel sachet 3.5 g 347 Compressive Emocontrol bandage 339 Pinocchio helicoidal open mouth Vento 324 Autoclavable resuscitator with facemask N° 4 322 Oxygen bottle 0.5 | empty - UNI standard 320 Guedel ainways 323 Atoxic tube for oxygen 324 Mouth opener 324
- 34151 GIMA 3 FIRST AID CASE + OXYGEN CYLINDER Advised for up to 50 people Size: 32x44.5x15 cm Meets Italian law D.M. 388 (15.7.03) art. 1 + emergency kit. Emergency kit includes:
- autoclavable resuscitation with security valve, and silicone
- oxygen bottle 0.5 l (empty) with reductor and oxygen distributor - UNI standard.
- 3 guedel airways, atoxic tube for connection to oxygen. mouth opener and wall support.
- 34148 GIMA 3 EMPTY PLASTIC CASE 34151 334

### MASK FOR MOUTH-TO-MOUTH REANIMATION





Pocket mask for mouth-to-mouth reanimation.

Its special one-direction valve allows oxvgen to flow straight to the patient and minimizes risks of cross-contamination Single-use, non sterile, made in atoxic transparent material, easy to use and carry. Suitable for adults and children.



• 34218 CPR MASK - pocket resuscitator The CPR pocket mask is a non-invasive, latex free mask with an integral nonrebreathing valve and efficient filter to prevent direct mouth contact with the patient's face when providing mouth-tomouth resuscitation.

GIMA

It can be used on adult, child and infant. Supplied in a compact plastic box with a corrugated tube for an easier use.



• 34211 VENTO AIRWAYS - Poly-bag

 34213 VENTO AIRWAYS - Key-holder box Disposable mouth to mouth airway with a one way polycarbonate valve and non-toxic pvc protective foil to avoid any direct contact between patient and rescuer.

Available in 2 versions: in poly-bag or key-holder box.

Instructions in GB, IT, FR, DE.



### LISTER BANDAGE S/S SCISSORS



• 34127 EMERGENCY SCISSORS Autoclavable Stainless steel AISI 420.

Made in Italy.



LISTER BANDAGE SCISSORS									
GIMA code	STAINLESS STEEL	GIMA code	FANTASY - COLOURED RING						
	Lister - 11 cm Lister - 15 cm		Lister - Green ring - 14 cm Lister - Lilac ring - 14 cm						
34130 20500 38530	Lister - 18 cm Lister with belt clip - 14 cm Lister tungsten carbide - 14 cm Lister tungsten carbide - 18 cm	20509 20511 20512	Lister - Foot print - 14 cm Lister - Leropard - 14 cm Lister - Bubble - 14 cm Lister - Hearts - 14 cm						

### STAINLESS STEEL UTILITY AND BANDAGES SCISSORS



All purpose, first aid scissors, easily cut bandages, leather and plaster casts. Autoclavable at 136°C

12 cm - 4.7"	16.5 cm - 6.5"	19 cm - 7.5"	Colour		
20560	20570	20580	Black		
-	- <b>20571 20581</b> Blue				
-	20572	20582	Red		
-	20573	20583	Purple	Special Control of Con	
-	20574	20584	Pink	2	
20590	Nonewood and a				
				2059	

### LEUKOTAPE® K NEUROMUSCULAR TAPE



### NEUROMUSCUI AR TAPE

Elastic adhesive tape for neuromuscular taping. 100% cotton fabric coated with a strong acrylic adhesive mass.

Water resistant. Latex-free. Multilanguage GB, FR, IT, ES, DE, PT, NL.

GIMA code	BSN code	LEUKOTAPE® K NEUROMUSCULAR TAPE
59010	72978-11	LEUKOTAPE® K 5 m x 5 cm - skin
59011	72978-16	LEUKOTAPE® K 5 m x 5 cm - red
59012	72978-21	LEUKOTAPE® K 5 m x 5 cm - blue
59013	72978-23	LEUKOTAPE® K 5 m x 5 cm - black
59014	72978-24	LEUKOTAPE® K 5 m x 5 cm - light blue
59015	72978-25	LEUKOTAPE® K 5 m x 5 cm - pink

### KINTAPE KINESIOLOGY TAPES

High quality Kinesiology tape conforms to all areas of the body. Provides firm support and compression, Ideal for treatment of muscular symptoms, stimulus to blood circulation and lymph and fascia diversion. Reduce pain improving athletic performance. Easy to tear and unwinds to the core. Individually packed in a plastic bag and cardboard box. - soft hypoallergenic cotton cloth, elasticity up to 160%

,			
GIMA code			
34745	Kinesiology tape 5 m x 5 cm - black	box of 1	
34746	Kinesiology tape 5 m x 5 cm - ceil blue	box of 1	
34747	Kinesiology tape 5 m x 5 cm - red	box of 1	
34749	Kinesiology tape 5 m x 5 cm - green	box of 1	
34750	Kinesiology tape 5 m x 5 cm - pink	box of 1	
34751	34751 Kinesiology tape 5 m x 5 cm - skin		
34752	Kinesiology tapes 5 m x 5 cm - mix colours	box of 6	
KÍNESIOLOGY PRO TAPES -			
thickness 0.32 mm			
34757	Kinesiology PRO tapes 5 m x 5 cm - skin	box of 1	

70% water proof (level 3) and sweat proof

- supersticky: up to 7 days, over 10 days for kinesiology PRO Kinesiology PRO: supersoft and quick drying



### **FABRIC SPORT TAPES**



Made in	l Italy	
GIMA code	WHITE ZINC OXIDE FABRIC TAPE NON ELASTIC ADHESIVE BANDAGE	Minimum order
34753	Tape 14 m x 2.5 cm - for finger	box of 48
34754	Tape 14 m x 3.8 cm - for wrist	box of 30
34755	Tape 14 m x 5 cm - for ankle	box of 24

### ELASTICATED TUBULAR NE

Surgifix

Elastic tubular net for the application of gauze and medication. Versatile, suitable for all parts of the body. The special structure of the material allows a stretching which holds without compressing. Made in Italy.

	•	
GIMA code	Range	Length under tension: 25 m
34701 34702 34703 34704 34705 34706 34707 34708 34709	1 2 3 4 5 6 7 8	1

### STRAPPAL® SPORT TAPE

### STRAPPAL® SPORT TAPE

Inelastic adhesive bandage (tape) indicated in traumatology to limit the joint movements.

High quality fabric made of inelastic viscose fibres coated with a strong adhesive mass. Hand tearable, Latex free. Multilanguage GB, FR, IT, ES, DE, PT, NI

iviaitiia	ngaage ab	, , , , , , , , , , , , , , , , , , , ,	
GIMA code	BSN code	STRAPPAL® SPORT TAPE	Minimum order
59051	71490-00	STRAPPAL® 10 m x 4 cm	box of 24
59052	71493-00	STRAPPAL® 10 m x 5 cm	box of 18



### COMPRILAN® COMPRESSIVE BANDAGES





### COMPRILAN® COMPRESSIVE **BANDAGES**

Short stretch compression bandage (90%) for phlebological and lymphological application. 100% cotton fabric (flesh colour). Stretched length 5 m. Washable and sterilizable. Latex-free.

GIMA code	BSN code	COMPRILAN® COMPRESSIVE BANDAGES	Minimum order
59150	01026-00	COMPRILAN® 5 m x 6 cm	box of 1
59151	01027-00	COMPRILAN® 5 m x 8 cm	box of 1
59152	01028-00	COMPRILAN® 5 m x 10 cm	box of 1
59153	01029-00	COMPRILAN® 5 m x 12 cm	box of 1

### ELASTIC COMPRESSION BANDAGES - LIGHT TO STRONG COMPRESSION

PREVI MEDICAL

33%

7%

160%

69%

25%

6%

250%



### PREVIBIELASTICA - medical prescription

- bandage - ideal for bandaging when support and strong, constant compression is required
- used in the treatment of varicose veins and postoperative patients
- its ability to stretch in any direction makes it ideal for bandaging joints.

Composition:

Extensibility



### PREVIFORTE

- medical prescription bandage
- compression bandage for phlebitis treatment - support bandage with strong, constant compression, ideal for varicose veins, for the
- prevention and cure of sport and work injuries. Suitable for distortions, light fractures and sprains.

TECHNICAL SPECIFICATIONS

PREVI BIELASTICA

19%

11%

160%



### **PREVINOVA**

- universal compression bandage
- protects and supports all types of medication - to fix medications, support light fractures, distorsions,

types of medication - to fix medications, for support and relief in case of sprains, sport and work injuries contusions and haematomas with medium compression. with medium-light compression. **ELASTIC COMPRESSION BANDAGES** 

**PREVIMEDICAL** 

bandage

- universal compression

- protects and supports all

COMPRESSIO

	PREVIBIE	LASTICA - strong compression	
34644	PreviBielastica	7 m x 8 cm	box of 10
34645	PreviBielastica	7 m x 10 cm	box of 10
	PREVIE	ORTE - strong compression	
34647	PreviForte	7 m x 8 cm	box of 10
34648	PreviForte	7 m x 10 cm	box of 10
PREVINOVA - medium compression			
34650	PreviNova	4.5 m x 6 cm	box of 10
	PreviNova		box of 10
34652	PreviNova	4.5 m x 10 cm	box of 10
PREVIMEDICAL - medium light compression			
34654	PreviMedical	5 m x 8 cm	box of 10
34655	PreviMedical	5 m x 10 cm	box of 10

individually packed, with clip

### CO-PLUS® BANDAGES

8%

170%



polyamide

polyurethane

longitudinal

BSN. Flexible cohesive bandage. Sticks only to itself, not on skin. Indications: support and compression in traumatology and phlebology. Longer than competitors (6.3 m stretched instead of 4.5 m).

Multilanguage box: GB, FR, IT, ES, DE, NL.

GIMA code	BSN code	CO-PLUS® BANDAGES	Minimum order
		CO-PLUS® 6.3 m x 7.5 cm - skin	box of 1
59183	72100-04	CO-PLUS® 6.3 m x 10 cm - skin	box of 1
59186	72102-03	CO-PLUS® 6.3 m x 7.5 cm - mix colours*	box of 24
59187	72102-02	CO-PLUS® 6.3 m x 10 cm - mix colours*	box of 18
Mix of bandages in 6 colours (blue, light blue, red, violet, neon green, neon pink)			

### **3M COBAN™** ELASTIC WRAP



GIMA code	3M code	3M COBAN™ SELF ADHERENT COHESIVE ELASTIC WRAP - LATEX	Minimum order
34923	1583	COBAN™ 7.5 cm x 2 to 4.57 m	box of 24
34924	1584	COBAN™ 10 cm x 2 to 4.57 m	box of 18

### ELASTOMULL® HAFT COHESIVE BANDAGES



### **ELASTOMULL® COHESIVE BANDAGES** Elastic retention bandage. It provides wound care splint retention and light support. Confortable non woven fabric (cotton, viscose and polyamide) coated with

syntethic latex. Stretched length 4 m.

•			
GIMA code	BSN code	ELASTOMULL® HAFT COHESIVE BANDAGES	Minimum order
59211	45471-00	Elastomull® Haft 4 m x 6 cm	box of 10
59212	45472-00	Elastomull® Haft 4 m x 8 cm	box of 10
59213	45473-00	Elastomull® Haft 4 m x 10 cm	box of 10
59214	45474-00	Elastomull® Haft 4 m x 12 cm	box of 10
59218	45477-00	Elastomull® Haft 20 m x 8 cm	box of 1
59219	45478-00	Flastomull® Haft 20 m x 10 cm	hox of 1

### **ELASTIC COHESIVE BANDAGES** COHESIVE BANDAGES



ideal for supporting light joint fractures. - this bandage does not require clips because perfectly adherent.

Extensibility: approx. 50%

TECHNICAL SPECIFICATIONS Composition: 42% cotton, 29% viscose, 29% polyamide, latex or latex free Width: 6 - 8 - 10 - 12 cm Length: streched length 4 m

GIMA code	ELASTIC COHESIVE BANDAGE	Minimum order
	Cohesive bandage 4 m x 6 cm	box of 10
	Cohesive bandage 4 m x 8 cm	box of 10
34659	Cohesive bandage 4 m x 10 cm	box of 10
34660	Cohesive bandage 4 m x 12 cm	box of 10
34661	Cohesive bandage 20 m x 6 cm	box of 1
34662	Cohesive bandage 20 m x 8 cm	box of 1
34663	Cohesive bandage 20 m x 10 cm	box of 1
GIMA	ELASTIC COHESIVE BANDAGE -	Minimum
code	LATEX FREE	order
59201	Cohesive bandage 4 m x 8 cm	box of 10
59202	Cohesive bandage 4 m x 10 cm	box of 10
59206	Cohesive bandage 20 m x 8 cm	box of 1


### **ELASTIC COHESIVE BANDAGES**

Cohesive bandage with instantaneous and lasting fixation.

It adheres only to itself and not to the skin, hair or clothing.

Doesn't slip, is air-permeable, with stretchability of approx

Comfortable, well tolerated



34712 Cohesive bandage size 4 m x 10 cm

34713 Cohesive bandage size 4 m x 12 cm

by skin, it adapts perfectly to part to be treated. Versatile to use, easy to apply, permits free movement. Made in Italy.				
GIMA code	COHESIVE BANDAGE	Minimum order		
	Cohesive bandage size 4 m x 6 cm Cohesive bandage size 4 m x 8 cm	box of 72 pcs box of 72 pcs		

### **ELASTIC COLOUR COHESIVE BANDAGES - EXTENSIBILITY 90%**

Cohesive bandages through microfine latex dots

- for fixing dressings

itself.

- ideal for supporting joint treating light fractures - this bandage does not require clips because it remains well-attached to

### TECHNICAL SPECIFICATIONS Composition: 42% cotton, 29% viscose,

box of 1

28% polyamide, 1% elastan and latex Width: 6 - 8 - 10 cm Length: streched length Length: streched length 4 m Extensibility: approx. 90%

	COHE	SIVE C	OLOUR	BANDA	AGE	
Size	Green	Blue	Red	Yellow	Colours*	Minimum order
4 m x 6 cm	-	34665	34666	-	34668	box of 10
4 m x 8 cm	34669	34670	34671	34672	34673	box of 10
4 m x 10 cm	34674	34675	34676	-	34678	box of 10
*Mix 2 bandage	s x 5 colo	urs (red, g	reen, blu	e, yellow,	white)	



### PREVITNT COHESIVE NON WOVEN ELASTIC BANDAGES

### PREVITNT NON WOVEN ELASTIC BANDAGES

59207 Cohesive bandage 20 m x 10 cm

For fixing dressings.

Ideal for supporting joints, treating light fractures

This bandage does not require clips because it remains well-attached to itself.

Particularly suitable for use on joints, for sports and veterinary use. Composition: 85% polypropylene - 15% spandex and latex. Extensibility: approx 100%.

COHESIVE COLOUR NON WOVEN BANDAGE					
Size	Blue	Red	Colours*	Minimum order	
4.5 m x 7.5 cm	34734	34735	34736	box of 10	
4.5 m x 10 cm	34738	34739	34740	box of 10	
*A div 2 handages y E cal-	sure lead aroon	blue vellerer e	leim)		



### TENSOPLAST® ELASTIC ADHESIVE BANDAGES



### TENSOPLAST® BANDAGES Elastic adhesive bandage. High quality elastic fabric, soft edges and porous adhesive mass. Yellow center line. It provides strong support and compression in traumato and phlebological diseas Stretched length 4.5 m. Multilanguage box: GB,

ES, DE, PT, GR, NL, SE.

ology se.		-	1	
FR, IT,				
		AST® BAN		
NSOPLA	4ST® 4.5	m x 5 cr	n	

code	code	TENSOPLAST® BANDAGES
59250	71545-00	TENSOPLAST® 4.5 m x 5 cm
59251	71546-00	TENSOPLAST® 4.5 m x 7.5 cm
59252	71547-00	TENSOPLAST® 4.5 m x 10 cm

### **GAUZE BANDAGES**

For fixing dressing and for absorption of exudates. 100% cotton wool. Latex free. Made in Europe



GIMA code	Threads	GAUZE BANDAGES - DISPOSABLE	Minimum order
34840	20	Gauze bandage 3.5 m x 5 cm	box of 12
34841	20	Gauze bandage 3.5 m x 7 cm	box of 10
34842	20	Gauze bandage 3.5 m x 10 cm	box of 6
34844	20	Gauze bandage 5 m x 5 cm	box of 100
34846	20	Gauze bandage 5 m x 7 cm	box of 100
34847	20	Gauze bandage 5 m x 10 cm	box of 100

### FIXATION ELASTIC BANDAGES

For fixing dressing, for support and light compression. Its characteristic crepe like touch enables the bandage to remain well-attached to itself. Well-tolerated by the skin, it ensures a high level of breathing. Washable at 60°C Made of 99% cotton 1% lycra.

Made in Eu

GIMA code	PREVICREPE S ELASTICATED BAN		Minimum order
34725	Previcrepe bandage 4	m x 5 cm	box of 10
34726	Previcrepe bandage 4	m x 7 cm	box of 10
34727	Previcrepe bandage 4	m x 10 cm	box of 10
34728	Previcrepe bandage 4	m x 15 cm	box of 10

### ELASTICATED BANDAGES

Elasticated non adhesive bandages for containment, individually cellophane wrapped, in a box. Non adhesive bandages are made of 65% cotton and 35% polyamide fibre. Provided with clasp. Made in Italy



GIMA code	ELASTICATED BA	NDAGES	Minimum order
34720	Bandage size 4.5 m x 5	5 cm	box of 20 pcs
34721	Bandage size 4.5 m x 7	7 cm	box of 20 pcs
34722	Bandage size 4.5 m x 1		box of 20 pcs

### ELASTICATED ADHESIVE BANDAGES

Elasticated adhesive bandages for containment individually cellophane wrapped, in a box. Adhesive bandages are made of 99.7% cotton and 0.3% polyamide. Made in Switzerland



GIMA code	ELASTICATED ADHESIVE BANDAGES
	Adhesive bandage size 4.5 m x 6 cm
	Adhesive bandage size 4.5 m x 8 cm
34732	Adhesive bandage size 4.5 m x 10 cm

### **HYPOR-PLAST**

Extensible adhesive bandage White extensible non-woven 100% polyester bandage roll. Extremely breathable and conformable. Hypoallergenic, reliable skin friendly acrylic adhesive.

Indications: suitable to fix dressings and other medical devices.

GIMA code	BANDAGE
34863 34864 34865	roll m 10 x 5 cm roll m 10 x 10 cm roll m 10 x 15 cm

### **EMOCONTROL**

### • 34782 EMOCONTROL

Emocontrol is an easy, quick and effective elastic bandage for injuries and small haemorrhages. Length 4.5 m, width 10 cm with a 10x10 cm pad and 2 clips. English and Italian instructions. Made in Italy



### ZINC-OINTMENT BANDAGE



• 34715 ZINC-OINTMENT ELASTIC BANDAGE 5 m x 10 cm • 34717 ZINC-OINTMENT ELASTIC BANDAGE 10 m x 10 cm Homogeneously soaked in zinc ointment ready for use and

stretchable (in length).

Each band is packed in sealed aluminium foil bag and cardboard box. Made in Italy.

### TEXTILE COMPOSITION

Viscose 71% - Polyamide 29% - Soaked with zinc oxide, gelatine, glycerin. propyl-hydroxybenzoate, methyl-hydroxybenzoate, water. Elasticity: 60% (±10%)

### PREVIZINC A and E



Previzinc E: 54% polyamide, 46% viscose zinc oxide paste

Previzinc "A" and "E" are banda ges impregnated with zinc oxide paste indicated in the treatment of thrombophlebitis, oedema, chronic venous insufficiency and in the healing phase and follow up care of fractures, sprains and

GIMA code	PREVIZINC "A" INELASTIC BANDAGES	Minimum order		
34714	Previzinc "A" 6 m x 8 cm	box of 10		
34716	Previzinc "A" 5 m x 10 cm	box of 10		
	PREVIZINC "E" ELASTIC BANDAGES			
34718	Previzinc "E" 6 m x 8 cm	box of 10		
34719	Previzinc "E" 5 m x 10 cm	box of 10		
TEXTILE COMPOSITION				
Previzinc A: 100% cotton zinc oxide paste				

### PLATRIX® HIGH QUALITY PLASTER OF PARIS BANDAGES





PLATRIX® PLASTER OF PARIS High quality plaster of Paris bandages. Économic thanks to the high strength and the minimal plaster loss. Multilanguage box: GB, FR, IT, ES, DE, NL.

GIMA code	BSN code	PLATRIX® PLASTER OF PARIS	Minimum order
34686	71996 - 05	Platrix® 2 m x 15 cm	box of 40
34688	71996 - 14	Platrix® 3 m x 20 cm	box of 20
34691	71996 - 28	Platrix® 4 m x 20 cm	box of 20

### P.O.P. (PLASTER OF PARIS) BANDAGES

### PLASTER OF PARIS BANDAGES

Absorbent 100% cotton gauze 170 threads/cm<sup>2</sup> complying with British Pharmacopoeia requirements.

GIMA code CELLONIT - PLASTER OF PARIS BANDAGE		Minimum order
	P.O.P. Bandage 2 m x 10 cm	box of 100
34693	P.O.P. Bandage 2 m x 15 cm	box of 50
34694	P.O.P. Bandage 2 m x 20 cm	box of 50
34695	P.O.P. Bandage 2.7 m x 10 cm	box of 80
34696	P.O.P. Bandage 2.7 m x 15 cm	box of 40
34697	P.O.P. Bandage 2.7 m x 20 cm	box of 40




### OSCILLATING PLASTER SAW



- 59100 SG 600 PLASTER SAW
- 59101 SAW BLADE Ø 50 mm
- 59102 SAW BLADE Ø 65 mm

German made professional plaster saw, ideal for cutting plasters and synthetic bandages. Adjustable oscillating speed.

### STANDARD ACCESSORIES Saw blade Ø 50 mm Saw blade Ø 65 mm One pair of wrenches Locking screw Fixation ring User manual: GB, IT, ES (DE on request)



### **TECHNICAL SPECIFICATIONS**

Voltage: Power: Strokes Length without cord: Weight with/without cable Cord length: IP code:

220-240 V, 50-60 Hz 250 W 12,000 - 21,000 oscillations/min 340 mm 1.3/1.7 Kg 68-82 dB 4.5 m

IP2X

### COTTON GAUZE SWABS



### GAUZE SWABS: COTTON, NON-WOVEN

CIMA

Gauze swabs pure cotton, 20 threads, yarn 40/40, folded and hemmed without X-ray thread, non-sterile.

Non woven swabs, 30% polyester, 70% viscose 30 g/m² folded and hemmed without X-ray thread. Carton of 10 packs of 100.

Cotton	Plies	Non Woven	Plies	GAUZE SWABS NON STERILE	Minimum order		
35005	16	35010	4	Size 5x5 cm	box of 1,000 (10 packs of 100)		
35006	12	35011	4	Size 7.5x7.5 cm	box of 1,000 (10 packs of 100)		
35007	16	35012	4	Size 10x10 cm	box of 1,000 (10 packs of 100)		

### **COTTON GAUZE SWABS - STERILE**

Cotton gauze pad 30x30 cm - 1 kg



3476	34763	34760
Threads	COTTON GAUZE SWABS - STERILE Made in Italy	Minimum order
12/8	Size 10x10 cm	carton of 150 bags of 25 pcs
12/8	Size 15x15 cm	carton of 100 bags of 25 pcs
12/8	Size 20x20 cm	carton of 100 bags of 25 pcs
12/8	Size 18x40 cm	carton of 50 box of 12 pcs
12/0	Sizo 26v40 cm	carton of EO boy of 12 pcc

### NON WOVEN GAUZE SWABS - STERILE



### carton of 100 bags of 25 pcs carton of 30 box of 12 pcs Size 10x10 cm Size 18x40 cm 35028 Size 36x40 cm carton of 30 box of 12 pcs

### **COTTON GAUZE SWABS - STERILE**



34791

14079. Each dispenser contains sterile packs of 5 gauze swabs. **( €** 0373

35038

100% cotton gauze,

17 threads / 59 cm<sup>2</sup>,

1 pack

GIMA code	Plies	Threads	GAUZE SWABS - STERILE	Minimum order
35035	12	17	5x5 cm	dispenser of 350 (70 packs of 5 swabs)
35036	12	17	5x5 cm - X-ray	dispenser of 350 (70 packs of 5 swabs)
35037	12	17	7.5x7.5 cm	dispenser of 250 (50 packs of 5 swabs)
35038	12	17	7.5x7.5 cm - X-ray	dispenser of 250 (50 packs of 5 swabs)
35039	12	17	10x10 cm	dispenser of 150 (30 packs of 5 swabs)
35040	12	17	10x10 cm - X-ray	dispenser of 150 (30 packs of 5 swabs)

### COTTON GAUZE BALLS - STERILE **( €**0373 100% cotton gauze, 20



threads / 59 cm<sup>2</sup> according to European Pharmacopoeia and EN 14079. Each dispenser contains sterile

packs of 5 gauze balls.

GIMA



1A le	Threads	GAUZE BALLS - STERILE	Minimum order
45	20	Gauze balls Ø 30 mm	dispenser of 250 (50 pack of 5)
46	20	Gauze balls Ø 40 mm	dispenser of 200 (40 pack of 5)
47	20	Gauze balls Ø 50 mm	dispenser of 300 (60 pack of 5)

### **COTTON GAUZE BALLS**



### COTTON GAUZE BALLS

Pure hydrophilic cotton gauze balls 20 threads, yarn 40/40, without X-ray thread, non sterile package. Carton of 10 bags of 100 balls.



Cotton	Non Woven	GAUZE ROUND BALLS	Open size	Minimum order
35015	35020	Gauze ball Ø 15 mm	11x11 cm	1,000 pcs (10 bags of 100)
35016	35021	Gauze ball Ø 25 mm	12x15 cm	1,000 pcs (10 bags of 100)
35017	35022	Gauze ball Ø 50 mm	30x40 cm	1,000 pcs (10 bags of 100)

### GAUZE LAPAROTOMIC SPONGE | 100% COTTON WOOL


100% cotton gauze according to the European Pharmacopoeia and EN 14079, non sterile X-ray detectable apx 60% Barium Sulphate.

GIMA code	Plies	Threads	LAPAROTOMIC SPONGE GAUZE	Minimum order
34775	4	17	Size 20x20 cm	box of 100
34776	4	17	Size 30x30 cm	box of 100
34777	4	17	Size 40x40 cm	box of 100
34778	4	17	Size 50x50 cm	box of 100

### 34832 soft Cotone idrofile CE 34837 GIMA **COTTON WOOL** 34837 Cotton wool 100 g - box of 50 packs **34832** Cotton wool 250 g - box of 20 packs **34838** Cotton wool 1000 g - box of 10 packs

### **DENTAL COTTON ROLLS**

• 35000 COTTON ROLLS 1x3.8 cm 100% cotton interior, soft, pliable, non-linting, non-irritating, highly absorbent up to 6 times their weight. Will not adhere to mucous membranes, maintains shape better when wet, non sterile.







### STERILE ABSORBENT PADS

			GB, FR, IT, ES, PT, DE, NL, SE
Ideal for situations where a great capacity of absorption	GIMA code	STERILE ABSORBENT PADS	Minimum order
is needed, such as blendings	59402	10x10 cm	box of 60
and chronic wounds. Made of	59403	10x20 cm	box of 30
cellulose pulp, white and blue		20x20 cm	box of 30
polypropilene and tissue paper.	59405	20x40 cm	box of 25



100% cotton gauze rolls with 20 threads sg cm according to European Pharmacopoeia and EN 14079. X-Ray detectable thread (approx. 60% barium sulphat) 80 cm width, folded 8 to

10 cm ply. Multilanguage box: GB, FR, IT, ES, PT, DE, NL, SE. **GAUZE ROLLS** GIMA code 80 cm x 1 m 59410 10 cm x 1 m 20 59411 80 cm x 2 m 10 cm x 2 m 20 10 cm x 10 m

### 100% COTTON GAUZE ROLLS | 100% COTTON RIBBON GAUZE

- Wound	care durin	g surgery	
		Mul	tilanguage box: GB, FR, IT, ES,
M.	1		PT, DE, NL, SE
GIMA	GIMA	100% COTTON RIBBON GAUZE	Minimum
code	code	weight 33 g/sq. m	order
-	X-Ray*	22 threads/sq. m	
59420	59430	5 m x 1.25 cm	box of 24
59421	59431	5 m x 2.5 cm	box of 12
59422	59432	5 m x 5 cm	box of 12
59423	59433	5 m x 7.5 cm	box of 8
59424	59434	5 m x 10 cm	box of 6
59440	-	5 m x 1.25 cm - sterile	box of 60
59441	-	5 m x 2.5 cm - sterile	box of 30
59442	-	5 m x 5 cm - sterile	box of 26
*V Paur ar	nrov 600	harium sulphat contents	

### 3M RESTON<sup>™</sup> FOAM PAD





Self-adhering open cell foam designed to protect skin from splints, casts and prostheses.

Not intended to be used as a pressure reducing device. It can also be used as a padding for beds and chairs. Can be cut, layered and shaped.

GIMA code	3M code	3M RESTON™ FOAM PAD	Minimum order
34920	1560	RESTON™ 30x20x1.1 cm	box of 10
34921	1561	RESTON™ 30x20x2.5 cm	box of 5
34922	1563	RESTON™ ROLL 10cmx5mx4mm	1 roll

### ADHESIVE DRESSING



code	DRESSING HYPOALLERGENIC	order	
34860	Sterile adhesive dressing 5x7 cm	box of 100 pcs	
34861	Sterile adhesive dressing 8x10 cm	box of 50 pcs	
34862	Sterile adhesive dressing 8x15 cm	box of 50 pcs	

### STERILE ADHESIVE DRESSINGS



• 34848 OCULAR ADHESIVE DRESSING

Sterile, extremely absorbent ocular dressing on hypoallergenic permeable adhesive backing.

Suitable for a safe and comfortable eye medication. Size 6.5x9.5 cm - box of 10 pcs

 34845 STERILE ADHESIVE DEVICE for cannula fixation Size 8x5.8 cm - box of 50 pcs

### ADHESIVE DRESSINGS



GIMA code	STERILE HYPOALLERGENIC ADHESIVE DRESSING WITH CENTRAL NON-WOUND-STICKING ABSORBANT PAD	Minimum order
34850 34851 34852 34853 34854	Sterile adh. dressing 7.2x5 cm Sterile adh. dressing 10x10 cm Sterile adh. dressing 10x15 cm Sterile adh. dressing 10x8 cm Sterile adh. dressing 10x15 cm	box of 8 pcs box of 6 pcs box of 4 pcs box of 50 pcs box of 50 pcs
GIMA code	HYPOALLERGENIC EXTENSIBLE NON WOVEN ADHESIVE DRESSING TO BE CUT, WITH HIGHLY ABSORBENT CENTRAL WOUND PAD	Minimum order
34855 34856	Size 1 m x 6 cm Size 5 m x 6 cm Recommended for sensitive skin	1 roll 1 roll

### **BWT ADHESIVE DRESSING**



NON-WOUND-STICKING ABSORBANT PAD code Sterile adh. BWT dressing 8x6 cm - box of 50 pcs 34857 Sterile adh. BWT dressing 10x10 cm - box of 50 pcs Sterile adh. BWT dressing 10x15 cm - box of 50 pcs

### SILK PLASTER ROLL

• 34787 SILK PLASTER ROLL 10 m x 2.5 cm - box of 12 • 34788 SILK PLASTER ROLL 10 m x 5 cm - box of 6 Silk surgical tape, white colour.


### **PLASTER ROLLS**



Each roll is supplied with a plastic roll cover except code 34798

PLASTER ROLLS - MADE IN ITALY								
Skintone fabric	Hypoallergenic Non woven	Size	Minimum order					
34803	34804	5 m x 2.5 cm	box of 12 rolls					
-	34798	9.14 m x 2.5 cm	box of 12 rolls					
34806	34807	5 m x 5 cm	box of 6 rolls					
34799	34799 Shop Display: for showing up to 88 boxes (32 x 25 xh 63 mm)							

### NON WOVEN PAPER TAPE ROLL



code	HYPOALLERGENIC ADHESIVE	order
34795	Tape roll h 25 mm x 5 m	box of 12 pcs
34796	Tape roll h 25 mm x 9.14 m	box of 12 pcs
34797	Tape roll h 50 mm x 9.14 m	box of 6 pcs

### 3M TAPES: MICROPORE™, MEDIPORE™, DURAPORE™, TRANSPORE™





A latex-free, hypoallergenic paper tape that is gentle to the skin and doesn't leave adhe sive upon removal. Highly breathable and economical. Can be used on wet skin

GIMA code	3M code	3M MICROPORE™ PAPER TAPES	Minimum order
34904	1530-0	MICROPORE™ - h 12.5 mm x 9.14 m	box of 24 rolls
34905	1530-1	MICROPORE™ - h 25 mm x 9.14 m	box of 12 rolls
34906	1530-2	MICROPORE™ - h 51 mm x 9.14 m	box of 6 rolls
34907	1530-3	MICROPORE™ - h 76 mm x 9.14 m	box of 4 rolls



code



A silk tape with a latex-free hvnoallergenic adhesive that offers high strength and adhesion to skin.







GIMA code	3M code	3M MEDIPORE™ SOFT CLOTH TAPES and 3M MEDIPORE™ + PAD	Minimum order
34930	2991-1	MEDIPORE™ - h 50 mm x 10 m	box of 1 roll
34931	2991-2	MEDIPORE™ - h 100 mm x 10 m	box of 1 roll
34932	2991-3	MEDIPORE™ - h 150 mm x 10 m	box of 1 roll
34933	2991-4	MEDIPORE™ - h 200 mm x 10 m	box of 1 roll
34936	3562E	MEDIPORE™ + PAD - 5x7 cm	box of 25 pcs
34937	3566E	MEDIPORE™ + PAD - 10x10 cm	box of 25 pcs
34938	3569E	MEDIPORE™ + PAD - 10x15 cm	box of 25 pcs
34939	3570E	MEDIPORE™ + PAD - 10x20 cm	





Latex-rree, hypoaliergenic, transparent and perioral ted plastic tape that offers strong adhesion. Elastic and water-resistant.

code	code	3M TRANSPORE™ PLASTIC TAPES	order
34941	1527-1	TRANSPORE™ - h 25 mm x 9.14 m	box of 12 rolls
34942	1527-2	TRANSPORE™ - h 51 mm x 9.14 m	box of 6 rolls

### BSN TAPES: LEUKOPOR®, LEUKOPLAST®, HYPAFIX®



The gentle tape for highly sensitive skin. For the fixation of dressings of all types and sizes. Non woven fabric and skin friendly adhesive mass

GIMA code	BSN code	LEUKOPOR®	Minimum order
		LEUKOPOR® 25 mm x 9.2 m LEUKOPOR® 50 mm x 9.2 m	box of 12 rolls box of 6 rolls
	Leukov		



	GIMA code	BSN code	LEUKOPLAST®	Minimum order	ľ
			LEUKOPLAST® 25 mm x 5 m	box of 12 rolls	
	59505	01534-00	LEUKOPLAST® 50 mm x 5 m	box of 6 rolls	





1	code	BSN code	HYPAFIX®	Minimum order
	59510	71443-01	HYPAFIX® 50 mm x 10 m	box of 1
	59511	71443-02	HYPAFIX® 100 mm x 10 m	box of 1
	59512	71443-03	HYPAFIX® 150 mm x 10 m	box of 1
	59513	71443-04	HYPAFIX® 200 mm x 10 m	box of 1

### 3M STERI-STRIP™ - SKIN CLOSURE STRIPS

Adhesive skin closures made of non-woven backing coated with a pressure-sensitive hypoallergenic adhesive. Sterile, breathable and comfortable to wear.



REINFORCED STERI-STRIP™ With polyester reinforcing filaments for higher tensile strength, reduced infection and scarring risk and better cosmetic outcom







body movemen or edema Mostly suited for

speciál applications (e.g. joints or plastic surge Skin tone

GIMA	3M	3M ELASTIC STERI-STRIP™ -	Minimum
code	code	sterile	order
		STERI-STRIP™ - 3x75 mm	50 bags of 5 strips
34988	E4541	STERI-STRIP™ - 6x75 mm	50 bags of 3 strips
34989	E4542	STERI-STRIP™ - 6x38 mm	50 bags of 6 strips
34990	E4546	STERI-STRIP™ - 6x100 mm	50 bags of 10 strip
34991	E4549	STERI-STRIP™ - 12x50 mm	50 bags of 6 strips
34992	E4547	STERI-STRIP™ - 12x100 mm	50 bags of 6 strips
34993	E4548	STERI-STRIP™ - 25x125 mm	25 bags of 4 strips

### 34914 R1548 STERI-STRIP™ - 25x125 mm **SUTURE STRIPS**

code code sterile - skin closure 34909 R1540 STERI-STRIP™ - 3x75 mm

34910 R1541 STERI-STRIP™ - 6x75 mm

34908 R1542 STERI-STRIP™ - 6x38 mm

34911 R1546 STERI-STRIP™ - 6x100 mm

**34913** R1549 STERI-STRIP™ - 12x50 mm

34912 R1547 STERI-STRIP™ - 12x100 mm

• 34997 STERILE SUTURE STRIPS - box of 8 Sterile adhesive strips for cut and wound suture.

Cut to measure. Dermatologically tested. It contains 5 small strips (3x75 mm) and 3 medium strips (6.4x80 mm). Multilanguage box: GB, FR, IT, ES, DE



50 bags of 5 strips

50 bags of 3 strips

50 bags of 6 strips

50 bags of 10 strips

50 bags of 6 strips

50 bags of 6 strips


25 bags of 4 strips

### SOOTHING PATCH

### • 34830 PREVIDOL SOOTHING PATCH 9x14 cm - pouch of 5

Previdol is a Medical Device patch adjuvant in the treatment of pains in the joints and the muscular-skeletal system. It acts on the affected part, keeping the skin protected and helping to give relief in presence of pain. To improve the cutaneous tolerability of the

patch, some plant extracts like Arnica Montana, Devil's Claw and Boswellia were inserted, as well as some essential oils of Mint and Menthol to give a pleasant fragrance. Box: GB, IT.



A complete range of barrier products to protect the skin from body fluids and friction. Cavilon™ products create on the skin a highly breathable, long lasting transparent coating to prevent maceration and trauma. Alcohol-free, hypoallergenic and non irritating, can be used on broken skin and under any tapes and dressing

asea on broken skin and ander any tapes and aressing			,-
GIMA code	Minimum order		
34974	3346E	Cavilon™ no sting barrier film - spray 28 ml	box of 12
34973	3346P	Cavilon™ no sting barrier film - spray 28 ml	box of 1
34975	3392G	Cavilon™ durable barrier cream 92 g	1 dispenser
34976	9274	Cavilon™ continence care wipes	12 boxes of 8

3M CAVILON™ NO STING BARRIER FILM Up to 72 hours of protection for peri-wound and peri-ostomy skin



3M CAVILON™ DURABLE BARRIER CREAM Zinc-oxide free barrier cream for continence care. Apply twice a day.

3M CAVILON™ CONTINENCE CARE WIPES «All in 1» wipes for cleansing, moisturizing and protecting the skin



34976

### ADHESIVE PLASTERS AND SPRAY PLASTER DISPENSER



34809 Water resistant - 19x72 mm

34814 Water resistant - 4 mixed sizes

34817 Sensitive skin - 5 mixed sizes

34823 Spray plaster - bottle of 30 ml



HYPOALLERGENIC

ADHESIVE PLASTERS





2,000 (100 boxes of 20)

2.000 (100 boxes of 20)

3,200 (80 boxes of 40)

box of 12



- 34826 PLASTER DISPENSER with 2 refills (one each type)
- 34827 REFILL 42 TEXTILE PLASTERS 19x72 mm box of 6 34828 REFILL 38 TEXTILE PLASTERS 25x72 mm - box of 6

Dispenser for adhesive plasters ready for use. It allows operator to extract plaster with one hand and apply directly on the wound. Transparent cover protects plaster and shows residual quantities. Lockable and with fixing wall kit included.

### I 3M TEGADERM™ DRESSINGS





**TEGADERM** Transparent, sterile waterproof dressing. Highly breathable

Frame style for easy application also available in non-sterile role

GIMA code	3M code	3M TEGADERM™ FILM	Minimum order
34900	1624W	TEGADERM™ - 6x7 cm - sterile	box of 100 pcs.
34901	1626W	TEGADERM™ - 10x12 cm - sterile	box of 50 pcs.
34902	1627	TEGADERM™ - 10x25 cm - sterile	box of 20 pcs.
34903	1628	TEGADERM™ - 15x20 cm - sterile	box of 10 pcs.
34899	16004	TEGADERM™ - 10 cmx10 m non sterile	1 roll





### Transparent, sterile waterproof dressing. Highly breathable.

Frame style for easy application. With a non-adherent absorbent PAD. Ideal for surgical wounds.


GIMA code	3M code	3M TEGADERM™ PAD	Minimum order
34895	3582	TEGADERM™ + PAD 5x7.2 cm - sterile	box of 50 pcs.
34896	3586	TEGADERM™ + PAD 9x10 cm - sterile	box of 25 pcs.
34897		TEGADERM™ + PAD 9x15 cm - sterile	
34898	3591	TEGADERM™ + PAD 9x25 cm - sterile	box of 25 pcs.

### 3M VASCULAR ACCESS SOLUTIONS - TEGADERM™IV

A complete range of sterile, waterproof, highly-breathable trasparent film dressings to protect IV sites from water, virus and bacteria. With antifriction backing and reinforced non-woven borders for longer wearing time and minimized catheter dislodgement risk.







cost-effe	<b>3M</b>		
GIMA	3M	3M TEGADERM™IV - STERILE	Minimum
code	code		order
34945		7x8.5 cm - for peripheral lines	box of 100
34946		8.5x10.5 cm - for central lines	box of 50





A reinforced, 100% waterproof, advanced solution for better securement and longer

ı	GIMA code	3M code	3M TEGADERM™IV ADVANCED - STERILE	Minimum order
)	34947	1683	6.5x7 cm for peripheral lines	box of 100
	34948	1685	8.5x11.5 cm for central lines	box of 50

### 3M SOLUTIONS FOR CHRONIC WOUNDS





TEGADERM™ HYDROCOLLOID

Sterile hydrocolloid dressing for low to moderate draining wounds Also available in sacral shape with highly breathable waterproof border

GIMA	3M	3M TEGADERM™ HYDROCOLLOID	Minimum
code	code		order
34968	90002	HYDROCOLLOID™ 10x10 cm square	box of 5
34969	90007	HYDROCOLLOID™ 16x17 cm sacral	box of 6





### TEGADERM™ ALGINATE AG

High integrity, gel forming alginate Antimicrobial, highly absorbent wound dressing for moderate to heavily exuding dressing with calcium alginate, carbowounds. Compact and confortable. xymethyl cellulose and ionic silver complex. To prevent and treat wound infections.

GIMA	3M	3M TEGADERM™ ALGINATE	Minimum
code	code	and ALGINATE AG	order
		TEGADERM™ ALGINATE - 10x10 cm	box of 10








### TEGADERM™ HIGH PERFORMANCE FOAM

Sterile, multi-layer foam dressing that combines high absorbency with high breathability to reduce the risk of wound maceration. Well suited for changing levels of exudate to maintain moisture balance for optimal wound healing. Highly breathable and waterproof also available in heel/elbow shape with adhesive border and simplified application system

GIMA code	3M code	3M TEGADERM™ FOAM - non adhesive or adhesive dressing	Minimum order
		TEGADERM™ FOAM - 10x10 cm TEGADERM™ FOAM - 9x9 cm	box of 10 box of 10
		for tracheostomy	
34957	90619	TEGADERM™ FOAM ADHESIVE	box of 5
		for heel and elbow - 14x14 cm	

### TEGADERM™ HYDROGEL

Preservative-free hydrogel wound filler, easy to apply. Formulated to help provide a moist wound healing environment



### BURNFREE® - BURN CARE PRODUCTS



A complete range of burn care products with superior benefits: - dissipates heat on contact

- cools the burn site, relieves pain, calms the burn victim, helps stop the burn process
- covers the burn, helps to prevent contamination
- accommodates swelling or the need to flex joints thanks to elastic texture

### Sterile burn and wounds dressings

Made of a soft open-cell, non-adherent, inert foam, saturated with Burnfree® gel, does not leave residues imbedded in the wound. Pain relieving gel

Ideal for all minor burns (including sunburns), cuts and abrasions, available in bottle or single use dose 3.5 q. Without lidocaine, which makes it suitable for children.

GIMA code	BURNFREE® PRODUCTS
34869	Burn Dressing - 5x5 cm - box of 120 pcs
34870	Burn Dressing - 5x15 cm - box of 10 pcs
34871	Burn Dressing - 10x10 cm - box of 10 pcs
34872	Burn Dressing - 20x20 cm - box of 5 pcs
	Burn Dressing - 30x30 cm - box of 20 pcs
	Pain Relieving Gel - bottle 120 ml
34883	Pain Relieving Gel - 3.5 g sachets - box of 20 pcs
34882	Pain Relieving Gel - 3.5 g sachets - box of 1,000 pcs
34878	Burn Kit (2 sterile dressing 5x15 cm and 2 10x10 cm,
	1 gel bottle 120 ml, 20 gel sachets 3.5g and 2 rollers gauzes)

### HYPOTHERMIC BLANKET

### • 34086 HYPOTHERMIC BLANKET

Reflects and retains over 80% of radiated body heat to keep a person warm and protected even at subzero temperature. Waterproof, reusable, wind proof, lightweight.



### ISOTHERMIC COVER

### • 34085 EMERGENCY COVER

TNT

**( (** 0476

Suitable for protection against cold and heat. Silver side in keeps the warmth of the body, gold side out reflects sunbeams.



PE

34111

# BURNFREE® - FIRE BLANKET



**34879** 91x76 cm 2.3 kg Fire resistant are a protective 34880 183x152 cm 6.9 kg - 15 lbs shield for a person trapped 34881 244x152 cm 10.9 kg



• 34087 FIRE RETARDANT BLANKET Made in glass fibre. Can be used to extinguish small fires Size: 150x180 cm

### INSTANT ICE: SPRAY OR BAG IN THT OR PE

34112

• 34110 INSTANT ICE - TNT 14x18 cm bag (non woven fabric) • 34111 INSTANT ICE - PE 14x18 cm bag (polyethylene)

minimum order: pack of 25 bags

34087

Icy-pack "instant ice" is recommended for cryotherapy. Excellent in case of traumas to soothe the pain and to prevent haematomas, swellings, etc.

### Easy and quick to use anywhere and anytime.

Press the bag to break the inner bubble and shake to mix contents. The blend you obtain drops temperature of the pack down. Activates at -6°C, reaches 0°C in 30 minutes (at environment temperature of 20 °C).

### • 34112 SPRAY INSTANT ICE - bottle 400 ml

Ecological, useful for small bruises, haematomas or trauma, in first aid or sport applications. Spray on the injured area at 20 cm distance. (see the reference temperature chart). Content: Ammonium nitrate + water.



346

### ANTIBACTERIAL HAND CLEANING GEL



ANTIBACTERIAL HAND CLEANING GEL

Antibacterial hand cleaning gel, cleans the hands and prevents the settlement of bacteria.

It is effective against bacteria, virus, fungi.

No need of water. Gima range includes 4 sizes and 4 different flavours (neutral transparent, apple, strawberry, lemon).

GIMA code	ANTIBACTERIAL HAND CLEANING GEL	minimum order
36580	Antibacterial gel 85 ml tube - transparent	box of 48
36581	Antibacterial gel 85 ml tube - green - apple	box of 48
	Antibacterial gel 85 ml tube - red - strawberry	box of 48
	Antibacterial gel 85 ml tube - yellow - lemon	box of 48
	Antibacterial gel 500 ml bottle* - transparent	box of 15
	Antibacterial gel 500 ml bottle* - yellow - lemon	box of 15
	Antibacterial gel 1 l bottle* - transparent	box of 12
	Antibacterial gel 5 l bag - transparent	box of 4
33283	Dispenser pump for 36597	1
*Each bott	le includes dispenser pump	11 - 11

### MULTIUSI GEL

- 36646 MULTIUSI GEL 50 ml box of 24 tubes • 36647 MULTIUSI GEL - 75 ml - box of 24 tubes
- 36645 MULTIUSI GEL 65 ml spray box of 36 pcs.
- 36642 MULTIUSI GEL 150 ml box of 24 pcs. 36644
- 36644 MULTIUSI GEL 1000 ml\*

• 36692 DISPENSER PUMP - for 36644

Cleanser hygienic for hands without water. Ready-to-use product, which contains 62% ethyl alcohol for a rapid and effective hands disinfection. It has been studied to sanitize and clean hands without using water.

It dries fast and leaves hands soft and fresh. Its disinfecting power is combined with an effective skin-protecting action, it guarantees hygienic protection in few seconds.

Made in Italy.

only 2 pieces come

with dispenser pump



MULTIUSI GEL

36645

MYA

## SURGERY DISINFECTANT

- 36632 NEO STERIXIDINA SOAP 1 I
- 36690 DISPENSER PUMP

Recommended for preparation of hands before surgical intervention and for complete washing of patients. Direct action towards bacteria Gram<sup>+</sup>, Gram<sup>-</sup> Made in Italy.



CHEMICAL COMPOSITION

100 a contains: Chlorhexidine dialuconate 4 a - Isopropyl alcohol 4 g - Coformulants - Depurated water as needed for

Italian Health Ministry registration 18980

### MEDICAL SOAP

- 36629 MEDICAL SOAP 0.5 I box of 12
- 36630 MEDICAL SOAP 1 I 36690 DISPENSER PUMP

Antiseptic liquid for disinfection of skin and hands. It is studied for people who need frequent washing as surgeons, medical and hospital attendants also before surgical operations. 2 dispenser pump every 12 bottles

Instruction: GB, IT. Made in Italy.

Italian Health Ministry registration 19570



1

36629

### BARRIER CREAM - HANDS PROTECTION

### • 36578 BARRIER CREAM - 500 ml

White barrier cream, enriched with vitamins and ingredients which protect the skin from everyday risks. It acts as an invisible barrier that allows regular perspiration and prevents from irritation,

pricking, redness, cracking and from contact with liquids such as detergents, greases and oils. Waterproof: its film barrier resists even after several washing with water.

Can be used many times during the day. The cream is also ideal to avoid skin's maceration due to the use of gloves. For professional use. Made in Italy.

36578

### DENTAL PROTECTION

### • 36650 GERMOXID MOUTHWASH

### 1 I with chlorhexidine

Specifically formulated to guarantee the highest hygienic standards and oral cavity disinfection. Chlorhexidine is the most widely used and effective germicidal agent and acts against Gram<sup>+</sup> and Gram bacteria, giving an overall anti-plaque and anti-gingivitis action.

Germoxid with its anti-plaque action guarantees efficient and long-lasting protection up to 12 hours

Its alcohol-free formula assures that neither gum irritation nor a burning sensation will be felt. It contains Aloe Vera in its formula: this is a particularly suitable extract for oral hygiene with high cicatrizing power. Made in Italy.

36650

### NOVALCOL SKIN DISINFECTANT

- 36609 NOVALCOL 250 ml box of 12 bottles
- 36611 NOVALCOL 1 I

36613 NOVALCOL - 3 I

Novalcol must be used pure before and after the injection, or in the preoperative cleaning of the patient (or for those confined to bed).

Novalcol is non irritant and non inflammable. It does


not stain or burn. Efficient against gram+, gram-. Instructions on the bottle in GB. IT.

### FLOW PACK WIPES

### • 36627 FLOW PACK 20 WIPES

Disinfectant detergent perfumed wipes for hands e un'igiene sicura and body disinfection. Active against bacteria to guarantee hygiene and total protection. Suitable to fight against effects of perspiration, eliminating bacteria that cause bad smells. Good for children and in case of insects bites. Ready to use, they do not stain and do not grease.

Minimum order: 1 display of 16 flow pack with 20 wipes



### HYDROGEN PEROXIDE

• 36604 OXYGENATED WATER (Hydrogen peroxide) - 250 ml - box of 12 • 36606 OXYGENATED WATER (Hydrogen peroxide) - 1 l

Hydrogen peroxide (3% diluted solution) 10 volumes. Colourless, odourless.

100% biodegradable. Made in Italy

### ALCOHOL SWABS/PADS

### • 36601 OUICKPAD DISPENSER

Fleece pads saturated with 70% Isopropyl Alcohol. The tight fitting lid prevents

evaporations Size 50x50x80 mm contains 150 pads, size: 44x44 mm.

U.S. and International Patents FDA Reg. #8010920

50 ALCOHOL SWAB

### CHEMICAL COMPOSITION

O-phenilphenol Isopropylic Alcohol, Coformulants, depurated water as needed to Made in Italy.

Italian Health Ministry

FAZZOLETTI DISINFETTANTI

Per una rapida

disinfezione

SALVIETTE DIBINFETTANT

Benzalkonium Chloride 0.02 g

Registration 13428



36609 WIPES

### DISINFECTANT DISINFECTANT WIPES

### • 36625 tube of 100 wipes • 36626 box of 400 bags

Active against bacteria are ideal for children since they do not burn. Indispensable in the house, the car. in sporting events

- Indicated for the disinfection of: - insect bites
- skin before and after injections - disinfection of hands and other

body parts. Instructions on the box in GR IT

Italian Health Ministry Registration 12671



CHEMICAL COMPOSITION

100 g contain: Benzalkonium Chloride 0.5% - O-phenilphenol 0.01% - Coformulants and water as needed to 100 g. Made in Italy.

### ALCOHOL SWABS/PADS

### • 36598 ALCOMED PADS box of 100

• 36599 ALCOMED PADS carton of 10,000 (100 boxes of 100 pads)

Alcohol saturated pads with 70% isopropyl alcohol for skin preparation prior to injection. Bag size 50x50 mm,

1,000 ml solution contain:

sodium chloride 9 a water

injection electrolytes: mmol/l

folded pad 32.5x30 mm, open pad 65x30 mm.

### NaCl 0.9% B-BRAUN STERILE IRRIGATION SOLUTIONS



### **ECOLAV**®

The spray nozzle of Ecolav® allows a precise and direct irrigation of the target area by simply applying a slight pressure on the container, helping optimize the time for irrigation processes. Multilanguage manual and box: GB. FR. IT. ES. DE. PT. NL.

### **ECOTAINER®**

Ecotainer® non-drip pouring characteristics help reduce contamination risks during the irrigation process. Suggested for quick irrigation with high volume of solution. Multilanguage manual and label: GB, FR, IT, ES, DE, PT, NL, DK, FI, NO, SE.

### B-BRAUN OMNIFLUSH®

PREFILLED FLUSH syringe 10 ml with NaCl 0.9% - box of 100 - EM-3513576 The Omniflush® syringe is designed specifically to minimize unintended blood reflux into the catheter lumen thus reduces the risk of catheter blockage. With Omniflush®

the fluid amount used for flushing can be reduced to the required minimum. For flushing of all introvenous accesses. Multilanguage manual and label: GB, FR, IT, ES, DE, PT, PL, CZ, BG, DK, EE, FI, GR, HU, LT, LV, NL, NO RO, SK, SI, SE.





36558



GERMOXID

### SURGICAL SCRUB BRUSHES/SPONGES



### • 36570 SCRUB KIT - sterile - dispenser of

Sterile hand-cleaning hospital kit. It includes a scrub, a sponge and a plastic nail cleaner. Dry, without detergent. Sterilization method: ETO. Multilanguage label (blister and dispenser): GB, FR, IT, ES, DE, PT, PL, NL, GR, RU, Arab.

Made in Italy Δll scrub kits are individually blistered in 30 pieces dispense





 36571 IODO-POVIDONE SCRUB KIT dispenser of 30 pcs - IT

Italian Health Ministry registration PMC 19575 • 36572 IODO-POVIDONE SCRUB KIT dispenser of 30 pcs - Multilanguage\* "Label: GB\_FR\_FS\_DF\_PT\_PL\_NL\_GR (blister and dispen ser), PL, RU, Arab (blister only)

Same as 36570 with solution of PVP lodine 7.5 g in 100 ml. Made in Italy.







 36573 CHLOREXIDINA SCRUB KIT dispenser of 30 pcs - IT

Italian Health Ministry registration PMC 19531 • 36574 CHLOREXIDINA SCRUB KIT

dispenser of 30 pcs - Multilanguage \*Label: GB, FR, ES, DE, PT, PL, RU, Arab (blister only)

Chlorhexidine Gluconate 20% 4 g in 100 ml





### 25715 PERFECTION BRUSHES

Nylon brushes for cleaning before and after operation. These brushes are autoclavable (at 100°C for not more than 5 minutes) and can be stored in any standard brush dispenser in hospitals. Resistant and reliable. Handle in PP. Supplied in boxes of 12 units.

### IODO-POVIDONE ANTISEPTIC • 36614 IODO-POVIDONE ANTISEPTIC 125 ml

• 36608 IODO-POVIDONE ANTISEPTIC 500 ml • 36619 IODO-POVIDONE ANTISEPTIC 1,000 ml

Wide spectrum disinfectant for the disinfection and cleaning of the skin in hospital wards with high risk of infection. Medical-Surgical Presidium n.19661. The range of action includes Gram and Gram germs, acid and acid resistant bacteria and virus. Its activity is maintained in the presence of organic materials.



Label: GB, IT. Made in Italy.

CHEMICAL COMPOSITION

Each 100 ml contains: polyvinylpyrrolidone ioding 10 g, coformulants and



### HLORHEXIDINE DISINFECTION LINE



36634

• 36637 GERMOXID SPRAY DISINFECTION - 100 ml - box of 12

• 36635 GERMOXID DISINFECTION - 250 ml - box of 12

• 36636 GERMOXID DISINFECTION - 1,000 ml - box of 12

• 36634 GERMOXID WIPE - 12 boxes of 10 wipes

suitable • 36638 GERMOXID WIPE - box of 400 wipes for hands Germoxid is a ready-to-use disinfectant for skin that contains

> Chlorhexidine with long-lasting bactericidal action. Chlorhexidine has a proven broad-spectrum effectiveness against Gram+ and Gram- bacteria.

The molecular structure of Chlorhexidine is very similar to that one of epidermis proteins and it is therefore rapidly and constantly absorbed

Chlorhexidine is particularly suitable for skin disinfection. It is particularly safe for medical operators thanks to its high epidermis compatibility, it neither irritates the skin nor stains or burns. Available in 3 versions: liquid (250 or 1,000 ml), spray (spray dispenser allows a quick and efficient action and is eco-friendly) or wipes (ready-

to-use disinfecting wet wipes containing chlorhexidine). Italian Health Ministry registration 11571



### BARRYCIDAL"30 PLUS": A WIDE-SPECTRUM DISINFECTANT



• 35761 BARRYCIDAL "30 PLUS" - diluted 5% - bottle 1 l

• 35759 BARRYCIDAL "30 PLUS" - diluted 5% - bottle 1.2 I Ready for use 1 or 1.2 I bottle with 10 cc measurer cap.

• 35763 BARRYCIDAL "30 PLUS" - concentrate, to be diluted - tube 224 ml • 35764 BARRYCIDAL "30 PLUS" - concentrate, to be diluted - tank 3.785 I (1 Gallon)

Barrycidal 30 Plus is a water-based solution with gluteraldehyde and phenols, suitable to cleanse and disinfect surgical instruments and thermosensitive, non-autoclavable endoscopes, with good property to dissolve blood and organic traces. Colourless liquid emulsion. The product diluted by 5% is not classified as hazardous pursuant to the provisions set in Regulation 1272/2008 (CLP). Medical Device according 35764

to Class IIb - Directive 93/42 EEC. Tested action-spectrum in "clean" conditions: bactericide (EN 13727 and

EN 14561), fungicide (Candida Albicans, Aspergillus Niger; EN 13624 and EN 14562), mycobactericidal and tuberculocidal (Mycobacterium Avium, Mycobacterium Terrae; EN 14348 and EN 14563), virucidal (EN 14476). 30 Plus concentrate acts in 15 min. if diluted by 5%, 60 min. if diluted by 2.5%. Diluted by 2.5% results in 9 l of ready to use product.

CHEMICAL COMPOSITION

30 Plus concentrate: 100 ml contain: gluteraldehyde (<2%), 2-benzil-4-chlorophenol 4.5%, 2-phenylphenol 7%, coformulants and purified water.

30 Plus standard: contains less than 0.2% at 5% dilution gluteraldehyde, phenols, surfactant

### DISINFECTANT POWDER

• 36639 GERMOCID PERACETIC POWDER - bag 16 g - box of 50 bags • 36620 GERMOCID SPRAY DISINFECTANT - 400 ml • 36640 GERMOCID PERACETIC POWDER - box of 500 g ( 60546 Cold sterilizer disinfectant: the peracetic acid which forms from the reaction of sodium percarbonate and tetracetilethylendiammine (which is obtained after dissolving

the product into water) carries on an efficacious biocidal action against spores, virus (HIV, HBV, HCV), bacteria, mycobacteria and fungi. At the concentration of 0.3% it carries on sterilization in 10 minutes.

The product is active in 15 minutes from dissolution, solution remains active for max 24 hours. Suitable for a cold rapid sterilization and disinfection of endoscopes, surgical and dental instruments, transducer, etc.

The product is active also in presence of organic materials.

In this case it is better to previously clean the device with suitable detergent, better if with enzymatic

It can also be used with automatic washing machines for endoscopes. No environmental impact: once in contact with discharge water, it degrades immediately into acetic acid, water, oxygen.

Chemical composition: peracetic acid precursors and coformulants.

Made in Italy.

### SPRAY DISINFECTANT Spray disinfectant with bactericidal power. Disinfects

and deodorizes surfaces and objects of crowded and smoky areas (hospitals, classrooms, examination and surgery rooms, bathrooms, cars, trailers). Instructions on box in GB, IT.

### CHEMICAL COMPOSITION

100 g contain: O-phenilphenol 0.02 g; benzalkonium chloride 0.1 g. Coformulants and propellants as needed to 100 g. Made in Italy. Italian Health Ministry registration 7604

# **BOXES FOR COLD STERILIZATION**





minimum order: box of 6 hottle

35772 autoclavable

• 35770 STERILIZATION BOX - 1.5 l (internal: 10x25.5xh 7.5 cm) • 35772 STERILIZATION BOX - 3 I (internal 18.3x29xh 9 cm) - autoclavable Useful plastic box, with an internal removable perforated instrument tray, specially developed for cold sterilization of medical instruments. White colour. Made in Italy.

### GERMOCID TABS

### • 36622 GERMOCID TABS CHLORINE TABLETS - 1 kg

White round effervescent chlorine tablets for cleaning, disinfecting and deodorizing. The dilution of 1 tablet in 7-8 litres of water or 2 tablets if you need stronger disinfection allows to hygienize rubber, plastic or glass. Germocid tabs can be used for many other purposes:

wc sanitizing, dishwasher, floor cleaning and also for mopping bars, restaurants, hospitals. Rinsing required. Packed in 1 kg jar, containing approx: 300 tabs.

Label/instruction in GB, IT. Made in Italy.



GERMOCID POLVERE

36640

### ENZYME-BASED DETERGENT

### • 36618 ENZYME-BASED

DETERGENT - 3 I

Medical device enzymatic based detergent for invasive surgical instruments. This clear liquid detergent is very useful to improve the cleaning of orthodontic and surgical instruments, glassware, plastic and metal objects. Also suitable for ultrasound cleaners. Dilute in 1 litre warm water, immerse the instruments for 10 minutes and rinse. Label/instruction in GB, IT. Made in Italy.


€ 0546 CHEMICAL COMPOSITION

36618

100 q contain: proteolytic enzymes 0.5 g, non-ionic surfactant agents 10-15 g, coformulants, water as needed to 100 g

351

### MULTILAYER DECONTAMINATING MAT WITH ANTIBACTERIAL



- 36685 DECONTAMINATING MAT 45x90 box of 5 blue
- 36686 DECONTAMINATING MAT 60x90 box of 5 blue

### **DECONTAMINATING MATS**

Mats to be used in all environments that require total absence of contaminating agents and the preservation of high hygienic levels. GIMA mat, thanks to antibacterial glue captures and retains dust and bacteria and substantially reduces bacteria growth and spreading. A full length adhesive sheet on the bottom of the mat provides a firm grip to the floor. Easy removability without leaving any adhesive trace.



Each mat includes 30 numbered polythene sheets and a nonadhesive edge strip to allow easy removal of each used layer. Medical disposable device CE Classe 1 non-sterile. Packed in a stylish dispenser folder with handle for easy carriage and vertical storage. Each mat can be easily picked leaving the others perfectly stored. Total mat thickness: 1.5 mm. Box of 5 mats with 30 sheet each. On request (minimum 10 boxes) available in white or green and size 60x95 cm or 90x95 cm.

- 36693 DECONTAMINATING MAT 45x115 box of 5 blue
- 36694 DECONTAMINATING MAT 60x115 box of 5 blue
- 36695 DECONTAMINATING MAT 90x115 box of 5 blue
- 36696 DECONTAMINATING MAT 45x115 box of 5 white

### GERMOCID WIPES FOR SURFACES, MEDICAL DEVICES

• 36680 GERMOCID WIPES - 120 wipes - tube

Ready to use wipe, it contains a Chlorhexidine and Quaternary Ammonium Salt based alcoholic solution. With a fast and effective disinfectant action against Bacteria Gram Yeasts, Moulds, Fungi, Tuberculous Mycobacteria (TBC). Lipophilic and hydrophilic Viruses (HIV - HVB - HVC). The product has a high detergent power and it quickly evaporates.

It is not inactivated by organic residuals.

Suitable for cleaning and disinfection of non-invasive medical devices and surfaces disinfection in medical and dental medical offices. **( €** 0546 Wipe size: 200x240 mm.

36615

GERMOCID



### GERMOCID BASIC SPRAY

CHEMICAL COMPOSITION 100g of product contain Chlorhexidine digluconate Benzalkonium chloride 0.1 g Ethanol 45 g 2-Propanol Coformulants and depurated water as needed for Appearance: green liquid 0546 Smell: characteristic pine

• 36615 GERMOCID BASIC - 750 ml For disinfection and fast cleaning of every kind of medical surface materials which are not sensitive to alcohol like arms, handles and different dentistry obiects.

- Disinfectant action: the association between Chlorhexidine and Quaternary ammonium Salt and the high alcoholic content quarantee a large action spectrum towards:

- Bacteria gram+ and gram-, fungi and virus HIV, HBC, HCV (HEPATITIS B and C) in 1 minute of contact.

- Fungi, microbacteria and TBC in 5 minutes of contact. Strong detergent power and fast evaporation.

It is not de-activated by organic substances.

- Bactericide, virucide and fungicide activity.

Sold in box of 12 - only 2 bottles come with vaporizer.

• 36691 VAPORIZER

### ENVIRONMENT DISINFECTANT

• 36616 ENVIRONMENT DISINFECTANT - bottle of 1 litre • 36617 ENVIRONMENT DISINFECTANT - tank of 3 litres

Concentrated liquid detergent-disinfectant for environments.

Dilute it in water to a ratio of 0.5% for the disinfection and the cleaning of surfaces, counter, tiles, floors, sanitary fixtures, also using floor-washing machines Suitable in large areas (hospitals, clinics, rest homes, gyms, swimming pools) for the disinfection and cleaning of surfaces. - Disinfectant action: guarantees a wide protection against virus, fungi, bacteria Gram+ and Gram-.



- Detergent action: contains non-ionic surface active agents to enhance the cleaning of surfaces.

CHEMICAL COMPOSITION

0.2 g 100 g

100 g of product contain Quaternary ammonium compound Isotyazolinone magnesium chloride Coformulants and depurated water Appearance: pale yellow liquid

Smell: citrus flavour Biodegradability: detergent according to rules CE n° 648/2004 Italian Health Ministry authorization N° 9658

### BRANSON ULTRASONIC CLEANERS

### Precision cleaning power

Ultrasonic cleaning is faster and safer than any other method. It's powerful enough to remove heavy oils and waxes. penetrating enough to deflux circuit boards, yet gentle

enough to clean tiny precision assemblies. Ultrasonic sound waves moving through a cleaning solution create an effect called cavitation, the rapid formation and

implosion of microscopic bubbles. Heat enhances the process. The deep-cleaning action of ultrasonics removes even the most stubborn dirt and contaminations.

### Branson: pioneer in ultrasonic cleaning

We have selected Branson because their cleaners incorporate years of experience in ultrasonic cleaning:

- easy to handle and safe to fill
- frequency higher than average for a deep cleaning
- less noise longer lifetime.

All Branson cleaners are supplied with tank cover, and multilanguage manual (GB, FR, IT, ES, DE, PT, SE, NL, RU). Recommended use with optional perforated tray.

### M Series: M (Mechanical timer) or MH (Mechanical timer with heater)

Includes 60-minute mechanical timer and continuous operation with heating capability (MH only).

### **CPXH Series (Digital control with heater)** Are the most technologically advanced

ultrasonic cleaners available. With programmable features, digital operation with power tracking capabilities

temp calibration


stored and saved

Operating parameters

3 MODELS: MECHANICAL.

DIGITAL + HEATER

to adjust for light or heavy loads, high/low power control and degassing. The CPXH is the most versatile system available.



High/low power control provides safer cleaning of delicate components, 100% power for normal or 70% for delicate applications

CPX series is completely

programmable so

engineers can choose

ston times for "set-it-

Temperature can

be set for either

Fahrenheit or Celsius

up to 69 °C/156.2

temperature, start, and

and-forget-it" operation

TECHNICAL SPECIFICATIONS Branson 2800 Branson 3800 Branson 5800 Branson 8800 230x140x100 290x150x150 290x240x150 495x290x150 337x304x302 397x317x377 397x401x378 596x466x391 95 (25) Tank capacity: litres (gal) 2.8 (0.75) 5 7 (1 5) 20.8 (5.5) Drain and valve kit No Included Included Included 4.1 (9) 5.4 (12) 6.4 (14) 11.8 (26)

40 KHz

230-240 V

40 KHz

230-240 V

40 KHz

230-240 V

Degassing periods of up to 99

minutes also allow for various

sample prep applications.

Digital timer allows

ultrasonic operation

up to 99 minutes

Ultrasonic power

tracking maintains

steady, consistent

activity in the both

hen condition change

for continuous

4 SIZES: 2.8, 5.7, 9.5, 20.8 LITRES. MECHANICAL + HEATER



40 KHz

230-240 V

	35501	35511	35522	355
ULTRASONIC CLEANERS	BRANSON 2800	BRANSON 3800	BRANSON 5800	BRANSON 8800
	2.8 litres	5.7 litres	9.5 litres	20.8 litres
M Mechanical timer	35501	35510	35520	35531
MH Mechanical timer with heater	35502	35511	35521	35532
CPXH Digital timer with heater	35503	35512	35522	35533
ACCESSORIES	Branson 2800	Branson 3800	Branson 5800	Branson 8800
Tank cover, plastic* or stainless steel**	35507°	35517°	35527°	35537**
Perforated tray	35508	35518	35528	35538
Tray	35505	35515	35525	35535
Beaker positioning cover	35506 2x 250 ml	35516 3x 250 ml	-	-
Beaker positioning cover 600 ml	35509 2x 600ml	35519 2x 600ml	35529 4x 600ml	35539 6x 600ml
Glass beaker 250 ml	35540	35540	-	-
Glass beaker 600 ml	35541	35541	35541	35541
Glass beaker 600 IIII	33341	33341	3334 I	33341





35516+35540

### FREE AND BASIC ULTRASONIC CLEANERS



ULTRASONIC CLEANERS	BASIC	FREE	BASIC	FREE
	3 I	3 I	9 I	9 I
Tank size mm	235x1	00x135	332x1	20x227—⊣
Overall size mm	305x248x168	305x248x178	418x268x259	418x268x26
Weight kg	3.7	4	7.1	7.4
Ultrasonic power W	150	150	300	300

### ULTRASONIC CLEANERS

The ultrasonic tub is designed to wash instruments used in the medical, dental, cosmetic, veterinary fields. The ultrasound cleaning (cavitation) allows to thoroughly clean instruments difficult to clean manually.

Heating - FREE only
The device heats the detergent and stops automatically when the preset temperature is reached.

Degassing (degas) - FREE and BASIC

This process reduces the gas dissolved in the liquid, thus improving the efficiency of the subsequent washing.

Ultrasonic cleaning - FREE and BASIC Washing phase through ultrasonic cavitation.

Sweep - FREE and BASIC

Ultrasounds are modulated in frequency, thus reducing the negative effects of stationary waves, increasing the distribution of ultrasonic energy within the washing liquid. Discharge - FREE only

Tub of Basic has to be manually emptied, tub of Free can be emptied by opening the appropriate valve.

asket and lid.

	All ultrasonic cleaners are supplied with basket and lid.						
E	GIMA code	FREE AND BASIC ULTRASONIC CLEANERS					
	35550	Basic ultrasonic cleaner 3 l					
3x269	35551	Free ultrasonic cleaner 3 I - with heating and discharge					
1	35552	Basic ultrasonic cleaner 9 l					
)	35553	Free ultrasonic cleaner 9 I - with heating and discharge					

### ULTRASONIC CLEANER



### • 35549 GIMA 50 ULTRASONIC CLEANER 0.6

This ultra-compact cleaner is very easy to use, efficient and economic. Ideal to clean small objects. Electronic, non adjustable timer with plastic cover and basket. No heating Internal size: 168x89x55 mm.

Supersonic wave 46,000 cycles per second.

### GENERAL PURPOSE CLEANER

### • 35544 BRANSON GENERAL PURPOSE

CLEANER - bottle 1 l concentrate

BRANSON PURPOSE is a cleaning solution developed for use with ultrasonic cleaners. Removes general soils, fingerprints, dust, light oils and greases.

Branson cleaning liquid has been specially developed to provide optimal transfer of acoustic energy.

Mainly used in: dentistry, medical and optical applications, laboratory, electronics, gold and silver works.

### CHEMICAL SPECIFICATIONS

Concentration: 10-12% Biodegradability: yes Phosphate free Concentration PH: 13.5 Rinsability: good



### GIMA QUICK: STERILIZATION IN 2 MINUTES

- 35640 GIMA QUICK hot bead sterilizer
- 35642 GIMA QUICK PLUS with thermometer

GIMA OUICK hot bead sterilizer has been designed and developed specifically for medical use. Also recommended for dentistry, podology, veterinary, tattoo and beauty studios. It ensures a quick and effective sterilization.

It sterilizes files and mirrors in 2 minutes, surgical instruments in 2 minutes, curettes and forceps in 3 minutes. Its constant temperature over 230°C ensures the total destruction of micro-organisms and spores in few seconds. GIMA QUICK has epoxydic powders painted steel casing; the inside cylinder is completely isolated by fibres and glass, which prevents heat from being transmitted to the external casing. It can work continuously for the whole day.

Supplied with a pack of glass beads (220 g). Made in Italy.

- 35645 PYREX BASIN
- 35646 PACK OF GLASS BEADS



### **TECHNICAL SPECIFICATIONS**

Outer structure in white painted steel Size: 130x130x190 mm Copper plated basket: diameter 5.5 cm depth 7.5 cm

Weight: 2.8 kg Power consumption: 150 W Operating voltage: 220 V - 50 Hz. Warranty: 12 months Made in Italy

### DIGITAL OR THERMOVENTILATED DRY HEAT STERILIZERS



TITANOX dry heat sterilizers 20, 60, 120 litres.

Inner structure and height adjustable inner shelves completely made of stainless steel. Door with lock and key.

Thermoventilated unit: to guarantee the uniformity of the temperature in the heating room and to allow the circulation of the air, the device is provided with a ventilation motor that results always in operation, both during the cycle of heating and during the pauses of cooling.

Digital unit: adjustable aeration tunnels, placed on the bottom of the right side and on the top of the left side for hot air adjustment and circulation, which is useful for a quick cooling of the device.

GIMA code Thermoventilated	GIMA code Digital	Capacity	Outside dimensions (mm)	Inside dimensions (mm)
35583	35586	20		405x255xh 210
35584 35585	35587 35588	60 l 120 l		535x320xh 345 670x420xh 415



Supplied with manual in: GB, FR, IT, (ES on request) and 2 height adjustable trays. Made in Italy.

### TECHNICAL SPECIFICATIONS

Thermoventilated:

Timer 0-120 minutes that switches off the oven at the end of the planned time Probe thermometer from 0° to 200°

Probe thermoregulator from 0° to 200°

Safety thermostat

Thermometer

Made in Italy

Ventilator for forced ventilation Double check up light bulb

Digital:

Electronic running C.P.S. Use modality: continuous (stand by) or timed Timer from 0 to 250 minutes

Optimum heat distribution

Automatic indication for possible problems of feeding (in case of mains tension lack, the program will start again from the beginning)

Operating voltage: 230 V - 50/60 Hz (110 V on request with surcharge for 35583-5)

### TAU STERIL AUTOMATIC DRY HEAT STERILIZERS 1.6, 6,18 LITRES Shining 18/8 stainless steel non corrosive, almost





• 35600 TAU STERIL 1.6 - automatic hot air sterilizer

• 35619 TAU STERIL 18 - automatic hot air sterilizer TAU sterilizers have been designed to satisfy all daily medical requirements in the field of sterilization.

Extremely robust, totally automatic, guarantee complete

• 35606 TAU STERIL 6 - automatic hot air sterilizer

**TAU 1.6 and 6** have double wall and inner insulation, outside is made of stove-enamelled sheet steel, inside of stainless steel 18/8 (double cover, sterilization chamber and removable perforated tray).

TAU 18 comes complete with safety fuses, neon warning lights to control timer and thermostat, power cable, 3 itallumac treated shelves (375x200 mm), shelf extracting tongs.



TECHNICAL SPECIFICATIONS TAU 1.6 TAU 6 **TAU 18** 385x170xh 90 375x230xh 200 Inside dimensions (mm) 245x115xh 55 310x180xh 180 495x310xh 220 440x310xh 380 Outside dimensions (mm): Weight: 5 kg 10.5 kg 14 kg Operating voltage 220 V 220 V 220 V 110V available on request -Power consumption: 250 W 400 W 600 W Fuses: 3.15 A Automatic capillary bulb type with self registration Thermostat: from 90° to 200° from 0 to 120 minutes Timer

high precision with capillary bulb

### ■ HOT AIR STERILIZERS: GIMETTE 1.5, 7, 21, 28 AND 50 LITRES



• 35601 GIMETTE 1.5 - hot air sterilizer • 35607 GIMETTE 7 - hot air sterilizer

**C** € 0425 Automatic Gimette are compact and high quality hot air sterilizers with the same reliability and efficiency as larger models. Outside structure is made of painted plate with anti-scratch epoxy powder. Stainless steel lid and sterilization chamber with approx. Capacity of 1.5 I and 7 I.

Removable, perforated for air circulation, tray with pliers. All components certified by most important European brands, assembling in compliance with EN-61010. A second safety thermostat triggers in case temperature should exceed 220°C. Red LED indicates any anomaly in thermoregulation and consequent starting of safety thermostat.

- 35631 RESISTOR 250 W for 35601 spare
- 35632 RESISTOR 400 W for 35607 spare
- 35612 GASKET for 35607 spare
- 35613 GASKET for 35601 spare



### TECHNICAL SPECIFICATIONS

GIMETTE 1.5 Inside dimensions Outside dimensions Power consumption: GIMETTE 7 Inside dimensions

245x120x50 mm = vol. 1.5 dm 310x180x180 mm Weight: 4.3 kg 250 Watt Fuse: 1 A

Outside dimensions: Power consumption:

490x310x180 mm Weight: 8 kg 400 Watt Fuses: 2 x 2.5 A Thermometer: high precision with capillary bulb Same specifications for both models:

Operating Voltage: 230 V - 50 Hz Thermostat: 2° Thermostat Green LED:

automatic, adjustable 0-200 °C manual from 0 to 120 minutes bi-metallic certified timer, orange LED: heating, red LED: alarm

410x180x90 mm = vol. 7 dm

Made in Italy - Warranty 1 year User/Service manual in IT. GB. FR

0425



- 35621 GIMETTE 21 hot air sterilizer
- 35628 GIMETTE 28 hot air sterilizer
- 35629 GIMETTE 50 hot air sterilizer

Fully automatic hot air sterilizer, with adjustable temperature from 0°C to 200°C, kills off even particularly resistant micro-

Stainless steel structure is powder painted, except for the door, to assure maximum heat and shock resistance over time. Four perforated, anodized aluminium travs make hot air circulation easier. Capacity approximately 20 I, 28 I and 50 I. A second safety thermostat triggers in case temperature should exceed 230°C.

SPARE ACCESSORIES						
STERILIZER	TRAY	GASKET	RESISTOR 600 W			
Gimette 21	35610	35614	35639			
Gimette 28	35611	35615	35639			
Gimette 50*	-	35617	35639			

\*Needs 2 resistors



Red LED indicates any anomaly in thermoregulation and consequent starting of safety thermostat.

### TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS					
	GIMETTE 21	<b>GIMETTE 28</b>	GIMETTE 50		
Inside dimensions mm:	300x250x260	380x250x260	405x340x350		
Approx. volume	20 dm <sup>3</sup>	28 dm <sup>3</sup>	50 dm <sup>3</sup>		
Outside dimensions mr	n: 440x340x400	550x340x400	605x460x480		
Weight:	13 kg	17 kg	24.5 kg		
Power consumption:	600 Watt	500 Watt	1200 Watt		
Same specifications for					
Operating Voltage:	230 V - 50 Hz				
Fuses:	2 x 4 A (35621, 35628	) 2 x 8 A (35629)			

manual from 0 to 120 minutes Thermostat: automatic high precision with capillary bulb Thermometer.

2° Thermostat: bi-metallic certified
timer, orange LED; heating, red LED; alarm Green LED:

Made in Italy - Warranty 1 year User/Service manual in IT. GB. FR

### 356

### PRESTIGE CLINICAL AUTOCLAVES: EXCELLENCE THROUGH DESIGN



### GIMΔ PRESTIGE MEDICAL AUTOCLAVES 35709 Prestige autoclave 9 litres 35712 Prestige autoclave 12 litres 35720 Silicone sealing gasket 35724 Depressurization valve - since 2011

### PRESTIGE AUTOCLAVES - class N

Prestige is one of the world's largest selling and most cost effective automatic autoclave available, with an enviable reputation for reliability, durability, safety and quality. - method recommended by healthcare professional worldwide including the World Health Organisation (WHO)

- each autoclave is computer tested and issued with a unique Performance Test Certificate - at only 4.5 kg net weight, offers full device portability

- supplied with basket and multilingual user manual Recommended for infection control not only in hospital and general medical and dental surgeries, but also in veterinary, chiropody, professional beauty, tattooists, acupuncture, laboratories and schools.

Comply with: IEC 61010 (product safety), BS3970 part 4 (pressure vessel only), BS 5500 (pressure vessel).

### TECHNICAL SPECIFICATIONS 35709 35712

Capacity: Chamber internal dimensions (D/H) 210/236 Maximum instrument length (diagonal): 228 mm Maximum loading weight: 3 kg Width/height: Same specifications for 2 models: 340/335 Sterilizing time: 11 minutes Cycle time (nominal): 22 minutes Operating pressure: 1.40 bar Sterilizing temperature: 126 °C Operating voltage: 230 V - 50-60 Hz - Power 1,250 Watt Made in UK - Warranty: 1 year



### ■ GIMA VERTICAL AUTOCLAVE H100 - 9 LITRES - CLASS N

• 35746 H100 GIMA AUTOCLAVE - 9 litres - 230 V Safe and easy to use autoclave to sterilize surgical instruments and hand-pieces which can be sterilized up to 125°C, with a sterilization cycle of 15 minutes only. External frame of painted steel and stainless-steel 18/10 body without any welding. Equipped with three safety valves. Made in Italy.

Safety systems

- safety lock to prevent opening of the door during the sterilization cycle; the door can only be opened when pressure inside the chamber is levelled to the ambient one

- safety valve for vapour exhaust in case of damage with inside overpressure > 2.5 bar. Safety valve TUV certified (PED IV) - safety thermostat which occurs if the inner temperature of the chamber rises over 135°C

- safety valve kit to adjust pressure if it rises over 2.0 bar - thermodynamic vacuum

Complies with 93/42/EEC Class IIb, IEC601, EMC

• 35747 SEALING GASKET for H100 with serial number: A, D, E, F. K. L. Please advise if different serial number.

STANDARD ACCESSORIES Stainless steel basket int: Ø 195xh 183 mm ext: Ø 210xh 210 mm with feet Distilled water bottle 1 l

User manual in GB, IT, ES on request FR, DE TECHNICAL SPECIFICATIONS

External size: 250x385xh 310 mm Size of the sterilizing chamber: Ø 220 mm - h 235 mm Removable basket: Ø 210 mm - h 210 mm Sterilizing liquid: distilled water Absorbed power: 1500 Watts Operating voltage: 230 V - 50/60 Hz Fuses: type 6.3 x 32 mm - 8A Operating temperature: 125 °C Sterilizing time: 15 minutes Operational pressure: 1.3/1.6 bars (130/160 KPa) Net weight: 13.3 kg



### GERMY GIMA PLUS: GERMICIDAL ULTRAVIOLET LAMPS



• 35750 GERMY GIMA PLUS 8 W - 38x20xh 17 cm • 35751 GERMY GIMA PLUS 15 W - 50x24xh 20 cm

• 35752 GERMY GIMA PLUS 30 W - 96x24xh 20 cm

• 35754 SPARE NEON LAMP - 8 Watt

• 35755 SPARE NEON LAMP - 15 Watt

• 35756 SPARE NEON LAMP - 30 Watt

### **AVAILABLE IN 3 SIZES**

### GERMY GIMA PLUS: ULTRA VIOLET LAMPS

These instruments incorporate a germicidal ultra-violet lamp which rapidly destroys every micro-organism hit by its rays. Recommended to keep the instruments stored inside sterile. Instruments previously sterilized can be preserved for a long time and they are always ready for use (UV treatments do not generate heat).

An inside supporting grate keeps instruments raised from reflecting surface which enables both surfaces to be uniformly irradiated, improving the UV germicidal action. Operator safety is guaranteed by a micro switch which

extinguishes the lamp if door is opened.

Solid construction, painted steel outside and reflecting stainless steel inside

Installation on table or wall.

Operating voltage: 230 V - 50/60 Hz - 1 A

Made in Italy.

### HYDRA EVO ELECTRONIC 15 OR 18 L STEAM AUTOCLAVE - N

• 35658 HYDRA EVO AUTOCLAVE - 15 litres - 230 V

• 35659 HYDRA EVO PLUS AUTOCLAVE - 18 litres - 230 V Automatic steam autoclaves for the sterilization

of unwrapped instruments. Closure system with an operator safety pivot. Thermodynamic system for the ejecting of the "cool" air locks.

Two sterilization cycles: 121°C and 134°C

Automatic phases of pre-heating, sterilization cycle and

### Pre-set, non-modificable cycles

All cycles are pre-set at the factory and quarantee perfect and safe sterilization of treated materials.

There is no way the operator can manipulate or alter the cycles, and this safeguards against risks deriving from human error.

### Pre-set temperatures

The temperatures set for our autoclave cycles are 134°C and 121°C. The 134°C cycles are normally used for the sterilization of solid and ferrous materials 121°C cycles are normally used for sterilization of thermoplastic and delicate materials.

### Water tank

Hydra EVO only has one water tank. This tank must be filled with distilled or demineralized water and acts as a container for collecting the used water which is then re-utilized for new cycles.

### Safety on the door

Each door is equipped with 2 locks:

- a mechanical one which does not open when pressure is exerted
- a dynamic one, that operates thanks to a special form of door

### Safety devices installed

- Certified safety valve
- PED on sterilization chambers
- Insulation of the chamber with certified ceramic material

### TECHNICAL SPECIFICATIONS

Stainless steel chamber: Ø 24.5 x 32 cm Ø 24.5 x 40 cm (Plus) External size: 44 x 38 x 50 cm (W x H x D) Net weight: 35 kg

2 sterilization cycles: 121°C and 134°C Operating Voltage: 230 V±10% - 50/60 Hz Power consumption: 1700W Class N

Made in Italy - Warranty: 1 year







### Controls on the Autoclave

- · Control of the water that enters into the chamber
- Safety Thermostat
- Time Control

The sterilization chamber is completely stainless steel AISI 304 and it is heated by a band shaped heating element which grants uniformity of the heat. Supplied with four aluminium trays and one key for their extraction.

User manual available in English, French, Italian, Spanish.

- 35671 Sealing GASKET spare
- 35669° HEATING BAND DHY A035 for 35650, 35654
- 35670° HEATING BAND DXB A835 for 35658, 35659

\*Need serial number of autoclave

Cycles	Materials	Sterilization time	Drying time	Max load	Working pressure
Not wrapped 121° C	•Fragile solids •Rubber solids •Glass •Turbines if indicated by producer	20 min.	5 min.	2.8 kg 700 g load in any tray	1.2÷1.3 bars
Not wrapped 134° C	Stainless metal solids     Turbines if indicated by producer	10 min.	5 min.	2.8 kg 700 g load in any tray	2.1÷2.2 bars

### NUBYRA 6 LITRES STEAM AUTOCLAVE - CLASS N



Cycles	Materials	Sterilization time	Drying time	Max load	Working pressure
Not wrapped 121° C	•Fragile solids •Rubber solids	18 min.	5 min. short dry or 15 min long dry	1 kg 500 g load in any tray	1.1÷1.2 bars
Not wrapped 134° C	•Fragile solids •Rubber solids	6 min.	5 min. short dry or 15 min long dry	1 kg 500 g load in any tray	2.1÷2.2 bars

### • 35647 NUBYRA AUTOCLAVE - 6 litres - 230 V

Electronic steam autoclave for the sterilization of unwrapped instruments. 2 fully automatic, microprocessor controlled, sterilization cycles: at 134°C or 121°C with short or long automatic drving.

LCD display with visualization of temperature and pressure for total control of sterilization cycle. Easy closure system with double safety sensor. Air pockets automatic ejection system: thermodynamic system for the ejection of "cold" air pockets. Anodized aluminium chamber, 2 electronic temperature sensors (1 inside chamber and 1 outside) and electronic transducer for better control of pressure.

Supplied with 3 aluminium trays.

• 35648 GASKET - spare

### TECHNICAL SPECIFICATIONS

Anodized aluminium chamber Ø 17x26.5 cm - 6.1l External size: 44.5x48xh 35 cm Trays size: 1 large 15x24x2 cm 2 small 11x24x2 cm Maximum load: 1 kg (short dry) 0.5 kg (long dry)

2 sterilization cycles: 121°C and 134°C Operating voltage: 230V - 50/60 Hz Max absorbed power: 1,350 Watt Net weight: 27 kg Class N Made in Italy - Warranty: 1 year User manual: GB, IT (FR, ES on request).

### EUROPA B EVQ: CLASS B AUTOCLAVE 15 AND 24 I

EN13060

Tray holder with 4 aluminium trays



Supplied with 1 closed tray holder, 4 aluminium trays, 1 double-use key for tray extraction and door adjustment, water loading and unloading hoses. chamber cleaning sponge and inte-



C €0434 TUV



Constant control and monitoring of the entire autoclave functional system



121°C-134°C suitable for both enveloped and free materials. All cycles are for type-B loads.

As regards to safety in health practice, sterilisation is the first aspect to consider. Autoclaves offer physical and legal safety. This is why autoclaves must be chosen according to rational logics and based on professional and not only cost-related

With the new EN 13060 standard, the choice of the right autoclave is now easier for professionals: they must choose a certified, adequate model, based on the type of materials to sterilise. A B-type loads autoclave allows to sterilize hollow materials such as handpieces and turbines and porous materials (overalls, gauze...).

### P.I.D. System (Proportional Integral Derivate)

It represents the top of closed loop controls. P.I.D. ensures a constant control and monitoring of the whole operating system of the autoclave, acting automatically in case of anomalies or incorrect technical and electronic parameters. Internal tanks

All the autoclaves are equipped with an internal tank for pure water and another for used water. Each tank is equipped with probes to detect the minimum and maximum water levels.

### Preset temperatures

The preset temperatures used in our autoclaves cycles are 134°C and 121°C. 134°C cycles are normally used for sterilization of solid and ferrous materials. 121°C cycles are normally used for sterilization of thermoplastic and delicate materials Ease of use

Sterilization cycle is selected by pushing one button and activated by pushing another. First button allows to scroll and view data about all sterilization cycles on the display and select the cycle that suits your materials best, second button automatically starts the whole sterilization cycle. It is impossible to make mistake or choose an inadequate sterilization cycle. In case of any error or warning a series of messages and LEDS will inform you about the problem.

### Fully automatic cycles

All cycles are fully automatic, with all steps managed by the leading-edge computer board with a powerful microprocessor. Each step (vacuum, preheating, exposure time, drying) is automatically monitored, assisted and handled. There is no need for human intervention in cycle management.

Cycles without operator intervention and with autoshutdown In sterilization cycles an automatic function will trigger an anti-

35657 Autoclave equipped with integrated printer LEDON B EVO 24 Miles & B 359

condensation process and auto-shutdown if the operator is not by the machine when the cycle ends.

### Test cycles

Our autoclaves are equipped with test cycles for periodic control by means of physical and functional tests.

Helix test, to assess vacuum capacity in hollow bodies. Bowie & Dick test to evaluate vacuum capability in hollow bodies. Vacuum test to evaluate vacuum retaining capability.

### Costantly monitored cycles

A device constantly controls and monitors the sterilization cycles. Any anomaly or uncommon feature is quickly detected and immediately blocked if it jeopardises the sterilization cycles. The operator is warned of the anomaly by a message.

### All cycles ensure sterilization of B-type loads

All the sterilization cycles feature the fractional vacuum system as well as the controls of parameters that ensure sterilization of B-type loads. Therefore, even if the type of cycle chosen is incorrect the sterilization carried out on the material will be equally adequate.

### Integrated Osmosis system (35657 only)

Inverse osmosis is a safe water treatment system that eliminates even the tiniest polluting particle, to guarantee bacteriological purity. It works through an osmotic membrane which is able to filter water down the molecular levels.

GIMA code	CLASS B AUTOCLAVES
35653	Europa B Evo Autoclave - 15 l
35657	Europa B Evo Autoclave - 24 I with integrated osmosis system
	SPARES

35672 Bacterial filter for Europa B conical threading 1/8 Compatible also with W&H, Cominox, Mocom, Mediline, Euronda 33250 Thermal paper 57mm x 25m (pack of 5 rolls)

Cycles	Working pressure min-max	Minimum time of the total cycle* - minutes			
		Europa B EVO	Europa B EVO 24		
121° C Wrapped	1.04 - 1.30	60 min. (25+18+17)	56 min. (25+18+13)		
121° C Unwrapped	1.04 - 1.30	49 min. (25+18+6)	55 min. (25+18+12)		
134° C Flash	2.02 - 2.38	31 min. (25+4+2)	33 min. (25+4+4)		
134° C Wrapped	2.02 - 2.38	47 min. (25+5+17)	43 min. (25+5+13)		
134° C Unwrapped	2.02 - 2.38	36 min. (25+5+6)	42 min. (25+5+12)		
134° C Prion	2.02 - 2.38	62 min. (25+20+17)	58 min. (25+20+13)		
*The total time includes: vacuum, pre-heating time, cycle and drying phase.					

The times are to be intended for a fully loaded autoclave All sterilization cycles have 3 stages of vacuum

/acuum and pre-heating time can vary depending on the conditions of autoclave from

TECHNICA	AL SPECIFICATIONS	
	35653	35657
	Europa B - 15 l	Europa B - 24 I
External size mm (WxHxD):	510x390x590	510x390x730
Chamber size mm (Øxdept):	245x320	245x500
Operating voltage	230V - 50/60 Hz	230V - 50/60 Hz
Max absorbed power	1,700 W	2,200 W
Weight kg:	54	58
Built in printer:	yes	yes
Manual closing:	yes	yes
Fitting for pura deioniser:	yes	yes
PID system	yes	yes

### ANDROMEDA VACUUM XP AUTOCLAVE WITH PRINTER 15-21 LITRES



Pre-and post-vacuum: Andromeda Vacuum is provided with powerful vacuum pump which, at the beginning of the cycle, ejects the airpockets from the sterilization chamber, and at the end of the sterilization phase ensures a very good drying. Rapid preheating: A very new method of preheating, through a special band heating element, gives a high reduction of the preheating times.

Guaranteed sterilization: A sophisticated electronic device gives a constant monitoring of pressure, temperature and time. In case of anomalies there will be an electronic lock of the autoclave and the display will indicate the anomaly.

### **TECHNICAL SPECIFICATIONS** External size: 45x39x54 cm (35651), 45x39x66 cm (35662) Chamber dimension: Ø 24.5x32 cm depth (35651), Ø 24.5x43 cm depth (35662) Weight: 50 kg Operating Voltage: 230 V - 50/60 Hz Power consumption: 2000 Watt Made in Italy Class S Cycles

Andromeda Vacuum is provided with 5 cycles of sterilization: 121° C and 134° C for unwrapped and wrapped instruments, and a "Flash" cycle for the fast sterilizations

Cycles	Temperature	Max load	Pressure	Total time*
Program 1 Unwrapped instruments	134° C	2.8 kg	2.2	33
Program 2 Wrapped instruments	134° C	2.8 kg	2.2	38
Program 3 Unwrapped instruments	121° C	2.8 kg	1.2	42
Program 4 Wrapped instruments	121° C	2.8 kg	1.2	46
Program 5 Flash	134° C	2.8 kg	2.2	16

\* pre-heating - vacuum - cycle - drying in vacuur User manual available in English, French, Spanish, Italian, German

• 35652 THERMAL PAPER 60 mm x 25 m

operator presence as all functions are automatic. At the end of each cycle a special device eliminates the backwater of condensate, afterwards there is the automatic

sign off, but with electronic storage. Safety of the operator: Andromeda Vacuum has an electromagnetic block device on the door. The door opens only with atmospheric pressure into the chamber, and after having

pressed the push button. Completely computerized monitoring of all automatic functions, and auto-diagnosis of each component. The total automation of each phase of the cycle prevents any possible

human error, also from inexperienced personnel Timed start, with positioning in "Stand-by" at 80°C and automatic switch off

Automatic filling up of the water: a pump allows the filling up, and stops automatically when the maximum level is reached



35671 SEALING GASKET - for Andromeda and Europa

• 35672 BACTERIAL FILTER - for Andromeda and Europa

• 35673 VAPOR LINE STERILIZATION INTEGRATOR

- for Andromeda and Europa

### DISTILLER: SYSTEM OF WATER DISTILLATION



• 35690 WATER DISTILLER

The autoclaves must run with distilled or demineralised water to avoid problems on electrovalves and on internal mechanism and white traces of limestone on the sterilized tools and devices. Distiller produces 100% distilled water in a cheap and safe way. It produces 4 litres in about 7 hours.

It is equipped with an automatic control thermostat with block system at the end of operation.

Supplied with 6 active coal filters, 1 detergent, 1 container for produced distilled water. Operating Voltage: 220 V - 50-60 Hz.

• 35691 COAL FILTERS FOR DISTILLER - box of 12

• 35692 DETERGENT FOR DISTILLER

### DIGITAL SEALING MACHINES WITHWITHOUT DOT MATRIX PRINTER



• 35909 D-400 SEALING MACHINE without printer • 35910 D-500 SEALING MACHINE with dot matrix printer Continuous sealing machines for medical pouches according to DIN rules 58953-7:2010 with or without dot matrix printer. They allow a 12 mm multi-line seal and features stand-by function and automatic infeed through photocell. D-500 is equipped with **built-in printer** to print different data on the bag (sterilization/expiry dates) during the sealing process in order to provide constant control on the sterility of your instruments, especially when the paper layer of the

sterilization bag is less tight, after 30 days, and consequently losing instruments sterility. Built in epoxy coated stainless steel. D-400 and D-500 are sophisticated units controlled by a microprocessor and equipped with a device to adjust temperature (displayed by LCD) and printing parameters. The sealing pressure is automatically adjusted according to the material thickness. It also guarantees 30 mm safety distance between seal and product.

according to DIN rules. Easy to use and maintenance-free, they are the ideal solution for clinics and hospitals. Compatible for sealing with Tyvek rolls and envelopes. Made in Italy.

• 35912 INK-CARTRIDGE D-500/700 - spare part

	TECHNICAL S	PECIFICATIONS	
	35909		35910
nfeed speed	-	6 m/min	
Temperature control		<ul> <li>by digital thermoregulator-</li> </ul>	
Sealing temperature	40°÷200° C		40°÷180° C
Temperature tolerance	-	±5°C	
ieal	-		
Seal width	-	12 mm	
Adjustable free edge		0 ÷ 30	
Power supply	-	230 V-50 Hz-single phase	
Absorption	500 W		600 W
Dimensions	-		
Net weight	11.5 kg		12 kg

### SEALING MACHINES WITH VALIDATION SYSTEM



• 35915 D-600 ROTARY HEAT SEALER - without printer • 35916 D-700 ROTARY HEAT SEALER - with printer

With validation system complying with ISO 11607 P.2 rule. GIMA 600 and GIMA 700 have been designed to continuously monitor, during the whole sealing phase, all critical process parameters: Temperature, Speed, Pressure. They guarantee sealing in full respect of EN 868-5 / ISO 11607 P.2 rules, provide real-time monitoring of working temperature, applied force

and running speed, time used during the sealing process. All sealing data can be recorded on an external carrier which can be linked to the sealer through a USB port placed on the unit. They are controlled by a microprocessor. Operator's interface is a clear 2 line display, integrated in an ergonomic keyboard placed at the upper side of the sealer in an extremely user friendly position. Simple use, high reliability, they are the ideal solution for hospitals and clinics. Compatible for use with Tyvek rolls and envelopes. Made in Italy.

• 35912 INK-CAKTRIDGE D-500//00 - spare					
AL SPECIFICATIONS	5				
35915	35916				
12 mm	12.5 mm				
——m	ultiline				
6 m/min	8.5 m/min				
<b>⊢</b> ——10-20	00°C ± 5 °C				
yes	yes				
yes	yes				
yes	yes				
6 characters	8 characters				
yes	yes				
yes	yes				
yes	yes				
230 V / 50 Hz - single-pl	hase (on request 110 V, 60 Hz)				
500 W	500 W				
⊢473x235x1	81 mm - 12.5 kg→				
	AL SPECIFICATION: 35915 12 mm				

### STEAM AND DRY HEAT ADHESIVE TAPE INDICATORS



STEAM AND DRY HEAT TAPE INDICATORS


Gima range of tapes is specially formulated for packing purposes as well as to show visibly that the pack has undergone a sterilization cycle. The backing of the different tapes is made of strong, semicreped, impregnated paper which gives excellent conformability during the application. Sterile tapes unwind easily and can be torn by hand without

Special adhesives formulated to withstand high temperature and humidity ensure excellent bond to paper, plastic, nonwovens, board, metal, glass and linen.

Each tape is individually packed with due date. Made in Italy.

TAPE INDICATOR - 50 m	Width 19 mm	Width 25 mm	Minimum order	
Dry Heat Tape - hot air sterilizer	35842	-	12 rolls	
Steam Tape - autoclave	35846	35847	12 rolls	

### D-351 SEALING MACHINE: ELECTRO-MAGNETE OPERATION



Compact impulse medical sealers, conform to DIN 58953 P.7 rules, specially designed to be used in medical, dental, oculistic surgeries and

• 35900 D-351 IMPULSE SEALING MACHINE

Main features: sealing and cutting length 35 cm - Safety check with alarm. Main board with temperature control to avoid overheating of the sealing wire - Sealing bars closed by electromagnet. Complete with foil-roll dispenser and built-in cutting device.

Easy: by the pressure of only one finger, without using levers, the bars close automatically. The electro-magnet guarantees a steady sealing pressure for the whole set period. The sealing bar opens automatically at the end of the cycle, requiring no action by the operator.

Quick: the electro-magnetic system allows a substantial saving of the packing time. Quick foil feeding.

Safe: the machine does not start the sealing cycle if there is an object with a thickness over 3 mm between the bars. The electronic temperature control through a NTC probe provides a perfect temperature accuracy from seal to seal. The electronic alarm function avoids any overheating. Made in Italy.

• 35902 TEFLON - spare • 35903 RESISTOR - spare

### **TECHNICAL SPECIFICATIONS**

Sealed materials: paper/polyethylene/polyester Sealing length: 350 mm Sealing width: 8 mm as per DIN 58953-7:2010 Electronically controlled sealing time: 0.5 sec. Cutting length: 350 mm Foil-roll dispenser 350 mm Power: 230V- 50/60 Hz single - phase

Max absorption: 700W, only during the sealing time Dimensions: 44x17 5x31 cm Weight: 18 kg Built in accordance with CE Norms

GD-301 EVO SEALING MACHINE FOR CONTINUOUS HEAT SEALING



### TECHNICAL SPECIFICATIONS

Flat sealing 12 mm Sealing length 300 mm Thermo controlled continuous heat sealing Built-in cutting device

Fixed sealing temperature and sealing time Power 230 V / 50-60 Hz, single phase Manual actuation Electrical input: 900 W Protection degree IP 20

Sealer dimensions 452x248x146 mm Roll-holder dimensions 458x412x242 mm • 35928 GD-301 EVO SEALING MACHINE - machine only • 35929 GD-301 EVO SEALING MACHINE - complete

Manual heat sealer for medical pouches and reels according to DIN 58953-7:2008. New models with **3 ceramic heater** elements for a faster and more accurate sealing and improved infeed and outfeed guide to keep film flat (infeed) and prevent the film moving upward inside machine.

Available in 2 versions: compact without accessories (35928) or with sealer roll holder, cutter and plane (35929) User friendly, reliable and extremely compact, ideal in dentistry, medical and veterinary laboratories. Sealing bar 300 mm manually actuated by a lever. Thermo controlled continuous heat sealing, to save consumables. Compact vertical design to reduce space at the minimum. Integrated, removable roll-holder, can stand alone apart from the sealer.

Usable only with polypropylene film coupled to medical grade paper and/or plastic envelopes suitable for steam sterilization.

• 35933 CERAMIC HEATING ELEMENTS - spare • 35935 BLADES kit of 5 - spare 35928

### **TESTS FOR AUTOCLAVE**



Notice "Sterilisé" and three stars drawing change colours from white to dark brown to show safe sterilization of 121°C - 15 minutes or 134°C - 3.5 minutes

EN 867 - Class D box of 1,000

ISO 11140 - Class 6 Indicator for sterilization by autoclave with pressure 1 to 2 bar 120°C/135°C. No special stocking requirements. Safety and reliability. Made in Japan.

• 35849 "STEAM STAR" INDICATOR - autoclave -

### **BOWIE & DICK TEST READY FOR USE**



Test sheet Test sheet Test sheet after sterilization before after sterilization

Correct test

Failed test

• 35853 UPSTAR - "BOWIE & DICK" - test - 14x14x0.8 cm The Bowie & Dick ready to use test pack is designed to control the proper functioning of steam autoclave and to test its ability to sterilize porous devices (compresses, fields, gowns, woven or non-woven,...).

High sensitivity: detects any default.

Easy interpretation.

 Stability of color change. - Waterproof aluminium packaging

EN 867 - Class B ISO 11140 - Class 2

### ROLLS FOR AUTOCLAVE, STEAM AND ETO



### **OTHER SIZES AVAILABLE**

FLAT ROLLS for sterilization by steam or ethylene oxide gas Flat rolls consist of transparent, polyester-polypropylene film coupled to medical grade paper which permit steam and gas penetration during sterilization. Steam and gas indicators provide clear colour changes when exposed to sterilization process. Each roll is 200 m long.

	FLAT ROLLS FOR AUTOCLAVE, STEAM AND ETO						
GIMA code		External m x mm	Internal m x mm	Minimum order			
35810	Flat rolls	200x50	200x36	8 rolls			
35811	Flat rolls	200x75	200x53	8 rolls			
35812	Flat rolls	200x100	200x78	4 rolls			
35813	Flat rolls	200x150	200x128	4 rolls			
35814	Flat rolls	200x200	200x178	2 rolls			
35817	Flat rolls	200x250	200x228	2 rolls			
35815	Flat rolls	200x300	200x278	2 rolls			
35816	Flat rolls	200x400	200x378	1 roll			

GUSSET ROLLS FOR AUTOCLAVE, STEAM AND ETO						
GIMA		External	Internal	Minimum		
code		m x mm x mm	m x mm x mm	order		
35871	Gusset rolls	100x100x25	100x78x25	4 rolls		
35872	Gusset rolls	100x150x25	100x128x25	4 rolls		
35873	Gusset rolls	100x200x30	100x178x30	2 rolls		
35874	Gusset rolls	100x250x32.5	100x228x32.5	2 rolls		
35875	Gusset rolls	100x300x40	100x278x40	1 rolls		
35876	Gusset rolls	100x400x40	100x378x40	1 rolls		

**GUSSET ROLLS for sterilization by steam or ETO** Made with coated film PET 12/PP 40 green and 60 g medical white paper.

For sterilization of voluminous objects. Each roll is 100 m long.

### FLAT AND SELF-SEAL POUCHES FOR AUTOCLAVE



**SELF-SEAL POUCHES** for sterilization by autoclave, steam or ethylene oxide gas

Self-seal pouches consist of light green, polyester-polypropylene transparent film coupled to medical grade paper which permit steam and gas penetration during sterilization.

Steam and gas indicators change colour when exposed to sterilization.

- 1. Reinforced corners to prevent dust from collecting near to the opening, reducing the risk of contamination during
- 2. The laminated transparent film complies with the German standard EN 10/204. The medical paper conforms to the following standards: DIN 58953 (German), Pharmacopoeia 589 (French), pr EN 868-3 (European) and BS 6256 (English).
- 3. The chevrons allow rapid and correct opening.

4. These consist of one layer of laminated transparent film (special type polyester and copolymer polypropylene) and white damp-resistant medical Kraft paper, specially designed to assure a high anti-bacterial protection.

5. The heat-sealed lines (Multiline) are highly resistant and spaced equally; the external welding runs along the entire length of the pouch.

Reels and pouches are certified and are manufactured according to international standards DIN 58953 BS 6871. EN 868-5, CN 13485

### **OTHER SIZES AVAILABLE** minimum 10.000 pouches

	FLAT POUCHES FOR AUTOCLAVE, STEAM AND ETO								
GIMA		External	Internal	Minimum					
code		mm	mm	order					
35880	Flat pouches	100x300	78x285	1,000					
35881	Flat pouches	150x200	128x185	1,000					
35882	Flat pouches	150x250	128x235	1,000					
35883	Flat pouches	150x300	128x285	1,000					
35884	Flat pouches	150x400	128x385	1,000					
35885	Flat pouches	200x300	178x285	1,000					
35886	Flat pouches	200x350	178x335	500					
35887	Flat pouches	200x400	178x385	500					
35888	Flat pouches	250x400	228x385	500					
35889	Flat pouches	250x500	228x485	500					
35890	Flat pouches	300x400	278x385	500					
35891	Flat pouches	400x600	378x585	500					
35895	Special size pouches			10,000					

SELF-SEAL POUCHES FOR AUTOCLAVE, STEAM AND ETO								
GIMA code		External mm	Internal mm	Minimum order				
35860	Self-seal pouches	90x165	68x150	1,800				
35861	Self-seal pouches	90x230	68x215	1,800				
35862	Self-seal pouches	140x250	118x235	1,200				
35863	Self-seal pouches	190x330	168x315	1,200				
35864	Self-seal pouches	190x400	168x385	1,200				
35866	Self-seal pouches	300x450	278x435	400				

### BOWIE DICK TEST PACK

GB, IT, ES, FR, PT GR DF



### • 35950 BOWIE DICK TEST PACK - box of 20 pcs

Used for daily monitoring of pre-vacuum steam sterilizer. Based upon the Bowie Dick test result the steam sterilizer is released for usage during the day. The Bowie Dick test detect failures like air leaks, insufficient vacuum, inadequate steam penetration.

- fulfill requirements of EN 285 and ISO 17665 conform to ISO 11140 4 Type 2 / EN 867 4 class B
- (EU standard 7 kilo)
- independently tested to show performance similar to original pack
- clear blue violet colour change - easy to interpret and document
- non-Toxic / lead free


### TYPE 5 MOVING FRONT

Conform to ISO 11140 type 5



User manual GB. IT. FR. ES.





Package and manual in: GB, IT, FR, ES, PT GR DE

Non-toxic / lead free

### 35952 TYPE 5 MOVING FRONT INTEGRATOR box of 1,000 pcs Moving front integrators 134 °C - 3.5 min are giving you the best interpretation possible in case of any failure in your steam sterilization cycle. If temperature is not reached or holding time was too short the dark colour will not reach the accept area.

- shelf life: 5 years after production - packed in white aluminium re.closable bags
- very easy interpretation of result
- complete indicator area sealed of by foil

### TYPE 4 STEAM INDICATOR







two separate pieces for economical use.







### • 35954 TYPE 4 MULTI-VARIABLE STEAM STRIPS - box of 250 dual strips Type 4 multi-variable steam indicator strips are designed to be used in steam sterilizers operating at 134 °C - 3.5 min. The indicator strips will provide assurance of steam penetration into the packs. The water based, non-toxic chemical indicator in compliance with ISO 11140-1 will show a clear colour change from blue to black after successful steam sterilization. Test indicator strips are cost effective and can be divided into

### TYPE 6 STEAM INDICATOR



• 35955 TYPE 6 EMULATING STEAM STRIPS - box of 250 strips Type 6 emulating steam indicator strips are designed to be used in steam sterilizers operating at 121 °C - 15 min and 134 °C - 3.5 min. The cycle verification indicators can be used in every pack and will provide assurance of steam penetration into the packs and presence of all critical parameters of steam sterilization cycle.

The water based, non-toxic chemical indicator in compliance with ISO 11140-1 will show a clear and accurate colour change from blue to lilac after successful steam sterilization.

### **BOWIE DICK HELIX TEST**



### • 35951 BOWIE DICK HELIX TEST PACK - box of 100 pcs

Helix devices and their indicators have proven that they detect failures during each cycle much earlier than other chemical indicators / integrators. The EN 285: 2009 are specifying the Helix test (Hollow A) to be used as Bowie Dick Test as well as Batch Monitoring when hospitals are sterilizing hollow loads, Next to that this Bowie Dick Helix Test is an obligatory test for class B Bench Top Steam sterilizers.

- conform to ISO 11140 1 Type 2 EN 867 part 5 class B
- clear transition of color into pink
- easy to interpret and document
- non-Toxic / Lead Free
- PCD guaranteed for 500 Cycles (134°C 3,5 min)

### TYPE 5 STEAM INDICATOR

ISO 11140



• 35953 TYPE 5 STEAM INTEGRATOR - box of 500 pcs Integrators can be used in addition to the batch control Helix which allow to release load. It allow to re-affirm sterilization condition inside trays or containers. SV: 134 °C - 3.5 min / 121 °C - 15 min

- shelf life: 5 years after production
- packed in an easy dispensing carton
   clear colour transition from blue into pink of lacquer covered

### TYPE 5 EO INDICATOR











assurance of E.O. gas penetration into the packs. The water based, non-toxic chemical indicator in compliance with ISO 11140-1 will show a clear colour change from white to yellow after successful sterilization. Test indicator strips are cost effective

and can be divided into two separate pieces for economical use.

### SEAL CHECKER



Suitable for all rotary heat sealers

### • 35957 SEAL CHECKER - box of 250 pcs

The ISO-11607 standard is specifying a routine, daily check of vour heat sealers.

The seal checker is a way to perform the test required and to document which sealer, which day, which person did perform the test and to easily show results of your heat sealer capacity of properly heat seal your pouch.

When place inside a pouch and seal, the sealed area will be darker and can be easily read whether the seal is consistent, regular and completely without any gaps.


### PILL MANAGERS VET PRODUCTS



PILL PULVERIZERS See page 81.

- CLOGS See page 24-25
- TOURNIOUETS See page 56
- SCALPELS and BLADES See page 41
- THERMOMETERS See page 75-78
- VFT BAGS See page 57-60
- TROLLEYS See page 113-123
- BANDAGES, GAUZES, PLASTERS See page 336-342
- BARRYCIDAL 30 PLUS DISINFECTANT See page 351

### BIOPSY PUNCHES



**DERMAL CURETTES** See page 42.

### **SURGICAL CLIPPER** SUTURES



SURGICAL CLIPPER See page 42.

# Clinibut

SUTURES AND SKIN STAPLER DEVICE See page 39-40.

### **SUCTION UNITS**



SUCTION UNITS See page 161-164.

### ELECTROSURGERY



**ELECTROSURGICAL UNITS** See page 181-186.

### **ELECTROSURGERY**



**ELECTROSURGERY ACCESSORIES** See page 187-192.

### HEADLIGHTS



### **EXAMINATION LIGHTS**



HALOGEN AND LED EXAMINATION LIGHTS See page 199-205.

### 3M LITTMANN® STETHO



3M LITTMANN® CLASSIC II 3M LITTMANN® CARDIOLOGY See page 235-238.

### SURGEON BRUSHES



**SCRUB KIT** CHLOREXIDINA SCRUB KIT IODO-POVIDONE SCRUB KIT See page 350.

### **DIGITAL PET SCALES** FOR LARGE AND SMALL ANIMALS



80210 DIGITAL VET SCALE - metal platform

• 80211 DIGITAL VET SCALE - stainless steel platform High reliable and professional full electronic scale. Robust platform with a separate LCD digital display. Overload and low battery function. Switchable kg/lb/st. Made in Europe.

• 80216 AC POWER

TECHNICAL SPECIFICATIONS Capacity/Sensitivity: 300 kg / 100 g Platform size: 600x800 mm

Minimum measurable: 2 kg Power: 9 V alkaline batter



27266 SOEHNLE 8320 FOLDABLE SCALE

27271 CARRYING BAG

Foldable scale with magnetic lock for easy transport.

TECHNICAL SPECIFICATIONS

Capacity: 15 kg Dimensions: 395x315x105 mm (closed) - 740x315x53 mm (open) Alkaline battery 2x1.5V AAA - not included

Warranty: 2 years Made in Germany ninns 4

• 27258 DIGITAL PET SCALE - medium • 27259 DIGITAL PET SCALE - large

Precise full electronic multifunctional scale, designed for measuring your pet's weight available in two sizes. Quality product with very competitive price. Minimal measuring weight: 2 kg. Made in Europe.



• 27261 DIGITAL SMALL PET SCALE

**TECHNICAL SPECIFICATIONS** 

Minimum measurable weight: 20 g (27261), 2 kg (27258-27259) 355x635 mm (27258) - 620x830 mm (27259) Dimensions: Automatic switch-off Lithium battery

20 kg / 10 g (27261) - 100 kg / 100 g (27258-27259)

### DIAGNOSTIC AND OPERATIVE VETERINARY TABLES



80300 VETERINARY EXAMINATION TABLE

Veterinary operating table with enamelled tubular steel frame, with AISI 304 15/10 stainless steel top with hole and a liquid tray holder underneath. Lateral hook to immobilize animals.

### S/S INSTRUMENTS






Veterinary operating table with electric lift (82/102 cm), baked

enamelled steel tubular frame and AISI 304 stainless steel top (120x56 cm) with hole and a liquid bucket holder underneath. Manual Trendelenburg 15° and Antitrendelenburg up to 15°. Lateral hook to immobilize animals. Made in Italy.

### URINE STRIPS

• 24100 VETERINARY URINE STRIPS 11 parameters - bottle of 100 strips For examination of glucose, ascorbic acid, ketones, protein, ph-value, blood, nitrite, leukocytes,





quality standard Made in Germany

366

### **VETERINARY ECG - 1 OR 3 CHANNEL**

- 33305 VE-100 1 channel ECG
- 33306 VE-300 3 channel ECG
- 33336 ECG-Viewer software (GB, IT, FR, ES, RU, PT, PL, TU) for 33306
- complete digital design
- LCD display waveforms, parameter configuration
- high resolution thermal printer
- built in rechargeable Li-Ion battery for 6.5 hours use (AC/DC supply)
- complete digital filter, avoid baseline drift, AC, EMG interfere
- baseline automatically adjustable, optimizes printing position

### - selectable auto/manual operation Features of VE-300 only

- 12 leads simultaneous acquisition - automatic ECG parameter measu-
- rement and analysis - support USB ink-jet printer for 12 leads printing
- 120 patient data storage and transfer by USB flash disk, Ethernet or series port
- review and management of ECG data on Window PC with software (optional 33336)

Internal software: GB, IT (33305/6), DE, FR, ES (33305 only)

- 32963 THERMAL PAPER ROLL 50mm x 25m for 33305
- 32964 THERMAL PAPER ROLL 80mm x 25m for 33306 • 33318 RE-CHARGEABLE LITHIUM BATTERY 2200 mAh
- 33319 5-LEAD VETERINARY ECG CABLE spare

### STANDARD ACCESSORIES

5-lead veterinary ECG cable (Ø 4 mm, banana connector, IEC) Veterinary clip electrodes (set of 5, match Ø 3-4 mm ECG cable)

Rechargeable lithium battery (2,200 mAh)

N ver ecs w 

### TECHNICAL SPECIFICATIONS

33306 standard 12 lead One lead 12 leads simultaneously 0.05 Hz ~ 150 Hz

Acquisition mode Frequency response 2.5, 5, 10, 20 (mm/mV)

nput impedance  $\geq$  50 M $\Omega$  (10 Hz) EMG Filter 35 Hz (-3dB) EMG Filter 25/35/45Hz / OFF AC/DFT Filter 50/60Hz (-20dB) DFT Filter 0.05/0.15/0.25/ 0.32/0.5/0.67 Hz

Low pass Fliter 150/100/75 Hz AC Filter on/off
Auto/Manual/Rhythm/OFF/USBPRT

Recording mode Auto/Manual IEC I/CF AC: 100-115 V, 220-240 V, 50/60 Hz Safety standard Power supply

Built-in rechargeable Li-ion battery: voltage 14.8 V
More than 6.5 hrs, continuously operation under battery supply
50 mm x30 m
80 mm x20 m Thermal paper

50 mm x30 m 80 mm xzu m 5/50 mm/s (± 3%) 5/6.25/10/12.5/25/50 mm/s (± 3%) 300x260x75 mm 2.3 kg (with battery) 2.5 kg (with battery) 192x64 pixel LCD 192x64 pixel LCD Paper speed Size 2.3 kg (with battery) 2.5 kg (with battery) 192x64 pixel LCD 192x64 pixel LCD 192x64 pixel LCD 19 mpt ≥ 100 kΩ; Sensitivity: 10 mm/V ± 5% output: ≤100 kΩ; Sensitivity: 1 mm/V ± 5% face R523 Ethernet, R5232, USB Weight Display

External input/output Communication interface

### BM3 AND BM5 PORTABLE MULTIPARAMETER VET MONITORS

Lead

Sensitivity

VF-300 data transfer



• 33719 BM3 VET MONITOR - 7" TFT display • 33779 BM5 VET MONITOR - 10.4" TFT display

Versatile, portable, lightweight, BM monitors are designed to be used in veterinary environment.

Compact design and handle make it easy to move Colour monitor displays all vital signs in different colours for

easy recognition. A built in printer offers hard copy documentation of all

measured values. Alarms and settings are easily adjustable.

See all specifications and accessories at page 290, 293.

• 33772 RECTAL TEMPERATURE SENSOR - 2.75 m cable

• 33741 EXACON RECTAL TEMPERATURE SENSOR - 2.75 m cable

ECG+SpO<sub>2</sub>+NIBP +RESP+TEMPERATURE +2IBP (only 33779)

### VETERINARY DOPPLER

### • 80600 GIMA VET DOPPLER - FIXED 8 MHz probe

New doppler for detecting blood flow in small peripheral vessels with its unique 8 MHz probe ideal for veterinary practitioners for routine blood pressure measurement on pets. Flow signals are easily located using the lightweight narrow beam transducer while internal signal processing minimizes noise artefacts.

	TECHNICAL	SPECIFICA
rasound		Power

8 MHz continuous wave Frequency Transducer: 2 crystal narrow beam Output power:<15 mW/cm2 SATA Audio Response: 300 Hz - 4 kHz Unit Controls 1 key (for unit on/off) Controls rotary volume Indicators: yellow battery low LED

Power supply
Battery 9V Alkaline (not included) Expected battery life: >9 hours Output Headset: Audio output for optional

headset (not included) Material: ABS / Noryl Size: 150x75 mm 299 g (with transducer) Classification: Class I Type B - IEC 60601-I



- Chroma

- AIO (Automatic

Image Optimization)

### CHISON ECO1 AND ECO3EXP. VET DIGITAL ULTRASOUND SYSTEMS



Value Deyona imagi	1112
STANDARD PACKAGE  ECO1 ECO3EXP. ECO5	
12" high resolution LED monitor - B&W	
12" high resolution LED monitor - colour	
BG memory card	
Hot Key ● • •	
PC printer connection • • •	
B USB port • • •	
1 ethernet port • • •	
1 video out port, 1 VGA out port	
1 footswitch port • • •	
Full screen display • • •	
2 hours rechargeable lithium-ion battery optional • •	
Power adaptor • • •	
Standard software package • • •	
Easy View image archive system	
[HI • • •	
PW (doppler function to detect blood flow speed)	
TECHNICAL SPECIFICATIONS	
Dimension and weight: 33.5x15.5xh 35 cm (13.2"x6.1"xh 13.8"); 6 kg Display: 12" LED, high resolution 1,024x768	
Display: 12" LED, high resolution 1,024x768  Power: AC 100-240 V - 50/60 Hz	
rechargeable lithium-ion battery (ECO1 option, ECO3EXP. standard)	
LANGUAGE - switchable by user	
GB IT FR ES DE CZ TR CN RU	
db II FR E3 DE CZ IR CN RO	Ш

12" LED monitor

**CHISON** 

Software

Dicom 3.0

User manual

ECO5 VET

- 33994 CHISON ECO1 VET with 1 probe connector without probe • 33995 CHISON ECO3EXP. VET with 2 probe connectors without probe
  - ultra-compact and ultra-light weight, easy to carry
  - latest LED screen technology, super bright images allow to easily view scan even outdoor.
  - ergonomic monitor design, 30 degree rotation, adjustable. - ultra-long battery life up to 2 hours, for outdoor scanning
  - one-key to enlarge image to full screen, easy to view from distance - streamlined workflow, easy to operate, 6-one-key to finish the cycle of diagnosis.

### Display modes and imaging processing

B. B/B. 4B. M. B/M. PW (ECO3EXP. only) multi-frequency imaging Imaging processing - trapezoidal

- compound Imaging
- I-image intelligent image optimization automatic PW trace - THI (Tissue Harmonic Imaging) (ECO3EXP. only)
- SRA (Speckle Reduction Algorithm) - full digital beam-former - full screen display
- User interface

CHISON

- fold-up control panel and alphanumeric keyboard - back-lit keyboard for good visibility in dark room
- interactive back-lighting
- indicator lights identify activated keys
- 8 TGC slides for easy adjustment
- short cut knob for quick adjustment (hot key user- defined)
- neat and clear keyboard layout, doctor can remember easily - user defined preset

### Streamlined workflow, one key to:

- select desired application with automatic preset
- optimize the image automatically (AIO) - Make report
- save still image and CINE loop - Measure
- print to PC printer\* (laser or inkjet) or video printer ee list of compatible printers on our website

### EASYVIEW™ Archive system

- image archive on hard disk and USB mobile storage - 3 USB ports
- multiple image formats: BMP, JPG, DCM, CIN, AVI cine review: auto, manual (auto review segment can be set)
- for 2D, M, PW (ECO3EXP. only) images

### - cine memory capacity (256 frames/10s)

### CHISON ECO5 VET COLOUR DOPPLER DIGITAL ULTRASOUND SYSTEM

• 34008 CHISON ECO5 VET Colour Doppler 12" high resolution colour LED monitor, 8G high speed memory, 3 USB ports, 2 probe connectors, EASYVIEW™ archive system, without probe Imaging model: B, B/B, 4B, B/M, M, CFM, PW

### Imaging processing:

- MCI (Multiple Compound Imaging) - trapezoidal
- i-image intelligent image optimization automatic PW trace - Chroma
- THI (Tissue Harmonic Imaging)
- SRA (Speckle Reduction Algorithm) - full screen display model - full digital beam-former - AIO (Automatic Image Optimization)

Rechargeable lithium-ion battery

### Other specifications as ECO3EXP.

**TECHNICAL SPECIFICATIONS** 

Dimension and weight: 33.5x15.5xh 35 cm (13.2"x6.1"xh 13.8"); 6.5kg 12" LED, high-resolution colour 1,024x768 AC 100-240 V, 50-60 Hz Display:

### PROBES AND ACCESSORIES FOR CHISON ECO SERIES

PROBES ECO1 - 3 - 5			FREQU	JENCY(MHz)	Hz) • Main application		1		
GIMA code	CHISON code	Scanning method	Main freq.	Probe band width	CANINE	FELINE	OVINE	EQUINE	BOVINE
33998	C3-A	Convex	3.5	2.5 - 5.0			•	•	•
33999	L7M-A	Linear*	7.5	5.3 - 10.0	•	•	•	•	•
33871	L7S-A	Linear**	9.0	5.3 - 11.0	•	•	•	•	•
34000	L7V-A	Trans-rectal	7.5	5.3 - 10.0			•	•	•
33997	MC6-A	Micro-convex	6.0	4.5 - 8.0	•	•			
33874	MC3-A	Micro-convex	3.0	2.5 - 5.0	•	•	•	•	•
'With 40 i	nm footpri	nt, general linear pi	robe						

"With	30 mm	footprint	for superficial	tissue exams with	higher resolution

GIMA code	ECO SERIES ACCESSORIES
33869	Rechargeable lithium-ion battery BT-2500 (2.5 hours)
	ECO trolley TR-9000
33868 33866	Carrying case  Needle guided brackets - specify for which
55000	Needle guided brackets - specify for whic probe (available for 33998-9, 33874 only
	PRINTERS
33968	SONY UP-X898 MD B&W printer
	33869 33867 33868 33866

(for ECO1 and ECO3EXP.)
33993 SONY UP25MD colour printer(for ECO5)



### HANDHELD VET PULSE OXIMETER



### • 34343 OXY 100 VET PULSE OXIMETER

OXY 100 Handheld Pulse Oximeter can measure oxygen saturation (SpO<sub>2</sub>) and Pulse Rate (PR) by placing the sensor on a certain part of the animal, such as tongue, ear, leg or tail. It also provides plethysmogram, bar-graph and Perfusion Index display.

- lightweight, small and easy to handle
- data storage with trend review
- two options for measurement on: thin tissue: such as tongue, ear. thick tissue: such as leg, tail.
- up to 384 hours of data memory (with 1/2/4/8 sec. recording interval) - audible & visual alert for over-limits (limits are adjustable). Tested for cats and dogs. Not suitable for big or very small animals. See technical specifications page 297 Oximeter is supplied with universal "Y" type SpO, probe and three types of adapters: big clip, small clip and rubber wrapper. Each of these adapters allows a different measuring respectively on tongue, ear, leg or tail.

  • 34346 UNIVERSAL "Y" type SpO<sub>2</sub> probe - spare
- includes 3 probe adapters (big clip, small clip, rubber wrapper).

### VETA ELECTRONIC SPHYGMOMANOMETER AND SpO 80550 VET ELECTRONIC SPHYGMOMANOMETER

Electronic sphygmomanometer with fully automatic measurement of animals blood pressure and large, high definition colour LCD display.

- data storage for up to 100 groups of data with date and time
- automatic one-touch operation
- alarm function with possibility to set alarm limits
- dual scales: kPa and mmHg
- selection of five cuff sizes: small, small/medium,
- medium, large, X-large
- automatic power off
- optional SpO, probe with clip for tongue or ear Supplied with medium cuff (10-19 cm) and

### multilanguage manual (GB, FR, IT, ES, PT) TECHNICAL SPECIFICATION'S SPO

SpO<sub>2</sub> range: 0-100% (resolution 1% SpO<sub>3</sub> accuracy: 70%-100%: ± 2%

PR range: 30bpm-250bpm, (resolution 1bpm) PR accuracy: (select larger)

)	GIMA code	ACCESSORIES
		Power adaptor
	80557	SpO <sub>2</sub> probe - optional
	00550	Extension cable for 9055

GIMA code	CUFFS	Size	Suitable for	
80551	Small	6-11 cm	Cats, baby dogs,	
80552	Small/medium	10-19 cm	Small dogs, fox, sheep	
80553	Medium	18-26 cm	Baby horses, baby pigs, big dogs, deers	
80554	Large	22-32 cm	Horses, pigs, puma, baby bears, lions	
80555	X-Large	33-47 cm	Bears, lions, tigers	

Display: 2.8" colour LCD screen
Power: four "AA" batteries or optional power adapter

Inflation - Deflation: automatic inflation - automatic multistep deflation

25588

TECHNICAL SPECIFICATIONS SPHYGMO

Accuracy: static pressure: ±0.4 kPa (±3 mmHg)

Safety: class II device type BF applied part Dimension - Weight: 130x110x80 mm - 300 g

Measurement method: oscillomet Measurement range: 0-38.67 kPa (0-290 mmHg)

Resolution: 1 mmHg

### • 32545 REGALITE VET - black

Top quality single head stethoscope. Patented multi-frequency "ring-oraised™" diaphragm system. Chromed plated chestpiece with "SUPERFLEX" inner spring binaural and 1 piece moulded PVC, latex free, tubing 90 cm long. Supplied in deluxe box, with spare soft eartips and one spare diaphragm.



### VET STETHOSCOPE 🔲 DIGITAL THERMOMETERS

### • 25588 VET RECTAL THERMOMETER

Designed to be ergonomically correct for animals. Setting for pets, pigs, cattle and other animals.

• 80450 VET DIGITAL THERMOMETER - flexible tip LCD size 15x7 mm



### • 80455 THERMOFOCUS® ANIMAL NON CONTACT THERMOMETER Infrared non contact thermometer allows to take pet's body

temperature at distance from its eye. MQCS function allows manual calibration in case veterinary is moving to different environments. Thermofocus® animal is suitable for all animals and is multipurpose (can take temperature of liquid, food, ...). Made in Italy.

**ECHNICAL SPECIFICATIONS** 

	Measurement range:	
	Accuracy:	3
	Battery life is approx.	
į	Dimension:	
	Battery:	

25588 32~44°C Measurement time:

0.1 °C (35~39°C) 5.000 readouts 190x110x35 mm 138x21x10 mm 2x1.5V AAA 1.5V LR41

80450 32~42.9 °C 32~43.5 °C ± 0.2 °C (36~ 39°C) 10,000 readouts ± 0.1 °C 165x40x22 mm 4x1.5 V AAA

Sold in bliste

369



### MD SCOPE VET VIDEO OTOSCOPE

MD SCOPE VET VIDEO OTOSCOPE

Instant View

A clear and sharp image can be acquired and displayed instantly on a built-in screen.

Just press a single button and wait for 3 seconds. Real Time Interaction

The medical image can be captured and displayed simultaneously on TV monitor or downloaded to Mac/ PC system.

Electronic medical record

A medical image is automatically generated to support most of the stand-alone health information system. Probes and accessories at page 208.

### TECHNICAL SPECIFICATIONS

2.4" colour LCD display Size/weight: 8x20 cm (2.5"x8") - 218 g Battery lifespan: 4 hours



 32164 VET MD SCOPE PACK 32175 3 cameras

- 3 camera probes 75/150/300 mm

- image dongle - cable set

- 2 AA alkaline batteries

• 32175 CRADLE



### HEINE VET OTO AND OPHTHALMO



• 80500 BETA OTOSCOPE SET 2.5 V - G-112.10.118 Set complete with slit illumination head, 1 set long closed metal specula (57x4,65x6,90x7 mm), 1 spare bulb, hard case.

80501 BETA 200 VET F.O. XHL OTO-OPHTHALMO SET

2.5 V - G-151.10.118 Set complete with:

Beta 200 ophthalmo, Beta 200 vet otoscope

3 reusable Sanalons vet specula 61x Ø 4/6/9 mm

- 1 spare bulb for each instrument

zipper case

31772 HEINE 077 OTOSCOPE BULB 2.5 V - spare

31781 HEINE 069 OPHTHALMOSCOPE BULB 2.5 V - spar



### VET OTOSCOPES, OPHTHALMO AND DIAGNOSTIC SETS



• 31442 PARKER VETERINARY OTOSCOPE Includes: kit of 3 reusable plastic cannulas (31447)



• 31424 XENON HALOGEN DIAGNOSTIC SET

Includes: xenon halogen open otoscope head+handle xenon-halogen ophtalmoscope head, kit of 5 reusable plastic cannulas (31451), metal tongue depressor holder illuminator, nasal specula

Rechargeable battery handle 2.5V All sets have 2.5V handle for use with 2xC batteries or rechargeable batteries (34479)



• 31422 XENON HALOGEN OTOSCOPE SET

31422

Includes: xenon-halogen open otoscope head+handle, kit of 5 reusable plastic cannulas (31451), kit of 3 reusable plastic cannulas (31447)

### 31425 • 31425 XENON HALOGEN

**DIAGNOSTIC SET** metal cannulas Includes: xenon-halogen open otoscope head+handle, xenonhalogen ophtalmoscope head, kit of 3 reusable metal cannulas + 2 metal specula (31453)

	31451	Kit of 5 reusable plastic cannulas
		(Ø 2.5, 3.5, 4.5, 5.5, 9 mm)
	31447	Kit of 3 reusable plastic cannulas (Ø 4,5, 7 mm)
	31453	Kit of 3 reusable metal cannulas (Ø 4, 5, 6 mm)
		+ 2 slotted metal specula (Ø 7.5, 9.4 mm)
	31454	Nasal specula
•		Xenon halogen otoscope bulb 2.5 V
	31479	Xenon halogen ophthalmoscope bulb 2.5 V
	31449	Standard otoscope bulb vacuum 2.5 V for 31442
)	31542	Charging station
	34479	
	31429	Swivel lens 2X for Vet oto sets 31422, 31424, 31425

VETERINARY SETS AND ACCESSORIES





• 40010 HEAD DISSECTION - life size Size: 18x25x23 cm - 140 q - 4 parts - 1X



Can be divided into 9 parts showing the temporal and occipital lobes, the frontal and parietal lobes, the cerebellum, the brain stem and basilary artery

 40020 BRAIN WITH ARTERIES Size: 16x18x16 cm - 1 kg - 9 parts - 1X

cerebellum, 40021 REGIONAL BRAIN

Size: 20x17x15 cm - 1.3 kg - 2 parts

Life size brain with

distinct colour for

ontal lobe, parienta

lobe, occipital lobe

temporal lobe notor cortex

somatosen

sory cortex

imbic cortex





EAR SIZES **40041** 33x23x21 cm 1 40042 33x23x21 cm 2



40031 40033

Models show the eye ball with optic nerves and muscles in its natural position in the bony orbit

Size: 18x11x8 cm - 450 g - 5 parts - 2X

Mounted on a base with stand.

• 40058 LARYNX

40088

GIMA code	EYE WITH ORBIT SIZES	Kg	Parts	Mag
40030	15x17x27 cm	0.9	6	6X
40031	42x30x31 cm	3.2	4	5X
40033	42x30x31 cm	3.4	11	5X

### RESPIRATORY SYSTEM: NASAL CAVITY, LARYNX



nasal cavity. The nasal septum and part of the olfactory epithelium are removable to show deep internal struc-

### • 40056 NASAL CAVITY

Size: 15x20x30 cm - 1 kg - 3 parts - 3X Mounted on base with stand.



respiratory system. It is composed of 7 part showing the larynx (dissected along the sagittal plane), the • 40050 RESPIRATORY SYSTEM Size: 26x40x12 cm - 1.3 kg - 7 parts life size

Longitudinally sectioned to reveal inner details of internal structure including hyoid bone. vessels, ligaments, nerves and thyroid gland

DIGESTIVE SYSTEMS: LIVER, PANCREAS, STOMACH Can be opened to show the internal



• 40080 LIVER SECTION WITH GALLBLADDER Size: 28x27x14 cm - 880 g - 1 part - 1.5X Mounted on a base with stand.

Mounted on a base with stand.

Accurate representation of th pancreas, spleen and duodenum. The pancreas is open to show the entire pancreatic duct. The duodenum is partially dissected to expose its interna 40086

 40086 PANCREAS, DUODENUM AND SPLEEN Size: 16x15x23 cm - 350 g - 1 part - 1X

tructure of the stomach, including the nucosa, the pylorus, and a section of the gastric wall. Superficial dissection exposes the longitudinal, circular and oblique muscle layers, with nerves and vascular structures

40088 STOMACH

Size: 16x14.5x5 cm - 235 q -2 parts - 1.5X Mounted on a base with stand.

### HEART AND CIRCULATORY SYSTEM

Life size in 2 parts The anterior heart wall can be removed to show the left and right ventricles and atria as well as the tricuspid monary, mitral and aortic valves 40071



Enlarged 2000 times, this model shows the various types of blood cells, including red blood cells, white blood cells (lymphocytes, monocytes. neutrophils, eosino phils and basophils)



cardiac valves and the comparative mor phology of the right and left ventricles. The right atrium is also removable





A general view o human circula It includes the h (2 parts), lungs, spleen, kidneys relevant connect with the pulmoi and system circula

Size

f the tion. leart liver, and tions nary natic itory vays.	
	40075

Parts Magnif.

1X

ı	40071	HEART - mounted on base	11x7x10	0.23	2	1X
1	40072	GIANT HEART - mounted on base	24x25x28	3.5	4	3X
	40077	BLOOD CELLS - mounted on board	58x38x7	1.0	1	2000X
	40075	CIRCULATORY SYSTEM - mounted on board	90x32x11	2.3	2	0.5X

**HEART AND CIRCULATORY SYSTEM** 

40105

### URINARY SYSTEM: MALE BLADDER, KIDNEY • 40090 MALE URINARY BLADDER

WITH PROSTATE Size: 27x20x15 cm - 1.2 kg - 2 parts - 3X

This model, enlarged 3 times, shows the male urinary bladder with the prostate gland surrounding the urethra. The model is dissected medially to expose both internal and external structures of the bladder and prostate, including the ureteric and urethral orifices, ductus deferens, seminal gland, eiaculatory duct




 40094 KIDNEY WITH ADRENAL GLAND+RENAL CORPUSCLE Size: 40x15x8 cm - 1.2 kg - 1 part - 3X

This model shows a frontal section of the human kidney enlarged 3 times. The kidney is shown with the renal capsule. Additional structures include: the cortex. medulla, pyramids with papillae, partially dissected renal pelvis, renal calices, ureter, blood vessels, suprarenal gland with cortex and medulla. A schematic representation of the renal corpuscle with the system of collecting tubules is included.



### ■ PELVIS - FEMALE AND MALE



This life size model, composed of 3 parts, shows an open dissection through the median sagittal section of the pelvis. Internal structures of the female urogenital system are portraved in great detail. Removable parts include half of the female reproductive system with the uterus opened to reveal medial and transverse sectional views

This life size model, composed of 4 parts, presents an open view through a median sagittal section of the pelvis. Internal structures of the male urogenital system are represented in fine detail. The removable parts include a half penis divided into medial and transverse sections, and half of the male reproductive system with an open dissection of a testis showing de-

tails of the ir structure.					
GIMA code	PELVIS size cm	Sex	Kg	Parts	Mag
40100	30x20x27	fem	1.7	3	1X

### PREGNANCY PELVIS

This life size model depicts the female human pelvis in median section with a fetus in the 40th week of pregnancy. The fetus is in the normal

position prior to birth, showing the anatomical relationship between various structures of the maternal pelvis and the fetus. Fetus is detachable for close examination



• 40110 PREGNANCY PELVIS WITH MATURE FETUS

**40105** 30x20x27 male 1.7 4 1X Size: 40x26x34 cm - 3.3 kg - 2 part - 1X




 40060 SKIN MODEL - 70X Size: 25x18x28 cm - 1.5 kg 2 parts - 70X Mounted on base


Anatomical structures are shown in details including the hair follicles, sebaceous, glands, sweat glands, erector muscles, Pacinian corpuscles, nerves and blood vessels. The different layers of the skin are clearly defined. A portion of a hair shaft can be removed to show internal details



HUMAN TORSOS WITH CD AND MUSCULAR FIGURES



Some of the detachable parts of human torsos (40005-8-9)



Removable structures, of codes 40005-8-9, include the following: eve with ontic nerve and extraocular muscles half of the brain - trachea - descending thoracic aorta and esophagus - right and left lungs (two parts each)- liver with gallbladder half of one kidney - two part heart - stomach dissected in two parts (not for 40005) pancreas, duodenum and spleen - small and large intestines - male and female urogenital systems (4 parts each), (on 40009 female system is in 3 parts and provided of detachable fetus) - thoracic vertebra (T12) with spinal cord (code 40008 and 40009 only).

Detachable parts of human muscular



body systems from various angle

• 40015 HEAD/NECK MUSCULATURE Size: 37x23x46 cm

- 3.1 kg - 1 part - life size

Superficial and deep musculature are well represented as are the pathways of the subclavian and carotid



### HEAD MUSCULATURE MUSCLES: SHOULDER, ARM, LEG

• 40016 SHOULDER MUSCLE • 40017 ARM MUSCLE Size: 23x19x11 cm - 435 q Size: 74x20x12 cm - 1.9 kg 1 part - 1X - 7 parts

Mounted on a base with stand



This model illustrates in great details the muscles, ligaments and bones of the shoulder.

Through different muscles section it is possible to observe the deep musculature to the bone.

• 40018 LEG MUSCLE Size: 110x19x14.5 cm - 5.1 kg

40017

This 7-part life size model shows, in

of the arm, complete with super-

represented

deltoid muscle

biceps muscle

tricens muscle

muscle of wrist

- brachioradial muscle

palmar aponeurosis

ficial and deeper muscles, vascular

great detail, the anatomical structure

structures, nerves and ligaments. The

hand and the shoulder are also well

The following parts are removable:

- radial extensor muscle of wrist

- long palmar muscle with radial flexor

13 parts

Mounted on a base with stand This 13-part model shows, in great

detail, the anatomical structure of the leg, complete with superficial and deeper muscles, vascular structures, nerves and ligaments.

40018

The following parts are removable.

- sartorius long head of biceps


- gluteus maximus - soleus

- gastrocnemius aluteus medius

- gracilis - semitendinosus and

semimembranous





VERTEBRAL COLUMNS

40131

Fully flexible life size vertebral columns consisting of the

sacrum, coccyx, complete pelvis with symphysis, removable

On 40131 the left side of the skeleton shows the points of

origin (red) and the point of insertion (blue) of the muscles.

to show the sacral section of the spinal cord and associated

On 40133 the various regions of the spinal column are colour

95x20x20

95x20x20

3 kg 1X

On 40131 and 40132 the sacral crest and coccyx are removable

occipital plate, cervical, thoracic and lumbar vertebrae.

All models also feature representation of the vertebral

arteries, spinal nerve branches, and a prolapsed L3-L4

GIMA FLEXIBLE VERTEBRAL COLUMNS Size cm

40132 VERTEBRAL COL with femur + open sacrum 95x20x20

40133 SPINAL COL with colour coded regions 98x23x23 970 g

40130 VERTEBRAL COLUMN with femur heads

40131 VERTEBRAL COL with femur + muscle

FLEXIBLE VERTEBRAL COLUMNS

femur heads (only 40130,31,32).

coded for easy identification.

intervertebral disc.

### 40115 MINI SKELETON

Height: 80 cm Weight: 1.5 kg. This 1/2 life size model shows the anatomy of the human skeleton in high detail. The skull can be disassembled into 3 parts: skullcap, base of skull and mandible. All the main joints are articulated. Arms and legs can be removed easily. Mounted on a stand for hanging.

40120 HUMAN SKELETON

Height: 170 cm. Weight: approx 10 kg. This model is a replica of a life size human skeleton and shows all the skeleton parts in high detail. It's hand-assembled to provide intricate details and long-lasting durability. The main joints are articulated; the upper and lower limbs can be removed easily. The following parts are detachable: Calvarium, Skull, Jaw. Arms, Legs. Supplied with 5-caster roller stand.

40125 MUSCULAR HUMAN SKELETON

Same as code 40120 but with the left side of the skeleton showing the point of origin (red) and the point of insertion (blue) of the muscles.

Advanced osteoporosis model

pathological changes at advanced stage

### KNEE AND SHOULDER

• 40140 SHOULDER JOINT Size: 29x12x12cm - 560g -

1 part - 1X

Mounted on stand 40145 KNEE JOINT

Size: 12x12x31cm - 440g -

The life size model represents a functional model of knee joint with lateral ligaments, meniscus and patellar ligament.



# SKELETAL SYSTEM Shows 3 vertebrae: one healthy vertebra, one vertebra with pathological changes at first stage, one vertebra with







Cervical spinal with intervertebral cervical nerves ver- and spinal cord tebral arteries, spinal cord and brain stem

Lumbar spinal column consists of column consists of column with sacral with hernia 7 cervical vertebrae 12 thoracic vertebrae and coccyx bones. and prolapsed with intervertebral It consists of 5 lumdiscs, occipital plate, discs, thoracic nerves bar vertebrae with intervertehral discs lumbar nerves and spinal cord. The sacral crest and

3 lumbar vertebrae intervertebral disc Shows 3 lumbar vertehrae with spinal nerves, dura mater and 2 intervertebral discs affected by

lateral and media

40185 40180

GIMA code	SKELETAL SYSTEM	Size cm	Weight	Magnif.
40136	CERVICAL SPINAL COLUMN	12x12x22	350 g	1X
40137	THORACIC SPINAL COLUMN	12x12x40	600 g	1X
40138	LUMBAR SPINAL COLUMN	12x12x36	800 g	1X
40180	HERNIA PATHOLOGY	16.5x12x26	300 g	1X
40185	ADVANCED OSTEOPOROSIS	12x12x15	200 g	1X

coccvx are remo-

### ■ HUMAN SKULLS - 3 PARTS





Significant structures are numerated

Coloured skull (40162) All the bones are depicted in different colours, making this model a useful tool to study the correct position and relationship of all the structures.

Muscular skull (40163)

The left side of the skull shows the points of origin(red) and the point of insertion (blue) of the muscles. MINI SKULL (40165) ½ adult natural size

It depicts all structural details of the skull. It can be disassembled into skullcap and base of skull

Articulated mandible.







Life size human skull reproduction with all details, made in PVC. Removable skull cap and articulated mandible.



GIMA code	HUMAN SKULLS	Size cm	Weight	Magnif.
40160	HUMAN SKULL	22x14x16	950	1X
	<b>HUMAN SKULL - numerated</b>		950	1X
	HUMAN SKULL - coloured	19.5x17x21.5	950	1X
	HUMAN SKULL - muscular	18x17x21	875	1X
40165	MINI SKULL	11x11x16.5	150	0.5X

### DENTAL MODELS

### • 40206 DECIDUOUS TEETH

Size: 9x9x10 cm - weight: 85 g. Mounted on base with stand. This life size model shows the upper and lower jaw of a 5 year old child. The lower jaw is movable to reproduce the natural chew. The model exposes the arrangement of the young teeth

### • 40205 PERMANENT TEETH

Size: 11x11x12 cm - weight: 170 g. Mounted on base with stand.

This life size model shows the upper and lower jaw of an adult. The lower jaw is movable to reproduce the natural chew. The model exposes the complete set of permanent teeth with roots and nerves fibres.





• 40213 SET 3 TEETH:

Size: 33x33x11 cm -

weight: 700 g

375

INCISOR, CANINE, MOLAR

5-part model includes representations (10X life size) of

human incisor, canine and molar teeth. The canine and

features (dentine, ename), cement and pulp)

molar can be divided into 2 parts each, showing internal

Size: 35x18x31 cm - weight: 1130 g Mounted on base with stand.

This 3X life size model is divisible into 6 parts to show all the characteristics of an adult half mandible. A portion of the jaw can be removed to show the roots of the teeth and the internal structure of the bone. Canine and molar teeth can be removed and dissected longitudinally to observe the tooth roots, pulp and nerves



### 40212 DENTAL PATHOLOGY MODEL

Size: 6x4.5x11 cm - weight: approx. 100 g This 4X life size model shows the process of dental caries in its progressive stages.

The tissues forming the tooth (enamel, dentine and pulp) are shown, along with the way in which they are affected by the caries process



### Mounted on base. A 3X life size model useful to teach the correct way to brush teeth. A giant toothbrush is included

Size: 12x16x22 cm - weight: 1 kg



### • 40214 LOWER MOLAR WITH CARIES Size: 11x11x19.5 cm - weight: approx. 250 g Mounted on base with stand

This 1-piece model is approximately 10X life size; it shows the most important dental pathologies, including dental caries, pulpitis, gingivitis and periapical periodontitis



Size: 12x6x6 cm weight: approx. 300 g This model, composed of 7 parts, is 4X life size. It consists of 3 teeth, seated

in their sockets, showing the progressive deterioration of tooth structure by dental caries. The first tooth shows the caries in the enamel. In the second tooth, the caries spreads through the dentine. In the third tooth, the pathology affects the pulp, jeopardizing the vitality of the tooth.



### VALUE HUMAN ANATOMY MODELS

A detailed reproduction of a life size human skull with all structural details. The mandible is articulated, the skullcap is removable to show internal details. All of the joints, sutures, fissures, foramina and processes are portrayed with utmost accuracy



• 40155 HUMAN SKULL 1X -3 parts



• 40157 HUMAN SKULL 1X COLOURED - 3 parts

Fully flexible life size vertebral columns consisting of the occipital plate, cervical, thoracic and coccyx, complete pelvis with symphysis, removable femur heads

• 40127 FLEXIBLE VERTEBRAL **COLUMN** with femur heads



- 3X

**NUMERATED - 3 parts** 



**40144 KNEE JOINT** 

Cornea, iris, lens and vitreous body can be

removed

• 40199 ORAL HYGIENE MODEL • 40119 HUMAN SKELETON






• 40070 HEART 3X - 3 parts





• 40039 EAR 3X - 5 parts



 40124 HUMAN MUSCULAR SKELETON



• 40069 HEART 1X - 2 parts



the cardiac valves and the comparative morphology of the right and left ventricles.







MULTIPARAMETER MONITORS page 288-292





SIGMA F.O. OTO-OPHTHALMOSCOPES page 212









ECG AND ACCESSORIES





page 337-346



GIMA S.p.A. - Via Marconi, 1 - 20060 Gessate (MI) - Italy Tel. +39 02 953854209/221/225 - Fax: +39 02 95380056 E-Mail: export@gimaitaly.com www.gimaitaly.com



40028 EYE 6X - 6 parts



• 40038 EAR 3X - 3 parts